

NVS 600(1.01)

All-in-One LED Video Processor & Controller

Product Description

The NVS 600(1.01) is a professional all-in-one LED video processor and controller designed to combine video processing and LED display control in a single unit. It supports high-resolution video processing, multi-layer processing, scaling, low-latency operation, output synchronization and flexible signal management. With four Gigabit Ethernet outputs and optical fiber interfaces, it is suitable for professional LED video wall installations.

Technical Specifications

Parameter	Specification
Brand/Make	NVS NEWTECH VIDEO SYSTEMS PVT LTD
Model	NVS 600 (1.01)
Product Type	All-in-One LED Video Processor & Controller
Maximum Input Resolution	Up to 4K × 2K @ 60 Hz
Layout	1x 4K & 2x2K or 6x2k layers
LED Loading Capacity	Up to 3.9 million pixels
Maximum Width	Up to 10,240 pixels
Maximum Height	Up to 8,192 pixels
Gigabit Ethernet Outputs	6
Optical Fiber	1 × 10G optical ports
HDMI Monitor Input	1x HDMI 2.0, 2x HDMI 1.3
SDI Port	1x 3G-SDI (IN & LOOP)
HDMI Monitor Output	1 × HDMI 1.3
3D Interface	1
Control Port	2xEthernet, 1xLight Sensor, 2x USB
Audio	2 x Audio (1x Audio input, 1× Audio output)
USB	USB interface for configuration / firmware-related functions
Control	Front panel
Processing	Multi-layer video processing
Scaling	Up-scaling / Down-scaling
Low Latency	Supported
Working Modes	Video Controller, Fiber Converter and ByPass
Output Synchronization	Supported
Free Topology	Supported with compatible receiving cards
Calibration	Brightness and chroma calibration supported
Input Interfaces	HDMI, 3G-SDI and other supported interfaces depending on configuration
Power Supply	100–240 VAC, 50/60 Hz
Rated Power Consumption	41 W
Operating Temperature	0°C to 50°C

Applications

Fine-Pitch LED Video Walls, Command Centers, Corporate AV, Conference Systems, Control Rooms, Rental & Staging and Professional Large-Format LED Displays.