

# NVS P4 SMD Gold Wired LED Display

## High-Resolution Outdoor SMD LED Video Wall

### Product Description

The NVS P4.0 SMD Gold Wire LED Display is a high-performance Outdoor LED video wall solution designed for professional environments requiring high image clarity, smooth motion and reliable 24×7 operation.

### Technical Specifications

| Parameter             | Specification                                                        |
|-----------------------|----------------------------------------------------------------------|
| Brand / Make          | NVS NEWTECH VIDEO SYSTEMS PVT LTD                                    |
| Model                 | P4.0(960mmX960mm)                                                    |
| Make of LED           | Nichia/Cree/Nationstar                                               |
| LED Technology        | S.M.D (Gold Wired)                                                   |
| Pixel Pitch           | P4.0 mm                                                              |
| Module Dimension      | 320mm x160mm                                                         |
| Panel size            | 960mm x 960 mm                                                       |
| Panel Resolution      | 240 mm x 240 mm                                                      |
| Pixel Density         | 62500 pixels/m2                                                      |
| Aspect Ratio          | 16:9                                                                 |
| Processing            | 14-bit                                                               |
| Colour                | 4.4 Trillion                                                         |
| Brightness            | 5000 - 5500 cd/m² (adjustable)                                       |
| Brightness Adjustment | Automatic brightness adjustment based on ambient lighting conditions |
| Material              | Mild steel/Aluminium                                                 |
| Refresh Rate          | 3840 Hz                                                              |
| Contrast Ratio        | 8,000:1                                                              |
| Driving IC            | MBI/Chipone                                                          |
| Drive method          | 1/13 or better                                                       |
| Viewing Angle         | 140° Horizontal / 140° Vertical                                      |
| LED Lifespan          | ≥100,000 hours                                                       |
| Maintenance           | Rear accessible / Rear maintenance                                   |
| Installation          | Wall mounting kit / mobile floor stand                               |
| Power supply          | Meanwell/TDK Lambda                                                  |
| Operating Voltage     | 100–240 VAC, 50/60 Hz                                                |
| Operating Temperature | 0°C to 40°C                                                          |
| Display Coating       | Black matt powder coated finish                                      |
| System Reliability    | 24×7 performance                                                     |
| Certification         | BIS                                                                  |