#### ESTR4120 Computer Networks

Lecture 10: Security and Availability

Hong Xu

# Security III: Availability, DDoS, and Routing Security

15-441/641 Fall 2022 Prof Justine Sherry



# What were the four requirements for a secure communications channel?



### What do we need for a secure comm channel?

Authentication (Who am I talking to?)

Confidentiality (Is my data hidden?)

Integrity (Has my data been modified?)

Availability (Can I reach the destination?)



## A Chinese ISP momentarily hijacks the Internet (again)

By Robert McMillan

IDG News Service | Apr 8, 2010 5:59 PM PT

For the second time in two weeks, bad networking information spreading from China has disrupted the Internet.

On Thursday morning, bad routing data from a small Chinese ISP called IDC China Telecommunication was retransmitted by China's state-owned China Telecommunications, and then spread around the Internet, affecting Internet service providers such as AT&T, Level3, Deutsche Telekom, Qwest Communications and Telefonica.

#### **MORE LIKE THIS**


China's Great Firewall spreads overseas

China telecom operator denies hijacking Internet traffic

Research experiment disrupts Internet, for some

on IDG Answers A

What is a BGP hijack?





## Internet-Wide Catastrophe—Last Year









One year ago today TTNet in Turkey (AS9121) pretended to be the entire Internet. And unfortunately for the rest of the Internet, many large network providers believed them (or at least believed them in part). As far as anyone knows, it was a mistake, not a malicious act. But the consequences were far from benign: for several hours a large number of Internet users were unable to reach a large number of Internet sites. Twelve months later we can take a look at what happened, and whether we've learned much in the intervening time.

Early Christmas Eve morning 2004, TTNet (AS9121) started announcing what appeared to be a full table (well over 100,000 entries) of Internet routes to all of their transit providers. I was on call that Christmas (as I am this Christmas; I'm sensing a bad pattern here). So around 4:30 in the morning US Eastern Standard Time, I started getting paged.



## DDoS Attack Hits 400 Gbit/s, Breaks Record

A distributed denial-of-service NTP reflection attack was reportedly 33% bigger than last year's attack against Spamhaus.



### **ProtonMail On Battling A Sustained DDoS Attack**

Posted 23 hours ago by Natasha Lomas (@riptari)

897


















Next Story



Encrypted webmail provider, ProtonMail, has been fighting a wave of DDoS attacks since November 3 that, by last Friday, had taken its service offline for more than 24 hours. At the time of writing the attacks are still coming.

They have included what ProtonMail co-founder Andy Yen described as a "co-ordinated assault" on its ISP that exceeded 100Gbps and attacked not only the Swiss datacenter but routers in various locations where the ISP has nodes — taking multiple services offline, not just ProtonMail's email.

#### **CrunchBase**

#### **ProtonMail**

FOUNDED 2013

#### OVERVIEW

End-to-end encrypted email, based in Switzerland. ProtonMail is a new service that provides easy to use secure email. ProtonMail's secure email system is designed around the principle of zero access. This means user data cannot be read by ProtonMail and turned over to third parties because ProtonMail servers do not store user encryption keys. The service is backwards compatible with insecure email ...

#### LOCATION

Geneva, 07

#### CATEGORIES

Messaging, Email, Data Security, Security

#### FOUNDERS



## Two classes of attacks on availability today

#### Resource Exhaustion

- DDoS
- SYN Floods

### Routing Attacks


- We'll talk about flaws in BGP
- There are so many kinds of attacks we're not discussing though!
  - Take 18-487 with Prof. Sekar!





## Recall: Internet routing

- An Interior Gateway Protocol (IGP) is used to route packets within an AS: Intra-domain routing
- An Exterior Gateway Protocol (EGP) to maintain Internet connectivity among ASs: Inter-domain routing





# What kind of routing algorithm is BGP?



## How does BGP work?

Internet routers communicate using the Border Gateway Protocol (BGP):


- Destinations are prefixes (CIDR blocks)
  - Example: 128.2.0.0/16 (CMU)
- Routes through Autonomous Systems (ISPs)
- Each ISP is uniquely identified by a number
  - Example: 9 (Carnegie Mellon)
- Each route includes a list of traversed ISPs:
  - Example:  $9 \leftarrow 5050 \leftarrow 11537 \leftarrow 2153$

Where are the security mechanisms?
The nice cryptographic checks for authenticity and integrity we talked about in the last two lectures?!











# All you need is one compromised BGP speaker





### Pakistan Telecom: Sub-prefix hijack



#### Corrigendum- Most Urgent

### GOVERNMENT OF PAKISTAN PAKISTAN TELECOMMUNICATION AUTHORITY ZONAL OFFICE PESHAWAR

Plot-11, Sector A-3, Phase-V, Hayatabad, Peshawar.
Ph: 091-9217279- 5829177 Fax: 091-9217254

www.pta.gov.pk

NWFP-33-16 (BW)/06/PTA

February ,2008

Subject: Blocking of Offensive Website

Reference: This office letter of even number dated 22.02.2008.

I am directed to request all ISPs to immediately block access to the following website


URL: <a href="http://www.youtube.com/watch?v=o3s8jtvvg00">http://www.youtube.com/watch?v=o3s8jtvvg00</a>

IPs: 208.65.153.238, 208.65.153.253, 208.65.153.251

Compliance report should reach this office through return fax or at email peshawar@pta.gov.pk today please.








#### Pakistan wanted to send an iBGP announcement to blackhole traffic to YouTube...


### Pakistan Telecom: Sub-prefix hijack





### But they accidentally sent an eBGP announcement to blackhole YouTube!

Pakistan Telecom: Sub-prefix hijack





# Potential attack objectives

- Blackholing make something unreachable
- Redirection e.g., congestion, eavesdropping
- Instability
- But more often than not, just a mistake!



# How can we fix this problem?



# What tools from the last two lectures might we use?



# BGP Security Requirements

- Verification of address space "ownership"
- Authentication of Autonomous Systems (AS)
- Router authentication and authorization (relative to an AS)
- Route and address advertisement authorization
- Route withdrawal authorization
- Integrity and authenticity of all BGP traffic on the wire
- Timeliness of BGP traffic



## Idea #1: RPKI & Origin Authentication


- Have all legitimate network operators register their prefixes along with a public key with a central authority.
  - Called: "RPKI" for Routing Public Key Infrastructure
- Whenever I announce my prefix, I sign my announcement.
- Anyone can verify that I am indeed allowed to originate this prefix.



Resource Public Key Infrastructure (RPKI): Certified mapping from ASes to public keys and IP prefixes.







RPKI shows Evil Telecom is not a valid origin for this prefix.




66.174.161.0/24

Resource Public Key Infrastructure (RPKI): Certified mapping from ASes to public keys and IP prefixes.







RPKI shows Evil Telecom is not a valid origin for this prefix.




66.174.161.0/24


# Why is this solution insufficient?



Resource Public Key Infrastructure (RPKI): Certified mapping from ASes to public keys and IP prefixes.

## But RPKI alone is not enough!







S-BGP [1997]: RPKI + Cannot announce a path that was not announced to you. (22394, Prefix) **VZW: Level3: (VZW, 22394, Prefix) ISP 1:** (Level3, VZW, 22394, Prefix) ISP 1 Level 3 Verizon Evil **Wireless** (22394, Prefix) **VZW:** Telecom **Level3: (VZW, 22394, Prefix)** 10-00-22394 VZW: (22394, Prefix)





S-BGP [1997]: RPKI + Cannot announce a path that was not announced to you. (22394, Prefix) **VZW:** Level3: (VZW, 22394, Prefix) (Level3, VZW, 22394, Prefix) **ISP 1:** ISP 1 Level 3 Verizon Evil **Wireless** Telecom

Malicious router can't announce a direct path to 22394, since 22394 never said

EvilTel: (22394, Prefix)



22394

## S-BGP Secure Version of BGP

- Address attestations
  - Claim the right to originate a prefix
  - Signed and distributed out-of-band
  - Checked through delegation chain from ICANN
- Route attestations
  - Distributed as an attribute in BGP update message
  - Signed by each AS as route traverses the network
  - Signature signs previously attached signatures
- S-BGP can validate
  - AS path indicates the order ASes were traversed
  - No intermediate ASes were added or removed



# What might be hard about upgrading BGP to S-BGP?



# S-BGP Deployment Challenges

- Complete, accurate registries
  - E.g., of prefix ownership
- Public Key Infrastructure
  - To know the public key for any given AS
- Cryptographic operations
  - E.g., digital signatures on BGP messages
- Need to perform operations quickly
  - To avoid delaying response to routing changes
- Difficulty of incremental deployment
  - Hard to have a "flag day" to deploy S-BGP



# S-BGP Deployment Challenges

- Need ISPs to agree on and deploy a new protocol!
  - These are competing organizations!
- Economic incentives?
  - Doesn't improve performance
  - Hard to convince customers to pay more for security
- No benefit to unilateral deployment
  - Need entire path to deploy SBGP/soBGP before you get any benefit!
  - Like IPv6.... But worse <sup>®</sup>



## Has S-BGP been adopted?

- Sadly, no
- If you solve this or want to solve this you can go to grad school
  - Or join a big company's networking team
  - Lots of people will thank you
  - You will be very popular at Internet parties



# Summary

- BGP was built on the assumption of cooperation
- Assumption fails due to attacks... and just to errors.
- Proposed fixes are many, but all have some limitations
  - S-BGP
    - Relies on a PKI
    - Potentially significant overhead

Very hard to retrofit security in an existing model!



## DoS: General definition

- DoS is not access or theft of information or services
- Instead, goal is to stop the service from operating
- Deny service to legitimate users

- Why?
  - · Economic, political, personal etc...



# "Resource Asymmetry"

- One attacker with one server generating traffic probably cannot completely overwhelm the victim.
- Smurf and DNS attacks:
  - Attacker can harness arbitrary machines (lots of them!)
  - Receiver is just one server.
  - "Resource Asymmetry" is the problem.



# How much traffic do I need to overwhelm a reciever?



### Look up: Victim, Year, Bandwidth of Attack



ddos bandwidth







# Evolution of (D)DoS in history


 Poir o-point DoS attacks
 T SYN floods, Ping of death, etc.. (reflection) attacks nated DoS age DDoS



### Coordinated DoS


Attackers'

- Simple extension of DoS
- Coordination between multiple parties
  - Can be done off-band
  - IRC channels, email...





### Typical DDoS setup circa 2005




Traffic Generators (Infected Machines)






### Typical DDoS setup circa 2005




Infection/recruitment Command & control Assault





### Modern Botnet setup



# Goal: Overload the Host and Disable their Availability

- Multiple ways to achieve overload!
  - Smurf and DNS amplification attacks overload the network link.
    - Botnets can do that too.




### DoS Attacks Characteristics

- Link flooding causes high loss rates for incoming traffic
- TCPthroughput

$$BW = \frac{MSS \cdot C}{RTT \cdot \sqrt{q}}$$


 During DoS few legitimate clients served



### Content Distribution Networks (CDNs)

- CDN company installs hundreds of CDN servers throughout Internet
- Replicated customers' content

- How can this help DDoS?
- Legitimate requests can still go through
- Attack scale must be higher




origin server

in North America



### Some CDNs even specialize in DDoS Defense!





#### Crunchbase

Cloudflare	
FOUNDED 2009	
OVERVIEW Cloudflare is a web perform company that provides only accelerate websites online platforms include Cloudflat content around the world to Cloudflare optimizer that eservers and third-party wides of tware on mobiles and content around the content around the world to content around the world the world to content around the world to content are world to cont	line services to protect and The company's online re CDN, which distributes to speed up websites; enables web pages with ad ligets to download Snappy
LOCATION San Francisco, CA	
CATEGORIES Security, Web Hosting, Adve	rtising, Analytics, Ad Server,
FOUNDERS	

Next Stor



### Finding the Zombies and Destroying Them



**PRODUCTS & SERVICES** 

SECURITY BASICS

**GET HELP** 


**ABOUT** 

Search

# Bot Detection and Removal

Detection, notification, and prevention against malicious software.

Have you noticed any suspicious email account activity, unusual error messages, or unfamiliar browsers? Your computer may be infected by a "bot," malicious software that secretly uses your computer to send spam, host phishing sites, and steal your personal information.



#### How our proactive bot notification works


The XFINITY Internet Security bot notification tool looks for patterns coming from your home network that match our infection libraries. If we suspect that a device on your home network is

# Goal: Overload the Host and Disable their Availability

- Multiple ways to achieve overload!
  - Smurf and DNS amplification attacks overload the network link.
    - Botnets can do that too.
  - May also try to overload at the application or transport layer, e.g.:
    - Send a database a lot of very large queries
    - Open lots of TCP connections "SYN attack"



### TCP SYN Flood I: low rate (DoS bug)



#### Single machine:

 SYN Packets with random source IPaddresses

Can't filter out traffic from a malicious sender

- Fills up backlog queue on server
- No further connections possible



### SYN Floods

(phrack 48, no 13, 1996)

	Backlog
OS	queue size
Linux 1.2.x	10
FreeBSD 2.1.5	128
WinNT 4.0	6

Backlog timeout: 3 minutes

- → Attacker need only send 128 SYN packets every 3 minutes.
- ⇒ Low rate SYN flood



## How to prevent SYN flood attacks

- Non-solution:
  - Increase backlog queue size or decrease timeout

- Correct solution (when under attack):
  - Syncookies: remove state from server
  - Small performance overhead



# Syncookies [Bernstein, Schenk]

- Idea: use secret key and data in packet to gen. server SN
- Server responds to Client with SYN-ACK cookie:
  - T = 5-bit counter incremented every 64 secs.
  - $L = MAC_{kev}$  (SAddr, SPort, DAddr, DPort, SN<sub>C</sub>, T) [24 bits]
    - key: picked at random during boot
  - $SN_S = (T.mss.L)$  (|L| = 24 bits)
  - Server does not save state (other TCP options are lost)
- Honest client responds with ACK (AN=SN<sub>S</sub>, SN=SN<sub>C</sub>+1)
  - Server allocates space for socket only if valid SN<sub>S</sub>.



# What about attacks on applications — like RPC calls and database queries?




What about a DDoS attack on a web server? (There is a simple mechanism, invented at Carnegie Mellon, that you have all used)



### CAPTCHAS

• Idea: verify that connection is from a human



- Applies to application layer DDoS [Killbots '05]
  - During attack: generate CAPTCHAs and process request only if valid solution
  - Present one CAPTCHA per source IP address.



# What do net operators do?

Best common operational practices:

http://nabcop.org/index.php/DDoS-DoS-attack-BCOP

 Often, blackholing malicious looking IPs and rerouting to custom "Scrubbers" / Firewalls



### THIS IS A SAD STORY





# I HAVE JUST LISTED A TON OF PROBLEMS WITH THE INTERNET NONE OF WHICH ARE FULLY SOLVED



# Summary



# Summary...

- Today: two classes of attacks on Internet availability.
  - Routing attacks on BGP to prevent traffic from reaching victim
    - Need to validate routes... but getting all 50k+ networks to upgrade is challenging.
  - DoS and DDoS to overwhelm resources of victim
    - Modern bonnets mean attackers can amass large amounts of resources to overrun victims
    - No "off button" on the Internet all traffic is allowed through by the network, even if it is unwanted: