

Scheme


Announcements

Lists

Scheme Lists


In the late 1950s, computer scientists used confusing names

- **cons**: Two-argument procedure that creates a linked list
- **car**: Procedure that returns the first element of a list
- **cdr**: Procedure that returns the rest of a list
- **nil**: The empty list



Important! Scheme lists are written in parentheses with elements separated by spaces

```
> (cons 1 (cons 2 nil))  
(1 2)  
> (define x (cons 1 (cons 2 nil)))  
> x  
(1 2)  
> (car x)  
1  
> (cdr x)  
(2)  
> (cons 1 (cons 2 (cons 3 (cons 4 nil))))  
(1 2 3 4)
```



(Demo)

Symbolic Programming

Symbolic Programming

Symbols normally refer to values; how do we refer to **symbols**?

```
> (define a 1)
> (define b 2)
> (list a b)
(1 2)
```

No sign of “a” and “b” in the resulting value

Quotation is used to refer to symbols directly in Lisp.

```
> (list 'a 'b)
(a b)
> (list 'a b)
(a 2)
```

Short for (quote a), (quote b):
Special form to indicate that the expression **itself** is the value.

Quotation can also be applied to combinations to form lists.

```
> '(a b c)
(a b c)
> (car '(a b c))
a
> (cdr '(a b c))
(b c)
```

(Demo)

Programs as Data

A Scheme Expression is a Scheme List

Scheme programs consist of expressions, which can be:

- Primitive expressions: 2 3.3 true + quotient
- Combinations: (quotient 10 2) (not true)

The built-in Scheme list data structure (which is a linked list) can represent combinations

```
scm> (list 'quotient 10 2)
(quotient 10 2)
```

```
scm> (eval (list 'quotient 10 2))
5
```

In such a language, it is straightforward to write a program that writes a program

(Demo)

Generating Code

Quasiquote

There are two ways to quote an expression

Quote: '(a b) => (a b)

Quasiquote: `(a b) => (a b)

They are different because parts of a quasiquoted expression can be unquoted with ,

```
(define b 4)
```

Quote: '(a ,(+ b 1)) => (a (unquote (+ b 1)))

Quasiquote: `(a ,(+ b 1)) => (a 5)

Quasiquote is particularly convenient for generating Scheme expressions:

```
(define (make-add-procedure n) `(lambda (d) (+ d ,n)))
```

```
(make-add-procedure 2) => (lambda (d) (+ d 2))
```

Example: While Statements

What's the sum of the squares of even numbers less than 10, starting with 2?

```
x = 2
total = 0
while x < 10:
    total = total + x * x
    x = x + 2
```

```
(begin
  (define (f x total)
    (if (< x 10)
        (f (+ x 2) (+ total (* x x)))
        total))
  (f 2 0))
```

What's the sum of the numbers whose squares are less than 50, starting with 1?

```
x = 1
total = 0
while x * x < 50:
    total = total + x
    x = x + 1
```

```
(begin
  (define (f x total)
    (if (< (* x x) 50)
        (f (+ x 1) (+ total x))
        total))
  (f 1 0))
```

(Demo)