Ch 13 Tracability

18/12/2014

projet

Ch 13 Tracability

18/12/2014

Numéro et Nom	traces to
26.3.13.1 Introduction 3.13	
26.3.13.1.1 Definition of speed and distance monitoring	No tracability
26.3.13.1.2 Limit of responsability	No tracability
26.3.13.1.3 Overview	No tracability
26.3.13.1.4 Definition of d	No tracability
26.3.13.2 Inputs for speed and distance monitoring	
26.3.13.2.1 Introduction 3.13.2	No tracability
26.3.13.2.2 Train related inputs	
26.3.13.2.2.1 Introduction 3.13.2.2	
26.3.13.2.2.1.1 List of train related inputs	EI.4.1 A_est (loc/)(stp1) EI.4.8 V_est (loc/)(stp2)
26.3.13.2.2.1.2 Acquisition of train related inputs	
26.3.13.2.2.1.3 Acquisition of braking models	
26.3.13.2.2.2 Traction model	EI.3.2.4 A_traction (tr/) EI.3.2.15 T_traction_cut_off (tr/)(stp3)
26.3.13.2.2.3 Braking Models	
26.3.13.2.2.3.1 Speed Dependent Deceleration	*FT.1.4.3 Calculate expected deceleration (step 3)* *FT.1.4.3.1 Select deceleration of service brake model (step 3)* *FT.1.4.4 Calculate normal service brake deceleration (step 4)* *EI.3.2.1 A_brake_emergency models (V) (tr/)(stp3)* *EI.3.2.2 A_brake_normal_service m. (V) (tr/)(stp4)* *EI.3.2.3 A_brake_service models (V) (tr/)(stp3)*
26.3.13.2.2.3.2 Brake build up time	*EI.3.2.13 T_brake_emergency values (tr/)(stp3)* *EI.3.2.14 T_brake_service values (tr/)(stp3)*
26.3.13.2.2.4 Brake Position	EI.1.2 Brake position (dr/)(stp3)
26.3.13.2.2.5 Brake Percentage	FT.1.4.2.2.2 Build brake percentage conversion model (step 3) FT.1.5.1.2 Build brake position model (step 3)

	FT.1.5.5.1 Select T_brake_emergency value (step 3)
	EI.1.1 Brake percentage (dr/)(stp3)
26.3.13.2.2.6 Special Brakes	FT.1.4.2.2.6 Calculate emergency brake deceleration (step 3)
	FT.1.4.3.1 Select deceleration of service brake model (step 3)
	FT.1.5.1.1 Select T_brake_service value (step 3)
	FT.1.5.5.1 Select T_brake_emergency value (step 3)
	EI.3.2.11 Special brakes status (tr/)(stp4)
26.3.13.2.2.7 Service brake interface	No tracability
26.3.13.2.2.8 Traction cut-off interface	No tracability
26.3.13.2.2.9 On-board Correction Factors	
26.3.13.2.2.9.1 Correction factors for the emergency deceleration	*FT.1.4.2.2.2 Build brake percentage conversion model (step 3)*
	FT.1.4.2.2.7 Calculate safe emergency brake deceleration - Train Data (step 3)
	EI.3.2.5 Kdry_rst Kwet-rst RollStkCorr (tr/)(stp3)
26.3.13.2.2.9.2 Correction factor for gradient on normal service deceleration	*EI.3.2.6 Kn+(V) and Kn-(V) CorrGrdt(V)(tr/)(stp4)*
26.3.13.2.2.10 Nominal Rotating mass	EI.3.2.8 M_rotating_nom (tr/)(stp3)
26.3.13.2.2.11 Train length	EI.3.2.7 L_TRAIN Train length (tr/)(stp3)
26.3.13.2.2.12 Fixed values	EI.3.1.1 Compensation (trfv/)
	EI.3.1.2 dV_ebi_max (trfv/) (stp1)
	EI.3.1.3 dV_ebi_min (trfv/) (stp1)
	EI.3.1.4 dV_sbi_max (trfv/) (stp1)
	EI.3.1.5 dV_sbi_min (trfv/) (stp1)
	EI.3.1.6 dV_warning_max (trfv/) (stp1)
	EI.3.1.7 dV_warning_min (trfv/) (stp1)
	EI.3.1.8 M_rotating_max (trfv/)(stp3)
	EI.3.1.9 M_rotating_min (trfv/)(stp3)
	EI.3.1.10 T_driver (trfv/)(stp2)
	EI.3.1.11 T_preindication (trfv/)(stp2)
	EI.3.1.12 T_warning (trfv/)(stp2)

	EI.3.1.13 V_ebi_max (trfv/)
	EI.3.1.14 V_ebi_min (trfv/)
	EI.3.1.15 V_sbi_max(trfv/)
	EI.3.1.16 V_sbi_min (trfv/)
	EI.3.1.17 V_warning_max (trfv/)
	EI.3.1.18 V_warning_min (trfv/)
26.3.13.2.2.13 Maximum train speed	FT.1.1.1 Calculate the Most Restrictive Speed Profile (stp1)
	EI.3.2.9 Maximum train speed (tr/)(stp3)
26.3.13.2.3 Trackside related inputs	EI.2.2.22 V_NVREL (tk/)(stp1)
26.3.13.2.3.1 Introduction 3.13.2.3 List of inputs	
26.3.13.2.3.2 Trackside related speed restrictions	FT.1.1.1 Calculate the Most Restrictive Speed Profile (stp1)
	EI.2.3.1 ASP Axle load Speed Profile (tk/)
	EI.2.3.2 BBD SR (tk/)
	EI.2.3.3 LX SR Level Crossing speed restriction (tk/)
	EI.2.3.4 Mode related Speed Restriction (tk/)
	EI.2.3.5 Override ftrelated Speed Restrict. (tk/)
	EI.2.3.6 Signalling related speed restriction (tk/)
	EI.2.3.7 SSP Static Speed Profile (tk/)
	EI.2.3.8 STM Max speed (tk/)
	EI.2.3.9 STM System speed (tk/)
	EI.2.3.10 TSR Temporary Speed Restrict. (tk/)
26.3.13.2.3.3 Gradients	EI.2.1.4 Default gradient for TSR (tk/)(stp3)
	EI.2.1.5 Gradient profile (tk/)(stp3)
26.3.13.2.3.4 Track conditions	EI.2.1.6 Inhibition of eddy current brake (tk/)
	EI.2.1.7 Inhibition of magnetic shoe brake (tk/)
	EI.2.1.8 Inhibition of regenerative brake (tk/)
	EI.2.1.11 Powerless section (tk/)
26.3.13.2.3.5 Reduced adhesion conditions	FT.1.4.1 Select adhesion factor (step 3)

	EI.1.3 Slippery rail (dr/)(stp3)
	EI.2.1.1 Adhesion factor pck 71 (tk/)(stp3)
	Adhesion factor (a)
	Slippery rail (/dmi)
26.3.13.2.3.6 Specific speed / distance limits	EI.2.1.10 MA (tk/)(stp1)
	EI.2.2.6 D_NVSTFF (tk/)(stp3)
26.3.13.2.3.7 National Values for speed and distance monitoring	
26.3.13.2.3.7.1 Inhibition of the service brake command	EI.2.2.20 Q_NVSBTSMPERM (tk/)(stp3)
26.3.13.2.3.7.2 Emergency brake revocation	EI.2.2.14 Q_NVEMRRLS (tk/)
26.3.13.2.3.7.3 Inhibition of the Guidance Curve	EI.2.2.15 Q_NVGUIPERM (tk/)(stp2)
26.3.13.2.3.7.4 Inhibition of the service brake feedback	EI.2.2.19 Q_NVSBFBPERM (tk/)(stp3)
26.3.13.2.3.7.5 Dry rails	EI.2.2.9 M_NVEBCL (tk/)(stp3)
26.3.13.2.3.7.6 Wheel / rail adhesion	EI.2.2.8 M_NVAVADH (tk/)(stp3)
26.3.13.2.3.7.7 Maximum value of the speed dependent deceleration for the emergency brake	EI.2.2.1 A_NVMAXREDADH1 (tk/)(stp3)
	EI.2.2.2 A_NVMAXREDADH2 (tk/)(stp3)
	EI.2.2.3 A_NVMAXREDADH3 (tk/)(stp3)
26.3.13.2.3.7.8 Release speed	
26.3.13.2.3.7.9 Speed measurement inaccuracy	EI.2.2.16 Q_NVINHSMICPERM (tk/)(stp1)
26.3.13.2.3.7.10 Integrated correction factors	EI.2.2.4 A_NVP12 (tk/)(stp3)
	EI.2.2.5 A_NVP23 (tk/)(stp3)
	EI.2.2.7 L_NVKRINT (tk/)(stp3)
	EI.2.2.10 M_NVKRINT (tk/)(stp3)
	EI.2.2.11 M_NVKTINT (tk/)(stp3)
	EI.2.2.12 M_NVKVINT (tk/)(stp3)
	EI.2.2.17 Q_NVKVINTSET (tk/)(stp3)
	EI.2.2.21 V_NVKVINT (tk/)(stp3)
	Kr_int(L)
	Kt_int(stp3)

Ch 13 Tracability

	Kv_int(V)
26.3.13.2.3.7.10.1 Kv_int(V) speed dependent factor	EI.2.2.12 M_NVKVINT (tk/)(stp3)
	EI.2.2.17 Q_NVKVINTSET (tk/)(stp3)
	EI.2.2.21 V_NVKVINT (tk/)(stp3)
	Kv_int(V)
26.3.13.2.3.7.10.2 Kv_int(I) lenght dependent factor	FT.1.4.2.2.4 Determinate the speed / lenght dependent integrated correct. factor (stp3)
	EI.2.2.7 L_NVKRINT (tk/)(stp3)
	EI.2.2.10 M_NVKRINT (tk/)(stp3)
	Kr_int(L)
26.3.13.2.3.7.10.3 Brake factor	EI.2.2.11 M_NVKTINT (tk/)(stp3)
	Kt_int(stp3)
26.3.13.3 Conversion Models	
26.3.13.3.1 Introduction 3.13.3	EI.1.1 Brake percentage (dr/)(stp3)
	EI.1.2 Brake position (dr/)(stp3)
26.3.13.3.2 Applicability of the conversion models	FT.1.4.2.2.1 Are conversion model valid ?
26.3.13.3.3 Brake percentage conversion model	FT.1.4.2.2.2 Build brake percentage conversion model (step 3)
	FT.1.4.3 Calculate expected deceleration (step 3)
	FT.1.4.4 Calculate normal service brake deceleration (step 4)
26.3.13.3.3.1 Input parameters	FT.1.4.2.2.2 Build brake percentage conversion model (step 3)
	FT.1.4.3 Calculate expected deceleration (step 3)
	FT.1.4.4 Calculate normal service brake deceleration (step 4)
26.3.13.3.3.2 Calculation of the basic deceleration	FT.1.4.2.2.2 Build brake percentage conversion model (step 3)
	FT.1.4.3 Calculate expected deceleration (step 3)
	FT.1.4.4 Calculate normal service brake deceleration (step 4)
26.3.13.3.3.3 Output parameters	FT.1.4.2.2.2 Build brake percentage conversion model (step 3)
	FT.1.4.3 Calculate expected deceleration (step 3)
	FT.1.4.4 Calculate normal service brake deceleration (step 4)
	A_brake_emergency (V)

Ch 13 Tracability

18/12/2014

26.3.13.3.4 Brake position conversion model	FT.1.5.1.2 Build brake position model (step 3)
26.3.13.3.4.1 Input parameters 3.13.3.3	FT.1.5.1.2 Build brake position model (step 3)
26.3.13.3.4.2 Calculation of the emergency brake equivalent time	FT.1.5.1.2 Build brake position model (step 3)
26.3.13.3.4.3 Calculation of the full service brake equivalent time	FT.1.5.1.2 Build brake position model (step 3)
26.3.13.3.4.4 Output parameters 3.13.3.4	FT.1.5.1.2 Build brake position model (step 3)
	T_brake_emergency_cm0
	T_brake_emergency_cmt
	T_brake_service_cm0
	T_brake_service_cmt
26.3.13.4 Acceleration / Deceleration due to gradient	FT.1.4.2.1 Calculate acceleration / deceleration due to gradiant (step 3)
26.3.13.4.1 Introduction 3.13.4	FT.1.4.2.1 Calculate acceleration / deceleration due to gradiant (step 3)
26.3.13.4.2 Train length compensation	FT.1.4.2.1 Calculate acceleration / deceleration due to gradiant (step 3)
26.3.13.4.3 Rotating mass	FT.1.4.2.1 Calculate acceleration / deceleration due to gradiant (step 3)
	A_gradiant(d)
26.3.13.5 Determination of locations without special brake contribution and with reduced adhesion conditions	FT.1.4.1 Select adhesion factor (step 3)
	FT.1.4.2.2.6 Calculate emergency brake deceleration (step 3)
	FT.1.4.3.1 Select deceleration of service brake model (step 3)
26.3.13.6 Calculation of the deceleration and brake build up time	
26.3.13.6.1 Introduction 3.13.6	No tracability
26.3.13.6.2 Emergency brake	FT.1.4.2 Calculate safe deceleration (step 3)
26.3.13.6.2.1 Safe deceleration	FT.1.4.2 Calculate safe deceleration (step 3)
	FT.1.4.2.2.3 Calculate maximal acceleration (step 3)
	FT.1.4.2.2.4 Determinate the speed / lenght dependent integrated correct. factor (stp3)
	FT.1.4.2.2.5 Calculate safe emergency brake deceleration - Convers. model (stp3)
	FT.1.4.2.2.6 Calculate emergency brake deceleration (step 3)
	FT.1.4.2.2.7 Calculate safe emergency brake deceleration - Train Data (step 3)
	FT.1.4.2.3 Determine factor adhesion parameter (step 3)

Ch 13 Tracability

18/12/2014

26.3.13.6.2.2 Safe brake build up time	FT.1.5.5 Calculate safe break build up time (step 3)
	FT.1.5.5.1 Select T_brake_emergency value (step 3)
	FT.1.5.5.2 Calculate safe break build up time - train data (step 3)
	FT.1.5.5.4 Calculate safe break build up time - conversion model (step 3)
26.3.13.6.3 Service brake	
26.3.13.6.3.1 Expected deceleration	FT.1.4.3 Calculate expected deceleration (step 3)
	FT.1.4.3.1 Select deceleration of service brake model (step 3)
	FT.1.4.3.3 Calculate the expected deceleration (step 3)
	FT.1.5.1.2 Build brake position model (step 3)
26.3.13.6.3.2 Expected brake build up time	FT.1.5.1 Calculate expected brake build up time (step 3)
	FT.1.5.1.1 Select T_brake_service value (step 3)
	FT.1.5.1.2 Build brake position model (step 3)
	FT.1.5.1.3 Calculate the expected brake build up time (step 3)
26.3.13.6.4 Normal service brake deceleration	FT.1.4.2.2.2 Build brake percentage conversion model (step 3)
	FT.1.4.4 Calculate normal service brake deceleration (step 4)
	FT.1.4.4.2 Calculate normal deceleration of service brake (step 4)
	FT.1.4.4.3 Calculate the normal service brake deceleration (step 4)
26.3.13.7 Determination of Most Restrictive Speed Profile (MRSP)	FT.1.1 Calculate Most Restrictive Speed Profile (out of prm)
	FT.1.1.1 Calculate the Most Restrictive Speed Profile (stp1)
26.3.13.8 Determination of targets and brake deceleration curves	
26.3.13.8.1 Introduction 3.13.8	List of Targets
	Target location
26.3.13.8.2 Determination of the supervised targets	FT.1.3.1 Determinate supervised targets (step 1)
26.3.13.8.3 Emergency Brake Deceleration curves (EBD)	FT.1.3.2 Determinate Emergency Brake Deceleration curves (step 1)
26.3.13.8.4 Service Brake Deceleration curves (SBD)	FT.1.3.3 Determine Service Brake Deceleration Curve (step 2)
26.3.13.8.5 Guidance curves (GUI)	FT.1.3.4 Determine Guidance Curves (step 4)
26.3.13.9 Supervision limits	FT.6 Supervision limits computation
26.3.13.9.1 Overview 3.13.9	FT.6 Supervision limits computation

Ch 13 Tracability

18/12/2014

26.3.13.9.2 Ceiling supervision limits	FT.1.2.1 Determine the ceiling supervision speeds (step 1)
26.3.13.9.3 Braking to target supervision limits	
26.3.13.9.3.1 Overview 3.13.9.3	FT.1.6 Determine braking to target supervision limits (step 1&2)
26.3.13.9.3.2 EBI supervision limit	FT.1.5.3 Calculate T_Traction (step 3)
	FT.1.5.4 Calculate T_berem (step 3)
	FT.1.6.2.1 Determine EBI= f(EBD) supervision limit (step 1)
26.3.13.9.3.3 SBI supervision limit	FT.1.3.1 Determinate supervised targets (step 1)
	FT.1.5.2 Calculate T_bs1 and T_bs2 (step 3)
	FT.1.6.1.1 Determine SBI1=f(SBD) supervision limit (step 2)
	FT.1.6.2.2 Determine SBI2 f(EBD) limit (step 1)
	FT.1.6.3 Determine FLOI-SBI limit in TSM (step 2)
26.3.13.9.3.4 Warning supervision limit (W)	FT.1.6.4 Determine Warning supervision limit (W) (step 2)
26.3.13.9.3.5 Permitted speed supervision limit (P)	FT.1.6.5 Determine Permitted speed supervision limit (P) (step 2)
26.3.13.9.3.6 Indication supervision limit (I)	FT.1.6.6 Determine Indication supervision limit (I) (step 2)
26.3.13.9.4 Release speed supervision limits	FT.1.7.1 Determine Release speed supervision limits 2
	FT.1.8 Join CSM, TSM and RSM curves and define type change location (step 1&2)
26.3.13.9.5 Pre-indication location	FT.1.6.7 Determine Pre-indication location (step 2)
26.3.13.10 Speed and distance monitoring commands	FT.7 Commands
26.3.13.10.1 Introduction 3.13.10	FT.2.1 CSM Ceiling speed monitoring
	FT.2.1.2.2 0 Normal status
	FT.2.1.2.3 1 Indication status
	FT.2.1.2.4 2 Overspeed status
	FT.2.1.2.5 3 Warning status
	FT.2.1.2.6 4 Intervention status
	FT.2.2 TSM Target speed monitoring
	FT.2.3 RSM Release speed monitoring
	FX.2.1 Traction Cut Off (TCO) (/tr)(stp1)
	FX.2.2 EB Emergency Break (/tr)(stp1)

Ch 13 Tracability

18/12/2014

	FX.2.3 SB Service Break (/tr)(stp2)
26.3.13.10.2 General requirements	FT.2.1.1.3 Command Trip braking
	FT.2.1.2.2 0 Normal status
	FT.2.1.2.3 1 Indication status
	FT.2.1.2.4 2 Overspeed status
	FT.2.1.2.5 3 Warning status
	FT.2.1.2.6 4 Intervention status
	FT.2.1.3.1 Command brakes and TCO 2
	EI.4.4 Min safe antenna position (loc/)
	FX.2.1 Traction Cut Off (TCO) (/tr)(stp1)
	FX.2.2 EB Emergency Break (/tr)(stp1)
	FX.2.3 SB Service Break (/tr)(stp2)
	IT.2.1.1 Brake revocation
	Estimated train speed (/dmi)
26.3.13.10.3 Requirements for Ceiling speed monitoring	FT.1.2.1 Determine the ceiling supervision speeds (step 1)
	FT.2.1 CSM Ceiling speed monitoring
	FT.2.1.1.1 Command supervision status in CSM mode
	FT.2.1.1.2 Command train in CSM mode
	FT.2.1.2.2 0 Normal status
	FT.2.1.2.3 1 Indication status
	FT.2.1.2.4 2 Overspeed status
	FT.2.1.2.5 3 Warning status
	FT.2.1.2.6 4 Intervention status
	Target Speed (/dmi)
	V_FLOI_DMI (/dmi)
	V_P_DMI (/dmi)
26.3.13.10.3.3 Tables 5/6	FT.7.2 CSM Ceiling Speed monitoring
26.3.13.10.3.4 Table 7	FT.7.2 CSM Ceiling Speed monitoring

Ch 13 Tracability

18/12/2014

26.3.13.10.4 Requirements for Target speed monitoring TBD	FT.1.2.1 Determine the ceiling supervision speeds (step 1)
	FT.1.6 Determine braking to target supervision limits (step 1&2)
	FT.2.1.2.2 0 Normal status
	FT.2.1.2.3 1 Indication status
	FT.2.1.2.4 2 Overspeed status
	FT.2.1.2.5 3 Warning status
	FT.2.1.2.6 4 Intervention status
	FT.2.1.3.1 Command brakes and TCO 2
	FT.2.2 TSM Target speed monitoring
	FT.2.2.1.1 Determine speed and distance target to display
	FT.2.2.1.2 Determine FLOI and Permitted Speeds to display
26.3.13.10.4.15 3.13.10.4.15	FX.1 Data for DMI
26.3.13.10.5 Requirements for release speed monitoring	FT.2.1.2.2 0 Normal status
	FT.2.1.2.3 1 Indication status
	FT.2.1.2.4 2 Overspeed status
	FT.2.1.2.5 3 Warning status
	FT.2.1.2.6 4 Intervention status
	FT.2.2.1.1 Determine speed and distance target to display
	FT.2.3 RSM Release speed monitoring
26.3.13.10.5.4 Tables 13/14	FT.7.3 RSM Release Spead Monoring
26.3.13.10.5.5 Table 15	FT.7.3 RSM Release Spead Monoring
26.3.13.10.6 Transitions between types of Speed and distance monitorin	FT.1.8.2 Select types of speed and distance monitoring
	FT.2.1.2.1 Select Supervision status
	FT.2.1.3.1 Command brakes and TCO 2
26.3.13.10.6.1 Table 16	FT.7.1 Select type of speed monitoring