

# GOOL: A Generic Object-Oriented Language

Jacques Carette, Brooks MacLachlan, Spencer Smith

Computing and Software Department  
Faculty of Engineering  
McMaster University

PEPM 2020

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

OO languages:

- Conceptually similar

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

OO languages:

- Conceptually similar
- Mainly *shallow* syntactic differences

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

OO languages:

- Conceptually similar
- Mainly *shallow* syntactic differences
- Like Romance languages

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

OO languages:

- Conceptually similar
- Mainly *shallow* syntactic differences
- Like Romance languages
- We tend to **say** similar things in all of them

## The Goal



One language to express them all.

- Is it possible?
- Capture the meaning of **OO programs**
- DSL for domain of **OO programs**
- Currently targets Java, Python, C#, C++

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience



# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience
- **idiomatic:** For readability, understandability

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience
- **idiomatic:** For readability, understandability
- **documented:** For readability, understandability

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience
- **idiomatic:** For readability, understandability
- **documented:** For readability, understandability
- **patterns:** More efficient coding

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience
- **idiomatic:** For readability, understandability
- **documented:** For readability, understandability
- **patterns:** More efficient coding
- **expressivity:** Works for real examples

# Requirements

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- **mainstream:** Most potential users
- **readable:** Human beings are a target audience
- **idiomatic:** For readability, understandability
- **documented:** For readability, understandability
- **patterns:** More efficient coding
- **expressivity:** Works for real examples
- **common:** Reduce code duplication

# Approach

Introduction

Requirements

**Creation**

Implementation

Patterns

Example

Current Work

Conclusions

Start from real OO programs

# Approach

Introduction

Requirements

**Creation**

Implementation

Patterns

Example

Current Work

Conclusions

Start from real OO programs

What we can say vs. **want to say** vs. need to say

## Example: Blocks

- Semantically meaningless
- Reflect how people write programs

---

```
# Initialize dimensions
```

```
h = input('What is the height?_')
```

```
w = input('What is the width?_')
```

```
d = input('What is the depth?_')
```

```
# Calculate volume and surface area
```

```
v = h * w * d
```

```
sa = 2 * (h * w + w * d + h * d)
```



# Some ingredients

Introduction

Requirements

**Creation**

Implementation

Patterns

Example

Current Work

Conclusions

- Variables distinct from values (viz use/mention)
- Smart constructors for common idioms

# GOOL Language

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

Types

bool, int, float, char, string, infile (**read mode**), outfile (**write mode**), listType, obj

Variables

var, extVar, classVar, objVar, \$-> (**infix operator for objVar**), self, [listVar]

Values

valueOf (**value from variable**), litTrue, litFalse, litInt, litFloat, litChar, litString, ?!, ?&&, ?<, ?<=, ?>, ?>=, ?==, ?!=, #~, #/^, #—, #+, #-, #\*, #/, #^, inlineIf, funcApp, extFuncApp, newObj, objMethodCall, [selfFuncApp, objMethodCallNoParams]

Statements

varDec, varDecDef, assign, &=, &+=, &-=, &++, &~- , break, continue, returnState, throw, free, comment, ifCond, ifNoElse, switch, for, forRange, forEach, while, tryCatch, block, body [bodyStatements (**single-block body**), oneLiner (**single-statement body**)]

List API

listAccess, at (**same as** listAccess), listSet, listAppend, listIndexExists, indexOf, listSlice

Scope

public, private

Binding

static\_, dynamic\_

Functions

function, method, param, pointerParam, mainFunction, docFunc, [pubMethod, privMethod]

State Variables

stateVar, constVar, [privMVar, pubMVar (**dynamic**), pubGVar (**static**)]

Classes

buildClass, docClass, [pubClass, privClass]

Packages



buildModule, fileDoc, docMod, prog, package, doxConfig, makefile

## Tagless with type families – 2 Layers of abstraction


- ① Over target language
- ② Over language-specific representational data structures

```
class (TypeSym repr) => VariableSym repr where
  type Variable repr
  var :: Label -> repr (Type repr)
      -> repr (Variable repr)
```





- 43 classes, 328 methods
- 300 functions that abstract over commonalities
- 40% more common methods between Java and C# than Java and Python



# Things we need/want to say

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

- Command line arguments
- Lists
- I/O
- Procedures with Input/Output/Both parameters
- Getters and setters
- Design patterns

## Example: List Slicing

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL: *hideous, we know*

```
listSlice sliced (valueOf old) (Just $ litInt 1)  
      (Just $ litInt 3) Nothing
```

Python:

```
sliced = old[1:3:]
```



## Example: List Slicing

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL: *hideous, we know*

```
listSlice sliced (valueOf old) (Just $ litInt 1)
(Just $ litInt 3) Nothing
```

Java:

```
ArrayList<Double> temp = new ArrayList<Double>(0);
for (int i_temp = 1; i_temp < 3; i_temp++) {
    temp.add(old.get(i_temp));
}
sliced = temp;
```

## Example: List Slicing

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL: *hideous, we know*

```
listSlice sliced (valueOf old) (Just $ litInt 1)
(Just $ litInt 3) Nothing
```

C#:

```
List<double> temp = new List<double>(0);
for (int i_temp = 1; i_temp < 3; i_temp++) {
    temp.Add(old[i_temp]);
}
sliced = temp;
```

## Example: List Slicing

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL: *hideous, we know*

```
listSlice sliced (valueOf old) (Just $ litInt 1)
  (Just $ litInt 3) Nothing
```

C++:

```
vector<double> temp(0);
for (int i_temp = 1; i_temp < 3; i_temp++) {
    temp.push_back(old.at(i_temp));
}
sliced = temp;
```

## Example: Setters

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL:

setMethod "FooClass" foo

Python:

```
def setFoo(self, foo):  
    self.foo = foo
```

## Example: Setters

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL:

setMethod "FooClass" foo

Java:

```
public void setFoo(int foo) throws Exception {  
    this.foo = foo;  
}
```

## Example: Setters

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL:

setMethod "FooClass" foo

C#:

```
public void setFoo(int foo) {  
    this.foo = foo;  
}
```

## Example: Setters

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL:

setMethod "FooClass" foo

C++:

```
void FooClass::setFoo(int foo) {  
    this—>foo = foo;  
}
```

# Complete Example

Introduction

Requirements

Creation

Implementation

Patterns

**Example**

Current Work

Conclusions

As part of **Drasil**, we can look at the Projectile program

## Design 1

- Documented
- Bundled inputs

## Design 2

- Logging
- More modular



# Currently working on

Introduction

Requirements

Creation

Implementation

Patterns

Example

**Current Work**

Conclusions

- More types
- Smarter generation - ex. import statements
- Interfacing with external libraries
- User-decisions - ex. which type to use for lists?
- More patterns

# Language of Design

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

Drasil project -

<http://github.com/JacquesCarette/Drasil>

- Generate scientific software
- **Design language** lets users guide design
- GOOL is the backend

## Conclusion: it works

Introduction

Requirements

Creation

Implementation

Patterns

Example

Current Work

Conclusions

GOOL used to generate some scientific software (glass breakage, projectile simulation)

Together new:

- Idiomatic code generation
- Human-readable, documented code generation
- Coding patterns are language idioms