

# Software Requirements Specification for HGHC

W. Spencer Smith

June 17, 2021

## Contents

<b>1</b>	<b>Reference Material</b>	<b>2</b>
1.1	Table of Units . . . . .	2
1.2	Table of Symbols . . . . .	2
<b>2</b>	<b>Specific System Description</b>	<b>2</b>
2.1	Solution Characteristics Specification . . . . .	3
2.1.1	Data Definitions . . . . .	3

# 1 Reference Material

This section records information for easy reference.

## 1.1 Table of Units

The unit system used throughout is SI (Système International d’Unités). In addition to the basic units, several derived units are also used. For each unit, [Tab:ToU](#) lists the symbol, a description and the SI name.

Symbol	Description	SI Name
°C	temperature	centigrade
m	length	metre
W	power	watt

Table 1: Table of Units

## 1.2 Table of Symbols

The symbols used in this document are summarized in [Tab:ToS](#) along with their units. The choice of symbols was made to be consistent with the nuclear physics literature and with that used in the FP manual.

Symbol	Description	Units
$h_b$	Initial coolant film conductance	—
$h_c$	Convective heat transfer coefficient between clad and coolant	$\frac{W}{m^2 \cdot ^\circ C}$
$h_g$	Effective heat transfer coefficient between clad and fuel surface	$\frac{W}{m^2 \cdot ^\circ C}$
$h_p$	Initial gap film conductance	—
$k_c$	Clad conductivity	—
$\tau_c$	Clad thickness	—

Table 2: Table of Symbols

# 2 Specific System Description

This section first presents the problem description, which gives a high-level view of the problem to be solved. This is followed by the solution characteristics specification, which presents the assumptions, theories, and definitions that are used.

## 2.1 Solution Characteristics Specification

The instance models that govern HGHC are presented in Sec:Instance Models. The information to understand the meaning of the instance models and their derivation is also presented, so that the instance models can be verified.

### 2.1.1 Data Definitions

This section collects and defines all the data needed to build the instance models.

Refname	DD:htTransCladFuel
Label	Effective heat transfer coefficient between clad and fuel surface
Symbol	$h_g$
Units	$\frac{\text{W}}{\text{m}^2\text{°C}}$
Equation	$h_g = \frac{2k_c h_p}{2k_c + \tau_c h_p}$
Description	$h_g$ is the effective heat transfer coefficient between clad and fuel surface ( $\frac{\text{W}}{\text{m}^2\text{°C}}$ ) $k_c$ is the clad conductivity (Unitless) $h_p$ is the initial gap film conductance (Unitless) $\tau_c$ is the clad thickness (Unitless)

Refname	DD:htTransCladCool
Label	Convective heat transfer coefficient between clad and coolant
Symbol	$h_c$
Units	$\frac{\text{W}}{\text{m}^2\text{°C}}$
Equation	$h_c = \frac{2k_c h_b}{2k_c + \tau_c h_b}$
Description	<p><math>h_c</math> is the convective heat transfer coefficient between clad and coolant  <math>(\frac{\text{W}}{\text{m}^2\text{°C}})</math>  <math>k_c</math> is the clad conductivity (Unitless)  <math>h_b</math> is the initial coolant film conductance (Unitless)  <math>\tau_c</math> is the clad thickness (Unitless)</p>