

Parameters Module

Template Module

param

Uses

N/A

Syntax

Exported Constants

Constant name	Type	Value
E	\mathbb{R}	7.17×10^7
TD	\mathbb{R}	3.0
M	\mathbb{R}	7.0
MK	\mathbb{R}	2.86×10^{-53}
LSF	\mathbb{R}	1.0

Exported Types

Type name	Type
Param	?

Exported Access Programs

Routine name	In	Out	Exceptions
Param		Param	

Semantics

State Variables

Variable name	Type
a	\mathbb{R}
b	\mathbb{R}
t	\mathbb{R}
w	\mathbb{R}
tnt	\mathbb{R}
pbtol	\mathbb{R}
asprat	\mathbb{R}
sd	\mathbb{R}
h	\mathbb{R}
gtf	\mathbb{R}
ldf	\mathbb{R}
wtnt	\mathbb{R}
sdvect	sequence [3] of \mathbb{R}
gt	String

Environment Variables

N/A

Assumptions

N/A

Access Routine Semantics

Param():

- transition:

$a \quad := 0.0$
 $b \quad := 0.0$
 $t \quad := 0.0$
 $w \quad := 0.0$
 $tnt \quad := 0.0$
 $pbtol \quad := 0.0$
 $asprat := 0.0$
 $sd \quad := 0.0$
 $h \quad := 0.0$

```

gtf    := 0.0
ldf    := 0.0
wtnt   := 0.0
sdvect := ⟨0.0, 0.0, 0.0⟩
gt     := “”

```

- output:

```
out := self
```

- exception:

N/A

Input Format Module

Module

inputFormat

Uses

param

Syntax

Exported Constants

N/A

Exported Types

N/A

Exported Access Programs

Routine name	In	Out	Exceptions
get_input	string	Param	

Semantics

State Variables

N/A

Environment Variables

Variable name	Type
filesys	FileSystem Read

Assumptions

N/A

Access Routine Semantics

get_input(filename, p):

- transition:

```

filesys    := filename
p.a        := filesys.readline
p.b        := filesys.readline
p.t        := filesys.readline
p.gt       := filesys.readline
p.w        := filesys.readline
p.tnt      := filesys.readline
p.sdvect[0] := filesys.readline
p.sdvect[1] := filesys.readline
p.sdvect[2] := filesys.readline
pbtol      := filesys.readline

```

- output:

N/A

- exception:

N/A

Input Constraints Module

Module

derivedValues

Uses

param

Syntax

Exported Constants

N/A

Exported Types

N/A

Exported Access Programs

Routine name	In	Out	Exceptions
derived_params	Param	Param	

Semantics

State Variables

N/A

Environment Variables

N/A

Assumptions

N/A

Access Routine Semantics

derived_params(p):

- transition:

$$\begin{aligned}
p.asprat &:= \frac{p.a}{p.b} \\
p.sd &:= \sqrt{p.sdvect[0]^2 + p.sdvect[1]^2 + p.sdvect[2]^2} \\
p.ldf &:= \frac{p.m}{p.td \cdot 16.0} \\
p.wtnt &:= p.w \times p.tnt \\
p.h &:= \begin{cases} p.t = 2.50 \implies 2.16 \\ p.t = 2.70 \implies 2.59 \\ p.t = 3.0 \implies 2.92 \\ p.t = 4.0 \implies 3.78 \\ p.t = 5.0 \implies 4.57 \\ p.t = 6.0 \implies 5.56 \\ p.t = 8.0 \implies 7.42 \\ p.t = 10.0 \implies 9.02 \\ p.t = 12.0 \implies 11.91 \\ p.t = 16.0 \implies 15.09 \\ p.t = 19.0 \implies 18.26 \\ p.t = 22.0 \implies 21.44 \\ \text{True} \implies 0.0 \end{cases} \\
p.gtf &:= \begin{cases} p.gt = \text{"AN"} \implies 1.0 \\ p.gt = \text{"HS"} \implies 2.0 \\ p.gt = \text{"FT"} \implies 3.0 \\ \text{True} \implies 0.0 \end{cases}
\end{aligned}$$

- output:

$$out := p$$

- exception:

N/A

Input Constraints Module

Module

checkConstraints

Uses

param

Syntax

Exported Constants

N/A

Exported Types

N/A

Exported Access Programs

Routine name	In	Out	Exceptions
check_constraints	Param		INPUTERROR

Semantics

State Variables

N/A

Environment Variables

N/A

Assumptions

N/A

Access Routine Semantics

derived_params(p):

- transition:

N/A

- output:

N/A

- exception:

$$exc := \begin{cases} p.a \leq 0.0 \wedge p.b \leq 0.0 & \implies \text{INPUTERROR} \\ \neg(1.0 \leq p.asprat \leq 5.0) & \implies \text{INPUTERROR} \\ p.t \notin \begin{Bmatrix} 2.50, 2.70, 3.0, 4.0, \\ 5.0, 6.0, 8.0, 10.0, \\ 12.0, 16.0, 19.0, 22.0, \end{Bmatrix} & \implies \text{INPUTERROR} \\ p.qt \notin \begin{Bmatrix} \text{"AN"}, \text{"HS"}, \text{"FT"}, \\ \text{"an"}, \text{"hs"}, \text{"ft"}, \end{Bmatrix} & \implies \text{INPUTERROR} \\ p.tnt \leq 0.0 & \implies \text{INPUTERROR} \\ \neg(4.5 \leq p.wtnt \leq 910.0) & \implies \text{INPUTERROR} \\ \neg(6.0 \leq p.sd \leq 130.0) & \implies \text{INPUTERROR} \end{cases}$$

Table Input Module

Module

readTable

Uses

None

Syntax

Exported Access Programs

Routine name	In	Out	Exceptions
read_table	string	sequence [2, ?, ?] of real	FILEERROR

Semantics

State Variables

contents : sequence [?, ?] of string

Environment Variables

filesys : FileSystem Read

Assumptions

None

Access Routine Semantics

read_table(*filename*):

- transition:

$$contents := \text{map } \text{splitOn}(' ') \text{ filesys.readall}(\text{filename})$$

- output:

$$out := \text{map } (\lambda x \rightarrow x[1 : 2]) \text{ contents} \parallel \text{map } (\lambda x \rightarrow x[2 : 2]) \text{ contents}$$

- exception:

$$exc := \neg \text{filesys.exists}(\text{filename}) \implies \text{FILEERROR}$$