

# Multi-lingual code generation in Drasil

Jacques Carette, Spencer Smith, Dan Szymczak and  
Steven Palmer

McMaster University

WG 2.11, July 2017 Meeting

# GENERATE



# ALL THE THINGS!

memegenerator

**NO**



# Context

software

certification

## Context

software (re)certification

# Context

## software (re)certification

- ▶ All software artifacts as evidence:
  - ▶ requirements, software specification, software design, code, tests, “theory manual”, user manual, build mechanism, . . .

# Context

## software (re)certification

- ▶ All software artifacts as **evidence**:
  - ▶ requirements, software specification, software design, code, tests, “theory manual”, user manual, build mechanism, . . .
- ▶ Massive amounts of **knowledge duplication**
  - ▶ Implies that either
    - ▶ non-code artifacts do not get maintained well enough, OR
    - ▶ are felt to be an expensive nuisance
  - ▶ duplication harms traceability

# Engineering Software

Or, software that engineers write.

- ▶ **GlassBR**: Computer whether a given plate of glass will resist a blast force.
- ▶ GamePhysics: “Chipmunk” game physics engine.
- ▶ SSP: Computation of mixed-soil slope stability.
- ▶ SWHS: Solar Water Heating System (w/ phase change material).
- ▶ NoPCM: Solar Water Heating System without PCM.
- ▶ Tiny: convective and effective heat transfer coefficients.



# Ontologies

Data.Drasil

Computation

Math

Software

Documentation

Physics

Solid Mechanics


Education

Physical  
Properties

Thermodynamics

# Ontologies

## Data.Drasil - Language Concepts



# Ontologies

Data.Drasil - Language Concepts - Document Language

*Show the details already!*

# GOOL

## Generic Object-Oriented Language.

### History:

- ▶ Lucas Beyak, JC. SAGA: A DSL for Story Management. DSL 2011.
- ▶ Jason Costabile. GOOL: A Generic OO Language. M.Eng. 2012.
- ▶ Yuriy Toporovskyy. Used GOOL for assign. gen. for 2<sup>nd</sup> year CS (Java) course.

# GOOL

## Generic Object-Oriented Language.

### History:

- ▶ Lucas Beyak, JC. SAGA: A DSL for Story Management. DSL 2011.
- ▶ Jason Costabile. GOOL: A Generic OO Language. M.Eng. 2012.
- ▶ Yuriy Toporovskyy. Used GOOL for assign. gen. for 2<sup>nd</sup> year CS (Java) course.

### Currently covers

- ▶ Java, C#
- ▶ C++
- ▶ Python, Lua
- ▶ Objective-C
- ▶ GOOL

# GOOL Design

## Requirements

1. Capture the essence of programming in mainstream, pseudo-OO languages.
2. Make the embedded DSL palatable.
3. Eschew language-specific “idiomatic” patterns.
4. Target for generation.

# GOOL Design

## Requirements

1. Capture the essence of programming in mainstream, pseudo-OO languages.
2. Make the embedded DSL palatable.
3. Eschew language-specific “idiomatic” patterns.
4. Target for generation.
  - ▶ multiple languages implies GOOL must capture

# GOOL Design

## Requirements

1. Capture the essence of programming in mainstream, pseudo-OO languages.
2. Make the embedded DSL palatable.
3. Eschew language-specific “idiomatic” patterns.
4. Target for generation.
  - ▶ multiple languages implies GOOL must capture
    - ▶ features common to all targeted languages, and



# GOOL Design

## Requirements

1. Capture the essence of programming in mainstream, pseudo-OO languages.
2. Make the embedded DSL palatable.
3. Eschew language-specific “idiomatic” patterns.
4. Target for generation.
  - ▶ multiple languages implies GOOL must capture
    - ▶ features common to all targeted languages, and
    - ▶ *language-required* features not common to all languages:
      - ▶ public/private scoping
      - ▶ dynamic/static binding
      - ▶ explicit destructors
      - ▶ explicit types in IO statements

# GOOL Design

## Requirements

1. Capture the essence of programming in mainstream, pseudo-OO languages.
2. Make the embedded DSL palatable.
3. Eschew language-specific “idiomatic” patterns.
4. Target for generation.
  - ▶ multiple languages implies GOOL must capture
    - ▶ features common to all targeted languages, and
    - ▶ *language-required* features not common to all languages:
      - ▶ public/private scoping
      - ▶ dynamic/static binding
      - ▶ explicit destructors
      - ▶ explicit types in IO statements
  - ▶ when rendering, extra information can be dropped

# GOOL Design

## Renderer

- ▶ uses record that acts as virtual dispatch table:

```
data Config = Config {  
  assignDoc  :: Assignment -> Doc,  
  binOpDoc   :: BinaryOp   -> Doc,  
  bodyDoc    :: Body       -> Doc,  
  blockDoc   :: Block      -> Doc,  
  callFuncParamList :: [Value] -> Doc,  
  conditionalDoc :: Conditional -> Doc,  
  declarationDoc :: Declaration -> Doc,  
  exprDoc    :: Expression -> Doc,  
  funcDoc    :: Function -> Doc,  
  — and many more  
}
```

- ▶ one for each language (7)
- ▶ Text.PrettyPrint used to make rendered code look nice

# GOOL Design

## GOOL syntax

- ▶ designed to look like a programming language by using

# GOOL Design

## GOOL syntax

- ▶ designed to look like a programming language by using

1. custom infix operators:

- *logical operators*

(?!), (?<), (?<=), (?>), (?>=), — *etc.*

- *arithmetic operators*

(#~), (#/^), (#|), (#+), (#-), — *etc.*

- *assignment operators*

(&=), (&-), (&++), (&~-) — *etc.*

# GOOL Design

## GOOL syntax

- ▶ designed to look like a programming language by using

1. custom infix operators:

- *logical operators*

(?!), (?<), (?<=), (?>), (?>=), — *etc.*

- *arithmetic operators*

(#~), (#/^), (#|), (#+), (#-), — *etc.*

- *assignment operators*

(&=), (&-), (&++), (&~-) — *etc.*

2. smart constructors:

bool, int, float, char, string,

true, false,

pubClass, privClass,

pubMethod, privMethod,

**print**, println

and so on (about 100).

# GOOL Design

Consider the function  $f(x, y) = 2x/y$ . In GOOL:

```
f :: FunctionDecl
f = pubMethod (methodType float) "f"
  [param "x" float, param "y" float]
  (oneLiner $ return $
    (litFloat 2) #* (var "x") #/ (var "y"))
```

# Implementation Choices

(Of generated code)

- ▶ programming language to be rendered?



# Implementation Choices

(Of generated code)

- ▶ programming language to be rendered?
- ▶ generate library or program?

# Implementation Choices

(Of generated code)

- ▶ programming language to be rendered?
- ▶ generate library or program?
- ▶ logging?
  - ▶ function calls
  - ▶ assignments

# Implementation Choices

(Of generated code)

- ▶ programming language to be rendered?
- ▶ generate library or program?
- ▶ logging?
  - ▶ function calls
  - ▶ assignments
- ▶ documentation in code?
  - ▶ commented classes
  - ▶ commented functions
  - ▶ commented variables

# Design Choices

- ▶ structure of input/output?
  - ▶ file vs console
  - ▶ how data is arranged

# Design Choices

- ▶ structure of input/output?
  - ▶ file vs console
  - ▶ how data is arranged
- ▶ behaviour on failed constraints?
  - ▶ print warning
  - ▶ quit with error
  - ▶ throw exception

# Design Choices

- ▶ structure of input/output?
  - ▶ file vs console
  - ▶ how data is arranged
- ▶ behaviour on failed constraints?
  - ▶ print warning
  - ▶ quit with error
  - ▶ throw exception
- ▶ which (common) algorithms to use?
  - ▶ sorting algorithm
  - ▶ searching algorithm
  - ▶ matrix multiplication, solving
  - ▶ ODE solver
  - ▶ etc.

# Design Choices

- ▶ structure of input/output?
  - ▶ file vs console
  - ▶ how data is arranged
- ▶ behaviour on failed constraints?
  - ▶ print warning
  - ▶ quit with error
  - ▶ throw exception
- ▶ which (common) algorithms to use?
  - ▶ sorting algorithm
  - ▶ searching algorithm
  - ▶ matrix multiplication, solving
  - ▶ ODE solver
  - ▶ etc.
- ▶ Inline code or library calls?

# Open Questions

How to classify *choices*.




# Open Questions

How to classify *choices*.

Proper Language(s) of choices.

**GENERATE**



**NO**

