

Template Manager Docker 3051 Operations Guide

How to rebuild and restart the local Docker server with the newest project version

Purpose

Use this guide when localhost:3051 is showing an older version of the Printable Intake Template Manager and you want it to run the newest version from this project folder.

This project currently uses Docker image templatemanager:local, container templatemanager-3051, and host port 3051 mapped to container port 3000.

Start In The Project Folder

Open a terminal and move into the Template Manager repo before running any commands.

```
cd
/home/anthony/Desktop/AnthonysFolder/clients/DelAireBC/digitalintake/v1/digitalintake/templ
atemanager
```

Recommended Update Flow

Run these commands when you have changed templates, images, API routes, docs, or app code and want localhost:3051 to show the newest project state.

```
npm run seed
npm run lint
docker build -t templatemanager:local .
docker rm -f templatemanager-3051
docker run -d --name templatemanager-3051 -p 3051:3000 templatemanager:local
```

What Those Commands Do

npm run seed refreshes data/printable-templates.json from the static template catalog. Run this after adding or editing PrintableTemplate records.

npm run lint checks the project for code issues before building the image.

docker build -t templatemanager:local . creates a fresh Docker image from the current files in this folder.

docker rm -f templatemanager-3051 stops and removes the old running container. It does not delete the rebuilt image.

docker run -d --name templatemanager-3051 -p 3051:3000 templatemanager:local starts a new container and exposes it at http://localhost:3051.

Verify It Worked

After the container starts, check that Docker shows the container and the port mapping.

```
docker ps --filter name=templatemanager-3051
```

Then check the app routes from your terminal.

```
curl -I http://localhost:3051/
```

```
curl http://localhost:3051/api/templates/page-ids
```

For a specific template, open or query its editor/context route.

```
http://localhost:3051/dev/test-template-editor/PAGE_ID
```

```
http://localhost:3051/api/templates/PAGE_ID/context
```

Useful Docker Commands

See running containers:

```
docker ps
```

See all containers, including stopped ones:

```
docker ps -a
```

Read recent server logs:

```
docker logs --tail 100 templatemanager-3051
```

Follow live logs:

```
docker logs -f templatemanager-3051
```

Stop the server:

```
docker stop templatemanager-3051
```

Start it again without rebuilding:

```
docker start templatemanager-3051
```

Remove the container:

```
docker rm -f templatemanager-3051
```

List local images:

```
docker images
```

When To Rebuild

Rebuild the image after any code change, template module change, public asset change, package change, or seeded data change that should appear in the Docker-served app.

If you only stopped the container and did not change project files, you can use `docker start templatemanager-3051` instead of rebuilding.

If port 3051 is already in use, find the existing container with `docker ps` and remove or stop the container using that port before running the new one.

Important Files

Dockerfile defines how the production image is built.

.dockerignore controls what files are excluded from the Docker build context.

public/template-assets contains runtime image assets used by templates.

data/printable-templates.json is the active local template store copied into the Docker image.

lib/printable-templates/templates contains the static seed catalog.

One Command Block To Memorize

```
cd
/home/anthony/Desktop/AnthonysFolder/clients/DelAireBC/digitalintake/v1/digitalintake/templ
atemanager

npm run seed && npm run lint && docker build -t templatemanager:local . && docker rm -f
templatemanager-3051 && docker run -d --name templatemanager-3051 -p 3051:3000
templatemanager:local
```

Then open <http://localhost:3051>.