

## vul\_files\_31 Scan Report

Project Name	vul_files_31
Scan Start	Tuesday, January 7, 2025 3:41:58 PM
Preset	Checkmarx Default
Scan Time	03h:10m:46s
Lines Of Code Scanned	289502
Files Scanned	124
Report Creation Time	Tuesday, January 7, 2025 7:02:40 PM
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033</a>
Team	CxServer
Checkmarx Version	8.7.0
Scan Type	Full
Source Origin	LocalPath
Density	9/10000 (Vulnerabilities/LOC)
Visibility	Public

## Filter Settings

### **Severity**

Included: High, Medium, Low, Information

Excluded: None

### **Result State**

Included: Confirmed, Not Exploitable, To Verify, Urgent, Proposed Not Exploitable

Excluded: None

### **Assigned to**

Included: All

### **Categories**

Included:

Uncategorized All

Custom All

PCI DSS v3.2 All

OWASP Top 10 2013 All

FISMA 2014 All

NIST SP 800-53 All

OWASP Top 10 2017 All

OWASP Mobile Top 10  
2016 All

Excluded:

Uncategorized None

Custom None

PCI DSS v3.2 None

OWASP Top 10 2013 None

FISMA 2014 None

NIST SP 800-53	None
OWASP Top 10 2017	None
OWASP Mobile Top 10 2016	None

**Results Limit**


Results limit per query was set to 50

**Selected Queries**


Selected queries are listed in [Result Summary](#)

---


### Result Summary



### Most Vulnerable Files



### Top 5 Vulnerabilities



## Scan Summary - OWASP Top 10 2017

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2017](#)

Category	Threat Agent	Exploitability	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	App. Specific	EASY	COMMON	EASY	SEVERE	App. Specific	25	23
A2-Broken Authentication	App. Specific	EASY	COMMON	AVERAGE	SEVERE	App. Specific	47	47
A3-Sensitive Data Exposure	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	App. Specific	7	7
A4-XML External Entities (XXE)	App. Specific	AVERAGE	COMMON	EASY	SEVERE	App. Specific	0	0
A5-Broken Access Control*	App. Specific	AVERAGE	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A6-Security Misconfiguration	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A7-Cross-Site Scripting (XSS)	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A8-Insecure Deserialization	App. Specific	DIFFICULT	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A9-Using Components with Known Vulnerabilities*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	MODERATE	App. Specific	49	49
A10-Insufficient Logging & Monitoring	App. Specific	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	App. Specific	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - OWASP Top 10 2013

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2013](#)

Category	Threat Agent	Attack Vectors	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	AVERAGE	SEVERE	ALL DATA	0	0
A2-Broken Authentication and Session Management	EXTERNAL, INTERNAL USERS	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	AFFECTED DATA AND FUNCTIONS	0	0
A3-Cross-Site Scripting (XSS)	EXTERNAL, INTERNAL, ADMIN USERS	AVERAGE	VERY WIDESPREAD	EASY	MODERATE	AFFECTED DATA AND SYSTEM	0	0
A4-Insecure Direct Object References	SYSTEM USERS	EASY	COMMON	EASY	MODERATE	EXPOSED DATA	0	0
A5-Security Misconfiguration	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	EASY	MODERATE	ALL DATA AND SYSTEM	0	0
A6-Sensitive Data Exposure	EXTERNAL, INTERNAL, ADMIN USERS, USERS BROWSERS	DIFFICULT	UNCOMMON	AVERAGE	SEVERE	EXPOSED DATA	0	0
A7-Missing Function Level Access Control*	EXTERNAL, INTERNAL USERS	EASY	COMMON	AVERAGE	MODERATE	EXPOSED DATA AND FUNCTIONS	0	0
A8-Cross-Site Request Forgery (CSRF)	USERS BROWSERS	AVERAGE	COMMON	EASY	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A9-Using Components with Known Vulnerabilities*	EXTERNAL USERS, AUTOMATED TOOLS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	49	49
A10-Unvalidated Redirects and Forwards	USERS BROWSERS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - PCI DSS v3.2

Category	Issues Found	Best Fix Locations
PCI DSS (3.2) - 6.5.1 - Injection flaws - particularly SQL injection	0	0
PCI DSS (3.2) - 6.5.2 - Buffer overflows	24	24
PCI DSS (3.2) - 6.5.3 - Insecure cryptographic storage	0	0
PCI DSS (3.2) - 6.5.4 - Insecure communications	0	0
PCI DSS (3.2) - 6.5.5 - Improper error handling*	0	0
PCI DSS (3.2) - 6.5.7 - Cross-site scripting (XSS)	0	0
PCI DSS (3.2) - 6.5.8 - Improper access control	0	0
PCI DSS (3.2) - 6.5.9 - Cross-site request forgery	0	0
PCI DSS (3.2) - 6.5.10 - Broken authentication and session management	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - FISMA 2014

Category	Description	Issues Found	Best Fix Locations
Access Control	Organizations must limit information system access to authorized users, processes acting on behalf of authorized users, or devices (including other information systems) and to the types of transactions and functions that authorized users are permitted to exercise.	1	1
Audit And Accountability*	Organizations must: (i) create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity; and (ii) ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.	0	0
Configuration Management	Organizations must: (i) establish and maintain baseline configurations and inventories of organizational information systems (including hardware, software, firmware, and documentation) throughout the respective system development life cycles; and (ii) establish and enforce security configuration settings for information technology products employed in organizational information systems.	0	0
Identification And Authentication*	Organizations must identify information system users, processes acting on behalf of users, or devices and authenticate (or verify) the identities of those users, processes, or devices, as a prerequisite to allowing access to organizational information systems.	46	46
Media Protection	Organizations must: (i) protect information system media, both paper and digital; (ii) limit access to information on information system media to authorized users; and (iii) sanitize or destroy information system media before disposal or release for reuse.	7	7
System And Communications Protection	Organizations must: (i) monitor, control, and protect organizational communications (i.e., information transmitted or received by organizational information systems) at the external boundaries and key internal boundaries of the information systems; and (ii) employ architectural designs, software development techniques, and systems engineering principles that promote effective information security within organizational information systems.	0	0
System And Information Integrity	Organizations must: (i) identify, report, and correct information and information system flaws in a timely manner; (ii) provide protection from malicious code at appropriate locations within organizational information systems; and (iii) monitor information system security alerts and advisories and take appropriate actions in response.	10	10

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - NIST SP 800-53

Category	Issues Found	Best Fix Locations
AC-12 Session Termination (P2)	0	0
AC-3 Access Enforcement (P1)	47	47
AC-4 Information Flow Enforcement (P1)	0	0
AC-6 Least Privilege (P1)	0	0
AU-9 Protection of Audit Information (P1)	0	0
CM-6 Configuration Settings (P2)	0	0
IA-5 Authenticator Management (P1)	0	0
IA-6 Authenticator Feedback (P2)	0	0
IA-8 Identification and Authentication (Non-Organizational Users) (P1)	0	0
SC-12 Cryptographic Key Establishment and Management (P1)	0	0
SC-13 Cryptographic Protection (P1)	0	0
SC-17 Public Key Infrastructure Certificates (P1)	0	0
SC-18 Mobile Code (P2)	0	0
SC-23 Session Authenticity (P1)*	0	0
SC-28 Protection of Information at Rest (P1)	7	7
SC-4 Information in Shared Resources (P1)	0	0
SC-5 Denial of Service Protection (P1)*	89	62
SC-8 Transmission Confidentiality and Integrity (P1)	0	0
SI-10 Information Input Validation (P1)*	14	14
SI-11 Error Handling (P2)*	12	12
SI-15 Information Output Filtering (P0)	0	0
SI-16 Memory Protection (P1)	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.



## Scan Summary - OWASP Mobile Top 10 2016

Category	Description	Issues Found	Best Fix Locations
M1-Improper Platform Usage	This category covers misuse of a platform feature or failure to use platform security controls. It might include Android intents, platform permissions, misuse of TouchID, the Keychain, or some other security control that is part of the mobile operating system. There are several ways that mobile apps can experience this risk.	0	0
M2-Insecure Data Storage	This category covers insecure data storage and unintended data leakage.	0	0
M3-Insecure Communication	This category covers poor handshaking, incorrect SSL versions, weak negotiation, cleartext communication of sensitive assets, etc.	0	0
M4-Insecure Authentication	This category captures notions of authenticating the end user or bad session management. This can include: -Failing to identify the user at all when that should be required -Failure to maintain the user's identity when it is required -Weaknesses in session management	0	0
M5-Insufficient Cryptography	The code applies cryptography to a sensitive information asset. However, the cryptography is insufficient in some way. Note that anything and everything related to TLS or SSL goes in M3. Also, if the app fails to use cryptography at all when it should, that probably belongs in M2. This category is for issues where cryptography was attempted, but it wasn't done correctly.	0	0
M6-Insecure Authorization	This is a category to capture any failures in authorization (e.g., authorization decisions in the client side, forced browsing, etc.). It is distinct from authentication issues (e.g., device enrolment, user identification, etc.). If the app does not authenticate users at all in a situation where it should (e.g., granting anonymous access to some resource or service when authenticated and authorized access is required), then that is an authentication failure not an authorization failure.	0	0
M7-Client Code Quality	This category is the catch-all for code-level implementation problems in the mobile client. That's distinct from server-side coding mistakes. This would capture things like buffer overflows, format string vulnerabilities, and various other code-level mistakes where the solution is to rewrite some code that's running on the mobile device.	0	0
M8-Code Tampering	This category covers binary patching, local resource modification, method hooking, method swizzling, and dynamic memory modification. Once the application is delivered to the mobile device, the code and data resources are resident there. An attacker can either directly modify the code, change the contents of memory dynamically, change or replace the system APIs that the application uses, or	0	0

	modify the application's data and resources. This can provide the attacker a direct method of subverting the intended use of the software for personal or monetary gain.		
M9-Reverse Engineering	This category includes analysis of the final core binary to determine its source code, libraries, algorithms, and other assets. Software such as IDA Pro, Hopper, otool, and other binary inspection tools give the attacker insight into the inner workings of the application. This may be used to exploit other nascent vulnerabilities in the application, as well as revealing information about back end servers, cryptographic constants and ciphers, and intellectual property.	0	0
M10-Extraneous Functionality	Often, developers include hidden backdoor functionality or other internal development security controls that are not intended to be released into a production environment. For example, a developer may accidentally include a password as a comment in a hybrid app. Another example includes disabling of 2-factor authentication during testing.	0	0


## Scan Summary - Custom

Category	Issues Found	Best Fix Locations
Must audit	0	0
Check	0	0
Optional	0	0

## Results Distribution By Status First scan of the project

	High	Medium	Low	Information	Total
New Issues	0	156	92	0	248
Recurrent Issues	0	0	0	0	0
Total	0	156	92	0	248

Fixed Issues	0	0	0	0	0
--------------	---	---	---	---	---



## Results Distribution By State

	High	Medium	Low	Information	Total
Confirmed	0	0	0	0	0
Not Exploitable	0	0	0	0	0
To Verify	0	156	92	0	248
Urgent	0	0	0	0	0
Proposed Not Exploitable	0	0	0	0	0
Total	0	156	92	0	248

## Result Summary

Vulnerability Type	Occurrences	Severity
<a href="#">Use of Zero Initialized Pointer</a>	70	Medium
<a href="#">Dangerous Functions</a>	49	Medium
<a href="#">Buffer Overflow boundcpy WrongSizeParam</a>	14	Medium
<a href="#">Memory Leak</a>	8	Medium
<a href="#">Integer Overflow</a>	7	Medium

<a href="#">Divide By Zero</a>	5	Medium
<a href="#">Float Overflow</a>	3	Medium
<a href="#">Improper Resource Access Authorization</a>	46	Low
<a href="#">Unchecked Return Value</a>	12	Low
<a href="#">NULL Pointer Dereference</a>	11	Low
<a href="#">Use of Sizeof On a Pointer Type</a>	8	Low
<a href="#">Use of Insufficiently Random Values</a>	7	Low
<a href="#">Unchecked Array Index</a>	4	Low
<a href="#">Inconsistent Implementations</a>	2	Low
<a href="#">Incorrect Permission Assignment For Critical Resources</a>	1	Low
<a href="#">TOCTOU</a>	1	Low

## 10 Most Vulnerable Files

### High and Medium Vulnerabilities

File Name	Issues Found
libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	20
libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	20
libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	20
libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	9
libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	9
libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	7
libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c	3
libsdl-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c	3
libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	3
libsdl-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c	3

# Scan Results Details

## Use of Zero Initialized Pointer

Query Path:

CPP\Cx\CPP Medium Threat\Use of Zero Initialized Pointer Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

### Description

#### Use of Zero Initialized Pointer\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=89">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=89</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	829	847
Object	ctx	ctx

### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```

....
829.                video_decoder_context_t *ctx = NULL;
....
847.                stride                        = ctx->target-
>linesize[0];

```

#### Use of Zero Initialized Pointer\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=90">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=90</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

Source	Destination
--------	-------------

File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	829	846
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.                video_decoder_context_t *ctx = NULL;  
....  
846.                src                        = ctx->target-  
>data[0];
```

#### Use of Zero Initialized Pointer\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=91">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=91</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	829	833
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.                video_decoder_context_t *ctx = NULL;  
....  
833.                pts                        = ctx->pts;
```

#### Use of Zero Initialized Pointer\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=92">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=92</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	928	933
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....
928.                video_decoder_context_t *ctx = NULL;
....
933.                stride                        = ctx->target-
>linesize[0];
```

#### Use of Zero Initialized Pointer\Path 5:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=93>

Status New

The variable declared in ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	928	932
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....
928.                video_decoder_context_t *ctx = NULL;
....
932.                src                        = ctx->target-
>data[0];
```

#### Use of Zero Initialized Pointer\Path 6:

Severity Medium

Result State To Verify

Online Results <http://WIN->



	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=94">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=94</a>
Status	New

The variable declared in ctx at libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	928	931
Object	ctx	ctx

#### Code Snippet

File Name libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.          video_decoder_context_t *ctx = NULL;  
....  
931.          pts = ctx->pts;
```

#### Use of Zero Initialized Pointer\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=95">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=95</a>
Status	New

The variable declared in decoder\_ctx at libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 1509 is not initialized when it is used by decoder\_ctx at libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c in line 1509.

	Source	Destination
File	libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	1515	1544
Object	decoder_ctx	decoder_ctx

#### Code Snippet

File Name libretto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method static void decode\_video(AVCodecContext \*ctx, AVPacket \*pkt, size\_t frame\_size, ASS\_Track \*ass\_track\_active)

```
....  
1515.      video_decoder_context_t *decoder_ctx = NULL;  
....  
1544.      ret = avcodec_receive_frame(ctx, decoder_ctx->source);
```

**Use of Zero Initialized Pointer\Path 8:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=96">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=96</a>
Status	New

The variable declared in `audio_buffer` at `libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c` in line 1709 is not initialized when it is used by `audio_buffer` at `libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c` in line 1709.

	Source	Destination
File	<code>libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c</code>	<code>libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c</code>
Line	1716	1832
Object	<code>audio_buffer</code>	<code>audio_buffer</code>

**Code Snippet**

File Name `libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c`  
Method `static void decode_thread(void *data)`

```
....  
1716.      int16_t *audio_buffer  = NULL;  
....  
1832.          audio_buffer = decode_audio(actx_active, pkt, aud_frame,
```

**Use of Zero Initialized Pointer\Path 9:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=97">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=97</a>
Status	New

The variable declared in `ctx` at `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c` in line 607 is not initialized when it is used by `ctx` at `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c` in line 607.

	Source	Destination
File	<code>libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c</code>	<code>libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c</code>
Line	829	847
Object	<code>ctx</code>	<code>ctx</code>

**Code Snippet**

File Name `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c`  
Method `void CORE_PREFIX(retro_run)(void)`

```
.....
829.                video_decoder_context_t *ctx = NULL;
.....
847.                stride                        = ctx->target-
>linesize[0];
```

#### Use of Zero Initialized Pointer\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=98">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=98</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	829	846
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
.....
829.                video_decoder_context_t *ctx = NULL;
.....
846.                src                        = ctx->target-
>data[0];
```

#### Use of Zero Initialized Pointer\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=99">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=99</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	829	833
Object	ctx	ctx

**Code Snippet**

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.                video_decoder_context_t *ctx = NULL;  
....  
833.                pts                        = ctx->pts;
```

**Use of Zero Initialized Pointer\Path 12:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=100>  
Status New

The variable declared in ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	928	933
Object	ctx	ctx

**Code Snippet**

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.                video_decoder_context_t *ctx = NULL;  
....  
933.                stride                        = ctx->target->linesize[0];
```

**Use of Zero Initialized Pointer\Path 13:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=101>  
Status New

The variable declared in ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Line	928	932
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.                video_decoder_context_t *ctx = NULL;  
....  
932.                src                        = ctx->target->  
>data[0];
```

#### Use of Zero Initialized Pointer\Path 14:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=102>

Status New

The variable declared in ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	928	931
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.                video_decoder_context_t *ctx = NULL;  
....  
931.                pts                        = ctx->pts;
```

#### Use of Zero Initialized Pointer\Path 15:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=103>

Status New

The variable declared in decoder\_ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 1509 is not initialized when it is used by decoder\_ctx at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 1509.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	1515	1544
Object	decoder_ctx	decoder_ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void decode\_video(AVCodecContext \*ctx, AVPacket \*pkt, size\_t frame\_size, ASS\_Track \*ass\_track\_active)

```
....  
1515.      video_decoder_context_t *decoder_ctx = NULL;  
....  
1544.      ret = avcodec_receive_frame(ctx, decoder_ctx->source);
```

#### Use of Zero Initialized Pointer\Path 16:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=104">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=104</a>
Status	New

The variable declared in audio\_buffer at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 1709 is not initialized when it is used by audio\_buffer at libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c in line 1709.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	1716	1832
Object	audio_buffer	audio_buffer

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void decode\_thread(void \*data)

```
....  
1716.      int16_t *audio_buffer = NULL;  
....  
1832.      audio_buffer = decode_audio(actx_active, pkt, aud_frame,
```

#### Use of Zero Initialized Pointer\Path 17:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=105">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=105</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	829	847
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.                video_decoder_context_t *ctx = NULL;  
....  
847.                stride                        = ctx->target->linesize[0];
```

#### Use of Zero Initialized Pointer\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=106">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=106</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	829	846
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.                video_decoder_context_t *ctx = NULL;  
....  
846.                src                        = ctx->target->data[0];
```

#### Use of Zero Initialized Pointer\Path 19:

Severity	Medium
Result State	To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=107">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=107</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	829	833
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
829.          video_decoder_context_t *ctx = NULL;  
....  
833.          pts = ctx->pts;
```

#### Use of Zero Initialized Pointer\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=108">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=108</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	928	933
Object	ctx	ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.          video_decoder_context_t *ctx = NULL;  
....  
933.          stride = ctx->target->linesize[0];
```



**Use of Zero Initialized Pointer\Path 21:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=109">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=109</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	928	932
Object	ctx	ctx

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.          video_decoder_context_t *ctx = NULL;  
....  
932.          src                          = ctx->target-  
>data[0];
```

**Use of Zero Initialized Pointer\Path 22:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=110">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=110</a>
Status	New

The variable declared in ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607 is not initialized when it is used by ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 607.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	928	931
Object	ctx	ctx

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
928.          video_decoder_context_t *ctx = NULL;  
....  
931.          pts                        = ctx->pts;
```

#### Use of Zero Initialized Pointer\Path 23:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=111">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=111</a>
Status	New

The variable declared in decoder\_ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 1509 is not initialized when it is used by decoder\_ctx at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 1509.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	1515	1544
Object	decoder_ctx	decoder_ctx

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void decode\_video(AVCodecContext \*ctx, AVPacket \*pkt, size\_t frame\_size, ASS\_Track \*ass\_track\_active)

```
....  
1515.          video_decoder_context_t *decoder_ctx = NULL;  
....  
1544.          ret = avcodec_receive_frame(ctx, decoder_ctx->source);
```

#### Use of Zero Initialized Pointer\Path 24:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=112">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=112</a>
Status	New

The variable declared in audio\_buffer at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 1709 is not initialized when it is used by audio\_buffer at libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c in line 1709.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	1716	1832

Object	audio_buffer	audio_buffer
--------	--------------	--------------

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void decode\_thread(void \*data)

```
....
1716.      int16_t *audio_buffer    = NULL;
....
1832.          audio_buffer = decode_audio(actx_active, pkt, aud_frame,
```

#### Use of Zero Initialized Pointer\Path 25:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=113">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=113</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 605 is not initialized when it is used by texturedata at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 605.

	Source	Destination
File	libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c	libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c
Line	610	656
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c  
Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
610.      GLES_TextureData *texturedata = NULL;
....
656.          *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 26:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=114">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=114</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 605 is not initialized when it is used by texturedata at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 605.

Source	Destination
--------	-------------

File	libsdl-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c	libsdl-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c
Line	610	655
Object	texturedata	texturedata

#### Code Snippet

File Name libsdl-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c  
Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....  
610.         GLES_TextureData *texturedata = NULL;  
....  
655.         *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 27:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=115">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=115</a>
Status	New

The variable declared in texturedata at libsdl-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 595 is not initialized when it is used by texturedata at libsdl-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 595.

	Source	Destination
File	libsdl-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c	libsdl-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c
Line	600	646
Object	texturedata	texturedata

#### Code Snippet

File Name libsdl-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c  
Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....  
600.         GLES_TextureData *texturedata = NULL;  
....  
646.         *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 28:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=116">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=116</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 595 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 595.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c	libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c
Line	600	645
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c

Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
600.      GLES_TextureData *texturedata = NULL;
....
645.      *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 29:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=117>

Status New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c in line 602 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c in line 602.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c	libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c
Line	607	653
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c

Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
607.      GLES_TextureData *texturedata = NULL;
....
653.      *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=118">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=118</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c in line 602 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c in line 602.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c	libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c
Line	607	652
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.25.1-CVE-2022-4743-TP.c  
 Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
607.      GLES_TextureData *texturedata = NULL;
....
652.      *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 31:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=119">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=119</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c	libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c
Line	598	644
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c  
 Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.         GLES_TextureData *texturedata = NULL;
....
644.             *(verts++) = uv_[1] * texturedata->texh;
```

### Use of Zero Initialized Pointer\Path 32:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=120">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=120</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c	libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c
Line	598	643
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.27.1-CVE-2022-4743-FP.c  
 Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.         GLES_TextureData *texturedata = NULL;
....
643.             *(verts++) = uv_[0] * texturedata->texw;
```

### Use of Zero Initialized Pointer\Path 33:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=121">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=121</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c	libSDL-org@@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c
Line	598	644

Object	texturedata	texturedata
--------	-------------	-------------

#### Code Snippet

File Name libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c  
 Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.      GLES_TextureData *texturedata = NULL;
....
644.      *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 34:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=122">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=122</a>
Status	New

The variable declared in texturedata at libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c	libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c
Line	598	643
Object	texturedata	texturedata

#### Code Snippet

File Name libsd-@SDL-prerelease-2.29.1-CVE-2022-4743-FP.c  
 Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.      GLES_TextureData *texturedata = NULL;
....
643.      *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 35:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=123">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=123</a>
Status	New

The variable declared in texturedata at libsd-@SDL-release-2.0.18-CVE-2022-4743-TP.c in line 605 is not initialized when it is used by texturedata at libsd-@SDL-release-2.0.18-CVE-2022-4743-TP.c in line 605.



	Source	Destination
File	libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c	libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c
Line	610	656
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c  
Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
610.         GLES_TextureData *texturedata = NULL;
....
656.         *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 36:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=124">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=124</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c in line 605 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c in line 605.

	Source	Destination
File	libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c	libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c
Line	610	655
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-release-2.0.18-CVE-2022-4743-TP.c  
Method GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
610.         GLES_TextureData *texturedata = NULL;
....
655.         *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 37:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=125">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=125</a>

Status New

The variable declared in texturedata at libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c
Line	598	644
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c  
Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....  
598.      GLES_TextureData *texturedata = NULL;  
....  
644.      *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 38:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=126>  
Status New

The variable declared in texturedata at libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c
Line	598	643
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-release-2.28.4-CVE-2022-4743-FP.c  
Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....  
598.      GLES_TextureData *texturedata = NULL;  
....  
643.      *(verts++) = uv_[0] * texturedata->texw;
```

**Use of Zero Initialized Pointer\Path 39:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=127">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=127</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c
Line	598	644
Object	texturedata	texturedata

**Code Snippet**

File Name libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c  
Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....  
598.     GLES_TextureData *texturedata = NULL;  
....  
644.         *(verts++) = uv_[1] * texturedata->texh;
```

**Use of Zero Initialized Pointer\Path 40:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=128">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=128</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c
Line	598	643
Object	texturedata	texturedata

**Code Snippet**

File Name libSDL-org@@SDL-release-2.30.3-CVE-2022-4743-FP.c  
Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.         GLES_TextureData *texturedata = NULL;
....
643.             *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=129">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=129</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c
Line	598	644
Object	texturedata	texturedata

#### Code Snippet

File Name libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c  
 Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.         GLES_TextureData *texturedata = NULL;
....
644.             *(verts++) = uv_[1] * texturedata->texh;
```

#### Use of Zero Initialized Pointer\Path 42:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=130">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=130</a>
Status	New

The variable declared in texturedata at libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c in line 593 is not initialized when it is used by texturedata at libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c in line 593.

	Source	Destination
File	libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c	libSDL-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c
Line	598	643

Object	texturedata	texturedata
--------	-------------	-------------

#### Code Snippet

File Name libsd-org@@SDL-release-2.30.6-CVE-2022-4743-FP.c  
Method static int GLES\_QueueGeometry(SDL\_Renderer \*renderer, SDL\_RenderCommand \*cmd, SDL\_Texture \*texture,

```
....
598.         GLES_TextureData *texturedata = NULL;
....
643.         *(verts++) = uv_[0] * texturedata->texw;
```

#### Use of Zero Initialized Pointer\Path 43:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=131">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=131</a>
Status	New

The variable declared in varname at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 161 is not initialized when it is used by varname at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 161.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c	libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c
Line	168	169
Object	varname	varname

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c  
Method static int registerlocalvar (LexState \*ls, TString \*varname) {

```
....
168.         f->locvars[oldsize++].varname = NULL;
169.         f->locvars[fs->nlocvars].varname = varname;
```

#### Use of Zero Initialized Pointer\Path 44:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=132">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=132</a>
Status	New

The variable declared in name at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 228 is not initialized when it is used by name at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 228.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2022-	libretro@@RetroArch-v1.9.11-CVE-2022-

	28805-FP.c	28805-FP.c
Line	235	238
Object	name	name

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c  
Method static int newupvalue (FuncState \*fs, TString \*name, expdesc \*v) {

```
....
235.     f->upvalues[oldsize++].name = NULL;
....
238.     f->upvalues[fs->nups].name = name;
```

#### Use of Zero Initialized Pointer\Path 45:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=133">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=133</a>
Status	New

The variable declared in prev at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 1488 is not initialized when it is used by prev at libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c in line 1147.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c	libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c
Line	1494	1152
Object	prev	prev

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c  
Method static void exprstat (LexState \*ls) {

```
....
1494.     v.prev = NULL;
```

File Name libretro@@RetroArch-v1.9.11-CVE-2022-28805-FP.c  
Method static void assignment (LexState \*ls, struct LHS\_assign \*lh, int nvars) {

```
....
1152.     nv.prev = lh;
```

#### Use of Zero Initialized Pointer\Path 46:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=133">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=133</a>

[PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=134](http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=134)

Status New

The variable declared in varname at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 161 is not initialized when it is used by varname at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 161.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c
Line	168	169
Object	varname	varname

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c

Method static int registerlocalvar (LexState \*ls, TString \*varname) {

```
....
168.      f->locvars[oldsize++].varname = NULL;
169.      f->locvars[fs->nlocvars].varname = varname;
```

#### Use of Zero Initialized Pointer\Path 47:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=135>

Status New

The variable declared in name at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 228 is not initialized when it is used by name at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 228.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c
Line	235	238
Object	name	name

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c

Method static int newupvalue (FuncState \*fs, TString \*name, expdesc \*v) {

```
....
235.      f->upvalues[oldsize++].name = NULL;
....
238.      f->upvalues[fs->nups].name = name;
```

#### Use of Zero Initialized Pointer\Path 48:

Severity Medium

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=136">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=136</a>
Status	New

The variable declared in prev at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 1488 is not initialized when it is used by prev at libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c in line 1147.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c	libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c
Line	1494	1152
Object	prev	prev

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c  
Method static void exprstat (LexState \*ls) {

```
....
1494.      v.prev = NULL;
```



File Name libretro@@RetroArch-v1.9.6-CVE-2022-28805-FP.c  
Method static void assignment (LexState \*ls, struct LHS\_assign \*lh, int nvars) {

```
....
1152.      nv.prev = lh;
```

#### Use of Zero Initialized Pointer\Path 49:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=137">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=137</a>
Status	New

The variable declared in fbo at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 318 is not initialized when it is used by driverdata at libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c in line 318.

	Source	Destination
File	libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c	libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c
Line	362	403
Object	fbo	driverdata

#### Code Snippet

File Name libSDL-org@@SDL-2.0.22-RC1-CVE-2022-4743-TP.c  
Method GLES\_CreateTexture(SDL\_Renderer \* renderer, SDL\_Texture \* texture)



```
....
362.          data->fbo = NULL;
....
403.          texture->driverdata = data;
```

### Use of Zero Initialized Pointer\Path 50:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=138">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=138</a>
Status	New

The variable declared in fbo at libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 308 is not initialized when it is used by driverdata at libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c in line 308.

	Source	Destination
File	libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c	libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c
Line	352	393
Object	fbo	driverdata

### Code Snippet

File Name libSDL-org@@SDL-prerelease-2.23.2-CVE-2022-4743-TP.c  
 Method GLES\_CreateTexture(SDL\_Renderer \* renderer, SDL\_Texture \* texture)

```
....
352.          data->fbo = NULL;
....
393.          texture->driverdata = data;
```

## Dangerous Functions

Query Path:

CPP\Cx\CPP Medium Threat\Dangerous Functions Version:1

### Categories

OWASP Top 10 2013: A9-Using Components with Known Vulnerabilities  
 OWASP Top 10 2017: A9-Using Components with Known Vulnerabilities

### Description

### Dangerous Functions\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=32">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=32</a>
Status	New

The dangerous function, memcpy, was found in use at line 343 in libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	356	356
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method static int read\_buf(z\_stream strm, Bytef \*buf, unsigned size)

```
....  
356.      memcpy(buf, strm->next_in, len);
```

#### Dangerous Functions\Path 2:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=33>

Status New

The dangerous function, memcpy, was found in use at line 380 in libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	410	410
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method static void fill\_window(deflate\_state \*s)

```
....  
410.      memcpy(s->window, s->window+wsiz, (unsigned)wsiz);
```

#### Dangerous Functions\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=34>

Status New

The dangerous function, memcpy, was found in use at line 826 in libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	837	837
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method static void flush\_pending(z\_streamp strm)

```
....  
837.      memcpy(strm->next_out, s->pending_out, len);
```

#### Dangerous Functions\Path 4:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=35>

Status New

The dangerous function, memcpy, was found in use at line 227 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	234	234
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....  
234.      memcpy(attachments[attachments_size].data, data, size);
```

#### Dangerous Functions\Path 5:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=36>

Status New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	850	850
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
.....  
850.                memcpy(data, src, width);
```

#### Dangerous Functions\Path 6:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=37>

Status New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	936	936
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
.....  
936.                memcpy(data, src, width);
```

#### Dangerous Functions\Path 7:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=37>

[033&pathid=38](#)

Status New

The dangerous function, memcpy, was found in use at line 1214 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	1273	1273
Object	memcpy	memcpy

## Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method static bool open\_codecs(void)

```
....
1273.          memcpy(ass_extra_data[subtitle_streams_num],
(*s)->extradata, size);
```

**Dangerous Functions\Path 8:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=39>

Status New

The dangerous function, memcpy, was found in use at line 227 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	234	234
Object	memcpy	memcpy

## Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....
234.      memcpy(attachments[attachments_size].data, data, size);
```

**Dangerous Functions\Path 9:**

Severity Medium

Result State To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=40">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=40</a>
Status	New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	850	850
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
850.                memcpy(data, src, width);
```

#### Dangerous Functions\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=41">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=41</a>
Status	New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	936	936
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
936.                memcpy(data, src, width);
```

#### Dangerous Functions\Path 11:

Severity	Medium
----------	--------

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=42">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=42</a>
Status	New

The dangerous function, memcpy, was found in use at line 1214 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	1273	1273
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static bool open\_codecs(void)

```
....  
1273.                memcpy(ass_extra_data[subtitle_streams_num],  
(*s)->extradata, size);
```

#### Dangerous Functions\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=43">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=43</a>
Status	New

The dangerous function, memcpy, was found in use at line 343 in libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	356	356
Object	memcpy	memcpy

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c  
Method static int read\_buf(z\_stream strm, Bytef \*buf, unsigned size)

```
....  
356.    memcpy(buf, strm->next_in, len);
```

**Dangerous Functions\Path 13:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=44">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=44</a>
Status	New

The dangerous function, memcpy, was found in use at line 380 in libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	410	410
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c  
Method static void fill\_window(deflate\_state \*s)

```
....  
410.          memcpy(s->window, s->window+wsiz, (unsigned)wsiz);
```

**Dangerous Functions\Path 14:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=45">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=45</a>
Status	New

The dangerous function, memcpy, was found in use at line 826 in libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	837	837
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c  
Method static void flush\_pending(z\_stream strm)

```
....  
837.          memcpy(strm->next_out, s->pending_out, len);
```



**Dangerous Functions\Path 15:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=46">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=46</a>
Status	New

The dangerous function, memcpy, was found in use at line 227 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	234	234
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....  
234.     memcpy(attachments[attachments_size].data, data, size);
```

**Dangerous Functions\Path 16:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=47">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=47</a>
Status	New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	850	850
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
850.                memcpy(data, src, width);
```

**Dangerous Functions\Path 17:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=48">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=48</a>
Status	New

The dangerous function, memcpy, was found in use at line 607 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	936	936
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
936.                memcpy(data, src, width);
```

**Dangerous Functions\Path 18:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=49">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=49</a>
Status	New

The dangerous function, memcpy, was found in use at line 1214 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	1273	1273
Object	memcpy	memcpy

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Method static bool open\_codecs(void)

```
....  
1273.                memcpy(ass_extra_data[subtitle_streams_num],  
(*s)->extradata, size);
```

### Dangerous Functions\Path 19:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=50">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=50</a>
Status	New

The dangerous function, memcpy, was found in use at line 42 in llvm@@llvm-project-llvmorg-10.0.0-rc4-CVE-2022-32234-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	llvm@@llvm-project-llvmorg-10.0.0-rc4-CVE-2022-32234-TP.c	llvm@@llvm-project-llvmorg-10.0.0-rc4-CVE-2022-32234-TP.c
Line	57	57
Object	memcpy	memcpy

### Code Snippet

File Name llvm@@llvm-project-llvmorg-10.0.0-rc4-CVE-2022-32234-TP.c  
Method void SmallVectorBase::grow\_pod(void \*FirstEl, size\_t MinCapacity,

```
....  
57.                memcpy(NewElts, this->BeginX, size() * TSize);
```

### Dangerous Functions\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=51">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=51</a>
Status	New

The dangerous function, memcpy, was found in use at line 42 in llvm@@llvm-project-llvmorg-10.0.1-rc2-CVE-2022-32234-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	llvm@@llvm-project-llvmorg-10.0.1-rc2-CVE-2022-32234-TP.c	llvm@@llvm-project-llvmorg-10.0.1-rc2-CVE-2022-32234-TP.c
Line	57	57
Object	memcpy	memcpy

**Code Snippet**

File Name      llvm@@llvm-project-llvmorg-10.0.1-rc2-CVE-2022-32234-TP.c  
Method          void SmallVectorBase::grow\_pod(void \*FirstEl, size\_t MinCapacity,

```
....  
57.            memcpy(NewElts, this->BeginX, size() * TSize);
```

**Dangerous Functions\Path 21:**

Severity          Medium  
Result State      To Verify  
Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=52>  
Status            New

The dangerous function, sscanf, was found in use at line 380 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	413	413
Object	sscanf	sscanf

**Code Snippet**

File Name      libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method          static void check\_variables(bool firststart)

```
....  
413.            if (sscanf(fft_var.value, "%ux%u", &w, &h) == 2)
```

**Dangerous Functions\Path 22:**

Severity          Medium  
Result State      To Verify  
Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=53>  
Status            New

The dangerous function, sscanf, was found in use at line 380 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	413	413
Object	sscanf	sscanf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void check\_variables(bool firststart)

```
....  
413.          if (sscanf(fft_var.value, "%ux%u", &w, &h) == 2)
```

**Dangerous Functions\Path 23:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=54>  
Status New

The dangerous function, sscanf, was found in use at line 380 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	413	413
Object	sscanf	sscanf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void check\_variables(bool firststart)

```
....  
413.          if (sscanf(fft_var.value, "%ux%u", &w, &h) == 2)
```

**Dangerous Functions\Path 24:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=55>  
Status New

The dangerous function, strlen, was found in use at line 1709 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	1902	1902

Object	strlen	strlen
--------	--------	--------

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method static void decode\_thread(void \*data)

```
....  
1902.                                sub.rects[i]->ass, strlen(sub.rects[i]-  
>ass));
```

#### Dangerous Functions\Path 25:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=56>

Status New

The dangerous function, strlen, was found in use at line 1709 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	1902	1902
Object	strlen	strlen

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Method static void decode\_thread(void \*data)

```
....  
1902.                                sub.rects[i]->ass, strlen(sub.rects[i]-  
>ass));
```

#### Dangerous Functions\Path 26:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=57>

Status New

The dangerous function, strlen, was found in use at line 1709 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-	libretro@@RetroArch-v1.9.6-CVE-2024-

	23775-TP.c	23775-TP.c
Line	1902	1902
Object	strlen	strlen

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void decode\_thread(void \*data)

```
....  
1902.                                sub.rects[i]->ass, strlen(sub.rects[i]-  
>ass));
```

#### Dangerous Functions\Path 27:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=58>  
Status New

The dangerous function, strlen, was found in use at line 640 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	849	849
Object	strlen	strlen

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method tiffcp(TIFF\* in, TIFF\* out)

```
....  
849.                                int inknameslen = strlen(inknames) + 1;
```

#### Dangerous Functions\Path 28:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=59>  
Status New

The dangerous function, strlen, was found in use at line 640 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	854	854
Object	strlen	strlen

#### Code Snippet

File Name      libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method          tiffcp(TIFF\* in, TIFF\* out)

```
....  
854.                                     inknameslen += (strlen(cp)  
+ 1);
```

#### Dangerous Functions\Path 29:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=60">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=60</a>
Status	New

The dangerous function, strlen, was found in use at line 295 in lua@@lua-v5.4.0-CVE-2021-3520-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2021-3520-FP.c	lua@@lua-v5.4.0-CVE-2021-3520-FP.c
Line	308	308
Object	strlen	strlen

#### Code Snippet

File Name      lua@@lua-v5.4.0-CVE-2021-3520-FP.c  
Method          static void setpath (lua\_State \*L, const char \*fieldname,

```
....  
308.          size_t len = strlen(path);
```

#### Dangerous Functions\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=61">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=61</a>
Status	New

The dangerous function, vsnprintf, was found in use at line 214 in libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.



	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	221	221
Object	vsnprintf	vsnprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method static void ass\_msg\_cb(int level, const char \*fmt, va\_list args, void \*data)

```
....  
221.          vsnprintf(buffer, sizeof(buffer), fmt, args);
```

#### Dangerous Functions\Path 31:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=62>

Status New

The dangerous function, vsnprintf, was found in use at line 214 in libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	221	221
Object	vsnprintf	vsnprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c

Method static void ass\_msg\_cb(int level, const char \*fmt, va\_list args, void \*data)

```
....  
221.          vsnprintf(buffer, sizeof(buffer), fmt, args);
```

#### Dangerous Functions\Path 32:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=63>

Status New

The dangerous function, vsnprintf, was found in use at line 214 in libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	221	221
Object	vsnprintf	vsnprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Method static void ass\_msg\_cb(int level, const char \*fmt, va\_list args, void \*data)

```
....  
221.          vsnprintf(buffer, sizeof(buffer), fmt, args);
```

### Dangerous Functions\Path 33:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=64>

Status New

The dangerous function, atoi, was found in use at line 206 in libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	215	215
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c

Method processCompressOptions(char\* opt)

```
....  
215.          quality = atoi(cp+1);
```

### Dangerous Functions\Path 34:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=65>

Status New

The dangerous function, atoi, was found in use at line 206 in libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	227	227
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c  
Method processCompressOptions(char\* opt)

```
....  
227.                                defpredicator = atoi(cp+1);
```

#### Dangerous Functions\Path 35:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=66">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=66</a>
Status	New

The dangerous function, atoi, was found in use at line 206 in libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	232	232
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c  
Method processCompressOptions(char\* opt)

```
....  
232.                                defpredicator = atoi(cp+1);
```

#### Dangerous Functions\Path 36:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=67">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=67</a>
Status	New

The dangerous function, atoi, was found in use at line 356 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	362	362
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method processZIPOptions(char\* cp)

```
....  
362.                                defpredictor = atoi(cp);
```

#### Dangerous Functions\Path 37:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=68">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=68</a>
Status	New

The dangerous function, atoi, was found in use at line 356 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	364	364
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method processZIPOptions(char\* cp)

```
....  
364.                                defpreset = atoi(++cp);
```

#### Dangerous Functions\Path 38:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=69">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=69</a>
Status	New

The dangerous function, atoi, was found in use at line 356 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	366	366
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method processZIOOptions(char\* cp)

```
....  
366.                                subcodec = atoi(++cp);
```

#### Dangerous Functions\Path 39:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=70">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=70</a>
Status	New

The dangerous function, atoi, was found in use at line 394 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	407	407
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method processCompressOptions(char\* opt)

```
....  
407.                                quality = atoi(cp+1);
```

#### Dangerous Functions\Path 40:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=71">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=71</a>
Status	New

The dangerous function, atoi, was found in use at line 394 in libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	423	423
Object	atoi	atoi

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method processCompressOptions(char\* opt)

```
....  
423.                                defpredictor = atoi(cp+1);
```

### Dangerous Functions\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=72">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=72</a>
Status	New

The dangerous function, realloc, was found in use at line 741 in LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c
Line	756	756
Object	realloc	realloc

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c  
Method rfbBool sraRgnIteratorNext(sraRectangleIterator\* i,sraRect\* r)

```
....  
756.                i->sPtrs = (sraSpan**) realloc(i->sPtrs, sizeof(sraSpan*)*i->ptrSize);
```

### Dangerous Functions\Path 42:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=73">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=73</a>
Status	New

The dangerous function, realloc, was found in use at line 741 in LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c
Line	756	756
Object	realloc	realloc

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c

Method rfbBool sraRgnIteratorNext(sraRectangleIterator\* i,sraRect\* r)

```
....  
756.          i->sPtrs = (sraSpan**) realloc(i->sPtrs, sizeof(sraSpan*)*i->ptrSize);
```

#### Dangerous Functions\Path 43:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=74>

Status New

The dangerous function, atoi, was found in use at line 32 in litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c
Line	38	38
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c

Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
38.          if (env && atoi(env))
```

#### Dangerous Functions\Path 44:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=75>

Status New

The dangerous function, atoi, was found in use at line 32 in litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c
Line	38	38
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c

Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
38.      if (env && atoi(env))
```

#### Dangerous Functions\Path 45:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=76>

Status New

The dangerous function, atoi, was found in use at line 37 in litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c
Line	43	43
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c

Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
43.      if (env && atoi(env))
```

#### Dangerous Functions\Path 46:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=76>



Status	<a href="#">033&amp;pathid=77</a> New
--------	--

The dangerous function, atoi, was found in use at line 39 in litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c
Line	45	45
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....
45.      if (env && atoi(env))
```

#### Dangerous Functions\Path 47:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=78">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=78</a>
Status	New

The dangerous function, atoi, was found in use at line 39 in litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c
Line	45	45
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....
45.      if (env && atoi(env))
```

#### Dangerous Functions\Path 48:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=78">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=78</a>

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=79">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=79</a>
Status	New

The dangerous function, atoi, was found in use at line 39 in litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c
Line	45	45
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....
45.      if (env && atoi(env))
```

### Dangerous Functions\Path 49:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=80">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=80</a>
Status	New

The dangerous function, atoi, was found in use at line 39 in litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c
Line	45	45
Object	atoi	atoi

#### Code Snippet

File Name litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....
45.      if (env && atoi(env))
```

## Buffer Overflow boundcpy WrongSizeParam

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow boundcpy WrongSizeParam Version:1

## Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow boundcpy WrongSizeParam\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=8">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=8</a>
Status	New

The size of the buffer used by `elf_parse` in `Elf_Binary_t`, at line 62 of `lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `elf_parse` passes to `Elf_Binary_t`, at line 62 of `lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c</code>	<code>lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c</code>
Line	70	70
Object	<code>Elf_Binary_t</code>	<code>Elf_Binary_t</code>

#### Code Snippet

File Name `lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c`  
Method `Elf_Binary_t* elf_parse(const char *file) {`

```
....
70.    memset(c_binary, 0, sizeof(Elf_Binary_t));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=9">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=9</a>
Status	New

The size of the buffer used by `read_buf` in `len`, at line 343 of `libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `read_buf` passes to `len`, at line 343 of `libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c</code>	<code>libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c</code>
Line	356	356
Object	<code>len</code>	<code>len</code>

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c  
Method static int read\_buf(z\_streamp strm, Bytef \*buf, unsigned size)

```
....  
356.      memcpy(buf, strm->next_in, len);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 3:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=10>  
Status New

The size of the buffer used by flush\_pending in len, at line 826 of libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that flush\_pending passes to len, at line 826 of libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	837	837
Object	len	len

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c  
Method static void flush\_pending(z\_streamp strm)

```
....  
837.      memcpy(strm->next_out, s->pending_out, len);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 4:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=11>  
Status New

The size of the buffer used by append\_attachment in size, at line 227 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that append\_attachment passes to size, at line 227 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	234	234
Object	size	size

**Code Snippet**

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....  
234.     memcpy(attachments[attachments_size].data, data, size);
```

**Buffer Overflow boundcpy WrongSizeParam\Path 5:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=12>

Status New

The size of the buffer used by CORE\_PREFIX in width, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that CORE\_PREFIX passes to width, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	850	850
Object	width	width

**Code Snippet**

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....  
850.     memcpy(data, src, width);
```

**Buffer Overflow boundcpy WrongSizeParam\Path 6:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=13>

Status New

The size of the buffer used by CORE\_PREFIX in width, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that CORE\_PREFIX passes to width, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	936	936
Object	width	width

**Code Snippet**

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
936.                memcpy(data, src, width);
```

**Buffer Overflow boundcpy WrongSizeParam\Path 7:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=14>  
Status New

The size of the buffer used by `append_attachment` in `size`, at line 227 of `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `append_attachment` passes to `size`, at line 227 of `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c`, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	234	234
Object	size	size

**Code Snippet**

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....  
234.                memcpy(attachments[attachments_size].data, data, size);
```

**Buffer Overflow boundcpy WrongSizeParam\Path 8:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=15>  
Status New

The size of the buffer used by `CORE_PREFIX` in `width`, at line 607 of `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `CORE_PREFIX` passes to `width`, at line 607 of `libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c`, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	850	850

Object	width	width
--------	-------	-------

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
850.                memcpy(data, src, width);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 9:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=16>  
Status New

The size of the buffer used by CORE\_PREFIX in width, at line 607 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that CORE\_PREFIX passes to width, at line 607 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	936	936
Object	width	width

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
936.                memcpy(data, src, width);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 10:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=17>  
Status New

The size of the buffer used by read\_buf in len, at line 343 of libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that read\_buf passes to len, at line 343 of libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Line	356	356
Object	len	len

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method static int read\_buf(z\_streamp strm, Bytef \*buf, unsigned size)

```
....  
356.      memcpy(buf, strm->next_in, len);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 11:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=18>

Status New

The size of the buffer used by flush\_pending in len, at line 826 of libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that flush\_pending passes to len, at line 826 of libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	837	837
Object	len	len

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method static void flush\_pending(z\_streamp strm)

```
....  
837.      memcpy(strm->next_out, s->pending_out, len);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 12:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=19>

Status New

The size of the buffer used by append\_attachment in size, at line 227 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that append\_attachment passes to size, at line 227 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-	libretro@@RetroArch-v1.9.6-CVE-2024-



	23775-TP.c	23775-TP.c
Line	234	234
Object	size	size

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Method static void append\_attachment(const uint8\_t \*data, size\_t size)

```
....  
234.      memcpy(attachments[attachments_size].data, data, size);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 13:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=20>

Status New

The size of the buffer used by CORE\_PREFIX in width, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that CORE\_PREFIX passes to width, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, to overwrite the target buffer.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	850	850
Object	width	width

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....  
850.      memcpy(data, src, width);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 14:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=21>

Status New

The size of the buffer used by CORE\_PREFIX in width, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that CORE\_PREFIX passes to width, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c, to overwrite the target buffer.

Source	Destination
--------	-------------

File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	936	936
Object	width	width

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....
936.                memcpy(data, src, width);
```

## Memory Leak

Query Path:

CPP\Cx\CPP Medium Threat\Memory Leak Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

### Description

#### Memory Leak\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=81">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=81</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	306	306
Object	window	window

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c  
Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
306.        s->window        = (Bytef*)calloc(s->w_size, 2*sizeof(Byte));
```

#### Memory Leak\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=82">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=82</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	307	307
Object	prev	prev

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream\* strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
307.      s->prev      = (Posf*) calloc(s->w_size, sizeof(Pos));
```

#### Memory Leak\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=83>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	308	308
Object	head	head

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream\* strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
308.      s->head      = (Posf*) calloc(s->hash_size, sizeof(Pos));
```

#### Memory Leak\Path 4:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=84>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Line	314	314
Object	overlay	overlay

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
314.      overlay      = (ushf *)calloc(s->lit_bufsize, sizeof(ush)+2);
```

#### Memory Leak\Path 5:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=85>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	306	306
Object	window	window

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
306.      s->window      = (Bytef*)calloc(s->w_size, 2*sizeof(Byte));
```

#### Memory Leak\Path 6:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=86>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	307	307
Object	prev	prev

## Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
307.      s->prev      = (Posf*) calloc(s->w_size, sizeof(Pos));
```

**Memory Leak\Path 7:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=87>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	308	308
Object	head	head

## Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
308.      s->head      = (Posf*) calloc(s->hash_size, sizeof(Pos));
```

**Memory Leak\Path 8:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=88>

Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	314	314
Object	overlay	overlay

## Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
314.      overlay      = (ushf *)calloc(s->lit_bufsize, sizeof(ush)+2);
```

## Integer Overflow

Query Path:

CPP\Cx\CPP Integer Overflow\Integer Overflow Version:0

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows

FISMA 2014: System And Information Integrity

NIST SP 800-53: SI-10 Information Input Validation (P1)

### Description

#### Integer Overflow\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=25">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=25</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 500 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	543	543
Object	AssignExpr	AssignExpr

### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....
543.      seek_frames_capped = (int)(seek_step_time *
media.interpolate_fps);
```

#### Integer Overflow\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=26">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=26</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 500 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

Source	Destination
--------	-------------

File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	543	543
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....  
543.                seek_frames_capped = (int)(seek_step_time *  
media.interpolate_fps);
```

#### Integer Overflow\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=27">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=27</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 500 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	543	543
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....  
543.                seek_frames_capped = (int)(seek_step_time *  
media.interpolate_fps);
```

#### Integer Overflow\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=28">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=28</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 493 of libsdll-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c	libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c
Line	554	554
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c

Method LZWDecodeCompat(TIFF\* tif, tidata\_t op0, tsize\_t occ0, tsample\_t s)

```
....  
554.                NextCode(tif, sp, bp, code, GetNextCodeCompat);
```

#### Integer Overflow\Path 5:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=29>

Status New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 493 of libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c	libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c
Line	562	562
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libsdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c

Method LZWDecodeCompat(TIFF\* tif, tidata\_t op0, tsize\_t occ0, tsample\_t s)

```
....  
562.                NextCode(tif, sp, bp, code, GetNextCodeCompat);
```

#### Integer Overflow\Path 6:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=30>

Status New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 600 of libsdl-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.



	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c
Line	674	674
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c  
Method LZWDecodeCompat(TIFF\* tif, uint8\* op0, tmsize\_t occ0, uint16 s)

```
....
674.                NextCode(tif, sp, bp, code, GetNextCodeCompat);
```

### Integer Overflow\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=31">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=31</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 600 of libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c
Line	685	685
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-2731-TP.c  
Method LZWDecodeCompat(TIFF\* tif, uint8\* op0, tmsize\_t occ0, uint16 s)

```
....
685.                NextCode(tif, sp, bp, code,
GetNextCodeCompat);
```

## Divide By Zero

Query Path:

CPP\Cx\CPP Medium Threat\Divide By Zero Version:1

[Description](#)

### Divide By Zero\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=3">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=3</a>
Status	New

The application performs an illegal operation in uv\_\_idna\_toascii\_label, in libuv@@libuv-v1.35.0-CVE-2021-22918-TP.c. In line 102, the program attempts to divide by BinaryExpr, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input BinaryExpr in uv\_\_idna\_toascii\_label of libuv@@libuv-v1.35.0-CVE-2021-22918-TP.c, at line 102.

	Source	Destination
File	libuv@@libuv-v1.35.0-CVE-2021-22918-TP.c	libuv@@libuv-v1.35.0-CVE-2021-22918-TP.c
Line	236	236
Object	BinaryExpr	BinaryExpr

#### Code Snippet

File Name libuv@@libuv-v1.35.0-CVE-2021-22918-TP.c

Method static int uv\_\_idna\_toascii\_label(const char\* s, const char\* se,

```
....  
236.          bias += 36 * delta / (delta + 38);
```

#### Divide By Zero\Path 2:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=4>

Status New

The application performs an illegal operation in uv\_\_idna\_toascii\_label, in libuv@@libuv-v1.38.1-CVE-2021-22918-TP.c. In line 102, the program attempts to divide by BinaryExpr, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input BinaryExpr in uv\_\_idna\_toascii\_label of libuv@@libuv-v1.38.1-CVE-2021-22918-TP.c, at line 102.

	Source	Destination
File	libuv@@libuv-v1.38.1-CVE-2021-22918-TP.c	libuv@@libuv-v1.38.1-CVE-2021-22918-TP.c
Line	236	236
Object	BinaryExpr	BinaryExpr

#### Code Snippet

File Name libuv@@libuv-v1.38.1-CVE-2021-22918-TP.c

Method static int uv\_\_idna\_toascii\_label(const char\* s, const char\* se,

```
....  
236.          bias += 36 * delta / (delta + 38);
```

#### Divide By Zero\Path 3:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=4>

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=5">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=5</a>
Status	New

The application performs an illegal operation in uv\_\_idna\_toascii\_label, in libuv@@libuv-v1.41.0-CVE-2021-22918-TP.c. In line 102, the program attempts to divide by BinaryExpr, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input BinaryExpr in uv\_\_idna\_toascii\_label of libuv@@libuv-v1.41.0-CVE-2021-22918-TP.c, at line 102.

	Source	Destination
File	libuv@@libuv-v1.41.0-CVE-2021-22918-TP.c	libuv@@libuv-v1.41.0-CVE-2021-22918-TP.c
Line	236	236
Object	BinaryExpr	BinaryExpr

#### Code Snippet

File Name libuv@@libuv-v1.41.0-CVE-2021-22918-TP.c  
 Method static int uv\_\_idna\_toascii\_label(const char\* s, const char\* se,

```
....
236.         bias += 36 * delta / (delta + 38);
```

#### Divide By Zero\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=6">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=6</a>
Status	New

The application performs an illegal operation in LZWEncode, in libstdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c. In line 721, the program attempts to divide by outcount, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input outcount in LZWEncode of libstdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c, at line 721.

	Source	Destination
File	libstdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c	libstdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c
Line	844	844
Object	outcount	outcount

#### Code Snippet

File Name libstdl-org@@libtiff-v3.5.1-CVE-2023-2731-TP.c  
 Method LZWEncode(TIFF\* tif, tidata\_t bp, tsize\_t cc, tsample\_t s)

```
....
844.         CALCRATIO(sp, rat);
```

#### Divide By Zero\Path 5:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=7">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=7</a>
Status	New

The application performs an illegal operation in LZWEncode, in libsd-@libtiff-v4.2.0-CVE-2023-2731-TP.c. In line 899, the program attempts to divide by outcount, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input outcount in LZWEncode of libsd-@libtiff-v4.2.0-CVE-2023-2731-TP.c, at line 899.

	Source	Destination
File	libsd-@libtiff-v4.2.0-CVE-2023-2731-TP.c	libsd-@libtiff-v4.2.0-CVE-2023-2731-TP.c
Line	1028	1028
Object	outcount	outcount

#### Code Snippet

File Name libsd-@libtiff-v4.2.0-CVE-2023-2731-TP.c  
Method LZWEncode(TIFF\* tif, uint8\* bp, tmsize\_t cc, uint16 s)

```
....  
1028.                                CALCRATIO(sp, rat);
```

## Float Overflow

Query Path:

CPP\Cx\CPP Integer Overflow\Float Overflow Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
FISMA 2014: System And Information Integrity  
NIST SP 800-53: SI-10 Information Input Validation (P1)

### Description

#### Float Overflow\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=22</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	873	873

Object	AssignExpr	AssignExpr
--------	------------	------------

#### Code Snippet

File Name libreto@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
873.          mix_factor = (min_pts - frames[0].pts) / (frames[1].pts -  
frames[0].pts);
```

#### Float Overflow\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=23">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=23</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 607 of libreto@@RetroArch-v1.9.1-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libreto@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libreto@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	873	873
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libreto@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
873.          mix_factor = (min_pts - frames[0].pts) / (frames[1].pts -  
frames[0].pts);
```

#### Float Overflow\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=24">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=24</a>
Status	New

A variable of a larger data type, AssignExpr, is being assigned to a smaller data type, in 607 of libreto@@RetroArch-v1.9.6-CVE-2024-23775-TP.c. This will cause a loss of data, often the significant bits of a numerical value or the sign bit.

	Source	Destination
File	libreto@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libreto@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Line	873	873
Object	AssignExpr	AssignExpr

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c

Method void CORE\_PREFIX(retro\_run)(void)

```
....  
873.          mix_factor = (min_pts - frames[0].pts) / (frames[1].pts -  
frames[0].pts);
```

## Improper Resource Access Authorization

Query Path:

CPP\Cx\CPP Low Visibility\Improper Resource Access Authorization Version:1

### Categories

FISMA 2014: Identification And Authentication

NIST SP 800-53: AC-3 Access Enforcement (P1)

OWASP Top 10 2017: A2-Broken Authentication

### Description

#### Improper Resource Access Authorization\Path 1:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=159>

Status New

	Source	Destination
File	libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	1180	1180
Object	fprintf	fprintf

#### Code Snippet

File Name libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c

Method pickCopyFunc(TIFF\* in, TIFF\* out, uint16 bitspersample, uint16 samplesperpixel)

```
....  
1180.          fprintf(stderr,
```

#### Improper Resource Access Authorization\Path 2:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=160>

Status New

	Source	Destination
File	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	1263	1263
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c

Method pickCopyFunc(TIFF\* in, TIFF\* out, uint16 bitspersample, uint16 samplesperpixel)

```
....  
1263.          fprintf(stderr, "tiffcp: %s: Don't know how to copy/convert  
image.\n",
```

#### Improper Resource Access Authorization\Path 3:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=161>

Status New

	Source	Destination
File	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	290	290
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c

Method usage(void)

```
....  
290.          fprintf(stderr, "%s\n", stuff[i]);
```

#### Improper Resource Access Authorization\Path 4:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=162>

Status New

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	1886	1886

Object	fprintf	fprintf
--------	---------	---------

**Code Snippet**

File Name libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c

Method pickCopyFunc(TIFF\* in, TIFF\* out, uint16 bitspersample, uint16 samplesperpixel)

```
....  
1886.                fprintf(stderr,
```

**Improper Resource Access Authorization\Path 5:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=163>

Status New

	Source	Destination
File	libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	1900	1900
Object	fprintf	fprintf

**Code Snippet**

File Name libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c

Method pickCopyFunc(TIFF\* in, TIFF\* out, uint16 bitspersample, uint16 samplesperpixel)

```
....  
1900.                fprintf(stderr,
```

**Improper Resource Access Authorization\Path 6:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=164>

Status New

	Source	Destination
File	libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	1978	1978
Object	fprintf	fprintf

**Code Snippet**

File Name libsd1-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c

Method pickCopyFunc(TIFF\* in, TIFF\* out, uint16 bitspersample, uint16 samplesperpixel)



```
.....
1978.          fprintf(stderr, "tiffcp: %s: Don't know how to copy/convert
image.\n",
```

#### Improper Resource Access Authorization\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=165">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=165</a>
Status	New

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	119	119
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method static void\* limitMalloc(tmsize\_t s)

```
.....
119.          fprintf(stderr, "                                use -m option to
change limit.\n");
```

#### Improper Resource Access Authorization\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=166">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=166</a>
Status	New

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	142	142
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method static int nextSrcImage (TIFF \*tif, char \*\*imageSpec)

```
.....
142.          fprintf (stderr,
```

**Improper Resource Access Authorization\Path 9:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=167">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=167</a>
Status	New

	Source	Destination
File	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	149	149
Object	fprintf	fprintf

**Code Snippet**

File Name libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method static int nextSrcImage (TIFF \*tif, char \*\*imageSpec)

```
....  
149.                fprintf (stderr, "%s%c%d not found!\n",
```

**Improper Resource Access Authorization\Path 10:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=168">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=168</a>
Status	New

	Source	Destination
File	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	520	520
Object	fprintf	fprintf

**Code Snippet**

File Name libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method usage(int code)

```
....  
520.                fprintf(out, "%s\n\n", TIFFGetVersion());
```

**Improper Resource Access Authorization\Path 11:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=169">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=169</a>
Status	New

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	522	522
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method usage(int code)

```
....  
522.                fprintf(out, "%s\n", stuff[i]);
```

### Improper Resource Access Authorization\Path 12:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=170>  
Status New

	Source	Destination
File	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	668	668
Object	fprintf	fprintf

#### Code Snippet

File Name libSDL-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method tiffcp(TIFF\* in, TIFF\* out)

```
....  
668.                fprintf(stderr, "tiffcp: %s: Can't copy/convert  
subsampled image.\n",
```

### Improper Resource Access Authorization\Path 13:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=171>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Line	145	145
Object	fprintf	fprintf

## Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method int main(int argc, char \*\*argv) {

```
....  
145.      fprintf(stderr, "Usage: %s <MachO binary>\n", argv[0]);
```

**Improper Resource Access Authorization\Path 14:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=172>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	9	9
Object	fprintf	fprintf

## Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
9.      fprintf(stdout, "Binary Name: %s\n", binary->name);
```

**Improper Resource Access Authorization\Path 15:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=173>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	12	12
Object	fprintf	fprintf

## Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
12.    fprintf(stdout, "Header\n");
```

#### Improper Resource Access Authorization\Path 16:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=174>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	13	13
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
13.    fprintf(stdout, "=====\n");
```

#### Improper Resource Access Authorization\Path 17:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=175>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	15	15
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
15.    fprintf(stdout, "CPU Type: %s\n",  
CPU_TYPES_to_string(header.cpu_type));
```

**Improper Resource Access Authorization\Path 18:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=176">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=176</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	17	17
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
17.     fprintf(stdout, "File type: %s\n",  
FILE_TYPES_to_string(header.file_type));
```

**Improper Resource Access Authorization\Path 19:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=177">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=177</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	23	23
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
23.     fprintf(stdout, "Commands\n");
```

**Improper Resource Access Authorization\Path 20:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=178">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=178</a>

Status	New
--------	-----

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	24	24
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
24.     fprintf(stdout, "=====\n");
```

### Improper Resource Access Authorization\Path 21:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=179">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=179</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	39	39
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
39.     fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

### Improper Resource Access Authorization\Path 22:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=180">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=180</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Line	44	44
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
44.     fprintf(stdout, "Segments\n");
```

**Improper Resource Access Authorization\Path 23:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=181>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	45	45
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
45.     fprintf(stdout, "=====\n");
```

**Improper Resource Access Authorization\Path 24:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=182>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	72	72
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c



Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
72.      fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

#### Improper Resource Access Authorization\Path 25:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=183>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	78	78
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
78.      fprintf(stdout, "Sections\n");
```

#### Improper Resource Access Authorization\Path 26:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=184>

Status New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	79	79
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
79.      fprintf(stdout, "=====\n");
```

#### Improper Resource Access Authorization\Path 27:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=185">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=185</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	113	113
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
113.      fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

#### Improper Resource Access Authorization\Path 28:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=186">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=186</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	118	118
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
118.      fprintf(stdout, "Symbols\n");
```

#### Improper Resource Access Authorization\Path 29:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=187">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=187</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c
Line	119	119
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.13.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
119.     fprintf(stdout, "=====\n");
```

**Improper Resource Access Authorization\Path 30:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=188>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	145	145
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method int main(int argc, char \*\*argv) {

```
....  
145.     fprintf(stderr, "Usage: %s <MachO binary>\n", argv[0]);
```

**Improper Resource Access Authorization\Path 31:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=189>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	9	9

Object	fprintf	fprintf
--------	---------	---------

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
9.     fprintf(stdout, "Binary Name: %s\n", binary->name);
```

#### Improper Resource Access Authorization\Path 32:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=190>

Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	12	12
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
12.    fprintf(stdout, "Header\n");
```

#### Improper Resource Access Authorization\Path 33:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=191>

Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	13	13
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
13.      fprintf(stdout, "=====\n");
```

### Improper Resource Access Authorization\Path 34:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=192">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=192</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	15	15
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
15.      fprintf(stdout, "CPU Type: %s\n",  
CPU_TYPES_to_string(header.cpu_type));
```

### Improper Resource Access Authorization\Path 35:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=193">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=193</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	17	17
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
17.      fprintf(stdout, "File type: %s\n",  
FILE_TYPES_to_string(header.file_type));
```

**Improper Resource Access Authorization\Path 36:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=194">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=194</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	23	23
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
23.     fprintf(stdout, "Commands\n");
```

**Improper Resource Access Authorization\Path 37:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=195">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=195</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	24	24
Object	fprintf	fprintf

**Code Snippet**

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
24.     fprintf(stdout, "=====\n");
```

**Improper Resource Access Authorization\Path 38:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=196">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=196</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	39	39
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
39.      fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

#### Improper Resource Access Authorization\Path 39:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=197>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	44	44
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
44.      fprintf(stdout, "Segments\n");
```

#### Improper Resource Access Authorization\Path 40:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=198>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	45	45

Object	fprintf	fprintf
--------	---------	---------

## Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
45.     fprintf(stdout, "=====\n");
```

**Improper Resource Access Authorization\Path 41:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=199>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	72	72
Object	fprintf	fprintf

## Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
72.     fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

**Improper Resource Access Authorization\Path 42:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=200>  
Status New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	78	78
Object	fprintf	fprintf

## Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {



```
....  
78.     fprintf(stdout, "Sections\n");
```

#### Improper Resource Access Authorization\Path 43:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=201">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=201</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	79	79
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
79.     fprintf(stdout, "=====\n");
```

#### Improper Resource Access Authorization\Path 44:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=202">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=202</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	113	113
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c  
Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
113.     fprintf(stdout, "content[0..3]: %02x %02x %02x\n",
```

#### Improper Resource Access Authorization\Path 45:

Severity	Low
----------	-----

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=203">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=203</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	118	118
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
118.     fprintf(stdout, "Symbols\n");
```

### Improper Resource Access Authorization\Path 46:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=204">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=204</a>
Status	New

	Source	Destination
File	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c
Line	119	119
Object	fprintf	fprintf

#### Code Snippet

File Name lief-project@@LIEF-0.14.0-CVE-2024-31636-FP.c

Method void print\_binary(Macho\_Binary\_t\* binary) {

```
....  
119.     fprintf(stdout, "=====\n");
```

## Unchecked Return Value

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Return Value Version:1

### Categories

NIST SP 800-53: SI-11 Error Handling (P2)

### Description

#### Unchecked Return Value\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=213">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=213</a>
Status	New

The seek\_frame method calls the snprintf function, at line 500 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	563	563
Object	snprintf	snprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....  
563.      snprintf(msg, sizeof(msg), "%02d:%02d:%02d / %02d:%02d:%02d",
```

#### Unchecked Return Value\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=214">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=214</a>
Status	New

The CORE\_PREFIX method calls the snprintf function, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	692	692
Object	snprintf	snprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
692.      snprintf(msg, sizeof(msg), "Audio Track #%d.",  
audio_streams_ptr);
```

**Unchecked Return Value\Path 3:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=215">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=215</a>
Status	New

The CORE\_PREFIX method calls the sprintf function, at line 607 of libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c
Line	714	714
Object	sprintf	sprintf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.11-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
714.      sprintf(msg, sizeof(msg), "Subtitle Track #%d.",  
subtitle_streams_ptr);
```

**Unchecked Return Value\Path 4:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=216">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=216</a>
Status	New

The seek\_frame method calls the sprintf function, at line 500 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	563	563
Object	sprintf	sprintf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....  
563.      snprintf(msg, sizeof(msg), "%02d:%02d:%02d / %02d:%02d:%02d",
```

#### Unchecked Return Value\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=217">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=217</a>
Status	New

The CORE\_PREFIX method calls the snprintf function, at line 607 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	692	692
Object	snprintf	snprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
692.      snprintf(msg, sizeof(msg), "Audio Track #d.",  
audio_streams_ptr);
```

#### Unchecked Return Value\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=218">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=218</a>
Status	New

The CORE\_PREFIX method calls the snprintf function, at line 607 of libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c
Line	714	714
Object	snprintf	snprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.1-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
714.      snprintf(msg, sizeof(msg), "Subtitle Track #d.",  
subtitle_streams_ptr);
```

#### Unchecked Return Value\Path 7:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=219>  
Status New

The seek\_frame method calls the snprintf function, at line 500 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	563	563
Object	snprintf	snprintf

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method static void seek\_frame(int seek\_frames)

```
....  
563.      snprintf(msg, sizeof(msg), "%02d:%02d:%02d / %02d:%02d:%02d",
```

#### Unchecked Return Value\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=220>  
Status New

The CORE\_PREFIX method calls the snprintf function, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	692	692
Object	snprintf	snprintf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
692.          snprintf(msg, sizeof(msg), "Audio Track #d.",  
audio_streams_ptr);
```

**Unchecked Return Value\Path 9:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=221>  
Status New

The CORE\_PREFIX method calls the snprintf function, at line 607 of libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c	libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c
Line	714	714
Object	snprintf	snprintf

**Code Snippet**

File Name libretro@@RetroArch-v1.9.6-CVE-2024-23775-TP.c  
Method void CORE\_PREFIX(retro\_run)(void)

```
....  
714.          snprintf(msg, sizeof(msg), "Subtitle Track #d.",  
subtitle_streams_ptr);
```

**Unchecked Return Value\Path 10:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=222>  
Status New

The deflateInit2\_ method calls the overlay function, at line 236 of libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Line	314	314
Object	overlay	overlay

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_streamp strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
314.      overlay      = (ushf *)calloc(s->lit_bufsize, sizeof(ush)+2);
```

#### Unchecked Return Value\Path 11:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=223>

Status New

The deflateInit2\_ method calls the overlay function, at line 236 of libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	314	314
Object	overlay	overlay

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_streamp strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....  
314.      overlay      = (ushf *)calloc(s->lit_bufsize, sizeof(ush)+2);
```

#### Unchecked Return Value\Path 12:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=224>

Status New

The elf\_parse method calls the Pointer function, at line 62 of lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.



	Source	Destination
File	lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c	lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c
Line	69	69
Object	Pointer	Pointer

#### Code Snippet

File Name lief-project@@LIEF-0.15.0-CVE-2024-31636-FP.c  
Method Elf\_Binary\_t\* elf\_parse(const char \*file) {

```
....
69.     auto* c_binary =
static_cast<Elf_Binary_t*>(malloc(sizeof(Elf_Binary_t)));
```

## NULL Pointer Dereference

Query Path:

CPP\Cx\CPP Low Visibility\NULL Pointer Dereference Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

OWASP Top 10 2017: A1-Injection

### Description

#### NULL Pointer Dereference\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=233">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=233</a>
Status	New

The variable declared in null at LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c in line 34 is not initialized when it is used by span at LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c in line 81.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c
Line	36	82
Object	null	span

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c  
Method sraSpanCreate(int start, int end, const sraSpanList \*subspan) {

```
....
36.     if (!item) return NULL;
```

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c

Method sraSpanDestroy(sraSpan \*span) {

```
....
82.    if (span->subspan) sraSpanListDestroy(span->subspan);
```

### NULL Pointer Dereference\Path 2:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=234>

Status New

The variable declared in null at LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c in line 34 is not initialized when it is used by span at LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c in line 81.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c
Line	36	82
Object	null	span

### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c

Method sraSpanCreate(int start, int end, const sraSpanList \*subspan) {

```
....
36.    if (!item) return NULL;
```

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c

Method sraSpanDestroy(sraSpan \*span) {

```
....
82.    if (span->subspan) sraSpanListDestroy(span->subspan);
```

### NULL Pointer Dereference\Path 3:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=235>

Status New

The variable declared in null at LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c in line 34 is not initialized when it is used by span at LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c in line 81.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c
Line	36	82
Object	null	span

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c  
Method sraSpanCreate(int start, int end, const sraSpanList \*subspan) {

```
....
36.     if (!item) return NULL;
```

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c  
Method sraSpanDestroy(sraSpan \*span) {

```
....
82.     if (span->subspan) sraSpanListDestroy(span->subspan);
```

#### NULL Pointer Dereference\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=236">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=236</a>
Status	New

The variable declared in null at LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c in line 34 is not initialized when it is used by span at LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c in line 81.

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c
Line	36	82
Object	null	span

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c  
Method sraSpanCreate(int start, int end, const sraSpanList \*subspan) {

```
....
36.     if (!item) return NULL;
```

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c

Method sraSpanDestroy(sraSpan \*span) {

```
....
82.     if (span->subspan) sraSpanListDestroy(span->subspan);
```

### NULL Pointer Dereference\Path 5:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=237>

Status New

The variable declared in null at lua@@lua-v5.4.0-CVE-2022-28805-TP.c in line 1661 is not initialized when it is used by l at lua@@lua-v5.4.0-CVE-2022-28805-TP.c in line 550.

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2022-28805-TP.c	lua@@lua-v5.4.0-CVE-2022-28805-TP.c
Line	1666	553
Object	null	l

### Code Snippet

File Name lua@@lua-v5.4.0-CVE-2022-28805-TP.c

Method static void test\_then\_block (LexState \*ls, int \*escapelist) {

```
....
1666.     TString *jlb = NULL;
```

File Name lua@@lua-v5.4.0-CVE-2022-28805-TP.c

Method static int newlabelentry (LexState \*ls, Labellist \*l, TString \*name,

```
....
553.     luaM_growvector(ls->L, l->arr, n, l->size,
```

### NULL Pointer Dereference\Path 6:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=238>

Status New

The variable declared in 0 at libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c in line 844 is not initialized when it is used by g at libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c in line 844.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c

Line	850	850
Object	0	g

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c

Method static int runafewfinalizers (lua\_State \*L) {

```
....
850.      g->gcfinnum = (!g->tobefnz) ? 0 /* nothing more to finalize? */
```

#### NULL Pointer Dereference\Path 7:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=239>

Status New

The variable declared in 0 at libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c in line 236 is not initialized when it is used by strm at libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c in line 236.

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	257	257
Object	0	strm

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_streamp strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
257.      strm->opaque = (voidpf)0;
```

#### NULL Pointer Dereference\Path 8:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=240>

Status New

The variable declared in 0 at libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c in line 844 is not initialized when it is used by g at libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c in line 844.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c

Line	850	850
Object	0	g

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c

Method static int runafewfinalizers (lua\_State \*L) {

```
....
850.      g->gcfinnum = (!g->tobefnz) ? 0 /* nothing more to finalize? */
```

#### NULL Pointer Dereference\Path 9:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=241>

Status New

The variable declared in 0 at libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c in line 236 is not initialized when it is used by strm at libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c in line 236.

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	257	257
Object	0	strm

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateInit2\_(z\_stream strm, int level, int method, int windowBits, int memLevel, int strategy,

```
....
257.      strm->opaque = (voidpf)0;
```

#### NULL Pointer Dereference\Path 10:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=242>

Status New

The variable declared in 0 at lua@@lua-v5.4.0-CVE-2020-15889-TP.c in line 120 is not initialized when it is used by g at lua@@lua-v5.4.0-CVE-2020-15889-TP.c in line 596.

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2020-15889-TP.c	lua@@lua-v5.4.0-CVE-2020-15889-TP.c

Line	132	599
Object	0	g

#### Code Snippet

File Name lua@@lua-v5.4.0-CVE-2020-15889-TP.c

Method static GCOBJECT \*\*getgclist (GCOBJECT \*o) {

```
....
132.         default: lua_assert(0); return 0;
```



File Name lua@@lua-v5.4.0-CVE-2020-15889-TP.c

Method static lu\_mem propagatemark (global\_State \*g) {

```
....
599.         g->gray = *getgclist(o); /* remove from 'gray' list */
```

#### NULL Pointer Dereference\Path 11:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=243>

Status New

The variable declared in 0 at lua@@lua-v5.4.0-CVE-2020-24371-TP.c in line 120 is not initialized when it is used by g at lua@@lua-v5.4.0-CVE-2020-24371-TP.c in line 596.

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2020-24371-TP.c	lua@@lua-v5.4.0-CVE-2020-24371-TP.c
Line	132	599
Object	0	g

#### Code Snippet

File Name lua@@lua-v5.4.0-CVE-2020-24371-TP.c

Method static GCOBJECT \*\*getgclist (GCOBJECT \*o) {

```
....
132.         default: lua_assert(0); return 0;
```



File Name lua@@lua-v5.4.0-CVE-2020-24371-TP.c

Method static lu\_mem propagatemark (global\_State \*g) {

```
....
599.         g->gray = *getgclist(o); /* remove from 'gray' list */
```

## Use of Sizeof On a Pointer Type

Query Path:

CPP\Cx\CPP Low Visibility\Use of Sizeof On a Pointer Type Version:1

[Description](#)

### Use of Sizeof On a Pointer Type\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=225">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=225</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c
Line	493	493
Object	sizeof	sizeof

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c  
Method static lu\_mem traversetable (global\_State \*g, Table \*h) {

```
....  
493.                                sizeof(Proto *) * f->sizep +
```

### Use of Sizeof On a Pointer Type\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=226">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=226</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c
Line	1049	1049
Object	sizeof	sizeof

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2020-24371-FP.c  
Method static lu\_mem singlestep (lua\_State \*L) {

```
....  
1049.                g->GCmemtrav = g->strt.size * sizeof(GCObject*);
```

### Use of Sizeof On a Pointer Type\Path 3:

Severity	Low
Result State	To Verify



Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=227">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=227</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c
Line	493	493
Object	sizeof	sizeof

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c

Method static lu\_mem traversetable (global\_State \*g, Table \*h) {

```
....  
493.                sizeof(Proto *) * f->sizep +
```

#### Use of Sizeof On a Pointer Type\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=228">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=228</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c	libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c
Line	1049	1049
Object	sizeof	sizeof

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2020-24371-FP.c

Method static lu\_mem singlestep (lua\_State \*L) {

```
....  
1049.                g->GCmemtrav = g->strt.size * sizeof(GCObject*);
```

#### Use of Sizeof On a Pointer Type\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=229">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=229</a>
Status	New

Source	Destination
--------	-------------

File	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c
Line	701	701
Object	sizeof	sizeof

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c  
Method sraRectangleIterator \*sraRgnGetIterator(sraRegion \*s)

```
....
701.      i->sPtrs = (sraSpan**)malloc(sizeof(sraSpan*)*DEFSIZE);
```

#### Use of Sizeof On a Pointer Type\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=230">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=230</a>
Status	New

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c
Line	756	756
Object	sizeof	sizeof

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.13-CVE-2020-14397-FP.c  
Method rfbBool sraRgnIteratorNext(sraRectangleIterator\* i,sraRect\* r)

```
....
756.      i->sPtrs = (sraSpan**)realloc(i->sPtrs, sizeof(sraSpan*)*i->ptrSize);
```

#### Use of Sizeof On a Pointer Type\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=231">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=231</a>
Status	New

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c
Line	701	701
Object	sizeof	sizeof

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c  
Method sraRectangleIterator \*sraRgnGetIterator(sraRegion \*s)

```
....
701.      i->sPtrs = (sraSpan**)malloc(sizeof(sraSpan*)*DEFSIZE);
```

#### Use of Sizeof On a Pointer Type\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=232>  
Status New

	Source	Destination
File	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c	LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c
Line	756	756
Object	sizeof	sizeof

#### Code Snippet

File Name LibVNC@@libvncserver-LibVNCServer-0.9.14-CVE-2020-14397-FP.c  
Method rfbBool sraRgnIteratorNext(sraRectangleIterator\* i,sraRect\* r)

```
....
756.      i->sPtrs = (sraSpan**)realloc(i->sPtrs, sizeof(sraSpan*)*i->ptrSize);
```

## Use of Insufficiently Random Values

Query Path:

CPP\Cx\CPP Low Visibility\Use of Insufficiently Random Values Version:0

### Categories

FISMA 2014: Media Protection

NIST SP 800-53: SC-28 Protection of Information at Rest (P1)

OWASP Top 10 2017: A3-Sensitive Data Exposure

### Description

#### Use of Insufficiently Random Values\Path 1:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=206>  
Status New

Method qeh\_write\_type at line 32 of litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c
Line	40	40
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v2.12.9-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
40.          s = rand() & 3;
```

### Use of Insufficiently Random Values\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=207">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=207</a>
Status	New

Method qeh\_write\_type at line 32 of litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c
Line	40	40
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v2.13.3-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
40.          s = rand() & 3;
```

### Use of Insufficiently Random Values\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=208">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=208</a>
Status	New

Method qeh\_write\_type at line 37 of litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c
Line	45	45
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v2.17.2-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
45.          s = rand() & 3;
```

#### Use of Insufficiently Random Values\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=209">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=209</a>
Status	New

Method qeh\_write\_type at line 39 of litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c
Line	47	47
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v2.27.0-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
47.          s = rand() & 3;
```

#### Use of Insufficiently Random Values\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=210">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=210</a>
Status	New

Method qeh\_write\_type at line 39 of litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c
Line	47	47
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v2.29.6-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
47.          s = rand() & 3;
```

#### Use of Insufficiently Random Values\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=211">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=211</a>
Status	New

Method qeh\_write\_type at line 39 of litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c
Line	47	47
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v3.0.3-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....  
47.          s = rand() & 3;
```

#### Use of Insufficiently Random Values\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=212">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=212</a>
Status	New

Method qeh\_write\_type at line 39 of litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c uses a weak method rand to produce random values. These values might be used for secret values, personal identifiers or cryptographic input, allowing an attacker to guess the value.

	Source	Destination
File	litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c	litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c
Line	47	47
Object	rand	rand

#### Code Snippet

File Name litespeedtech@@lsquic-v3.0.4-CVE-2022-30592-TP.c  
Method qeh\_write\_type (struct qpack\_enc\_hdl \*qeh)

```
....
47.          s = rand() & 3;
```

## Unchecked Array Index

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Array Index Version:1

### Categories

NIST SP 800-53: SI-10 Information Input Validation (P1)

### Description

#### Unchecked Array Index\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=244">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=244</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	472	472
Object	ins_h	ins_h

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c  
Method static void fill\_window(deflate\_state \*s)

```
....
472.          s->head[s->ins_h] = (Pos)str;
```

#### Unchecked Array Index\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=245">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=245</a>
Status	New

	Source	Destination
File	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c
Line	575	575
Object	ins_h	ins_h

#### Code Snippet

File Name libretro@@RetroArch-v1.9.11-CVE-2023-6992-TP.c  
Method int deflateSetDictionary (z\_stream strm, const Bytef \*dictionary, uInt dictLength)

```
....  
575.          s->head[s->ins_h] = (Pos)str;
```

#### Unchecked Array Index\Path 3:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=246>  
Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c
Line	472	472
Object	ins_h	ins_h

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c  
Method static void fill\_window(deflate\_state \*s)

```
....  
472.          s->head[s->ins_h] = (Pos)str;
```

#### Unchecked Array Index\Path 4:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&projectid=20033&pathid=247>  
Status New

	Source	Destination
File	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c	libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c



Line	575	575
Object	ins_h	ins_h

#### Code Snippet

File Name libretro@@RetroArch-v1.9.6-CVE-2023-6992-TP.c

Method int deflateSetDictionary (z\_stream strm, const Bytef \*dictionary, uInt dictLength)

```
....
575.          s->head[s->ins_h] = (Pos)str;
```

## Inconsistent Implementations

Query Path:

CPP\Cx\CPP Low Visibility\Inconsistent Implementations Version:0

### Description

#### Inconsistent Implementations\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=1">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=1</a>
Status	New

	Source	Destination
File	libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c
Line	85	85
Object	getopt	getopt

#### Code Snippet

File Name libsdl-org@@libtiff-v3.5.1-CVE-2023-6228-TP.c

Method main(int argc, char\* argv[])

```
....
85.    while ((c = getopt(argc, argv, "c:f:l:o:p:r:w:a:stBLMC")) != -1)
```

#### Inconsistent Implementations\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=2">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=2</a>
Status	New

	Source	Destination
File	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c	libsdl-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c
Line	206	206

Object	getopt	getopt
--------	--------	--------

#### Code Snippet

File Name libstd-org@@libtiff-v4.2.0-CVE-2023-6228-TP.c  
Method main(int argc, char\* argv[])

```
....
206.         while ((c = getopt(argc, argv,
    "m:,b:c:f:l:o:p:r:w:aistBLMC8xh")) != -1)
```

## Incorrect Permission Assignment For Critical Resources

Query Path:

CPP\Cx\CPP Low Visibility\Incorrect Permission Assignment For Critical Resources Version:1

### Categories

FISMA 2014: Access Control  
NIST SP 800-53: AC-3 Access Enforcement (P1)  
OWASP Top 10 2017: A2-Broken Authentication

### Description

#### Incorrect Permission Assignment For Critical Resources\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=205">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=205</a>
Status	New

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2021-3520-FP.c	lua@@lua-v5.4.0-CVE-2021-3520-FP.c
Line	433	433
Object	f	f

#### Code Snippet

File Name lua@@lua-v5.4.0-CVE-2021-3520-FP.c  
Method static int readable (const char \*filename) {

```
....
433.     FILE *f = fopen(filename, "r"); /* try to open file */
```

## TOCTOU

Query Path:

CPP\Cx\CPP Low Visibility\TOCTOU Version:1

### Description

#### TOCTOU\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=248">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020040&amp;projectid=20033&amp;pathid=248</a>
Status	New

The readable method in lua@@lua-v5.4.0-CVE-2021-3520-FP.c file utilizes fopen that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	lua@@lua-v5.4.0-CVE-2021-3520-FP.c	lua@@lua-v5.4.0-CVE-2021-3520-FP.c
Line	433	433
Object	fopen	fopen

#### Code Snippet

File Name lua@@lua-v5.4.0-CVE-2021-3520-FP.c  
Method static int readable (const char \*filename) {

```
....  
433.     FILE *f = fopen(filename, "r"); /* try to open file */
```

## Divide By Zero

### Risk

#### What might happen

When a program divides a number by zero, an exception will be raised. If this exception is not handled by the application, unexpected results may occur, including crashing the application. This can be considered a DoS (Denial of Service) attack, if an external user has control of the value of the denominator or can cause this error to occur.

### Cause

#### How does it happen

The program receives an unexpected value, and uses it for division without filtering, validation, or verifying that the value is not zero. The application does not explicitly handle this error or prevent division by zero from occurring.

## General Recommendations

#### How to avoid it

- Before dividing by an unknown value, validate the number and explicitly ensure it does not evaluate to zero.
- Validate all untrusted input from all sources, in particular verifying that it is not zero before dividing with it.
- Verify output of methods, calculations, dictionary lookups, and so on, and ensure it is not zero before dividing with the result.
- Ensure divide-by-zero errors are caught and handled appropriately.

## Source Code Examples

## Java

### Divide by Zero

```
public float getAverage(HttpServletRequest req) {  
    int total = Integer.parseInt(req.getParameter("total"));  
    int count = Integer.parseInt(req.getParameter("count"));  
  
    return total / count;  
}
```

### Checked Division

```
public float getAverage(HttpServletRequest req) {  
    int total = Integer.parseInt(req.getParameter("total"));  
    int count = Integer.parseInt(req.getParameter("count"));  
  
    if (count > 0)  
        return total / count;  
    else  
        return 0;  
}
```

# Buffer Overflow boundcpy WrongSizeParam

## Risk

### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

---

## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
  - Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
  - Consistently apply tests for the size of buffers.
  - Do not return variable addresses outside the scope of their variables.
- 

## Source Code Examples

### CPP

#### Overflowing Buffers

```
const int BUFFER_SIZE = 10;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    strcpy(buffer, inputString);
}
```

#### Checked Buffers

```
const int BUFFER_SIZE = 10;
const int MAX_INPUT_SIZE = 256;
```

```
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    if (strlen(inputString, MAX_INPUT_SIZE) < sizeof(buffer))
    {
        strncpy(buffer, inputString, sizeof(buffer));
    }
}
```

# Float Overflow

## Risk

### What might happen

Assigning large data types into smaller data types, without proper checks and explicit casting, will lead to undefined behavior and unintentional effects, such as data corruption (e.g. value wraparound, wherein maximum values become minimum values); system crashes; infinite loops; logic errors, such as bypassing of security mechanisms; or even buffer overflows leading to arbitrary code execution.

---

## Cause

### How does it happen

This flaw can occur when implicitly casting numerical data types of a larger size, into a variable with a data type of a smaller size. This forces the program to discard some bits of information from the number. Depending on how the numerical data types are stored in memory, this is often the bits with the highest value, causing substantial corruption of the stored number. Alternatively, the sign bit of a signed integer could be lost, completely reversing the intention of the number.

---

## General Recommendations

### How to avoid it

- Avoid casting larger data types to smaller types.
  - Prefer promoting the target variable to a large enough data type.
  - If downcasting is necessary, always check that values are valid and in range of the target type, before casting
- 

## Source Code Examples

### CPP

#### Unsafe Downsize Casting

```
int unsafe_addition(short op1, int op2) {  
    // op2 gets forced from int into a short  
    short total = op1 + op2;  
    return total;  
}
```

#### Safer Use of Proper Data Types

```
int safe_addition(short op1, int op2) {  
    // total variable is of type int, the largest type that is needed  
    int total = 0;  
    // check if total will overflow available integer size  
    if (INT_MAX - abs(op2) > op1)
```

```
{
    total = op1 + op2;
}
else
{
    // instead of overflow, saturate (but this is not always a good thing)
    total = INT_MAX
}

return total;
}
```



# Integer Overflow

## Risk

### What might happen

Assigning large data types into smaller data types, without proper checks and explicit casting, will lead to undefined behavior and unintentional effects, such as data corruption (e.g. value wraparound, wherein maximum values become minimum values); system crashes; infinite loops; logic errors, such as bypassing of security mechanisms; or even buffer overflows leading to arbitrary code execution.

---

## Cause

### How does it happen

This flaw can occur when implicitly casting numerical data types of a larger size, into a variable with a data type of a smaller size. This forces the program to discard some bits of information from the number. Depending on how the numerical data types are stored in memory, this is often the bits with the highest value, causing substantial corruption of the stored number. Alternatively, the sign bit of a signed integer could be lost, completely reversing the intention of the number.

---

## General Recommendations

### How to avoid it

- Avoid casting larger data types to smaller types.
  - Prefer promoting the target variable to a large enough data type.
  - If downcasting is necessary, always check that values are valid and in range of the target type, before casting
- 

## Source Code Examples

# Dangerous Functions

## Risk

### What might happen

Use of dangerous functions may expose varying risks associated with each particular function, with potential impact of improper usage of these functions varying significantly. The presence of such functions indicates a flaw in code maintenance policies and adherence to secure coding practices, in a way that has allowed introducing known dangerous code into the application.

---

## Cause

### How does it happen

A dangerous function has been identified within the code. Functions are often deemed dangerous to use for numerous reasons, as there are different sets of vulnerabilities associated with usage of such functions. For example, some string copy and concatenation functions are vulnerable to Buffer Overflow, Memory Disclosure, Denial of Service and more. Use of these functions is not recommended.

---

## General Recommendations

### How to avoid it

- Deploy a secure and recommended alternative to any functions that were identified as dangerous.
    - If no secure alternative is found, conduct further researching and testing to identify whether current usage successfully sanitizes and verifies values, and thus successfully avoids the use-cases for whom the function is indeed dangerous
  - Conduct a periodical review of methods that are in use, to ensure that all external libraries and built-in functions are up-to-date and whose use has not been excluded from best secure coding practices.
- 

## Source Code Examples

### CPP

#### Buffer Overflow in gets()

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    gets(buf); // veryveryverylongname
    if (buf == ACCEPTED_NAME)
    {
        // Do something
    }
    return 0;
}
```

## Safe reading from user

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    fgets(buf, sizeof(buf), stdin); //setting the amount of bytes to read
    if (buf == ACCEPTED_NAME)
    {
        //Do something
    }
    return 0;
}
```

## Unsafe function for string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strcpy(buf, argv[1]); // overflow occurs when len(argv[1]) > 10 bytes

    return 0;
}
```

## Safe string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strncpy(buf, argv[1], sizeof(buf));
    buf[9] = '\0'; //strncpy doesn't NULL terminates

    return 0;
}
```

## Unsafe format string

```
int main(int argc, char* argv[])
{
    printf(argv[1]); // If argv[1] contains a format token, such as %s,%x or %d, will cause an access violation
    return 0;
}
```

## Safe format string

```
int main(int argc, char* argv[])
{
    printf("%s", argv[1]); // Second parameter is not a formattable string
    return 0;
}
```

## Failure to Release Memory Before Removing Last Reference ('Memory Leak')

**Weakness ID:** 401 (*Weakness Base*)

**Status:** Draft

### Description

#### Description Summary

The software does not sufficiently track and release allocated memory after it has been used, which slowly consumes remaining memory.

#### Extended Description

This is often triggered by improper handling of malformed data or unexpectedly interrupted sessions.

#### Terminology Notes

"memory leak" has sometimes been used to describe other kinds of issues, e.g. for information leaks in which the contents of memory are inadvertently leaked (CVE-2003-0400 is one such example of this terminology conflict).

#### Time of Introduction

- Architecture and Design
- Implementation

#### Applicable Platforms

#### Languages

C

C++

#### Modes of Introduction

Memory leaks have two common and sometimes overlapping causes:

- Error conditions and other exceptional circumstances
- Confusion over which part of the program is responsible for freeing the memory

#### Common Consequences

Scope	Effect
Availability	Most memory leaks result in general software reliability problems, but if an attacker can intentionally trigger a memory leak, the attacker might be able to launch a denial of service attack (by crashing or hanging the program) or take advantage of other unexpected program behavior resulting from a low memory condition.

#### Likelihood of Exploit

Medium

#### Demonstrative Examples

##### Example 1

The following C function leaks a block of allocated memory if the call to read() fails to return the expected number of bytes:

(*Bad Code*)

*Example Language: C*

```
char* getBlock(int fd) {
char* buf = (char*) malloc(BLOCK_SIZE);
if (!buf) {
return NULL;
}
if (read(fd, buf, BLOCK_SIZE) != BLOCK_SIZE) {

return NULL;
}
```

```
return buf;
}
```

## Example 2

Here the problem is that every time a connection is made, more memory is allocated. So if one just opened up more and more connections, eventually the machine would run out of memory.

(Bad Code)

Example Language: C

```
bar connection(){
foo = malloc(1024);
return foo;
}

endConnection(bar foo) {

free(foo);
}

int main() {

while(1) //thread 1
//On a connection
foo=connection(); //thread 2
//When the connection ends
endConnection(foo)
}
```

## Observed Examples

Reference	Description
<a href="#">CVE-2005-3119</a>	Memory leak because function does not free() an element of a data structure.
<a href="#">CVE-2004-0427</a>	Memory leak when counter variable is not decremented.
<a href="#">CVE-2002-0574</a>	Memory leak when counter variable is not decremented.
<a href="#">CVE-2005-3181</a>	Kernel uses wrong function to release a data structure, preventing data from being properly tracked by other code.
<a href="#">CVE-2004-0222</a>	Memory leak via unknown manipulations as part of protocol test suite.
<a href="#">CVE-2001-0136</a>	Memory leak via a series of the same command.

## Potential Mitigations

Pre-design: Use a language or compiler that performs automatic bounds checking.

### Phase: Architecture and Design

Use an abstraction library to abstract away risky APIs. Not a complete solution.

Pre-design through Build: The Boehm-Demers-Weiser Garbage Collector or valgrind can be used to detect leaks in code. This is not a complete solution as it is not 100% effective.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	398	<a href="#">Indicator of Poor Code Quality</a>	<b>Seven Pernicious Kingdoms (primary)700</b>
ChildOf	Category	399	<a href="#">Resource Management Errors</a>	<b>Development Concepts (primary)699</b>
ChildOf	Category	633	<a href="#">Weaknesses that Affect Memory</a>	<b>Resource-specific Weaknesses (primary)631</b>
ChildOf	Category	730	<a href="#">OWASP Top Ten 2004 Category A9 - Denial of Service</a>	<b>Weaknesses in OWASP Top Ten (2004) (primary)711</b>
ChildOf	Weakness Base	772	<a href="#">Missing Release of Resource after Effective</a>	<b>Research Concepts (primary)1000</b>

MemberOf	View	630	<a href="#">Lifetime Weaknesses Examined by SAMATE</a>	<b>Weaknesses Examined by SAMATE (primary) 630</b> Research Concepts1000
CanFollow	Weakness Class	390	<a href="#">Detection of Error Condition Without Action</a>	

## Relationship Notes

This is often a resultant weakness due to improper handling of malformed data or early termination of sessions.

## Affected Resources

- Memory

## Functional Areas

- Memory management

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
PLOVER			Memory leak
7 Pernicious Kingdoms			Memory Leak
CLASP			Failure to deallocate data
OWASP Top Ten 2004	A9	CWE More Specific	Denial of Service

## White Box Definitions

A weakness where the code path has:

1. start statement that allocates dynamically allocated memory resource
2. end statement that loses identity of the dynamically allocated memory resource creating situation where dynamically allocated memory resource is never relinquished

Where "loses" is defined through the following scenarios:

1. identity of the dynamic allocated memory resource never obtained
2. the statement assigns another value to the data element that stored the identity of the dynamically allocated memory resource and there are no aliases of that data element
3. identity of the dynamic allocated memory resource obtained but never passed on to function for memory resource release
4. the data element that stored the identity of the dynamically allocated resource has reached the end of its scope at the statement and there are no aliases of that data element

## References

J. Whittaker and H. Thompson. "How to Break Software Security". Addison Wesley. 2003.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	PLOVER		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-01		KDM Analytics	External
	added/updated white box definitions		
2008-08-15		Veracode	External
	Suggested OWASP Top Ten 2004 mapping		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Relationships, Other Notes, References, Relationship Notes, Taxonomy Mappings, Terminology Notes		
2008-10-14	CWE Content Team	MITRE	Internal
	updated Description		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Other Notes		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Name		
2009-07-17	KDM Analytics		External
	Improved the White Box Definition		

2009-07-27	CWE Content Team updated White Box Definitions	MITRE	Internal
2009-10-29	CWE Content Team updated Modes of Introduction, Other Notes	MITRE	Internal
2010-02-16	CWE Content Team updated Relationships	MITRE	Internal
<b>Previous Entry Names</b>			
<b>Change Date</b>	<b>Previous Entry Name</b>		
2008-04-11	Memory Leak		
2009-05-27	Failure to Release Memory Before Removing Last Reference (aka 'Memory Leak')		

[BACK TO TOP](#)



# Use of Zero Initialized Pointer

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

### CPP

#### Explicit NULL Dereference

```
char * input = NULL;
printf("%s", input);
```

#### Implicit NULL Dereference

```
char * input;
printf("%s", input);
```

### Java

#### Explicit Null Dereference

```
Object o = null;
out.println(o.getClass());
```



## Use of Function with Inconsistent Implementations

**Weakness ID:** 474 (*Weakness Base*)

**Status:** Draft

### Description

### Description Summary

The code uses a function that has inconsistent implementations across operating systems and versions, which might cause security-relevant portability problems.

### Time of Introduction

- Architecture and Design
- Implementation

### Applicable Platforms

### Languages

C: (*Often*)

PHP: (*Often*)

All

### Potential Mitigations

Do not accept inconsistent behavior from the API specifications when the deviant behavior increase the risk level.

### Other Notes

The behavior of functions in this category varies by operating system, and at times, even by operating system version. Implementation differences can include:

- Slight differences in the way parameters are interpreted leading to inconsistent results.
- Some implementations of the function carry significant security risks.
- The function might not be defined on all platforms.

### Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	398	<a href="#">Indicator of Poor Code Quality</a>	<b>Development Concepts (primary)699</b> <b>Seven Pernicious Kingdoms (primary)700</b> <b>Research Concepts (primary)1000</b>
ParentOf	Weakness Variant	589	<a href="#">Call to Non-ubiquitous API</a>	<b>Research Concepts (primary)1000</b>

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Inconsistent Implementations

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Potential Mitigations, Time of Introduction		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Relationships, Other Notes, Taxonomy Mappings		
Previous Entry Names			
Change Date	Previous Entry Name		
2008-04-11	Inconsistent Implementations		

[BACK TO TOP](#)

**Improper Access Control (Authorization)****Weakness ID:** 285 (*Weakness Class*)**Status:** Draft**Description****Description Summary**

The software does not perform or incorrectly performs access control checks across all potential execution paths.

**Extended Description**

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information leaks, denial of service, and arbitrary code execution.

**Alternate Terms****AuthZ:**

"AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

**Time of Introduction**

- Architecture and Design
- Implementation
- Operation

**Applicable Platforms****Languages**

Language-independent

**Technology Classes**

Web-Server: (*Often*)

Database-Server: (*Often*)

**Modes of Introduction**

A developer may introduce authorization weaknesses because of a lack of understanding about the underlying technologies. For example, a developer may assume that attackers cannot modify certain inputs such as headers or cookies.

Authorization weaknesses may arise when a single-user application is ported to a multi-user environment.

**Common Consequences**

Scope	Effect
Confidentiality	An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.
Integrity	An attacker could modify sensitive data, either by writing the data directly to a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.
Integrity	An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.

**Likelihood of Exploit**

High

**Detection Methods**

### **Automated Static Analysis**

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries.

Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

### ***Effectiveness: Limited***

### **Automated Dynamic Analysis**

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

### **Manual Analysis**

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

### ***Effectiveness: Moderate***

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

## **Demonstrative Examples**

### **Example 1**

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

*(Bad Code)*

#### ***Example Language: Perl***

```
sub DisplayPrivateMessage {
my($id) = @_ ;
my $Message = LookupMessageObject($id);
print "From: " . encodeHTML($Message->{from}) . "<br>\n";
print "Subject: " . encodeHTML($Message->{subject}) . "\n";
print "<hr>\n";
print "Body: " . encodeHTML($Message->{body}) . "\n";
}

my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
ExitError("invalid username or password");
}

my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users. One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

## **Observed Examples**

Reference	Description
<a href="#">CVE-2009-3168</a>	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords.

<a href="#">CVE-2009-2960</a>	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users.
<a href="#">CVE-2009-3597</a>	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request.
<a href="#">CVE-2009-2282</a>	Terminal server does not check authorization for guest access.
<a href="#">CVE-2009-3230</a>	Database server does not use appropriate privileges for certain sensitive operations.
<a href="#">CVE-2009-2213</a>	Gateway uses default "Allow" configuration for its authorization settings.
<a href="#">CVE-2009-0034</a>	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges.
<a href="#">CVE-2008-6123</a>	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect.
<a href="#">CVE-2008-5027</a>	System monitoring software allows users to bypass authorization by creating custom forms.
<a href="#">CVE-2008-7109</a>	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client.
<a href="#">CVE-2008-3424</a>	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access.
<a href="#">CVE-2009-3781</a>	Content management system does not check access permissions for private files, allowing others to view those files.
<a href="#">CVE-2008-4577</a>	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions.
<a href="#">CVE-2008-6548</a>	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files.
<a href="#">CVE-2007-2925</a>	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries.
<a href="#">CVE-2006-6679</a>	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header.
<a href="#">CVE-2005-3623</a>	OS kernel does not check for a certain privilege before setting ACLs for files.
<a href="#">CVE-2005-2801</a>	Chain: file-system code performs an incorrect comparison (CWE-697), preventing defaults ACLs from being properly applied.
<a href="#">CVE-2001-1155</a>	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions.

## Potential Mitigations

### Phase: Architecture and Design

Divide your application into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries.

Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

### Phase: Architecture and Design

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

### Phase: Architecture and Design

## Strategy: Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness

easier to avoid.

For example, consider using authorization frameworks such as the JAAS Authorization Framework and the OWASP ESAPI Access Control feature.

### Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page.

One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

### Phases: System Configuration; Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	254	<a href="#">Security Features</a>	<b>Seven Pernicious Kingdoms (primary)700</b>
ChildOf	Weakness Class	284	<a href="#">Access Control (Authorization) Issues</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	721	<a href="#">OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access</a>	<b>Weaknesses in OWASP Top Ten (2007) (primary)629</b>
ChildOf	Category	723	<a href="#">OWASP Top Ten 2004 Category A2 - Broken Access Control</a>	<b>Weaknesses in OWASP Top Ten (2004) (primary)711</b>
ChildOf	Category	753	<a href="#">2009 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)750</b>
ChildOf	Category	803	<a href="#">2010 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
ParentOf	Weakness Variant	219	<a href="#">Sensitive Data Under Web Root</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Base	551	<a href="#">Incorrect Behavior Order: Authorization Before Parsing and Canonicalization</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts1000</b>
ParentOf	Weakness Class	638	<a href="#">Failure to Use Complete Mediation</a>	<b>Research Concepts1000</b>
ParentOf	Weakness Base	804	<a href="#">Guessable CAPTCHA</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">1</a>	Accessing Functionality Not Properly Constrained by ACLs	
<a href="#">13</a>	Subverting Environment Variable Values	

<a href="#">17</a>	Accessing, Modifying or Executing Executable Files
<a href="#">87</a>	Forceful Browsing
<a href="#">39</a>	Manipulating Opaque Client-based Data Tokens
<a href="#">45</a>	Buffer Overflow via Symbolic Links
<a href="#">51</a>	Poison Web Service Registry
<a href="#">59</a>	Session Credential Falsification through Prediction
<a href="#">60</a>	Reusing Session IDs (aka Session Replay)
<a href="#">77</a>	Manipulating User-Controlled Variables
<a href="#">76</a>	Manipulating Input to File System Calls
<a href="#">104</a>	Cross Zone Scripting

## References

NIST. "Role Based Access Control and Role Based Security". <<http://csrc.nist.gov/groups/SNS/rbac/>>.

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 4, "Authorization" Page 114; Chapter 6, "Determining Appropriate Access Control" Page 171. 2nd Edition. Microsoft. 2002.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-15		Veracode	External
	Suggested OWASP Top Ten 2004 mapping		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Relationships, Other Notes, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences, Description, Likelihood of Exploit, Name, Other Notes, Potential Mitigations, References, Relationships		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Description, Related Attack Patterns		
2009-07-27	CWE Content Team	MITRE	Internal
	updated Relationships		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Type		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Demonstrative Examples, Detection Factors, Modes of Introduction, Observed Examples, Relationships		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Detection Factors, Potential Mitigations, References, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-01-12	Missing or Inconsistent Access Control		

[BACK TO TOP](#)



**Incorrect Permission Assignment for Critical Resource****Weakness ID:** 732 (*Weakness Class*)**Status:** Draft**Description****Description Summary**

The software specifies permissions for a security-critical resource in a way that allows that resource to be read or modified by unintended actors.

**Extended Description**

When a resource is given a permissions setting that provides access to a wider range of actors than required, it could lead to the disclosure of sensitive information, or the modification of that resource by unintended parties. This is especially dangerous when the resource is related to program configuration, execution or sensitive user data.

**Time of Introduction**

- Architecture and Design
- Implementation
- Installation
- Operation

**Applicable Platforms****Languages**

Language-independent

**Modes of Introduction**

The developer may set loose permissions in order to minimize problems when the user first runs the program, then create documentation stating that permissions should be tightened. Since system administrators and users do not always read the documentation, this can result in insecure permissions being left unchanged.

The developer might make certain assumptions about the environment in which the software runs - e.g., that the software is running on a single-user system, or the software is only accessible to trusted administrators. When the software is running in a different environment, the permissions become a problem.

**Common Consequences**

Scope	Effect
Confidentiality	An attacker may be able to read sensitive information from the associated resource, such as credentials or configuration information stored in a file.
Integrity	An attacker may be able to modify critical properties of the associated resource to gain privileges, such as replacing a world-writable executable with a Trojan horse.
Availability	An attacker may be able to destroy or corrupt critical data in the associated resource, such as deletion of records from a database.

**Likelihood of Exploit**

Medium to High

**Detection Methods****Automated Static Analysis**

Automated static analysis may be effective in detecting permission problems for system resources such as files, directories, shared memory, device interfaces, etc. Automated techniques may be able to detect the use of library functions that modify permissions, then analyze function calls for arguments that contain potentially insecure values.

However, since the software's intended security policy might allow loose permissions for certain operations (such as publishing a file on a web server), automated static analysis may produce some false positives - i.e., warnings that do not have any security consequences or require any code changes.

When custom permissions models are used - such as defining who can read messages in a particular forum in a bulletin board system - these can be difficult to detect using automated static analysis. It may be possible to define custom signatures that

identify any custom functions that implement the permission checks and assignments.

---

### Automated Dynamic Analysis

Automated dynamic analysis may be effective in detecting permission problems for system resources such as files, directories, shared memory, device interfaces, etc.

However, since the software's intended security policy might allow loose permissions for certain operations (such as publishing a file on a web server), automated dynamic analysis may produce some false positives - i.e., warnings that do not have any security consequences or require any code changes.

When custom permissions models are used - such as defining who can read messages in a particular forum in a bulletin board system - these can be difficult to detect using automated dynamic analysis. It may be possible to define custom signatures that identify any custom functions that implement the permission checks and assignments.

---

### Manual Static Analysis

Manual static analysis may be effective in detecting the use of custom permissions models and functions. The code could then be examined to identifying usage of the related functions. Then the human analyst could evaluate permission assignments in the context of the intended security model of the software.

---

### Manual Dynamic Analysis

Manual dynamic analysis may be effective in detecting the use of custom permissions models and functions. The program could then be executed with a focus on exercising code paths that are related to the custom permissions. Then the human analyst could evaluate permission assignments in the context of the intended security model of the software.

---

### Fuzzing

Fuzzing is not effective in detecting this weakness.

---

## Demonstrative Examples

### Example 1

The following code sets the umask of the process to 0 before creating a file and writing "Hello world" into the file.

*(Bad Code)*

*Example Language: C*

```
#define OUTFILE "hello.out"

umask(0);
FILE *out;
/* Ignore CWE-59 (link following) for brevity */
out = fopen(OUTFILE, "w");
if (out) {
    fprintf(out, "hello world!\n");
    fclose(out);
}
```

After running this program on a UNIX system, running the "ls -l" command might return the following output:

*(Result)*

```
-rw-rw-rw- 1 username 13 Nov 24 17:58 hello.out
```

The "rw-rw-rw-" string indicates that the owner, group, and world (all users) can read the file and write to it.

### Example 2

The following code snippet might be used as a monitor to periodically record whether a web site is alive. To ensure that the file can always be modified, the code uses chmod() to make the file world-writable.

*(Bad Code)*

*Example Language: Perl*

```
$fileName = "secretFile.out";

if (-e $fileName) {
    chmod 0777, $fileName;
}
```

```
my $outFH;  
if (! open($outFH, ">>$fileName")) {  
    ExitError("Couldn't append to $fileName: $!");  
}  
my $dateString = FormatCurrentTime();  
my $status = IsHostAlive("cwe.mitre.org");  
print $outFH "$dateString cwe status: $status!\n";  
close($outFH);
```

The first time the program runs, it might create a new file that inherits the permissions from its environment. A file listing might look like:

*(Result)*

```
-rw-r--r-- 1 username 13 Nov 24 17:58 secretFile.out
```

This listing might occur when the user has a default umask of 022, which is a common setting. Depending on the nature of the file, the user might not have intended to make it readable by everyone on the system.

The next time the program runs, however - and all subsequent executions - the chmod will set the file's permissions so that the owner, group, and world (all users) can read the file and write to it:

*(Result)*

```
-rw-rw-rw- 1 username 13 Nov 24 17:58 secretFile.out
```

Perhaps the programmer tried to do this because a different process uses different permissions that might prevent the file from being updated.

### Example 3

The following command recursively sets world-readable permissions for a directory and all of its children:

*(Bad Code)*

*Example Language: Shell*

```
chmod -R ugo+r DIRNAME
```

If this command is run from a program, the person calling the program might not expect that all the files under the directory will be world-readable. If the directory is expected to contain private data, this could become a security problem.

### Observed Examples

Reference	Description
<a href="#">CVE-2009-3482</a>	Anti-virus product sets insecure "Everyone: Full Control" permissions for files under the "Program Files" folder, allowing attackers to replace executables with Trojan horses.
<a href="#">CVE-2009-3897</a>	Product creates directories with 0777 permissions at installation, allowing users to gain privileges and access a socket used for authentication.
<a href="#">CVE-2009-3489</a>	Photo editor installs a service with an insecure security descriptor, allowing users to stop or start the service, or execute commands as SYSTEM.
<a href="#">CVE-2009-3289</a>	Library function copies a file to a new target and uses the source file's permissions for the target, which is incorrect when the source file is a symbolic link, which typically has 0777 permissions.
<a href="#">CVE-2009-0115</a>	Device driver uses world-writable permissions for a socket file, allowing attackers to inject arbitrary commands.
<a href="#">CVE-2009-1073</a>	LDAP server stores a cleartext password in a world-readable file.
<a href="#">CVE-2009-0141</a>	Terminal emulator creates TTY devices with world-writable permissions, allowing an attacker to write to the terminals of other users.

<a href="#">CVE-2008-0662</a>	VPN product stores user credentials in a registry key with "Everyone: Full Control" permissions, allowing attackers to steal the credentials.
<a href="#">CVE-2008-0322</a>	Driver installs its device interface with "Everyone: Write" permissions.
<a href="#">CVE-2009-3939</a>	Driver installs a file with world-writable permissions.
<a href="#">CVE-2009-3611</a>	Product changes permissions to 0777 before deleting a backup; the permissions stay insecure for subsequent backups.
<a href="#">CVE-2007-6033</a>	Product creates a share with "Everyone: Full Control" permissions, allowing arbitrary program execution.
<a href="#">CVE-2007-5544</a>	Product uses "Everyone: Full Control" permissions for memory-mapped files (shared memory) in inter-process communication, allowing attackers to tamper with a session.
<a href="#">CVE-2005-4868</a>	Database product uses read/write permissions for everyone for its shared memory, allowing theft of credentials.
<a href="#">CVE-2004-1714</a>	Security product uses "Everyone: Full Control" permissions for its configuration files.
<a href="#">CVE-2001-0006</a>	"Everyone: Full Control" permissions assigned to a mutex allows users to disable network connectivity.
<a href="#">CVE-2002-0969</a>	Chain: database product contains buffer overflow that is only reachable through a .ini configuration file - which has "Everyone: Full Control" permissions.

## Potential Mitigations

### **Phase: Implementation**

When using a critical resource such as a configuration file, check to see if the resource has insecure permissions (such as being modifiable by any regular user), and generate an error or even exit the software if there is a possibility that the resource could have been modified by an unauthorized party.

### **Phase: Architecture and Design**

Divide your application into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully defining distinct user groups, privileges, and/or roles. Map these against data, functionality, and the related resources. Then set the permissions accordingly. This will allow you to maintain more fine-grained control over your resources.

### **Phases: Implementation; Installation**

During program startup, explicitly set the default permissions or umask to the most restrictive setting possible. Also set the appropriate permissions during program installation. This will prevent you from inheriting insecure permissions from any user who installs or runs the program.

### **Phase: System Configuration**

For all configuration files, executables, and libraries, make sure that they are only readable and writable by the software's administrator.

### **Phase: Documentation**

Do not suggest insecure configuration changes in your documentation, especially if those configurations can extend to resources and other software that are outside the scope of your own software.

### **Phase: Installation**

Do not assume that the system administrator will manually change the configuration to the settings that you recommend in the manual.

### **Phase: Testing**

Use tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session. These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules.

### **Phase: Testing**

Use monitoring tools that examine the software's process as it interacts with the operating system and the network. This technique is useful in cases when source code is unavailable, if the software was not developed by you, or if you want to verify that the build phase did not introduce any new weaknesses. Examples include debuggers that directly attach to the running process; system-call tracing utilities such as truss (Solaris) and strace (Linux); system activity monitors such as FileMon, RegMon, Process Monitor, and other Sysinternals utilities (Windows); and sniffers and protocol analyzers that monitor network traffic.

Attach the monitor to the process and watch for library functions or system calls on OS resources such as files, directories, and shared memory. Examine the arguments to these calls to infer which permissions are being used.

Note that this technique is only useful for permissions issues related to system resources. It is not likely to detect application-level business rules that are related to permissions, such as if a user of a blog system marks a post as "private," but the blog system inadvertently marks it as "public."

### Phases: Testing; System Configuration

Ensure that your software runs properly under the Federal Desktop Core Configuration (FDCC) or an equivalent hardening configuration guide, which many organizations use to limit the attack surface and potential risk of deployed software.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	275	<a href="#">Permission Issues</a>	<b>Development Concepts (primary)699</b>
ChildOf	Weakness Class	668	<a href="#">Exposure of Resource to Wrong Sphere</a>	<b>Research Concepts (primary)1000</b>
ChildOf	Category	753	<a href="#">2009 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)750</b>
ChildOf	Category	803	<a href="#">2010 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
RequiredBy	Compound Element: Composite	689	<a href="#">Permission Race Condition During Resource Copy</a>	Research Concepts1000
ParentOf	Weakness Variant	276	<a href="#">Incorrect Default Permissions</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Variant	277	<a href="#">Insecure Inherited Permissions</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Variant	278	<a href="#">Insecure Preserved Inherited Permissions</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Variant	279	<a href="#">Incorrect Execution- Assigned Permissions</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Base	281	<a href="#">Improper Preservation of Permissions</a>	<b>Research Concepts (primary)1000</b>

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">232</a>	Exploitation of Privilege/Trust	
<a href="#">1</a>	Accessing Functionality Not Properly Constrained by ACLs	
<a href="#">17</a>	Accessing, Modifying or Executing Executable Files	
<a href="#">60</a>	Reusing Session IDs (aka Session Replay)	
<a href="#">61</a>	Session Fixation	
<a href="#">62</a>	Cross Site Request Forgery (aka Session Riding)	
<a href="#">122</a>	Exploitation of Authorization	
<a href="#">180</a>	Exploiting Incorrectly Configured Access Control Security Levels	
<a href="#">234</a>	Hijacking a privileged process	

## References

Mark Dowd, John McDonald and Justin Schuh. "The Art of Software Security Assessment". Chapter 9, "File Permissions." Page 495.. 1st Edition. Addison Wesley. 2006.

John Viega and Gary McGraw. "Building Secure Software". Chapter 8, "Access Control." Page 194.. 1st Edition. Addison-Wesley. 2002.

## Maintenance Notes

The relationships between privileges, permissions, and actors (e.g. users and groups) need further refinement within the Research view. One complication is that these concepts apply to two different pillars, related to control of resources (CWE-664) and protection mechanism failures (CWE-396).

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
2008-09-08			Internal CWE Team
	new weakness-focused entry for Research view.		
Modifications			
Modification Date	Modifier	Organization	Source
2009-01-12	CWE Content Team	MITRE	Internal
	updated Description, Likelihood of Exploit, Name, Potential Mitigations, Relationships		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Potential Mitigations, Related Attack Patterns		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Name		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Demonstrative Examples, Detection Factors, Modes of Introduction, Observed Examples, Potential Mitigations, References		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Potential Mitigations, Related Attack Patterns		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-01-12	Insecure Permission Assignment for Resource		
2009-05-27	Insecure Permission Assignment for Critical Resource		

[BACK TO TOP](#)

# Use of Insufficiently Random Values

## Risk

### What might happen

Random values are often used as a mechanism to prevent malicious users from guessing a value, such as a password, encryption key, or session identifier. Depending on what this random value is used for, an attacker would be able to predict the next numbers generated, or previously generated values. This could enable the attacker to hijack another user's session, impersonate another user, or crack an encryption key (depending on what the pseudo-random value was used for).

---

## Cause

### How does it happen

The application uses a weak method of generating pseudo-random values, such that other numbers could be determined from a relatively small sample size. Since the pseudo-random number generator used is designed for statistically uniform distribution of values, it is approximately deterministic. Thus, after collecting a few generated values (e.g. by creating a few individual sessions, and collecting the sessionids), it would be possible for an attacker to calculate another sessionid.

Specifically, if this pseudo-random value is used in any security context, such as passwords, keys, or secret identifiers, an attacker would be able to predict the next numbers generated, or previously generated values.

---

## General Recommendations

### How to avoid it

Generic Guidance:

- Whenever unpredictable numbers are required in a security context, use a cryptographically strong random number generator, instead of a statistical pseudo-random generator.
- Use the cryptorandom generator that is built-in to your language or platform, and ensure it is securely seeded. Do not seed the generator with a weak, non-random seed. (In most cases, the default is securely random).
- Ensure you use a long enough random value, to make brute-force attacks unfeasible.

Specific Recommendations:

- Do not use the statistical pseudo-random number generator, use the cryptorandom generator instead. In Java, this is the SecureRandom class.
- 

## Source Code Examples

### Java

#### Use of a weak pseudo-random number generator

```
Random random = new Random();  
  
long sessNum = random.nextLong();  
  
String sessionId = sessNum.toString();
```

### Cryptographically secure random number generator

```
SecureRandom random = new SecureRandom();

byte sessBytes[] = new byte[32];

random.nextBytes(sessBytes);

String sessionId = new String(sessBytes);
```

### Objc

#### Use of a weak pseudo-random number generator

```
long sessNum = rand();
NSString* sessionId = [NSString stringWithFormat:@"%ld", sessNum];
```

### Cryptographically secure random number generator

```
UInt32 sessBytes;
SecRandomCopyBytes(kSecRandomDefault, sizeof(sessBytes), (uint8_t*)&sessBytes);

NSString* sessionId = [NSString stringWithFormat:@"%llu", sessBytes];
```

### Swift

#### Use of a weak pseudo-random number generator

```
let sessNum = rand();
let sessionId = String(format:@"%ld", sessNum)
```

### Cryptographically secure random number generator

```
var sessBytes: UInt32 = 0
withUnsafeMutablePointer(&sessBytes, { (sessBytesPointer) -> Void in
    let castedPointer = unsafeBitCast(sessBytesPointer, UnsafeMutablePointer<UInt8>.self)
    SecRandomCopyBytes(kSecRandomDefault, sizeof(UInt32), castedPointer)
})

let sessionId = String(format:@"%llu", sessBytes)
```



# Unchecked Return Value

## Risk

### What might happen

A program that does not check function return values could cause the application to enter an undefined state. This could lead to unexpected behavior and unintended consequences, including inconsistent data, system crashes or other error-based exploits.

---

## Cause

### How does it happen

The application calls a system function, but does not receive or check the result of this function. These functions often return error codes in the result, or share other status codes with its caller. The application simply ignores this result value, losing this vital information.

---

## General Recommendations

### How to avoid it

- Always check the result of any called function that returns a value, and verify the result is an expected value.
  - Ensure the calling function responds to all possible return values.
  - Expect runtime errors and handle them gracefully. Explicitly define a mechanism for handling unexpected errors.
- 

## Source Code Examples

### CPP

#### Unchecked Memory Allocation

```
buff = (char*) malloc(size);
strncpy(buff, source, size);
```

#### Safer Memory Allocation

```
buff = (char*) malloc(size+1);
if (buff==NULL) exit(1);

strncpy(buff, source, size);
buff[size] = '\0';
```

## Use of sizeof() on a Pointer Type

**Weakness ID:** 467 (*Weakness Variant*)

**Status:** Draft

### Description

### Description Summary

The code calls sizeof() on a malloced pointer type, which always returns the wordsize/8. This can produce an unexpected result if the programmer intended to determine how much memory has been allocated.

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C

C++

### Common Consequences

Scope	Effect
Integrity	This error can often cause one to allocate a buffer that is much smaller than what is needed, leading to resultant weaknesses such as buffer overflows.

### Likelihood of Exploit

High

### Demonstrative Examples

#### Example 1

Care should be taken to ensure sizeof returns the size of the data structure itself, and not the size of the pointer to the data structure.

In this example, sizeof(foo) returns the size of the pointer.

*(Bad Code)*

*Example Languages: C and C++*

```
double *foo;
...
foo = (double *)malloc(sizeof(foo));
```

In this example, sizeof(\*foo) returns the size of the data structure and not the size of the pointer.

*(Good Code)*

*Example Languages: C and C++*

```
double *foo;
...
foo = (double *)malloc(sizeof(*foo));
```

#### Example 2

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

*(Bad Code)*

*/\* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. \*/*

```
char *username = "admin";
char *pass = "password";

int AuthenticateUser(char *inUser, char *inPass) {
```

```
printf("Sizeof username = %d\n", sizeof(username));
printf("Sizeof pass = %d\n", sizeof(pass));

if (strcmp(username, inUser, sizeof(username))) {
printf("Auth failure of username using sizeof\n");
return(AUTH_FAIL);
}
/* Because of CWE-467, the sizeof returns 4 on many platforms and architectures. */
if (! strcmp(pass, inPass, sizeof(pass))) {
printf("Auth success of password using sizeof\n");
return(AUTH_SUCCESS);
}
else {
printf("Auth fail of password using sizeof\n");
return(AUTH_FAIL);
}
}

int main (int argc, char **argv)
{
int authResult;

if (argc < 3) {
ExitError("Usage: Provide a username and password");
}
authResult = AuthenticateUser(argv[1], argv[2]);
if (authResult != AUTH_SUCCESS) {
ExitError("Authentication failed");
}
else {
DoAuthenticatedTask(argv[1]);
}
}
```

In `AuthenticateUser()`, because `sizeof()` is applied to a parameter with an array type, the `sizeof()` call might return 4 on many modern architectures. As a result, the `strcmp()` call only checks the first four characters of the input password, resulting in a partial comparison (CWE-187), leading to improper authentication (CWE-287).

Because of the partial comparison, any of these passwords would still cause authentication to succeed for the "admin" user:

*(Attack)*

```
pass5
passABCDEFGH
passWORD
```

Because only 4 characters are checked, this significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "adminXYZ" and "administrator" will succeed for the username.

## Potential Mitigations

### Phase: Implementation

Use expressions such as "`sizeof(*pointer)`" instead of "`sizeof(pointer)`", unless you intend to run `sizeof()` on a pointer type to gain some platform independence or if you are allocating a variable on the stack.

## Other Notes

The use of `sizeof()` on a pointer can sometimes generate useful information. An obvious case is to find out the wordsize on a platform. More often than not, the appearance of `sizeof(pointer)` indicates a bug.

## Weakness Ordinalities

Ordinality	Description
Primary	(where the weakness exists independent of other weaknesses)

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	465	<a href="#">Pointer Issues</a>	<b>Development Concepts (primary)699</b>
ChildOf	Weakness Class	682	<a href="#">Incorrect Calculation</a>	<b>Research Concepts (primary)1000</b>
ChildOf	Category	737	<a href="#">CERT C Secure Coding Section 03 - Expressions (EXP)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
CanPrecede	Weakness Base	131	<a href="#">Incorrect Calculation of Buffer Size</a>	Research Concepts1000

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Use of sizeof() on a pointer type
CERT C Secure Coding	ARR01-C		Do not apply the sizeof operator to a pointer when taking the size of an array
CERT C Secure Coding	EXP01-C		Do not take the size of a pointer to determine the size of the pointed-to type

## White Box Definitions

A weakness where code path has:

1. end statement that passes an identity of a dynamically allocated memory resource to a sizeof operator
2. start statement that allocates the dynamically allocated memory resource

## References

Robert Seacord. "EXP01-A. Do not take the sizeof a pointer to determine the size of a type".  
<https://www.securecoding.cert.org/confluence/display/seccode/EXP01-A.+Do+not+take+the+sizeof+a+pointer+to+determine+the+size+of+a+type>.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-01		KDM Analytics	External
	added/updated white box definitions		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities		
2008-11-24	CWE Content Team	MITRE	Internal
	updated Relationships, Taxonomy Mappings		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Demonstrative Examples		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Demonstrative Examples		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Relationships		

[BACK TO TOP](#)

# NULL Pointer Dereference

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

## Improper Validation of Array Index

**Weakness ID:** 129 (*Weakness Base*)

**Status:** Draft

### Description

### Description Summary

The product uses untrusted input when calculating or using an array index, but the product does not validate or incorrectly validates the index to ensure the index references a valid position within the array.

### Alternate Terms

out-of-bounds array index

index-out-of-range

array index underflow

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C: (*Often*)

C++: (*Often*)

### Language-independent

### Common Consequences

Scope	Effect
Integrity Availability	Unchecked array indexing will very likely result in the corruption of relevant memory and perhaps instructions, leading to a crash, if the values are outside of the valid memory area.
Integrity	If the memory corrupted is data, rather than instructions, the system will continue to function with improper values.
Confidentiality Integrity	Unchecked array indexing can also trigger out-of-bounds read or write operations, or operations on the wrong objects; i.e., "buffer overflows" are not always the result. This may result in the exposure or modification of sensitive data.
Integrity	If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow and possibly without the use of large inputs if a precise index can be controlled.
Integrity Availability Confidentiality	A single fault could allow either an overflow (CWE-788) or underflow (CWE-786) of the array index. What happens next will depend on the type of operation being performed out of bounds, but can expose sensitive information, cause a system crash, or possibly lead to arbitrary code execution.

### Likelihood of Exploit

High

### Detection Methods

#### Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report array index errors that originate from command line arguments in a program that is not expected to run with setuid or other special privileges.

**Effectiveness: High**

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

---

### Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

---

### Black Box

Black box methods might not get the needed code coverage within limited time constraints, and a dynamic test might not produce any noticeable side effects even if it is successful.

---

## Demonstrative Examples

### Example 1

The following C/C++ example retrieves the sizes of messages for a pop3 mail server. The message sizes are retrieved from a socket that returns in a buffer the message number and the message size, the message number (num) and size (size) are extracted from the buffer and the message size is placed into an array using the message number for the array index.

*(Bad Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;

    // read values from socket and added to sizes array
    while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
    {

        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
            break;
        else if (sscanf(buf, "%d %d", &num, &size) == 2)
            sizes[num - 1] = size;
        }
    ...
}
```

In this example the message number retrieved from the buffer could be a value that is outside the allowable range of indices for the array and could possibly be a negative number. Without proper validation of the value to be used for the array index an array overflow could occur and could potentially lead to unauthorized access to memory addresses and system crashes. The value of the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;

    // read values from socket and added to sizes array
    while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
    {

        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
```

```
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2) {
if (num > 0 && num <= (unsigned)count)
sizes[num - 1] = size;
else
/* warn about possible attempt to induce buffer overflow */
report(stderr, "Warning: ignoring bogus data for message sizes returned by server.\n");
}
}
...
}
```

## Example 2

In the code snippet below, an unchecked integer value is used to reference an object in an array.

*(Bad Code)*

*Example Language: Java*

```
public String getValue(int index) {
return array[index];
}
```

If index is outside of the range of the array, this may result in an `ArrayIndexOutOfBoundsException` Exception being raised.

## Example 3

In the following Java example the method `displayProductSummary` is called from a Web service servlet to retrieve product summary information for display to the user. The servlet obtains the integer value of the product number from the user and passes it to the `displayProductSummary` method. The `displayProductSummary` method passes the integer value of the product number to the `getProductSummary` method which obtains the product summary from the array object containing the project summaries using the integer value of the product number as the array index.

*(Bad Code)*

*Example Language: Java*

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");

try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
return products[index];
}
```

In this example the integer value used as the array index that is provided by the user may be outside the allowable range of indices for the array which may provide unexpected results or may cause the application to fail. The integer value used for the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

*Example Language: Java*

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");
```



```
try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
String productSummary = "";

if ((index >= 0) && (index < MAX_PRODUCTS)) {
productSummary = products[index];
}
else {
System.err.println("index is out of bounds");
throw new IndexOutOfBoundsException();
}

return productSummary;
}
```

An alternative in Java would be to use one of the collection objects such as `ArrayList` that will automatically generate an exception if an attempt is made to access an array index that is out of bounds.

*(Good Code)*

#### Example Language: Java

```
ArrayList productArray = new ArrayList(MAX_PRODUCTS);
...
try {
productSummary = (String) productArray.get(index);
} catch (IndexOutOfBoundsException ex) {...}
```

### Observed Examples

Reference	Description
<a href="#">CVE-2005-0369</a>	large ID in packet used as array index
<a href="#">CVE-2001-1009</a>	negative array index as argument to POP LIST command
<a href="#">CVE-2003-0721</a>	Integer signedness error leads to negative array index
<a href="#">CVE-2004-1189</a>	product does not properly track a count and a maximum number, which can lead to resultant array index overflow.
<a href="#">CVE-2007-5756</a>	chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error.

### Potential Mitigations

#### Phase: Architecture and Design

### Strategies: Input Validation; Libraries or Frameworks

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

---

#### Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

---

#### Phase: Requirements

### Strategy: Language Selection

Use a language with features that can automatically mitigate or eliminate out-of-bounds indexing errors.

---

For example, Ada allows the programmer to constrain the values of a variable and languages such as Java and Ruby will allow the programmer to handle exceptions when an out-of-bounds index is accessed.

#### Phase: Implementation

### Strategy: Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy (i.e., use a whitelist). Reject any input that does not strictly conform to specifications, or transform it into something that does. Use a blacklist to reject any unexpected inputs and detect potential attacks.

When accessing a user-controlled array index, use a stringent range of values that are within the target array. Make sure that you do not allow negative values to be used. That is, verify the minimum as well as the maximum of the range of acceptable values.

#### Phase: Implementation

Be especially careful to validate your input when you invoke code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

### Weakness Ordinalities

Ordinality	Description
Resultant	The most common condition situation leading to unchecked array indexing is the use of loop index variables as buffer indexes. If the end condition for the loop is subject to a flaw, the index can grow or shrink unbounded, therefore causing a buffer overflow or underflow. Another common situation leading to this condition is the use of a function's return value, or the resulting value of a calculation directly as an index in to a buffer.

### Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	20	<a href="#">Improper Input Validation</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	189	<a href="#">Numeric Errors</a>	Development Concepts699
ChildOf	Category	633	<a href="#">Weaknesses that Affect Memory</a>	<b>Resource-specific Weaknesses (primary)631</b>
ChildOf	Category	738	<a href="#">CERT C Secure Coding Section 04 - Integers (INT)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
ChildOf	Category	802	<a href="#">2010 Top 25 - Risky Resource Management</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
CanPrecede	Weakness Class	119	<a href="#">Failure to Constrain Operations within the Bounds of a Memory Buffer</a>	Research Concepts1000
CanPrecede	Weakness Variant	789	<a href="#">Uncontrolled Memory Allocation</a>	Research Concepts1000
PeerOf	Weakness Base	124	<a href="#">Buffer Underwrite ('Buffer Underflow')</a>	Research Concepts1000

### Theoretical Notes

An improperly validated array index might lead directly to the always-incorrect behavior of "access of array using out-of-bounds index."

### Affected Resources

## Memory

### f Causal Nature

### Explicit

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unchecked array indexing
PLOVER			INDEX - Array index overflow
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C		Guarantee that array indices are within the valid range
CERT C Secure Coding	ARR38-C		Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element
CERT C Secure Coding	INT32-C		Ensure that operations on signed integers do not result in overflow

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">100</a>	Overflow Buffers	

### References

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 5, "Array Indexing Errors" Page 144. 2nd Edition. Microsoft. 2002.

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Sean Eidemiller	Cigital	External
	added/updated demonstrative examples		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities		
2008-11-24	CWE Content Team	MITRE	Internal
	updated Relationships, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Description, Name, Relationships		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Observed Examples, Other Notes, Potential Mitigations, Theoretical Notes, Weakness Ordinalities		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Demonstrative Examples, Detection Factors, Likelihood of Exploit, Potential Mitigations, References, Related Attack Patterns, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Related Attack Patterns		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-10-29	Unchecked Array Indexing		

[BACK TO TOP](#)

# TOCTOU

## Risk

### What might happen

At best, a Race Condition may cause errors in accuracy, overridden values or unexpected behavior that may result in denial-of-service. At worst, it may allow attackers to retrieve data or bypass security processes by replaying a controllable Race Condition until it plays out in their favor.

---

## Cause

### How does it happen

Race Conditions occur when a public, single instance of a resource is used by multiple concurrent logical processes. If these logical processes attempt to retrieve and update the resource without a timely management system, such as a lock, a Race Condition will occur.

An example for when a Race Condition occurs is a resource that may return a certain value to a process for further editing, and then updated by a second process, resulting in the original process' data no longer being valid. Once the original process edits and updates the incorrect value back into the resource, the second process' update has been overwritten and lost.

---

## General Recommendations

### How to avoid it

When sharing resources between concurrent processes across the application ensure that these resources are either thread-safe, or implement a locking mechanism to ensure expected concurrent activity.

---

## Source Code Examples

### Java Different Threads Increment and Decrement The Same Counter Repeatedly, Resulting in a Race Condition

```
public static int counter = 0;
public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) {
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); //Will stop and return either -1 or 1 due to race
    condition over counter
}

public static class incrementCounter extends Thread {
    public void run() {
        counter++;
    }
}
```

```
}

public static class decrementCounter extends Thread {
    public void run() {
        counter--;
    }
}
```

### Different Threads Increment and Decrement The Same Thread-Safe Counter Repeatedly, Never Resulting in a Race Condition

```
public static int counter = 0;
public static Object lock = new Object();

public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) { // because of proper locking, this condition is never false
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); // Never reached
}

public static class incrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter++;
        }
    }
}

public static class decrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter--;
        }
    }
}
```

## Scanned Languages

Language	Hash Number	Change Date
CPP	4541647240435660	1/6/2025
Common	0105849645654507	1/6/2025