

## vul\_files\_36 Scan Report

Project Name	vul_files_36
Scan Start	Tuesday, January 7, 2025 7:04:08 PM
Preset	Checkmarx Default
Scan Time	04h:41m:42s
Lines Of Code Scanned	298602
Files Scanned	109
Report Creation Time	Tuesday, January 7, 2025 11:13:46 PM
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038</a>
Team	CxServer
Checkmarx Version	8.7.0
Scan Type	Full
Source Origin	LocalPath
Density	1/1000 (Vulnerabilities/LOC)
Visibility	Public

## Filter Settings

### **Severity**

Included: High, Medium, Low, Information

Excluded: None

### **Result State**

Included: Confirmed, Not Exploitable, To Verify, Urgent, Proposed Not Exploitable

Excluded: None

### **Assigned to**

Included: All

### **Categories**

Included:

Uncategorized	All
Custom	All
PCI DSS v3.2	All
OWASP Top 10 2013	All
FISMA 2014	All
NIST SP 800-53	All
OWASP Top 10 2017	All
OWASP Mobile Top 10 2016	All

Excluded:

Uncategorized	None
Custom	None
PCI DSS v3.2	None
OWASP Top 10 2013	None
FISMA 2014	None

NIST SP 800-53	None
OWASP Top 10 2017	None
OWASP Mobile Top 10 2016	None

**Results Limit**


Results limit per query was set to 50

**Selected Queries**


Selected queries are listed in [Result Summary](#)

---

## Result Summary




## Most Vulnerable Files



- nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
- nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
- nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
- nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c
- nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

## Top 5 Vulnerabilities



## Scan Summary - OWASP Top 10 2017

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2017](#)

Category	Threat Agent	Exploitability	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	App. Specific	EASY	COMMON	EASY	SEVERE	App. Specific	106	90
A2-Broken Authentication	App. Specific	EASY	COMMON	AVERAGE	SEVERE	App. Specific	12	12
A3-Sensitive Data Exposure	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	App. Specific	0	0
A4-XML External Entities (XXE)	App. Specific	AVERAGE	COMMON	EASY	SEVERE	App. Specific	0	0
A5-Broken Access Control*	App. Specific	AVERAGE	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A6-Security Misconfiguration	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A7-Cross-Site Scripting (XSS)	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A8-Insecure Deserialization	App. Specific	DIFFICULT	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A9-Using Components with Known Vulnerabilities*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	MODERATE	App. Specific	60	60
A10-Insufficient Logging & Monitoring	App. Specific	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	App. Specific	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - OWASP Top 10 2013

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2013](#)

Category	Threat Agent	Attack Vectors	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	AVERAGE	SEVERE	ALL DATA	0	0
A2-Broken Authentication and Session Management	EXTERNAL, INTERNAL USERS	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	AFFECTED DATA AND FUNCTIONS	0	0
A3-Cross-Site Scripting (XSS)	EXTERNAL, INTERNAL, ADMIN USERS	AVERAGE	VERY WIDESPREAD	EASY	MODERATE	AFFECTED DATA AND SYSTEM	0	0
A4-Insecure Direct Object References	SYSTEM USERS	EASY	COMMON	EASY	MODERATE	EXPOSED DATA	0	0
A5-Security Misconfiguration	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	EASY	MODERATE	ALL DATA AND SYSTEM	0	0
A6-Sensitive Data Exposure	EXTERNAL, INTERNAL, ADMIN USERS, USERS BROWSERS	DIFFICULT	UNCOMMON	AVERAGE	SEVERE	EXPOSED DATA	0	0
A7-Missing Function Level Access Control*	EXTERNAL, INTERNAL USERS	EASY	COMMON	AVERAGE	MODERATE	EXPOSED DATA AND FUNCTIONS	0	0
A8-Cross-Site Request Forgery (CSRF)	USERS BROWSERS	AVERAGE	COMMON	EASY	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A9-Using Components with Known Vulnerabilities*	EXTERNAL USERS, AUTOMATED TOOLS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	60	60
A10-Unvalidated Redirects and Forwards	USERS BROWSERS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - PCI DSS v3.2

Category	Issues Found	Best Fix Locations
PCI DSS (3.2) - 6.5.1 - Injection flaws - particularly SQL injection	0	0
PCI DSS (3.2) - 6.5.2 - Buffer overflows	51	51
PCI DSS (3.2) - 6.5.3 - Insecure cryptographic storage	0	0
PCI DSS (3.2) - 6.5.4 - Insecure communications	0	0
PCI DSS (3.2) - 6.5.5 - Improper error handling*	0	0
PCI DSS (3.2) - 6.5.7 - Cross-site scripting (XSS)	0	0
PCI DSS (3.2) - 6.5.8 - Improper access control	0	0
PCI DSS (3.2) - 6.5.9 - Cross-site request forgery	0	0
PCI DSS (3.2) - 6.5.10 - Broken authentication and session management	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - FISMA 2014

Category	Description	Issues Found	Best Fix Locations
Access Control	Organizations must limit information system access to authorized users, processes acting on behalf of authorized users, or devices (including other information systems) and to the types of transactions and functions that authorized users are permitted to exercise.	0	0
Audit And Accountability*	Organizations must: (i) create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity; and (ii) ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.	0	0
Configuration Management	Organizations must: (i) establish and maintain baseline configurations and inventories of organizational information systems (including hardware, software, firmware, and documentation) throughout the respective system development life cycles; and (ii) establish and enforce security configuration settings for information technology products employed in organizational information systems.	0	0
Identification And Authentication*	Organizations must identify information system users, processes acting on behalf of users, or devices and authenticate (or verify) the identities of those users, processes, or devices, as a prerequisite to allowing access to organizational information systems.	12	12
Media Protection	Organizations must: (i) protect information system media, both paper and digital; (ii) limit access to information on information system media to authorized users; and (iii) sanitize or destroy information system media before disposal or release for reuse.	0	0
System And Communications Protection	Organizations must: (i) monitor, control, and protect organizational communications (i.e., information transmitted or received by organizational information systems) at the external boundaries and key internal boundaries of the information systems; and (ii) employ architectural designs, software development techniques, and systems engineering principles that promote effective information security within organizational information systems.	0	0
System And Information Integrity	Organizations must: (i) identify, report, and correct information and information system flaws in a timely manner; (ii) provide protection from malicious code at appropriate locations within organizational information systems; and (iii) monitor information system security alerts and advisories and take appropriate actions in response.	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - NIST SP 800-53

Category	Issues Found	Best Fix Locations
AC-12 Session Termination (P2)	0	0
AC-3 Access Enforcement (P1)	12	12
AC-4 Information Flow Enforcement (P1)	0	0
AC-6 Least Privilege (P1)	0	0
AU-9 Protection of Audit Information (P1)	0	0
CM-6 Configuration Settings (P2)	0	0
IA-5 Authenticator Management (P1)	0	0
IA-6 Authenticator Feedback (P2)	0	0
IA-8 Identification and Authentication (Non-Organizational Users) (P1)	0	0
SC-12 Cryptographic Key Establishment and Management (P1)	0	0
SC-13 Cryptographic Protection (P1)	0	0
SC-17 Public Key Infrastructure Certificates (P1)	0	0
SC-18 Mobile Code (P2)	0	0
SC-23 Session Authenticity (P1)*	0	0
SC-28 Protection of Information at Rest (P1)	0	0
SC-4 Information in Shared Resources (P1)	0	0
SC-5 Denial of Service Protection (P1)*	141	76
SC-8 Transmission Confidentiality and Integrity (P1)	0	0
SI-10 Information Input Validation (P1)*	36	36
SI-11 Error Handling (P2)*	0	0
SI-15 Information Output Filtering (P0)	0	0
SI-16 Memory Protection (P1)	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.



## Scan Summary - OWASP Mobile Top 10 2016

Category	Description	Issues Found	Best Fix Locations
M1-Improper Platform Usage	This category covers misuse of a platform feature or failure to use platform security controls. It might include Android intents, platform permissions, misuse of TouchID, the Keychain, or some other security control that is part of the mobile operating system. There are several ways that mobile apps can experience this risk.	0	0
M2-Insecure Data Storage	This category covers insecure data storage and unintended data leakage.	0	0
M3-Insecure Communication	This category covers poor handshaking, incorrect SSL versions, weak negotiation, cleartext communication of sensitive assets, etc.	0	0
M4-Insecure Authentication	This category captures notions of authenticating the end user or bad session management. This can include: -Failing to identify the user at all when that should be required -Failure to maintain the user's identity when it is required -Weaknesses in session management	0	0
M5-Insufficient Cryptography	The code applies cryptography to a sensitive information asset. However, the cryptography is insufficient in some way. Note that anything and everything related to TLS or SSL goes in M3. Also, if the app fails to use cryptography at all when it should, that probably belongs in M2. This category is for issues where cryptography was attempted, but it wasn't done correctly.	0	0
M6-Insecure Authorization	This is a category to capture any failures in authorization (e.g., authorization decisions in the client side, forced browsing, etc.). It is distinct from authentication issues (e.g., device enrolment, user identification, etc.). If the app does not authenticate users at all in a situation where it should (e.g., granting anonymous access to some resource or service when authenticated and authorized access is required), then that is an authentication failure not an authorization failure.	0	0
M7-Client Code Quality	This category is the catch-all for code-level implementation problems in the mobile client. That's distinct from server-side coding mistakes. This would capture things like buffer overflows, format string vulnerabilities, and various other code-level mistakes where the solution is to rewrite some code that's running on the mobile device.	0	0
M8-Code Tampering	This category covers binary patching, local resource modification, method hooking, method swizzling, and dynamic memory modification. Once the application is delivered to the mobile device, the code and data resources are resident there. An attacker can either directly modify the code, change the contents of memory dynamically, change or replace the system APIs that the application uses, or	0	0

	modify the application's data and resources. This can provide the attacker a direct method of subverting the intended use of the software for personal or monetary gain.		
M9-Reverse Engineering	This category includes analysis of the final core binary to determine its source code, libraries, algorithms, and other assets. Software such as IDA Pro, Hopper, otool, and other binary inspection tools give the attacker insight into the inner workings of the application. This may be used to exploit other nascent vulnerabilities in the application, as well as revealing information about back end servers, cryptographic constants and ciphers, and intellectual property.	0	0
M10-Extraneous Functionality	Often, developers include hidden backdoor functionality or other internal development security controls that are not intended to be released into a production environment. For example, a developer may accidentally include a password as a comment in a hybrid app. Another example includes disabling of 2-factor authentication during testing.	0	0

## Scan Summary - Custom


Category	Issues Found	Best Fix Locations
Must audit	0	0
Check	0	0
Optional	0	0

## Results Distribution By Status

First scan of the project

	High	Medium	Low	Information	Total
New Issues	0	197	200	0	397
Recurrent Issues	0	0	0	0	0
Total	0	197	200	0	397

Fixed Issues	0	0	0	0	0
--------------	---	---	---	---	---



## Results Distribution By State

	High	Medium	Low	Information	Total
Confirmed	0	0	0	0	0
Not Exploitable	0	0	0	0	0
To Verify	0	197	200	0	397
Urgent	0	0	0	0	0
Proposed Not Exploitable	0	0	0	0	0
Total	0	197	200	0	397

## Result Summary

Vulnerability Type	Occurrences	Severity
<a href="#">Use of Zero Initialized Pointer</a>	86	Medium
<a href="#">Dangerous Functions</a>	60	Medium
<a href="#">Buffer Overflow boundcpy WrongSizeParam</a>	51	Medium
<a href="#">Use of Sizeof On a Pointer Type</a>	89	Low
<a href="#">NULL Pointer Dereference</a>	55	Low

<a href="#">Unchecked Array Index</a>	36	Low
<a href="#">Improper Resource Access Authorization</a>	12	Low
<a href="#">TOCTOU</a>	8	Low

## 10 Most Vulnerable Files

### High and Medium Vulnerabilities

File Name	Issues Found
nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	16
nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	16
nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	16
nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	16
nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	10
nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	10
nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	10
nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	8
nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	8
nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	8

# Scan Results Details

## Use of Zero Initialized Pointer

Query Path:

CPP\Cx\CPP Medium Threat\Use of Zero Initialized Pointer Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

### Description

#### Use of Zero Initialized Pointer\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=292">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=292</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 2309 is not initialized when it is used by item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 3258.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	2364	3366
Object	item	item

### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2364.         session->aob.item = NULL;
```



File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3366.         aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=293">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=293</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 2309 is not initialized when it is used by item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 3258.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	2383	3366
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....  
2383.         session->aob.item = NULL;
```



File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....  
3366.         aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 3:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=294>  
Status New

The variable declared in item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 405 is not initialized when it is used by item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 3258.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	411	3366
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....  
411.         aob->item = NULL;
```



Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=295">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=295</a>
Status	New

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	411	2310
Object	item	item

File Name	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Method	static void active_outbound_item_reset(nghttp2_active_outbound_item *aob,  ..... 411.       aob->item = NULL;
	▼
File Name	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Method	static int session_prep_frame(nghttp2_session *session,  ..... 2310.                               nghttp2_outbound_item *item) {

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=296">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=296</a>
Status	New

Source	Destination
--------	-------------



File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	2383	2310
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```

....
2383.         session->aob.item = NULL;
....
2310.         nghttp2_outbound_item *item) {

```

#### Use of Zero Initialized Pointer\Path 6:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=297">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=297</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 2309 is not initialized when it is used by item at nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c in line 2309.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	2364	2310
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```

....
2364.         session->aob.item = NULL;
....
2310.         nghttp2_outbound_item *item) {

```

#### Use of Zero Initialized Pointer\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=298">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=298</a>
Status	New

The variable declared in `closed_next` at `nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c` in line 1605 is not initialized when it is used by `idle_stream_tail` at `nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c` in line 1589.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	1628	1600
Object	closed_next	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....  
1628.     stream->closed_next = NULL;
```



File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....  
1600.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 8:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=299>

Status New

The variable declared in `closed_prev` at `nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c` in line 1605 is not initialized when it is used by `idle_stream_tail` at `nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c` in line 1589.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	1627	1600
Object	closed_prev	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....  
1627.     stream->closed_prev = NULL;
```

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....  
1600.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 9:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=300>  
Status New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	2344	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....  
2344.     session->aob.item = NULL;
```

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....  
3316.     aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 10:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=301>  
Status New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	2359	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2359.         session->aob.item = NULL;
```



File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3316.         aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=302">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=302</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 406 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	412	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
412.         aob->item = NULL;
```



File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3316.          aob->item = item;
```

### Use of Zero Initialized Pointer\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=303">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=303</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 406 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	412	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
 Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
412.      aob->item = NULL;
```

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
 Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2300.          nghttp2_outbound_item *item) {
```

### Use of Zero Initialized Pointer\Path 13:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=304">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=304</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Line	2359	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2359.         session->aob.item = NULL;
....
2300.         nghttp2_outbound_item *item) {
```

#### Use of Zero Initialized Pointer\Path 14:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=305>

Status New

The variable declared in item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	2344	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2344.         session->aob.item = NULL;
....
2300.         nghttp2_outbound_item *item) {
```

#### Use of Zero Initialized Pointer\Path 15:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=306>

Status New

The variable declared in closed\_prev at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 1600 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 1584.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	1622	1595
Object	closed_prev	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1622.     stream->closed_prev = NULL;
```

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....
1595.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 16:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=307">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=307</a>
Status	New

The variable declared in closed\_next at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 1600 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c in line 1584.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	1623	1595
Object	closed_next	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1623.     stream->closed_next = NULL;
```

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....  
1595.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 17:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=308>

Status New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	2344	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....  
2344.     session->aob.item = NULL;
```



File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....  
3316.     aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 18:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=309>

Status New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-	nghttp2@@nghttp2-v1.59.0-CVE-2020-



	11080-FP.c	11080-FP.c
Line	2359	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2359.         session->aob.item = NULL;
```



File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3316.         aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 19:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=310">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=310</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 406 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 3208.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	412	3316
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
412.         aob->item = NULL;
```



File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static ssize\_t nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3316.          aob->item = item;
```

### Use of Zero Initialized Pointer\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=311">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=311</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 406 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	412	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
412.      aob->item = NULL;
```

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2300.          nghttp2_outbound_item *item) {
```

### Use of Zero Initialized Pointer\Path 21:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=312">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=312</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Line	2359	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2359.         session->aob.item = NULL;
....
2300.         nghttp2_outbound_item *item) {
```

#### Use of Zero Initialized Pointer\Path 22:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=313">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=313</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299 is not initialized when it is used by item at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 2299.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	2344	2300
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2344.         session->aob.item = NULL;
....
2300.         nghttp2_outbound_item *item) {
```

#### Use of Zero Initialized Pointer\Path 23:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=314">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=314</a>
Status	New

The variable declared in closed\_next at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 1600 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 1584.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	1623	1595
Object	closed_next	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1623.     stream->closed_next = NULL;
```

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....
1595.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 24:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=315">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=315</a>
Status	New

The variable declared in closed\_prev at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 1600 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c in line 1584.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	1622	1595
Object	closed_prev	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1622.     stream->closed_prev = NULL;
```

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....
1595.     session->idle_stream_tail = stream;
```

### Use of Zero Initialized Pointer\Path 25:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=316">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=316</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 3242.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	2375	3350
Object	item	item

### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2375.     session->aob.item = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static nghttp2\_ssize nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3350.     aob->item = item;
```

### Use of Zero Initialized Pointer\Path 26:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=317">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=317</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 3242.

Source	Destination
--------	-------------

File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	2390	3350
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2390.         session->aob.item = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static nghttp2\_ssize nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3350.         aob->item = item;
```

#### Use of Zero Initialized Pointer\Path 27:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=318">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=318</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 407 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 3242.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	413	3350
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
413.         aob->item = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static nghttp2\_ssize nghttp2\_session\_mem\_send\_internal(nghttp2\_session \*session,

```
....
3350.          aob->item = item;
```

### Use of Zero Initialized Pointer\Path 28:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=319">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=319</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 407 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	413	2331
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static void active\_outbound\_item\_reset(nghttp2\_active\_outbound\_item \*aob,

```
....
413.      aob->item = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```
....
2331.          nghttp2_outbound_item *item) {
```

### Use of Zero Initialized Pointer\Path 29:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=320">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=320</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Line	2375	2331
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```

.....
2375.         session->aob.item = NULL;
.....
2331.         nghttp2_outbound_item *item) {

```

#### Use of Zero Initialized Pointer\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=321">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=321</a>
Status	New

The variable declared in item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330 is not initialized when it is used by item at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 2330.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	2390	2331
Object	item	item

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static int session\_prep\_frame(nghttp2\_session \*session,

```

.....
2390.         session->aob.item = NULL;
.....
2331.         nghttp2_outbound_item *item) {

```

#### Use of Zero Initialized Pointer\Path 31:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=322">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=322</a>
Status	New

The variable declared in closed\_prev at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 1620 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 1604.



	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	1642	1615
Object	closed_prev	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1642.     stream->closed_prev = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_keep\_idle\_stream(nghttp2\_session \*session,

```
....
1615.     session->idle_stream_tail = stream;
```

#### Use of Zero Initialized Pointer\Path 32:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=323">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=323</a>
Status	New

The variable declared in closed\_next at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 1620 is not initialized when it is used by idle\_stream\_tail at nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c in line 1604.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	1643	1615
Object	closed_next	idle_stream_tail

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method void nghttp2\_session\_detach\_idle\_stream(nghttp2\_session \*session,

```
....
1643.     stream->closed_next = NULL;
```

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Method void nhttp2\_session\_keep\_idle\_stream(nhttp2\_session \*session,

```
....  
1615.     session->idle_stream_tail = stream;
```

### Use of Zero Initialized Pointer\Path 33:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=324>

Status New

The variable declared in next at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2445	2449
Object	next	next

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2445.         pr->next = NULL;  
....  
2449.         p->next = pr;
```

### Use of Zero Initialized Pointer\Path 34:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=325>

Status New

The variable declared in out at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2444	2449
Object	out	next

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2444.         pr->out = NULL;
....
2449.         p->next = pr;
```

### Use of Zero Initialized Pointer\Path 35:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=326>  
Status New

The variable declared in content\_handler at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 2554 is not initialized when it is used by content\_handler at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 1303.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2600	1380
Object	content_handler	content_handler

### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....
2600.         r->content_handler = NULL;
```



File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_update\_location\_config(ngx\_http\_request\_t \*r)

```
....
1380.         r->content_handler = clcf->handler;
```

### Use of Zero Initialized Pointer\Path 36:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=327>  
Status New

The variable declared in out at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2444	2449
Object	out	next

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2444.          pr->out = NULL;  
....  
2449.          p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 37:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=328">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=328</a>
Status	New

The variable declared in next at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2445	2449
Object	next	next

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2445.          pr->next = NULL;  
....  
2449.          p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 38:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=329">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=329</a>
Status	New

The variable declared in `content_handler` at `nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c` in line 2554 is not initialized when it is used by `content_handler` at `nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c` in line 1303.

	Source	Destination
File	<code>nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c</code>	<code>nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c</code>
Line	2600	1380
Object	<code>content_handler</code>	<code>content_handler</code>

#### Code Snippet

File Name `nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c`  
 Method `ngx_http_named_location(ngx_http_request_t *r, ngx_str_t *name)`

```
....
2600.             r->content_handler = NULL;
```



File Name `nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c`  
 Method `ngx_http_update_location_config(ngx_http_request_t *r)`

```
....
1380.             r->content_handler = clcf->handler;
```

#### Use of Zero Initialized Pointer\Path 39:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=330">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=330</a>
Status	New

The variable declared in `out` at `nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c` in line 2315 is not initialized when it is used by `next` at `nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c` in line 2315.

	Source	Destination
File	<code>nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c</code>	<code>nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c</code>
Line	2444	2449
Object	<code>out</code>	<code>next</code>

#### Code Snippet

File Name `nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c`  
 Method `ngx_http_subrequest(ngx_http_request_t *r,`

```

.....
2444.          pr->out = NULL;
.....
2449.          p->next = pr;

```

#### Use of Zero Initialized Pointer\Path 40:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=331">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=331</a>
Status	New

The variable declared in next at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2445	2449
Object	next	next

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```

.....
2445.          pr->next = NULL;
.....
2449.          p->next = pr;

```

#### Use of Zero Initialized Pointer\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=332">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=332</a>
Status	New

The variable declared in content\_handler at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 2554 is not initialized when it is used by content\_handler at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 1303.

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2600	1380
Object	content_handler	content_handler

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....
2600.                r->content_handler = NULL;
```



File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_update\_location\_config(ngx\_http\_request\_t \*r)

```
....
1380.                r->content_handler = clcf->handler;
```

#### Use of Zero Initialized Pointer\Path 42:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=333>  
Status New

The variable declared in out at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2444	2449
Object	out	next

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2444.                pr->out = NULL;
....
2449.                p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 43:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=334>  
Status New

The variable declared in next at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 2315 is not initialized when it is used by next at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 2315.

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2445	2449
Object	next	next

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2445.         pr->next = NULL;
....
2449.         p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 44:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=335">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=335</a>
Status	New

The variable declared in content\_handler at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 2554 is not initialized when it is used by content\_handler at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 1303.

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2600	1380
Object	content_handler	content_handler

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....
2600.         r->content_handler = NULL;
```

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_update\_location\_config(ngx\_http\_request\_t \*r)

```
....
1380.         r->content_handler = clcf->handler;
```

#### Use of Zero Initialized Pointer\Path 45:



Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=336">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=336</a>
Status	New

The variable declared in out at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2318 is not initialized when it is used by next at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2318.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2447	2452
Object	out	next

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2447.         pr->out = NULL;  
....  
2452.         p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 46:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=337">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=337</a>
Status	New

The variable declared in next at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2318 is not initialized when it is used by next at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2318.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2448	2452
Object	next	next

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2448.         pr->next = NULL;  
....  
2452.         p->next = pr;
```

#### Use of Zero Initialized Pointer\Path 47:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=338">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=338</a>
Status	New

The variable declared in content\_handler at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2557 is not initialized when it is used by content\_handler at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 1305.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2603	1382
Object	content_handler	content_handler

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....  
2603.             r->content_handler = NULL;
```



File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_update\_location\_config(ngx\_http\_request\_t \*r)

```
....  
1382.             r->content_handler = clcf->handler;
```

#### Use of Zero Initialized Pointer\Path 48:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=339">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=339</a>
Status	New

The variable declared in headers at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717 is not initialized when it is used by next at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2733	2735
Object	headers	next

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_get\_forwarded\_addr(ngx\_http\_request\_t \*r, ngx\_addr\_t \*addr,

```
....
2733.         for (h = headers, headers = NULL; h; h = next) {
....
2735.             h->next = headers;
```

**Use of Zero Initialized Pointer\Path 49:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=340>

Status New

The variable declared in headers at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717 is not initialized when it is used by headers at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2768	2771
Object	headers	headers

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_get\_forwarded\_addr(ngx\_http\_request\_t \*r, ngx\_addr\_t \*addr,

```
....
2768.         for (h = headers, headers = NULL; h; h = next) {
....
2771.             headers = h;
```

**Use of Zero Initialized Pointer\Path 50:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=341>

Status New

The variable declared in headers at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717 is not initialized when it is used by headers at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 2717.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Line	2733	2771
Object	headers	headers

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_get\_forwarded\_addr(ngx\_http\_request\_t \*r, ngx\_addr\_t \*addr,

```
....
2733.         for (h = headers, headers = NULL; h; h = next) {
....
2771.             headers = h;
```

## Dangerous Functions

Query Path:

CPP\Cx\CPP Medium Threat\Dangerous Functions Version:1

### Categories

OWASP Top 10 2013: A9-Using Components with Known Vulnerabilities

OWASP Top 10 2017: A9-Using Components with Known Vulnerabilities

### Description

#### Dangerous Functions\Path 1:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=52>

Status New

The dangerous function, memcpy, was found in use at line 433 in nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	527	527
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....
527.         memcpy((*session_ptr)->user_rcv_ext_types, option-
>user_rcv_ext_types,
```

#### Dangerous Functions\Path 2:

Severity Medium

Result State To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=53">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=53</a>
Status	New

The dangerous function, memcpy, was found in use at line 7469 in nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	7493	7493
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method int nghttp2\_session\_add\_goaway(nghttp2\_session \*session, int32\_t last\_stream\_id,

```
....  
7493.      memcpy(opaque_data_copy, opaque_data, opaque_data_len);
```

#### Dangerous Functions\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=54">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=54</a>
Status	New

The dangerous function, memcpy, was found in use at line 32 in nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	34	34
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint16be(uint8\_t \*buf, uint16\_t n) {

```
....  
34.      memcpy(buf, &x, sizeof(uint16_t));
```

#### Dangerous Functions\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=55">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=55</a>
Status	New

The dangerous function, memcpy, was found in use at line 37 in nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	39	39
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint32be(uint8\_t \*buf, uint32\_t n) {

```
....  
39.     memcpy(buf, &x, sizeof(uint32_t));
```

#### Dangerous Functions\Path 5:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=56">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=56</a>
Status	New

The dangerous function, memcpy, was found in use at line 42 in nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	44	44
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method uint16\_t nghttp2\_get\_uint16(const uint8\_t \*data) {

```
....  
44.     memcpy(&n, data, sizeof(uint16_t));
```

**Dangerous Functions\Path 6:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=57">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=57</a>
Status	New

The dangerous function, memcpy, was found in use at line 48 in nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	50	50
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method uint32\_t nghttp2\_get\_uint32(const uint8\_t \*data) {

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

**Dangerous Functions\Path 7:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=58">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=58</a>
Status	New

The dangerous function, memcpy, was found in use at line 760 in nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	765	765
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.     memcpy(dest, src, len);
```

**Dangerous Functions\Path 8:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=59">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=59</a>
Status	New

The dangerous function, memcpy, was found in use at line 434 in nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	532	532
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....  
532.         memcpy((*session_ptr)->user_rcv_ext_types, option-  
>user_rcv_ext_types,
```

**Dangerous Functions\Path 9:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=60">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=60</a>
Status	New

The dangerous function, memcpy, was found in use at line 7413 in nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	7437	7437
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c  
Method int nghttp2\_session\_add\_goaway(nghttp2\_session \*session, int32\_t last\_stream\_id,



```
....  
7437.      memcpy(opaque_data_copy, opaque_data, opaque_data_len);
```

### Dangerous Functions\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=61">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=61</a>
Status	New

The dangerous function, memcpy, was found in use at line 32 in nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	34	34
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint16be(uint8\_t \*buf, uint16\_t n) {

```
....  
34.      memcpy(buf, &x, sizeof(uint16_t));
```

### Dangerous Functions\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=62">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=62</a>
Status	New

The dangerous function, memcpy, was found in use at line 37 in nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	39	39
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c

Method void nghttp2\_put\_uint32be(uint8\_t \*buf, uint32\_t n) {

```
....  
39.     memcpy(buf, &x, sizeof(uint32_t));
```

### Dangerous Functions\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=63">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=63</a>
Status	New

The dangerous function, memcpy, was found in use at line 42 in nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	44	44
Object	memcpy	memcpy

### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method uint16\_t nghttp2\_get\_uint16(const uint8\_t \*data) {

```
....  
44.     memcpy(&n, data, sizeof(uint16_t));
```

### Dangerous Functions\Path 13:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=64">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=64</a>
Status	New

The dangerous function, memcpy, was found in use at line 48 in nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	50	50
Object	memcpy	memcpy

### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method uint32\_t nghttp2\_get\_uint32(const uint8\_t \*data) {

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

#### Dangerous Functions\Path 14:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=65>  
Status New

The dangerous function, memcpy, was found in use at line 760 in nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	765	765
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.     memcpy(dest, src, len);
```

#### Dangerous Functions\Path 15:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=66>  
Status New

The dangerous function, memcpy, was found in use at line 434 in nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	532	532
Object	memcpy	memcpy

## Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....  
532.          memcpy((*session_ptr)->user_rcv_ext_types, option-  
>user_rcv_ext_types,
```

**Dangerous Functions\Path 16:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=67>

Status New

The dangerous function, memcpy, was found in use at line 7413 in nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	7437	7437
Object	memcpy	memcpy

## Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method int nghttp2\_session\_add\_goway(nghttp2\_session \*session, int32\_t last\_stream\_id,

```
....  
7437.          memcpy(opaque_data_copy, opaque_data, opaque_data_len);
```

**Dangerous Functions\Path 17:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=68>

Status New

The dangerous function, memcpy, was found in use at line 32 in nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	34	34

Object	memcpy	memcpy
--------	--------	--------

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c

Method void nghttp2\_put\_uint16be(uint8\_t \*buf, uint16\_t n) {

```
....  
34.     memcpy(buf, &x, sizeof(uint16_t));
```

#### Dangerous Functions\Path 18:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=69>

Status New

The dangerous function, memcpy, was found in use at line 37 in nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	39	39
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c

Method void nghttp2\_put\_uint32be(uint8\_t \*buf, uint32\_t n) {

```
....  
39.     memcpy(buf, &x, sizeof(uint32_t));
```

#### Dangerous Functions\Path 19:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=70>

Status New

The dangerous function, memcpy, was found in use at line 42 in nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c

Line	44	44
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method uint16\_t nghttp2\_get\_uint16(const uint8\_t \*data) {

```
....  
44.     memcpy(&n, data, sizeof(uint16_t));
```

**Dangerous Functions\Path 20:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=71">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=71</a>
Status	New

The dangerous function, memcpy, was found in use at line 48 in nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	50	50
Object	memcpy	memcpy

**Code Snippet**

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method uint32\_t nghttp2\_get\_uint32(const uint8\_t \*data) {

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

**Dangerous Functions\Path 21:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=72">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=72</a>
Status	New

The dangerous function, memcpy, was found in use at line 760 in nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-	nghttp2@@nghttp2-v1.59.0-CVE-2024-

	28182-TP.c	28182-TP.c
Line	765	765
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c

Method uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.     memcpy(dest, src, len);
```

#### Dangerous Functions\Path 22:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=73>

Status New

The dangerous function, memcpy, was found in use at line 435 in nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	534	534
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....  
534.     memcpy((*session_ptr)->user_rcv_ext_types, option-  
>user_rcv_ext_types,
```

#### Dangerous Functions\Path 23:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=74>

Status New

The dangerous function, memcpy, was found in use at line 7476 in nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	7500	7500
Object	memcpy	memcpy

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method int nghttp2\_session\_add\_goaway(nghttp2\_session \*session, int32\_t last\_stream\_id,

```
....  
7500.      memcpy(opaque_data_copy, opaque_data, opaque_data_len);
```

#### Dangerous Functions\Path 24:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=75">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=75</a>
Status	New

The dangerous function, memcpy, was found in use at line 1436 in nginx@@njs-0.3.9-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	1466	1466
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1466.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 25:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=76">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=76</a>
Status	New

The dangerous function, memcpy, was found in use at line 1436 in nginx@@njs-0.3.9-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.



	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	1467	1467
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1467.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 26:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=77>

Status New

The dangerous function, memcpy, was found in use at line 1436 in nginx@@njs-0.3.9-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	1466	1466
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1466.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 27:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=78>

Status New

The dangerous function, memcpy, was found in use at line 1436 in nginx@@njs-0.3.9-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	1467	1467
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1467.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 28:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=79>

Status New

The dangerous function, memcpy, was found in use at line 264 in nginx@@njs-0.3.9-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	274	274
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....  
274.      memcpy(file.start, info->name.start, file.length);
```

#### Dangerous Functions\Path 29:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=80>

Status New

The dangerous function, memcpy, was found in use at line 337 in nginx@@njs-0.3.9-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	373	373
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_read(njs\_vm\_t \*vm, int fd, njs\_str\_t \*text)

```
....  
373.      memcpy(p, NJS_MODULE_END, njs_length(NJS_MODULE_END));
```

#### Dangerous Functions\Path 30:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=81>

Status New

The dangerous function, memcpy, was found in use at line 425 in nginx@@njs-0.3.9-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	453	453
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
453.      memcpy(module, shared, sizeof(njs_module_t));
```

#### Dangerous Functions\Path 31:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=82>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.4.2-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

### Dangerous Functions\Path 32:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=83>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.4.2-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

### Dangerous Functions\Path 33:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=84>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.4.2-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 34:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=85>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.4.2-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 35:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=86>

Status New

The dangerous function, memcpy, was found in use at line 328 in nginx@@njs-0.4.2-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-29379-TP.c	nginx@@njs-0.4.2-CVE-2022-29379-TP.c
Line	338	338
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....  
338.         memcpy(file.start, info->name.start, file.length);
```

#### Dangerous Functions\Path 36:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=87>

Status New

The dangerous function, memcpy, was found in use at line 474 in nginx@@njs-0.4.2-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-29379-TP.c	nginx@@njs-0.4.2-CVE-2022-29379-TP.c
Line	502	502
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-29379-TP.c

Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
502.         memcpy(module, shared, sizeof(njs_module_t));
```

#### Dangerous Functions\Path 37:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=88>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.0-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 38:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=89>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.0-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 39:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=90>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.0-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 40:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=91>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.0-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 41:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=92>

Status New

The dangerous function, memcpy, was found in use at line 328 in nginx@@njs-0.5.0-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.



	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-29379-TP.c	nginx@@njs-0.5.0-CVE-2022-29379-TP.c
Line	338	338
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....  
338.         memcpy(file.start, info->name.start, file.length);
```

#### Dangerous Functions\Path 42:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=93>

Status New

The dangerous function, memcpy, was found in use at line 474 in nginx@@njs-0.5.0-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-29379-TP.c	nginx@@njs-0.5.0-CVE-2022-29379-TP.c
Line	502	502
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-29379-TP.c

Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
502.         memcpy(module, shared, sizeof(njs_module_t));
```

#### Dangerous Functions\Path 43:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=94>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.2-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2021-46461-TP.c	nginx@@njs-0.5.2-CVE-2021-46461-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 44:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=95>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.2-CVE-2021-46461-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2021-46461-TP.c	nginx@@njs-0.5.2-CVE-2021-46461-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 45:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=96>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.2-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-28049-TP.c	nginx@@njs-0.5.2-CVE-2022-28049-TP.c
Line	1472	1472
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Dangerous Functions\Path 46:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=97>

Status New

The dangerous function, memcpy, was found in use at line 1442 in nginx@@njs-0.5.2-CVE-2022-28049-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-28049-TP.c	nginx@@njs-0.5.2-CVE-2022-28049-TP.c
Line	1473	1473
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Dangerous Functions\Path 47:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=98>

Status New

The dangerous function, memcpy, was found in use at line 328 in nginx@@njs-0.5.2-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-29379-TP.c	nginx@@njs-0.5.2-CVE-2022-29379-TP.c
Line	338	338
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....  
338.      memcpy(file.start, info->name.start, file.length);
```

#### Dangerous Functions\Path 48:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=99>

Status New

The dangerous function, memcpy, was found in use at line 474 in nginx@@njs-0.5.2-CVE-2022-29379-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-29379-TP.c	nginx@@njs-0.5.2-CVE-2022-29379-TP.c
Line	502	502
Object	memcpy	memcpy

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-29379-TP.c

Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
502.      memcpy(module, shared, sizeof(njs_module_t));
```

#### Dangerous Functions\Path 49:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=100>

Status New

The dangerous function, strlen, was found in use at line 217 in nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	237	237
Object	strlen	strlen

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method static int session\_terminate\_session(nghttp2\_session \*session,

```
....  
237.         debug_datalen = strlen(reason);
```

#### Dangerous Functions\Path 50:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=101>

Status New

The dangerous function, strlen, was found in use at line 218 in nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	238	238
Object	strlen	strlen

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method static int session\_terminate\_session(nghttp2\_session \*session,

```
....  
238.         debug_datalen = strlen(reason);
```

## Buffer Overflow boundcpy WrongSizeParam

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow boundcpy WrongSizeParam Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows

OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow boundcpy WrongSizeParam\Path 1:

Severity Medium

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=1">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=1</a>
Status	New

The size of the buffer used by session\_new in session\_ptr, at line 433 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_new passes to session\_ptr, at line 433 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	528	528
Object	session_ptr	session_ptr

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....  
528.          sizeof ((*session_ptr)->user_rcv_ext_types));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=2">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=2</a>
Status	New

The size of the buffer used by nghttp2\_put\_uint16be in uint16\_t, at line 32 of nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_put\_uint16be passes to uint16\_t, at line 32 of nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	34	34
Object	uint16_t	uint16_t

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint16be(uint8\_t \*buf, uint16\_t n) {

```
....  
34.    memcpy(buf, &x, sizeof(uint16_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=3">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=3</a>
Status	New

The size of the buffer used by `nghttp2_put_uint32be` in `uint32_t`, at line 37 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `nghttp2_put_uint32be` passes to `uint32_t`, at line 37 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>
Line	39	39
Object	<code>uint32_t</code>	<code>uint32_t</code>

#### Code Snippet

File Name `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`  
Method `void nghttp2_put_uint32be(uint8_t *buf, uint32_t n) {`

```
....  
39.     memcpy(buf, &x, sizeof(uint32_t));
```

#### Buffer Overflow `boundcpy WrongSizeParam\Path 4:`

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=4">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=4</a>
Status	New

The size of the buffer used by `nghttp2_get_uint16` in `uint16_t`, at line 42 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `nghttp2_get_uint16` passes to `uint16_t`, at line 42 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>
Line	44	44
Object	<code>uint16_t</code>	<code>uint16_t</code>

#### Code Snippet

File Name `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`  
Method `uint16_t nghttp2_get_uint16(const uint8_t *data) {`

```
....  
44.     memcpy(&n, data, sizeof(uint16_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 5:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=5">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=5</a>
Status	New

The size of the buffer used by `nghttp2_get_uint32` in `uint32_t`, at line 48 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `nghttp2_get_uint32` passes to `uint32_t`, at line 48 of `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>	<code>nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c</code>
Line	50	50
Object	<code>uint32_t</code>	<code>uint32_t</code>

**Code Snippet**

File Name `nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c`  
Method `uint32_t nghttp2_get_uint32(const uint8_t *data) {`

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 6:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=6">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=6</a>
Status	New

The size of the buffer used by `session_new` in `session_ptr`, at line 434 of `nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `session_new` passes to `session_ptr`, at line 434 of `nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c</code>	<code>nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c</code>
Line	533	533
Object	<code>session_ptr</code>	<code>session_ptr</code>

**Code Snippet**

File Name `nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c`  
Method `static int session_new(nghttp2_session **session_ptr,`

```
....  
533.     sizeof((*session_ptr)->user_recv_ext_types));
```



**Buffer Overflow boundcpy WrongSizeParam\Path 7:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=7">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=7</a>
Status	New

The size of the buffer used by `nghttp2_put_uint16be` in `uint16_t`, at line 32 of `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `nghttp2_put_uint16be` passes to `uint16_t`, at line 32 of `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c</code>	<code>nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c</code>
Line	34	34
Object	<code>uint16_t</code>	<code>uint16_t</code>

## Code Snippet

File Name `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`  
Method `void nghttp2_put_uint16be(uint8_t *buf, uint16_t n) {`

```
....  
34.     memcpy(buf, &x, sizeof(uint16_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 8:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=8">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=8</a>
Status	New

The size of the buffer used by `nghttp2_put_uint32be` in `uint32_t`, at line 37 of `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `nghttp2_put_uint32be` passes to `uint32_t`, at line 37 of `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c</code>	<code>nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c</code>
Line	39	39
Object	<code>uint32_t</code>	<code>uint32_t</code>

## Code Snippet

File Name `nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c`  
Method `void nghttp2_put_uint32be(uint8_t *buf, uint32_t n) {`

```
....
39.     memcpy(buf, &x, sizeof(uint32_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 9:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=9">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=9</a>
Status	New

The size of the buffer used by nghttp2\_get\_uint16 in uint16\_t, at line 42 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_get\_uint16 passes to uint16\_t, at line 42 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	44	44
Object	uint16_t	uint16_t

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method uint16\_t nghttp2\_get\_uint16(const uint8\_t \*data) {

```
....
44.     memcpy(&n, data, sizeof(uint16_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=10">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=10</a>
Status	New

The size of the buffer used by nghttp2\_get\_uint32 in uint32\_t, at line 48 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_get\_uint32 passes to uint32\_t, at line 48 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	50	50
Object	uint32_t	uint32_t

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c

Method      uint32\_t nghttp2\_get\_uint32(const uint8\_t \*data) {

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=11">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=11</a>
Status	New

The size of the buffer used by session\_new in session\_ptr, at line 434 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_new passes to session\_ptr, at line 434 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	533	533
Object	session_ptr	session_ptr

#### Code Snippet

File Name      nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method          static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....  
533.             sizeof((*session_ptr)->user_recv_ext_types));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=12">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=12</a>
Status	New

The size of the buffer used by nghttp2\_put\_uint16be in uint16\_t, at line 32 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_put\_uint16be passes to uint16\_t, at line 32 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	34	34
Object	uint16_t	uint16_t

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint16be(uint8\_t \*buf, uint16\_t n) {

```
....  
34.     memcpy(buf, &x, sizeof(uint16_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 13:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=13>  
Status New

The size of the buffer used by nghttp2\_put\_uint32be in uint32\_t, at line 37 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_put\_uint32be passes to uint32\_t, at line 37 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	39	39
Object	uint32_t	uint32_t

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method void nghttp2\_put\_uint32be(uint8\_t \*buf, uint32\_t n) {

```
....  
39.     memcpy(buf, &x, sizeof(uint32_t));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 14:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=14>  
Status New

The size of the buffer used by nghttp2\_get\_uint16 in uint16\_t, at line 42 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_get\_uint16 passes to uint16\_t, at line 42 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	44	44
Object	uint16_t	uint16_t

**Code Snippet**

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method uint16\_t nghttp2\_get\_uint16(const uint8\_t \*data) {

```
....  
44.     memcpy(&n, data, sizeof(uint16_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 15:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=15>  
Status New

The size of the buffer used by nghttp2\_get\_uint32 in uint32\_t, at line 48 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that nghttp2\_get\_uint32 passes to uint32\_t, at line 48 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	50	50
Object	uint32_t	uint32_t

**Code Snippet**

File Name nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c  
Method uint32\_t nghttp2\_get\_uint32(const uint8\_t \*data) {

```
....  
50.     memcpy(&n, data, sizeof(uint32_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 16:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=16>  
Status New

The size of the buffer used by session\_new in session\_ptr, at line 435 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_new passes to session\_ptr, at line 435 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	535	535
Object	session_ptr	session_ptr

**Code Snippet**

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Method static int session\_new(nghttp2\_session \*\*session\_ptr,

```
....
535.                sizeof((*session_ptr)->user_rcv_ext_types));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 17:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=17>

Status New

The size of the buffer used by njs\_module\_find in njs\_module\_t, at line 425 of ngx@@njs-0.3.9-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_module\_find passes to njs\_module\_t, at line 425 of ngx@@njs-0.3.9-CVE-2022-29379-TP.c, to overwrite the target buffer.

	Source	Destination
File	ngx@@njs-0.3.9-CVE-2022-29379-TP.c	ngx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	453	453
Object	njs_module_t	njs_module_t

**Code Snippet**

File Name ngx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....
453.                memcpy(module, shared, sizeof(njs_module_t));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 18:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=18>

Status New

The size of the buffer used by njs\_module\_find in njs\_module\_t, at line 474 of ngx@@njs-0.4.2-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_module\_find passes to njs\_module\_t, at line 474 of ngx@@njs-0.4.2-CVE-2022-29379-TP.c, to overwrite the target buffer.

	Source	Destination
File	ngx@@njs-0.4.2-CVE-2022-29379-TP.c	ngx@@njs-0.4.2-CVE-2022-29379-TP.c
Line	502	502

Object	njs_module_t	njs_module_t
--------	--------------	--------------

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-29379-TP.c  
Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
502.          memcpy(module, shared, sizeof(njs_module_t));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 19:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=19">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=19</a>
Status	New

The size of the buffer used by njs\_module\_find in njs\_module\_t, at line 474 of nginx@@njs-0.5.0-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_module\_find passes to njs\_module\_t, at line 474 of nginx@@njs-0.5.0-CVE-2022-29379-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-29379-TP.c	nginx@@njs-0.5.0-CVE-2022-29379-TP.c
Line	502	502
Object	njs_module_t	njs_module_t

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-29379-TP.c  
Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....  
502.          memcpy(module, shared, sizeof(njs_module_t));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=20">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=20</a>
Status	New

The size of the buffer used by njs\_module\_find in njs\_module\_t, at line 474 of nginx@@njs-0.5.2-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_module\_find passes to njs\_module\_t, at line 474 of nginx@@njs-0.5.2-CVE-2022-29379-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-29379-TP.c	nginx@@njs-0.5.2-CVE-2022-29379-TP.c



Line	502	502
Object	njs_module_t	njs_module_t

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-29379-TP.c  
Method njs\_module\_find(njs\_vm\_t \*vm, njs\_str\_t \*name, njs\_bool\_t local)

```
....
502.         memcpy(module, shared, sizeof(njs_module_t));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 21:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=21">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=21</a>
Status	New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_frame, at line 304 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_frame, at line 304 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	377	377
Object	nghttp2_frame	nghttp2_frame

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c  
Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....
377.         memset(&iframe->frame, 0, sizeof(nghttp2_frame));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 22:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=22</a>
Status	New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_ext\_frame\_payload, at line 304 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_ext\_frame\_payload, at line 304 of nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c, to overwrite the target buffer.



	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	378	378
Object	nghttp2_ext_frame_payload	nghttp2_ext_frame_payload

#### Code Snippet

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....  
378.     memset(&iframe->ext_frame_payload, 0,  
sizeof(nghttp2_ext_frame_payload));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 23:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=23>

Status New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_frame, at line 305 of nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_frame, at line 305 of nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	378	378
Object	nghttp2_frame	nghttp2_frame

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....  
378.     memset(&iframe->frame, 0, sizeof(nghttp2_frame));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 24:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=24>

Status New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_ext\_frame\_payload, at line 305 of nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_ext\_frame\_payload, at line 305 of nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	379	379
Object	nghttp2_ext_frame_payload	nghttp2_ext_frame_payload

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....  
379.     memset(&iframe->ext_frame_payload, 0,  
sizeof(nghttp2_ext_frame_payload));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 25:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=25>

Status New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_frame, at line 305 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_frame, at line 305 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	378	378
Object	nghttp2_frame	nghttp2_frame

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....  
378.     memset(&iframe->frame, 0, sizeof(nghttp2_frame));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 26:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=26>

[PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=26](http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=26)

Status New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_ext\_frame\_payload, at line 305 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_ext\_frame\_payload, at line 305 of nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	379	379
Object	nghttp2_ext_frame_payload	nghttp2_ext_frame_payload

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....
379.     memset(&iframe->ext_frame_payload, 0,
sizeof(nghttp2_ext_frame_payload));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 27:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=27>

Status New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_frame, at line 306 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_frame, at line 306 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	379	379
Object	nghttp2_frame	nghttp2_frame

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....
379.     memset(&iframe->frame, 0, sizeof(nghttp2_frame));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 28:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=28">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=28</a>
Status	New

The size of the buffer used by session\_inbound\_frame\_reset in nghttp2\_ext\_frame\_payload, at line 306 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that session\_inbound\_frame\_reset passes to nghttp2\_ext\_frame\_payload, at line 306 of nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	380	380
Object	nghttp2_ext_frame_payload	nghttp2_ext_frame_payload

**Code Snippet**

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method static void session\_inbound\_frame\_reset(nghttp2\_session \*session) {

```
....  
380.     memset(&iframe->ext_frame_payload, 0,  
sizeof(nghttp2_ext_frame_payload));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 29:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=29">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=29</a>
Status	New

The size of the buffer used by \*nghttp2\_cpymem in len, at line 760 of nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*nghttp2\_cpymem passes to len, at line 760 of nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c
Line	765	765
Object	len	len

**Code Snippet**

File Name nghttp2@@nghttp2-v1.54.0-CVE-2024-28182-TP.c  
Method uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.     memcpy(dest, src, len);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=30">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=30</a>
Status	New

The size of the buffer used by \*nghttp2\_cpymem in len, at line 760 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*nghttp2\_cpymem passes to len, at line 760 of nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c
Line	765	765
Object	len	len

#### Code Snippet

File Name      nghttp2@@nghttp2-v1.57.0-CVE-2024-28182-TP.c  
Method          uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.     memcpy(dest, src, len);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 31:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=31">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=31</a>
Status	New

The size of the buffer used by \*nghttp2\_cpymem in len, at line 760 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*nghttp2\_cpymem passes to len, at line 760 of nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c, to overwrite the target buffer.

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c	nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c
Line	765	765
Object	len	len

#### Code Snippet

File Name      nghttp2@@nghttp2-v1.59.0-CVE-2024-28182-TP.c

Method      uint8\_t \*nghttp2\_cpymem(uint8\_t \*dest, const void \*src, size\_t len) {

```
....  
765.      memcpy(dest, src, len);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 32:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=32">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=32</a>
Status	New

The size of the buffer used by njs\_string\_concat in string1, at line 1436 of nginx@@njs-0.3.9-CVE-2021-46461-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string1, at line 1436 of nginx@@njs-0.3.9-CVE-2021-46461-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	1466	1466
Object	string1	string1

#### Code Snippet

File Name      nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method          njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1466.      (void) memcpy(start, string1.start, string1.size);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 33:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=33">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=33</a>
Status	New

The size of the buffer used by njs\_string\_concat in string2, at line 1436 of nginx@@njs-0.3.9-CVE-2021-46461-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string2, at line 1436 of nginx@@njs-0.3.9-CVE-2021-46461-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	1467	1467
Object	string2	string2

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1467.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 34:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=34>  
Status New

The size of the buffer used by njs\_string\_concat in string1, at line 1436 of nginx@@njs-0.3.9-CVE-2022-28049-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string1, at line 1436 of nginx@@njs-0.3.9-CVE-2022-28049-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	1466	1466
Object	string1	string1

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c  
Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1466.      (void) memcpy(start, string1.start, string1.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 35:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=35>  
Status New

The size of the buffer used by njs\_string\_concat in string2, at line 1436 of nginx@@njs-0.3.9-CVE-2022-28049-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string2, at line 1436 of nginx@@njs-0.3.9-CVE-2022-28049-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	1467	1467
Object	string2	string2



#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....
1467.      (void) memcpy(start + string1.size, string2.start,
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 36:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=36>

Status New

The size of the buffer used by njs\_module\_absolute\_path in file, at line 264 of nginx@@njs-0.3.9-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_module\_absolute\_path passes to file, at line 264 of nginx@@njs-0.3.9-CVE-2022-29379-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	274	274
Object	file	file

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....
274.      memcpy(file.start, info->name.start, file.length);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 37:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=37>

Status New

The size of the buffer used by njs\_string\_concat in string1, at line 1442 of nginx@@njs-0.4.2-CVE-2021-46461-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string1, at line 1442 of nginx@@njs-0.4.2-CVE-2021-46461-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c



Line	1472	1472
Object	string1	string1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....
1472.      (void) memcpy(start, string1.start, string1.size);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 38:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=38>

Status New

The size of the buffer used by njs\_string\_concat in string2, at line 1442 of nginx@@njs-0.4.2-CVE-2021-46461-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string2, at line 1442 of nginx@@njs-0.4.2-CVE-2021-46461-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	1473	1473
Object	string2	string2

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....
1473.      (void) memcpy(start + string1.size, string2.start,
string2.size);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 39:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=39>

Status New

The size of the buffer used by njs\_string\_concat in string1, at line 1442 of nginx@@njs-0.4.2-CVE-2022-28049-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string1, at line 1442 of nginx@@njs-0.4.2-CVE-2022-28049-TP.c, to overwrite the target buffer.

Source	Destination
--------	-------------

File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	1472	1472
Object	string1	string1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 40:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=40>

Status New

The size of the buffer used by njs\_string\_concat in string2, at line 1442 of nginx@@njs-0.4.2-CVE-2022-28049-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that njs\_string\_concat passes to string2, at line 1442 of nginx@@njs-0.4.2-CVE-2022-28049-TP.c, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	1473	1473
Object	string2	string2

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c

Method njs\_string\_concat(njs\_vm\_t \*vm, njs\_value\_t \*val1, njs\_value\_t \*val2)

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 41:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=41>

Status New

The size of the buffer used by njs\_module\_absolute\_path in file, at line 328 of nginx@@njs-0.4.2-CVE-2022-29379-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack,

using the source buffer that `njs_module_absolute_path` passes to `file`, at line 328 of `nginx@@njs-0.4.2-CVE-2022-29379-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>
Line	338	338
Object	<code>file</code>	<code>file</code>

#### Code Snippet

File Name `nginx@@njs-0.4.2-CVE-2022-29379-TP.c`

Method `njs_module_absolute_path(njs_vm_t *vm, njs_module_info_t *info)`

```
....  
338.      memcpy(file.start, info->name.start, file.length);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 42:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=42>

Status New

The size of the buffer used by `njs_string_concat` in `string1`, at line 1442 of `nginx@@njs-0.5.0-CVE-2021-46461-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string1`, at line 1442 of `nginx@@njs-0.5.0-CVE-2021-46461-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.5.0-CVE-2021-46461-TP.c</code>	<code>nginx@@njs-0.5.0-CVE-2021-46461-TP.c</code>
Line	1472	1472
Object	<code>string1</code>	<code>string1</code>

#### Code Snippet

File Name `nginx@@njs-0.5.0-CVE-2021-46461-TP.c`

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

### Buffer Overflow boundcpy WrongSizeParam\Path 43:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=43>

Status New

The size of the buffer used by `njs_string_concat` in `string2`, at line 1442 of `nginx@@njs-0.5.0-CVE-2021-46461-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string2`, at line 1442 of `nginx@@njs-0.5.0-CVE-2021-46461-TP.c`, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	1473	1473
Object	string2	string2

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 44:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=44>

Status New

The size of the buffer used by `njs_string_concat` in `string1`, at line 1442 of `nginx@@njs-0.5.0-CVE-2022-28049-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string1`, at line 1442 of `nginx@@njs-0.5.0-CVE-2022-28049-TP.c`, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	1472	1472
Object	string1	string1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 45:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=45>

Status New

The size of the buffer used by `njs_string_concat` in `string2`, at line 1442 of `nginx@@njs-0.5.0-CVE-2022-28049-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string2`, at line 1442 of `nginx@@njs-0.5.0-CVE-2022-28049-TP.c`, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	1473	1473
Object	string2	string2

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 46:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=46>

Status New

The size of the buffer used by `njs_module_absolute_path` in file, at line 328 of `nginx@@njs-0.5.0-CVE-2022-29379-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_module_absolute_path` passes to file, at line 328 of `nginx@@njs-0.5.0-CVE-2022-29379-TP.c`, to overwrite the target buffer.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-29379-TP.c	nginx@@njs-0.5.0-CVE-2022-29379-TP.c
Line	338	338
Object	file	file

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-29379-TP.c

Method `njs_module_absolute_path(njs_vm_t *vm, njs_module_info_t *info)`

```
....  
338.      memcpy(file.start, info->name.start, file.length);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 47:

Severity Medium

Result State To Verify

Online Results <http://WIN->

	<a href="#">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=47</a>
Status	New

The size of the buffer used by `njs_string_concat` in `string1`, at line 1442 of `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string1`, at line 1442 of `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2021-46461-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2021-46461-TP.c</code>
Line	1472	1472
Object	<code>string1</code>	<code>string1</code>

#### Code Snippet

File Name `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 48:

Severity	Medium
Result State	To Verify
Online Results	<a href="#">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=48</a>
Status	New

The size of the buffer used by `njs_string_concat` in `string2`, at line 1442 of `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string2`, at line 1442 of `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2021-46461-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2021-46461-TP.c</code>
Line	1473	1473
Object	<code>string2</code>	<code>string2</code>

#### Code Snippet

File Name `nginx@@njs-0.5.2-CVE-2021-46461-TP.c`

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 49:

Severity	Medium
----------	--------

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=49">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=49</a>
Status	New

The size of the buffer used by `njs_string_concat` in `string1`, at line 1442 of `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string1`, at line 1442 of `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2022-28049-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2022-28049-TP.c</code>
Line	1472	1472
Object	<code>string1</code>	<code>string1</code>

#### Code Snippet

File Name `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1472.      (void) memcpy(start, string1.start, string1.size);
```

#### Buffer Overflow `boundcpy WrongSizeParam\Path 50`:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=50">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=50</a>
Status	New

The size of the buffer used by `njs_string_concat` in `string2`, at line 1442 of `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `njs_string_concat` passes to `string2`, at line 1442 of `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2022-28049-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2022-28049-TP.c</code>
Line	1473	1473
Object	<code>string2</code>	<code>string2</code>

#### Code Snippet

File Name `nginx@@njs-0.5.2-CVE-2022-28049-TP.c`

Method `njs_string_concat(njs_vm_t *vm, njs_value_t *val1, njs_value_t *val2)`

```
....  
1473.      (void) memcpy(start + string1.size, string2.start,  
string2.size);
```

## Use of Sizeof On a Pointer Type

Query Path:

CPP\Cx\CPP Low Visibility\Use of Sizeof On a Pointer Type Version:1

[Description](#)

### Use of Sizeof On a Pointer Type\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=112">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=112</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.17.9-CVE-2021-3618-TP.c	nginx@@nginx-release-1.17.9-CVE-2021-3618-TP.c
Line	345	345
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.17.9-CVE-2021-3618-TP.c  
Method ngx\_mail\_init\_session(ngx\_connection\_t \*c)

```
....  
345.      s->ctx = ngx_pcalloc(c->pool, sizeof(void *) *  
ngx_mail_max_module);
```

### Use of Sizeof On a Pointer Type\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=113">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=113</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.19.1-CVE-2021-3618-TP.c	nginx@@nginx-release-1.19.1-CVE-2021-3618-TP.c
Line	345	345
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.19.1-CVE-2021-3618-TP.c  
Method ngx\_mail\_init\_session(ngx\_connection\_t \*c)

```
....  
345.      s->ctx = ngx_pcalloc(c->pool, sizeof(void *) *  
ngx_mail_max_module);
```

### Use of Sizeof On a Pointer Type\Path 3:



Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=114">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=114</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.19.4-CVE-2021-3618-TP.c	nginx@@nginx-release-1.19.4-CVE-2021-3618-TP.c
Line	345	345
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.19.4-CVE-2021-3618-TP.c  
Method ngx\_mail\_init\_session(ngx\_connection\_t \*c)

```
....  
345.      s->ctx = ngx_palloc(c->pool, sizeof(void *) *  
ngx_mail_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=115">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=115</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.19.7-CVE-2021-3618-TP.c	nginx@@nginx-release-1.19.7-CVE-2021-3618-TP.c
Line	345	345
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.19.7-CVE-2021-3618-TP.c  
Method ngx\_mail\_init\_session(ngx\_connection\_t \*c)

```
....  
345.      s->ctx = ngx_palloc(c->pool, sizeof(void *) *  
ngx_mail_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=116">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=116</a>

Status	New
--------	-----

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2357	2357
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
.....  
2357.         sr->ctx = ngx_palloc(r->pool, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=117">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=117</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2531	2531
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_internal\_redirect(ngx\_http\_request\_t \*r,

```
.....  
2531.         ngx_memzero(r->ctx, sizeof(void *) * ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=118">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=118</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Line	2605	2605
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....
2605.          ngx_memzero(r->ctx, sizeof(void *) *
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=119>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2831	2831
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2831.          ctx->srv_conf = ngx_pcalloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 9:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=120>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2838	2838
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2838.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 10:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=121>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2971	2971
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2971.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 11:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=122>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	3303	3303
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_create\_main\_conf(ngx\_conf\_t \*cf)

```
.....
3303.                                sizeof(ngx_http_core_srv_conf_t *))
```

### Use of Sizeof On a Pointer Type\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=123">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=123</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	3396	3396
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_merge\_srv\_conf(ngx\_conf\_t \*cf, void \*parent, void \*child)

```
.....
3396.                                prev->connection_pool_size, 64 *
sizeof(void *));
```

### Use of Sizeof On a Pointer Type\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=124">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=124</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	4489	4489
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
.....
4489.        ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 14:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=125">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=125</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2357	2357
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2357.         sr->ctx = ngx_pcalloc(r->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 15:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=126">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=126</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2531	2531
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method ngx\_http\_internal\_redirect(ngx\_http\_request\_t \*r,

```
....
2531.         ngx_memzero(r->ctx, sizeof(void *) * ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 16:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=127">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=127</a>

Status	New
--------	-----

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2605	2605
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....  
2605.          ngx_memzero(r->ctx, sizeof(void *) *  
          ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=128">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=128</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2831	2831
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2831.          ctx->srv_conf = ngx_pcalloc(cf->pool, sizeof(void *) *  
          ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=129">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=129</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-	nginx@@nginx-release-1.21.2-CVE-

	2021-3618-FP.c	2021-3618-FP.c
Line	2838	2838
Object	sizeof	sizeof

**Code Snippet**

File Name      ngx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method          ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2838.          ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 19:**

Severity          Low

Result State      To Verify

Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=130>

Status            New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2971	2971
Object	sizeof	sizeof

**Code Snippet**

File Name      ngx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method          ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2971.          ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 20:**

Severity          Low

Result State      To Verify

Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=131>

Status            New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	3303	3303
Object	sizeof	sizeof



## Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_create\_main\_conf(ngx\_conf\_t \*cf)

```
....  
3303.                                sizeof(ngx_http_core_srv_conf_t *))
```

**Use of Sizeof On a Pointer Type\Path 21:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=132>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	3396	3396
Object	sizeof	sizeof

## Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_merge\_srv\_conf(ngx\_conf\_t \*cf, void \*parent, void \*child)

```
....  
3396.                                prev->connection_pool_size, 64 *  
sizeof(void *));
```

**Use of Sizeof On a Pointer Type\Path 22:**

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=133>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	4489	4489
Object	sizeof	sizeof

## Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4489.         ctx->loc_conf = ngx_pcalloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

### Use of Sizeof On a Pointer Type\Path 23:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=134">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=134</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2357	2357
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....  
2357.         sr->ctx = ngx_pcalloc(r->pool, sizeof(void *) *  
ngx_http_max_module);
```

### Use of Sizeof On a Pointer Type\Path 24:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=135">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=135</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2531	2531
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_internal\_redirect(ngx\_http\_request\_t \*r,

```
....  
2531.         ngx_memzero(r->ctx, sizeof(void *) * ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 25:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=136">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=136</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2605	2605
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....  
2605.          ngx_memzero(r->ctx, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 26:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=137">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=137</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2831	2831
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2831.          ctx->srv_conf = ngx_pcalloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 27:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=137">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=137</a>

Status	<a href="#">038&amp;pathid=138</a> New
--------	---

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2838	2838
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2838.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 28:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=139">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=139</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2971	2971
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2971.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 29:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=140">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=140</a>
Status	New

Source	Destination
--------	-------------

File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	3303	3303
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c

Method ngx\_http\_core\_create\_main\_conf(ngx\_conf\_t \*cf)

```
....
3303.                                sizeof(ngx_http_core_srv_conf_t *) )
```

#### Use of Sizeof On a Pointer Type\Path 30:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=141>

Status New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	3396	3396
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c

Method ngx\_http\_core\_merge\_srv\_conf(ngx\_conf\_t \*cf, void \*parent, void \*child)

```
....
3396.                                prev->connection_pool_size, 64 *
sizeof(void *));
```

#### Use of Sizeof On a Pointer Type\Path 31:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=142>

Status New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	4489	4489
Object	sizeof	sizeof

## Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....
4489.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 32:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=143>

Status New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2357	2357
Object	sizeof	sizeof

## Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2357.         sr->ctx = ngx_palloc(r->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 33:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=144>

Status New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2531	2531
Object	sizeof	sizeof

## Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_internal\_redirect(ngx\_http\_request\_t \*r,

```
....  
2531.          ngx_memzero(r->ctx, sizeof(void *) * ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 34:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=145">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=145</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2605	2605
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....  
2605.          ngx_memzero(r->ctx, sizeof(void *) *  
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 35:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=146">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=146</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2831	2831
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2831.          ctx->srv_conf = ngx_pcalloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 36:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=147">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=147</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2838	2838
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2838.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 37:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=148">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=148</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2971	2971
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2971.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *  
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 38:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=148">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=148</a>



Status	<a href="#">038&amp;pathid=149</a> New
--------	---

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	3303	3303
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_create\_main\_conf(ngx\_conf\_t \*cf)

```
....  
3303.                                sizeof(ngx_http_core_srv_conf_t *))
```

#### Use of Sizeof On a Pointer Type\Path 39:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=150">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=150</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	3396	3396
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_merge\_srv\_conf(ngx\_conf\_t \*cf, void \*parent, void \*child)

```
....  
3396.                                prev->connection_pool_size, 64 *  
sizeof(void *));
```

#### Use of Sizeof On a Pointer Type\Path 40:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=151">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=151</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-	nginx@@nginx-release-1.22.0-CVE-

	2021-3618-FP.c	2021-3618-FP.c
Line	4489	4489
Object	sizeof	sizeof

**Code Snippet**

File Name      nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method          ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....
4489.          ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 41:**

Severity          Low

Result State      To Verify

Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=152>

Status            New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2360	2360
Object	sizeof	sizeof

**Code Snippet**

File Name      nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method          ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2360.          sr->ctx = ngx_palloc(r->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 42:**

Severity          Low

Result State      To Verify

Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=153>

Status            New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2534	2534
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_internal\_redirect(ngx\_http\_request\_t \*r,

```
....
2534.         ngx_memzero(r->ctx, sizeof(void *) * ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 43:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=154>

Status New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2608	2608
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_named\_location(ngx\_http\_request\_t \*r, ngx\_str\_t \*name)

```
....
2608.         ngx_memzero(r->ctx, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 44:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=155>

Status New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2923	2923
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2923.      ctx->srv_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 45:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=156">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=156</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2930	2930
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2930.      ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

#### Use of Sizeof On a Pointer Type\Path 46:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=157">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=157</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	3063	3063
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
3063.      ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

**Use of Sizeof On a Pointer Type\Path 47:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=158">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=158</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	3395	3395
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_create\_main\_conf(ngx\_conf\_t \*cf)

```
....  
3395.                                sizeof(ngx_http_core_srv_conf_t *))
```

**Use of Sizeof On a Pointer Type\Path 48:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=159">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=159</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	3488	3488
Object	sizeof	sizeof

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_merge\_srv\_conf(ngx\_conf\_t \*cf, void \*parent, void \*child)

```
....  
3488.                                prev->connection_pool_size, 64 *  
sizeof(void *));
```

**Use of Sizeof On a Pointer Type\Path 49:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=159">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=159</a>

Status	<a href="#">038&amp;pathid=160</a> New
--------	---

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	4581	4581
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....
4581.         ctx->loc_conf = ngx_palloc(cf->pool, sizeof(void *) *
ngx_http_max_module);
```

### Use of Sizeof On a Pointer Type\Path 50:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=161>

Status New

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	2357	2357
Object	sizeof	sizeof

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_subrequest(ngx\_http\_request\_t \*r,

```
....
2357.         sr->ctx = ngx_palloc(r->pool, sizeof(void *) *
ngx_http_max_module);
```

## NULL Pointer Dereference

Query Path:

CPP\Cx\CPP Low Visibility\NULL Pointer Dereference Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

OWASP Top 10 2017: A1-Injection

### Description

#### NULL Pointer Dereference\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=201">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=201</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
202.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=202">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=202</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
231.          *retval = *value1;
```

**NULL Pointer Dereference\Path 3:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=203">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=203</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2021-46461-TP.c	nginx@@njs-0.3.9-CVE-2021-46461-TP.c
Line	130	157
Object	null	value1

**Code Snippet**

File Name nginx@@njs-0.3.9-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
157.          *retval = *value1;
```

**NULL Pointer Dereference\Path 4:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=204">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=204</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	130	202
Object	null	value1

**Code Snippet**

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)



```

....
130.          value1 = NULL;
....
202.          *retval = *value1;

```

### NULL Pointer Dereference\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=205">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=205</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```

....
130.          value1 = NULL;
....
231.          *retval = *value1;

```

### NULL Pointer Dereference\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=206">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=206</a>
Status	New

The variable declared in null at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.3.9-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-28049-TP.c	nginx@@njs-0.3.9-CVE-2022-28049-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
157.          *retval = *value1;
```

### NULL Pointer Dereference\Path 7:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=207>  
Status New

The variable declared in null at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	130	202
Object	null	value1

### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
202.          *retval = *value1;
```

### NULL Pointer Dereference\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=208>  
Status New

The variable declared in null at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
231.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 9:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=209>  
Status New

The variable declared in null at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2021-46461-TP.c	nginx@@njs-0.4.2-CVE-2021-46461-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
157.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 10:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=210>  
Status New

The variable declared in null at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c

Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
202.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=211">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=211</a>
Status	New

The variable declared in null at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.          value1 = NULL;
....
231.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=212">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=212</a>
Status	New

The variable declared in null at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.4.2-CVE-2022-28049-TP.c in line 77.

Source	Destination
--------	-------------

File	nginx@@njs-0.4.2-CVE-2022-28049-TP.c	nginx@@njs-0.4.2-CVE-2022-28049-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.         value1 = NULL;
....
157.         *retval = *value1;
```

#### NULL Pointer Dereference\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=213">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=213</a>
Status	New

The variable declared in null at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.         value1 = NULL;
....
202.         *retval = *value1;
```

#### NULL Pointer Dereference\Path 14:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=214">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=214</a>
Status	New

The variable declared in null at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
231.          *retval = *value1;
```

### NULL Pointer Dereference\Path 15:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=215">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=215</a>
Status	New

The variable declared in null at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2021-46461-TP.c	nginx@@njs-0.5.0-CVE-2021-46461-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
157.          *retval = *value1;
```

### NULL Pointer Dereference\Path 16:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=216">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=216</a>
Status	New

The variable declared in null at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
202.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=217">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=217</a>
Status	New

The variable declared in null at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
231.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=218">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=218</a>

Status New

The variable declared in null at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.0-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-28049-TP.c	nginx@@njs-0.5.0-CVE-2022-28049-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-28049-TP.c

Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
157.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 19:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=219>

Status New

The variable declared in null at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2021-46461-TP.c	nginx@@njs-0.5.2-CVE-2021-46461-TP.c
Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2021-46461-TP.c

Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
202.          *retval = *value1;
```

#### NULL Pointer Dereference\Path 20:

Severity Low

Result State To Verify

Online Results <http://WIN->



	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=220">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=220</a>
Status	New

The variable declared in null at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2021-46461-TP.c	nginx@@njs-0.5.2-CVE-2021-46461-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.         value1 = NULL;
....
231.         *retval = *value1;
```

#### NULL Pointer Dereference\Path 21:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=221">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=221</a>
Status	New

The variable declared in null at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2021-46461-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2021-46461-TP.c	nginx@@njs-0.5.2-CVE-2021-46461-TP.c
Line	130	157
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2021-46461-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....
130.         value1 = NULL;
....
157.         *retval = *value1;
```

#### NULL Pointer Dereference\Path 22:

Severity Low

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=222">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=222</a>
Status	New

The variable declared in null at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-28049-TP.c	nginx@@njs-0.5.2-CVE-2022-28049-TP.c
Line	130	202
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
202.          *retval = *value1;
```

### NULL Pointer Dereference\Path 23:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=223">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=223</a>
Status	New

The variable declared in null at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-28049-TP.c	nginx@@njs-0.5.2-CVE-2022-28049-TP.c
Line	130	231
Object	null	value1

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.          value1 = NULL;  
....  
231.          *retval = *value1;
```

**NULL Pointer Dereference\Path 24:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=224">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=224</a>
Status	New

The variable declared in null at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77 is not initialized when it is used by value1 at nginx@@njs-0.5.2-CVE-2022-28049-TP.c in line 77.

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-28049-TP.c	nginx@@njs-0.5.2-CVE-2022-28049-TP.c
Line	130	157
Object	null	value1

**Code Snippet**

File Name nginx@@njs-0.5.2-CVE-2022-28049-TP.c  
Method njs\_vmcode\_interpreter(njs\_vm\_t \*vm, u\_char \*pc)

```
....  
130.         value1 = NULL;  
....  
157.         *retval = *value1;
```

**NULL Pointer Dereference\Path 25:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=225">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=225</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

**Code Snippet**

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.         b->memory = val.len ? 1 : 0;
```

**NULL Pointer Dereference\Path 26:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=226">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=226</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

**Code Snippet**

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

**NULL Pointer Dereference\Path 27:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=227">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=227</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 4316 is not initialized when it is used by clcf at nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c in line 4316.

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	4373	4373
Object	0	clcf

**Code Snippet**

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4373.      clcf->alias = alias ? clcf->name.len : 0;
```

**NULL Pointer Dereference\Path 28:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=228">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=228</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

**Code Snippet**

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.      b->memory = val.len ? 1 : 0;
```

**NULL Pointer Dereference\Path 29:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=229">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=229</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

**Code Snippet**

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

**NULL Pointer Dereference\Path 30:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=230">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=230</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 4316 is not initialized when it is used by clcf at nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c in line 4316.

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	4373	4373
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4373.         clcf->alias = alias ? clcf->name.len : 0;
```

#### NULL Pointer Dereference\Path 31:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=231">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=231</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.         b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 32:

Severity	Low
----------	-----

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=232">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=232</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

### NULL Pointer Dereference\Path 33:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=233">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=233</a>
Status	New

The variable declared in 0 at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 4316 is not initialized when it is used by clcf at nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c in line 4316.

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	4373	4373
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4373.      clcf->alias = alias ? clcf->name.len : 0;
```

### NULL Pointer Dereference\Path 34:

Severity	Low
Result State	To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=234">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=234</a>
Status	New

The variable declared in 0 at ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c	ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

#### Code Snippet

File Name ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.      b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 35:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=235">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=235</a>
Status	New

The variable declared in 0 at ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c in line 1750 is not initialized when it is used by b at ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c in line 1750.

	Source	Destination
File	ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c	ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

#### Code Snippet

File Name ngx@@ngx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 36:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=236">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=236</a>



[PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=236](http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=236)

Status New

The variable declared in 0 at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 4316 is not initialized when it is used by clcf at nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c in line 4316.

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	4373	4373
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4373.      clcf->alias = alias ? clcf->name.len : 0;
```

#### NULL Pointer Dereference\Path 37:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=237>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	1817	1817
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1817.      b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 38:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=238>

[038&pathid=238](#)

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	1818	1818
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1818.      b->last_buf = (r == r->main) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 39:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=239>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 4408 is not initialized when it is used by clcf at nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c in line 4408.

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	4465	4465
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4465.      clcf->alias = alias ? clcf->name.len : 0;
```

#### NULL Pointer Dereference\Path 40:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=240>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.      b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 41:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=241>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 42:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=242>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	1816	1816
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1816.          b->sync = (b->last_buf || b->memory) ? 0 : 1;
```

### NULL Pointer Dereference\Path 43:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=243>

Status New

The variable declared in 0 at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 4418 is not initialized when it is used by clcf at nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c in line 4418.

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	4475	4475
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4475.          clcf->alias = alias ? clcf->name.len : 0;
```

### NULL Pointer Dereference\Path 44:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=244>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.      b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 45:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=245>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 46:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=246>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	1816	1816
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1816.          b->sync = (b->last_buf || b->memory) ? 0 : 1;
```

#### NULL Pointer Dereference\Path 47:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=247>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 4460 is not initialized when it is used by clcf at nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c in line 4460.

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	4517	4517
Object	0	clcf

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_root(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4517.          clcf->alias = alias ? clcf->name.len : 0;
```

#### NULL Pointer Dereference\Path 48:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=248>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	1813	1813
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1813.      b->memory = val.len ? 1 : 0;
```

#### NULL Pointer Dereference\Path 49:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=249>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	1814	1814
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1814.      b->last_buf = (r == r->main) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 50:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=250>

Status New

The variable declared in 0 at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753 is not initialized when it is used by b at nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c in line 1753.

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	1816	1816
Object	0	b

#### Code Snippet

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_send\_response(ngx\_http\_request\_t \*r, ngx\_uint\_t status,

```
....  
1816.          b->sync = (b->last_buf || b->memory) ? 0 : 1;
```

## Unchecked Array Index

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Array Index Version:1

### Categories

NIST SP 800-53: SI-10 Information Input Validation (P1)

#### Description

##### Unchecked Array Index\Path 1:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=256>

Status New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2856	2856
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2856.          ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

##### Unchecked Array Index\Path 2:

Severity Low

Result State To Verify



Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=257">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=257</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2865	2865
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2865.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=258">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=258</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	2984	2984
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2984.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

#### Unchecked Array Index\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=259">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=259</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c
Line	4508	4508
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.0-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4508.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 5:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=260>

Status New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c
Line	2856	2856
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2856.                ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 6:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=261>

Status New

	Source	Destination
File	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Line	2865	2865
Object	ctx_index	ctx_index

### Unchecked Array Index\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=262">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=262</a>
Status	New

### Unchecked Array Index\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=263">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=263</a>
Status	New

Code Snippet  
File Name nginx@@nginx-release-1.21.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4508.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 9:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=264>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2856	2856
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2856.             ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 10:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=265>  
Status New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2865	2865
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2865.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=266">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=266</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	2984	2984
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2984.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

#### Unchecked Array Index\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=267">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=267</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c	nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c
Line	4508	4508
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.21.5-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4508.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 13:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=268">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=268</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2856	2856
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2856.             ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 14:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=269">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=269</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2865	2865
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2865.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 15:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=270">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=270</a>

Status	<a href="#">038&amp;pathid=270</a> New
--------	---

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	2984	2984
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2984.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

#### Unchecked Array Index\Path 16:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=271">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=271</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c
Line	4508	4508
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.22.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....
4508.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
mconf;
```

#### Unchecked Array Index\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=272">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=272</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-	nginx@@nginx-release-1.23.2-CVE-

	2021-3618-FP.c	2021-3618-FP.c
Line	2948	2948
Object	ctx_index	ctx_index

## Code Snippet

File Name	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Method	ngx_http_core_server(ngx_conf_t *cf, ngx_command_t *cmd, void *dummy)

```

.....
2948.         ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =
mconf;

```

### Unchecked Array Index\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=273">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=273</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	2957	2957
Object	ctx_index	ctx_index

## Code Snippet

File Name	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Method	ngx_http_core_server(ngx_conf_t *cf, ngx_command_t *cmd, void *dummy)

```

2957.         ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
mconf;

```

### Unchecked Array Index\Path 19:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=274">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=274</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	3076	3076
Object	ctx_index	ctx_index



**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
3076.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

**Unchecked Array Index\Path 20:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=275>

Status New

	Source	Destination
File	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c
Line	4600	4600
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.23.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4600.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 21:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=276>

Status New

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	2945	2945
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2945.             ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =
mconf;
```

#### Unchecked Array Index\Path 22:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=277">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=277</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	2954	2954
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
2954.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
mconf;
```

#### Unchecked Array Index\Path 23:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=278">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=278</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	3073	3073
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....
3073.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

**Unchecked Array Index\Path 24:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=279">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=279</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c
Line	4610	4610
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.23.4-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4610.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 25:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=280">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=280</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	2945	2945
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2945.             ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 26:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=280">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=280</a>

Status	<a href="#">038&amp;pathid=281</a> New
--------	---

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	2954	2954
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2954.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

#### Unchecked Array Index\Path 27:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=282>

Status New

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c
Line	3074	3074
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
3074.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

#### Unchecked Array Index\Path 28:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=283>

Status New

	Source	Destination
File	nginx@@nginx-release-1.25.2-CVE-	nginx@@nginx-release-1.25.2-CVE-

	2021-3618-FP.c	2021-3618-FP.c
Line	4652	4652
Object	ctx_index	ctx_index

## Code Snippet

File Name      nginx@@nginx-release-1.25.2-CVE-2021-3618-FP.c

Method	<code>ngx_http_core_limit_except(ngx_conf_t *cf, ngx_command_t *cmd, void *conf)</code>
--------	---

```

4652.         ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
mconf;

```

### Unchecked Array Index\Path 29:

Severity	Low
----------	-----

Result State	To Verify
--------------	-----------

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=284>

Status	New
--------	-----

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	2945	2945
Object	ctx_index	ctx_index

## Code Snippet

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```

....
2945.         ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =
mconf;

```

### Unchecked Array Index\Path 30:

Severity	Low
----------	-----

Result	State	To Verify
Success	...	...
Failure	...	...

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=285>

Status	New
--------	-----

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	2954	2954
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
2954.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

**Unchecked Array Index\Path 31:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=286>

Status New

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	3074	3074
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
3074.             ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

**Unchecked Array Index\Path 32:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=287>

Status New

	Source	Destination
File	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c	nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c
Line	4678	4678
Object	ctx_index	ctx_index

**Code Snippet**

File Name nginx@@nginx-release-1.25.4-CVE-2021-3618-FP.c

Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
.....  
4678.          ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

### Unchecked Array Index\Path 33:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=288">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=288</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c
Line	2945	2945
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
.....  
2945.          ctx->srv_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

### Unchecked Array Index\Path 34:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=289">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=289</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c
Line	2954	2954
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_server(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
.....  
2954.          ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

### Unchecked Array Index\Path 35:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=290">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=290</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c
Line	3074	3074
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_location(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*dummy)

```
....  
3074.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =
```

### Unchecked Array Index\Path 36:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=291">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=291</a>
Status	New

	Source	Destination
File	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c	nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c
Line	4678	4678
Object	ctx_index	ctx_index

#### Code Snippet

File Name nginx@@nginx-release-1.27.0-CVE-2021-3618-FP.c  
Method ngx\_http\_core\_limit\_except(ngx\_conf\_t \*cf, ngx\_command\_t \*cmd, void \*conf)

```
....  
4678.                ctx->loc_conf[cf->cycle->modules[i]->ctx_index] =  
mconf;
```

## Improper Resource Access Authorization

Query Path:

CPP\Cx\CPP Low Visibility\Improper Resource Access Authorization Version:1

Categories



FISMA 2014: Identification And Authentication  
NIST SP 800-53: AC-3 Access Enforcement (P1)  
OWASP Top 10 2017: A2-Broken Authentication

#### Description

##### **Improper Resource Access Authorization\Path 1:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=378">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=378</a>
Status	New

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	361	361
Object	p	p

##### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c  
Method njs\_module\_read(njs\_vm\_t \*vm, int fd, njs\_str\_t \*text)

```
....  
361.      n = read(fd, p, sb.st_size);
```

##### **Improper Resource Access Authorization\Path 2:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=379">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=379</a>
Status	New

	Source	Destination
File	nginx@@njs-0.4.2-CVE-2022-29379-TP.c	nginx@@njs-0.4.2-CVE-2022-29379-TP.c
Line	418	418
Object	start	start

##### Code Snippet

File Name nginx@@njs-0.4.2-CVE-2022-29379-TP.c  
Method njs\_module\_read(njs\_vm\_t \*vm, int fd, njs\_str\_t \*text)

```
....  
418.      n = read(fd, text->start, sb.st_size);
```

##### **Improper Resource Access Authorization\Path 3:**

Severity	Low
----------	-----

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=380">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=380</a>
Status	New

	Source	Destination
File	nginx@@njs-0.5.0-CVE-2022-29379-TP.c	nginx@@njs-0.5.0-CVE-2022-29379-TP.c
Line	418	418
Object	start	start

#### Code Snippet

File Name nginx@@njs-0.5.0-CVE-2022-29379-TP.c

Method njs\_module\_read(njs\_vm\_t \*vm, int fd, njs\_str\_t \*text)

```
....  
418.      n = read(fd, text->start, sb.st_size);
```

### Improper Resource Access Authorization\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=381">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=381</a>
Status	New

	Source	Destination
File	nginx@@njs-0.5.2-CVE-2022-29379-TP.c	nginx@@njs-0.5.2-CVE-2022-29379-TP.c
Line	418	418
Object	start	start

#### Code Snippet

File Name nginx@@njs-0.5.2-CVE-2022-29379-TP.c

Method njs\_module\_read(njs\_vm\_t \*vm, int fd, njs\_str\_t \*text)

```
....  
418.      n = read(fd, text->start, sb.st_size);
```

### Improper Resource Access Authorization\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=382">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=382</a>
Status	New

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	6952	6952
Object	fprintf	fprintf

**Code Snippet**

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6952.          fprintf(stderr, "recv: [IB_EXPECT_CONTINUATION]\n");
```

**Improper Resource Access Authorization\Path 6:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=383>

Status New

	Source	Destination
File	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c
Line	6954	6954
Object	fprintf	fprintf

**Code Snippet**

File Name nghttp2@@nghttp2-v1.54.0-CVE-2020-11080-FP.c

Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6954.          fprintf(stderr, "recv: [IB_IGN_CONTINUATION]\n");
```

**Improper Resource Access Authorization\Path 7:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=384>

Status New

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	6896	6896

Object	fprintf	fprintf
--------	---------	---------

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6896.          fprintf(stderr, "recv: [IB_EXPECT_CONTINUATION]\n");
```

#### Improper Resource Access Authorization\Path 8:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=385>

Status New

	Source	Destination
File	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c
Line	6898	6898
Object	fprintf	fprintf

#### Code Snippet

File Name nghttp2@@nghttp2-v1.57.0-CVE-2020-11080-FP.c

Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6898.          fprintf(stderr, "recv: [IB_IGN_CONTINUATION]\n");
```

#### Improper Resource Access Authorization\Path 9:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&projectid=20038&pathid=386>

Status New

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	6896	6896
Object	fprintf	fprintf

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c

Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6896.          fprintf(stderr, "recv: [IB_EXPECT_CONTINUATION]\n");
```

### Improper Resource Access Authorization\Path 10:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=387">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=387</a>
Status	New

	Source	Destination
File	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c
Line	6898	6898
Object	fprintf	fprintf

#### Code Snippet

File Name nghttp2@@nghttp2-v1.59.0-CVE-2020-11080-FP.c  
Method ssize\_t nghttp2\_session\_mem\_recv(nghttp2\_session \*session, const uint8\_t \*in,

```
....  
6898.          fprintf(stderr, "recv: [IB_IGN_CONTINUATION]\n");
```

### Improper Resource Access Authorization\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=388">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=388</a>
Status	New

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	6954	6954
Object	fprintf	fprintf

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c  
Method nghttp2\_ssize nghttp2\_session\_mem\_recv2(nghttp2\_session \*session,

```
....  
6954.          fprintf(stderr, "recv: [IB_EXPECT_CONTINUATION]\n");
```

### Improper Resource Access Authorization\Path 12:

Severity	Low
----------	-----

Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=389">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=389</a>
Status	New

	Source	Destination
File	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c	nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c
Line	6956	6956
Object	fprintf	fprintf

#### Code Snippet

File Name nghttp2@@nghttp2-v1.62.0-CVE-2020-11080-FP.c

Method nghttp2\_ssize nghttp2\_session\_mem\_recv2(nghttp2\_session \*session,

```
....
6956.          fprintf(stderr, "recv: [IB_IGN_CONTINUATION]\n");
```

## TOCTOU

Query Path:

CPP\Cx\CPP Low Visibility\TOCTOU Version:1

[Description](#)

### TOCTOU\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=390">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=390</a>
Status	New

The njs\_module\_absolute\_path method in nginx@@njs-0.3.9-CVE-2022-29379-TP.c file utilizes open that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	nginx@@njs-0.3.9-CVE-2022-29379-TP.c	nginx@@njs-0.3.9-CVE-2022-29379-TP.c
Line	277	277
Object	open	open

#### Code Snippet

File Name nginx@@njs-0.3.9-CVE-2022-29379-TP.c

Method njs\_module\_absolute\_path(njs\_vm\_t \*vm, njs\_module\_info\_t \*info)

```
....
277.          info->fd = open((char *) file.start, O_RDONLY);
```

### TOCTOU\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=391">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=391</a>
Status	New

The `njs_module_relative_path` method in `nginx@@njs-0.3.9-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.3.9-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.3.9-CVE-2022-29379-TP.c</code>
Line	321	321
Object	<code>open</code>	<code>open</code>

#### Code Snippet

File Name `nginx@@njs-0.3.9-CVE-2022-29379-TP.c`  
Method `njs_module_relative_path(njs_vm_t *vm, const njs_str_t *dir,`

```
....  
321.         info->fd = open((char *) file.start, O_RDONLY);
```

#### TOCTOU\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=392">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=392</a>
Status	New

The `njs_module_absolute_path` method in `nginx@@njs-0.4.2-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>
Line	341	341
Object	<code>open</code>	<code>open</code>

#### Code Snippet

File Name `nginx@@njs-0.4.2-CVE-2022-29379-TP.c`  
Method `njs_module_absolute_path(njs_vm_t *vm, njs_module_info_t *info)`

```
....  
341.         info->fd = open((char *) file.start, O_RDONLY);
```

**TOCTOU\Path 4:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=393">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=393</a>
Status	New

The `njs_module_relative_path` method in `nginx@@njs-0.4.2-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.4.2-CVE-2022-29379-TP.c</code>
Line	385	385
Object	<code>open</code>	<code>open</code>

**Code Snippet**

File Name `nginx@@njs-0.4.2-CVE-2022-29379-TP.c`

Method `njs_module_relative_path(njs_vm_t *vm, const njs_str_t *dir,`

```
....  
385.         info->fd = open((char *) file.start, O_RDONLY);
```

**TOCTOU\Path 5:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=394">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=394</a>
Status	New

The `njs_module_absolute_path` method in `nginx@@njs-0.5.0-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.5.0-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.5.0-CVE-2022-29379-TP.c</code>
Line	341	341
Object	<code>open</code>	<code>open</code>

**Code Snippet**

File Name `nginx@@njs-0.5.0-CVE-2022-29379-TP.c`

Method `njs_module_absolute_path(njs_vm_t *vm, njs_module_info_t *info)`

```
....  
341.         info->fd = open((char *) file.start, O_RDONLY);
```



**TOCTOU\Path 6:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=395">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=395</a>
Status	New

The `njs_module_relative_path` method in `nginx@@njs-0.5.0-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.5.0-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.5.0-CVE-2022-29379-TP.c</code>
Line	385	385
Object	<code>open</code>	<code>open</code>

**Code Snippet**

File Name `nginx@@njs-0.5.0-CVE-2022-29379-TP.c`

Method `njs_module_relative_path(njs_vm_t *vm, const njs_str_t *dir,`

```
....  
385.      info->fd = open((char *) file.start, O_RDONLY);
```

**TOCTOU\Path 7:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=396">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=396</a>
Status	New

The `njs_module_absolute_path` method in `nginx@@njs-0.5.2-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2022-29379-TP.c</code>
Line	341	341
Object	<code>open</code>	<code>open</code>

**Code Snippet**

File Name `nginx@@njs-0.5.2-CVE-2022-29379-TP.c`

Method `njs_module_absolute_path(njs_vm_t *vm, njs_module_info_t *info)`

```
....
341.      info->fd = open((char *) file.start, O_RDONLY);
```

### TOCTOU\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=397">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1020045&amp;projectid=20038&amp;pathid=397</a>
Status	New

The `njs_module_relative_path` method in `nginx@@njs-0.5.2-CVE-2022-29379-TP.c` file utilizes `open` that is accessed by other concurrent functionality in a way that is not thread-safe, which may result in a Race Condition over this resource.

	Source	Destination
File	<code>nginx@@njs-0.5.2-CVE-2022-29379-TP.c</code>	<code>nginx@@njs-0.5.2-CVE-2022-29379-TP.c</code>
Line	385	385
Object	<code>open</code>	<code>open</code>

### Code Snippet

File Name `nginx@@njs-0.5.2-CVE-2022-29379-TP.c`  
 Method `njs_module_relative_path(njs_vm_t *vm, const njs_str_t *dir,`

```
....
385.      info->fd = open((char *) file.start, O_RDONLY);
```

## Buffer Overflow boundcpy WrongSizeParam

### Risk

#### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

### Cause

#### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
- Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strcpy` over `strncpy`, and so on.
- Consistently apply tests for the size of buffers.
- Do not return variable addresses outside the scope of their variables.

---

## Source Code Examples

### CPP

#### Overflowing Buffers

```
const int BUFFER_SIZE = 10;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    strcpy(buffer, inputString);
}
```

#### Checked Buffers

```
const int BUFFER_SIZE = 10;
const int MAX_INPUT_SIZE = 256;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    if (strlen(inputString, MAX_INPUT_SIZE) < sizeof(buffer))
    {
        strncpy(buffer, inputString, sizeof(buffer));
    }
}
```

# Dangerous Functions

## Risk

### What might happen

Use of dangerous functions may expose varying risks associated with each particular function, with potential impact of improper usage of these functions varying significantly. The presence of such functions indicates a flaw in code maintenance policies and adherence to secure coding practices, in a way that has allowed introducing known dangerous code into the application.

---

## Cause

### How does it happen

A dangerous function has been identified within the code. Functions are often deemed dangerous to use for numerous reasons, as there are different sets of vulnerabilities associated with usage of such functions. For example, some string copy and concatenation functions are vulnerable to Buffer Overflow, Memory Disclosure, Denial of Service and more. Use of these functions is not recommended.

---

## General Recommendations

### How to avoid it

- Deploy a secure and recommended alternative to any functions that were identified as dangerous.
    - If no secure alternative is found, conduct further researching and testing to identify whether current usage successfully sanitizes and verifies values, and thus successfully avoids the use-cases for whom the function is indeed dangerous
  - Conduct a periodical review of methods that are in use, to ensure that all external libraries and built-in functions are up-to-date and whose use has not been excluded from best secure coding practices.
- 

## Source Code Examples

### CPP

#### Buffer Overflow in gets()

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    gets(buf); // veryveryverylongname
    if (buf == ACCEPTED_NAME)
    {
        // Do something
    }
    return 0;
}
```

## Safe reading from user

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    fgets(buf, sizeof(buf), stdin); //setting the amount of bytes to read
    if (buf == ACCEPTED_NAME)
    {
        //Do something
    }
    return 0;
}
```

## Unsafe function for string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strcpy(buf, argv[1]); // overflow occurs when len(argv[1]) > 10 bytes

    return 0;
}
```

## Safe string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strncpy(buf, argv[1], sizeof(buf));
    buf[9] = '\0'; //strncpy doesn't NULL terminates

    return 0;
}
```

## Unsafe format string

```
int main(int argc, char* argv[])
{
    printf(argv[1]); // If argv[1] contains a format token, such as %s,%x or %d, will cause an access violation
    return 0;
}
```

## Safe format string

```
int main(int argc, char* argv[])
{
    printf("%s", argv[1]); // Second parameter is not a formattable string
    return 0;
}
```

# Use of Zero Initialized Pointer

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

### CPP

#### Explicit NULL Dereference

```
char * input = NULL;
printf("%s", input);
```

#### Implicit NULL Dereference

```
char * input;
printf("%s", input);
```

### Java

#### Explicit Null Dereference

```
Object o = null;  
out.println(o.getClass());
```



## Use of sizeof() on a Pointer Type

**Weakness ID:** 467 (*Weakness Variant*)

**Status:** Draft

### Description

### Description Summary

The code calls sizeof() on a malloced pointer type, which always returns the wordsize/8. This can produce an unexpected result if the programmer intended to determine how much memory has been allocated.

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C

C++

### Common Consequences

Scope	Effect
Integrity	This error can often cause one to allocate a buffer that is much smaller than what is needed, leading to resultant weaknesses such as buffer overflows.

### Likelihood of Exploit

High

### Demonstrative Examples

#### Example 1

Care should be taken to ensure sizeof returns the size of the data structure itself, and not the size of the pointer to the data structure.

In this example, sizeof(foo) returns the size of the pointer.

*(Bad Code)*

*Example Languages: C and C++*

```
double *foo;
...
foo = (double *)malloc(sizeof(foo));
```

In this example, sizeof(\*foo) returns the size of the data structure and not the size of the pointer.

*(Good Code)*

*Example Languages: C and C++*

```
double *foo;
...
foo = (double *)malloc(sizeof(*foo));
```

#### Example 2

This example defines a fixed username and password. The AuthenticateUser() function is intended to accept a username and a password from an untrusted user, and check to ensure that it matches the username and password. If the username and password match, AuthenticateUser() is intended to indicate that authentication succeeded.

*(Bad Code)*

*/\* Ignore CWE-259 (hard-coded password) and CWE-309 (use of password system for authentication) for this example. \*/*

```
char *username = "admin";
char *pass = "password";

int AuthenticateUser(char *inUser, char *inPass) {
```

```
printf("Sizeof username = %d\n", sizeof(username));
printf("Sizeof pass = %d\n", sizeof(pass));

if (strcmp(username, inUser, sizeof(username))) {
printf("Auth failure of username using sizeof\n");
return(AUTH_FAIL);
}
/* Because of CWE-467, the sizeof returns 4 on many platforms and architectures. */
if (! strcmp(pass, inPass, sizeof(pass))) {
printf("Auth success of password using sizeof\n");
return(AUTH_SUCCESS);
}
else {
printf("Auth fail of password using sizeof\n");
return(AUTH_FAIL);
}
}

int main (int argc, char **argv)
{
int authResult;

if (argc < 3) {
ExitError("Usage: Provide a username and password");
}
authResult = AuthenticateUser(argv[1], argv[2]);
if (authResult != AUTH_SUCCESS) {
ExitError("Authentication failed");
}
else {
DoAuthenticatedTask(argv[1]);
}
}
```

In `AuthenticateUser()`, because `sizeof()` is applied to a parameter with an array type, the `sizeof()` call might return 4 on many modern architectures. As a result, the `strcmp()` call only checks the first four characters of the input password, resulting in a partial comparison (CWE-187), leading to improper authentication (CWE-287).

Because of the partial comparison, any of these passwords would still cause authentication to succeed for the "admin" user:

*(Attack)*

```
pass5
passABCDEFGH
passWORD
```

Because only 4 characters are checked, this significantly reduces the search space for an attacker, making brute force attacks more feasible.

The same problem also applies to the username, so values such as "adminXYZ" and "administrator" will succeed for the username.

## Potential Mitigations

### Phase: Implementation

Use expressions such as "`sizeof(*pointer)`" instead of "`sizeof(pointer)`", unless you intend to run `sizeof()` on a pointer type to gain some platform independence or if you are allocating a variable on the stack.

## Other Notes

The use of `sizeof()` on a pointer can sometimes generate useful information. An obvious case is to find out the wordsize on a platform. More often than not, the appearance of `sizeof(pointer)` indicates a bug.

## Weakness Ordinalities

Ordinality	Description
Primary	<i>(where the weakness exists independent of other weaknesses)</i>

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	465	<a href="#">Pointer Issues</a>	<b>Development Concepts (primary)699</b>
ChildOf	Weakness Class	682	<a href="#">Incorrect Calculation</a>	<b>Research Concepts (primary)1000</b>
ChildOf	Category	737	<a href="#">CERT C Secure Coding Section 03 - Expressions (EXP)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
CanPrecede	Weakness Base	131	<a href="#">Incorrect Calculation of Buffer Size</a>	Research Concepts1000

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Use of sizeof() on a pointer type
CERT C Secure Coding	ARR01-C		Do not apply the sizeof operator to a pointer when taking the size of an array
CERT C Secure Coding	EXP01-C		Do not take the size of a pointer to determine the size of the pointed-to type

## White Box Definitions

A weakness where code path has:

1. end statement that passes an identity of a dynamically allocated memory resource to a sizeof operator
2. start statement that allocates the dynamically allocated memory resource

## References

Robert Seacord. "EXP01-A. Do not take the sizeof a pointer to determine the size of a type".  
<https://www.securecoding.cert.org/confluence/display/seccode/EXP01-A.+Do+not+take+the+sizeof+a+pointer+to+determine+the+size+of+a+type>.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci updated Time of Introduction	Cigital	External
2008-08-01	 added/updated white box definitions	KDM Analytics	External
2008-09-08	CWE Content Team updated Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities	MITRE	Internal
2008-11-24	CWE Content Team updated Relationships, Taxonomy Mappings	MITRE	Internal
2009-03-10	CWE Content Team updated Demonstrative Examples	MITRE	Internal
2009-12-28	CWE Content Team updated Demonstrative Examples	MITRE	Internal
2010-02-16	CWE Content Team updated Relationships	MITRE	Internal

[BACK TO TOP](#)

# NULL Pointer Dereference

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

## Improper Validation of Array Index

**Weakness ID:** 129 (*Weakness Base*)

**Status:** Draft

### Description

### Description Summary

The product uses untrusted input when calculating or using an array index, but the product does not validate or incorrectly validates the index to ensure the index references a valid position within the array.

### Alternate Terms

out-of-bounds array index

index-out-of-range

array index underflow

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C: (*Often*)

C++: (*Often*)

### Language-independent

### Common Consequences

Scope	Effect
Integrity Availability	Unchecked array indexing will very likely result in the corruption of relevant memory and perhaps instructions, leading to a crash, if the values are outside of the valid memory area.
Integrity	If the memory corrupted is data, rather than instructions, the system will continue to function with improper values.
Confidentiality Integrity	Unchecked array indexing can also trigger out-of-bounds read or write operations, or operations on the wrong objects; i.e., "buffer overflows" are not always the result. This may result in the exposure or modification of sensitive data.
Integrity	If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow and possibly without the use of large inputs if a precise index can be controlled.
Integrity Availability Confidentiality	A single fault could allow either an overflow (CWE-788) or underflow (CWE-786) of the array index. What happens next will depend on the type of operation being performed out of bounds, but can expose sensitive information, cause a system crash, or possibly lead to arbitrary code execution.

### Likelihood of Exploit

High

### Detection Methods

#### Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report array index errors that originate from command line arguments in a program that is not expected to run with setuid or other special privileges.

**Effectiveness: High**

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

---

### Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

---

### Black Box

Black box methods might not get the needed code coverage within limited time constraints, and a dynamic test might not produce any noticeable side effects even if it is successful.

---

## Demonstrative Examples

### Example 1

The following C/C++ example retrieves the sizes of messages for a pop3 mail server. The message sizes are retrieved from a socket that returns in a buffer the message number and the message size, the message number (num) and size (size) are extracted from the buffer and the message size is placed into an array using the message number for the array index.

*(Bad Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;

    // read values from socket and added to sizes array
    while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
    {

        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
            break;
        else if (sscanf(buf, "%d %d", &num, &size) == 2)
            sizes[num - 1] = size;
        }
    ...
}
```

In this example the message number retrieved from the buffer could be a value that is outside the allowable range of indices for the array and could possibly be a negative number. Without proper validation of the value to be used for the array index an array overflow could occur and could potentially lead to unauthorized access to memory addresses and system crashes. The value of the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
    ...
    char buf[BUFFER_SIZE];
    int ok;
    int num, size;

    // read values from socket and added to sizes array
    while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
    {

        // continue read from socket until buf only contains '.'
        if (DOTLINE(buf))
```

```
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2) {
if (num > 0 && num <= (unsigned)count)
sizes[num - 1] = size;
else
/* warn about possible attempt to induce buffer overflow */
report(stderr, "Warning: ignoring bogus data for message sizes returned by server.\n");
}
}
...
}
```

## Example 2

In the code snippet below, an unchecked integer value is used to reference an object in an array.

*(Bad Code)*

**Example Language: Java**

```
public String getValue(int index) {
return array[index];
}
```

If index is outside of the range of the array, this may result in an `ArrayIndexOutOfBoundsException` Exception being raised.

## Example 3

In the following Java example the method `displayProductSummary` is called from a Web service servlet to retrieve product summary information for display to the user. The servlet obtains the integer value of the product number from the user and passes it to the `displayProductSummary` method. The `displayProductSummary` method passes the integer value of the product number to the `getProductSummary` method which obtains the product summary from the array object containing the project summaries using the integer value of the product number as the array index.

*(Bad Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");

try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
return products[index];
}
```

In this example the integer value used as the array index that is provided by the user may be outside the allowable range of indices for the array which may provide unexpected results or may cause the application to fail. The integer value used for the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");
```

```
try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
String productSummary = "";

if ((index >= 0) && (index < MAX_PRODUCTS)) {
productSummary = products[index];
}
else {
System.err.println("index is out of bounds");
throw new IndexOutOfBoundsException();
}

return productSummary;
}
```

An alternative in Java would be to use one of the collection objects such as `ArrayList` that will automatically generate an exception if an attempt is made to access an array index that is out of bounds.

*(Good Code)*

#### Example Language: Java

```
ArrayList productArray = new ArrayList(MAX_PRODUCTS);
...
try {
productSummary = (String) productArray.get(index);
} catch (IndexOutOfBoundsException ex) {...}
```

### Observed Examples

Reference	Description
<a href="#">CVE-2005-0369</a>	large ID in packet used as array index
<a href="#">CVE-2001-1009</a>	negative array index as argument to POP LIST command
<a href="#">CVE-2003-0721</a>	Integer signedness error leads to negative array index
<a href="#">CVE-2004-1189</a>	product does not properly track a count and a maximum number, which can lead to resultant array index overflow.
<a href="#">CVE-2007-5756</a>	chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error.

### Potential Mitigations

#### Phase: Architecture and Design

### Strategies: Input Validation; Libraries or Frameworks

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

---

#### Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

---

#### Phase: Requirements

### Strategy: Language Selection

Use a language with features that can automatically mitigate or eliminate out-of-bounds indexing errors.

---



For example, Ada allows the programmer to constrain the values of a variable and languages such as Java and Ruby will allow the programmer to handle exceptions when an out-of-bounds index is accessed.

#### Phase: Implementation

### Strategy: Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy (i.e., use a whitelist). Reject any input that does not strictly conform to specifications, or transform it into something that does. Use a blacklist to reject any unexpected inputs and detect potential attacks.

When accessing a user-controlled array index, use a stringent range of values that are within the target array. Make sure that you do not allow negative values to be used. That is, verify the minimum as well as the maximum of the range of acceptable values.

#### Phase: Implementation

Be especially careful to validate your input when you invoke code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

### Weakness Ordinalities

Ordinality	Description
Resultant	The most common condition situation leading to unchecked array indexing is the use of loop index variables as buffer indexes. If the end condition for the loop is subject to a flaw, the index can grow or shrink unbounded, therefore causing a buffer overflow or underflow. Another common situation leading to this condition is the use of a function's return value, or the resulting value of a calculation directly as an index in to a buffer.

### Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	20	<a href="#">Improper Input Validation</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	189	<a href="#">Numeric Errors</a>	Development Concepts699
ChildOf	Category	633	<a href="#">Weaknesses that Affect Memory</a>	<b>Resource-specific Weaknesses (primary)631</b>
ChildOf	Category	738	<a href="#">CERT C Secure Coding Section 04 - Integers (INT)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
ChildOf	Category	802	<a href="#">2010 Top 25 - Risky Resource Management</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
CanPrecede	Weakness Class	119	<a href="#">Failure to Constrain Operations within the Bounds of a Memory Buffer</a>	Research Concepts1000
CanPrecede	Weakness Variant	789	<a href="#">Uncontrolled Memory Allocation</a>	Research Concepts1000
PeerOf	Weakness Base	124	<a href="#">Buffer Underwrite ('Buffer Underflow')</a>	Research Concepts1000

### Theoretical Notes

An improperly validated array index might lead directly to the always-incorrect behavior of "access of array using out-of-bounds index."

### Affected Resources

## Memory

### f Causal Nature

### Explicit

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unchecked array indexing
PLOVER			INDEX - Array index overflow
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C		Guarantee that array indices are within the valid range
CERT C Secure Coding	ARR38-C		Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element
CERT C Secure Coding	INT32-C		Ensure that operations on signed integers do not result in overflow

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">100</a>	Overflow Buffers	

### References

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 5, "Array Indexing Errors" Page 144. 2nd Edition. Microsoft. 2002.

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Sean Eidemiller	Cigital	External
	added/updated demonstrative examples		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities		
2008-11-24	CWE Content Team	MITRE	Internal
	updated Relationships, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Description, Name, Relationships		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Observed Examples, Other Notes, Potential Mitigations, Theoretical Notes, Weakness Ordinalities		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Demonstrative Examples, Detection Factors, Likelihood of Exploit, Potential Mitigations, References, Related Attack Patterns, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Related Attack Patterns		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-10-29	Unchecked Array Indexing		

[BACK TO TOP](#)

## Improper Access Control (Authorization)

**Weakness ID:** 285 (*Weakness Class*)

**Status:** Draft

### Description

### Description Summary

The software does not perform or incorrectly performs access control checks across all potential execution paths.

### Extended Description

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information leaks, denial of service, and arbitrary code execution.

### Alternate Terms

#### AuthZ:

"AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

### Time of Introduction

- Architecture and Design
- Implementation
- Operation

### Applicable Platforms

#### Languages

Language-independent

#### Technology Classes

Web-Server: (*Often*)

Database-Server: (*Often*)

### Modes of Introduction

A developer may introduce authorization weaknesses because of a lack of understanding about the underlying technologies. For example, a developer may assume that attackers cannot modify certain inputs such as headers or cookies.

Authorization weaknesses may arise when a single-user application is ported to a multi-user environment.

### Common Consequences

Scope	Effect
Confidentiality	An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.
Integrity	An attacker could modify sensitive data, either by writing the data directly to a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.
Integrity	An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.

### Likelihood of Exploit

High

### Detection Methods

### Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries.

Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

### **Effectiveness: Limited**

---

### Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

---

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

### **Effectiveness: Moderate**

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

---

## Demonstrative Examples

### Example 1

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

*(Bad Code)*

#### Example Language: Perl

```
sub DisplayPrivateMessage {
my($id) = @_ ;
my $Message = LookupMessageObject($id);
print "From: " . encodeHTML($Message->{from}) . "<br>\n";
print "Subject: " . encodeHTML($Message->{subject}) . "\n";
print "<hr>\n";
print "Body: " . encodeHTML($Message->{body}) . "\n";
}

my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
ExitError("invalid username or password");
}

my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users. One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

## Observed Examples

Reference	Description
<a href="#">CVE-2009-3168</a>	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords.

<a href="#">CVE-2009-2960</a>	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users.
<a href="#">CVE-2009-3597</a>	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request.
<a href="#">CVE-2009-2282</a>	Terminal server does not check authorization for guest access.
<a href="#">CVE-2009-3230</a>	Database server does not use appropriate privileges for certain sensitive operations.
<a href="#">CVE-2009-2213</a>	Gateway uses default "Allow" configuration for its authorization settings.
<a href="#">CVE-2009-0034</a>	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges.
<a href="#">CVE-2008-6123</a>	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect.
<a href="#">CVE-2008-5027</a>	System monitoring software allows users to bypass authorization by creating custom forms.
<a href="#">CVE-2008-7109</a>	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client.
<a href="#">CVE-2008-3424</a>	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access.
<a href="#">CVE-2009-3781</a>	Content management system does not check access permissions for private files, allowing others to view those files.
<a href="#">CVE-2008-4577</a>	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions.
<a href="#">CVE-2008-6548</a>	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files.
<a href="#">CVE-2007-2925</a>	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries.
<a href="#">CVE-2006-6679</a>	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header.
<a href="#">CVE-2005-3623</a>	OS kernel does not check for a certain privilege before setting ACLs for files.
<a href="#">CVE-2005-2801</a>	Chain: file-system code performs an incorrect comparison (CWE-697), preventing defaults ACLs from being properly applied.
<a href="#">CVE-2001-1155</a>	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions.

## Potential Mitigations

### Phase: Architecture and Design

Divide your application into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries.

Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

### Phase: Architecture and Design

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

### Phase: Architecture and Design

## Strategy: Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness

easier to avoid.

For example, consider using authorization frameworks such as the JAAS Authorization Framework and the OWASP ESAPI Access Control feature.

### Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page.

One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

### Phases: System Configuration; Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	254	<a href="#">Security Features</a>	<b>Seven Pernicious Kingdoms (primary)700</b>
ChildOf	Weakness Class	284	<a href="#">Access Control (Authorization) Issues</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	721	<a href="#">OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access</a>	<b>Weaknesses in OWASP Top Ten (2007) (primary)629</b>
ChildOf	Category	723	<a href="#">OWASP Top Ten 2004 Category A2 - Broken Access Control</a>	<b>Weaknesses in OWASP Top Ten (2004) (primary)711</b>
ChildOf	Category	753	<a href="#">2009 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)750</b>
ChildOf	Category	803	<a href="#">2010 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
ParentOf	Weakness Variant	219	<a href="#">Sensitive Data Under Web Root</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Base	551	<a href="#">Incorrect Behavior Order: Authorization Before Parsing and Canonicalization</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts1000</b>
ParentOf	Weakness Class	638	<a href="#">Failure to Use Complete Mediation</a>	<b>Research Concepts1000</b>
ParentOf	Weakness Base	804	<a href="#">Guessable CAPTCHA</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">1</a>	Accessing Functionality Not Properly Constrained by ACLs	
<a href="#">13</a>	Subverting Environment Variable Values	

<a href="#">17</a>	Accessing, Modifying or Executing Executable Files
<a href="#">87</a>	Forceful Browsing
<a href="#">39</a>	Manipulating Opaque Client-based Data Tokens
<a href="#">45</a>	Buffer Overflow via Symbolic Links
<a href="#">51</a>	Poison Web Service Registry
<a href="#">59</a>	Session Credential Falsification through Prediction
<a href="#">60</a>	Reusing Session IDs (aka Session Replay)
<a href="#">77</a>	Manipulating User-Controlled Variables
<a href="#">76</a>	Manipulating Input to File System Calls
<a href="#">104</a>	Cross Zone Scripting

## References

NIST. "Role Based Access Control and Role Based Security". <<http://csrc.nist.gov/groups/SNS/rbac/>>.

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 4, "Authorization" Page 114; Chapter 6, "Determining Appropriate Access Control" Page 171. 2nd Edition. Microsoft. 2002.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-15		Veracode	External
	Suggested OWASP Top Ten 2004 mapping		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Relationships, Other Notes, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences, Description, Likelihood of Exploit, Name, Other Notes, Potential Mitigations, References, Relationships		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Description, Related Attack Patterns		
2009-07-27	CWE Content Team	MITRE	Internal
	updated Relationships		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Type		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Demonstrative Examples, Detection Factors, Modes of Introduction, Observed Examples, Relationships		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Detection Factors, Potential Mitigations, References, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-01-12	Missing or Inconsistent Access Control		

[BACK TO TOP](#)

# TOCTOU

## Risk

### What might happen

At best, a Race Condition may cause errors in accuracy, overridden values or unexpected behavior that may result in denial-of-service. At worst, it may allow attackers to retrieve data or bypass security processes by replaying a controllable Race Condition until it plays out in their favor.

---

## Cause

### How does it happen

Race Conditions occur when a public, single instance of a resource is used by multiple concurrent logical processes. If these logical processes attempt to retrieve and update the resource without a timely management system, such as a lock, a Race Condition will occur.

An example for when a Race Condition occurs is a resource that may return a certain value to a process for further editing, and then updated by a second process, resulting in the original process' data no longer being valid. Once the original process edits and updates the incorrect value back into the resource, the second process' update has been overwritten and lost.

---

## General Recommendations

### How to avoid it

When sharing resources between concurrent processes across the application ensure that these resources are either thread-safe, or implement a locking mechanism to ensure expected concurrent activity.

---

## Source Code Examples

### Java Different Threads Increment and Decrement The Same Counter Repeatedly, Resulting in a Race Condition

```
public static int counter = 0;
public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) {
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); //Will stop and return either -1 or 1 due to race
    condition over counter
}

public static class incrementCounter extends Thread {
    public void run() {
        counter++;
    }
}
```



```
}

public static class decrementCounter extends Thread {
    public void run() {
        counter--;
    }
}
```

### Different Threads Increment and Decrement The Same Thread-Safe Counter Repeatedly, Never Resulting in a Race Condition

```
public static int counter = 0;
public static Object lock = new Object();

public static void start() throws InterruptedException {
    incrementCounter ic;
    decrementCounter dc;
    while(counter == 0) { // because of proper locking, this condition is never false
        counter = 0;
        ic = new incrementCounter();
        dc = new decrementCounter();
        ic.start();
        dc.start();
        ic.join();
        dc.join();
    }
    System.out.println(counter); // Never reached
}

public static class incrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter++;
        }
    }
}

public static class decrementCounter extends Thread {
    public void run() {
        synchronized (lock) {
            counter--;
        }
    }
}
```

## Scanned Languages

Language	Hash Number	Change Date
CPP	4541647240435660	1/6/2025
Common	0105849645654507	1/6/2025