

## vul\_files\_20 Scan Report

Project Name	vul_files_20
Scan Start	Tuesday, January 7, 2025 10:17:38 AM
Preset	Checkmarx Default
Scan Time	01h:36m:20s
Lines Of Code Scanned	295798
Files Scanned	66
Report Creation Time	Tuesday, January 7, 2025 11:25:01 AM
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22</a>
Team	CxServer
Checkmarx Version	8.7.0
Scan Type	Full
Source Origin	LocalPath
Density	4/1000 (Vulnerabilities/LOC)
Visibility	Public

## Filter Settings

### **Severity**

Included: High, Medium, Low, Information

Excluded: None

### **Result State**

Included: Confirmed, Not Exploitable, To Verify, Urgent, Proposed Not Exploitable

Excluded: None

### **Assigned to**

Included: All

### **Categories**

Included:

Uncategorized All

Custom All

PCI DSS v3.2 All

OWASP Top 10 2013 All

FISMA 2014 All

NIST SP 800-53 All

OWASP Top 10 2017 All

OWASP Mobile Top 10  
2016 All

Excluded:

Uncategorized None

Custom None

PCI DSS v3.2 None

OWASP Top 10 2013 None

FISMA 2014 None

NIST SP 800-53	None
OWASP Top 10 2017	None
OWASP Mobile Top 10 2016	None

**Results Limit**


Results limit per query was set to 50

**Selected Queries**


Selected queries are listed in [Result Summary](#)

---

## Result Summary



## Most Vulnerable Files



gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c


gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c

gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c

gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c

## Top 5 Vulnerabilities



## Scan Summary - OWASP Top 10 2017

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2017](#)

Category	Threat Agent	Exploitability	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	App. Specific	EASY	COMMON	EASY	SEVERE	App. Specific	248	221
A2-Broken Authentication	App. Specific	EASY	COMMON	AVERAGE	SEVERE	App. Specific	52	52
A3-Sensitive Data Exposure	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	App. Specific	0	0
A4-XML External Entities (XXE)	App. Specific	AVERAGE	COMMON	EASY	SEVERE	App. Specific	0	0
A5-Broken Access Control*	App. Specific	AVERAGE	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A6-Security Misconfiguration	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A7-Cross-Site Scripting (XSS)	App. Specific	EASY	WIDESPREAD	EASY	MODERATE	App. Specific	0	0
A8-Insecure Deserialization	App. Specific	DIFFICULT	COMMON	AVERAGE	SEVERE	App. Specific	0	0
A9-Using Components with Known Vulnerabilities*	App. Specific	AVERAGE	WIDESPREAD	AVERAGE	MODERATE	App. Specific	720	720
A10-Insufficient Logging & Monitoring	App. Specific	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	App. Specific	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - OWASP Top 10 2013

Further details and elaboration about vulnerabilities and risks can be found at: [OWASP Top 10 2013](#)

Category	Threat Agent	Attack Vectors	Weakness Prevalence	Weakness Detectability	Technical Impact	Business Impact	Issues Found	Best Fix Locations
A1-Injection	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	AVERAGE	SEVERE	ALL DATA	0	0
A2-Broken Authentication and Session Management	EXTERNAL, INTERNAL USERS	AVERAGE	WIDESPREAD	AVERAGE	SEVERE	AFFECTED DATA AND FUNCTIONS	0	0
A3-Cross-Site Scripting (XSS)	EXTERNAL, INTERNAL, ADMIN USERS	AVERAGE	VERY WIDESPREAD	EASY	MODERATE	AFFECTED DATA AND SYSTEM	0	0
A4-Insecure Direct Object References	SYSTEM USERS	EASY	COMMON	EASY	MODERATE	EXPOSED DATA	0	0
A5-Security Misconfiguration	EXTERNAL, INTERNAL, ADMIN USERS	EASY	COMMON	EASY	MODERATE	ALL DATA AND SYSTEM	0	0
A6-Sensitive Data Exposure	EXTERNAL, INTERNAL, ADMIN USERS, USERS BROWSERS	DIFFICULT	UNCOMMON	AVERAGE	SEVERE	EXPOSED DATA	0	0
A7-Missing Function Level Access Control*	EXTERNAL, INTERNAL USERS	EASY	COMMON	AVERAGE	MODERATE	EXPOSED DATA AND FUNCTIONS	0	0
A8-Cross-Site Request Forgery (CSRF)	USERS BROWSERS	AVERAGE	COMMON	EASY	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0
A9-Using Components with Known Vulnerabilities*	EXTERNAL USERS, AUTOMATED TOOLS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	720	720
A10-Unvalidated Redirects and Forwards	USERS BROWSERS	AVERAGE	WIDESPREAD	DIFFICULT	MODERATE	AFFECTED DATA AND FUNCTIONS	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - PCI DSS v3.2

Category	Issues Found	Best Fix Locations
PCI DSS (3.2) - 6.5.1 - Injection flaws - particularly SQL injection	0	0
PCI DSS (3.2) - 6.5.2 - Buffer overflows	207	186
PCI DSS (3.2) - 6.5.3 - Insecure cryptographic storage	0	0
PCI DSS (3.2) - 6.5.4 - Insecure communications	0	0
PCI DSS (3.2) - 6.5.5 - Improper error handling*	0	0
PCI DSS (3.2) - 6.5.7 - Cross-site scripting (XSS)	0	0
PCI DSS (3.2) - 6.5.8 - Improper access control	0	0
PCI DSS (3.2) - 6.5.9 - Cross-site request forgery	0	0
PCI DSS (3.2) - 6.5.10 - Broken authentication and session management	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - FISMA 2014

Category	Description	Issues Found	Best Fix Locations
Access Control	Organizations must limit information system access to authorized users, processes acting on behalf of authorized users, or devices (including other information systems) and to the types of transactions and functions that authorized users are permitted to exercise.	0	0
Audit And Accountability*	Organizations must: (i) create, protect, and retain information system audit records to the extent needed to enable the monitoring, analysis, investigation, and reporting of unlawful, unauthorized, or inappropriate information system activity; and (ii) ensure that the actions of individual information system users can be uniquely traced to those users so they can be held accountable for their actions.	0	0
Configuration Management	Organizations must: (i) establish and maintain baseline configurations and inventories of organizational information systems (including hardware, software, firmware, and documentation) throughout the respective system development life cycles; and (ii) establish and enforce security configuration settings for information technology products employed in organizational information systems.	0	0
Identification And Authentication*	Organizations must identify information system users, processes acting on behalf of users, or devices and authenticate (or verify) the identities of those users, processes, or devices, as a prerequisite to allowing access to organizational information systems.	52	52
Media Protection	Organizations must: (i) protect information system media, both paper and digital; (ii) limit access to information on information system media to authorized users; and (iii) sanitize or destroy information system media before disposal or release for reuse.	0	0
System And Communications Protection	Organizations must: (i) monitor, control, and protect organizational communications (i.e., information transmitted or received by organizational information systems) at the external boundaries and key internal boundaries of the information systems; and (ii) employ architectural designs, software development techniques, and systems engineering principles that promote effective information security within organizational information systems.	0	0
System And Information Integrity	Organizations must: (i) identify, report, and correct information and information system flaws in a timely manner; (ii) provide protection from malicious code at appropriate locations within organizational information systems; and (iii) monitor information system security alerts and advisories and take appropriate actions in response.	0	0

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.

## Scan Summary - NIST SP 800-53

Category	Issues Found	Best Fix Locations
AC-12 Session Termination (P2)	0	0
AC-3 Access Enforcement (P1)	52	52
AC-4 Information Flow Enforcement (P1)	0	0
AC-6 Least Privilege (P1)	0	0
AU-9 Protection of Audit Information (P1)	0	0
CM-6 Configuration Settings (P2)	0	0
IA-5 Authenticator Management (P1)	0	0
IA-6 Authenticator Feedback (P2)	0	0
IA-8 Identification and Authentication (Non-Organizational Users) (P1)	0	0
SC-12 Cryptographic Key Establishment and Management (P1)	0	0
SC-13 Cryptographic Protection (P1)	0	0
SC-17 Public Key Infrastructure Certificates (P1)	0	0
SC-18 Mobile Code (P2)	0	0
SC-23 Session Authenticity (P1)*	0	0
SC-28 Protection of Information at Rest (P1)	0	0
SC-4 Information in Shared Resources (P1)	0	0
SC-5 Denial of Service Protection (P1)*	174	63
SC-8 Transmission Confidentiality and Integrity (P1)	0	0
SI-10 Information Input Validation (P1)*	60	41
SI-11 Error Handling (P2)*	19	19
SI-15 Information Output Filtering (P0)	0	0
SI-16 Memory Protection (P1)	3	1

\* Project scan results do not include all relevant queries. Presets and/or Filters should be changed to include all relevant standard queries.



## Scan Summary - OWASP Mobile Top 10 2016

Category	Description	Issues Found	Best Fix Locations
M1-Improper Platform Usage	This category covers misuse of a platform feature or failure to use platform security controls. It might include Android intents, platform permissions, misuse of TouchID, the Keychain, or some other security control that is part of the mobile operating system. There are several ways that mobile apps can experience this risk.	0	0
M2-Insecure Data Storage	This category covers insecure data storage and unintended data leakage.	0	0
M3-Insecure Communication	This category covers poor handshaking, incorrect SSL versions, weak negotiation, cleartext communication of sensitive assets, etc.	0	0
M4-Insecure Authentication	This category captures notions of authenticating the end user or bad session management. This can include: -Failing to identify the user at all when that should be required -Failure to maintain the user's identity when it is required -Weaknesses in session management	0	0
M5-Insufficient Cryptography	The code applies cryptography to a sensitive information asset. However, the cryptography is insufficient in some way. Note that anything and everything related to TLS or SSL goes in M3. Also, if the app fails to use cryptography at all when it should, that probably belongs in M2. This category is for issues where cryptography was attempted, but it wasn't done correctly.	0	0
M6-Insecure Authorization	This is a category to capture any failures in authorization (e.g., authorization decisions in the client side, forced browsing, etc.). It is distinct from authentication issues (e.g., device enrolment, user identification, etc.). If the app does not authenticate users at all in a situation where it should (e.g., granting anonymous access to some resource or service when authenticated and authorized access is required), then that is an authentication failure not an authorization failure.	0	0
M7-Client Code Quality	This category is the catch-all for code-level implementation problems in the mobile client. That's distinct from server-side coding mistakes. This would capture things like buffer overflows, format string vulnerabilities, and various other code-level mistakes where the solution is to rewrite some code that's running on the mobile device.	0	0
M8-Code Tampering	This category covers binary patching, local resource modification, method hooking, method swizzling, and dynamic memory modification. Once the application is delivered to the mobile device, the code and data resources are resident there. An attacker can either directly modify the code, change the contents of memory dynamically, change or replace the system APIs that the application uses, or	0	0

	modify the application's data and resources. This can provide the attacker a direct method of subverting the intended use of the software for personal or monetary gain.		
M9-Reverse Engineering	This category includes analysis of the final core binary to determine its source code, libraries, algorithms, and other assets. Software such as IDA Pro, Hopper, otool, and other binary inspection tools give the attacker insight into the inner workings of the application. This may be used to exploit other nascent vulnerabilities in the application, as well as revealing information about back end servers, cryptographic constants and ciphers, and intellectual property.	0	0
M10-Extraneous Functionality	Often, developers include hidden backdoor functionality or other internal development security controls that are not intended to be released into a production environment. For example, a developer may accidentally include a password as a comment in a hybrid app. Another example includes disabling of 2-factor authentication during testing.	0	0


## Scan Summary - Custom

Category	Issues Found	Best Fix Locations
Must audit	0	0
Check	0	0
Optional	0	0

## Results Distribution By Status First scan of the project

	High	Medium	Low	Information	Total
New Issues	24	1,062	140	0	1,226
Recurrent Issues	0	0	0	0	0
Total	24	1,062	140	0	1,226

Fixed Issues	0	0	0	0	0
--------------	---	---	---	---	---



## Results Distribution By State

	High	Medium	Low	Information	Total
Confirmed	0	0	0	0	0
Not Exploitable	0	0	0	0	0
To Verify	24	1,062	140	0	1,226
Urgent	0	0	0	0	0
Proposed Not Exploitable	0	0	0	0	0
Total	24	1,062	140	0	1,226

## Result Summary

Vulnerability Type	Occurrences	Severity
<a href="#">Buffer Overflow StrcpyStrcat</a>	24	High
<a href="#">Dangerous Functions</a>	720	Medium
<a href="#">Buffer Overflow boundcpy WrongSizeParam</a>	180	Medium
<a href="#">Use of Zero Initialized Pointer</a>	141	Medium
<a href="#">Divide By Zero</a>	18	Medium

<a href="#">Buffer Overflow Loops</a>	3	Medium
<a href="#">Improper Resource Access Authorization</a>	52	Low
<a href="#">NULL Pointer Dereference</a>	33	Low
<a href="#">Unchecked Array Index</a>	28	Low
<a href="#">Unchecked Return Value</a>	19	Low
<a href="#">Potential Precision Problem</a>	8	Low

## 10 Most Vulnerable Files

### High and Medium Vulnerabilities

File Name	Issues Found
gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	90
gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	78
gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	78
gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	78
gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	78
gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	78
gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	78
gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	78
gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	78
gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	63

# Scan Results Details

## Buffer Overflow StrcpyStrcat

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow StrcpyStrcat Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
NIST SP 800-53: SI-10 Information Input Validation (P1)  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow StrcpyStrcat\Path 1:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1</a>
Status	New

The size of the buffer used by revert\_cache\_file in item\_path, at line 4509 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4522
Object	mpd_src	item_path

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```



File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4522.      strcpy(szPATH, item_path);
```

#### Buffer Overflow StrcpyStrcat\Path 2:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22</a>

Status	<a href="#">&amp;pathid=2</a> New
--------	--------------------------------------

The size of the buffer used by `revert_cache_file` in `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `rip_mpd` passes to `output_dir`, at line 4566 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>
Line	4566	4522
Object	<code>output_dir</code>	<code>item_path</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`  
 Method `GF_Err rip_mpd(const char *mpd_src, const char *output_dir)`

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`  
 Method `static void revert_cache_file(char *item_path)`

```
....
4522.      strcpy(szPATH, item_path);
```

#### Buffer Overflow StrcpyStrcat\Path 3:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=3">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=3</a>
Status	New

The size of the buffer used by `revert_cache_file` in `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `revert_cache_file` passes to `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>
Line	4509	4522
Object	<code>item_path</code>	<code>item_path</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`  
 Method `static void revert_cache_file(char *item_path)`

```
....
4509. static void revert_cache_file(char *item_path)
....
4522.      strcpy(szPATH, item_path);
```

#### Buffer Overflow StrcpyStrcat\Path 4:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=4">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=4</a>
Status	New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4523
Object	mpd_src	szPATH

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4523.      strcat(szPATH, ".txt");
```

#### Buffer Overflow StrcpyStrcat\Path 5:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=5">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=5</a>
Status	New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.



	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4523
Object	output_dir	szPATH

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4523.      strcat(szPATH, ".txt");
```

#### Buffer Overflow StrcpyStrcat\Path 6:

Severity High  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=6>  
Status New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that revert\_cache\_file passes to item\_path, at line 4509 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4509	4523
Object	item_path	szPATH

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4509.  static void revert_cache_file(char *item_path)
....
4523.      strcat(szPATH, ".txt");
```

#### Buffer Overflow StrcpyStrcat\Path 7:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=7">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=7</a>
Status	New

The size of the buffer used by rip\_mpd in sess, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4606
Object	mpd_src	sess

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)  
....  
4606.          strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

#### Buffer Overflow StrcpyStrcat\Path 8:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=8">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=8</a>
Status	New

The size of the buffer used by rip\_mpd in gf\_dm\_sess\_get\_cache\_name, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4606
Object	mpd_src	gf_dm_sess_get_cache_name

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
....
4606.      strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

### Buffer Overflow StrcpyStrcat\Path 9:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=9">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=9</a>
Status	New

The size of the buffer used by rip\_mpd in output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4581
Object	output_dir	output_dir

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
....
4581.      strcpy(szName, output_dir);
```

### Buffer Overflow StrcpyStrcat\Path 10:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=10">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=10</a>
Status	New

The size of the buffer used by rip\_mpd in szName, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4566	4606
Object	output_dir	szName

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c

Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)  
....  
4606.          strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

**Buffer Overflow StrcpyStrcat\Path 11:**

Severity High

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=11>

Status New

The size of the buffer used by revert\_cache\_file in item\_path, at line 4509 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4522
Object	mpd_src	item_path

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```



File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method static void revert\_cache\_file(char \*item\_path)

```
....  
4522.          strcpy(szPATH, item_path);
```

**Buffer Overflow StrcpyStrcat\Path 12:**

Severity High

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=12>

Status New

The size of the buffer used by `revert_cache_file` in `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `rip_mpd` passes to `output_dir`, at line 4566 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>
Line	4566	4522
Object	<code>output_dir</code>	<code>item_path</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`  
 Method `GF_Err rip_mpd(const char *mpd_src, const char *output_dir)`

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`  
 Method `static void revert_cache_file(char *item_path)`

```
....
4522.      strcpy(szPATH, item_path);
```

#### Buffer Overflow StrcpyStrcat\Path 13:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=13">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=13</a>
Status	New

The size of the buffer used by `revert_cache_file` in `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `revert_cache_file` passes to `item_path`, at line 4509 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>
Line	4509	4522
Object	<code>item_path</code>	<code>item_path</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`  
 Method `static void revert_cache_file(char *item_path)`

```
....
4509. static void revert_cache_file(char *item_path)
....
4522.      strcpy(szPATH, item_path);
```

### Buffer Overflow StrcpyStrcat\Path 14:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=14">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=14</a>
Status	New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4523
Object	mpd_src	szPATH

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
 Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
 Method static void revert\_cache\_file(char \*item\_path)

```
....
4523.      strcat(szPATH, ".txt");
```

### Buffer Overflow StrcpyStrcat\Path 15:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=15">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=15</a>
Status	New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4523
Object	output_dir	szPATH

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
```

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4523.      strcat(szPATH, ".txt");
```

#### Buffer Overflow StrcpyStrcat\Path 16:

Severity High  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=16>  
Status New

The size of the buffer used by revert\_cache\_file in szPATH, at line 4509 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that revert\_cache\_file passes to item\_path, at line 4509 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4509	4523
Object	item_path	szPATH

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4509.  static void revert_cache_file(char *item_path)
....
4523.      strcat(szPATH, ".txt");
```

#### Buffer Overflow StrcpyStrcat\Path 17:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=17">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=17</a>
Status	New

The size of the buffer used by rip\_mpd in sess, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4606
Object	mpd_src	sess

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)  
....  
4606.          strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

#### Buffer Overflow StrcpyStrcat\Path 18:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=18">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=18</a>
Status	New

The size of the buffer used by rip\_mpd in gf\_dm\_sess\_get\_cache\_name, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to mpd\_src, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4606
Object	mpd_src	gf_dm_sess_get_cache_name

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)



```
....  
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)  
....  
4606.      strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

### Buffer Overflow StrcpyStrcat\Path 19:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=19">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=19</a>
Status	New

The size of the buffer used by rip\_mpd in output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4581
Object	output_dir	output_dir

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4566.  GF_Err rip_mpd(const char *mpd_src, const char *output_dir)  
....  
4581.      strcpy(szName, output_dir);
```

### Buffer Overflow StrcpyStrcat\Path 20:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=20">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=20</a>
Status	New

The size of the buffer used by rip\_mpd in szName, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that rip\_mpd passes to output\_dir, at line 4566 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4566	4606
Object	output_dir	szName

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4566. GF_Err rip_mpd(const char *mpd_src, const char *output_dir)
....
4606.          strcpy(szName, gf_dm_sess_get_cache_name(sess) );
```

#### Buffer Overflow StrcpyStrcat\Path 21:

Severity High  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=21>  
Status New

The size of the buffer used by xmt\_parse\_url in vals, at line 824 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that xmt\_parse\_string passes to name, at line 757 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	757	844
Object	name	vals

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
757. static u32 xmt_parse_string(GF_XMTParser *parser, const char
    *name, SFString *val, Bool is_mf, char *a_value)
```



File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_url(GF\_XMTParser \*parser, const char \*name, MFURL \*val, GF\_Node \*owner, Bool is\_mf, char \*a\_value)

```
....
844.          strcpy(value, val->vals[idx].url);
```

#### Buffer Overflow StrcpyStrcat\Path 22:

Severity High  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22>

Status [&pathid=22](#)  
New

The size of the buffer used by `xmt_parse_url` in `vals`, at line 824 of `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `xmt_parse_url` passes to `name`, at line 824 of `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	824	844
Object	name	vals

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`  
Method `static u32 xmt_parse_url(GF_XMTParser *parser, const char *name, MFURL *val, GF_Node *owner, Bool is_mf, char *a_value)`

```
....  
824. static u32 xmt_parse_url(GF_XMTParser *parser, const char *name,  
MFURL *val, GF_Node *owner, Bool is_mf, char *a_value)  
....  
844. strcpy(value, val->vals[idx].url);
```

### Buffer Overflow StrcpyStrcat\Path 23:

Severity High  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=23>  
Status New

The size of the buffer used by `xmt_strip_name` in `in`, at line 1256 of `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `xmt_strip_name` passes to `in`, at line 1256 of `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	1256	1259
Object	in	in

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c`  
Method `static void xmt_strip_name(const char *in, char *out)`

```
....
1256. static void xmt_strip_name(const char *in, char *out)
....
1259. strcpy(out, in);
```

### Buffer Overflow StrcpyStrcat\Path 24:

Severity	High
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=24">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=24</a>
Status	New

The size of the buffer used by xmt\_strip\_name in out, at line 1256 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that xmt\_strip\_name passes to out, at line 1256 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	1256	1259
Object	out	out

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_strip\_name(const char \*in, char \*out)

```
....
1256. static void xmt_strip_name(const char *in, char *out)
....
1259. strcpy(out, in);
```

## Dangerous Functions

Query Path:

CPP\Cx\CPP Medium Threat\Dangerous Functions Version:1

### Categories

OWASP Top 10 2013: A9-Using Components with Known Vulnerabilities

OWASP Top 10 2017: A9-Using Components with Known Vulnerabilities

### Description

#### Dangerous Functions\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=226">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=226</a>
Status	New

The dangerous function, memcpy, was found in use at line 331 in gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c	gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c
Line	386	386
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c  
Method GF\_Err ac3dmx\_process(GF\_Filter \*filter)

```
....  
386.                memcpy(ctx->ac3_buffer + ctx->ac3_buffer_size, data,  
pck_size);
```

#### Dangerous Functions\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=227">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=227</a>
Status	New

The dangerous function, memcpy, was found in use at line 331 in gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c	gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c
Line	462	462
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.0.0-CVE-2024-0322-TP.c  
Method GF\_Err ac3dmx\_process(GF\_Filter \*filter)

```
....  
462.                memcpy(output, sync, ctx->hdr.framesize);
```

#### Dangerous Functions\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=228">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=228</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681.         memcpy(ptr->nameURN, tmpName, i + 1);
```

#### Dangerous Functions\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=229">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=229</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	694	694
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.         memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

#### Dangerous Functions\Path 5:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=230">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=230</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.                memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

#### Dangerous Functions\Path 6:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=231">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=231</a>
Status	New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8120.                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

#### Dangerous Functions\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=232">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=232</a>
Status	New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c

Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....  
9853. memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 8:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=233>

Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c

Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681. memcpy(ptr->nameURN, tmpName, i + 1);
```

#### Dangerous Functions\Path 9:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=234>

Status New



The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	694	694
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.             memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

#### Dangerous Functions\Path 10:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=235">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=235</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.             memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

#### Dangerous Functions\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22</a>

Status [&pathid=236](#)  
New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c

Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
.....  
8120. memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

#### Dangerous Functions\Path 12:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=237>

Status New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c

Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
.....  
9853. memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 13:

Severity Medium

Result State To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=238">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=238</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681.         memcpy(ptr->nameURN, tmpName, i + 1);
```

#### Dangerous Functions\Path 14:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=239">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=239</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	694	694
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.         memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

#### Dangerous Functions\Path 15:

Severity	Medium
Result State	To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=240">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=240</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.                memcpy(str, ptr->extended_language, (u32) ptr->size);
```

#### Dangerous Functions\Path 16:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=241">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=241</a>
Status	New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err udt\_a\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8120.                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

#### Dangerous Functions\Path 17:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=242">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=242</a>
Status	New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....  
9853. memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=243">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=243</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681. memcpy(ptr->nameURN, tmpName, i + 1);
```

**Dangerous Functions\Path 19:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=244">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=244</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	694	694
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.             memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

**Dangerous Functions\Path 20:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=245">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=245</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	3448	3448
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
.....
3448.                memcpy(str, ptr->extended_language, (u32) ptr-
>size);
```

### Dangerous Functions\Path 21:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=246">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=246</a>
Status	New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
.....
8120.                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

### Dangerous Functions\Path 22:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=247">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=247</a>
Status	New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....  
9853.                memcpy(ptr->key_info+4, kid, 16);
```

### Dangerous Functions\Path 23:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=248>  
Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	681	681
Object	memcpy	memcpy

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681.                memcpy(ptr->nameURN, tmpName, i + 1);
```

### Dangerous Functions\Path 24:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=249>  
Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	694	694
Object	memcpy	memcpy

### Code Snippet



File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.                memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

#### Dangerous Functions\Path 25:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=250>  
Status New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.                memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

#### Dangerous Functions\Path 26:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=251>  
Status New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	8120	8120
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c

Method GF\_Err udt\_a\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8120.                                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

**Dangerous Functions\Path 27:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=252>

Status New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	9853	9853
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c

Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....  
9853.                                memcpy(ptr->key_info+4, kid, 16);
```

**Dangerous Functions\Path 28:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=253>

Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	681	681
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681.          memcpy(ptr->nameURN, tmpName, i + 1);
```

**Dangerous Functions\Path 29:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=254>  
Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	694	694
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.          memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

**Dangerous Functions\Path 30:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=255>  
Status New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	3448	3448
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.                memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

**Dangerous Functions\Path 31:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=256>  
Status New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	8120	8120
Object	memcpy	memcpy

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8120.                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

**Dangerous Functions\Path 32:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=257>  
Status New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	9853	9853

Object	memcpy	memcpy
--------	--------	--------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
.....  
9853.                memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 33:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=258">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=258</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
.....  
681.                memcpy(ptr->nameURN, tmpName, i + 1);
```

#### Dangerous Functions\Path 34:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=259">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=259</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	694	694

Object	memcpy	memcpy
--------	--------	--------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.             memcpy(ptr->location, tmpName + i + 1, (to_read - i -  
1));
```

#### Dangerous Functions\Path 35:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=260">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=260</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.             memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

#### Dangerous Functions\Path 36:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=261">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=261</a>
Status	New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c

Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c

Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....
8120.                                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

#### Dangerous Functions\Path 37:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=262>

Status New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c

Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....
9853.                                memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 38:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=263>

Status New

The dangerous function, memcpy, was found in use at line 59 in gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c

Line	190	190
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c

Method static GF\_Err BD\_XReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
190.                                memcpy(&sffield, &targetField,  
sizeof(GF_FieldInfo));
```

#### Dangerous Functions\Path 39:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=264>

Status New

The dangerous function, memcpy, was found in use at line 295 in gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	335	335
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c

Method static GF\_Err BD\_DecMultipleIndexReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
335.                                memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Dangerous Functions\Path 40:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=265>

Status New

The dangerous function, memcpy, was found in use at line 591 in gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-	gpac@@gpac-v2.2.0-CVE-2022-43043-



	FP.c	FP.c
Line	630	630
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_DecIndexInsert(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
630.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Dangerous Functions\Path 41:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=266>  
Status New

The dangerous function, memcpy, was found in use at line 831 in gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	887	887
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_DecIndexValueReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
887.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Dangerous Functions\Path 42:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=267>  
Status New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	681	681
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
681.         memcpy(ptr->nameURN, tmpName, i + 1);
```

#### Dangerous Functions\Path 43:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=268">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=268</a>
Status	New

The dangerous function, memcpy, was found in use at line 645 in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	694	694
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err urn\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
694.         memcpy(ptr->location, tmpName + i + 1, (to_read - i - 1));
```

#### Dangerous Functions\Path 44:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=269">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=269</a>
Status	New

The dangerous function, memcpy, was found in use at line 3436 in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	3448	3448
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err elng\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3448.                memcpy(str, ptr->extended_language, (u32) ptr->  
>size);
```

#### Dangerous Functions\Path 45:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=270">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=270</a>
Status	New

The dangerous function, memcpy, was found in use at line 8091 in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	8120	8120
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8120.                memcpy(map->uuid, ((GF_UUIDBox *)a)->uuid, 16);
```

#### Dangerous Functions\Path 46:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=271">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=271</a>
Status	New

The dangerous function, memcpy, was found in use at line 9712 in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	9853	9853
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method static void \*sgpd\_parse\_entry(u32 grouping\_type, GF\_BitStream \*bs, s32 bytes\_in\_box, u32 entry\_size, u32 \*total\_bytes)

```
....  
9853. memcpy(ptr->key_info+4, kid, 16);
```

#### Dangerous Functions\Path 47:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=272">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=272</a>
Status	New

The dangerous function, memcpy, was found in use at line 266 in gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c
Line	322	322
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c  
Method static void mhas\_dmx\_check\_pid(GF\_Filter \*filter, GF\_MHASDmxCtx \*ctx, u32 PL, u32 sample\_rate, u32 frame\_len, s32 CICPspeakerLayoutIdx, s32 numSpeakers, u8 \*dsi, u32 dsi\_size)

```
....  
322. memcpy(data+5, dsi, dsi_size);
```

#### Dangerous Functions\Path 48:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=273">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=273</a>
Status	New

The dangerous function, memcpy, was found in use at line 452 in gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c
Line	513	513
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c  
Method GF\_Err mhas\_dmx\_process(GF\_Filter \*filter)

```
....  
513.                memcpy(ctx->mhas_buffer + ctx->mhas_buffer_size, data,  
pck_size);
```

#### Dangerous Functions\Path 49:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=274">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=274</a>
Status	New

The dangerous function, memcpy, was found in use at line 452 in gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c
Line	725	725
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0817-TP.c  
Method GF\_Err mhas\_dmx\_process(GF\_Filter \*filter)

```
....  
725.                memcpy(output, start + au_start, au_size);
```

#### Dangerous Functions\Path 50:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=275">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=275</a>
Status	New

The dangerous function, memcpy, was found in use at line 553 in gpac@@gpac-v2.2.0-CVE-2023-0866-TP.c file. Such functions may expose information and allow an attacker to get full control over the host machine.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0866-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0866-TP.c
Line	608	608
Object	memcpy	memcpy

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0866-TP.c  
Method GF\_Err adts\_dmx\_process(GF\_Filter \*filter)

```
....
608.                memcpy(ctx->adts_buffer + ctx->adts_buffer_size, data,
pck_size);
```

## Buffer Overflow boundcpy WrongSizeParam

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow boundcpy WrongSizeParam Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows  
OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow boundcpy WrongSizeParam\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=43">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=43</a>
Status	New

The size of the buffer used by BD\_XReplace in GF\_FieldInfo, at line 59 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_XReplace passes to GF\_FieldInfo, at line 59 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	190	190
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_XReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....
190.                memcpy(&sffield, &targetField,
sizeof(GF_FieldInfo));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 2:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=44">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=44</a>
Status	New

The size of the buffer used by BD\_DecMultipleIndexReplace in GF\_FieldInfo, at line 295 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecMultipleIndexReplace passes to GF\_FieldInfo, at line 295 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	335	335
Object	GF_FieldInfo	GF_FieldInfo

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_DecMultipleIndexReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
335.      memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 3:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=45">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=45</a>
Status	New

The size of the buffer used by BD\_DecIndexInsert in GF\_FieldInfo, at line 591 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecIndexInsert passes to GF\_FieldInfo, at line 591 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	630	630
Object	GF_FieldInfo	GF_FieldInfo

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_DecIndexInsert(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
630.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=46">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=46</a>
Status	New

The size of the buffer used by BD\_DecIndexValueReplace in GF\_FieldInfo, at line 831 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecIndexValueReplace passes to GF\_FieldInfo, at line 831 of gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	887	887
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c  
Method static GF\_Err BD\_DecIndexValueReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
887.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 5:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=47">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=47</a>
Status	New

The size of the buffer used by vcrop\_process in ->, at line 94 of gpac@@gpac-v2.2.0-CVE-2023-37766-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that vcrop\_process passes to ->, at line 94 of gpac@@gpac-v2.2.0-CVE-2023-37766-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37766-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37766-TP.c
Line	189	189
Object	->	->

#### Code Snippet



File Name gpac@@gpac-v2.2.0-CVE-2023-37766-TP.c  
Method static GF\_Err vcrop\_process(GF\_Filter \*filter)

```
....  
189.                memcpy(vframe->stride, ctx->src_stride, sizeof(vframe->  
>stride));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 6:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=48>  
Status New

The size of the buffer used by BD\_XReplace in GF\_FieldInfo, at line 59 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_XReplace passes to GF\_FieldInfo, at line 59 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	190	190
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c  
Method static GF\_Err BD\_XReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
190.                memcpy(&sfffield, &targetField,  
sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 7:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=49>  
Status New

The size of the buffer used by BD\_DecMultipleIndexReplace in GF\_FieldInfo, at line 295 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecMultipleIndexReplace passes to GF\_FieldInfo, at line 295 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	335	335

Object	GF_FieldInfo	GF_FieldInfo
--------	--------------	--------------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c  
Method static GF\_Err BD\_DecMultipleIndexReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
335.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 8:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=50">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=50</a>
Status	New

The size of the buffer used by BD\_DecIndexInsert in GF\_FieldInfo, at line 591 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecIndexInsert passes to GF\_FieldInfo, at line 591 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	630	630
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c  
Method static GF\_Err BD\_DecIndexInsert(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
630.         memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 9:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=51">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=51</a>
Status	New

The size of the buffer used by BD\_DecIndexValueReplace in GF\_FieldInfo, at line 831 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BD\_DecIndexValueReplace passes to GF\_FieldInfo, at line 831 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-	gpac@@gpac-v2.2.0-CVE-2023-37767-

	TP.c	TP.c
Line	887	887
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c  
Method static GF\_Err BD\_DecIndexValueReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
887.                memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 10:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=52>  
Status New

The size of the buffer used by BM\_ParseIndexInsert in GF\_FieldInfo, at line 452 of gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that BM\_ParseIndexInsert passes to GF\_FieldInfo, at line 452 of gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c
Line	493	493
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c  
Method GF\_Err BM\_ParseIndexInsert(GF\_BifsDecoder \*codec, GF\_BitStream \*bs, GF\_List \*com\_list)

```
....  
493.                memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 11:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=53>  
Status New

The size of the buffer used by BM\_ParseIndexValueReplace in GF\_FieldInfo, at line 740 of gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c, is not properly verified before writing data to the buffer. This can enable a

buffer overflow attack, using the source buffer that BM\_ParseIndexValueReplace passes to GF\_FieldInfo, at line 740 of gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c
Line	791	791
Object	GF_FieldInfo	GF_FieldInfo

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c  
Method GF\_Err BM\_ParseIndexValueReplace(GF\_BifsDecoder \*codec, GF\_BitStream \*bs, GF\_List \*com\_list)

```
....  
791.                memcpy(&sffield, &field, sizeof(GF_FieldInfo));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=54">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=54</a>
Status	New

The size of the buffer used by tfra\_box\_read in GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that tfra\_box\_read passes to GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	3298	3298
Object	GF_RandomAccessEntry	GF_RandomAccessEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err tfra\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3298.                memset(p, 0, sizeof(GF_RandomAccessEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 13:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=55">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=55</a>
Status	New

The size of the buffer used by `trun_box_read` in `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `trun_box_read` passes to `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	7595	7595
Object	GF_TrunEntry	GF_TrunEntry

#### Code Snippet

File Name      `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`  
Method         `GF_Err trun_box_read(GF_Box *s, GF_BitStream *bs)`

```
....  
7595.                    memset(ptr->samples, 0, sizeof(GF_TrunEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 14:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=56">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=56</a>
Status	New

The size of the buffer used by `udta_on_child_box` in `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `udta_on_child_box` passes to `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	8116	8116
Object	GF_UserDataMap	GF_UserDataMap

#### Code Snippet

File Name      `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`  
Method         `GF_Err udta_on_child_box(GF_Box *s, GF_Box *a, Bool is_rem)`

```
....  
8116.                    memset(map, 0, sizeof(GF_UserDataMap));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 15:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=57">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=57</a>
Status	New

The size of the buffer used by `subs_box_read` in `GF_SubSampleInfoEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `subs_box_read` passes to `GF_SubSampleInfoEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	9489	9489
Object	GF_SubSampleInfoEntry	GF_SubSampleInfoEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9489.             memset(pSamp, 0, sizeof(GF_SubSampleInfoEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 16:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=58>  
Status New

The size of the buffer used by `subs_box_read` in `GF_SubSampleEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `subs_box_read` passes to `GF_SubSampleEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	9499	9499
Object	GF_SubSampleEntry	GF_SubSampleEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9499.             memset(pSubSamp, 0, sizeof(GF_SubSampleEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 17:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=59>

Status New

The size of the buffer used by \*dvcC\_box\_new in GF\_DOVIConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvcC\_box\_new passes to GF\_DOVIConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	11926	11926
Object	GF_DOVIConfigurationBox	GF_DOVIConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Box \*dvcC\_box\_new()

```
....
11926.      memset(tmp, 0, sizeof(GF_DOVIConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=60">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=60</a>
Status	New

The size of the buffer used by \*dvvC\_box\_new in GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvvC\_box\_new passes to GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	12015	12015
Object	GF_DOVIConfigurationBox	GF_DOVIConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Box \*dvvC\_box\_new()

```
....
12015.      memset(tmp, 0, sizeof(GF_DOVIConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 19:

Severity	Medium
Result State	To Verify



Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=61">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=61</a>
Status	New

The size of the buffer used by `dump_mpeg2_ts` in `GF_M2TS_Dump`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `dump_mpeg2_ts` passes to `GF_M2TS_Dump`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>
Line	4395	4395
Object	<code>GF_M2TS_Dump</code>	<code>GF_M2TS_Dump</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`  
Method `void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)`

```
....  
4395.          memset(&dumper, 0, sizeof(GF_M2TS_Dump));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=62">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=62</a>
Status	New

The size of the buffer used by `tfra_box_read` in `GF_RandomAccessEntry`, at line 3256 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `tfra_box_read` passes to `GF_RandomAccessEntry`, at line 3256 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>
Line	3298	3298
Object	<code>GF_RandomAccessEntry</code>	<code>GF_RandomAccessEntry</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`  
Method `GF_Err tfra_box_read(GF_Box *s, GF_BitStream *bs)`

```
....  
3298.          memset(p, 0, sizeof(GF_RandomAccessEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 21:

Severity	Medium
----------	--------



Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=63">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=63</a>
Status	New

The size of the buffer used by `trun_box_read` in `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `trun_box_read` passes to `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>
Line	7595	7595
Object	<code>GF_TrunEntry</code>	<code>GF_TrunEntry</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`  
Method `GF_Err trun_box_read(GF_Box *s, GF_BitStream *bs)`

```
....  
7595.             memset(ptr->samples, 0, sizeof(GF_TrunEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 22:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=64">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=64</a>
Status	New

The size of the buffer used by `udta_on_child_box` in `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `udta_on_child_box` passes to `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c</code>
Line	8116	8116
Object	<code>GF_UserDataMap</code>	<code>GF_UserDataMap</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c`  
Method `GF_Err udta_on_child_box(GF_Box *s, GF_Box *a, Bool is_rem)`

```
....  
8116.             memset(map, 0, sizeof(GF_UserDataMap));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 23:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=65">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=65</a>
Status	New

The size of the buffer used by subs\_box\_read in GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	9489	9489
Object	GF_SubSampleInfoEntry	GF_SubSampleInfoEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9489.                memset(pSamp, 0, sizeof(GF_SubSampleInfoEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 24:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=66">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=66</a>
Status	New

The size of the buffer used by subs\_box\_read in GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	9499	9499
Object	GF_SubSampleEntry	GF_SubSampleEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9499.                memset(pSubSamp, 0, sizeof(GF_SubSampleEntry));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 25:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=67">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=67</a>
Status	New

The size of the buffer used by \*dvcC\_box\_new in GF\_DOVConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvcC\_box\_new passes to GF\_DOVConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	11926	11926
Object	GF_DOVConfigurationBox	GF_DOVConfigurationBox

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Box \*dvcC\_box\_new()

```
....  
11926.      memset(tmp, 0, sizeof(GF_DOVConfigurationBox));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 26:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=68">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=68</a>
Status	New

The size of the buffer used by \*dvvC\_box\_new in GF\_DOVConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvvC\_box\_new passes to GF\_DOVConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	12015	12015
Object	GF_DOVConfigurationBox	GF_DOVConfigurationBox

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Box \*dvvC\_box\_new()

```
.....
12015.      memset(tmp, 0, sizeof(GF_DOVIconfigurationBox));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 27:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=69">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=69</a>
Status	New

The size of the buffer used by tfra\_box\_read in GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that tfra\_box\_read passes to GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	3298	3298
Object	GF_RandomAccessEntry	GF_RandomAccessEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err tfra\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
.....
3298.      memset(p, 0, sizeof(GF_RandomAccessEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 28:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=70">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=70</a>
Status	New

The size of the buffer used by trun\_box\_read in GF\_TruncEntry, at line 7562 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that trun\_box\_read passes to GF\_TruncEntry, at line 7562 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	7595	7595
Object	GF_TruncEntry	GF_TruncEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

Method GF\_Err trun\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
7595.                memset(ptr->samples, 0, sizeof(GF_TruncEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 29:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=71">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=71</a>
Status	New

The size of the buffer used by udata\_on\_child\_box in GF\_UserDataMap, at line 8091 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that udata\_on\_child\_box passes to GF\_UserDataMap, at line 8091 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	8116	8116
Object	GF_UserDataMap	GF_UserDataMap

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err udata\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....
8116.                memset(map, 0, sizeof(GF_UserDataMap));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 30:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=72">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=72</a>
Status	New

The size of the buffer used by subs\_box\_read in GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	9489	9489
Object	GF_SubSampleInfoEntry	GF_SubSampleInfoEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9489.                memset(pSamp, 0, sizeof(GF_SubSampleInfoEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 31:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=73>  
Status New

The size of the buffer used by subs\_box\_read in GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	9499	9499
Object	GF_SubSampleEntry	GF_SubSampleEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9499.                memset(pSubSamp, 0, sizeof(GF_SubSampleEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 32:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=74>  
Status New

The size of the buffer used by \*dvcC\_box\_new in GF\_DOVICONfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvcC\_box\_new passes to GF\_DOVICONfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	11926	11926
Object	GF_DOVICONfigurationBox	GF_DOVICONfigurationBox

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Box \*dvc\_box\_new()

```
....  
11926.      memset(tmp, 0, sizeof(GF_DOVICONfigurationBox));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 33:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=75>  
Status New

The size of the buffer used by \*dvc\_box\_new in GF\_DOVICONfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvc\_box\_new passes to GF\_DOVICONfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	12015	12015
Object	GF_DOVICONfigurationBox	GF_DOVICONfigurationBox

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method GF\_Box \*dvc\_box\_new()

```
....  
12015.      memset(tmp, 0, sizeof(GF_DOVICONfigurationBox));
```

**Buffer Overflow boundcpy WrongSizeParam\Path 34:**

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=76>  
Status New

The size of the buffer used by dump\_mpeg2\_ts in GF\_M2TS\_Dump, at line 4373 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that dump\_mpeg2\_ts passes to GF\_M2TS\_Dump, at line 4373 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c



Line	4395	4395
Object	GF_M2TS_Dump	GF_M2TS_Dump

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....
4395.          memset(&dumper, 0, sizeof(GF_M2TS_Dump));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 35:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=77>

Status New

The size of the buffer used by tfra\_box\_read in GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that tfra\_box\_read passes to GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	3298	3298
Object	GF_RandomAccessEntry	GF_RandomAccessEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c

Method GF\_Err tfra\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
3298.          memset(p, 0, sizeof(GF_RandomAccessEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 36:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=78>

Status New

The size of the buffer used by trun\_box\_read in GF\_TruncEntry, at line 7562 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that trun\_box\_read passes to GF\_TruncEntry, at line 7562 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-	gpac@@gpac-v2.2.0-CVE-2021-32268-



	FP.c	FP.c
Line	7595	7595
Object	GF_TrunEntry	GF_TrunEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err trun\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
7595.                memset(ptr->samples, 0, sizeof(GF_TrunEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 37:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=79">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=79</a>
Status	New

The size of the buffer used by udata\_on\_child\_box in GF\_UserDataMap, at line 8091 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that udata\_on\_child\_box passes to GF\_UserDataMap, at line 8091 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	8116	8116
Object	GF_UserDataMap	GF_UserDataMap

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err udata\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....
8116.                memset(map, 0, sizeof(GF_UserDataMap));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 38:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=80">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=80</a>
Status	New

The size of the buffer used by subs\_box\_read in GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleInfoEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	9489	9489
Object	GF_SubSampleInfoEntry	GF_SubSampleInfoEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
9489.                memset(pSamp, 0, sizeof(GF_SubSampleInfoEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 39:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=81">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=81</a>
Status	New

The size of the buffer used by subs\_box\_read in GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	9499	9499
Object	GF_SubSampleEntry	GF_SubSampleEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
9499.                memset(pSubSamp, 0, sizeof(GF_SubSampleEntry));
```

### Buffer Overflow boundcpy WrongSizeParam\Path 40:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=82">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=82</a>
Status	New

The size of the buffer used by \*dvc\_box\_new in GF\_DOVConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvc\_box\_new passes to

GF\_DOVIConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	11926	11926
Object	GF_DOVIConfigurationBox	GF_DOVIConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Box \*dvcC\_box\_new()

```
....  
11926.      memset(tmp, 0, sizeof(GF_DOVIConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=83">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=83</a>
Status	New

The size of the buffer used by \*dvvC\_box\_new in GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvvC\_box\_new passes to GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	12015	12015
Object	GF_DOVIConfigurationBox	GF_DOVIConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Box \*dvvC\_box\_new()

```
....  
12015.      memset(tmp, 0, sizeof(GF_DOVIConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 42:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=84">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=84</a>
Status	New

The size of the buffer used by `tfra_box_read` in `GF_RandomAccessEntry`, at line 3256 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `tfra_box_read` passes to `GF_RandomAccessEntry`, at line 3256 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	3298	3298
Object	GF_RandomAccessEntry	GF_RandomAccessEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err tfra\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
3298.             memset(p, 0, sizeof(GF_RandomAccessEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 43:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=85">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=85</a>
Status	New

The size of the buffer used by `trun_box_read` in `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `trun_box_read` passes to `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	7595	7595
Object	GF_TrunEntry	GF_TrunEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err trun\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
7595.             memset(ptr->samples, 0, sizeof(GF_TrunEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 44:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=86">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=86</a>
Status	New

The size of the buffer used by `udta_on_child_box` in `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `udta_on_child_box` passes to `GF_UserDataMap`, at line 8091 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	8116	8116
Object	GF_UserDataMap	GF_UserDataMap

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c

Method GF\_Err udta\_on\_child\_box(GF\_Box \*s, GF\_Box \*a, Bool is\_rem)

```
....  
8116.          memset(map, 0, sizeof(GF_UserDataMap));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 45:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=87>

Status New

The size of the buffer used by `subs_box_read` in `GF_SubSampleInfoEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `subs_box_read` passes to `GF_SubSampleInfoEntry`, at line 9475 of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	9489	9489
Object	GF_SubSampleInfoEntry	GF_SubSampleInfoEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c

Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
9489.          memset(pSamp, 0, sizeof(GF_SubSampleInfoEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 46:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=88>

Status New

The size of the buffer used by subs\_box\_read in GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that subs\_box\_read passes to GF\_SubSampleEntry, at line 9475 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	9499	9499
Object	GF_SubSampleEntry	GF_SubSampleEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err subs\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
9499.                memset(pSubSamp, 0, sizeof(GF_SubSampleEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 47:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=89>  
Status New

The size of the buffer used by \*dvcC\_box\_new in GF\_DOVConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvcC\_box\_new passes to GF\_DOVConfigurationBox, at line 11922 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	11926	11926
Object	GF_DOVConfigurationBox	GF_DOVConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Box \*dvcC\_box\_new()

```
....
11926.                memset(tmp, 0, sizeof(GF_DOVConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 48:

Severity Medium  
Result State To Verify  
Online Results <http://WIN->

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=90">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=90</a>
Status	New

The size of the buffer used by \*dvvC\_box\_new in GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that \*dvvC\_box\_new passes to GF\_DOVIConfigurationBox, at line 12011 of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	12015	12015
Object	GF_DOVIConfigurationBox	GF_DOVIConfigurationBox

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Box \*dvvC\_box\_new()

```
....
12015.      memset(tmp, 0, sizeof(GF_DOVIConfigurationBox));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 49:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=91">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=91</a>
Status	New

The size of the buffer used by tfra\_box\_read in GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that tfra\_box\_read passes to GF\_RandomAccessEntry, at line 3256 of gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	3298	3298
Object	GF_RandomAccessEntry	GF_RandomAccessEntry

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err tfra\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
3298.      memset(p, 0, sizeof(GF_RandomAccessEntry));
```

#### Buffer Overflow boundcpy WrongSizeParam\Path 50:

Severity	Medium
----------	--------



Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=92">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=92</a>
Status	New

The size of the buffer used by `trun_box_read` in `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `trun_box_read` passes to `GF_TrunEntry`, at line 7562 of `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c</code>
Line	7595	7595
Object	<code>GF_TrunEntry</code>	<code>GF_TrunEntry</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`  
 Method `GF_Err trun_box_read(GF_Box *s, GF_BitStream *bs)`

```
....
7595.             memset(ptr->samples, 0, sizeof(GF_TrunEntry));
```

## Use of Zero Initialized Pointer

Query Path:

CPP\Cx\CPP Medium Threat\Use of Zero Initialized Pointer Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

### Description

#### Use of Zero Initialized Pointer\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1034">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1034</a>
Status	New

The variable declared in `a` at `gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c` in line 104 is not initialized when it is used by `a` at `gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c` in line 104.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c</code>
Line	108	128
Object	<code>a</code>	<code>a</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c`



Method GF\_Err ilst\_item\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....
108.         GF_Box *a = NULL;
....
128.         ISOM_DECREASE_SIZE(ptr, a->size);
```

### Use of Zero Initialized Pointer\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1035">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1035</a>
Status	New

The variable declared in key\_info at gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c in line 1284 is not initialized when it is used by civ at gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c in line 1245.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c	gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c
Line	1347	1264
Object	key_info	civ

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c  
Method GF\_Err senc\_Parse(GF\_BitStream \*bs, GF\_TrackBox \*trak, GF\_TrackFragmentBox \*traf, GF\_SampleEncryptionBox \*senc)

```
....
1347.         const u8 *key_info=NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c  
Method u8 key\_info\_get\_iv\_size(const u8 \*key\_info, u32 key\_info\_size, u32 idx, u8 \*const\_iv\_size, const u8 \*\*const\_iv)

```
....
1264.         civ = key_info + kpos + 1;
```

### Use of Zero Initialized Pointer\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1036">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1036</a>
Status	New

The variable declared in sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1539 is not initialized when it is used by sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c	gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c
Line	1551	1556
Object	sub_samples	sub_samples

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c  
Method u32 gf\_isom\_sample\_get\_subsample\_entry(GF\_ISOFile \*movie, u32 track, u32 sampleNumber, u32 flags, GF\_SubSampleInfoEntry \*\*sub\_sample)

```
....  
1551.             sub_samples = NULL;  
....  
1556.             count = gf_list_count(sub_samples->Samples);
```

#### Use of Zero Initialized Pointer\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1037">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1037</a>
Status	New

The variable declared in sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1539 is not initialized when it is used by sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c	gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c
Line	1542	1556
Object	sub_samples	sub_samples

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c  
Method u32 gf\_isom\_sample\_get\_subsample\_entry(GF\_ISOFile \*movie, u32 track, u32 sampleNumber, u32 flags, GF\_SubSampleInfoEntry \*\*sub\_sample)

```
....  
1542.             GF_SubSampleInformationBox *sub_samples=NULL;  
....  
1556.             count = gf_list_count(sub_samples->Samples);
```

#### Use of Zero Initialized Pointer\Path 5:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1038">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1038</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	920
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....  
656.          SVG_Element *elt = NULL;  
....  
920.          SVG_handlerElement *handler =  
gf_dom_listener_build((GF_Node *)elt, evtType, 0);
```

#### Use of Zero Initialized Pointer\Path 6:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1039">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1039</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	822
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....  
656.          SVG_Element *elt = NULL;  
....  
822.          gf_svg_parse_style((GF_Node *)elt, att->value);
```

### Use of Zero Initialized Pointer\Path 7:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1040">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1040</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 590.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	610
Object	elt	command

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static void svg\_init\_root\_element(GF\_SVG\_Parser \*parser, SVG\_Element \*root\_svg)

```
....
610.          parser->command->node = (GF_Node *)root_svg;
```

### Use of Zero Initialized Pointer\Path 8:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1041">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1041</a>
Status	New

The variable declared in par at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 590.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1055	610

Object	par	command
--------	-----	---------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
1055.          SVG_Element *par = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static void svg\_init\_root\_element(GF\_SVG\_Parser \*parser, SVG\_Element \*root\_svg)

```
....
610.          parser->command->node = (GF_Node *)root_svg;
```

#### Use of Zero Initialized Pointer\Path 9:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1042">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1042</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1039
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
1039.          gf_node_init((GF_Node *)elt);
```

#### Use of Zero Initialized Pointer\Path 10:

Severity	Medium
Result State	To Verify

Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1043">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1043</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1015
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
1015.         gf_svg_parse_element_id((GF_Node *)elt,
node_name, parser->command_depth ? GF_TRUE : GF_FALSE);
```

#### Use of Zero Initialized Pointer\Path 11:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1044">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1044</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	994
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
994.          gf_svg_parse_attribute((GF_Node *)elt, &info,
(char*)ev_observer, 0);
```

### Use of Zero Initialized Pointer\Path 12:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1045">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1045</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1082
Object	elt	far_ptr

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
1082.          XMLEV_Event *ev = (XMLEV_Event *)info.far_ptr;
```

### Use of Zero Initialized Pointer\Path 13:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1046">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1046</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1075

Object	elt	far_ptr
--------	-----	---------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```

.....
656.          SVG_Element *elt = NULL;
.....
1075.          XMLRI *handler = (XMLRI *)info.far_ptr;

```

#### Use of Zero Initialized Pointer\Path 14:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1047">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1047</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1067
Object	elt	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```

.....
656.          SVG_Element *elt = NULL;
.....
1067.          XMLRI *target = (XMLRI *)info.far_ptr;

```

#### Use of Zero Initialized Pointer\Path 15:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1048">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1048</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.



	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1059
Object	elt	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
1059.          XMLRI *observer = (XMLRI *)info.far_ptr;
```

#### Use of Zero Initialized Pointer\Path 16:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1049">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1049</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	1003
Object	elt	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
1003.          gf_node_dom_listener_add(((XMLRI
*)info.far_ptr)->target, (GF_Node *) listener);
```

#### Use of Zero Initialized Pointer\Path 17:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1049">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1049</a>

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1050">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1050</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	989
Object	elt	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
989.         ((XMLRI *)info.far_ptr)->target = node;
```

#### Use of Zero Initialized Pointer\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1051">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1051</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	973
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
973.         GF_Node *node = (GF_Node *)elt;
```

### Use of Zero Initialized Pointer\Path 19:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1052">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1052</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	751
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
751.         gf_node_register((GF_Node*)elt, NULL);
```

### Use of Zero Initialized Pointer\Path 20:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1053">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1053</a>
Status	New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by anim at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	750
Object	elt	anim

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
750.          anim->animation_elt = elt;
```

#### Use of Zero Initialized Pointer\Path 21:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1054>  
Status New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	769
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.          SVG_Element *elt = NULL;
....
769.          gf_node_register((GF_Node*)elt, NULL);
```

#### Use of Zero Initialized Pointer\Path 22:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1055>  
Status New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by anim at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	768
Object	elt	anim

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
768.         anim->animation_elt = elt;
```

#### Use of Zero Initialized Pointer\Path 23:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1056>  
Status New

The variable declared in elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by elt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	736
Object	elt	elt

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
....
736.         gf_node_register((GF_Node *)elt, (parent ? (GF_Node *)parent->node : NULL));
```

#### Use of Zero Initialized Pointer\Path 24:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1056>

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1057">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1057</a>
Status	New

The variable declared in par at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by par at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1055	1090
Object	par	par

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```

....
1055.             SVG_Element *par = NULL;
....
1090.             gf_node_dom_listener_add((GF_Node *)par,
(GF_Node *) listener);

```

#### Use of Zero Initialized Pointer\Path 25:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1058">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1058</a>
Status	New

The variable declared in atNode at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1102	1128
Object	atNode	command

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```

.....
1102.         char *atNode = NULL;
.....
1128.         parser->command->node = svg_find_node(parser, atNode);

```

### Use of Zero Initialized Pointer\Path 26:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1059">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1059</a>
Status	New

The variable declared in atNode at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1102	1165
Object	atNode	command

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```

.....
1102.         char *atNode = NULL;
.....
1165.         parser->command->node = svg_find_node(parser, atNode);

```

### Use of Zero Initialized Pointer\Path 27:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1060">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1060</a>
Status	New

The variable declared in atNode at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1102	1250
Object	atNode	command

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
1102.         char *atNode = NULL;
....
1250.         parser->command->node = svg_find_node(parser, atNode);
```

**Use of Zero Initialized Pointer\Path 28:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1061>

Status New

The variable declared in atNode at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1102	1272
Object	atNode	command

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
1102.         char *atNode = NULL;
....
1272.         parser->command->node = svg_find_node(parser, atNode);
```

**Use of Zero Initialized Pointer\Path 29:**

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1062>

Status New

The variable declared in atOperandAtt at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c



Line	1105	1237
Object	atOperandAtt	command

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
1105.      char *atOperandAtt = NULL;
....
1237.                  parser->command->fromFieldIndex =
gf_xml_get_attribute_tag(opNode, atOperandAtt, parser->current_ns);
```

#### Use of Zero Initialized Pointer\Path 30:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1063>

Status New

The variable declared in atEvent at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097 is not initialized when it is used by command at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1097.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1109	1276
Object	atEvent	command

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static GF\_Err lsr\_parse\_command(GF\_SVG\_Parser \*parser, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
1109.      char *atEvent = NULL;
....
1276.                  parser->command->send_event_name =
gf_dom_event_type_by_name(atEvent);
```

#### Use of Zero Initialized Pointer\Path 31:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1064>

Status New

The variable declared in sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1539 is not initialized when it is used by sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c
Line	1551	1556
Object	sub_samples	sub_samples

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c

Method u32 gf\_isom\_sample\_get\_subsample\_entry(GF\_ISOFile \*movie, u32 track, u32 sampleNumber, u32 flags, GF\_SubSampleInfoEntry \*\*sub\_sample)

```
....
1551.             sub_samples = NULL;
....
1556.             count = gf_list_count(sub_samples->Samples);
```

#### Use of Zero Initialized Pointer\Path 32:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1065>

Status New

The variable declared in sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1539 is not initialized when it is used by sub\_samples at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c
Line	1542	1556
Object	sub_samples	sub_samples

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c

Method u32 gf\_isom\_sample\_get\_subsample\_entry(GF\_ISOFile \*movie, u32 track, u32 sampleNumber, u32 flags, GF\_SubSampleInfoEntry \*\*sub\_sample)

```
....
1542.             GF_SubSampleInformationBox *sub_samples=NULL;
....
1556.             count = gf_list_count(sub_samples->Samples);
```

#### Use of Zero Initialized Pointer\Path 33:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1065>

[PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1066](http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1066)

Status New

The variable declared in node at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	1659	1868
Object	node	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static GF\_Node \*xmt\_parse\_element(GF\_XMTParser \*parser, char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, XMTPNodeStack \*parent)

```
....  
1659.             node = NULL;  
....  
1868.             * ((GF_Node **)container.far_ptr) = node;
```

#### Use of Zero Initialized Pointer\Path 34:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1067>  
Status New

The variable declared in proto at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437 is not initialized when it is used by far\_ptr at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	1447	1868
Object	proto	far_ptr

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static GF\_Node \*xmt\_parse\_element(GF\_XMTParser \*parser, char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, XMTPNodeStack \*parent)

```

.....
1447.          GF_Proto *proto = NULL;
.....
1868.          * ((GF_Node **)container.far_ptr) = node;

```

### Use of Zero Initialized Pointer\Path 35:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1068">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1068</a>
Status	New

The variable declared in fieldName at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437 is not initialized when it is used by proto\_field at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 1437.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	1487	1501
Object	fieldName	proto_field

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static GF\_Node \*xmt\_parse\_element(GF\_XMTParser \*parser, char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, XMTPNodeStack \*parent)

```

.....
1487.          char *fieldName = NULL;
.....
1501.          parser->proto_field =
gf_sg_proto_field_new(parser->parsing_proto, fType, eType, fieldName);

```

### Use of Zero Initialized Pointer\Path 36:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1069">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1069</a>
Status	New

The variable declared in fieldValue at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 2024 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2154	772

Object	fieldValue	buffer
--------	------------	--------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
2154.          char *fieldValue = NULL;
```



File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
772.          if (len) val->buffer = gf_strdup(str);
```

#### Use of Zero Initialized Pointer\Path 37:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1070>

Status New

The variable declared in fieldValue at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 2073 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 772.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2073	772
Object	fieldValue	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
2073.          char *fieldValue = NULL;
```



File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
772.                if (len) val->buffer = gf_strdup(str);
```

### Use of Zero Initialized Pointer\Path 38:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1071">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1071</a>
Status	New

The variable declared in fieldValue at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 2074 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2073	793
Object	fieldValue	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
2073.                char *fieldValue = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
793.                if (len) val->buffer = gf_strdup(str);
```

### Use of Zero Initialized Pointer\Path 39:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1072">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1072</a>
Status	New

The variable declared in fieldValue at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 2074 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2154	793
Object	fieldValue	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
2154.          char *fieldValue = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
793.          if (len) val->buffer = gf_strdup(str);
```

#### Use of Zero Initialized Pointer\Path 40:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1073">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1073</a>
Status	New

The variable declared in buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 859 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 859.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	865	870
Object	buffer	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_script(GF\_XMTParser \*parser, const char \*name, SFScript \*val, Bool is\_mf, char \*a\_value)

```
....
865.          sfstr.buffer = NULL;
....
870.          val->script_text = (char*)sfstr.buffer;
```

### Use of Zero Initialized Pointer\Path 41:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1074">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1074</a>
Status	New

The variable declared in buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 859.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	818	870
Object	buffer	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
 Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....
818.          val->buffer = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
 Method static u32 xmt\_parse\_script(GF\_XMTParser \*parser, const char \*name, SFScript \*val, Bool is\_mf, char \*a\_value)

```
....
870.          val->script_text = (char*)sfstr.buffer;
```

### Use of Zero Initialized Pointer\Path 42:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1075">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1075</a>
Status	New

The variable declared in buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 859.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	792	870
Object	buffer	buffer



#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....  
792.                val->buffer = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_script(GF\_XMTParser \*parser, const char \*name, SFScript \*val, Bool is\_mf, char \*a\_value)

```
....  
870.                val->script_text = (char*)sfstr.buffer;
```

#### Use of Zero Initialized Pointer\Path 43:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1076>  
Status New

The variable declared in buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 757 is not initialized when it is used by buffer at gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c in line 859.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	771	870
Object	buffer	buffer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....  
771.                val->buffer = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_script(GF\_XMTParser \*parser, const char \*name, SFScript \*val, Bool is\_mf, char \*a\_value)

```
....  
870.                val->script_text = (char*)sfstr.buffer;
```

**Use of Zero Initialized Pointer\Path 44:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1077">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1077</a>
Status	New

The variable declared in output at gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c in line 928 is not initialized when it is used by pck at gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c in line 928.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c	gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c
Line	932	944
Object	output	pck

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c  
Method static GF\_Err av1dmx\_parse\_flush\_sample(GF\_Filter \*filter, GF\_AV1DmxCtx \*ctx)

```
....  
932.      u8 *output = NULL;  
....  
944.      pck = gf_filter_pck_new_alloc(ctx->opid, pck_size, &output);
```

**Use of Zero Initialized Pointer\Path 45:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1078">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1078</a>
Status	New

The variable declared in vp\_cfg at gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c in line 153 is not initialized when it is used by pck at gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c in line 928.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c	gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c
Line	168	944
Object	vp_cfg	pck

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c  
Method GF\_Err av1dmx\_check\_format(GF\_Filter \*filter, GF\_AV1DmxCtx \*ctx, GF\_BitStream \*bs, u32 \*last\_obu\_end)

```
....
168.         ctx->vp_cfg = NULL;
```

File Name      gpac@@gpac-v2.2.0-CVE-2023-1449-TP.c  
Method          static GF\_Err av1dmx\_parse\_flush\_sample(GF\_Filter \*filter, GF\_AV1DmxCtx \*ctx)

```
....
944.         pck = gf_filter_pck_new_alloc(ctx->opid, pck_size, &output);
```

#### Use of Zero Initialized Pointer\Path 46:

Severity          Medium  
Result State      To Verify  
Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1079>  
Status            New

The variable declared in avc\_state at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 477 is not initialized when it is used by avc\_state at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 477.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	483	632
Object	avc_state	avc_state

#### Code Snippet

File Name      gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c  
Method          static void naludmx\_check\_dur(GF\_Filter \*filter, GF\_NALUDmxCtx \*ctx)

```
....
483.         AVCState *avc_state = NULL;
....
632.         nal_type = avc_state->last_nal_type_parsed;
```

#### Use of Zero Initialized Pointer\Path 47:

Severity          Medium  
Result State      To Verify  
Online Results    <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1080>  
Status            New

The variable declared in pa at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833 is not initialized when it is used by pa at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	841	852
Object	pa	pa

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c

Method static void naludmx\_add\_param\_nalu(GF\_List \*param\_list, GF\_NALUFFParam \*sl, u8 nal\_type)

```
....
841.          pa = NULL;
....
852.          gf_list_add(pa->nalus, sl);
```

#### Use of Zero Initialized Pointer\Path 48:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1081>

Status New

The variable declared in pa at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833 is not initialized when it is used by pa at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	835	852
Object	pa	pa

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c

Method static void naludmx\_add\_param\_nalu(GF\_List \*param\_list, GF\_NALUFFParam \*sl, u8 nal\_type)

```
....
835.          GF_NALUFFParamArray *pa = NULL;
....
852.          gf_list_add(pa->nalus, sl);
```

#### Use of Zero Initialized Pointer\Path 49:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1082>

Status New

The variable declared in `_buf` at `gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c` in line 225 is not initialized when it is used by `_buf` at `gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c` in line 225.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c
Line	229	265
Object	_buf	_buf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c

Method void id3dmx\_flush(GF\_Filter \*filter, u8 \*id3\_buf, u32 id3\_buf\_size, GF\_FilterPid \*audio\_pid, GF\_FilterPid \*\*video\_pid\_p)

```
....
229.         char *_buf=NULL;
....
265.         _buf = gf_realloc(_buf, fsize+3);
```

#### Use of Zero Initialized Pointer\Path 50:

Severity Medium

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1083>

Status New

The variable declared in entries at `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c` in line 5370 is not initialized when it is used by entries at `gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c` in line 5370.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	5384	5402
Object	entries	entries

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c

Method GF\_Err stsc\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
5384.         ptr->entries = NULL;
....
5402.         if (i) ptr->entries[i-1].nextChunk = ptr->entries[i].firstChunk;
```

## Divide By Zero

Query Path:

CPP\Cx\CPP Medium Threat\Divide By Zero Version:1

[Description](#)

**Divide By Zero\Path 1:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=25">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=25</a>
Status	New

The application performs an illegal operation in mp3\_dmx\_check\_dur, in gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c. In line 118, the program attempts to divide by prev\_sr, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input prev\_sr in mp3\_dmx\_check\_dur of gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c, at line 118.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c
Line	159	159
Object	prev_sr	prev_sr

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c  
Method static void mp3\_dmx\_check\_dur(GF\_Filter \*filter, GF\_MP3DmxCtx \*ctx)

```
....  
159.                duration /= prev_sr;
```

**Divide By Zero\Path 2:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=26">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=26</a>
Status	New

The application performs an illegal operation in mp3\_dmx\_check\_dur, in gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c. In line 118, the program attempts to divide by prev\_sr, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input prev\_sr in mp3\_dmx\_check\_dur of gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c, at line 118.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c
Line	162	162
Object	prev_sr	prev_sr

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c  
Method static void mp3\_dmx\_check\_dur(GF\_Filter \*filter, GF\_MP3DmxCtx \*ctx)

```
.....
162.                cur_dur /= prev_sr;
```

### Divide By Zero\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=27">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=27</a>
Status	New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
.....
7843.                if (ctrn->ctso_multiplier) return
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

### Divide By Zero\Path 4:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=28">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=28</a>
Status	New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7847.          if (ctrn->ctso_multiplier) return
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 5:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=29>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7843.          if (ctrn->ctso_multiplier) return
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 6:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=30>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c, at line 7835.

Source	Destination
--------	-------------



File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7847.         if (ctrn->ctso_multiplier) return
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 7:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=31>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7843.         if (ctrn->ctso_multiplier) return
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 8:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=32>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at

time of division. This value could be a hard-coded zero value, or received from external, untrusted input `ctso_multiplier` in `ctrn_ctts_to_index` of `gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c`, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name      `gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c`  
Method         `static u32 ctrn_ctts_to_index(GF_TrackFragmentRunBox *ctrn, s32 ctts)`

```
....  
7847.           if (ctrn->ctso_multiplier) return  
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 9:

Severity        Medium  
Result State    To Verify  
Online Results   <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=33>  
Status          New

The application performs an illegal operation in `ctrn_ctts_to_index`, in `gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c`. In line 7835, the program attempts to divide by `ctso_multiplier`, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input `ctso_multiplier` in `ctrn_ctts_to_index` of `gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c`, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name       `gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c`  
Method          `static u32 ctrn_ctts_to_index(GF_TrackFragmentRunBox *ctrn, s32 ctts)`

```
....  
7843.           if (ctrn->ctso_multiplier) return  
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 10:

Severity        Medium  
Result State    To Verify  
Online Results   <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22>

Status [&pathid=34](#)  
New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....  
7847.          if (ctrn->ctso_multiplier) return  
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 11:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=35>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....  
7843.          if (ctrn->ctso_multiplier) return  
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

**Divide By Zero\Path 12:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=36">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=36</a>
Status	New

The application performs an illegal operation in `ctrn_ctts_to_index`, in `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`. In line 7835, the program attempts to divide by `ctso_multiplier`, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input `ctso_multiplier` in `ctrn_ctts_to_index` of `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`, at line 7835.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c</code>
Line	7847	7847
Object	<code>ctso_multiplier</code>	<code>ctso_multiplier</code>

**Code Snippet**

File Name `gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c`  
Method `static u32 ctrn_ctts_to_index(GF_TrackFragmentRunBox *ctrn, s32 ctts)`

```
....  
7847.      if (ctrn->ctso_multiplier) return  
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

**Divide By Zero\Path 13:**

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=37">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=37</a>
Status	New

The application performs an illegal operation in `ctrn_ctts_to_index`, in `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`. In line 7835, the program attempts to divide by `ctso_multiplier`, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input `ctso_multiplier` in `ctrn_ctts_to_index` of `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`, at line 7835.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c</code>
Line	7843	7843
Object	<code>ctso_multiplier</code>	<code>ctso_multiplier</code>

**Code Snippet**

File Name `gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c`  
Method `static u32 ctrn_ctts_to_index(GF_TrackFragmentRunBox *ctrn, s32 ctts)`

```
....  
7843.          if (ctrn->ctso_multiplier) return  
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 14:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=38">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=38</a>
Status	New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....  
7847.          if (ctrn->ctso_multiplier) return  
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 15:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=39">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=39</a>
Status	New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	7843	7843

Object	ctso_multiplier	ctso_multiplier
--------	-----------------	-----------------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7843.          if (ctrn->ctso_multiplier) return
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 16:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=40>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7847.          if (ctrn->ctso_multiplier) return
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

#### Divide By Zero\Path 17:

Severity Medium  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=41>  
Status New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	7843	7843
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7843.          if (ctrn->ctso_multiplier) return
ctrn_s32_to_index(ctts / ctrn->ctso_multiplier);
```

### Divide By Zero\Path 18:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=42">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=42</a>
Status	New

The application performs an illegal operation in ctrn\_ctts\_to\_index, in gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c. In line 7835, the program attempts to divide by ctso\_multiplier, which might be evaluate to 0 (zero) at time of division. This value could be a hard-coded zero value, or received from external, untrusted input ctso\_multiplier in ctrn\_ctts\_to\_index of gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c, at line 7835.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	7847	7847
Object	ctso_multiplier	ctso_multiplier

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method static u32 ctrn\_ctts\_to\_index(GF\_TrackFragmentRunBox \*ctrn, s32 ctts)

```
....
7847.          if (ctrn->ctso_multiplier) return
ctrn_u32_to_index((u32)ctts / ctrn->ctso_multiplier);
```

## Buffer Overflow Loops

Query Path:

CPP\Cx\CPP Buffer Overflow\Buffer Overflow Loops Version:1

### Categories

PCI DSS v3.2: PCI DSS (3.2) - 6.5.2 - Buffer overflows

NIST SP 800-53: SI-16 Memory Protection (P1)

OWASP Top 10 2017: A1-Injection

### Description

#### Buffer Overflow Loops\Path 1:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=223">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=223</a>
Status	New

The buffer allocated by c in gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c at line 254 does not correctly account for the actual size of the value, resulting in an incorrect allocation that is off by one.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c
Line	313	330
Object	16	c

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c  
Method GF\_Err vobsub\_read\_idx(FILE \*file, vobsub\_file \*vobsub, s32 \*version)

```
....  
313.                u8  palette[16][4];  
....  
330.                g = palette[c][1];
```

#### Buffer Overflow Loops\Path 2:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=224">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=224</a>
Status	New

The buffer allocated by c in gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c at line 254 does not correctly account for the actual size of the value, resulting in an incorrect allocation that is off by one.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c
Line	313	329
Object	16	c

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c  
Method GF\_Err vobsub\_read\_idx(FILE \*file, vobsub\_file \*vobsub, s32 \*version)



```

.....
313.                u8  palette[16][4];
.....
329.                r = palette[c][2];

```

### Buffer Overflow Loops\Path 3:

Severity	Medium
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=225">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=225</a>
Status	New

The buffer allocated by c in gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c at line 254 does not correctly account for the actual size of the value, resulting in an incorrect allocation that is off by one.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c
Line	313	331
Object	16	c

### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3523-TP.c  
Method GF\_Err vobsub\_read\_idx(FILE \*file, vobsub\_file \*vobsub, s32 \*version)

```

.....
313.                u8  palette[16][4];
.....
331.                b = palette[c][0];

```

## Improper Resource Access Authorization

### Query Path:

CPP\Cx\CPP Low Visibility\Improper Resource Access Authorization Version:1

### Categories

FISMA 2014: Identification And Authentication  
NIST SP 800-53: AC-3 Access Enforcement (P1)  
OWASP Top 10 2017: A2-Broken Authentication

### Description

### Improper Resource Access Authorization\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1175">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1175</a>
Status	New

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4600	4600
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4600.          fprintf(stderr, "Downloading %s\n", mpd_src);
```

#### Improper Resource Access Authorization\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1176">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1176</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4693	4693
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4693.          fprintf(stderr, "Downloading %s\n",  
seg_url);
```

#### Improper Resource Access Authorization\Path 3:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1177">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1177</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4721	4721
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c

Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4721.                                     fprintf(stderr, "Downloading %s\n",  
seg_url);
```

**Improper Resource Access Authorization\Path 4:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1178>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4186	4186
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c

Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4186.                                     fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

**Improper Resource Access Authorization\Path 5:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1179>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4191	4191
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c

Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4191.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

#### Improper Resource Access Authorization\Path 6:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1180>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4199	4199
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4199.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

#### Improper Resource Access Authorization\Path 7:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1181>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4205	4205
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4205.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

### Improper Resource Access Authorization\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1182">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1182</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4210	4210
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4210.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

### Improper Resource Access Authorization\Path 9:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1183">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1183</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4215	4215
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4215.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

### Improper Resource Access Authorization\Path 10:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1184">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1184</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4239	4239
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4239.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1185">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1185</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4247	4247
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4247.                                fprintf(dumper->timestamps_info_file,
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1186">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1186</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4255	4255
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4255.                                fprintf(dumper->timestamps_info_file,
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1187">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1187</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4312	4312
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4312.                                fprintf(dumper->timestamps_info_file,
"%u\t%d\t", pck->stream->pes_start_packet_number, pck->stream->pid);
```

#### Improper Resource Access Authorization\Path 14:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1188">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1188</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4313	4313
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4313.                                if (interpolated_pcr_value)
fprintf(dumper->timestamps_info_file, "%f",
interpolated_pcr_value/(300.0 * 90000));
```

#### Improper Resource Access Authorization\Path 15:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1189">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1189</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4314	4314
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)



```
.....
4314.                                fprintf(dumper->timestamps_info_file,
"\t");
```

#### Improper Resource Access Authorization\Path 16:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1190">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1190</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4315	4315
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4315.                                if (pck->DTS) fprintf(dumper-
>timestamps_info_file, "%f", (pck->DTS / 90000.0));
```

#### Improper Resource Access Authorization\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1191">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1191</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4316	4316
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....
4316.                                     fprintf(dumper->timestamps_info_file,
"\t%f\t%d\t%d", pck->PTS / 90000.0, (pck->flags & GF_M2TS_PES_PCK_RAP) ?
1 : 0, (pck->flags & GF_M2TS_PES_PCK_DISCONTINUITY) ? 1 : 0);
```

### Improper Resource Access Authorization\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1192">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1192</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4320	4320
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....
4320.                                     fprintf(dumper-
>timestamps_info_file, "\t%f\n", diff);
```

### Improper Resource Access Authorization\Path 19:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1193">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1193</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4325	4325
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```

.....
4325.                                     fprintf(dumper-
>timestamps_info_file, "\t\n");

```

## Improper Resource Access Authorization\Path 20:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1194">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1194</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4339	4339
Object	fprintf	fprintf

## Code Snippet

File Name	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Method	static void on_m2ts_dump_event(GF_M2TS_Demuxer *ts, u32 evt_type, void *par)

[illegible]

## Improper Resource Access Authorization\Path 21:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1195">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1195</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4384	4384
Object	fprintf	fprintf

## Code Snippet

```
File Name      gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Method        void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)
```

```
....  
4384.                fprintf(stderr, "No program number nor output filename  
specified. No timestamp file will be generated.");
```

### Improper Resource Access Authorization\Path 22:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1196">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1196</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4434	4434
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4434.                fprintf(stderr, "No program number specified,  
defaulting to first program\n");
```

### Improper Resource Access Authorization\Path 23:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1197">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1197</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4438	4438
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4438.                fprintf(stderr, "No program number nor output filename  
specified. No timestamp file will be generated\n");
```

**Improper Resource Access Authorization\Path 24:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1198">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1198</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4448	4448
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4448.                fprintf(dumper.timestamps_info_file,  
"PCK#\tPID\tPCR\tDTS\tPTS\tRAP\tDiscontinuity\tDTS-PCR Diff\n");
```

**Improper Resource Access Authorization\Path 25:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1199">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1199</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4491	4491
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void get\_file\_callback(void \*usr\_cbk, GF\_NETIO\_Parameter \*parameter)

```
....  
4491.                fprintf(stderr, "download %02d %% at %05d  
kpbs\r", (u32) max, bps*8/1000);
```

**Improper Resource Access Authorization\Path 26:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1199">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1199</a>

	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1200">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1200</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4516	4516
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method static void revert\_cache\_file(char \*item\_path)

```
....
4516.          fprintf(stderr, "%s is not a gpac cache file\n",
item_path);
```

### Improper Resource Access Authorization\Path 27:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1201">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1201</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4600	4600
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....
4600.          fprintf(stderr, "Downloading %s\n", mpd_src);
```

### Improper Resource Access Authorization\Path 28:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1202">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1202</a>
Status	New

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4693	4693
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4693.                                     fprintf(stderr, "Downloading %s\n",  
seg_url);
```

#### Improper Resource Access Authorization\Path 29:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1203">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1203</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4721	4721
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method GF\_Err rip\_mpd(const char \*mpd\_src, const char \*output\_dir)

```
....  
4721.                                     fprintf(stderr, "Downloading %s\n",  
seg_url);
```

#### Improper Resource Access Authorization\Path 30:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1204">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1204</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4186	4186

Object	fprintf	fprintf
--------	---------	---------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4186.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

#### Improper Resource Access Authorization\Path 31:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1205>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4191	4191
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4191.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

#### Improper Resource Access Authorization\Path 32:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1206>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4199	4199
Object	fprintf	fprintf



**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4199.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

**Improper Resource Access Authorization\Path 33:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1207>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4205	4205
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4205.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

**Improper Resource Access Authorization\Path 34:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1208>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4210	4210
Object	fprintf	fprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4210.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

### Improper Resource Access Authorization\Path 35:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1209>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4215	4215
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4215.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, 0);
```

### Improper Resource Access Authorization\Path 36:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1210>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4239	4239
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4239.                                fprintf(dumper->timestamps_info_file,
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 37:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1211">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1211</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4247	4247
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4247.                                fprintf(dumper->timestamps_info_file,
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 38:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1212">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1212</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4255	4255
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4255.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\n", ts->pck_number, prog->pmt_pid);
```

### Improper Resource Access Authorization\Path 39:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1213">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1213</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4312	4312
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
....  
4312.                                fprintf(dumper->timestamps_info_file,  
"%u\t%d\t", pck->stream->pes_start_packet_number, pck->stream->pid);
```

### Improper Resource Access Authorization\Path 40:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1214">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1214</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4313	4313
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4313.                                if (interpolated_pcr_value)
fprintf(dumper->timestamps_info_file, "%f",
interpolated_pcr_value/(300.0 * 90000));
```

#### Improper Resource Access Authorization\Path 41:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1215">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1215</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4314	4314
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4314.                                fprintf(dumper->timestamps_info_file,
"\t");
```

#### Improper Resource Access Authorization\Path 42:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1216">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1216</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4315	4315
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4315.                                if (pck->DTS) fprintf(dumper-
>timestamps_info_file, "%f", (pck->DTS / 90000.0));
```

#### Improper Resource Access Authorization\Path 43:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1217">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1217</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4316	4316
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....
4316.                                fprintf(dumper->timestamps_info_file,
"\t%f\t%d\t%d", pck->PTS / 90000.0, (pck->flags & GF_M2TS_PES_PCK_RAP) ?
1 : 0, (pck->flags & GF_M2TS_PES_PCK_DISCONTINUITY) ? 1 : 0);
```

#### Improper Resource Access Authorization\Path 44:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1218">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1218</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4320	4320
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....  
4320.                                     fprintf(dumper-  
>timestamps_info_file, "\\t%f\\n", diff);
```

#### Improper Resource Access Authorization\Path 45:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1219">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1219</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4325	4325
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

```
.....  
4325.                                     fprintf(dumper-  
>timestamps_info_file, "\\t\\n");
```

#### Improper Resource Access Authorization\Path 46:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1220">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1220</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4339	4339
Object	fprintf	fprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method static void on\_m2ts\_dump\_event(GF\_M2TS\_Demuxer \*ts, u32 evt\_type, void \*par)

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1221">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1221</a>
Status	New

Code Snippet

File Name	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Method	void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)

```
....
4384.                fprintf(stderr, "No program number nor output filename
specified. No timestamp file will be generated.");
```

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1222">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1222</a>
Status	New

Code Snippet	
File Name	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Method	void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)



```
....  
4434.                fprintf(stderr, "No program number specified,  
defaulting to first program\n");
```

#### Improper Resource Access Authorization\Path 49:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1223">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1223</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4438	4438
Object	fprintf	fprintf

##### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4438.                fprintf(stderr, "No program number nor output filename  
specified. No timestamp file will be generated\n");
```

#### Improper Resource Access Authorization\Path 50:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1224">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1224</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4448	4448
Object	fprintf	fprintf

##### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4448.                fprintf(dumper.timestamps_info_file,  
"PCK#\tPID\tPCR\tDTS\tPTS\tRAP\tDiscontinuity\tDTS-PCR Diff\n");
```

## NULL Pointer Dereference

Query Path:

CPP\Cx\CPP Low Visibility\NULL Pointer Dereference Version:1

### Categories

NIST SP 800-53: SC-5 Denial of Service Protection (P1)

OWASP Top 10 2017: A1-Injection

### Description

#### NULL Pointer Dereference\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=965">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=965</a>
Status	New

The variable declared in null at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 651 is not initialized when it is used by sgprivate at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 211.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	656	253
Object	null	sgprivate

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static SVG\_Element \*svg\_parse\_element(GF\_SVG\_Parser \*parser, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes, SVG\_NodeStack \*parent, Bool \*has\_ns)

```
....
656.         SVG_Element *elt = NULL;
```

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
 Method static void svg\_process\_media\_href(GF\_SVG\_Parser \*parser, GF\_Node \*elt, XMLRI \*iri)

```
....
253.                                     gf_svg_delete_attribute_value(att-
>data_type, att->data, elt->sgprivate->scenegraph);
```

#### NULL Pointer Dereference\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=966">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=966</a>
Status	New

The variable declared in null at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1352 is not initialized when it is used by stream\_name at gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c in line 1352.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	1516	1516
Object	null	stream_name

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static void svg\_node\_start(void \*sax\_cbck, const char \*name, const char \*name\_space, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....
1516.                                st->stream_name = ID ? gf_strdup(ID) : NULL;
```

#### NULL Pointer Dereference\Path 3:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=967>

Status New

The variable declared in null at gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c in line 59 is not initialized when it is used by Pointer at gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c in line 59.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c
Line	221	221
Object	null	Pointer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c

Method static GF\_Err BD\_XReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....
221.                                * ((GF_ChildNodeItem **) targetField.far_ptr) = NULL;
```

#### NULL Pointer Dereference\Path 4:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=968>

Status New

The variable declared in null at gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c in line 59 is not initialized when it is used by Pointer at gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c in line 59.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	221	221
Object	null	Pointer

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c

Method static GF\_Err BD\_XReplace(GF\_BifsDecoder \* codec, GF\_BitStream \*bs)

```
....  
221.                * ((GF_ChildNodeItem **) targetField.far_ptr) = NULL;
```

#### NULL Pointer Dereference\Path 5:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=969>

Status New

The variable declared in null at gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c in line 856 is not initialized when it is used by def\_name at gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c in line 856.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c
Line	885	885
Object	null	def_name

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c

Method GF\_Err BM\_SceneReplace(GF\_BifsDecoder \*codec, GF\_BitStream \*bs, GF\_List \*com\_list)

```
....  
885.                ri->def_name = r->name ? gf_strdup(r->name) : NULL;
```

#### NULL Pointer Dereference\Path 6:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=970>

Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

### NULL Pointer Dereference\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=971">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=971</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

### NULL Pointer Dereference\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=972">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=972</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 9:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=973">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=973</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 10:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=974">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=974</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 11:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=975>

Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 12:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=976>

Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=977">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=977</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 14:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=978">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=978</a>
Status	New



The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 15:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=979">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=979</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 16:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=980">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=980</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 17:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=981">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=981</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=982">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=982</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402 is not initialized when it is used by Marker at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	418	418
Object	0	Marker

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c

Method GF\_Err gp\_rtp\_builder\_do\_avc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....  
418.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
```

### NULL Pointer Dereference\Path 19:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=983>

Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402 is not initialized when it is used by builder at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	418	432
Object	0	builder

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c

Method GF\_Err gp\_rtp\_builder\_do\_avc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....  
418.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;  
....  
432.                builder->OnNewPacket(builder->cbk_obj, &builder->rtp_header);
```

### NULL Pointer Dereference\Path 20:

Severity Low

Result State To Verify

Online Results <http://WIN->

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=984">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=984</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402 is not initialized when it is used by rtp\_header at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 402.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	418	432
Object	0	rtp_header

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_avc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....  
418.          builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;  
....  
432.          builder->OnNewPacket(builder->cbk_obj, &builder-  
>rtp_header);
```

#### NULL Pointer Dereference\Path 21:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=985">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=985</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539 is not initialized when it is used by Marker at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	552	552
Object	0	Marker

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_hevc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....  
552.          builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
```

**NULL Pointer Dereference\Path 22:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=986">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=986</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539 is not initialized when it is used by rtp\_header at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	552	570
Object	0	rtp_header

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_hevc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....  
552.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;  
....  
570.                builder->OnNewPacket(builder->cbk_obj, &builder-  
>rtp_header);
```

**NULL Pointer Dereference\Path 23:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=987">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=987</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539 is not initialized when it is used by builder at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 539.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	552	570
Object	0	builder

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_hevc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
.....
552.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
.....
570.                builder->OnNewPacket(builder->cbk_obj, &builder-
>rtp_header);
```

### NULL Pointer Dereference\Path 24:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=988">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=988</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695 is not initialized when it is used by Marker at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	708	708
Object	0	Marker

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_vvc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
.....
708.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
```

### NULL Pointer Dereference\Path 25:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=989">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=989</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695 is not initialized when it is used by rtp\_header at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	708	726
Object	0	rtp_header

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_vvc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....
708.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
....
726.                builder->OnNewPacket(builder->cbk_obj, &builder-
>rtp_header);
```

#### NULL Pointer Dereference\Path 26:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=990>  
Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695 is not initialized when it is used by builder at gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c in line 695.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c	gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c
Line	708	726
Object	0	builder

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29537-FP.c  
Method GF\_Err gp\_rtp\_builder\_do\_vvc(GP\_RTPPacketizer \*builder, u8 \*nalu, u32 nalu\_size, u8 IsAUEnd, u32 FullAUSize)

```
....
708.                builder->rtp_header.Marker = (do_flush==1) ? 1 : 0;
....
726.                builder->OnNewPacket(builder->cbk_obj, &builder-
>rtp_header);
```

#### NULL Pointer Dereference\Path 27:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=991>  
Status New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-	gpac@@gpac-v2.2.0-CVE-2022-3178-

	FP.c	FP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.          ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 28:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=992">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=992</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.          ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 29:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=993">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=993</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c in line 3080 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c in line 3080.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-	gpac@@gpac-v2.2.0-CVE-2023-0760-



	TP.c	TP.c
Line	3083	3083
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err mdhd\_box\_size(GF\_Box \*s)

```
....  
3083.         ptr->version = (ptr->duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 30:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=994">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=994</a>
Status	New

The variable declared in 0 at gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c in line 4570 is not initialized when it is used by version at gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c in line 4570.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	4573	4573
Object	0	version

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err mehd\_box\_size(GF\_Box \*s)

```
....  
4573.         ptr->version = (ptr->fragment_duration>0xFFFFFFFF) ? 1 : 0;
```

#### NULL Pointer Dereference\Path 31:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=995">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=995</a>
Status	New

The variable declared in pSamp at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1459 is not initialized when it is used by sample\_delta at gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c in line 1459.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-29340-	gpac@@gpac-v2.2.0-CVE-2022-29340-

	TP.c	TP.c
Line	1462	1471
Object	pSamp	sample_delta

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-29340-TP.c  
Method GF\_Err gf\_isom\_add\_subsample\_info(GF\_SubSampleInformationBox \*sub\_samples, u32 sampleNumber, u32 subSampleSize, u8 priority, u32 reserved, Bool discardable)

```
....  
1462.          GF_SubSampleInfoEntry *pSamp;  
....  
1471.          if (last_sample + pSamp->sample_delta > sampleNumber)  
return GF_NOT_SUPPORTED;
```

#### NULL Pointer Dereference\Path 32:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=996>  
Status New

The variable declared in pSamp at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1459 is not initialized when it is used by sample\_delta at gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c in line 1459.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c
Line	1462	1471
Object	pSamp	sample_delta

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43254-FP.c  
Method GF\_Err gf\_isom\_add\_subsample\_info(GF\_SubSampleInformationBox \*sub\_samples, u32 sampleNumber, u32 subSampleSize, u8 priority, u32 reserved, Bool discardable)

```
....  
1462.          GF_SubSampleInfoEntry *pSamp;  
....  
1471.          if (last_sample + pSamp->sample_delta > sampleNumber)  
return GF_NOT_SUPPORTED;
```

#### NULL Pointer Dereference\Path 33:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=997>

Status New

The variable declared in pa at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833 is not initialized when it is used by type at gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c in line 833.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	835	840
Object	pa	type

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c

Method static void naludmx\_add\_param\_nalu(GF\_List \*param\_list, GF\_NALUFFParam \*sl, u8 nal\_type)

```

....
835.         GF_NALUFFParamArray *pa = NULL;
....
840.         if (pa->type == nal_type) break;

```

## Unchecked Array Index

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Array Index Version:1

### Categories

NIST SP 800-53: SI-10 Information Input Validation (P1)

### Description

#### Unchecked Array Index\Path 1:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1006>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c

Method GF\_Err cprt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```

....
248.         ptr->notice[bytesToRead] = 0;

```

**Unchecked Array Index\Path 2:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1007">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1007</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c	gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c
Line	2607	2607
Object	length	length

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-11558-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607.         ptr->payloadString[length] = 0;
```

**Unchecked Array Index\Path 3:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1008">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1008</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c	gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c
Line	166	166
Object	dataSize	dataSize

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c  
Method GF\_Err ilst\_item\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
166.         ptr->data->data[ptr->data->dataSize] = 0;
```

**Unchecked Array Index\Path 4:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1009">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1009</a>

Status	New
--------	-----

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c	gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c
Line	1019	1019
Object	size	size

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-19488-FP.c  
Method GF\_Err keys\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
1019.                k->data[k->size]=0;
```

#### Unchecked Array Index\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1010">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1010</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err cprt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248.                ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 6:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1011">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1011</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c	gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c

Line	2607	2607
Object	length	length

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-21852-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
2607.          ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 7:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1012>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c	gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c
Line	154	154
Object	len	len

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-31254-FP.c  
Method GF\_Err schm\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....
154.          ptr->URI[len] = 0;
```

#### Unchecked Array Index\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1013>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

Method GF\_Err cppt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248. ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 9:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1014>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c
Line	2607	2607
Object	length	length

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32134-FP.c

Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607. ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 10:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1015>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c

Method GF\_Err cppt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248. ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1016">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1016</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c
Line	2607	2607
Object	length	length

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32268-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607.          ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1017">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1017</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err cppt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248.          ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1018">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1018</a>
Status	New



	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c	gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c
Line	2607	2607
Object	length	length

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-4043-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607.          ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 14:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1019">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1019</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err cppt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248.          ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 15:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1020">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1020</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c	gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c
Line	2607	2607

Object	length	length
--------	--------	--------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-24577-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607.          ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 16:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1021>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err cppt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248.          ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 17:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1022>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c
Line	2607	2607
Object	length	length

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3178-FP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
.....  
2607.          ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 18:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1023">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1023</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	237	237
Object	size	size

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static void svg\_process\_media\_href(GF\_SVG\_Parser \*parser, GF\_Node \*elt, XMLRI \*iri)

```
.....  
237.          buffer[size]=0;
```

#### Unchecked Array Index\Path 19:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1024">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1024</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	266	266
Object	size64	size64

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static void svg\_process\_media\_href(GF\_SVG\_Parser \*parser, GF\_Node \*elt, XMLRI \*iri)

```
.....  
266.          buf64[size64] = 0;
```

**Unchecked Array Index\Path 20:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1025">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1025</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	808	808
Object	k	k

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....  
808.                value[k] = str[i];
```

**Unchecked Array Index\Path 21:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1026">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1026</a>
Status	New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	814	814
Object	k	k

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_parse\_string(GF\_XMTParser \*parser, const char \*name, SFString \*val, Bool is\_mf, char \*a\_value)

```
....  
814.                value[k] = 0;
```

**Unchecked Array Index\Path 22:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22</a>

[&pathid=1027](#)

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2425	2425
Object	del_proto_list_size	del_proto_list_size

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....  
2425.                                     parser->command-  
>del_proto_list[parser->command->del_proto_list_size] = p->ID;
```

#### Unchecked Array Index\Path 23:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1028>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2497	2497
Object	NbESDs	NbESDs

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....  
2497.                                     esdR->ES_ID[esdR->NbESDs] = es_id;
```

#### Unchecked Array Index\Path 24:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1029>

Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	2516	2516
Object	NbODs	NbODs

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_parse\_command(GF\_XMTParser \*parser, const char \*name, const GF\_XMLAttribute \*attributes, u32 nb\_attributes)

```
....  
2516.                                odR->OD_ID[odR->NbODs] = od_id;
```

#### Unchecked Array Index\Path 25:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1030>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	248	248
Object	bytesToRead	bytesToRead

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err cpvt\_box\_read(GF\_Box \*s,GF\_BitStream \*bs)

```
....  
248.                                ptr->notice[bytesToRead] = 0;
```

#### Unchecked Array Index\Path 26:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1031>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c	gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c
Line	2607	2607

Object	length	length
--------	--------	--------

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-0760-TP.c  
Method GF\_Err payt\_box\_read(GF\_Box \*s, GF\_BitStream \*bs)

```
....  
2607. ptr->payloadString[length] = 0;
```

#### Unchecked Array Index\Path 27:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1032>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	1010	1010
Object	num_layers_dependent_on	num_layers_dependent_on

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c  
Method GF\_Err naludmx\_set\_hevc\_oinf(GF\_NALUDmxCtx \*ctx, u8 \*max\_temporal\_id)

```
....  
1010. dep->dependent_on_layerID[dep->num_layers_dependent_on] = j;
```

#### Unchecked Array Index\Path 28:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1033>  
Status New

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c	gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c
Line	219	219
Object	count	count

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-41000-TP.c

Method static GF\_Err BM\_ParseProtoDelete(GF\_BifsDecoder \*codec, GF\_BitStream \*bs, GF\_List \*com\_list)

```
....
219.                                com->del_proto_list[count] = gf_bs_read_int(bs,
codec->info->config.ProtoIDBits);
```

## Unchecked Return Value

Query Path:

CPP\Cx\CPP Low Visibility\Unchecked Return Value Version:1

### Categories

NIST SP 800-53: SI-11 Error Handling (P2)

#### Description

##### Unchecked Return Value\Path 1:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=946">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=946</a>
Status	New

The dump\_mpeg2\_ts method calls the sprintf function, at line 4373 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4405	4405
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....
4405.                                sprintf(dumper.dump, "%s%d.raw", out_name,
dumper.dump_pid);
```

##### Unchecked Return Value\Path 2:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=947">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=947</a>
Status	New

The dump\_mpeg2\_ts method calls the sprintf function, at line 4373 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.



	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4442	4442
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c

Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4442.                sprintf(dumper.timestamps_info_name,  
"%s_prog_%d_timestamps.txt", mpeg2ts_file, prog_num/*, mpeg2ts_file*/);
```

#### Unchecked Return Value\Path 3:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=948>

Status New

The dump\_mpeg2\_ts method calls the sprintf function, at line 4373 of gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4405	4405
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4405.                sprintf(dumper.dump, "%s_%d.raw", out_name,  
dumper.dump_pid);
```

#### Unchecked Return Value\Path 4:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=949>

Status New

The `dump_mpeg2_ts` method calls the `sprintf` function, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4442	4442
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c

Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4442.             sprintf(dumper.timestamps_info_name,  
"%s_prog_%d_timestamps.txt", mpeg2ts_file, prog_num/*, mpeg2ts_file*/);
```

#### Unchecked Return Value\Path 5:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=950>

Status New

The `svg_process_media_href` method calls the `sprintf` function, at line 211 of `gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c`. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	275	275
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c

Method static void svg\_process\_media\_href(GF\_SVG\_Parser \*parser, GF\_Node \*elt, XMLRI \*iri)

```
....  
275.             sprintf(iri->string, "data:%s;base64,%s", mtype,  
buf64);
```

#### Unchecked Return Value\Path 6:

Severity Low

Result State To Verify

Online Results <http://WIN->

	<a href="http://PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=951">PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=951</a>
Status	New

The `gf_bifs_dec_proto_list` method calls the `sprintf` function, at line 999 of `gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c`. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c</code>
Line	1033	1033
Object	<code>sprintf</code>	<code>sprintf</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c`  
Method `GF_Err gf_bifs_dec_proto_list(GF_BifsDecoder * codec, GF_BitStream *bs, GF_List *proto_list)`

```
....  
1033.                sprintf(name, "Proto%d", gf_list_count(codec->current_graph->protos) );
```

#### Unchecked Return Value\Path 7:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=952">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=952</a>
Status	New

The `gf_bifs_dec_proto_list` method calls the `sprintf` function, at line 999 of `gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c`. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c</code>
Line	1057	1057
Object	<code>sprintf</code>	<code>sprintf</code>

#### Code Snippet

File Name `gpac@@gpac-v2.2.0-CVE-2022-43043-FP.c`  
Method `GF_Err gf_bifs_dec_proto_list(GF_BifsDecoder * codec, GF_BitStream *bs, GF_List *proto_list)`

```
....  
1057.                sprintf(name, "_field%d", numFields);
```

### Unchecked Return Value\Path 8:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=953">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=953</a>
Status	New

The xmt\_new\_od\_link method calls the sprintf function, at line 181 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	192	192
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_new\_od\_link(GF\_XMTParser \*parser, GF\_ObjectDescriptor \*od, char \*name, u32 ID)

```
....  
192.                sprintf(szURL, "%u", ID);
```

### Unchecked Return Value\Path 9:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=954">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=954</a>
Status	New

The xmt\_new\_od\_link\_from\_node method calls the sprintf function, at line 240 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	252	252
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_new\_od\_link\_from\_node(GF\_XMTParser \*parser, char \*name, MFURL \*url)

```
....  
252.          sprintf(szURL, "%u", ID);
```

#### Unchecked Return Value\Path 10:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=955">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=955</a>
Status	New

The xmt\_locate\_stream method calls the sprintf function, at line 381 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	391	391
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_locate\_stream(GF\_XMTParser \*parser, char \*stream\_name)

```
....  
391.          sprintf(szN, "es%d", esdl->ESID);
```

#### Unchecked Return Value\Path 11:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=956">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=956</a>
Status	New

The xmt\_locate\_stream method calls the sprintf function, at line 381 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	393	393
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static u32 xmt\_locate\_stream(GF\_XMTParser \*parser, char \*stream\_name)

```
....  
393.                sprintf(szN, "%d", esdl->ESID);
```

#### Unchecked Return Value\Path 12:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=957">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=957</a>
Status	New

The xmt\_locate\_stream method calls the sprintf function, at line 381 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	402	402
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static u32 xmt\_locate\_stream(GF\_XMTParser \*parser, char \*stream\_name)

```
....  
402.                sprintf(szN, "%d", sc->ESID);
```

#### Unchecked Return Value\Path 13:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=958">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=958</a>
Status	New

The xmt\_resolve\_od\_links method calls the sprintf function, at line 427 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	465	465
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_resolve\_od\_links(GF\_XMTParser \*parser)

```
....  
465.                sprintf(szTest, "%d", ocr_id);
```

#### Unchecked Return Value\Path 14:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=959>  
Status New

The xmt\_resolve\_od\_links method calls the sprintf function, at line 427 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	498	498
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_resolve\_od\_links(GF\_XMTParser \*parser)

```
....  
498.                sprintf(szTest, "%d", dep_id);
```

#### Unchecked Return Value\Path 15:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=960>  
Status New

The xmt\_resolve\_od\_links method calls the sprintf function, at line 427 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	585	585
Object	sprintf	sprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c

Method static void xmt\_resolve\_od\_links(GF\_XMTParser \*parser)

```
....  
585.                                     sprintf(szURL, "od:%d#%s", l-  
>od->objectDescriptorID, seg+1);
```

**Unchecked Return Value\Path 16:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=961>

Status New

The naludmx\_process method calls the sprintf function, at line 3027 of gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	3831	3831
Object	sprintf	sprintf

**Code Snippet**

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c

Method GF\_Err naludmx\_process(GF\_Filter \*filter)

```
....  
3831.                                     sprintf(szStatus, "%s %dx%d % 10d NALU % 8d I % 8d P %  
8d B % 8d SEI", ctx->log_name, ctx->width, ctx->height, ctx->nb_nalus,  
ctx->nb_i, ctx->nb_p, ctx->nb_b, ctx->nb_sei);
```

**Unchecked Return Value\Path 17:**

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=962>

Status New

The id3dmx\_flush method calls the sprintf function, at line 225 of gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c



Line	326	326
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c

Method void id3dmx\_flush(GF\_Filter \*filter, u8 \*id3\_buf, u32 id3\_buf\_size, GF\_FilterPid \*audio\_pid, GF\_FilterPid \*\*video\_pid\_p)

```
....  
326.                                sprintf(szTag, "tag_%s", gf_4cc_to_str(ftag));
```

#### Unchecked Return Value\Path 18:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=963>

Status New

The gf\_bifs\_dec\_proto\_list method calls the sprintf function, at line 999 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	1033	1033
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c

Method GF\_Err gf\_bifs\_dec\_proto\_list(GF\_BifsDecoder \* codec, GF\_BitStream \*bs, GF\_List \*proto\_list)

```
....  
1033.                                sprintf(name, "Proto%d", gf_list_count(codec->current_graph->protos) );
```

#### Unchecked Return Value\Path 19:

Severity Low

Result State To Verify

Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=964>

Status New

The gf\_bifs\_dec\_proto\_list method calls the sprintf function, at line 999 of gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c. However, the code does not check the return value from this function, and thus would not detect runtime errors or other unexpected states.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c	gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c
Line	1057	1057
Object	sprintf	sprintf

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-37767-TP.c  
Method GF\_Err gf\_bifs\_dec\_proto\_list(GF\_BifsDecoder \* codec, GF\_BitStream \*bs, GF\_List \*proto\_list)

```
....  
1057.                                sprintf(name, "_field%d", numFields);
```

## Potential Precision Problem

#### Query Path:

CPP\Cx\CPP Buffer Overflow\Potential Precision Problem Version:0

#### Categories

NIST SP 800-53: SI-10 Information Input Validation (P1)  
OWASP Top 10 2017: A1-Injection

#### Description

##### Potential Precision Problem\Path 1:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=998>  
Status New

The size of the buffer used by dump\_mpeg2\_ts in "%s\_%d.raw", at line 4373 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that dump\_mpeg2\_ts passes to "%s\_%d.raw", at line 4373 of gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c	gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c
Line	4405	4405
Object	"%s_%d.raw"	"%s_%d.raw"

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c  
Method void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....  
4405.                                sprintf(dumper.dump, "%s_%d.raw", out_name,  
dumper.dump_pid);
```

**Potential Precision Problem\Path 2:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=999">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=999</a>
Status	New

The size of the buffer used by `dump_mpeg2_ts` in `"%s_prog_%d_timestamps.txt"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `dump_mpeg2_ts` passes to `"%s_prog_%d_timestamps.txt"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c</code>
Line	4442	4442
Object	<code>"%s_prog_%d_timestamps.txt"</code>	<code>"%s_prog_%d_timestamps.txt"</code>

**Code Snippet**

File Name `gpac@@gpac-v2.2.0-CVE-2020-23932-FP.c`  
Method `void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)`

```
....  
4442.          sprintf(dumper.timestamps_info_name,  
"%s_prog_%d_timestamps.txt", mpeg2ts_file, prog_num/*, mpeg2ts_file*/);
```

**Potential Precision Problem\Path 3:**

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1000">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1000</a>
Status	New

The size of the buffer used by `dump_mpeg2_ts` in `"%s_%d.raw"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `dump_mpeg2_ts` passes to `"%s_%d.raw"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, to overwrite the target buffer.

	Source	Destination
File	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>	<code>gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c</code>
Line	4405	4405
Object	<code>"%s_%d.raw"</code>	<code>"%s_%d.raw"</code>

**Code Snippet**

File Name `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`  
Method `void dump_mpeg2_ts(char *mpeg2ts_file, char *out_name, Bool prog_num)`

```
....
4405.                sprintf(dumper.dump, "%s_%d.raw", out_name,
dumper.dump_pid);
```

#### Potential Precision Problem\Path 4:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1001">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1001</a>
Status	New

The size of the buffer used by `dump_mpeg2_ts` in `"%s_prog_%d_timestamps.txt"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `dump_mpeg2_ts` passes to `"%s_prog_%d_timestamps.txt"`, at line 4373 of `gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c	gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c
Line	4442	4442
Object	"%s_prog_%d_timestamps.txt"	"%s_prog_%d_timestamps.txt"

#### Code Snippet

File Name      gpac@@gpac-v2.2.0-CVE-2021-32136-FP.c  
Method          void dump\_mpeg2\_ts(char \*mpeg2ts\_file, char \*out\_name, Bool prog\_num)

```
....
4442.                sprintf(dumper.timestamps_info_name,
"%s_prog_%d_timestamps.txt", mpeg2ts_file, prog_num/*, mpeg2ts_file*/);
```

#### Potential Precision Problem\Path 5:

Severity	Low
Result State	To Verify
Online Results	<a href="http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1002">http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&amp;projectid=22&amp;pathid=1002</a>
Status	New

The size of the buffer used by `svg_process_media_href` in `"data:%s;base64,%s"`, at line 211 of `gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c`, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that `svg_process_media_href` passes to `"data:%s;base64,%s"`, at line 211 of `gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c`, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c	gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c
Line	275	275
Object	"data:%s;base64,%s"	"data:%s;base64,%s"

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-3957-FP.c  
Method static void svg\_process\_media\_href(GF\_SVG\_Parser \*parser, GF\_Node \*elt, XMLRI \*iri)

```
....
275.                                     sprintf(iri->string, "data:%s;base64,%s", mtype,
buf64);
```

#### Potential Precision Problem\Path 6:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1003>  
Status New

The size of the buffer used by xmt\_resolve\_od\_links in "od:%d#%s", at line 427 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that xmt\_resolve\_od\_links passes to "od:%d#%s", at line 427 of gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c	gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c
Line	585	585
Object	"od:%d#%s"	"od:%d#%s"

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2022-43255-FP.c  
Method static void xmt\_resolve\_od\_links(GF\_XMTParser \*parser)

```
....
585.                                     sprintf(szURL, "od:%d#%s", l-
>od->objectDescriptorID, seg+1);
```

#### Potential Precision Problem\Path 7:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1004>  
Status New

The size of the buffer used by naludmx\_process in "%s %dx%d % 10d NALU % 8d I % 8d P % 8d B % 8d SEI", at line 3027 of gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that naludmx\_process passes to "%s %dx%d % 10d NALU % 8d I % 8d P % 8d B % 8d SEI", at line 3027 of gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c, to overwrite the target buffer.

Source	Destination
--------	-------------

File	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c	gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c
Line	3831	3831
Object	"%s %dx%d % 10d NALU % 8d I % 8d P % 8d B % 8d SEI"	"%s %dx%d % 10d NALU % 8d I % 8d P % 8d B % 8d SEI"

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-2839-TP.c  
Method GF\_Err naludmx\_process(GF\_Filter \*filter)

```
....
3831.          sprintf(szStatus, "%s %dx%d % 10d NALU % 8d I % 8d P %
8d B % 8d SEI", ctx->log_name, ctx->width, ctx->height, ctx->nb_nalus,
ctx->nb_i, ctx->nb_p, ctx->nb_b, ctx->nb_sei);
```

#### Potential Precision Problem\Path 8:

Severity Low  
Result State To Verify  
Online Results <http://WIN-PTJMSNK3USL/CxWebClient/ViewerMain.aspx?scanid=1000028&projectid=22&pathid=1005>  
Status New

The size of the buffer used by id3dmx\_flush in "tag\_%s", at line 225 of gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c, is not properly verified before writing data to the buffer. This can enable a buffer overflow attack, using the source buffer that id3dmx\_flush passes to "tag\_%s", at line 225 of gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c, to overwrite the target buffer.

	Source	Destination
File	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c	gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c
Line	326	326
Object	"tag_%s"	"tag_%s"

#### Code Snippet

File Name gpac@@gpac-v2.2.0-CVE-2023-3291-TP.c  
Method void id3dmx\_flush(GF\_Filter \*filter, u8 \*id3\_buf, u32 id3\_buf\_size, GF\_FilterPid \*audio\_pid, GF\_FilterPid \*\*video\_pid\_p)

```
....
326.          sprintf(szTag, "tag_%s", gf_4cc_to_str(ftag));
```

## Buffer Overflow StrcpyStrcat

### Risk

#### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
  - Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
  - Consistently apply tests for the size of buffers.
  - Do not return variable addresses outside the scope of their variables.
- 

## Source Code Examples

# Divide By Zero

## Risk

### What might happen

When a program divides a number by zero, an exception will be raised. If this exception is not handled by the application, unexpected results may occur, including crashing the application. This can be considered a DoS (Denial of Service) attack, if an external user has control of the value of the denominator or can cause this error to occur.

---

## Cause

### How does it happen

The program receives an unexpected value, and uses it for division without filtering, validation, or verifying that the value is not zero. The application does not explicitly handle this error or prevent division by zero from occurring.

---

## General Recommendations

### How to avoid it

- Before dividing by an unknown value, validate the number and explicitly ensure it does not evaluate to zero.
  - Validate all untrusted input from all sources, in particular verifying that it is not zero before dividing with it.
  - Verify output of methods, calculations, dictionary lookups, and so on, and ensure it is not zero before dividing with the result.
  - Ensure divide-by-zero errors are caught and handled appropriately.
- 

## Source Code Examples

### Java

#### Divide by Zero

```
public float getAverage(HttpServletRequest req) {  
    int total = Integer.parseInt(req.getParameter("total"));  
    int count = Integer.parseInt(req.getParameter("count"));  
  
    return total / count;  
}
```

#### Checked Division

```
public float getAverage(HttpServletRequest req) {  
    int total = Integer.parseInt(req.getParameter("total"));  
    int count = Integer.parseInt(req.getParameter("count"));
```



```
if (count > 0)
    return total / count;
else
    return 0;
}
```

# Buffer Overflow boundcpy WrongSizeParam

## Risk

### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

---

## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
  - Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
  - Consistently apply tests for the size of buffers.
  - Do not return variable addresses outside the scope of their variables.
- 

## Source Code Examples

### CPP

#### Overflowing Buffers

```
const int BUFFER_SIZE = 10;
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    strcpy(buffer, inputString);
}
```

#### Checked Buffers

```
const int BUFFER_SIZE = 10;
const int MAX_INPUT_SIZE = 256;
```

```
char buffer[BUFFER_SIZE];

void copyStringToBuffer(char* inputString)
{
    if (strlen(inputString, MAX_INPUT_SIZE) < sizeof(buffer))
    {
        strncpy(buffer, inputString, sizeof(buffer));
    }
}
```

# Buffer Overflow Loops

## Risk

### What might happen

An off by one error may result in overwriting or over-reading of unintended memory; in most cases, this can result in unexpected behavior and even application crashes. In other cases, where allocation can be controlled by an attacker, a combination of variable assignment and an off by one error can result in execution of malicious code.

---

## Cause

### How does it happen

Often when designating variables to memory, a calculation error may occur when determining size or length that is off by one.

For example in loops, when allocating an array of size 2, its cells are counted as 0,1 - therefore, if a For loop iterator on the array is incorrectly set with the start condition `i=0` and the continuation condition `i<=2`, three cells will be accessed instead of 2, and an attempt will be made to write or read cell [2], which was not originally allocated, resulting in potential corruption of memory outside the bounds of the originally assigned array.

Another example occurs when a null-byte terminated string, in the form of a character array, is copied without its terminating null-byte. Without the null-byte, the string representation is unterminated, resulting in certain functions to over-read memory as they expect the missing null terminator.

---

## General Recommendations

### How to avoid it

- Always ensure that a given iteration boundary is correct:
    - With array iterations, consider that arrays begin with cell 0 and end with cell `n-1`, for a size `n` array.
    - With character arrays and null-byte terminated string representations, consider that the null byte is required and should not be overwritten or ignored; ensure functions in use are not vulnerable to off-by-one, specifically for instances where null-bytes are automatically appended after the buffer, instead of in place of its last character.
  - Where possible, use safe functions that manage memory and are not prone to off-by-one errors.
- 

## Source Code Examples

### CPP

#### Off-By-One in For Loop

```
int *ptr;
ptr = (int*)malloc(5 * sizeof(int));
for (int i = 0; i <= 5; i++)
{
```

```
    ptr[i] = i * 2 + 1; // ptr[5] will be set, but is out of bounds  
}
```

### Proper Iteration in For Loop

```
int *ptr;  
ptr = (int*)malloc(5 * sizeof(int));  
for (int i = 0; i < 5; i++)  
{  
    ptr[i] = i * 2 + 1; // ptr[0-4] are well defined  
}
```

### Off-By-One in strncat

```
strncat(buf, input, sizeof(buf) - strlen(buf)); // actual value should be sizeof(buf)-  
strlen(buf)-1 - this form will overwrite the terminating nullbyte
```

# Dangerous Functions

## Risk

### What might happen

Use of dangerous functions may expose varying risks associated with each particular function, with potential impact of improper usage of these functions varying significantly. The presence of such functions indicates a flaw in code maintenance policies and adherence to secure coding practices, in a way that has allowed introducing known dangerous code into the application.

---

## Cause

### How does it happen

A dangerous function has been identified within the code. Functions are often deemed dangerous to use for numerous reasons, as there are different sets of vulnerabilities associated with usage of such functions. For example, some string copy and concatenation functions are vulnerable to Buffer Overflow, Memory Disclosure, Denial of Service and more. Use of these functions is not recommended.

---

## General Recommendations

### How to avoid it

- Deploy a secure and recommended alternative to any functions that were identified as dangerous.
    - If no secure alternative is found, conduct further researching and testing to identify whether current usage successfully sanitizes and verifies values, and thus successfully avoids the use-cases for whom the function is indeed dangerous
  - Conduct a periodical review of methods that are in use, to ensure that all external libraries and built-in functions are up-to-date and whose use has not been excluded from best secure coding practices.
- 

## Source Code Examples

### CPP

#### Buffer Overflow in gets()

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    gets(buf); // veryveryverylongname
    if (buf == ACCEPTED_NAME)
    {
        // Do something
    }
    return 0;
}
```

## Safe reading from user

```
int main()
{
    char buf[10];

    printf("Please enter your name: ");
    fgets(buf, sizeof(buf), stdin); //setting the amount of bytes to read
    if (buf == ACCEPTED_NAME)
    {
        //Do something
    }
    return 0;
}
```

## Unsafe function for string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strcpy(buf, argv[1]); // overflow occurs when len(argv[1]) > 10 bytes

    return 0;
}
```

## Safe string copy

```
int main(int argc, char* argv[])
{
    char buf[10];
    strncpy(buf, argv[1], sizeof(buf));
    buf[9] = '\0'; //strncpy doesn't NULL terminates

    return 0;
}
```

## Unsafe format string

```
int main(int argc, char* argv[])
{
    printf(argv[1]); // If argv[1] contains a format token, such as %s,%x or %d, will cause an access violation
    return 0;
}
```

## Safe format string

```
int main(int argc, char* argv[])
{
    printf("%s", argv[1]); // Second parameter is not a formattable string
    return 0;
}
```



# Use of Zero Initialized Pointer

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

# Unchecked Return Value

## Risk

### What might happen

A program that does not check function return values could cause the application to enter an undefined state. This could lead to unexpected behavior and unintended consequences, including inconsistent data, system crashes or other error-based exploits.

---

## Cause

### How does it happen

The application calls a system function, but does not receive or check the result of this function. These functions often return error codes in the result, or share other status codes with its caller. The application simply ignores this result value, losing this vital information.

---

## General Recommendations

### How to avoid it

- Always check the result of any called function that returns a value, and verify the result is an expected value.
  - Ensure the calling function responds to all possible return values.
  - Expect runtime errors and handle them gracefully. Explicitly define a mechanism for handling unexpected errors.
- 

## Source Code Examples

### CPP

#### Unchecked Memory Allocation

```
buff = (char*) malloc(size);  
strncpy(buff, source, size);
```

#### Safer Memory Allocation

```
buff = (char*) malloc(size+1);  
if (buff==NULL) exit(1);  
  
strncpy(buff, source, size);  
buff[size] = '\0';
```

# NULL Pointer Dereference

## Risk

### What might happen

A null pointer dereference is likely to cause a run-time exception, a crash, or other unexpected behavior.

---

## Cause

### How does it happen

Variables which are declared without being assigned will implicitly retain a null value until they are assigned. The null value can also be explicitly set to a variable, to ensure clear out its contents. Since null is not really a value, it may not have object variables and methods, and any attempt to access contents of a null object, instead of verifying it is set beforehand, will result in a null pointer dereference exception.

---

## General Recommendations

### How to avoid it

- For any variable that is created, ensure all logic flows between declaration and use assign a non-null value to the variable first.
  - Enforce null checks on any received variable or object before it is dereferenced, to ensure it does not contain a null assigned to it elsewhere.
  - Consider the need to assign null values in order to overwrite initialized variables. Consider reassigning or releasing these variables instead.
- 

## Source Code Examples

### CPP

#### Explicit NULL Dereference

```
char * input = NULL;
printf("%s", input);
```

#### Implicit NULL Dereference

```
char * input;
printf("%s", input);
```

### Java

#### Explicit Null Dereference

```
Object o = null;  
out.println(o.getClass());
```

# Potential Precision Problem

## Risk

### What might happen

Buffer overflow attacks, in their various forms, could allow an attacker to control certain areas of memory. Typically, this is used to overwrite data on the stack necessary for the program to function properly, such as code and memory addresses, though other forms of this attack exist. Exploiting this vulnerability can generally lead to system crashes, infinite loops, or even execution of arbitrary code.

---

## Cause

### How does it happen

Buffer Overflows can manifest in numerous different variations. In its most basic form, the attack controls a buffer, which is then copied to a smaller buffer without size verification. Because the attacker's source buffer is larger than the program's target buffer, the attacker's data overwrites whatever is next on the stack, allowing the attacker to control program structures.

Alternatively, the vulnerability could be the result of improper bounds checking; exposing internal memory addresses outside of their valid scope; allowing the attacker to control the size of the target buffer; or various other forms.

---

## General Recommendations

### How to avoid it

- Always perform proper bounds checking before copying buffers or strings.
  - Prefer to use safer functions and structures, e.g. safe string classes over `char*`, `strncpy` over `strcpy`, and so on.
  - Consistently apply tests for the size of buffers.
  - Do not return variable addresses outside the scope of their variables.
- 

## Source Code Examples

## Improper Validation of Array Index

**Weakness ID:** 129 (*Weakness Base*)

**Status:** Draft

### Description

### Description Summary

The product uses untrusted input when calculating or using an array index, but the product does not validate or incorrectly validates the index to ensure the index references a valid position within the array.

### Alternate Terms

out-of-bounds array index

index-out-of-range

array index underflow

### Time of Introduction

### Implementation

### Applicable Platforms

### Languages

C: (*Often*)

C++: (*Often*)

### Language-independent

### Common Consequences

Scope	Effect
Integrity Availability	Unchecked array indexing will very likely result in the corruption of relevant memory and perhaps instructions, leading to a crash, if the values are outside of the valid memory area.
Integrity	If the memory corrupted is data, rather than instructions, the system will continue to function with improper values.
Confidentiality Integrity	Unchecked array indexing can also trigger out-of-bounds read or write operations, or operations on the wrong objects; i.e., "buffer overflows" are not always the result. This may result in the exposure or modification of sensitive data.
Integrity	If the memory accessible by the attacker can be effectively controlled, it may be possible to execute arbitrary code, as with a standard buffer overflow and possibly without the use of large inputs if a precise index can be controlled.
Integrity Availability Confidentiality	A single fault could allow either an overflow (CWE-788) or underflow (CWE-786) of the array index. What happens next will depend on the type of operation being performed out of bounds, but can expose sensitive information, cause a system crash, or possibly lead to arbitrary code execution.

### Likelihood of Exploit

High

### Detection Methods

#### Automated Static Analysis

This weakness can often be detected using automated static analysis tools. Many modern tools use data flow analysis or constraint-based techniques to minimize the number of false positives.

Automated static analysis generally does not account for environmental considerations when reporting out-of-bounds memory operations. This can make it difficult for users to determine which warnings should be investigated first. For example, an analysis tool might report array index errors that originate from command line arguments in a program that is not expected to run with setuid or other special privileges.

**Effectiveness: High**

This is not a perfect solution, since 100% accuracy and coverage are not feasible.

---

### Automated Dynamic Analysis

This weakness can be detected using dynamic tools and techniques that interact with the software using large test suites with many diverse inputs, such as fuzz testing (fuzzing), robustness testing, and fault injection. The software's operation may slow down, but it should not become unstable, crash, or generate incorrect results.

---

### Black Box

Black box methods might not get the needed code coverage within limited time constraints, and a dynamic test might not produce any noticeable side effects even if it is successful.

---

## Demonstrative Examples

### Example 1

The following C/C++ example retrieves the sizes of messages for a pop3 mail server. The message sizes are retrieved from a socket that returns in a buffer the message number and the message size, the message number (num) and size (size) are extracted from the buffer and the message size is placed into an array using the message number for the array index.

*(Bad Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
...
char buf[BUFFER_SIZE];
int ok;
int num, size;

// read values from socket and added to sizes array
while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
{

// continue read from socket until buf only contains '.'
if (DOTLINE(buf))
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2)
sizes[num - 1] = size;
}
...
}
```

In this example the message number retrieved from the buffer could be a value that is outside the allowable range of indices for the array and could possibly be a negative number. Without proper validation of the value to be used for the array index an array overflow could occur and could potentially lead to unauthorized access to memory addresses and system crashes. The value of the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

*Example Language: C*

```
/* capture the sizes of all messages */
int getsizes(int sock, int count, int *sizes) {
...
char buf[BUFFER_SIZE];
int ok;
int num, size;

// read values from socket and added to sizes array
while ((ok = gen_recv(sock, buf, sizeof(buf))) == 0)
{

// continue read from socket until buf only contains '.'
if (DOTLINE(buf))
```

```
break;
else if (sscanf(buf, "%d %d", &num, &size) == 2) {
if (num > 0 && num <= (unsigned)count)
sizes[num - 1] = size;
else
/* warn about possible attempt to induce buffer overflow */
report(stderr, "Warning: ignoring bogus data for message sizes returned by server.\n");
}
}
...
}
```

## Example 2

In the code snippet below, an unchecked integer value is used to reference an object in an array.

*(Bad Code)*

**Example Language: Java**

```
public String getValue(int index) {
return array[index];
}
```

If index is outside of the range of the array, this may result in an `ArrayIndexOutOfBoundsException` Exception being raised.

## Example 3

In the following Java example the method `displayProductSummary` is called from a Web service servlet to retrieve product summary information for display to the user. The servlet obtains the integer value of the product number from the user and passes it to the `displayProductSummary` method. The `displayProductSummary` method passes the integer value of the product number to the `getProductSummary` method which obtains the product summary from the array object containing the project summaries using the integer value of the product number as the array index.

*(Bad Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");

try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
return products[index];
}
```

In this example the integer value used as the array index that is provided by the user may be outside the allowable range of indices for the array which may provide unexpected results or may cause the application to fail. The integer value used for the array index should be validated to ensure that it is within the allowable range of indices for the array as in the following code.

*(Good Code)*

**Example Language: Java**

*// Method called from servlet to obtain product information*

```
public String displayProductSummary(int index) {

String productSummary = new String("");
```



```
try {
String productSummary = getProductSummary(index);

} catch (Exception ex) {...}

return productSummary;
}

public String getProductSummary(int index) {
String productSummary = "";

if ((index >= 0) && (index < MAX_PRODUCTS)) {
productSummary = products[index];
}
else {
System.err.println("index is out of bounds");
throw new IndexOutOfBoundsException();
}

return productSummary;
}
```

An alternative in Java would be to use one of the collection objects such as ArrayList that will automatically generate an exception if an attempt is made to access an array index that is out of bounds.

*(Good Code)*

#### Example Language: Java

```
ArrayList productArray = new ArrayList(MAX_PRODUCTS);
...
try {
productSummary = (String) productArray.get(index);
} catch (IndexOutOfBoundsException ex) {...}
```

### Observed Examples

Reference	Description
<a href="#">CVE-2005-0369</a>	large ID in packet used as array index
<a href="#">CVE-2001-1009</a>	negative array index as argument to POP LIST command
<a href="#">CVE-2003-0721</a>	Integer signedness error leads to negative array index
<a href="#">CVE-2004-1189</a>	product does not properly track a count and a maximum number, which can lead to resultant array index overflow.
<a href="#">CVE-2007-5756</a>	chain: device driver for packet-capturing software allows access to an unintended IOCTL with resultant array index error.

### Potential Mitigations

#### Phase: Architecture and Design

### Strategies: Input Validation; Libraries or Frameworks

Use an input validation framework such as Struts or the OWASP ESAPI Validation API. If you use Struts, be mindful of weaknesses covered by the CWE-101 category.

#### Phase: Architecture and Design

For any security checks that are performed on the client side, ensure that these checks are duplicated on the server side, in order to avoid CWE-602. Attackers can bypass the client-side checks by modifying values after the checks have been performed, or by changing the client to remove the client-side checks entirely. Then, these modified values would be submitted to the server.

Even though client-side checks provide minimal benefits with respect to server-side security, they are still useful. First, they can support intrusion detection. If the server receives input that should have been rejected by the client, then it may be an indication of an attack. Second, client-side error-checking can provide helpful feedback to the user about the expectations for valid input. Third, there may be a reduction in server-side processing time for accidental input errors, although this is typically a small savings.

#### Phase: Requirements

### Strategy: Language Selection

Use a language with features that can automatically mitigate or eliminate out-of-bounds indexing errors.

For example, Ada allows the programmer to constrain the values of a variable and languages such as Java and Ruby will allow the programmer to handle exceptions when an out-of-bounds index is accessed.

#### Phase: Implementation

### Strategy: Input Validation

Assume all input is malicious. Use an "accept known good" input validation strategy (i.e., use a whitelist). Reject any input that does not strictly conform to specifications, or transform it into something that does. Use a blacklist to reject any unexpected inputs and detect potential attacks.

When accessing a user-controlled array index, use a stringent range of values that are within the target array. Make sure that you do not allow negative values to be used. That is, verify the minimum as well as the maximum of the range of acceptable values.

#### Phase: Implementation

Be especially careful to validate your input when you invoke code that crosses language boundaries, such as from an interpreted language to native code. This could create an unexpected interaction between the language boundaries. Ensure that you are not violating any of the expectations of the language with which you are interfacing. For example, even though Java may not be susceptible to buffer overflows, providing a large argument in a call to native code might trigger an overflow.

### Weakness Ordinalities

Ordinality	Description
Resultant	The most common condition situation leading to unchecked array indexing is the use of loop index variables as buffer indexes. If the end condition for the loop is subject to a flaw, the index can grow or shrink unbounded, therefore causing a buffer overflow or underflow. Another common situation leading to this condition is the use of a function's return value, or the resulting value of a calculation directly as an index in to a buffer.

### Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Weakness Class	20	<a href="#">Improper Input Validation</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	189	<a href="#">Numeric Errors</a>	Development Concepts699
ChildOf	Category	633	<a href="#">Weaknesses that Affect Memory</a>	<b>Resource-specific Weaknesses (primary)631</b>
ChildOf	Category	738	<a href="#">CERT C Secure Coding Section 04 - Integers (INT)</a>	<b>Weaknesses Addressed by the CERT C Secure Coding Standard (primary)734</b>
ChildOf	Category	740	<a href="#">CERT C Secure Coding Section 06 - Arrays (ARR)</a>	Weaknesses Addressed by the CERT C Secure Coding Standard734
ChildOf	Category	802	<a href="#">2010 Top 25 - Risky Resource Management</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
CanPrecede	Weakness Class	119	<a href="#">Failure to Constrain Operations within the Bounds of a Memory Buffer</a>	Research Concepts1000
CanPrecede	Weakness Variant	789	<a href="#">Uncontrolled Memory Allocation</a>	Research Concepts1000
PeerOf	Weakness Base	124	<a href="#">Buffer Underwrite ('Buffer Underflow')</a>	Research Concepts1000

### Theoretical Notes

An improperly validated array index might lead directly to the always-incorrect behavior of "access of array using out-of-bounds index."

### Affected Resources

## Memory

### f Causal Nature

### Explicit

### Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
CLASP			Unchecked array indexing
PLOVER			INDEX - Array index overflow
CERT C Secure Coding	ARR00-C		Understand how arrays work
CERT C Secure Coding	ARR30-C		Guarantee that array indices are within the valid range
CERT C Secure Coding	ARR38-C		Do not add or subtract an integer to a pointer if the resulting value does not refer to a valid array element
CERT C Secure Coding	INT32-C		Ensure that operations on signed integers do not result in overflow

### Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">100</a>	Overflow Buffers	

### References

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 5, "Array Indexing Errors" Page 144. 2nd Edition. Microsoft. 2002.

### Content History

Submissions			
Submission Date	Submitter	Organization	Source
	CLASP		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Sean Eidemiller	Cigital	External
	added/updated demonstrative examples		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Applicable Platforms, Common Consequences, Relationships, Other Notes, Taxonomy Mappings, Weakness Ordinalities		
2008-11-24	CWE Content Team	MITRE	Internal
	updated Relationships, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Description, Name, Relationships		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Observed Examples, Other Notes, Potential Mitigations, Theoretical Notes, Weakness Ordinalities		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Demonstrative Examples, Detection Factors, Likelihood of Exploit, Potential Mitigations, References, Related Attack Patterns, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Related Attack Patterns		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-10-29	Unchecked Array Indexing		

[BACK TO TOP](#)

**Improper Access Control (Authorization)****Weakness ID:** 285 (*Weakness Class*)**Status:** Draft**Description****Description Summary**

The software does not perform or incorrectly performs access control checks across all potential execution paths.

**Extended Description**

When access control checks are not applied consistently - or not at all - users are able to access data or perform actions that they should not be allowed to perform. This can lead to a wide range of problems, including information leaks, denial of service, and arbitrary code execution.

**Alternate Terms****AuthZ:**

"AuthZ" is typically used as an abbreviation of "authorization" within the web application security community. It is also distinct from "AuthC," which is an abbreviation of "authentication." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

**Time of Introduction**

- Architecture and Design
- Implementation
- Operation

**Applicable Platforms****Languages**

Language-independent

**Technology Classes**

Web-Server: (*Often*)

Database-Server: (*Often*)

**Modes of Introduction**

A developer may introduce authorization weaknesses because of a lack of understanding about the underlying technologies. For example, a developer may assume that attackers cannot modify certain inputs such as headers or cookies.

Authorization weaknesses may arise when a single-user application is ported to a multi-user environment.

**Common Consequences**

Scope	Effect
Confidentiality	An attacker could read sensitive data, either by reading the data directly from a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to read the data.
Integrity	An attacker could modify sensitive data, either by writing the data directly to a data store that is not properly restricted, or by accessing insufficiently-protected, privileged functionality to write the data.
Integrity	An attacker could gain privileges by modifying or reading critical data directly, or by accessing insufficiently-protected, privileged functionality.

**Likelihood of Exploit**

High

**Detection Methods**

### Automated Static Analysis

Automated static analysis is useful for detecting commonly-used idioms for authorization. A tool may be able to analyze related configuration files, such as .htaccess in Apache web servers, or detect the usage of commonly-used authorization libraries.

Generally, automated static analysis tools have difficulty detecting custom authorization schemes. In addition, the software's design may include some functionality that is accessible to any user and does not require an authorization check; an automated technique that detects the absence of authorization may report false positives.

### **Effectiveness: Limited**

---

### Automated Dynamic Analysis

Automated dynamic analysis may find many or all possible interfaces that do not require authorization, but manual analysis is required to determine if the lack of authorization violates business logic

---

### Manual Analysis

This weakness can be detected using tools and techniques that require manual (human) analysis, such as penetration testing, threat modeling, and interactive tools that allow the tester to record and modify an active session.

Specifically, manual static analysis is useful for evaluating the correctness of custom authorization mechanisms.

### **Effectiveness: Moderate**

These may be more effective than strictly automated techniques. This is especially the case with weaknesses that are related to design and business rules. However, manual efforts might not achieve desired code coverage within limited time constraints.

---

## Demonstrative Examples

### Example 1

The following program could be part of a bulletin board system that allows users to send private messages to each other. This program intends to authenticate the user before deciding whether a private message should be displayed. Assume that `LookupMessageObject()` ensures that the `$id` argument is numeric, constructs a filename based on that id, and reads the message details from that file. Also assume that the program stores all private messages for all users in the same directory.

*(Bad Code)*

#### *Example Language: Perl*

```
sub DisplayPrivateMessage {
my($id) = @_ ;
my $Message = LookupMessageObject($id);
print "From: " . encodeHTML($Message->{from}) . "<br>\n";
print "Subject: " . encodeHTML($Message->{subject}) . "\n";
print "<hr>\n";
print "Body: " . encodeHTML($Message->{body}) . "\n";
}

my $q = new CGI;
# For purposes of this example, assume that CWE-309 and
# CWE-523 do not apply.
if (! AuthenticateUser($q->param('username'), $q->param('password'))) {
ExitError("invalid username or password");
}

my $id = $q->param('id');
DisplayPrivateMessage($id);
```

While the program properly exits if authentication fails, it does not ensure that the message is addressed to the user. As a result, an authenticated attacker could provide any arbitrary identifier and read private messages that were intended for other users. One way to avoid this problem would be to ensure that the "to" field in the message object matches the username of the authenticated user.

## Observed Examples

Reference	Description
<a href="#">CVE-2009-3168</a>	Web application does not restrict access to admin scripts, allowing authenticated users to reset administrative passwords.

<a href="#">CVE-2009-2960</a>	Web application does not restrict access to admin scripts, allowing authenticated users to modify passwords of other users.
<a href="#">CVE-2009-3597</a>	Web application stores database file under the web root with insufficient access control (CWE-219), allowing direct request.
<a href="#">CVE-2009-2282</a>	Terminal server does not check authorization for guest access.
<a href="#">CVE-2009-3230</a>	Database server does not use appropriate privileges for certain sensitive operations.
<a href="#">CVE-2009-2213</a>	Gateway uses default "Allow" configuration for its authorization settings.
<a href="#">CVE-2009-0034</a>	Chain: product does not properly interpret a configuration option for a system group, allowing users to gain privileges.
<a href="#">CVE-2008-6123</a>	Chain: SNMP product does not properly parse a configuration option for which hosts are allowed to connect, allowing unauthorized IP addresses to connect.
<a href="#">CVE-2008-5027</a>	System monitoring software allows users to bypass authorization by creating custom forms.
<a href="#">CVE-2008-7109</a>	Chain: reliance on client-side security (CWE-602) allows attackers to bypass authorization using a custom client.
<a href="#">CVE-2008-3424</a>	Chain: product does not properly handle wildcards in an authorization policy list, allowing unintended access.
<a href="#">CVE-2009-3781</a>	Content management system does not check access permissions for private files, allowing others to view those files.
<a href="#">CVE-2008-4577</a>	ACL-based protection mechanism treats negative access rights as if they are positive, allowing bypass of intended restrictions.
<a href="#">CVE-2008-6548</a>	Product does not check the ACL of a page accessed using an "include" directive, allowing attackers to read unauthorized files.
<a href="#">CVE-2007-2925</a>	Default ACL list for a DNS server does not set certain ACLs, allowing unauthorized DNS queries.
<a href="#">CVE-2006-6679</a>	Product relies on the X-Forwarded-For HTTP header for authorization, allowing unintended access by spoofing the header.
<a href="#">CVE-2005-3623</a>	OS kernel does not check for a certain privilege before setting ACLs for files.
<a href="#">CVE-2005-2801</a>	Chain: file-system code performs an incorrect comparison (CWE-697), preventing defaults ACLs from being properly applied.
<a href="#">CVE-2001-1155</a>	Chain: product does not properly check the result of a reverse DNS lookup because of operator precedence (CWE-783), allowing bypass of DNS-based access restrictions.

## Potential Mitigations

### Phase: Architecture and Design

Divide your application into anonymous, normal, privileged, and administrative areas. Reduce the attack surface by carefully mapping roles with data and functionality. Use role-based access control (RBAC) to enforce the roles at the appropriate boundaries.

Note that this approach may not protect against horizontal authorization, i.e., it will not protect a user from attacking others with the same role.

### Phase: Architecture and Design

Ensure that you perform access control checks related to your business logic. These checks may be different than the access control checks that you apply to more generic resources such as files, connections, processes, memory, and database records. For example, a database may restrict access for medical records to a specific database user, but each record might only be intended to be accessible to the patient and the patient's doctor.

### Phase: Architecture and Design

## Strategy: Libraries or Frameworks

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness

easier to avoid.

For example, consider using authorization frameworks such as the JAAS Authorization Framework and the OWASP ESAPI Access Control feature.

### Phase: Architecture and Design

For web applications, make sure that the access control mechanism is enforced correctly at the server side on every page. Users should not be able to access any unauthorized functionality or information by simply requesting direct access to that page.

One way to do this is to ensure that all pages containing sensitive information are not cached, and that all such pages restrict access to requests that are accompanied by an active and authenticated session token associated with a user who has the required permissions to access that page.

### Phases: System Configuration; Installation

Use the access control capabilities of your operating system and server environment and define your access control lists accordingly. Use a "default deny" policy when defining these ACLs.

## Relationships

Nature	Type	ID	Name	View(s) this relationship pertains to
ChildOf	Category	254	<a href="#">Security Features</a>	<b>Seven Pernicious Kingdoms (primary)700</b>
ChildOf	Weakness Class	284	<a href="#">Access Control (Authorization) Issues</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>
ChildOf	Category	721	<a href="#">OWASP Top Ten 2007 Category A10 - Failure to Restrict URL Access</a>	<b>Weaknesses in OWASP Top Ten (2007) (primary)629</b>
ChildOf	Category	723	<a href="#">OWASP Top Ten 2004 Category A2 - Broken Access Control</a>	<b>Weaknesses in OWASP Top Ten (2004) (primary)711</b>
ChildOf	Category	753	<a href="#">2009 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2009 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)750</b>
ChildOf	Category	803	<a href="#">2010 Top 25 - Porous Defenses</a>	<b>Weaknesses in the 2010 CWE/SANS Top 25 Most Dangerous Programming Errors (primary)800</b>
ParentOf	Weakness Variant	219	<a href="#">Sensitive Data Under Web Root</a>	<b>Research Concepts (primary)1000</b>
ParentOf	Weakness Base	551	<a href="#">Incorrect Behavior Order: Authorization Before Parsing and Canonicalization</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts1000</b>
ParentOf	Weakness Class	638	<a href="#">Failure to Use Complete Mediation</a>	<b>Research Concepts1000</b>
ParentOf	Weakness Base	804	<a href="#">Guessable CAPTCHA</a>	<b>Development Concepts (primary)699</b> <b>Research Concepts (primary)1000</b>

## Taxonomy Mappings

Mapped Taxonomy Name	Node ID	Fit	Mapped Node Name
7 Pernicious Kingdoms			Missing Access Control
OWASP Top Ten 2007	A10	CWE More Specific	Failure to Restrict URL Access
OWASP Top Ten 2004	A2	CWE More Specific	Broken Access Control

## Related Attack Patterns

CAPEC-ID	Attack Pattern Name	(CAPEC Version: 1.5)
<a href="#">1</a>	Accessing Functionality Not Properly Constrained by ACLs	
<a href="#">13</a>	Subverting Environment Variable Values	

<a href="#">17</a>	Accessing, Modifying or Executing Executable Files
<a href="#">87</a>	Forceful Browsing
<a href="#">39</a>	Manipulating Opaque Client-based Data Tokens
<a href="#">45</a>	Buffer Overflow via Symbolic Links
<a href="#">51</a>	Poison Web Service Registry
<a href="#">59</a>	Session Credential Falsification through Prediction
<a href="#">60</a>	Reusing Session IDs (aka Session Replay)
<a href="#">77</a>	Manipulating User-Controlled Variables
<a href="#">76</a>	Manipulating Input to File System Calls
<a href="#">104</a>	Cross Zone Scripting

## References

NIST. "Role Based Access Control and Role Based Security". <<http://csrc.nist.gov/groups/SNS/rbac/>>.

[REF-11] M. Howard and D. LeBlanc. "Writing Secure Code". Chapter 4, "Authorization" Page 114; Chapter 6, "Determining Appropriate Access Control" Page 171. 2nd Edition. Microsoft. 2002.

## Content History

Submissions			
Submission Date	Submitter	Organization	Source
	7 Pernicious Kingdoms		Externally Mined
Modifications			
Modification Date	Modifier	Organization	Source
2008-07-01	Eric Dalci	Cigital	External
	updated Time of Introduction		
2008-08-15		Veracode	External
	Suggested OWASP Top Ten 2004 mapping		
2008-09-08	CWE Content Team	MITRE	Internal
	updated Relationships, Other Notes, Taxonomy Mappings		
2009-01-12	CWE Content Team	MITRE	Internal
	updated Common Consequences, Description, Likelihood of Exploit, Name, Other Notes, Potential Mitigations, References, Relationships		
2009-03-10	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
2009-05-27	CWE Content Team	MITRE	Internal
	updated Description, Related Attack Patterns		
2009-07-27	CWE Content Team	MITRE	Internal
	updated Relationships		
2009-10-29	CWE Content Team	MITRE	Internal
	updated Type		
2009-12-28	CWE Content Team	MITRE	Internal
	updated Applicable Platforms, Common Consequences, Demonstrative Examples, Detection Factors, Modes of Introduction, Observed Examples, Relationships		
2010-02-16	CWE Content Team	MITRE	Internal
	updated Alternate Terms, Detection Factors, Potential Mitigations, References, Relationships		
2010-04-05	CWE Content Team	MITRE	Internal
	updated Potential Mitigations		
Previous Entry Names			
Change Date	Previous Entry Name		
2009-01-12	Missing or Inconsistent Access Control		

[BACK TO TOP](#)



## Scanned Languages

Language	Hash Number	Change Date
CPP	4541647240435660	1/6/2025
Common	0105849645654507	1/6/2025