PJ01_Romberg

November 11, 2018


```
In [1]: %matplotlib inline
    import numpy as np
    import matplotlib.pyplot as plt
    from math import *

In [2]: def f(x):
        if x==0:
            return 0
        else:
            return sqrt(x)*log(x)


In [3]: x = np.linspace(0,1,1000)

In [4]: plt.plot(x, [f(i) for i in x])
        plt.xlabel("x")
        plt.ylabel("f(x)")

Out [4]: Text(0,0.5,'f(x)')
```



```
In [38]: h=1
         r=h/2*(f(1)+f(0))
         k=np.arange(1,11)
         H=np.zeros_like(k, dtype=float)
         ans=np.zeros_like(k, dtype=float)
         y0=np.zeros_like(k, dtype=float)
         y=np.zeros_like(k, dtype=float)
         y0[0]=r
         H[0]=h
In [40]: for i in range(1,len(k)):
             n = k[i]
             X = 0
             for j in range(1,2**(n-2)+1):
                 X += f((j-0.5)*h)
             y[0]=0.5*(y0[0]+X*h)
             for j in range(2, n+1):
                 y[j-1]=y[j-2]+(y[j-2]-y0[j-1])/(pow(4,j-1)-1)
             h*=0.5
             for j in range(n):
                 y0[j]=y[j]
                 y[j]=0
             H[i]=h
             ans[i]=y0[n-1]
In [41]: plt.plot(k,ans)
         plt.xlabel("k")
         plt.ylabel("ans")
Out[41]: Text(0,0.5,'ans')
```



Out[42]: Text(0,0.5,'error')

