



Running Simulations with OpenMM

Peter Eastman

OpenMM Workshop, March 26, 2013



OpenMM is...

- A. An application for running molecular simulations
- B. A library of simulation routines for use by applications
- C. A domain specific language for molecular simulation
- D. All of the above

What is OpenMM?


- A toolkit for high performance molecular simulations
 - A low level computational library (C++)
 - A high level application layer (Python)
- Supports GPUs (NVIDIA and AMD) and CPUs
 - Computations implemented in OpenCL and CUDA

User Types



Biologists/Chemists: Use the application layer to run simulations

Application Developers: Use the computational library to add simulation features to their programs



Algorithm Developers: Use Python, C++, custom forces to implement new algorithms within the application layer

Running Simulations

- The “application layer” is really a set of Python libraries
- You write a Python script to run a simulation



*No programming
experience required!*

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Example Script

```
from simtk.openmm.app import *  
from simtk.openmm import *  
from simtk.unit import *
```

```
pdb = PDBFile('input.pdb')  
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')  
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,  
    nonbondedCutoff=1*nanometer, constraints=HBonds)  
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,  
    0.002*picoseconds)  
simulation = Simulation(pdb.topology, system, integrator)  
simulation.context.setPositions(pdb.positions)  
simulation.minimizeEnergy()  
simulation.reporters.append(PDBReporter('output.pdb', 1000))  
simulation.step(10000)
```

Tell Python about the OpenMM libraries we'll be using

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Load the PDB file

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Select the force field to use

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Construct the system to simulate

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Select the integration method and parameters

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Let's do a simulation!

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Set the initial atom positions

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Better run an energy minimization first

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Save a frame to a PDB file every 1000 steps

Example Script

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

pdb = PDBFile('input.pdb')
forcefield = ForceField('amber99sb.xml', 'tip3p.xml')
system = forcefield.createSystem(pdb.topology, nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(pdb.topology, system, integrator)
simulation.context.setPositions(pdb.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Simulate!

Starting from AMBER Files

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

prmtop = AmberPrmtopFile('input.prmtop')
inpcrd = AmberInpcrdFile('input.inpcrd')
system = prmtop.createSystem(nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(prmtop.topology, system, integrator)
simulation.context.setPositions(inpcrd.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```

Starting from AMBER Files

```
from simtk.openmm.app import *
from simtk.openmm import *
from simtk.unit import *

prmtop = AmberPrmtopFile('input.prmtop')
inpcrd = AmberInpcrdFile('input.inpcrd')
system = prmtop.createSystem(nonbondedMethod=PME,
    nonbondedCutoff=1*nanometer, constraints=HBonds)
integrator = LangevinIntegrator(300*kelvin, 1/picosecond,
    0.002*picoseconds)
simulation = Simulation(prmtop.topology, system, integrator)
simulation.context.setPositions(inpcrd.positions)
simulation.minimizeEnergy()
simulation.reporters.append(PDBReporter('output.pdb', 1000))
simulation.step(10000)
```