

	SECTION:	DOC REF / ID: AG 0001
--	-------------------	--------------------------

PORTABLE ANGLE GRINDER (4" / 7") PRE-USE CHECKLIST

DATE:	TIME:	GRINDER ASSET NO / ID:	GRINDER SPECIFICATION: ☐ 4" (100mm) ☐ 7" (180mm)
----------------	----------------	---------------------------------	---

NO.	COMPONENT / INSPECTION STANDARD	OK	NOT OK	COMMENTS / IDENTIFIED DEFECTS
1	Power Cable & Plug Inspect for exposed conductors, damaged insulation, loose fittings, or taped sections. Verify plug body and earth pin integrity.			
2	Trigger Switch & Dead-Man Lock Verify trigger returns fully to OFF position and lock-off mechanism prevents accidental activation.			
3	Structural Safety Guard Ensure guard is fitted securely, free from cracks, and positioned correctly to deflect sparks and debris.			
4	Auxiliary Side Handle Confirm handle is firmly installed and threads are not stripped or damaged.			
5	Clamping Flanges & Locking Nut Inspect flanges and locking nut for wear, distortion, or damage. Ensure proper fitment with abrasive disc.			
6	Abrasive Disc Integrity Inspect disc for cracks, chips, delamination, flat spots, or contamination. Remove defective discs from service immediately.			
7	Disc Velocity Compatibility (RPM) Verify disc maximum RPM rating is equal to or greater than grinder operating speed.			
8	Main Housing & Cooling Vents Inspect housing for cracks or structural damage. Ensure ventilation openings are free from dust and debris.			
9	Spindle / Mandrel Tightness Verify disc assembly is securely tightened using the correct spanner or manufacturer-approved method.			
10	Mandatory PPE Confirm availability and use of face shield, safety goggles, gloves, hearing protection, face mask, and protective clothing.			

CRITICAL OPERATIONAL POLICY: IF ANY ITEM IS IDENTIFIED AS NOT OK, DISCONTINUE USE IMMEDIATELY, ISOLATE THE EQUIPMENT, TAG IF REQUIRED, AND NOTIFY THE RESPONSIBLE SUPERVISOR.

ARTISAN / OPERATOR NAME	SIGNATURE	DATE	SHIFT
SUPERVISOR NAME	SIGNATURE	DATE	SHIFT

THIS PRE-USE CHECKLIST MUST BE FILLED IN FULLY AND SUBMITTED DIRECTLY TO THE SUPERVISOR