

CZ2007 LAB 3

INTRODUCTION TO DATABASE

Zou Zeren U2022422H
Zeng Xunyi U2022509A
Tan Pei Lun U2022841A
Bryan Chatsirichai U2022154D
Mulder Choo U2022324D

Contents

1	CREDIT_CARD	3
2	CUSTOMER	3
3	ORDER	5
4	ORDER_ITEM	5
5	PRODUCT_TYPE	5
6	RESTRICTED_TO	6
7	SHIPMENT	6
8	INVOICE	6
9	PAYMENT	7
10	PRODUCT	7
11	PHOTOS	7
12	SHOP	8
13	ERD REFERENCE	9

1 CREDIT_CARD

CREDIT_CARD (card_num, bank, date_valid_to, date_valid_from, customer_id)

Keys: card_num

Primary Key: card_num

FDs: $\text{card_num} \rightarrow \text{bank}, \text{date_valid_to}, \text{date_valid_from}, \text{customer_id}$

All the attributes are functionally dependent on solely the Primary Key (card_num)

LHS is a key

\therefore The relation is in 3NF

2 CUSTOMER

CUSTOMER (customer_id, username, email, password, full_name, address, phone_num)

Keys: customer_id, username, email

Primary Key: customer_id

FDs:

$\text{customer_id} \rightarrow \text{username}, \text{email}, \text{password}, \text{full_name}, \text{address}, \text{phone_num}$

$\text{username} \rightarrow \text{customer_id}, \text{email}, \text{password}, \text{full_name}, \text{address}, \text{phone_num}$

$\text{email} \rightarrow \text{username}, \text{customer_id}, \text{password}, \text{full_name}, \text{address}, \text{phone_num}$

$\text{phone_num} \rightarrow \text{full_name}, \text{address}$

\therefore The relation is **not** in 3NF

3NF Procedures:

Minimal Basis for R:

CUSTOMER (customer_id(A), username(B), email(C), password(D), full_name(E),
address(F), phone_num(G))

= CUSTOMER(A,B,C,D,E,F,G)

KEYS: A,B,C

FDS: $A \rightarrow BCDEFG, B \rightarrow ACDEFG, C \rightarrow BADEFG$
 $, G \rightarrow EF$

STEP 1.1: (Keep RHS only 1 attribute):

$A \rightarrow B, A \rightarrow C, A \rightarrow D, A \rightarrow E, A \rightarrow F, A \rightarrow G$

$B \rightarrow A, B \rightarrow C, B \rightarrow D, B \rightarrow E, B \rightarrow F, B \rightarrow G$

$C \rightarrow A, C \rightarrow B, C \rightarrow D, C \rightarrow E, C \rightarrow F, C \rightarrow G$

$G \rightarrow E, G \rightarrow F$

STEP 1.2: (Remove redundant FD):

Original closures:

$\{A\}^+ = \{ABCDEFGG\}, \quad \{B\}^+ = \{ACDEFG\}, \quad \{C\}^+ = \{BADEFG\},$
 $\{G\}^+ = \{EF\}$

we remove $A \rightarrow E, A \rightarrow F$ $\{A\}^+ = \{ABCDEFGG\}$

we remove $B \rightarrow C, B \rightarrow D, B \rightarrow E, B \rightarrow F, B \rightarrow G$ $\{B\}^+ = \{ACDEFG\}$

we remove $C \rightarrow B, C \rightarrow D, C \rightarrow E, C \rightarrow F, C \rightarrow G$ $\{C\}^+ = \{BADEFG\}$

CUSTOMER = { $A \rightarrow B, A \rightarrow C, A \rightarrow D, A \rightarrow G, G \rightarrow E, G \rightarrow F, B \rightarrow A, C \rightarrow A$ }

STEP 1.3: (Remove redundant attributes on LHS):

CUSTOMER = { $A \rightarrow B, A \rightarrow C, A \rightarrow D, A \rightarrow G, G \rightarrow E, G \rightarrow F, B \rightarrow A, C \rightarrow A$ }

Step 2: (Combine FDs whose LHS are same:)

CUSTOMER = { $A \rightarrow BCDG, G \rightarrow EF, B \rightarrow A, C \rightarrow A$ }

Step 3: (Create a table for each FD:)

$R_1 (ABCDG) = R_1 (\text{customer_id, username, email, password, phone_num})$

$R_2 (BA) = R_2 (\text{customer_id, username})$

$R_3 (CA) = R_3 (\text{customer_id, email})$

$R_4 (GEF) = R_4 (\text{phone_num, full_name, address})$

Step 4: (If non of the tables contain a key of the original table R,
create a table that contains a key of R:)

R_1 contains all keys. Do not need to create new table

Step 5: (Remove redundant tables:)

R_2 & R_3 is a sub set of R_1 so we remove them

Final Answer

$R_1 (\text{customer_id, username, email, password, phone_num}) \quad R_4 (\text{phone_num, full_name, address})$

\therefore The relation is in 3NF

3 ORDER

ORDER (order_id, date, status, customer_id)

Keys: order_id

Primary Key: order_id

FDs: order_id \rightarrow date, status, customer_id

All the attributes are functionally dependent on solely the Primary Key (order_id)

LHS is a key

\therefore The relation is in 3NF

4 ORDER_ITEM

ORDER_ITEM (sequence_num, order_id, product_unit_price, quantity, status, product_id, shipment_id)

Keys: {sequence_num, order_id}

Primary Key: {sequence_num, order_id}

FDs: sequence_num, order_id \rightarrow product_unit_price, quantity, status, product_id, shipment_id

All the attributes are functionally dependent on solely the
Primary Key {sequence_num, order_id}

LHS is a key

\therefore The relation is in 3NF

5 PRODUCT_TYPE

PRODUCT_TYPE (product_type_id, description, parent_product_type_id)

Keys: product_type_id

Primary Key: product_type_id

FDs: product_type_id \rightarrow description, parent_product_type_id

All the attributes are functionally dependent on solely its Primary Key(product_type_id)

LHS is a key

\therefore The relation is in 3NF

6 RESTRICTED_TO

RESTRICTED_TO (shop_id, product_type_id)

Keys: {shop_id, product_type_id}

Primary Key: {shop_id, product_type_id}

FDs: shop_id, product_type_id \rightarrow shop_id, product_type_id

Only trivial FD exists in the relation

\therefore The relation is in 3NF

7 SHIPMENT

SHIPMENT (shipment_id, tracking_num, date)

Keys: shipment_id, tracking_num

Primary Key: shipment_id

FDs: shipment_id \rightarrow tracking_num, date

tracking_num \rightarrow shipment_id, date

Both FD's LHS are superkey

\therefore The relation is in 3NF

8 INVOICE

INVOICE(invoice_number, date, status, order_id)

Keys: invoice_number

Primary Key: invoice_number

FDs: invoice_number \rightarrow date, status, order_id

All the attributes are functionally dependent on solely its Primary Key(invoice_number)

LHS is a key

\therefore The relation is in 3NF

9 PAYMENT

PAYMENT (payment_id, amount, card_num, invoice_number)

Keys: payment_id

Primary Key: payment_id

FDs: payment_id \rightarrow amount, card_num, invoice_number

All the attributes are functionally dependent on solely its Primary Key(payment_id)

LHS is a key

\therefore The relation is in 3NF

10 PRODUCT

PRODUCT(product_id, name, colour, price, size, description, shop_id, product_type_id)

Keys: product_id

Primary Key: product_id

FDs: product_id \rightarrow name, colour, price, size, description, shop_id, product_type_id

All the attributes are functionally dependent on solely its Primary Key(payment_id)

LHS is a key

\therefore The relation is in 3NF

11 PHOTOS

PHOTOS(photo_sequence, product_id, url)

Keys: {photo_sequence, product_id}

Primary Key: {photo_sequence, product_id}

FDs: photo_sequence, product_id \rightarrow url

All the attributes are functionally dependent on solely its

Primary Key (photo_sequence, product_id)

LHS is a key

\therefore The relation is in 3NF

12 SHOP

SHOP (shop_id, shop_name)

Keys: shop_id

Primary Key: shop_id

FDs: shop_id \rightarrow shop_name

All the attributes are functionally dependent on solely its
Primary Key (shop_id)

LHS is a key

\therefore The relation is in 3NF

13 ERD REFERENCE

