

0.1 English language?

- Grammar, syntax - defines rules, the structure of the statement, not the meaning
- Meaning (semantics) - even if structure is correct, meaning may not be direct or correct
- We need to follow the rules, and get the correct meaning

1 Introduction

- Syntax and semantics provide a language's definition
- Syntax: the form or structure of the expressions, statements, and program units
- Semantics: the meaning of the expressions, statements, and program units
- A *sentence (or statement)* is a string of characters over some alphabet
- A *language* is a set of sentences
- A *lexeme* is the lowest level syntactic unit of a language (e.g., *, sum, begin)
- A *token* is a category of lexemes (e.g., identifier)
- Programs are string of lexemes rather than characters. E.g., *sum+=2;*

Lexemes and Tokens are closely related:

<i>Lexemes</i>	<i>Token</i>
<i>sum</i>	identifier
+	arithmetic operator
=	equal_sign
2	int_literal
;	semicolon

1.1 Recognizers

- A recognition device reads input strings over the alphabet of the language and decides whether the input string belong to the language
- Example: syntax analysis part of a compiler

1.2 Generators

- A device that generates sentences of a language
- One can determine if the syntax of a particular sentence is syntactically correct by comparing it to the structure of the generator

2 BNF and Context-Free Grammars

2.1 Context-Free Grammars

- Developed by Noam Chomsky in the mid-1950s
- Language generators, meant to describe the syntax of natural languages
- Define a class of languages called context-free languages

2.2 Backus-Naur Form

- Invented by John Backus to describe the syntax of Algol58, later modified by Peter Naur for Algol 60
- BNF (Backus-Naur Form) is equivalent to context-free forms
- In BNF, abstractions are used to represent classes of syntactic structures; they act like syntactic variables, including nonterminal symbols or terminals
- *Terminals* are lexemes or tokens
- A **rule or production** has a left-hand side (LHS) which is a nonterminal, and a right hand side (RHS), which is a string of terminals and/or nonterminals
- Example:

$$\langle \textit{assign} \rangle \rightarrow \langle \textit{var} \rangle = \langle \textit{expression} \rangle$$

- Examples of BNF Rules:

- $\langle \textit{ident_list} \rangle \rightarrow \textit{identifier} | \textit{identifier}, \langle \textit{ident_list} \rangle$
- $\langle \textit{if_stmt} \rangle \rightarrow \textit{if} \langle \textit{logic_expr} \rangle \textit{ then } \langle \textit{stmt} \rangle$

- A *start symbol* is a special element of the nonterminals of a grammar
- Rules can be recursive

3 Derivation

- A derivation is a repeated application application of rules, starting with the start symbol, repeat till ending with a sentence (all terminal symbols)
- Application of rules:
 - Pick a non-terminal symbol on the right, and replace the non-terminal symbol using a RHS of rule for the non-terminal symbol
 - Example:

$\langle start_symbol \rangle \rightarrow \langle program \rangle$

$\langle program \rangle \rightarrow \mathbf{begin} \langle stmt_list \rangle \mathbf{end}$

$\langle stmt_list \rangle \rightarrow \langle stmt \rangle \mid \langle stmt \rangle ; \langle stmt_list \rangle$

$\langle stmt \rangle \rightarrow \langle var \rangle = \langle expression \rangle$

$\langle var \rangle \rightarrow A \mid B \mid C$

$\langle expression \rangle \rightarrow \langle var \rangle + \langle var \rangle \mid \langle var \rangle - \langle var \rangle \mid \langle var \rangle$

$\langle program \rangle \rightarrow begin \langle stmt_list \rangle end$

$\rightarrow begin \langle stmt \rangle ; \langle stmt_list \rangle end$

$\rightarrow begin \langle var \rangle = \langle expression \rangle ; \langle stmt_list \rangle end$

$\rightarrow begin A = \langle expression \rangle ; \langle stmt_list \rangle end$

$\rightarrow begin A = \langle var \rangle + \langle var \rangle ; \langle stmt_list \rangle end$

$\rightarrow begin A = B + \langle var \rangle ; \langle stmt_list \rangle end$

$\rightarrow begin A = B + C ; \langle stmt_list \rangle end$

$\rightarrow begin A = B + C ; B = C end$

4 The General Problem of Describing Syntax

-

5 Formal Methods of Describing Language

-

6 Introduction

-

7 Introduction

-

8 Introduction

-