

z/OS 3.1 IBM Education Assistant

Solution Name: z/OSMF RTD REST API support

Solution Element(s): z/OSMF REST Hub

July 2023



Agenda

- Trademarks
- Objectives
- Overview
- Usage & Invocation
- Interactions & Dependencies
- Upgrade & Coexistence Considerations
- Installation & Configuration
- Summary
- Appendix

Trademarks

- See url <http://www.ibm.com/legal/copytrade.shtml> for a list of trademarks.
- Additional Trademarks:
 - None.

Objectives

- Explain new function for z/OSMF RTD REST API support.

Overview

- Who (Audience)
 - z/OS system administrator and application developer
- What (Solution)
 - z/OSMF provides a standard HTTPs REST API that can be invoked by web client to get runtime diagnostic data returned by RTD API about a specified set of address spaces on a defined system.
- Wow (Benefit / Value, Need Addressed)
 - z/OS provides a REST endpoint available to any external product for getting z/OS anomaly diagnostic data for anomalous subsystem workloads. The endpoint is delivered via this RTD REST API and can be invoked for specified systems (members) within the same parallel sysplex.

Usage & Invocation

- The z/OSMF Runtime Diagnostics (RTD) REST services are an application programming interfaces (API) that are implemented through industry standard Representational State Transfer (REST) services. The RTD services provide a programming interface to get runtime diagnostic data about a specified set of address spaces on a defined system.
- For a successful request, this response takes the form of an HTTP 200 status code and a result set that is passed back to your program as a JSON object or Text/Plain.
- For an unsuccessful request, the server response consists of a non-OK HTTP response code and details of the error, which are provided in the form of a JSON object.

Usage & Invocation

- **HTTPs method and URI path**

- GET: /zosmf/resthub/hzr/<version>/analyze/anomaly?[sysname=name]&[asname=name&asname=name...]
- Where:
 - **<version>** is the URI path variable that identifies the version of the z/OS runtime diagnostic service. The following value is valid: v1.
 - **Sysname** is the name of an optional CHAR(8) input variable that specifies the name of the system to be analyzed by RTD. The name is left-justified and padded on the right with blanks.
 - **Asname** is the name of an optional CHAR(8) input variable that contains a list of address space names or a name prefix. The first character in the name must be an alphabetic character or a special character (the symbols #, @, and \$). The remaining characters can be alphanumeric or special characters, blank spaces cannot be included in a name. This path supports a maximum of four address space names at a time.

- **Custom headers X-IBM-Data-Type**

- This header indicates which response data type is returned. The following type are supported:
 - application/json
 - text/plain
 - Default: The JSON response data will be returned

Usage & Invocation

Example: The following request obtains the abnormal data in the system sys1:

GET: /zosmf/resthub/hzr/v1/analyze/anomaly?sysname=sy1

Header: X-IBM-Data-Type:*application/json*

Response: *status code: 200*

Usage & Invocation

Example response

```
{
  "HZR0200I RUNTIME DIAGNOSTICS RESULT SUMMARY": "SUCCESS",
  "REQ": "8",
  "TARGET SYSTEM": "SY1",
  "HOME": "SY1",
  "TIME": "2023/01/31 02:27:48",
  "INTERVAL": " 60 MINUTES",
  "TYPES": [
    "JES2:1"
  ],
  "EVENTS": [
    {
      "EVENT": "1",
      "PRIORITY": "HIGH",
      "TYPE": "JES2",
      "MESSAGE": "$HASP9250 RESOURCE TGS UTILIZATION IS AT 83.80%",
      "ERROR": "INDICATED RESOURCE IS ABOVE THE WARNING THRESHOLD.",
      "ACTION": "LOOK FOR MESSAGE $HASP050. FOLLOW THE MESSAGE DOCUMENTATION FOR THE INDICATED RESOURCE."
    }
  ]
}
```

Interactions & Dependencies

- Software Dependencies
 - z/OS Runtime Diagnostic
- Hardware Dependencies
 - NONE
- Exploiters
 - IZAA

Upgrade & Coexistence Considerations

- To exploit this solution, all systems in the Plex must be at the new z/OS level:
- Yes
- List any toleration/coexistence APARs/PTFs.
- N/A
- List anything that doesn't work the same anymore.
- N/A
- Upgrade involves only those actions required to make the new system behave as the old one did.
- N/A
- Coexistence applies to lower level systems which coexist (share resources) with latest z/OS systems.
- N/A

Installation & Configuration

- List anything that a client needs to be aware of during installation and include **examples** where appropriate - clients appreciate these:
 - Are any APARs or PTFs needed for enablement? No additional APARs are needed for V3.1.
 - What jobs need to be run? N/A
 - What hardware configuration is required? N/A
 - What PARMLIB statements or members are needed? N/A
 - Are any other system programmer procedures required? N/A
 - Are there any planning considerations? N/A
 - Are any special web deliverables needed? N/A
 - Does installation change any system defaults? N/A

Summary

z/OSMF RTD REST API support has been explained.

Appendix

- Please refer to z/OSMF Configuration Guide and z/OSMF Programming Guide for more details about z/OSMF RTD REST API.