

Developing SimObjects in gem5



We will cover

- Development environment, code style, git branches
- The most simple `SimObject`
- Simple run script
- How to add parameters to a `SimObject`

Let's begin by building gem5

Let's build gem5 in the base **gem5** directory while we go through some basics. Do it by running the following commands.

```
cd gem5  
scons build/NULL/gem5.opt -j$(nproc)
```



What is a SimObject?

`SimObject` is gem5's name for a simulated model. We use `SimObject` and its children classes (e.g. `ClockedObject`) to model computer hardware components. `SimObject` facilitates the following in gem5:

- Defining a model: e.g. a cache
- Parameterizing a model: e.g. cache size, associativity
- Gathering statistics: e.g. number of hits, number of accesses

SimObject in Code

In a gem5 build, each `SimObject` based class has 4 related files.

- `SimObject` declaration file: Python(ish) script (.py extension):
 - Represents the model at the highest level. Allows instantiation of the model and interfacing with the C++ backend. It defines the sets of parameters for the model.
 - **CAUTION:** You should not change parameter values (which we will learn about in the future) in this file if what you want to do is to reconfigure your `SimObject`.
- `SimObject` header file: C++ header file (.hh extension):
 - Declares the `SimObject` class in C++.
 - Strongly tied to `SimObject` definition file.
- `SimObject` source file: C++ source file (.cc extension):
 - Implements the `SimObject` functionalities.
- `SimObjectParams` header file: **Auto-generated** C++ header file (.hh) from `SimObject` definition:
 - Declares a C++ struct storing all the parameters of the `SimObject`.

HelloSimObject

We will start building our first `SimObject` called `HelloSimObject`, and we will look at one of the `SimObject` files.

We will start with the following steps.

1. Write a definition file.
2. Write a header file.
3. Write a source file.
4. Write a `SConscript`.
5. Compile.
6. Write a configuration script and run it.

Later, we'll do the following steps.

7. Add a parameter to the definition file.
8. Update the source file.
9. Compile.
10. Write a second configuration script and run it.

SimObject Definition File: Creating the Files

Let's create a python file for our `SimObject` under:
<src/bootcamp/hello-sim-object/HelloSimObject.py>

Since gem5 is still compiling, start by opening a new terminal.



Then, run the following commands in the base **gem5** directory:

```
cd gem5
mkdir src/bootcamp
mkdir src/bootcamp/hello-sim-object
touch src/bootcamp/hello-sim-object/HelloSimObject.py
```

SimObject Definition File: Importing and Defining

Open <src/bootcamp/hello-sim-object/HelloSimObject.py> in your editor of choice.

In `HelloSimObject.py`, we will define a new class that represents our `HelloSimObject`. We need to import the definition of `SimObject` from `m5.objects.SimObject`. Add the following line to `HelloSimObject.py` to import the definition for `SimObject`.

```
from m5.objects.SimObject import SimObject
```

Let's add the definition for our new `SimObject`.

```
class HelloSimObject(SimObject):  
    type = "HelloSimObject"  
    cxx_header = "bootcamp/hello-sim-object/hello_sim_object.hh"  
    cxx_class = "gem5::HelloSimObject"
```


SimObject Definition File: Deeper Look at What We Have Done

Let's take a deeper look at the few lines of code we have.

```
class HelloSimObject(SimObject):  
    type = "HelloSimObject"  
    cxx_header = "bootcamp/hello-sim-object/hello_sim_object.hh"  
    cxx_class = "gem5::HelloSimObject"
```

- `type` is the type name for the `SimObject` in python.
- `cxx_header` denotes the path to the C++ header file that declares the `SimObject` in C++.
IMPORTANT: This path should be specified relative to `gem5/src`.
- `cxx_class` is the name of your `SimObject` class in C++.

`type`, `cxx_header`, and `cxx_class` are keywords defined by the `MetaSimObject` metaclass. For a complete list of these keywords, look at [src/python/m5/SimObject::MetaSimObject](#). Some (if not all) of these keyword variables can be skipped. However, I strongly encourage you to at least define `type`, `cxx_header`, `cxx_class`.



Word to the Wise and A Little Peek into the Future

- I strongly recommend setting `type` to the name of the `SimObject` class in Python. I also recommend making sure that the C++ class name is the same as the Python class. You will see throughout the gem5 codebase that this is *not* always the case. However, I strongly recommend following this rule to rid yourself of any compilation headaches.
- We will see later that, when gem5 is built, there will be an **auto-generated** struct definition that stores the parameters of that class. The name of the struct will be determined by the name of the `SimObject` itself. For example, if the name of the `SimObject` is `HelloSimObject`, the struct storing its parameters will be `HelloSimObjectParams`. This definition will be in a file under [params/HelloSimObject.hh](#) in the build directory. This struct is used when instantiating an object of a `SimObject` in C++.

SimObject Header File: Creating the Files

Now, let's start building our `SimObject` in C++. First, let's create a file for our `SimObject` by running the following commands in the base **gem5** directory. **REMEMBER:** We set `cxx_header` to `bootcamp/hello-sim-object/hello_sim_object.hh`. Therefore, we need to add the definition for `HelloSimObject` in a file with that same path.

```
touch src/bootcamp/hello-sim-object/hello_sim_object.hh
```

VERY IMPORTANT: If a `SimObject` class inherits from another `SimObject` class in Python, it should do the same in C++. For example, `HelloSimObject` inherits from `SimObject` in Python, so in C++, `HelloSimObject` should inherit from `SimObject`.

VERY IMPORTANT: `SimObject` parameter structs are inherited in the same way as the `SimObject` itself. For example, if `HelloSimObject` inherits from `SimObject`, `HelloSimObjectParams` inherits from `SimObjectParams`.

SimObject Header File: First Few Lines

Open src/bootcamp/hello-sim-object/hello_sim_object.hh in your editor of choice and add the following code to it.

```
#ifndef __BOOTCAMP_HELLO_SIM_OBJECT_HELLO_SIM_OBJECT_HH__
#define __BOOTCAMP_HELLO_SIM_OBJECT_HELLO_SIM_OBJECT_HH__

#include "params/HelloSimObject.hh"
#include "sim/sim_object.hh"

namespace gem5
{

class HelloSimObject: public SimObject
{
    public:
        HelloSimObject(const HelloSimObjectParams& params);
};
```

SimObject Header File: Deeper Look into the First Few Lines

Things to note:

- `__BOOTCAMP_HELLO_SIM_OBJECT_HELLO_SIM_OBJECT_HH__` is an include guard to prevent double includes and cyclic includes. gem5's convention is that the name should reflect the location of the header file relative to the `gem5/src` directory, with `_` being the separator.
- `sim/sim_object.hh` holds the definition for class `SimObject` in C++.
- As mentioned previously, `params/HelloSimObject.hh` is auto-generated and declares a struct named `HelloSimObjectParams`.
- Every `SimObject` should be declared/defined inside the `namespace gem5`. Different categories of `SimObjects` may have their own specific namespace such as `gem5::memory`.
- Class `HelloSimObject` (C++ counterpart for `HelloSimObject` in Python) should inherit from class `SimObject` (C++ counterpart for `SimObject` in Python).
- Every `SimObject` class needs to define a constructor that takes exactly one argument. This argument must be a constant reference object of its parameter struct. Later on, we will look at gem5's internal process that instantiates objects from `SimObject` classes.



SimObject Source File: All the Code

Let's create a source file for `HelloSimObject` under:
src/bootcamp/hello-sim-object/hello_sim_object.cc.

```
touch src/bootcamp/hello-sim-object/hello_sim_object.cc
```

Open src/bootcamp/hello-sim-object/hello_sim_object.cc in your editor of choice and add the following code to it.

```
#include "bootcamp/hello-sim-object/hello_sim_object.hh"

#include <iostream>

namespace gem5
{

HelloSimObject::HelloSimObject(const HelloSimObjectParams& params):
    SimObject(params)
{

```

SimObject Source File: Deeper Look

Things to note:

- gem5's convention for the order of include statements is as follows.
 - the header for the `SimObject`.
 - C++ libraries in alphabetical order.
 - other gem5 header files in alphabetical order.
- We only define `HelloSimObject's` constructor since that's the only function it has so far.
- The `params` object passed to the `HelloSimObject::HelloSimObject` constructor is an object of `HelloSimObjectParams` which inherits from `SimObjectParams`. This means `params` can then be passed on to the `SimObject::SimObject` constructor.

Let's Start Building: SConscript

We need to register our `SimObject` with gem5 for it to be built into the gem5 executable. At build time, `scons` (gem5's build system) will look through the gem5 directory searching for files named `SConscript`. `SConscript` files include instructions on what needs to be built. We will simply create a file called `SConscript` (inside our `SimObject` directory) by running the following command in the base **gem5** directory.

```
touch src/bootcamp/hello-sim-object/SConscript
```

Add the following to the [SConscript](#).

```
Import("*")

SimObject("HelloSimObject.py", sim_objects=["HelloSimObject"])

Source("hello_sim_object.cc")
```


Let's Start Building: Deeper Look at the SConscript

Things to note:

- `SimObject("HelloSimObject.py", sim_objects=["HelloSimObject"])` registers `HelloSimObject` as a `SimObject`. The first argument denotes the name of the submodule that will be created under `m5.objects`. All the `SimObjects` listed under `sim_objects` will be added to that submodule. In this example, we will be able to import `HelloSimObject` as `m5.objects.HelloSimObject.HelloSimObject`. It is possible to define more than one `SimObject` in one Python script. Only `SimObjects` listed under `sim_objects` will be built.
- `Source("hello_sim_object.cc")` adds `hello_sim_object.cc` as a source file to be compiled.

Let's Compile

Now, the only thing left to do before we can use `HelloSimObject` in our configuration script is to recompile gem5. Run the following command in the base **gem5** directory to recompile gem5.

```
scons build/NULL/gem5.opt -j$(nproc)
```

While we wait for gem5 to build, we will create a configuration script that uses `HelloSimObject`. In a separate terminal, let's create that script inside [gem5/configs](#). First, let's create a directory structure for our scripts. Run the following set of commands in the base **gem5** directory to create a clean structure.

```
mkdir configs/bootcamp  
mkdir configs/bootcamp/hello-sim-object  
touch configs/bootcamp/hello-sim-object/first-hello-example.py
```



Configuration Script: First Hello Example: m5 and Root

Open [configs/bootcamp/first-hello-example.py](https://github.com/gem5/gem5/blob/master/configs/bootcamp/first-hello-example.py) in your editor of choice.

To run a simulation, we will need to interface with gem5's backend. `m5` will allow us to call on the C++ backend to instantiate `SimObjects` in C++ and simulate them. To import `m5` into your configuration script, add the following to your code.

```
import m5
```

Every configuration script in gem5 has to instantiate an object of class `Root`. This object represents the root of the device tree in the computer system that gem5 is simulating. To import `Root` into your configuration, add the following line to your script.

```
from m5.objects.Root import Root
```

Configuration Script: First Hello Example: Creating Instances in Python

We will also need to import `HelloSimObject` into our configuration script. To do that, add the following line to your configuration script.

```
from m5.objects>HelloSimObject import HelloSimObject
```

The next thing we need to do is create a `Root` object and a `HelloSimObject` object. We can just add our `HelloSimObject` object as a child of the `root` object by using the `.` operator. Add the following lines to your configuration to do that.

```
root = Root(full_system=False)
root.hello = HelloSimObject()
```

NOTE: We are passing `full_system=False` to `Root` because we are going to simulate in `SE` mode.

Configuration Script: First Hello Example: Instantiation in C++ and Simulation

Next, let's tell gem5 to instantiate our `SimObjects` in C++ by calling `instantiate` from `m5`. Add the following line to your code to do that.

```
m5.instantiate()
```

Now that we have instantiated our `SimObjects`, we can tell gem5 to start the simulation. We do that by calling `simulate` from `m5`. Add the following line to your code to do that.

```
exit_event = m5.simulate()
```

At this point, the simulation will start. It will return an object that holds the status of the simulation. We can see why the simulation exits by calling `getCause` from `exit_event`. Add the following line to your code to do that.

```
print(f"Exited simulation because: {exit_event.getCause()}.")
```

Everything Everywhere All at Once

Here is the complete version of our configuration script.

```
import m5
from m5.objects.Root import Root
from m5.objects.HelloSimObject import HelloSimObject

root = Root(full_system=False)
root.hello = HelloSimObject()

m5.instantiate()
exit_event = m5.simulate()

print(f"Exited simulation because: {exit_event.getCause()}")
```

Simulate: First Hello Example

Run with the following command in the base **gem5** directory.

```
./build/NULL/gem5.opt ./configs/bootcamp/hello-sim-object/first-hello-example.py
```

```
root@codespaces-11c89e:/workspaces/2024/gem5# ./build/NULL/gem5.opt ./configs/
```



A Little Bit of a Detour: m5.instantiate



Detour: m5.instantiate: SimObject Constructors and Connecting Ports

Below is a snippet of code from the definition of `m5.instantiate`:

```
# Create the C++ sim objects and connect ports
for obj in root.descendants():
    obj.createCObject()
for obj in root.descendants():
    obj.connectPorts()
```

When you call `m5.instantiate`, first, all the `SimObjects` are created (i.e. their C++ constructors are called). Then, all the `port` connections are created. If you don't know what a `Port` is, don't worry. We will get to that in the later slides. For now, think of `ports` as a facility for `SimObjects` to send each other data.

Detour: m5.instantiate: SimObject::init

Here is a later snippet of code in `instantiate`.

```
# Do a second pass to finish initializing the sim objects
for obj in root.descendants():
    obj.init()
```

In this step, gem5 will call the `init` function from every `SimObject`. `init` is a virtual function defined by the `SimObject` class. Every `SimObject` based class can override this function. The purpose of the `init` function is similar to the constructor. However, it is guaranteed that when the `init` function from any `SimObject` is called, all the `SimObjects` are created (i.e. their constructors are called).

Below is the declaration for `init` in `src/sim/sim_object.hh`.

```
/* init() is called after all C++ SimObjects have been created and
 * all ports are connected. Initializations that are independent
 * of unserialization but rely on a fully instantiated and
 * connected SimObject graph should be done here */
```

Detour: m5.instantiate: SimObject::initState, SimObject::loadState

Below shows another snippet from instantiate:

```
# Restore checkpoint (if any)
if ckpt_dir:
    _drain_manager.preCheckpointRestore()
    ckpt = _m5.core.getCheckpoint(ckpt_dir)
    for obj in root.descendants():
        obj.loadState(ckpt)
else:
    for obj in root.descendants():
        obj.initState()
```

`initState` and `loadState` are the last step of initializing `SimObjects`. However, only one of them is called for every simulation. `loadState` is called to unserialize a `SimObject`'s state from a checkpoint and `initState` is only called when starting a new simulation (i.e. not from a checkpoint).



Continued in next page

Detour: m5.instantiate: SimObject::initState, SimObject::loadState: C++

Below is the declaration for `initState` and `loadState` in `src/sim/sim_object.hh`.

```
/* loadState() is called on each SimObject when restoring from a
 * checkpoint. The default implementation simply calls
 * unserialize() if there is a corresponding section in the
 * checkpoint. However, objects can override loadState() to get
 * other behaviors, e.g., doing other programmed initializations
 * after unserialize(), or complaining if no checkpoint section is
 * found. */
virtual void loadState(CheckpointIn &cp);
/* initState() is called on each SimObject when *not* restoring
 * from a checkpoint. This provides a hook for state
 * initializations that are only required for a "cold start". */
virtual void initState();
```

We Will See Later

You might have noticed that we also call `m5.simulate` in our configuration script. For now, `HelloSimObject` does nothing interesting during simulation. We will look into the details of simulate later.

Params



Let's Talk About Params: Model vs Params

As we mentioned earlier, gem5 allows us to parameterize our models. The whole set of parameter classes in gem5 is defined under `m5.params`, so let's go ahead and import everything from `m5.params` into our `SimObject` definition file. Open <src/bootcamp/hello-sim-object/HelloSimObject.py> in your editor of choice and add the following line to it.

```
from m5.params import *
```

Now we just need to define a parameter for our `HelloSimObject`. Add the following line to the same file (the `HelloSimObject` definition) to do that. You should add this line under the definition of `class HelloSimObject`.

```
num_hellos = Param.Int("Number of times to say Hello.")
```

Make sure to take a look at <src/python/m5/params.py> for more information on different parameter classes and how you can add a parameter.

CAUTION: Params allow you to define a default value for them. I strongly recommend that you don't define defaults unless you really have to.



HelloSimObject Definition File Now

Here is what your `HelloSimObject` definition file should look like after the changes.

```
from m5.objects.SimObject import SimObject
from m5.params import *

class HelloSimObject(SimObject):
    type = "HelloSimObject"
    cxx_header = "bootcamp/hello-sim-object/hello_sim_object.hh"
    cxx_class = "gem5::HelloSimObject"

    num_hellos = Param.Int("Number times to say Hello.")
```

NOTE: This change to `HelloSimObject.py` will now add an attribute to the `HelloSimObjectParams` the next time you compile gem5. This means that we can now access this parameter in the C++ code.

Using num_hellos

Now, we're going to use `num_hellos` to print `Hello from ...` multiple times in the constructor of the `HelloSimObject`. Open src/bootcamp/hello-sim-object/hello_sim_object.cc in your editor of choice.

Change `HelloSimObject::HelloSimObject` like below:

```
HelloSimObject::HelloSimObject(const HelloSimObjectParams& params):
    SimObject(params)
{
    for (int i = 0; i < params.num_hellos; i++) {
        std::cout << "i: " << i << ", Hello from HelloSimObject's constructor!" << std::endl;
    }
}
```

Make sure you don't delete `include` statements and any lines containing `namespace gem5`

RECOMPILE: All we need to do now is just recompile gem5. Simply do that by running the following command in the base **gem5** directory.



params/HelloSimObject.hh

As we mentioned before, the parameters of a `SimObject` are defined in an auto-generated header file with the `SimObject's` name.

Now that we have added a parameter to `HelloSimObject`, it should now be defined under `HelloSimObjectParams` in <build/NULL/params/HelloSimObject.hh>.

If you look at the header file, you should see something like this.

Configuration Script: Second Hello Example

Let's create a copy of [first-hello-example.py](#) named [second-hello-example.py](#). Just run the following command in the base **gem5** directory to do this.

```
cp configs/bootcamp/hello-sim-object/first-hello-example.py configs/bootcamp/hello-sim-object/second-hello-example.py
```

Now, open [second-hello-example.py](#) in your editor of choice and change the code so that it passes a value for `num_hellos` when you instantiate a `HelloSimObject`. Below is a full example of this.

```
import m5
from m5.objects.Root import Root
from m5.objects.HelloSimObject import HelloSimObject

root = Root(full_system=False)
root.hello = HelloSimObject(num_hellos=5)

m5.instantiate()
exit_event = m5.simulate()
```

Simulate: Second Hello Example

Run with the following command in the base **gem5** directory.

```
./build/NULL/gem5.opt ./configs/bootcamp/hello-sim-object/second-hello-example.py
```

```
root@codespaces-11c89e:/workspaces/2024/gem5# ./build/NULL/gem5.opt ./configs/boot
```



Summary of Steps

- Creating a basic `SimObject`
 - `SimObject` [definition file](#) (.py)
 - Defines the sets of parameters for the model.
 - `SimObject` [header file](#) (.hh)
 - Declares the `SimObject` class in C++.
 - `SimObject` [source file](#) (.cc extension):
 - Implements the `SimObject` functionalities.
 - `SConscript`
 - Register our `SimObject` with gem5.
 - Auto-generated `SimObjectParams` [header file](#) (.hh)
 - Declares a C++ struct storing all the parameters of the `SimObject`.
 - [Configuration file](#) (.py)
 - Instantiate `SimObject` and run the simulation.
- Adding a parameter (`num_hellos`)
 - Update the [definition file](#) and the [source file](#).
 - Write a new [configuration file](#).
 - Re-compile and re-run.