

server.js

```

import express from 'express';
import { Client } from "@gradio/client";

const app = express();
app.use(express.json());

const PORT = process.env.PORT || 3000;

app.post('/generate', async (req, res) => {
  const { prompt, aspect_ratio = "1:1" } = req.body;

  if (!prompt) {
    return res.status(400).json({ error: "Prompt is required" });
  }

  try {
    console.log(`Generating image for prompt: ${prompt}`);
    const client = await Client.connect("multimodalart/Qwen-Image-Fast");

    const result = await client.predict("/infer", {
      prompt: prompt,
      seed: 0,
      randomize_seed: true,
      aspect_ratio: aspect_ratio,
      guidance_scale: 1,
      num_inference_steps: 4,
      prompt_enhance: true,
    });

    // result.data contains the image information
    // In Gradio 5+, this is usually an array of objects
    res.json({
      success: true,
      image_url: result.data[0].url,
      metadata: result.data[0]
    });
  } catch (error) {
    console.error("Generation error:", error);
    res.status(500).json({
      success: false,
      error: "Failed to generate image",
      details: error.message
    });
  }
});

app.get('/', (req, res) => {
  res.send('Qwen-Image API Wrapper is running. Send a POST request to /generate with { "prompt": "..."}');
});

app.listen(PORT, () => {
  console.log(`Server running on port ${PORT}`);
});

```