

# [220] Database 1

Meena Syamkumar  
Mike Doescher

**Cheaters caught: 6**  
**Work in progress: P6 to P10**

# Learning objectives – database topic

## Today's lecture

- "narrowing down" specific data from a big table – pandas
- SQL Data
  - schemas: tables, columns, types
  - advantages over JSON/CSV
- SQL Queries
  - select, where, limit, sort by
  - sqlite3 module
  - Pandas/DB integration

## Next lecture

- Summarizing data

## Next to next lecture

- worksheets - SQL practice

# What we don't cover ...

- Schema design:
  - What tables does a database have?
  - What columns does a table have?
  - What are the relationship between the columns?
- Changes to database data:
  - Add a row, remove a row
- Concurrency
- Performance
- Joins:
  - Combining multiple tables with related information

# 220 Progress

## Languages learned

- Python [**P**rogramming Language]
- HTML [**M**arkup Language]

## Data storage

- CSV files
- JSON files

# 220 Progress

## Languages learned

- Python [**P**rogramming Language]
- HTML [**M**arkup Language]
- SQL [**Q**uery Language]

## Data storage

- CSV files
- JSON files
- SQL databases

*structured query language*

# Learning Objectives Today

## SQL Data

- schemas: tables, columns, types
- advantages over JSON/CSV

## SQL Queries

- select, where, limit, sort by
- sqlite3 module
- Pandas/DB integration

# Outline

Tabular Data: CSVs vs. Databases

Common SQL Databases

Example: Madison bus-route data

SQL: Structured Query Language

Demos

# CSV

State	Capital	Population	Area
WI	Madison	5795000	65498
...	...	...	...

## Characteristics

- one table

# SQL Database

capitals

State	Capital
WI	Madison
...	...

populations

State	Population
WI	5795000
...	...

counties

County	Pop	un_emp
Dane	536416	0.02
...	...	...

areas

State	Area
WI	65498
...	...

## Characteristics

- collection of tables, each named



# CSV

State	Capital	Population	Area
WI	Madison	5795000	65498
...	...	...	...

## Characteristics

- one table
- *columns sometimes* named

# SQL Database

capitals

State	Capital
WI	Madison
...	...

populations

State	Population
WI	5795000
...	...

counties

County	Pop	un_emp
Dane	536416	0.02
...	...	...

areas

State	Area
WI	65498
...	...

## Characteristics

- collection of tables, each named
- *columns always* named

# CSV

State	Capital	Population	Area
string	string	string	string
string	string	string	string
string	string	string	string
string	string	string	string
string	string	string	string
string	string	string	string
string	string	string	string
string	string	string	string

## Characteristics

- one table
- columns *sometimes* named
- **everything is a string**

# SQL Database

capitals

State	Capital
text	text
text	text
text	text
text	text

populations

State	Population
text	integer
text	integer
text	integer
text	integer

counties

County	Pop	un_emp
Dane	536416	0.02
...	...	...

areas

State	Area
WI	65498
...	...

no text allowed

## Characteristics

- collection of tables, each named
- columns *always* named
- **types per column (enforced)**

# Why use a database?

## 1. More Structure

### Database

A	B	C
text	integer	real
text	integer	real
text	integer	real
text	integer	real

same fields and same  
types in every column

### CSV

```
A,B,C
string,string,string
string,string,string
string,string,string
string,string,string
```

everything is a string

### JSON

```
[{"A":"val", "B":10, "C":3.14},
{"A":"val"},
{"A":"v2", "B": 9, "C":False},
```

types, but...


missing values

types may differ across columns

# Why use a database?

1. More Structure

2. Sharing




# Why use a database?


1. More Structure

2. Sharing

3. Queries



which actor appeared  
in the most movies?





# Why use a database?

1. More Structure

2. Sharing

3. Queries



# Why use a database?

1. More Structure

2. Sharing

3. Queries

4. Performance


Let's play a game where we pretend to be a database!

## Question 1:

How many people are 23 or younger?

## Question 2:

How many people scored 23 or less?



names	age	score
Parker	?	?
Heidy	?	?
Shirly	?	?
Arla	?	?
Bella	?	?
Bill	?	?
Hollis	?	?
Maurita	?	?
Milda	?	?
Pearline	?	?
Teresa	?	?
Ceola	?	?
Milford	?	?
Alisha	?	?
Antonetta	?	?
Ryan	?	?
Karma	?	?
Lashandra	?	?
Breana	?	?
Sara	?	?




## Question 1:

How many people are 23 or younger?

## Question 2:

How many people scored 23 or less?



names	age	score
Parker	26	?
Heidy	22	?
Shirly	27	?
Arla	21	?
Bella	22	?
Bill	28	?
Hollis	26	?
Maurita	22	?
Milda	22	?
Pearline	29	?
Teresa	25	?
Ceola	30	?
Milford	25	?
Alisha	30	?
Antonetta	28	?
Ryan	25	?
Karma	23	?
Lashandra	24	?
Breana	22	?
Sara	28	?

## Question 1:

How many people are 23 or younger?

## Question 2:

How many people scored 23 or less?



names	age	score
Parker	?	21
Heidy	?	22
Shirly	?	22
Arla	?	22
Bella	?	22
Bill	?	22
Hollis	?	23
Maurita	?	24
Milda	?	25
Pearline	?	25
Teresa	?	25
Ceola	?	26
Milford	?	26
Alisha	?	27
Antonetta	?	28
Ryan	?	28
Karma	?	28
Lashandra	?	29
Breana	?	30
Sara	?	30

## Question 1:

How many people are 23 or younger?

## Question 2:

How many people scored 23 or less?

*Which question took longer to answer? Why?*

names	age	score
Parker	26	21
Heidy	22	22
Shirly	27	22
Arla	21	22
Bella	22	22
Bill	28	22
Hollis	26	23
Maurita	22	24
Milda	22	25
Pearline	29	25
Teresa	25	25
Ceola	30	26
Milford	25	26
Alisha	30	27
Antonetta	28	28
Ryan	25	28
Karma	23	28
Lashandra	24	29
Breana	22	30
Sara	28	30

DBs can keep **multiple copies** of the same data

- which organizations to use are **configured** (indexing)
- which copy to use is used is **automatically determined** based on the question being asked

names	age	score
Arla	21	22
Heidy	22	22
Bella	22	22
Maurita	22	24
Milda	22	25
Breana	22	30
Karma	23	28
Lashandra	24	29
Teresa	25	25
Milford	25	26
Ryan	25	28
Parker	26	21
Hollis	26	23
Shirly	27	22
Sara	28	30
Bill	28	22
Antonetta	28	28
Pearline	29	25
Alisha	30	27
Ceola	30	26

**copy 1**

names	age	score
Parker	26	21
Heidy	22	22
Shirly	27	22
Arla	21	22
Bella	22	22
Bill	28	22
Hollis	26	23
Maurita	22	24
Milda	22	25
Pearline	29	25
Teresa	25	25
Ceola	30	26
Milford	25	26
Alisha	30	27
Antonetta	28	28
Ryan	25	28
Karma	23	28
Lashandra	24	29
Breana	22	30
Sara	28	30

**copy 2**

# Why use a database?

1. More Structure
2. Sharing
3. Queries
4. Performance

# Why not use a database?

It's often overkill.

For many situations, a simple JSON or CSV is easier to use.

# Outline

Tabular Data: CSVs vs. Databases

Common SQL Databases

Example: Madison bus-route data

SQL: Structured Query Language

Demos

# Popular SQL Databases



There are minor differences in how you use these (e.g., what column types are available and how you query for data).

Most experience with one DB will translate to work with other DBs.

Download bus.db from today's lecture entry to follow along lecture demos



# Popular SQL Databases



ORACLE®



in CS 220

<https://www.sqlite.org/mostdeployed.html>

- Every Android device
- Every iPhone and iOS device
- Every Mac
- Every Windows 10 machine
- Every Firefox, Chrome, and Safari web browser
- Every instance of Skype
- Every instance of iTunes
- Every Dropbox client

## Why learn SQLite?

- easy to install/use
- sqlite3 **module** comes with Python
- it's public domain
- several billion deployments

# Outline

Tabular Data: CSVs vs. Databases


Common SQL Databases

Example: Madison bus-route data

SQL: Structured Query Language

Demos

Madison Bus Data: <http://data-cityofmadison.opendata.arcgis.com/datasets/metro-transit-ridership-by-route-weekday>




*"Metro Transit ridership by route weekday. March, 2015.*

*Caution should be used with this data. Daily bus stop boardings were estimated using a 12-day sample of weekday farebox records and AVL logs, and the GTFS file, from March 2015 from Metro Transit."*

# Metro\_Transit\_Bus\_Routes

OBJECTID	trips_routes_route_id	route_short_name	route_url	ShapeSTLength
63	8052	1	<a href="http://www.cityofmadison.com/Metro/schedules/Route01/">http://www.cityofmadison.com/Metro/schedules/Route01/</a>	32379.426524261
64	8053	2	<a href="http://www.cityofmadison.com/Metro/schedules/Route02/">http://www.cityofmadison.com/Metro/schedules/Route02/</a>	96906.9655714024
65	8054	3	<a href="http://www.cityofmadison.com/Metro/schedules/Route03/">http://www.cityofmadison.com/Metro/schedules/Route03/</a>	76436.6456435859
66	8055	4	<a href="http://www.cityofmadison.com/Metro/schedules/Route04/">http://www.cityofmadison.com/Metro/schedules/Route04/</a>	64774.1334846944
67	8056	5	<a href="http://www.cityofmadison.com/Metro/schedules/Route05/">http://www.cityofmadison.com/Metro/schedules/Route05/</a>	61216.7226616153
68	8057	6	<a href="http://www.cityofmadison.com/Metro/schedules/Route06/">http://www.cityofmadison.com/Metro/schedules/Route06/</a>	151142.298370202
69	8058	7	<a href="http://www.cityofmadison.com/Metro/schedules/Route07/">http://www.cityofmadison.com/Metro/schedules/Route07/</a>	98617.0056650761
70	8059	8	<a href="http://www.cityofmadison.com/Metro/schedules/Route08/">http://www.cityofmadison.com/Metro/schedules/Route08/</a>	56732.757385207
71	8060	10	<a href="http://www.cityofmadison.com/Metro/schedules/Route10/">http://www.cityofmadison.com/Metro/schedules/Route10/</a>	113468.940882266




SQLite Database

File: bus.db

routes  
Table

Metro\_Transit\_Ridership\_by\_Route\_Weekday

X	Y	OBJECTID	StopID	Route	Lat	Lon	DailyBoardings	DotSize
-89.385420971415726	43.073647056880461	13341	1163	27	43.073655	-89.385427	1.03	10323.2
-89.385420971415726	43.073647056880461	13342	1163	47	43.073655	-89.385427	0.11	1116.34
-89.385420971415726	43.073647056880461	13343	1163	75	43.073655	-89.385427	0.34	3406.36
-89.34001498094068	43.106457048781294	13344	1164	6	43.106465	-89.340021	10.59	105923.91
-89.369986975587182	43.07785905487895	13345	1167	3	43.077867	-89.369993	3.11	31128.99
-89.369986975587182	43.07785905487895	13346	1167	4	43.077867	-89.369993	2.23	22272.52
-89.369986975587182	43.07785905487895	13347	1167	10	43.077867	-89.369993	0.11	1112.87
-89.369986975587182	43.07785905487895	13348	1167	38	43.077867	-89.369993	1.36	13592
-89.329810986164361	43.089699051299455	13349	1169	3	43.089707	-89.329817	18.9	188997.43




SQLite Database  
File: bus.db


routes  
Table

boarding  
Table

*how do we use this data?*




SQLite Database  
File: bus.db



# Modules we've learned this semester

- math
- collections
- json
- csv
- sys
- os
- copy
- recordclass
- requests
- bs4 (BeautifulSoup)
- pandas  integrates with SQLite
- sqlite3  directly access SQLite databases (comes with Python)


python



*this semester, we'll only  
query data through pandas*

sqlite3 tool

SQLite Database  
File: bus.db





# sqlite3

```
import sqlite3
```

```
conn = sqlite3.connect("file.db")
```

**connect** for databases is  
analogous to **open** for files


database filename

- represented as a string
- will create if doesn't already exist  
(no "w" necessary)

# sqlite3

```
import sqlite3
```

```
conn = sqlite3.connect("file.db")
```




a **connection object** for  
databases is analogous to **file**  
**object** for files

# sqlite3

```
import sqlite3
```

```
conn = sqlite3.connect("file.db")
```

close it at the end



```
conn.close()
```


# sqlite3

```
import sqlite3
import pandas as pd
conn = sqlite3.connect("file.db")

df = pd.read_sql("select ??? from ???", conn)

conn.close()
```

ask this question query



Demo Time

```

1 import os, sqlite3
2
3 assert os.path.exists("bus.db")
4 sqlite3.connect("bus.db")
5
6 for sql in pd.read_sql("select sql from sqlite_master", conn)["sql"]:
7     print(sql)
8     print()

```

```
1 pd.read_sql("select * from routes", conn)
```

	index	OBJECTID	trips_routes_route_id	route_short_name	route_url	ShapeSTLength
0	0	63	8052	1	http://www.cityofmadison.com/Metro/schedules/R...	32379.426524
1	1	64	8053	2	http://www.cityofmadison.com/Metro/schedules/R...	96906.965571
2	2	65	8054	3	http://www.cityofmadison.com/Metro/schedules/R...	76436.645644

```
1 pd.read_sql("select * from boarding", conn)
```

	index	StopID	Route	Lat	Lon	DailyBoardings
0	0	1163	27	43.073655	-89.385427	1.03
1	1	1163	47	43.073655	-89.385427	0.11
2	2	1163	75	43.073655	-89.385427	0.04

**demo:** poke around DB  
(will explain more soon)

**CREATE TABLE** IF NOT EXISTS **"boarding"** (

"index" INTEGER,

"StopID" INTEGER,

"Route" INTEGER,

"Lat" REAL,

**table names**

"Lon" REAL,

"DailyBoardings" REAL

);

CREATE INDEX "ix\_boarding\_index" ON "boarding" ("index");

**CREATE TABLE** IF NOT EXISTS **"routes"** (

"index" INTEGER,

"OBJECTID" INTEGER,

"trips\_routes\_route\_id" INTEGER,

"route\_short\_name" INTEGER,

"route\_url" TEXT,

"ShapeSTLength" REAL

);

CREATE INDEX "ix\_routes\_index" ON "routes" ("index");

**CREATE TABLE** IF NOT EXISTS **"boarding"** (

"index" INTEGER,  
"StopID" INTEGER,  
"Route" INTEGER,  
"Lat" REAL,  
"Lon" REAL,  
"DailyBoardings" REAL

look for column names in parens

**columns**

- index
- StopID
- Route
- Lat
- Lon
- Daily Boardings

);

CREATE INDEX "ix\_boarding\_index" ON "boarding" ("index");

**CREATE TABLE** IF NOT EXISTS **"routes"** (

"index" INTEGER,  
"OBJECTID" INTEGER,  
"trips\_routes\_route\_id" INTEGER,  
"route\_short\_name" INTEGER,  
"route\_url" TEXT,  
"ShapeSTLength" REAL

);

CREATE INDEX "ix\_routes\_index" ON "routes" ("index");



```
CREATE TABLE IF NOT EXISTS "boarding" (  
  "index" INTEGER,  
  "StopID" INTEGER,  
  "Route" INTEGER,  
  "Lat" REAL,  
  "Lon" REAL,  
  "DailyBoardings" REAL  
);
```

types...

```
CREATE INDEX "ix_boarding_index" ON "boarding" ("index");
```

```
CREATE TABLE IF NOT EXISTS "routes" (  
  "index" INTEGER,  
  "OBJECTID" INTEGER,  
  "trips_routes_route_id" INTEGER,  
  "route_short_name" INTEGER,  
  "route_url" TEXT,  
  "ShapeSTLength" REAL  
);
```

```
CREATE INDEX "ix_routes_index" ON "routes" ("index");
```

# Overview: Narrowing Down

**table 1**


**table 2**


**table 3**


# Overview: Narrowing Down

table 1


table 2




table 3

col1	col2	col3

**FROM:** which table?

# Overview: Narrowing Down

table 1


table 2




table 3

col1	col2	col3



**FROM:** which table?  
**SELECT:** which columns?

# Overview: Narrowing Down

table 1


table 2


→ table 3

col1	col2	col3

↑                      ↑

**FROM:** which table?

**SELECT:** which columns?

**WHERE:** which rows?

# Overview: Narrowing Down

table 1


table 2


→ table 3

col1	col2	col3

→

→

→

↑

↑

**FROM:** which table?

**SELECT:** which columns?

**WHERE:** which rows?

**LIMIT:** how many rows?

# Overview: Narrowing Down

table 1


table 2


→ table 3

col1	col2	col3
A		B
C		D

Diagram illustrating the narrowing down process for table 3. Red arrows point to the first, third, and fifth rows, and the first and third columns. A grey arrow points to the second row.

**FROM:** which table?  
**SELECT:** which columns?  
**WHERE:** which rows?  
**LIMIT:** how many rows?

*a query result  
looks like a table*

col1	col3
A	B
C	D

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

SELECT  FROM  ;



# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select   
from  ;
```

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

select

from

*optional stuff*

;

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

select

from

table name

;

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

select



from boarding;

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

select

which columns

from boarding;

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

*star means all of them*

select \*  
from boarding;

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
0	1163	27	43.073655	-89.385427	1.03
1	1163	47	43.073655	-89.385427	0.11
2	1163	75	43.073655	-89.385427	0.34
3	1164	6	43.106465	-89.340021	10.59
4	1167	3	43.077867	-89.369993	3.11
5	1167	4	43.077867	-89.369993	2.23
6	1167	10	43.077867	-89.369993	0.11
7	1167	38	43.077867	-89.369993	1.36
8	1169	3	43.089707	-89.329817	18.90

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select Route, DailyBoardings  
from boarding;
```

**Result:**

Route	DailyBoardings
27	1.03
47	0.11
75	0.34
6	10.59
3	3.11
4	2.23
10	0.11
38	1.36
3	18.90

...

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from routes;
```

**Result:**

index	OBJECTID	trips_routes_route_id	route_short_name	route_url	ShapeSTLength
0	63	8052	1	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	32379.426524
1	64	8053	2	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	96906.965571
2	65	8054	3	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	76436.645644
3	66	8055	4	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	64774.133485
4	67	8056	5	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	61216.722662
5	68	8057	6	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	151142.298370
6	69	8058	7	<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>	98617.005665

...



# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**


```
select route_url  
from routes;
```

**Result:**

route_url
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>
<a href="http://www.cityofmadison.com/Metro/schedules/R...">http://www.cityofmadison.com/Metro/schedules/R...</a>

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**



# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding;
```

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
0	1163	27	43.073655	-89.385427	1.03
1	1163	47	43.073655	-89.385427	0.11
2	1163	75	43.073655	-89.385427	0.34
3	1164	6	43.106465	-89.340021	10.59
4	1167	3	43.077867	-89.369993	3.11
5	1167	4	43.077867	-89.369993	2.23
6	1167	10	43.077867	-89.369993	0.11
7	1167	38	43.077867	-89.369993	1.36
8	1169	3	43.089707	-89.329817	18.90

■ ■ ■

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80;
```

Note: SQL only has one  
equal sign for equality!

But == does work

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
732	2007	80	43.076436	-89.424388	72.82
733	2014	80	43.089239	-89.433760	99.50
735	2018	80	43.086293	-89.435043	6.23
737	2023	80	43.078800	-89.429795	100.05
738	2026	80	43.086248	-89.436661	18.45
739	2027	80	43.080259	-89.428067	4.34
740	2034	80	43.086445	-89.433772	120.73
741	2039	80	43.089158	-89.438057	86.27
742	2041	80	43.084252	-89.433487	1.56

■ ■ ■

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID;
```

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
1087	5	80	43.070947	-89.406982	317.94
1088	10	80	43.075933	-89.400154	750.61
1092	39	80	43.071895	-89.397341	628.88
1095	49	80	43.075529	-89.397191	690.92
1099	52	80	43.076131	-89.405660	243.91
1104	60	80	43.075996	-89.403660	160.42
1106	61	80	43.070893	-89.403698	154.41
1109	73	80	43.070820	-89.398650	412.10

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID DESC;
```

descending means  
biggest first

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
3341	2996	80	43.076534	-89.413067	89.16
3329	2978	80	43.076561	-89.416289	88.71
3256	2881	80	43.084225	-89.429092	12.78
3002	2442	80	43.076588	-89.419301	91.27
968	2349	80	43.078388	-89.430227	561.96
923	2267	80	43.076382	-89.419943	455.02
906	2240	80	43.078988	-89.426659	0.67

...

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID ASC;
```

ascending means  
smallest first

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
1087	5	80	43.070947	-89.406982	317.94
1088	10	80	43.075933	-89.400154	750.61
1092	39	80	43.071895	-89.397341	628.88
1095	49	80	43.075529	-89.397191	690.92
1099	52	80	43.076131	-89.405660	243.91
1104	60	80	43.075996	-89.403660	160.42
1106	61	80	43.070893	-89.403698	154.41
1109	73	80	43.070820	-89.398650	412.10

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID ASC  
limit 3;
```

only show the top N results

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
1087	5	80	43.070947	-89.406982	317.94
1088	10	80	43.075933	-89.400154	750.61
1092	39	80	43.071895	-89.397341	628.88

3 results



# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID ASC  
limit 3;
```

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
1087	5	80	43.070947	-89.406982	317.94
1088	10	80	43.075933	-89.400154	750.61
1092	39	80	43.071895	-89.397341	628.88

# SQL Queries: How to ask a DB questions

**Syntax for SELECT (case and spacing don't matter):**

```
select *  
from boarding  
where Route = 80  
order by StopID ASC  
limit 3;
```

**Result:**

index	StopID	Route	Lat	Lon	DailyBoardings
1087	5	80	43.070947	-89.406982	317.94
1088	10	80	43.075933	-89.400154	750.61
1092	39	80	43.071895	-89.397341	628.88

You can use any combination of where, order by, and limit.  
But whichever you use, they must appear in that order!

# Outline

Tabular Data: CSVs vs. Databases

Common SQL Databases

Example: Madison bus-route data

SQL: Structured Query Language

Demos

# Demo 1: How Many People Ride the Bus

Goal: add up all boardings across all bus stops/routes

## Input:

- bus.db
- use `DailyBoardings` column in `boarding` table

## Output:

- total riders

# Demo 2: West-most Bus Route


Goal: which Madison bus goes farthest west?

## Input:

- bus.db

## Output:

- route number of bus that goes farthest west



# Demo 3: Heart of Madison


Goal: what is the central-most location of all bus pickups?

## Input:

- bus.db

## Output:

- a latitude and longitude



# Demo 4: Fifa

Goal: load Fifa.csv to a SQLite DB, then query it

Queries:

- who are the youngest players?
- who are the oldest players?
- who are the five oldest players?
- how many players are from Brazil?
- who are the oldest players from Brazil?
- who are the 5 oldest players from Brazil?
- what percent of leagues have players from Brazil? `DISTINCT`

# Demo 5: Vocabulary Quiz

Goal: quiz user on words looked up while reading a Kindle

## Input (vocab.db):

- table of kindle words lookups
- table of definitions

## Output:

- random word
- real definition
- fake definitions

```
In [68]: pd.read_sql("select * from definitions limit 3", conn)
```

```
Out[68]:
```

	index	word	definition
0	0	'hood	(slang) a neighborhood
1	1	.22 caliber	of or relating to the bore of a gun (or its am...
2	2	.38 caliber	of or relating to the bore of a gun (or its am...

```
In [69]: pd.read_sql("select * from words limit 3", conn)
```

```
Out[69]:
```

	id	word	stem	lang	category	timestamp	profileid
0	en:practicing	practicing	practice	en	0	1507696967592	
1	en:melanoma	melanoma	melanoma	en	0	1508074078867	
2	en:prophylactic	prophylactic	prophylactic	en	0	1508076287957	