[220] Functions as Objects

Meena Syamkumar Mike Doescher

Cheaters caught: 0
(Through P5)
12 suspicious works for P7
(email Mike to confess)

Radical Claim:

Functions are Objects

implications:

- variables can reference functions
- lists/dicts can reference functions
- we can pass function references to other functions
- we can pass lists of function references to other functions

•

Function References (Part I)

Outline

- functions as objects
- sort

```
x = [1,2,3]
y = x

def f():
    return "hi"

g = f

z = f()
```

your notes should probably include this example, with an explanation of what each of the 5 steps do!

which line of code is most novel for us?


$$x = [1,2,3]$$

y = x

Explanation: f should reference a new function object

$$g = f$$

$$z = f()$$




$$x = [1,2,3]$$

y = x

Explanation: f should reference a new function object



$$g = f$$



$$x = [1,2,3]$$

y = x


Explanation: f should reference a new function object



$$g = f$$

$$z = f()$$

Explanation: g should reference whatever f references



$$x = [1,2,3]$$


y = x

Explanation: f should reference a new function object

$$q = f$$

Explanation: g should reference whatever f references






$$x = [1,2,3]$$

y = x

$$g = f$$



both of these calls would have run the same code, returning the same result:

•
$$z = f()$$

$$\bullet$$
 z = g()


Explanation: x should reference a new list object

Explanation: y should reference whatever x references

Explanation: f should reference a new function object

Explanation: g should reference whatever f references

Explanation: z should reference whatever f returns



z = f()

very similar (reference new object)

very similar (reference existing object)

CODING DEMOS [Python Tutor]

Function References (Part I)

Outline

- functions as objects
- sort

List of tuples:

```
names = [
    ("Catherine", "Baker"),
    ("Alice", "Clark"),
    ("Bob", "Adams"),
]
```

Catherine	Baker
Bob	Adams
Alice	Clark

List of tuples:

```
names = [
    ("Catherine", "Baker"),
    ("Alice", "Clark"),
    ("Bob", "Adams"),
]
```

```
Catherine Baker

Bob Adams

Alice Clark
```



names	•	SOI	r.	t	()
-------	---	-----	----	---	---	---


sorting tuples is done
 on first element
 (ties go to 2nd element)

Alice	Clark
Bob	Adams
Catherine	Baker

List of tuples:

```
names = [
    ("Catherine", "Baker"),
    ("Alice", "Clark"),
    ("Bob", "Adams"),
]
```

Catherine	Baker
Bob	Adams
Alice	Clark



names.sort()

what if we want to sort by the last name?

or by the length of the name?

Alice	Clark
Bob	Adams
Catherine	Baker

List of tuples:

```
names = [
    ("Catherine", "Baker"),
    ("Alice", "Clark"),
    ("Bob", "Adams"),
]

def extract(name_tuple):
    return name_tuple[1]
names.sort(key=extract)
```

Catherine	Baker
Bob	Adams
Alice	Clark



Bob	Adams
Catherine	Baker
Alice	Clark


List of tuples:

```
names = [
    ("Catherine", "Baker"),
    ("Alice", "Clark"),
    ("Bob", "Adams"),
]

def extract(name_tuple):
    return len(name_tuple[0])

names.sort(key=extract)
```

Catherine	Baker
Bob	Adams
Alice	Clark



Bob	Adams
Alice	Clark
Catherine	Baker