



FACE ATTENDANCE CHECKING

Course: EE3063 - Dr. Pham Viet Cuong

Conducted by Group 09


21/11/2018




Content

- Problem definition
- Literature review
- Implementation
- Experimental results
- Demo


Problem definition



Problem definition



Problem definition



Problem definition

Constraints:

- Single face
- Frontal view
- Standard webcam (480x640)
- Open-set recognition

Members

<https://github.com/AntiAegis/Face-Attendance-System>


Literature review

A. Relative works


1. Face Detection and Alignment

The face detector proposed by Viola and Jones used Haar-Like features and AdaBoost algorithm to train cascaded classifiers




1. Edge features



2. Line features




3. Center-surround features





Literature review

A Convolutional Neural Network Cascade for Face Detection



Literature review

Multi-task Convolutional Network



The learning objective is formulated as a regression problem, and the Euclidean loss:

$$L_i^{box} = \|y_i^{prediction} - y_i^{truth}\|_2^2$$

Literature review



A. Relative works

2. Face Recognition

Method	Net. Loss	Outside data	# models	Aligned	Verif. metric	Layers	Accu.
DeepFace [97]	ident.	4M	4	3D	wt. chi-sq.	8	97.35 \pm 0.25
Canon. view CNN [115]	ident.	203K	60	2D	Jt. Bayes	7	96.45 \pm 0.25
DeepID [92]	ident.	203K	60	2D	Jt. Bayes	7	97.45 \pm 0.26
DeepID2 [88]	ident. + verif.	203K	25	2D	Jt. Bayes	7	99.15 \pm 0.13
DeepID2+ [93]	ident. + verif.	290K	25	2D	Jt. Bayes	7	99.47 \pm 0.12
DeepID3 [89]	ident. + verif.	290K	25	2D	Jt. Bayes	10-15	99.53 \pm 0.10
Face++ [113]	ident.	5M	1	2D	L2	10	99.50 \pm 0.36
FaceNet [82]	verif. (triplet)	260M	1	no	L2	22	99.60 \pm 0.09
Tencent [8]	-	1M	20	yes	Jt. Bayes	12	99.65 \pm 0.25

Literature review


Deep Learning Face Representation from Predicting 10,000 Classes (DeepID 1)




One CNN for a feature extractor. 60 CNNs in total.

Literature review

DeepID 2 (NIPS 2014)




Patches selected for feature extraction




Literature review

FaceNet




Literature review

B. Proposal Model



Implementation




System pipeline

Implementation

Blur detection




FFT-2D




Implementation

Face detection (based on Histogram Of Gradient)




gradient

HOG face pattern generated
from lots of face images





HOG version of our image



Implementation

Landmark detection




Implementation

Landmark detection



Regressor



Implementation

Landmark detection




Cascaded regressors

Regressor1

Regressor2


...

RegressorN





Implementation

Face recognition




Implementation


Face recognition (based on FaceNet)



Experimental results





Visualization using PCA




Visualization using t-SNE

Experimental results



Experimental results



Experimental results



DANH SÁCH SINH VIÊN					
TRÍ TUỆ NHÂN TẠO TRONG ĐIỀU KHIỂN					
			1 = present		
			blank = absent		
ID	Last Name	First Name	Group	09/06/2018	Total
1511844	Lương Hữu Phú	Lộc	1		1
1512221	Phạm Ngọc Khởi	Nguyên	1	1	0
1512396	Bùi Tấn	Phát	1		1
1512534	Nguyễn Trọng	Phúc	1	1	0

Demo

Conclusion

Hard:

- Face Attendance Checking
- Deep-learning based
- Standard hardware
- High accuracy
- Easy-use GUI

Soft:

- Specialized-task assignment
- GitHub: store, collaborate, refer
- Open-source: MIT license
- Scientific-form paper report
- Unity

Acknowledge

- Dr. Pham Viet Cuong: promote a chance.
- Course-EE3063 students: donate data.