

ASTM D3034 SEWER GASKET BELL SDR 26 and SDR 35

MANUFACTURER'S CERTIFICATION

This is to certify the pipe manufactured by Sanderson Pipe Corporation meets or exceeds the applicable engineering standards listed under ASTM D3034.

- 1. Materials: Comply with ASTM D1784 standard, cell classification 12454 or 12364.
- 2. **Dimensions / Testing:** All pipe meets or exceeds all performance specifications set forth in the current version of the ASTM D3034 standard.
- Markings on the Pipe: Identification of nominal pipe size, cell classification, SDR class, ASTM designation D3034, material code, manufacturer's name and code.
 Additional labeling on the SDR 26 sewer series includes the words: "Heavy Wall Sewer Pipe".
- 4. **Gaskets**: All gaskets used in the pipe meet ASTM F477 standards.

Manufactured in the USA

Revised Date: October 03, 2014

ASTM D3034 SDR 26 (GREEN) SEWER GASKET BELL SPECIFICATIONS

Pipe	Outside	SDR 26	**Bell	*Bell	**Reference	Approx.
Size	Diameter	Minimum	Length	Diameter	Mark	Weight
	(OD)	Wall	(inches)	(inches)	(inches)	per foot
						(lbs.)
4"	4.215	0.162	5"	5.044	4"	1.450
6"	6.275	0.241	5 3/4"	7.300	4 1/2"	3.346
8"	8.400	0.323	7"	9.641	5 3/4"	5.889
10"	10.500	0.404	7 1/2"	12.124	6"	9.245
12"	12.500	0.481	8"	14.195	6 ½"	13.325
15"	15.300	0.588	7 ½"	17.330	6"	19.629

Notes:

Labeled "Heavy Wall Sewer Pipe"

Pipe made in 14-foot lay lengths.

^{*} Approximate Bell Diameter

^{**} May vary up to <u>+</u> ½"

ASTM D3034 SDR 35 (GREEN) SEWER GASKET BELL SPECIFICATIONS

Pipe	Outside	SDR 35	**Bell	*Bell	**Reference	Approx.
Size	Diameter	Minimum	Length	Diameter	Mark	Weight
	(OD)	Wall	(inches)	(inches)	(inches)	per foot
						(lbs.)
4"	4.215	0.120	5"	4.983	4"	1.127
6"	6.275	0.180	5 3/4"	7.220	4 1/2"	2.528
8"	8.400	0.240	7"	9.548	5 3/4"	4.436
10"	10.500	0.300	7 ½"	11.941	6"	7.375
12"	12.500	0.360	8"	14.025	6 ½"	10.125
15"	15.300	0.437	7 1/2"	17.132	6"	15.027

Notes:

Pipe made in 14-foot lay lengths.

^{*} Approximate Bell Diameter

^{**} May vary up to <u>+</u> ½"