JP WORK uTest random (Channel) -... Усі закла

токену

а нового Access-токену.
{refresh_token}`.

Cancel

SUzI1NiJ9.eyJpc3MiOiJja

Clear

.koyeb.app/refresh-token' \
eyJpc3MiOiJjaGF0LWVuZ2x5Iiwic3ViIjoiNzV1c2VyYnVzaWFAZ21haWwuY29tIiwiZXhwIjoxNzQxMTE5OTI1LCJpYXQiOjE3

oyeb.app/refresh-token

933+00:00",

Download

true
://favourable-rodie-java-service-b82e5859.koyeb.app

Project CHAT / ... / Оновлення Acc... / POST/refresh-token invalid data

POST https://favourable-rodie-java-service-b82e5859.koyeb.app

Params Auth Headers (10) Body Scripts Settings

Auth Type

Bearer Token

The authorization header will be automatically generated when you send the request. Learn more about Bearer Token authorization.

Heads up! These parameters hold sensitive
secure while working in a collaborative env
using variables. Learn more about variables

Token

Jh
GF
vb
aW
wZ
N8
LP
qi
aq
V8
Hb
e2
0fc
rsr

Body 500 Internal Server Error 399 ms 70

JSON Preview Visualize


```
{
    "timestamp": "2025-03-06T07:48:47.034+00:00",
    "status": 500,
    "error": "Internal Server Error",
    "path": "/refresh-token"
}
```