

# SDL\_bgi 2.4.2 Quick Reference

Guido Gonzato, PhD

November 11, 2020



## Contents

<b>1</b>	<b>Introduction to SDL_bgi</b>	<b>3</b>	<b>getactivepage()</b>	11
1.1	Constants	4	getarccords()	12
1.2	Structs	8	getaspectratio()	12
1.3	Environment Variables	9	getbkcolor()	12
1.4	Colours	9	getcolor()	12
1.5	Fonts	9	getdefaultpalette()	12
1.6	Note for SDL2 Programmers	9	getdrivername()	12
			getfillpattern()	12
			getfillsettings()	12
<b>2</b>	<b>Standard BGI Graphics Functions</b>	<b>10</b>	getgraphmode()	12
	arc()	10	getimage()	13
	bar()	10	getlinesettings()	13
	bar3d()	10	getmaxcolor()	13
	circle()	10	getmaxmode()	13
	cleardevice()	10	getmaxx()	13
	clearviewport()	11	getmaxy()	13
	closegraph()	11	getmodename()	13
	detectgraph()	11	getmoderange()	13
	drawpoly()	11	getpalette()	13
	ellipse()	11	getpalettesize()	13
	fillellipse()	11	getpixel()	14
	fillpoly()	11	gettextsettings()	14
	floodfill()	11	getviewsettings()	14

getvisualpage()	14	setvisualpage()	19
getx()	14	setwritemode()	19
gety()	14	textheight()	19
graphdefaults()	14	textwidth()	19
grapherrormsg()	14		
graphresult()	14	<b>3 Non-Graphics Functions and Macros</b>	<b>19</b>
imagesize()	15	getch()	20
initgraph()	15	kbhit()	20
installuserdriver()	15	random()	20
installuserfont()	15		
line()	15	<b>4 SDL_bgi Additions</b>	<b>20</b>
linereel()	16	ALPHA_VALUE()	20
lineto()	16	BLUE_VALUE()	20
moverel()	16	COLOR()	20
moveto()	16	COLOR32()	20
outtext()	16	colorRGB()	21
outtextxy()	16	GREEN_VALUE()	21
pieslice()	16	IS_BGI_COLOR()	21
putimage()	16	IS_RGB_COLOR()	21
putpixel()	16	RED_VALUE()	21
rectangle()	16	_putpixel()	21
registerbgidriver()	17	closewindow()	21
registerbgifont()	17	event()	22
restorecrtmode()	17	eventtype()	22
sector()	17	getbuffer()	22
setactivepage()	17	getcurrentwindow()	22
setallpalette()	17	getleftclick()	22
setaspectratio()	17	getevent()	22
setbkcolor()	17	getlinebuffer()	22
setcolor()	17	getmiddleclick()	22
setfillpattern()	17	getmaxheight()	22
setfillstyle()	18	getmaxwidth()	23
setgraphbufsize()	18	getmouseclick()	23
setgraphmode()	18	getrightclick()	23
setlinestyle()	18	getscreenSize()	23
setpalette()	18	initpalette()	23
settextjustify()	18	initwindow()	23
settextstyle()	18	ismouseclick()	23
setusercharsize()	19	mouseclick()	23
setviewport()	19	mousex()	23

<code>mousey()</code> . . . . .	24	<code>setbkrgbcolor()</code> . . . . .	25
<code>putbuffer()</code> . . . . .	24	<code>setblendmode()</code> . . . . .	25
<code>putlinebuffer()</code> . . . . .	24	<code>setcurrentwindow()</code> . . . . .	25
<code>readimagefile()</code> . . . . .	24	<code>setrgbcolor()</code> . . . . .	25
<code>refresh()</code> . . . . .	24	<code>setrgbpalette()</code> . . . . .	25
<code>resetwinoptions()</code> . . . . .	24	<code>setwinoptions()</code> . . . . .	25
<code>resizepalette()</code> . . . . .	24	<code>showerrorbox()</code> . . . . .	26
<code>sdlbgiauto()</code> . . . . .	24	<code>showinfobox()</code> . . . . .	26
<code>sdlbgifast()</code> . . . . .	25	<code>swapbuffers()</code> . . . . .	26
<code>sdlbgislow()</code> . . . . .	25	<code>writeimagefile()</code> . . . . .	26
<code>setalpha()</code> . . . . .	25	<code>xkbhit()</code> . . . . .	26

## 1 Introduction to SDL\_bgi

SDL\_bgi is a multiplatform, fast, SDL2-based implementation of BGI: the Borland Graphics Interface also known as `GRAPHICS.H`. BGI was a graphics library provided by Borland Turbo C / Borland C++ compilers for DOS, and it was very popular in the late eighties–early nineties. It became the *de facto* standard for computer graphics, especially in education. For more information, please see [https://en.wikipedia.org/wiki/Borland\\_Graphics\\_Interface](https://en.wikipedia.org/wiki/Borland_Graphics_Interface).

However, SDL\_bgi is not meant to be just a replica of BGI; it aims to be a functionally equivalent superset. It provides many extensions for ARGB colours, multiple windows, bitmap and vector fonts, and mouse support. SDL\_bgi implements nearly all extensions provided by another popular BGI implementation, WinBGIm, and adds several more. Please see <http://www.codecutter.net/tools/winbgim> for more information on WinBGIm.

SDL\_bgi is one of the easiest libraries to do graphics programming in C. It is much simpler to use than SDL2, OpenGL and the like; obviously, it's less complete. Teachers may find SDL\_bgi a useful tool for introductory computer graphics courses.

This is a minimal program that opens a window and draws 1000 random lines:

```
#include <graphics.h>

int main (int argc, char *argv[])
{
    int i, gd = DETECT, gm;
    initgraph (&gd, &gm, "");
    setbkcolor (BLACK);
    cleardevice ();
    outtextxy (0, 0, "Drawing 1000 lines...");
    for (i = 0; i < 1000; i++) {
        setcolor (1 + random (15));
        line (random(getmaxx()), random(getmaxy()),
            random (getmaxx()), random(getmaxy()) );
    }
    getch ();
}
```

```

    closegraph ();
    return 0;
}

```

The program includes the header file `graphics.h`, which in turn includes `SDL_bgi.h` that contains all necessary definitions. The call to `initgraph()` opens a window; from now on, graphics functions may be called. `closegraph()` closes the window.

Within the window, pixel coordinates range from (0, 0), the upper left corner, to (`getmaxx()`, `getmaxy()`), the lower right corner.

Some graphic functions set the coordinates of the last drawing position, defined as CP (Current Position). At any given moment, a foreground, background and fill colour, line style, line thickness, and fill pattern, are defined. A viewport (subwindow) may also be defined, with or without clipping. All of these parameters can be changed using appropriate functions.

## 1.1 Constants

Many constants are defined in `SDL_bgi.h`. The most important are the following:

```

#ifndef _SDL_BGI_H
#define _SDL_BGI_H

#ifndef __GRAPHICS_H
#define __GRAPHICS_H

// SDL2 stuff
#include <SDL2/SDL.h>
#include <SDL2/SDL_keycode.h>
#include <SDL2/SDL_mouse.h>

#include <stdio.h>    // for fprintf()
#include <stdlib.h>   // for exit(), calloc()
#include <math.h>     // for sin(), cos()
#include <string.h>   // for strlen(), memcpy()

#define SDL_BGI_VERSION 2.4.2

enum { NOPE, YEAH } ;
#define BGI_WINTITLE_LEN 512 // more than enough

// number of concurrent windows that can be created

#define NUM_BGI_WIN 16

// everything gets drawn here

extern SDL_Window    *bgi_window;
extern SDL_Renderer  *bgi_renderer;
extern SDL_Texture    *bgi_texture;
extern Uint32         PALETTE_SIZE;

// available visual pages

```

```

#define VPAGES 4

// BGI fonts

enum {
    DEFAULT_FONT,      // 8x8 bitmap
    TRIPLEX_FONT,      // trip.h
    SMALL_FONT,        // litt.h
    SANS_SERIF_FONT,   // sans.h
    GOTHIC_FONT,       // goth.h
    SCRIPT_FONT,       // scri.h
    SIMPLEX_FONT,      // simp.h
    TRIPLEX_SCR_FONT,  // tscr.h
    COMPLEX_FONT,      // lcom.h
    EUROPEAN_FONT,    // euro.h
    BOLD_FONT,         // bold.h
    LAST_SPEC_FONT
};

enum { HORIZ_DIR, VERT_DIR };

#define USER_CHAR_SIZE 0

enum {
    LEFT_TEXT, CENTER_TEXT, RIGHT_TEXT,
    BOTTOM_TEXT = 0, TOP_TEXT = 2
};

// BGI colours, including CGA and EGA palettes

enum {
    BLACK      = 0,          EGA_BLACK      = 0,
    BLUE       = 1,          EGA_BLUE       = 1,
    GREEN      = 2,  CGA_GREEN      = 2,  EGA_GREEN      = 2,
    CYAN       = 3,  CGA_CYAN       = 3,  EGA_CYAN       = 3,
    RED        = 4,  CGA_RED        = 4,  EGA_RED        = 4,
    MAGENTA    = 5,  CGA_MAGENTA    = 5,  EGA_MAGENTA    = 5,
    BROWN     = 6,  CGA_BROWN     = 6,  EGA_BROWN     = 6,
    LIGHTGRAY  = 7,  CGA_LIGHTGRAY  = 7,  EGA_LIGHTGRAY  = 7,
    DARKGRAY   = 8,          EGA_DARKGRAY   = 8,
    LIGHTBLUE  = 9,          EGA_LIGHTBLUE  = 9,
    LIGHTGREEN = 10, CGA_LIGHTGREEN = 10, EGA_LIGHTGREEN = 10,
    LIGHTCYAN  = 11, CGA_LIGHTCYAN  = 11, EGA_LIGHTCYAN  = 11,
    LIGHTRED   = 12, CGA_LIGHTRED   = 12, EGA_LIGHTRED   = 12,
    LIGHTMAGENTA = 13, CGA_LIGHTMAGENTA = 13, EGA_LIGHTMAGENTA = 13,
    YELLOW     = 14, CGA_YELLOW     = 14, EGA_YELLOW     = 14,
    WHITE      = 15, CGA_WHITE      = 15, EGA_WHITE      = 15,
    MAXCOLORS  = 15
};

// ARGB colours, set by COLOR ()

enum {
    ARGB_FG_COL  = 16,
    ARGB_BG_COL  = 17,
    ARGB_FILL_COL = 18,
    ARGB_TMP_COL  = 19,
    TMP_COLORS    = 4
};

```

```

};

// line style, thickness, and drawing mode

enum { NORM_WIDTH = 1, THICK_WIDTH = 3 };

enum { SOLID_LINE, DOTTED_LINE, CENTER_LINE, DASHED_LINE, USERBIT_LINE };

enum { COPY_PUT, XOR_PUT, OR_PUT, AND_PUT, NOT_PUT };

// fill styles

enum {
    EMPTY_FILL, SOLID_FILL, LINE_FILL, LTSLASH_FILL, SLASH_FILL,
    BKSLASH_FILL, LTBKSLASH_FILL, HATCH_FILL, XHATCH_FILL,
    INTERLEAVE_FILL, WIDE_DOT_FILL, CLOSE_DOT_FILL, USER_FILL
};

// mouse buttons

#define WM_LBUTTONDOWN    SDL_BUTTON_LEFT
#define WM_MBUTTONDOWN    SDL_BUTTON_MIDDLE
#define WM_RBUTTONDOWN    SDL_BUTTON_RIGHT
#define WM_WHEEL          SDL_MOUSEWHEEL
#define WM_WHEELUP        SDL_USEREVENT
#define WM_WHEELDOWN      SDL_USEREVENT + 1
#define WM_MOUSEMOVE      SDL_MOUSEMOTION

// keys
#define KEY_HOME          SDLK_HOME
#define KEY_LEFT          SDLK_LEFT
#define KEY_UP            SDLK_UP
#define KEY_RIGHT         SDLK_RIGHT
#define KEY_DOWN          SDLK_DOWN
#define KEY_PGUP          SDLK_PAGEUP
#define KEY_PGDN          SDLK_PAGEDOWN
#define KEY_END           SDLK_END
#define KEY_INSERT        SDLK_INSERT
#define KEY_DELETE        SDLK_DELETE
#define KEY_F1            SDLK_F1
#define KEY_F2            SDLK_F2
#define KEY_F3            SDLK_F3
#define KEY_F4            SDLK_F4
#define KEY_F5            SDLK_F5
#define KEY_F6            SDLK_F6
#define KEY_F7            SDLK_F7
#define KEY_F8            SDLK_F8
#define KEY_F9            SDLK_F9
#define KEY_F10           SDLK_F10
#define KEY_F11           SDLK_F11
#define KEY_F12           SDLK_F12
#define KEY_CAPSLOCK      SDLK_CAPSLOCK
#define KEY_LEFT_CTRL     SDLK_LCTRL
#define KEY_RIGHT_CTRL    SDLK_RCTRL
#define KEY_LEFT_SHIFT    SDLK_LSHIFT
#define KEY_RIGHT_SHIFT   SDLK_RSHIFT
#define KEY_LEFT_ALT      SDLK_LALT
#define KEY_RIGHT_ALT     SDLK_RALT

```

```

#define KEY_ALT_GR      SDLK_MODE
#define KEY_LGUI        SDLK_LGUI
#define KEY_RGUI        SDLK_RGUI
#define KEY_MENU        SDLK_MENU
#define KEY_TAB         SDLK_TAB
#define KEY_BS          SDLK_BACKSPACE
#define KEY_RET         SDLK_RETURN
#define KEY_PAUSE       SDLK_PAUSE
#define KEY_SCR_LOCK    SDLK_SCROLLLOCK
#define KEY_ESC         SDLK_ESCAPE

#define QUIT            SDL_QUIT

// graphics modes. Expanded from the original GRAPHICS.H

enum {
    DETECT = -1,
    SDL = 0,
    // all modes @ 320x200
    SDL_320x200 = 1, SDL_CGALO = 1, CGA = 1, CGACO = 1, CGAC1 = 1,
    CGAC2 = 1, CGAC3 = 1, MCGACO = 1, MCGAC1 = 1, MCGAC2 = 1,
    MCGAC3 = 1, ATT400C0 = 1, ATT400C1 = 1, ATT400C2 = 1, ATT400C3 = 1,
    // all modes @ 640x200
    SDL_640x200 = 2, SDL_CGAHI = 2, CGAHI = 2, MCGAMED = 2,
    EGALO = 2, EGA64LO = 2,
    // all modes @ 640x350
    SDL_640x350 = 3, SDL_EGA = 3, EGA = 3, EGAHI = 3,
    EGA64HI = 3, EGAMONHI = 3,
    // all modes @ 640x480
    SDL_640x480 = 4, SDL_VGA = 4, VGA = 4, MCGAHI = 4, VGAHI = 4,
    IBM8514LO = 4,
    // all modes @ 720x348
    SDL_720x348 = 5, SDL_HERC = 5,
    // all modes @ 720x350
    SDL_720x350 = 6, SDL_PC3270 = 6, HERCMONHI = 6,
    // all modes @ 800x600
    SDL_800x600 = 7, SDL_SVGALO = 7, SVGA = 7,
    // all modes @ 1024x768
    SDL_1024x768 = 8, SDL_SVGAMED1 = 8,
    // all modes @ 1152x900
    SDL_1152x900 = 9, SDL_SVGAMED2 = 9,
    // all modes @ 1280x1024
    SDL_1280x1024 = 10, SDL_SVGAHI = 10,
    // all modes @ 1366x768
    SDL_1366x768 = 11, SDL_WXGA = 11,
    // other
    SDL_USER = 12, SDL_FULLSCREEN = 13
};

// error messages
enum graphics_errors {
    grOk = 0,
    grNoInitGraph = -1,
    grNotDetected = -2,
    grFileNotFound = -3,
    grInvalidDriver = -4,
    grNoLoadMem = -5,
    grNoScanMem = -6,

```

```

    grNoFloodMem      = -7,
    grFontNotFound    = -8,
    grNoFontMem       = -9,
    grInvalidMode     = -10,
    grError           = -11,
    grIOerror         = -12,
    grInvalidFont     = -13,
    grInvalidFontNum  = -14,
    grInvalidVersion  = -18
};

```

## 1.2 Structs

Some of the BGI functions use the following structs:

```

struct arccoordstype {
    int x;
    int y;
    int xstart;
    int ystart;
    int xend;
    int yend;
};

struct date {
    int da_year;
    int da_day;
    int da_mon;
};

struct fillsettingstype {
    int pattern;
    int color;
};

struct linesettingstype {
    int linestyle;
    unsigned int upattern;
    int thickness;
};

struct palettetype {
    unsigned char size;
    // signed char in Turbo C / Borland C++
    Uint32 colors[MAXCOLORS + 1];
};

struct textsettingstype {
    int font;
    int direction;
    int charsize;
    int horiz;
    int vert;
};

```



```

struct viewporttype {
    int left;
    int top;
    int right;
    int bottom;
    int clip;
};

```

### 1.3 Environment Variables

**SDL\_BGI\_RES**: when set to **VGA**, default resolution will be  $640 \times 480$  instead of  $800 \times 600$ . Please see `initgraph()` (page 15) for details.

**SDL\_BGI\_RATE**: when set to **auto**, automatic screen refresh will be performed. Please see `initgraph()` (page 15) for details.

**SDL\_BGI\_PALETTE**: when set to **BGI**, the first 16 colours will use the same RGB values as Turbo C 2.01. Please see `initpalette()` (page 23) for details.

### 1.4 Colours

The default BGI palette includes 16 named colours (**BLACK... WHITE**); standard functions like `setbkcolor()` or `setcolor()` use this palette.

An extended ARGB palette of **PALETTE\_SIZE** additional colours can be created and accessed using functions like `setbkrgbcolor()` or `setrbgcolor()` described below. The palette can be resized using `resizepalette()`.

Constants **ARGB\_FG\_COL**, **ARGB\_BG\_COL**, **ARGB\_FILL\_COL**, and **ARGB\_TMP\_COL** denote the foreground, background, fill, and temporary ARGB colours that can be set with the `COLOR()` function described below.

### 1.5 Fonts

**SDL\_bgi** provides an  $8 \times 8$  bitmap font and vector fonts decoded from original **.CHR** files; loading **.CHR** fonts from disk is also possible. Please see `settextstyle()` (page 18) for details.

**.CHR** font supported was added by Marco Diego Aurélio Mesquita.

### 1.6 Note for SDL2 Programmers

The following variables are declared in **SDL\_bgi.h**, and are accessible to the programmer:

```

SDL_Window    *bgi_window;
SDL_Renderer  *bgi_renderer;
SDL_Texture   *bgi_texture;

```

and can be used by native SDL2 functions. That is, you can use BGI and native SDL2 functions together, as in the following code snippet:

```
SDL_Surface *bitmap;  
SDL_Texture *texture;  
...  
bitmap = SDL_LoadBMP ("picture.bmp");  
texture = SDL_CreateTextureFromSurface (bgi_renderer, bitmap);  
SDL_RenderCopy (bgi_renderer, texture, NULL, NULL);  
SDL_RenderPresent (bgi_renderer);  
...
```

## 2 Standard BGI Graphics Functions

The following are standard BGI functions, as implemented for example in Turbo C. They are all prototyped in `SDL_bgi.h`.

Unless otherwise specified, graphics routines draw shapes using the current drawing colour, i.e. as specified by `setcolor()`.

```
void arc (int x, int y, int stangle, int endangle, int radius);
```

Draws a circular arc centered at  $(x, y)$ , with a radius given by *radius*, traveling from *stangle* to *endangle*. The angle for `arc()` is measured counterclockwise, with 0 degrees at 3 o' clock, 90 degrees at 12 o' clock, etc.

**Note:** The *linestyle* parameter does not affect arcs, circles, ellipses, or pieslices. Only the *thickness* parameter is used.

```
void bar (int left, int top, int right, int bottom);
```

Draws a filled-in rectangle (bar), using the current fill colour and fill pattern. The bar is not outlined; to draw an outlined two-dimensional bar, use `bar3d()` with *depth* equal to 0.

```
void bar3d (int left, int top, int right, int bottom, int depth, int topflag);
```

Draws a three-dimensional, filled-in rectangle (bar), using the current fill colour and fill pattern. The three-dimensional outline of the bar is drawn in the current line style and colour. The bar's depth, in pixels, is given by *depth*. If *topflag* is nonzero, a top is put on.

```
void circle (int x, int y, int radius);
```

Draws a circle of the given *radius* at  $(x, y)$ .

**Note:** The *linestyle* parameter does not affect arcs, circles, ellipses, or pieslices. Only the *thickness* parameter is used.

```
void cleardevice (void);
```

Clears the graphics screen, filling it with the current background colour. The CP is moved to (0, 0).

```
void clearviewport (void);
```

Clears the viewport, filling it with the current background colour. The CP is moved to (0, 0), relative to the viewport.

```
void closegraph (void);
```

Closes the graphics system.

```
void detectgraph (int *graphdriver, int *graphmode);
```

Detects the graphics driver and default graphics mode to use; `SDL` and `SDL_FULLSCREEN`, respectively.

```
void drawpoly (int numpoints, int *polypoints);
```

Draws a polygon of *numpoints* vertices. *polypoints* is a pointer to a sequence of (2 \* *numpoints*) integers; each pair gives the *x* and *y* coordinate of each vertex.

```
void ellipse (int x, int y, int stangle, int endangle, int xradius, int yradius);
```

Draws an elliptical arc centered at (*x*, *y*), with axes given by *xradius* and *yradius*, traveling from *stangle* to *endangle*.

```
void fillellipse (int x, int y, int xradius, int yradius);
```

Draws an ellipse centered at (*x*, *y*), with axes given by *xradius* and *yradius*, and fills it using the current fill colour and fill pattern.

```
void fillpoly (int numpoints, int *polypoints);
```

Draws a polygon of *numpoints* vertices and fills it using the current fill colour.

```
void floodfill (int x, int y, int border);
```

Fills an enclosed area, containing the *x* and *y* points bounded by the *border* colour. The area is filled using the current fill colour.

```
int getactivepage (void);
```

Returns the active page number.

```
void getarccoords (struct arccoordstype *arccoords);
```

Gets the coordinates of the last call to `arc()`, filling the *arccoords* structure.

```
void getaspectratio (int *xasp, int *yasp);
```

Retrieves the current graphics mode's aspect ratio. In `SDL_bgi`, *xasp* and *yasp* are both 10000 (i.e. pixels are squares).

```
int getbkcolor (void);
```

Returns the current background colour in the default palette. If the background colour was set by `COLOR`, `getbkcolor` returns -1.

```
int getcolor (void);
```

Returns the current drawing (foreground) colour in the default palette. If the foreground colour was set by `COLOR`, `getcolor` returns -1.

```
struct palettetype *getdefaultpalette (void);
```

Returns the palette definition structure.

```
char *getdrivername (void);
```

Returns a pointer to a string containing the name of the current graphics driver.

```
void getfillpattern (char *pattern);
```

Copies the user-defined fill pattern, as set by `setfillpattern`, into the 8-byte area pointed to by *pattern*.

```
void getfillsettings (struct fillsettingstype *fillinfo);
```

Fills the `fillsettingstype` structure pointed to by *fillinfo* with information about the current fill pattern and fill colour.

```
int getgraphmode (void);
```

Returns the current graphics mode.

```
void getimage (int left, int top, int right, int bottom, void *bitmap);
```

Copies a bit image of the specified region into the memory pointed by *bitmap*.

```
void getlinesettings (struct linesettingstype *lineinfo);
```

Fills the `linesettingstype` structure pointed by *lineinfo* with information about the current line style, pattern, and thickness.

```
int getmaxcolor (void);
```

Returns the maximum colour value available (`MAXCOLORS`) in the default palette. If ARGB colours are being used, it returns `PALETTE_SIZE`.

```
int getmaxmode (void);
```

Returns the maximum mode number for the current driver. In `SDL_bgi`, the default is `SDL_FULLSCREEN`.

```
int getmaxx (void);
```

Returns the maximum *x* screen coordinate.

```
int getmaxy (void);
```

Returns the maximum *y* screen coordinate.

```
char* getmodename (int mode_number);
```

Returns a pointer to a string containing the name of the specified graphics mode.

```
void getmoderange (int graphdriver, int *lomode, int *himode);
```

Gets the range of valid graphics modes. The *graphdriver* parameter is ignored.

```
void getpalette (struct palettetype *palette);
```

Fills the `palettetype` structure pointed by *palette* with information about the current palette's size and colours.

```
int getpalettesize (void);
```

Returns the size of the palette (`MAXCOLORS + 1` or `MAXRGBCOLORS + 1`).

```
int getpixel (int x, int y);
```

Returns the colour of the pixel located at (*x*, *y*).

```
void gettextsettings (struct textsettingstype *textypeinfo);
```

Fills the `textsettingstype` structure pointed to by *textypeinfo* with information about the current text font, direction, size, and justification.

```
void getviewsettings (struct viewporttype *viewport);
```

Fills the `viewporttype` structure pointed to by *viewport* with information about the current viewport.

```
int getvisualpage (void);
```

Returns the visual page number.

```
int getx (void);
```

Returns the current viewport's *x* coordinate.

```
int gety (void);
```

Returns the current viewport's *y* coordinate.

```
void graphdefaults (void);
```

Resets all graphics settings to their defaults: sets the viewport to the entire screen, moves the CP to (0, 0), sets the default palette colours, the default drawing and background colour, the default fill style and pattern, the default text font and justification.

```
char* grapherrormsg (int errorcode);
```

Returns a pointer to the error message string associated with *errorcode*, returned by `graphresult()`.

```
int graphresult (void);
```

Returns the error code for the last unsuccessful graphics operation and resets the error level to grOk.

```
unsigned imagesize (int left, int top, int right, int bottom);
```

Returns the size in bytes of the memory area required to store a bit image.

```
void initgraph (int *graphdriver, int *graphmode, char *pathtodriver);
```

Initializes the graphics system. In `SDL.bgi`, you can use `SDL` as *graphdriver*, then choose a suitable graphics mode (listed in `graphics.h`) as *graphmode*. The *pathtodriver* argument is ignored. Typically, *graphdriver* is set to `DETECT`, and *graphmode* is not set; these values will set the default resolution ( $800 \times 600$ ) as `SVGA`. If the environment variable `SDL_BGI_RES` equals `VGA` or `vga`, then VGA resolution ( $640 \times 480$ ) will be forced.

You can also use `NULL` for *\*graphdriver* and *\*graphmode* to get the default resolution ( $800 \times 600$ ), or use `detectgraph` (see above) to get fullscreen.

Multiple windows can be created, unless a fullscreen window is already present.

Using `initgraph()`, the default 16-colour palette uses the same ARGB values as the original palette in Turbo C. Using `initwindow()`, the default 16-colour palette uses different (possibly, better-looking) ARGB values.

After `initgraph()`, all graphics commands are immediately displayed, as in the original BGI. This could make drawing very slow; you may want to use `initwindow()` instead.

Alternatively, automatic screen refresh can be performed according to the value of the `SDL_BGI_RATE` environment variable. If the variable is set to `auto`, screen refresh is automatically performed every *msec* milliseconds; this value is the current screen refresh rate, as given by `SDL.GetDisplayMode()`. If the variable is set to an integer value *msec*, automatic screen refresh will be performed every *msec* milliseconds.

Automatic screen refresh is much faster than the default behaviour; however, it is an experimental feature that may not work on some graphic cards.

```
int installuserdriver (char *name, int (*detect)(void));
```

Unimplemented; not used by `SDL.bgi`.

```
int installuserfont (char *name);
```

Loads and installs a `.CHR` font from disk. The function returns an integer to be used as first argument in `settextstyle`.

*Note:* font metrics of loaded `.CHR` files are not pixel-perfect yet. This function does not work on Windows.

```
void line (int x1, int y1, int x2, int y2);
```

Draws a line between two specified points; the CP is not updated.

```
void linerel (int dx, int dy);
```

Draws a line from the CP to a point that is  $(dx, dy)$  pixels from the CP. The CP is then advanced by  $(dx, dy)$ .

```
void lineto (int x, int y);
```

Draws a line from the CP to  $(x, y)$ , then moves the CP to  $(dx, dy)$ .

```
void moverel (int dx, int dy);
```

Moves the CP by  $(dx, dy)$  pixels.

```
void moveto (int x, int y);
```

Moves the CP to the position  $(x, y)$ , relative to the viewport.

```
void outtext (char *textstring);
```

Outputs *textstring* at the CP.

```
void outtextxy (int x, int y, char *textstring);
```

Outputs *textstring* at  $(x, y)$ .

```
void pieslice (int x, int y, int stangle, int endangle, int radius);
```

Draws and fills a pie slice centered at  $(x, y)$ , with a radius given by *radius*, traveling from *stangle* to *endangle*. The pie slice is filled using the current fill colour.

```
void putimage (int left, int top, void *bitmap, int op);
```

Puts the bit image pointed to by *bitmap* onto the screen, with the upper left corner of the image placed at  $(left, top)$ . *op* specifies the drawing mode (COPY.PUT, etc).

```
void putpixel (int x, int y, int color);
```

Plots a point at  $(x, y)$  in the colour defined by *color*.



```
void rectangle (int left, int top, int right, int bottom);
```

Draws a rectangle delimited by (*left*,*top*) and (*right*,*bottom*).

```
int registerbgidriver (void (*driver)(void));
```

Unimplemented; not used by SDL\_bgi.

```
int registerbgifont (void (*font)(void));
```

Unimplemented; not used by SDL\_bgi.

```
void restorecrtmode (void);
```

Hides the graphics window.

```
void sector (int x, int y, int stangle, int endangle, int xradius, int yradius);
```

Draws and fills an elliptical pie slice centered at (*x*, *y*), horizontal and vertical radii given by *xradius* and *yradius*, traveling from *stangle* to *endangle*.

```
void setactivepage (int page);
```

Makes *page* the active page for all subsequent graphics output. In multi-window mode, `setactivepage` only works for the first window.

```
void setallpalette (struct palettetype *palette);
```

Sets the current palette to the values given in *palette*.

```
void setaspectratio (int xasp, int yasp);
```

Changes the default aspect ratio of the graphics. In SDL\_bgi, this function is not necessary since the pixels are square.

```
void setbkcolor (int color);
```

Sets the current background colour in the default palette.

```
void setcolor (int color);
```

Sets the current drawing colour in the default palette.

```
void setfillpattern (char *upattern, int color);
```

Sets a user-defined fill pattern. *upattern* is a pointer to a sequence of 8 bytes; each byte corresponds to 8 pixels in the pattern; each bit set to 1 is plotted as a pixel.

```
void setfillstyle (int upattern, int color);
```

Sets the fill pattern and fill colour. *upattern* is a pointer to a sequence of 8 bytes, with each byte corresponding to 8 pixels in the pattern.

```
unsigned setgraphbufsize (unsigned bufsize);
```

Unimplemented; not used by SDL\_bgi.

```
void setgraphmode (int mode);
```

Shows the window that was hidden by `restorecrtmode()`. The *mode* parameter is ignored

```
void setlinestyle (int linestyle, unsigned upattern, int thickness);
```

Sets the line width and style for all lines drawn by `line()`, `lineto()`, `rectangle()`, `drawpoly()`, etc. The line style can be `SOLID_LINE`, `DOTTED_LINE`, `CENTER_LINE`, `DASHED_LINE`, or `USERBIT_LINE`; in the latter case, the user provides a 16-bit number (*upattern*) whose bits set to 1 will be plotted as pixels.

The line thickness can be set with `NORM_WIDTH` or `THICK_WIDTH`.

Arcs, circles, ellipses, and pieslices are not affected by *linestyle*, but are affected by *thickness*.

```
void setpalette (int colnum, int color);
```

Changes the standard palette *colnum* to *color*, which can also be specified using the `COLOR` function.

```
void setttextjustify (int horiz, int vert);
```

Sets text justification. Text output will be justified around the CP horizontally and vertically; settings are `LEFT_TEXT`, `CENTER_TEXT`, `RIGHT_TEXT`, `BOTTOM_TEXT`, and `TOP_TEXT`.

```
void setttextstyle (int font, int direction, int charsize);
```

Sets the text font (8×8 bitmap font `DEFAULT_FONT` and vector fonts `TRIPLEX_FONT`, `SMALL_FONT`, `SANS_SERIF_FONT`, `GOTHIC_FONT`, `SCRIPT_FONT`, `SIMPLEX_FONT`, `TRIPLEX_SCR_FONT`), the text direction (`HORIZ_DIR`, `VERT_DIR`), and the size of the characters.

*charsize* is a scaling factor for the text (max. 10). If *charsize* is 0, the text will either use the default size, or it will be scaled by the values set with `setusercharsize()`.

Vector fonts are implemented using built-in Hershey fonts. Fonts `EUROPEAN_FONT` and `BOLD_FONT` have no Hershey equivalent, and are mapped to `TRIPLEX_FONT`.

Experimental feature: if a `.CHR` font is available in the same directory as the running program, it will be loaded and used instead of its Hershey equivalent.

*Note:* pixel-perfect font metrics are not supported yet. This feature does not work on Windows.

```
void setusercharsize (int multx, int divx, int multy, int divy);
```

Lets the user change the character width and height. If a previous call to `settextstyle()` set *charsize* to 0, the default width is scaled by *multx/divx*, and the default height is scaled by *multy/divy*.

```
void setviewport (int left, int top, int right, int bottom, int clip);
```

Sets the current viewport for graphics output. If *clip* is nonzero, all drawings will be clipped (truncated) to the current viewport.

```
void setvisualpage (int page);
```

Sets the visual graphics page number. In “fast mode”, the screen is not cleared.

```
void setwritemode (int mode);
```

Sets the writing mode for line drawing. *mode* can be `COPY_PUT`, `XOR_PUT`, `OR_PUT`, `AND_PUT`, and `NOT_PUT`.

```
int textheight (char *textstring);
```

Returns the height in pixels of a string.

```
int textwidth (char *textstring);
```

Returns the height in pixels of a string.

### 3 Non-Graphics Functions and Macros

```
void delay (int millisec);
```

Waits for *millisec* milliseconds. In “slow mode”, a screen refresh is performed. Events that occur during the delay are disregarded.

```
int getch (void);
```

Waits for a key and returns its ASCII code. In “slow mode”, a screen refresh is performed. If an SDL\_QUIT event occurs, QUIT is returned.

```
int kbhit (void);
```

Returns 1 when a key is pressed, excluding special keys (Ctrl, Shift, etc.); in “slow mode”, a screen refresh is performed. If an SDL\_QUIT event occurs, QUIT is returned.

```
int random (int range) (macro)
```

Returns a random number between 0 and *range* - 1.

## 4 SDL\_bgi Additions

The following SDL\_bgi extensions are mostly compatible with those made available by WinBGIm.

```
int ALPHA_VALUE (int color)
```

Returns the alpha (transparency) component of an ARGB colour in the ARGB palette.

```
int BLUE_VALUE (int color)
```

Returns the blue component of an ARGB colour in the ARGB palette.

```
int COLOR (int r, int g, int b);
```

Can be used as an argument for `setcolor()`, `setbkcolor()`, `setfillpattern()`, and `setfillstyle()` to set a colour specifying its ARGB components. The colour is stored in ARGB\_TMP\_COL, and it is also copied in one of the following: ARGB\_FG\_COL, ARGB\_BG\_COL, ARGB\_FILL\_COL.

Functions ALPHA\_VALUE, BLUE\_VALUE, GREEN\_VALUE, and RED\_VALUE do not work on temporary colours.

```
int COLOR32 (int Uint32color);
```

Can be used as an argument for `setcolor()`, `setbkcolor()`, `setfillpattern()`, and `setfillstyle()` to set a colour as ARGB integer. The colour is stored in `ARGB_TMP_COL`, and it is also copied in one of the following: `ARGB_FG_COL`, `ARGB_BG_COL`, `ARGB_FILL_COL`.

Functions `ALPHA_VALUE`, `BLUE_VALUE`, `GREEN_VALUE`, and `RED_VALUE` do not work on temporary colours.

```
int colorRGB (int r, int g, int b) (macro)
```

Can be used to compose a 32 bit colour with *r g b* components; the alpha value is set to 0xff. This macro is typically used to set values in memory buffers.

```
int GREEN_VALUE (int color)
```

Returns the green component of an ARGB colour in the ARGB palette.

```
int IS_BGI_COLOR (int color);
```

Returns 1 if the *current* drawing colour is a standard BGI colour (that is, not ARGB).

```
int IS_RGB_COLOR (int color);
```

Returns 1 if the *current* drawing colour is ARGB. The *color* argument is actually redundant.

```
int RED_VALUE (int color)
```

Returns the red component of an ARGB colour in the ARGB palette.

```
void _putpixel (int x, int y);
```

Plots a point at (*x,y*) using the current drawing colour. This function may be faster than `putpixel()`.

```
void closewindow (int id);
```

Closes the window whose identifier is *id*.

```
int edelay (int millisec);
```

Waits for *millisec* milliseconds. In “slow mode”, a screen refresh is performed. If an event occurs during the delay, this function returns 1, otherwise 0. Use `eventtype` to get the last event.

```
void event (void);
```

Returns 1 if an event (mouse click, key press, or `QUIT`) has occurred.

```
void eventtype (void);
```

Returns the type of the last event; either `SDL_KEYPRESS` or `SDL_MOUSEBUTTONDOWN`.

```
void getbuffer (Uint32 *buffer);
```

Copies the contents of the active window to *buffer*, which must be a `getmaxy()+1`  $\times$  `getmaxx()+1` array of *Uint32* in ARGB format.

```
int getcurrentwindow (void);
```

Returns the integer *id* of the current window.

```
void getleftclick (void);
```

Waits for the left mouse button to be clicked and released.

```
int getevent (void);
```

Waits for a keypress, mouse click, or `SDL_QUIT` event, and returns the code of the key, mouse button, or `QUIT`.

```
void getlinebuffer (int y, Uint32 *linebuffer);
```

Copies the *y*-th screen line to *linebuffer*, which must be a `getmaxx()+1` array of *Uint32* in ARGB format.

```
void getmiddleclick (void);
```

Waits for the middle mouse button to be clicked and released.

```
int getmaxheight (void);
```

Returns the maximum possible height for a new window (actual screen height in pixels).

```
int getmaxwidth (void);
```

Returns the maximum possible width for a new window (actual screen width in pixels).

```
void getmouseclick (int kind, int *x, int *y);
```

Sets the *x,y* coordinates of the last *kind* button click expected by `ismouseclick()`.

```
void getrightclick (void);
```

Waits for the right mouse button to be clicked and released.

```
void getscreensize (int *width, int *height);
```

Reports the screen width and height in *width* and *height*, regardless of current window dimensions. This function may be called before graphics initialisation.

```
void initpalette (void);
```

Initialises the palette to the standard 16 colours. If the environment variable `SDL_BGI_PALETTE` equals `BGI`, the first 16 colours will use the same RGB values as Turbo C 2.01; otherwise, a brighter palette will be used.

```
void initwindow (int width, int height);
```

Initializes the graphics system, opening a *width*×*height* window. If either *width* or *height* is 0, then `SDL_FULLSCREEN` will be used. Multiple windows can be created, unless a fullscreen window is already present.

The user must update the screen as needed using `refresh()`, or use `sdlbgiauto()`.

```
int ismouseclick (int kind);
```

Returns 1 if the *kind* mouse button was clicked.

```
int mouseclick (void);
```

Returns the code of the mouse button that was clicked, or 0 if none was clicked.

```
int mousex (void);
```

Returns the X coordinate of the last mouse click.

```
int mousey (void);
```

Returns the Y coordinate of the last mouse click.

```
void putbuffer (Uint32 *buffer);
```

Copies *buffer* to the current window. *buffer* must be a `getmaxy()+1 × getmaxx()+1` array of *Uint32* in ARGB format. This function is faster than direct pixel manipulation.

```
void putlinebuffer (int y, Uint32 *buffer);
```

Copies *linebuffer* to the *y* coordinate in the current window. *linebuffer* must be a `getmaxx()+1` array of *Uint32* in ARGB format. This function is faster than direct pixel manipulation.

```
void readimagefile (char *filename, int x1, int y1, int x2, int y2);
```

Reads a `.bmp` file and displays it immediately at  $(x1, y1)$ . If  $(x2, y2)$  are not 0, the bitmap is stretched to fit the rectangle  $x1, y1—x2, y2$ ; otherwise, the bitmap is clipped as necessary.

```
void refresh (void);
```

Updates the screen contents, i.e. displays all graphics.

```
void setwinoptions (int id, char *title, int x, int y);
```

Resets the window title *title* and position to  $(x, y)$  of an existing window identified by *id*. *x* and *y* can be set to `SDL_WINDOWPOS_CENTERED` or `SDL_WINDOWPOS_UNDEFINED`. If either *x* or *y* is -1, the position parameters are ignored.

```
int resizepalette (Uint32 newsize);
```

Resizes the ARGB palette to *newsize*; returns 0 if successfull, 1 otherwise. The initial size of the ARGB palette is 4096.



```
void sdlbgiauto (void);
```

Triggers “auto mode”, i.e. `refresh()` is performed automatically. Caveat: it may not work on some graphics cards.

```
void sdlbgifast (void);
```

Triggers “fast mode”, i.e. `refresh()` is needed to display graphics.

```
void sdlbgislow (void);
```

Triggers “slow mode”, i.e. `refresh()` is not needed to display graphics.

```
void setalpha (int col, Uint8 alpha);
```

Sets alpha transparency for colour *col* to *alpha* (0–255); 0 means full transparency, 255 full opacity. `setalpha()` works with colours in both palettes.

```
void setbkrgbcolor (int n);
```

Sets the current background colour using the *n*-th colour entry in the ARGB palette.

```
void setblendmode (int blendmode);
```

Sets the blend mode to be used with screen refresh. *blendmode* can be `SDL_BLENDMODE_NONE` (default in “slow mode”) or `SDL_BLENDMODE_BLEND`. The latter enables alpha blending.

```
void setcurrentwindow (int id);
```

Sets the current active window to `int id`.

```
void setrgbcolor (int n);
```

Sets the current drawing colour using the *n*-th colour entry in the ARGB palette.

```
void setrgbpalette (int n, int r, int g, int b);
```

Sets the *n*-th entry in the ARGB palette specifying the *r*, *g*, and *b* components. Using `setrgbpalette()` and `setrgbcolor()` is faster than setting colours with `setcolor()` with a `COLOR()` argument.

```
void setwinoptions (char *title, int x, int y, Uint32 flags);
```

Sets the window title *title*, the initial position to (*x*, *y*), and SDL2 flags OR'ed together. *x* and *y* can be set to `SDL_WINDOWPOS_CENTERED` or `SDL_WINDOWPOS_UNDEFINED`.

If *title* is an empty string, the window title is set to the default value `SDL_bgi`.

If either *x* or *y* is -1, the position parameters are ignored.

If *flags* is -1, the parameter is ignored; otherwise, only the values `SDL_WINDOW_FULLSCREEN`, `SDL_WINDOW_FULLSCREEN_DESKTOP`, `SDL_WINDOW_SHOWN`, `SDL_WINDOW_HIDDEN`, `SDL_WINDOW_BORDERLESS`, and `SDL_WINDOW_MINIMIZED` can be applied.

```
void showerrorbox (const char *message);
```

Opens an error message box with the specified message. The message box waits for the user to click on the OK button.

```
void showinfobox (const char *message);
```

Opens an information message box with the specified message. The message box waits for the user to click on the OK button.

```
int swapbuffers (void);
```

Swaps the current active and the current visual graphics pages.

```
void writeimagefile (char *filename, int left, int top, int right, int bottom);
```

Writes a `.bmp` file from the screen rectangle defined by *left*,*top*—*right*,*bottom*.

```
int xkbhit (void);
```

Returns 1 when any key is pressed, including special keys (Ctrl, Shift, etc.); in “slow mode”, a screen refresh is performed. If an `SDL_QUIT` event occurs, `QUIT` is returned.

---

This document is a free manual, released under the GNU Free Documentation License (FDL) v. 1.3 or later.