

1 AssociationExplorer: A user-friendly Shiny application 2 for exploring associations and visual patterns

3 Antoine Soetewey^{a,b,*}, Cédric Heuchenne^{a,b}, Arnaud Claes^c, Antonin
4 Descampe^c

5 ^aHEC Liège, ULiège, Rue Louvrex 14, 4000 Liège, Belgium

6 ^bThe Center for Applied Public Economics (CAPE), UCLouvain Saint-Louis Bruxelles,
7 Boulevard du Jardin Botanique 43, 1000 Brussels, Belgium

8 ^cObservatory for Research on Media and Journalism (ORM), UCLouvain, Ruelle de la
9 Lanterne Magique 14, 1348 Louvain-la-Neuve

10 Abstract

AssociationExplorer is an open-source interactive R Shiny application designed to help non-technical users explore statistical associations within multivariate datasets. Aimed particularly at journalists, educators, and engaged citizens, the tool facilitates the discovery and interpretation of meaningful patterns between variables without requiring programming or statistical expertise. Users can upload structured data (e.g., from surveys or open government datasets), select relevant variables, and dynamically visualize relationships via a correlation network and contextual bivariate plots. To illustrate its capabilities, we present a case study based on the European Social Survey (ESS), showcasing how users can investigate links between attitudes, behaviors, and socio-demographic indicators across countries. The app supports a range of association measures adapted to variable types (Pearson's r , Eta, and Cramer's V), ensuring both flexibility and statistical rigor. The visual interface enables users to adjust thresholds for association strength and examine results through interactive graphs and summary tables, making the app particularly well-suited for data storytelling, exploratory research, and public communication. AssociationExplorer demonstrates how open-source statistical tooling can enhance transparency, accessibility, and insight in the interpretation of complex social data.

11 **Keywords:** R Shiny, Exploratory data analysis, Correlation network

Nr.	Code metadata description	Metadata
C1	Current code version	v3.5.5
C2	Permanent link to code/repository used for this code version	https://github.com/AntoineSoetewey/AssociationExplorer
C3	Permanent link to Reproducible Capsule	For example: https://codeocean.com/capsule/0270963/tree/v1xxx
C4	Legal Code License	MIT License
C5	Code versioning system used	Git/GitHub
C6	Software code languages, tools, and services used	R, R Shiny
C7	Compilation requirements, operating environments & dependencies	See a list of the required R packages at https://github.com/AntoineSoetewey/AssociationExplorer/blob/main/packages.md
C8	If available link to developer documentation/manual	https://github.com/AntoineSoetewey/AssociationExplorer/tree/main/documentation
C9	Support for questions or issues	https://github.com/AntoineSoetewey/AssociationExplorer/issues

Table 1: Code metadata

12 Metadata

13 The metadata associated with the current version of the software is summarized in Table 1.

14
15 The remainder of this paper is structured as follows. Section 1 outlines
16 the motivation and significance of the application, highlighting its contribution
17 to data accessibility and exploratory analysis. Section 2 provides a detailed
18 description of the software’s architecture and functionalities. Section 3
19 presents an illustrative example using data from the European Social Sur-

*Corresponding author.

Email addresses: antoine.soetewey@uliege.be (Antoine Soetewey),
cedric.heuchenne@uclouvain.be (Cédric Heuchenne), arnaud.claes@uclouvain.be
(Arnaud Claes), antonin.descampe@uclouvain.be (Antonin Descampe)

vey. Section 4 discusses the potential impact of the application in research, education, and journalism. Finally, Section 5 concludes with a summary and future directions.

1. Motivation and significance

The growing availability of large, complex, and high-dimensional datasets in the social sciences and public policy domains offers unprecedented opportunities for insight but also presents significant challenges for exploration and interpretation, particularly for non-specialist audiences. Journalists, educators, and engaged citizens often struggle to identify and interpret meaningful relationships between variables without the aid of programming skills or formal statistical training. This barrier limits the broader societal impact of open data initiatives, which are designed to promote transparency, accountability, and informed public discourse.

To address this gap, we developed AssociationExplorer, a free, open-source R Shiny [1] application that enables intuitive and statistically grounded exploration of multivariate associations. The tool guides users through a visual journey of variable relationships by automatically computing appropriate bivariate association measures—Pearson’s r , Eta, and Cramer’s V —depending on variable types, and presenting the results in an interactive correlation network. Users can set thresholds for the strength of association and explore linked bivariate plots or tables with descriptive labels. This workflow supports transparent, reproducible, and non-technical exploratory data analysis (EDA).

Our software is particularly suited to survey-based datasets and public opinion studies. As an illustrative case, we apply AssociationExplorer to the European Social Survey (ESS), a cross-national survey that collects attitudinal, behavioral, and socio-demographic data across European countries. The tool allows users to uncover associations between trust in institutions, policy preferences, media usage, and demographic characteristics without any coding. This type of interactive analysis can empower journalists to build data-driven narratives, educators to teach statistical thinking, and citizens to explore evidence underlying public debate.

While several tools and libraries exist for correlation analysis (e.g., `corrr` [5], `GGally` [11], `corrplot` [14], `ggstatsplot` [9], `correlation` [7, 8], `lares` [6] and `Hmisc` [4] in R [10], or Python packages like `seaborn` [13] and `pingouin` [12]), they typically require programming proficiency and focus primarily on numerical associations. Most of these tools do not handle nominal categorical variables directly; if included, such variables are often transformed using one-hot or dummy encoding, which can transform their original structure and

59 limit interpretations.

60 In contrast, AssociationExplorer is designed to handle both quantitative and
61 qualitative variables (including nominal factors) natively and transparently.
62 It provides a guided, end-to-end workflow that begins with data upload and
63 preprocessing, continues through variable selection and association filtering,
64 and ends with interpretable visualizations. This structured process is in-
65 tuitive and accessible for users of all backgrounds, making the app espe-
66 cially suitable for those without programming experience or formal statistical
67 training. By lowering the technical barrier for statistical exploration, Asso-
68 ciationExplorer contributes to a more inclusive data culture and supports
69 data-driven discovery in both academic and public-facing contexts.

70 **2. Software description**

71 *2.1. Software architecture*

72 Upon upload, the dataset is preprocessed to exclude variables with zero vari-
73 ance, as these variables do not vary across observations and therefore cannot
74 contribute to meaningful associations or visualizations. Removing them helps
75 reduce noise and ensures that only informative variables are included in the
76 analysis. Optionally, the user can provide a variable description file, which
77 is integrated and used to annotate visual elements. The backend computes
78 association measures tailored to the variable types: Pearson’s r for numeric
79 pairs, Cramer’s V for categorical pairs, and the correlation ratio (η) for mixed
80 pairs. Associations are filtered using user-defined thresholds and represented
81 in a correlation network and complementary bivariate plots. The app handles
82 both CSV and Excel files.

83 The application is currently available as a standalone open-source R Shiny
84 application on GitHub.¹ It can be launched directly from an R session using
85 the following command, provided the `shiny` package is installed:

```
86 library(shiny)  
87 runGitHub("AssociationExplorer", "AntoineSoetewey")
```

88 A fully web-based version, requiring no installation or technical setup, is also
89 planned as part of its integration into a broader online platform developed
90 within the ODALON (Open multimodal Data for Automated LOcal News)
91 research project, which aims to support the production of local news (more
92 information about this project in Sections 3 and 4).

¹<https://github.com/AntoineSoetewey/AssociationExplorer>

93 *2.2. Software functionalities*

94 The major functionalities of the AssociationExplorer application include:

- 95 • **Data upload and cleaning:** The app supports CSV and Excel files.
 96 It automatically removes variables with only one unique value, as they
 97 lack variability and cannot contribute to association analyses. Addi-
 98 tionally, it can optionally integrate user-supplied descriptions of vari-
 99 ables, which are used to enhance the clarity and interpretability of
 100 visualizations, particularly for non-technical users. The description file
 101 must be structured with two columns: **Variable** (containing the ex-
 102 act variable names as in the dataset) and **Description** (containing the
 103 corresponding descriptions).
- 104 • **Variable selection interface:** Users can interactively choose which
 105 variables to explore. When a description file is provided, a summary
 106 table links variable names to their descriptions.
- 107 • **Dynamic association filtering:** The app computes pairwise associ-
 108 ation measures between all selected variables, using a method tailored
 109 to the types of variables involved:
 - 110 – For pairs of numeric variables X and Y , the app calculates Pear-
 111 son’s correlation coefficient (r), and retains the association if the
 112 coefficient of determination (R^2) exceeds a user-defined threshold:

$$R^2 = r^2 = (\text{cor}(X, Y))^2 \quad (1)$$

113 where the Pearson’s correlation coefficient $\text{cor}(X, Y)$ is defined as:

$$r(X, Y) = \frac{\sum_{i=1}^n (X_i - \bar{X})(Y_i - \bar{Y})}{\sqrt{\sum_{i=1}^n (X_i - \bar{X})^2} \sqrt{\sum_{i=1}^n (Y_i - \bar{Y})^2}} \quad (2)$$

114 where $\bar{X}$ and $\bar{Y}$ are the sample means of X and Y , respectively,
 115 and n is the number of observations.

- 116 – For pairs of categorical variables, it computes Cramer’s V , a nor-
 117 malized measure of association derived from the chi-squared statis-
 118 tic:

$$V = \sqrt{\frac{\chi^2}{n \cdot \min(k - 1, r - 1)}} \quad (3)$$

119 where χ^2 is the chi-squared statistic, n is the total number of ob-
 120 servations, and k, r are the numbers of categories in each variable.

121 – For mixed pairs (one numeric and one categorical variable), the
 122 app computes the correlation ratio (η), which quantifies how much
 123 of the variance in the numeric variable is explained by the grouping
 124 structure of the categorical variable. It is defined as:

$$\eta = \sqrt{\frac{SS_{\text{between}}}{SS_{\text{total}}}} \quad (4)$$

125 where:

126 - SS_{total} is the *total sum of squares* of the numeric variable:

$$SS_{\text{total}} = \sum_{i=1}^n (y_i - \bar{y})^2$$

127 with y_i the observed numeric values and $\bar{y}$ their overall mean.

128 - SS_{between} is the *between-group sum of squares*, computed as:

$$SS_{\text{between}} = \sum_{g=1}^G n_g (\bar{y}_g - \bar{y})^2$$

129 where G is the number of groups (categories), n_g is the number
 130 of observations in group g , $\bar{y}_g$ is the group mean, and $\bar{y}$ is the
 131 overall mean.

132 This formulation captures the proportion of the total variance in
 133 the numeric variable that can be attributed to differences between
 134 the categorical groups. A pair is retained only if η^2 exceeds the
 135 numeric threshold defined by the user.

136 Each association is retained only if its corresponding strength metric—
 137 R^2 , η^2 , or Cramer’s V —exceeds the threshold set by the user. These
 138 thresholds can be adjusted interactively through the interface, and
 139 the filtering process is reactive: updates to the thresholds immediately
 140 propagate to the network and bivariate visualizations. This allows users
 141 to dynamically control the sensitivity of the association analysis and
 142 focus on relationships of substantive interest.

143 • **Interactive correlation network:** The filtered associations are dis-
 144 played as an interactive graph where nodes represent variables and
 145 edges represent associations. Edge thickness and length reflect the
 146 strength of the association: stronger associations are shown with thicker

and shorter edges, whereas weaker associations are displayed with thinner and longer edges. For quantitative–quantitative pairs specifically, the color of the edges conveys direction: red edges indicate negative associations, while blue edges indicate positive ones. This combination of visual cues helps users quickly identify the most meaningful relationships in the network. When hovering over nodes, variable descriptions are displayed if a description file has been provided by the user; otherwise, the variable names are shown by default. This allows for quick access to additional context without cluttering the visualization, enhancing interpretability while keeping the network clean and readable. The network is built using the **visNetwork** R package, which supports interactive, customizable graph layouts; full documentation is available at <https://datastorm-open.github.io/visNetwork/>.

- **Bivariate visualization of variable pairs:** For each variable pair exceeding the threshold:
 - Scatter plots with linear regression lines are shown for numeric pairs, helping visualize the direction and strength of the relationship. The regression line is computed using the ordinary least squares (OLS) method, which minimizes the sum of squared vertical distances between the observed data points and the fitted line.
 - Colored contingency tables with marginal sums are shown for categorical pairs, where cell background colors vary in intensity according to the frequency of observations, using a blue gradient to highlight higher counts.
 - Mean plots are shown for numeric-categorical pairs, with bars ordered by mean value to make it easy to compare and rank categories based on the quantitative variable.

Confidence intervals for the regression lines and standard errors in the mean plots are intentionally omitted to maintain a clean, uncluttered visualization that prioritizes ease of interpretation. Mean plots were selected over boxplots to avoid overwhelming non-expert users with distributional information, focusing instead on clear, accessible insights about average group differences.

- **Accessibility and user guidance:** A dedicated help section explains each step, allowing users with a limited statistical background to interactively explore their data.

184 *2.3. Sample code snippets analysis*

185 Below is a representative snippet from the application showing how the soft-
186 ware selects the appropriate association measure depending on the types of
187 the variable pair and filters associations based on user thresholds:

```
188 # Numeric vs numeric case
189 if (is_num1 && is_num2) {
190   ...
191   r <- cor(x, y, use = "complete.obs")
192   cor_val <- ifelse(r^2 >= threshold_num, r, 0)
193   cor_type <- "Pearson's r"
194
195 # Categorical vs categorical case
196 } else if (!is_num1 && !is_num2) {
197   ...
198   tbl <- table(x, y)
199   ...
200   n_obs <- sum(tbl)
201   df_min <- min(nrow(tbl) - 1, ncol(tbl) - 1)
202   if (df_min > 0) {
203     v_cramer <- sqrt(chi$statistic / (n_obs * df_min))
204     cor_val <- ifelse(v_cramer >= threshold_cat,
205                       v_cramer, 0)
206     cor_type <- "Cramer's V"
207   }
208
209 # Mixed case (numeric vs categorical)
210 } else {
211   ...
212   means_by_group <- tapply(num_var, cat_var,
213                             mean, na.rm = TRUE)
214   overall_mean <- mean(num_var, na.rm = TRUE)
215   n_groups <- tapply(num_var, cat_var, length)
216   bss <- sum(n_groups * (means_by_group - overall_mean)^2,
217             na.rm = TRUE)
218   tss <- sum((num_var - overall_mean)^2, na.rm = TRUE)
219
220   if (tss > 0) {
221     eta <- sqrt(bss / tss)
222     cor_val <- ifelse(eta^2 >= threshold_num, eta, 0)
223     cor_type <- "Eta"
```



```
224 }  
225 }
```

226 This conditional structure ensures that the correct statistical method is ap-
227 plied for each type of variable pair, supporting a robust and interpretable
228 exploration of associations.

229 3. Illustrative example

230 To demonstrate the core functionalities of AssociationExplorer, we use a cu-
231 rated subset of data from the European Social Survey (ESS), Round 11.
232 The ESS is a large-scale, cross-national survey that measures attitudes, be-
233 liefs, and behaviors across European countries. The original dataset includes
234 responses from over 46,000 individuals on topics such as politics, trust, well-
235 being, media use, and health. The full ESS dataset, codebook, and docu-
236 mentation are freely available at <https://ess.sikt.no/en/> [3, 2].

237 For this example, we focus on the Belgian respondents, resulting in a re-
238 duced dataset of 1,594 individuals. We selected 60 variables covering areas
239 highly relevant for understanding public opinion and everyday life in Belgium:
240 interest in politics, confidence in institutions, lifestyle behaviors, perceived
241 discrimination, vaccination, and more. These variables include both numbers
242 (quantitative data) and labels or categories (qualitative data), making the
243 dataset ideal for exploring diverse forms of associations.

244 This example is particularly relevant for our research project ODALON,
245 which aims to develop a platform that supports the (semi-)automated pro-
246 duction of local news in Belgium. AssociationExplorer plays a key role in
247 this effort by offering journalists, researchers, and citizens an intuitive tool to
248 explore potentially newsworthy patterns in public and survey data, without
249 requiring programming skills or statistical training.

250 Data preparation for the curated dataset was carried out in R and included:

- 251 • Filtering the dataset to include only Belgian respondents.
- 252 • Converting survey-specific nonresponse codes (e.g., 77, 88, 9999, etc.)
253 to NA values, based on the ESS codebook.
- 254 • Recoding several categorical variables to have meaningful and inter-
255 pretable labels (e.g., for gender, religion, political participation, or
256 health behaviors).

257 The full R script used to perform this transformation is openly available in the
258 data folder of the GitHub repository at [https://github.com/AntoineSoetewey/](https://github.com/AntoineSoetewey/AssociationExplorer/tree/main/shiny_app/data)
259 AssociationExplorer/tree/main/shiny_app/data.

Association Explorer

Upload your dataset (CSV or Excel)

Browse... ESS11_BE_data.csv
Upload complete

(Optional) Upload variable descriptions (CSV or Excel)

Browse... ESS11_BE_description.csv
Upload complete

The descriptions file must contain exactly two columns named 'Variable' and 'Description'.

Process data

Figure 1: Data upload tab. Users upload their dataset and can optionally provide a variable description file containing variable names and descriptions.

260 Once the dataset is uploaded into AssociationExplorer via the **Data** tab (see
261 Figure 1), users are guided through a step-by-step process. In addition to
262 the main dataset, users can optionally upload a separate description file that
263 provides human-readable explanations for each variable. In our example, this
264 file was created using information from the official ESS codebook, allowing
265 for clearer interpretation throughout the app interface. If no description
266 file is provided, the application will automatically use the variable names
267 themselves as default labels in all visualizations and summary tables.

268 In the **Variables** tab, they select the variables they wish to explore, op-
269 tionally assisted by a table of the variables' names and descriptions (see
270 Figure 2).

271 Next, users can adjust the association thresholds in the **Correlation Network**
272 tab to focus on the most meaningful relationships among the selected vari-
273 ables (see Figure 3).

274 Finally, the **Pairs Plots** tab displays detailed bivariate visualizations, in-
275 cluding scatter plots, mean plots, and contingency tables, for each retained
276 association (see Figures 4-6).

277 In addition, the **Help** tab provides a concise, step-by-step guide on how to
278 use the application (see Figure 7).

279 This example shows how non-expert users, such as journalists or engaged cit-
280 izens, can uncover unexpected or important relationships in a public opinion
281 dataset. These insights can serve as the starting point for local news, public
282 debates, or policy communication.

Association Explorer




Figure 2: Variables tab. Users select the variables to include in the analysis, with access to descriptions (if provided in the data tab) for easier selection.

Association Explorer




Figure 3: Interactive correlation network. Nodes represent variables and edges represent associations; edge thickness and length indicate strength, and edge color reflects direction (for numeric pairs only).

Association Explorer




Figure 4: Example of a scatter plot for a numeric-numeric pair. The plot includes a linear regression line fitted via ordinary least squares (OLS).

Association Explorer



Figure 5: Example of a mean plot for a numeric-categorical pair. Categories are ordered by the mean value of the quantitative variable to aid interpretation.

Association Explorer




Figure 6: Example of a colored contingency table for a categorical-categorical pair, with color intensity reflecting frequencies and marginal sums displayed.

Association Explorer



How to use the Association Explorer app?

- Upload your dataset (CSV or Excel) in the 'Data' tab. Optionally, upload a file with variable descriptions. This file must contain 2 columns called 'Variable' and 'Description'.
- In the 'Variables' tab, select the variables you want to explore. If you upload a file containing variables' descriptions, a summary table below shows the selected variables along with their descriptions.
- Click 'Visualize all associations' to access the correlation network.
- Adjust the thresholds to filter associations by strength. Only variables that have strong associations (as defined by the thresholds) will appear in the network and pairs plots.
- In the network, thicker and shorter edges indicate stronger associations.
- Click 'See pairs plots' to display bivariate visualizations for retained associations.

Figure 7: Help tab, offering guidance on how to use the application.

283 Note that in this example, no survey weights have been applied. While the
284 ESS dataset includes weights to account for complex sampling designs, we
285 chose not to use them here in order to maintain clarity and responsiveness
286 in the interface, and because our focus is on demonstrating the app’s core
287 functionality rather than producing nationally representative statistics.

288 4. Impact

289 AssociationExplorer enables a broader range of users, including researchers,
290 students, journalists, and engaged citizens, to explore complex datasets in-
291 volving both quantitative and qualitative variables. By eliminating the need
292 for advanced programming or statistical knowledge, the software lowers the
293 barrier to entry for data-driven discovery and interpretation.

294 From a research perspective, the app facilitates the systematic screening of
295 pairwise associations in survey or public data, offering insights that can guide
296 hypothesis generation, variable selection, or further multivariate modeling.
297 It is planned to be used in the context of the ODALON research project,
298 which aims to support the semi-automated generation of local news. Ini-
299 tially targeted at Belgian journalists, the platform, and the use of Associa-
300 tionExplorer within it, may later be extended to other professional or public
301 audiences. The app will help identify patterns in public opinion data that
302 may serve as starting points for local news articles, for example, by revealing
303 unexpected associations between political attitudes, trust in institutions, or
304 lifestyle behaviors.

305 The software also improves the pursuit of existing research questions by mak-
306 ing it easier to assess relationships between variables of different types (nu-
307 meric, ordinal, and nominal) within a single unified interface. Unlike many
308 tools that require preprocessing steps such as dummy coding, Association-
309 Explorer handles categorical variables natively and automatically selects the
310 appropriate statistical association measure (i.e., Pearson’s r , Cramer’s V ,
311 correlation ratio η). This ensures that users can obtain meaningful and in-
312 terpretable results without needing to master complex preprocessing steps or
313 statistical diagnostics.

314 The app is also planned to be used as an interactive teaching aid in statistics
315 and data literacy courses. It will allow students to upload real datasets and
316 immediately visualize how variables relate, reinforcing theoretical concepts
317 through intuitive, hands-on exploration. By presenting associations visually,
318 the app encourages learners to engage with their data more actively and
319 reflect critically on patterns, variable relationships, and data quality.

320 Although already fully functional, the software is currently made available as
321 a standalone open-source R Shiny application on GitHub and can be launched

322 directly from R. At this stage, it is therefore only accessible to users who have
323 R installed on their machine. As part of the broader ODALON research
324 project, which aims to build an integrated platform combining multiple tools
325 for automated local news production, AssociationExplorer will serve as a key
326 building block. A public, fully online version of the app will be released as the
327 project progresses, and no later than December 2026 (which corresponds to
328 the end of the project), ensuring that anyone, including those without access
329 to R, can freely use the application through a user-friendly web interface.
330 Future impact is expected through integration into platforms for civic data
331 storytelling, local journalism, and public communication. While not intended
332 for commercialization, the application’s role in supporting open, inclusive,
333 and responsible data exploration reflects its potential for broader societal
334 relevance.

335 5. Conclusions

336 AssociationExplorer provides a user-friendly, open-source solution for explor-
337 ing statistical associations within multivariate datasets. By integrating ro-
338 bust statistical measures with dynamic and intuitive visualizations, the app
339 empowers non-expert users, such as journalists, educators, and engaged cit-
340 izens, to uncover patterns and relationships that might otherwise remain
341 hidden. Its ability to handle both quantitative and qualitative variables,
342 combined with an interactive interface and an easy-to-follow workflow, makes
343 it especially suitable for exploratory research, data storytelling, and public
344 communication.

345 Beyond its technical features, the application contributes to democratizing
346 access to statistical tools and supports data literacy in a wide range of con-
347 texts. The case study using the European Social Survey illustrates how users
348 can navigate from raw data to meaningful insights with minimal technical
349 knowledge.

350 While the app is currently accessible through R for users with basic technical
351 setup, a fully web-based version will make it universally available as part of
352 a broader data exploration platform being developed under the ODALON
353 project. By lowering barriers to data exploration and interpretation, Asso-
354 ciationExplorer supports more inclusive, transparent, and evidence-informed
355 engagement with complex social data.

356 Future improvements will be guided by user feedback and community con-
357 tributions. One planned feature is the ability to incorporate user-specified
358 weights, especially relevant for survey data. However, this functionality is
359 not yet implemented in the current version to preserve simplicity and ensure

360 responsiveness in the user interface, particularly for users unfamiliar with
361 survey weighting procedures.

362 Additional avenues for future research and development include extending
363 the application to compute partial correlations, which can help isolate direct
364 relationships between variables by controlling for confounders. Visualizations
365 involving three variables could also be introduced, for instance, scatter plots
366 where the size or color of points reflects a third variable, to uncover more nu-
367 anced patterns. Furthermore, users could be allowed to filter variables based
368 on missingness thresholds or variable types, and a module for longitudinal
369 data (e.g., panel structures or time series) could expand the app’s relevance
370 to temporal analyses. Lastly, adding options for exporting results or gener-
371 ating automated summaries of key associations could further enhance its use
372 in reporting and collaborative workflows.

373 A more ambitious extension would integrate a large language model (LLM)
374 to enable users to enter a free-text prompt or a thematic query. The app
375 would then automatically identify variables that are semantically similar or
376 potentially associated with the theme, based on the dataset and the optional
377 description file provided by the user. These extracted variables would be
378 pre-selected in the interface, as if the user had chosen them manually, after
379 which the analysis would proceed as in the current version. This feature
380 could significantly enhance accessibility for users unfamiliar with the dataset
381 or its structure, and accelerate the discovery of relevant associations.

382 Acknowledgements

383 The authors gratefully acknowledge the Walloon region and the SPW Recherche
384 in Belgium for funding the ODALON research project. The authors addi-
385 tionally thank the researchers from UCLouvain Saint-Louis Brussels involved
386 in the Beamm research project for their feedback on previous versions of the
387 software.

388 References

- 389 [1] Chang, W., Cheng, J., Allaire, J., Sievert, C., Schloerke, B., Xie, Y.,
390 Allen, J., McPherson, J., Dipert, A., and Borges, B. (2024). *shiny: Web*
391 *Application Framework for R*. R package version 1.9.1.
- 392 [2] European Social Survey European Research Infrastructure (ESS ERIC)
393 (2024a). ESS11 Data Documentation.
- 394 [3] European Social Survey European Research Infrastructure (ESS ERIC)
395 (2024b). ESS11 integrated file, edition 3.0. [Data set].

- 396 [4] Harrell Jr, F. E. (2025). *Hmisc: Harrell Miscellaneous*. R package version
397 5.2-3.
- 398 [5] Kuhn, M., Jackson, S., and Cimentada, J. (2022). *corrr: Correlations in*
399 *R*. R package version 0.4.4.
- 400 [6] Lares, B. (2025). *lares: Analytics & Machine Learning Sidekick*. R pack-
401 age version 5.2.11.
- 402 [7] Makowski, D., Ben-Shachar, M. S., Patil, I., and Lüdecke, D. (2020).
403 Methods and algorithms for correlation analysis in r. *Journal of Open*
404 *Source Software*, 5(51):2306.
- 405 [8] Makowski, D., Wiernik, B., Patil, I., Lüdecke, D., and Ben-Shachar, M.
406 (2022). *correlation: Methods for correlation analysis* [r package].
- 407 [9] Patil, I. (2021). Visualizations with statistical details: The ‘ggstatsplot’
408 approach. *Journal of Open Source Software*, 6(61):3167.
- 409 [10] R Core Team (2024). *R: A Language and Environment for Statistical*
410 *Computing*. R Foundation for Statistical Computing, Vienna, Austria.
- 411 [11] Schloerke, B., Cook, D., Larmarange, J., Briatte, F., Marbach, M.,
412 Thoen, E., Elberg, A., and Crowley, J. (2024). *GGally: Extension to*
413 *‘ggplot2’*. R package version 2.2.1.
- 414 [12] Vallat, R. (2018). Pingouin: statistics in python. *Journal of Open Source*
415 *Software*, 3(31):1026.
- 416 [13] Waskom, M. L. (2021). seaborn: statistical data visualization. *Journal*
417 *of Open Source Software*, 6(60):3021.
- 418 [14] Wei, T. and Simko, V. (2024). *R package ‘corrplot’: Visualization of a*
419 *Correlation Matrix*. (Version 0.95).