

Package ‘AssociationExplorer2’

December 2, 2025

Title Shiny Application for Exploring Statistical Associations

Version 0.0.0.9000

Description A user-friendly Shiny application to explore statistical associations and visual patterns in multivariate datasets. The app provides interactive correlation networks, bivariate plots, and summary tables for different types of variables (numeric and categorical). It also supports optional survey weights and range-based filters on association strengths, making it suitable for the exploration of survey and public data by non-technical users, journalists, educators, and researchers.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Depends R (>= 4.1.0)

Imports shiny, visNetwork, ggplot2, plotly, dplyr, tidyr, readr, readxl, stringr, purrr, tibble, forcats, reactable, scales, igraph

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Antoine Soetewey [aut, cre] (<<https://orcid.org/0000-0001-8159-0804>>),
Cédric Heuchenne [aut] (-6196),
Arnaud Claes [aut] (-1517),
Antonin Descampe [aut] (-5071)

Maintainer Antoine Soetewey <antoine.soetewey@uliege.be>

Contents

package_imports	2
run_associationexplorer	2
Index	3

package_imports	<i>Internal package imports</i>
-----------------	---------------------------------

Description

These import statements ensure that the packages listed in the Imports field of DESCRIPTION are properly imported into the package namespace, as required for CRAN.

run_associationexplorer	<i>Launch the AssociationExplorer2 Shiny Application</i>
-------------------------	--

Description

This function launches the AssociationExplorer2 Shiny application in your default web browser. The app provides interactive tools for exploring statistical associations, correlation networks, bivariate visualizations, and summary tables, with optional support for survey weights and range-based filtering of association strengths.

Usage

```
run_associationexplorer(...)
```

Arguments

... Additional arguments passed to shiny::runApp(), such as port or launch.browser.

Value

The function is called for its side effect of launching the app.

Examples

```
## Not run:
  run_associationexplorer()

## End(Not run)
```

Index

- * **internal**
 - package_imports, [2](#)
- package_imports, [2](#)
- run_associationexplorer, [2](#)