

Fundamental Haskell notes

Anton Latukha

February 25, 2020

Contents

I	Introduction	21
II	Definitions	24
1	Algebra	25
1.1	*	25
1.2	Algebraic	25
1.3	Algebraic structure	25
1.3.1	*	26
1.3.2	Fundamental theorem of algebra	26
1.4	Modular arithmetic	26
1.4.1	*	26
1.4.2	Modulus	26
1.4.2.1	*	26
2	Bind	27
2.1	*	27
3	Category theory	28
3.1	*	28
3.2	Abelian category	29
3.2.1	*	29
3.3	Composition	30
3.3.1	*	30
3.4	Endofunctor category	30
3.5	Functor	30
3.5.1	*	31
3.5.2	Power set functor	31
3.5.2.1	*	31
3.5.2.2	Power set functor laws	31
3.5.2.3	Lift	32
3.5.2.4	Power set functor is a free monad	32
3.5.3	Functorial	32
3.5.4	Forgetful functor	32
3.5.4.1	*	32
3.5.5	Identity functor	32
3.5.6	Endofunctor	33
3.5.6.1	*	33
3.5.7	Applicative functor	33
3.5.7.1	*	33
3.5.7.2	Applicative law	34
3.5.7.3	*	34
3.5.7.4	Applicative function	34
3.5.7.5	Special applicatives	35

3.5.7.6	Monad	36
3.5.7.7	Alternative type class	49
3.5.7.8	$\llangle \leq^* \gg\rangle$	50
3.5.8	Monoidal functor	50
3.5.9	Fusion	50
3.5.10	$\llangle \leq^{\$} \gg\rangle$	50
3.5.11	Multifunctor	50
3.5.11.1	*	51
3.5.12	*	51
3.6	Hask category	51
3.6.1	*	51
3.7	Magma	51
3.7.1	Mag category	52
3.7.1.1	*	52
3.7.2	Semigroup	52
3.7.2.1	*	52
3.7.2.2	Monoid	52
3.8	Morphism	54
3.8.1	*	54
3.8.2	Homomorphism	54
3.8.2.1	*	54
3.8.3	Identity morphism	54
3.8.3.1	Identity	55
3.8.3.2	Identity function	55
3.8.4	Monomorphism	55
3.8.4.1	*	55
3.8.5	Epimorphism	56
3.8.5.1	*	56
3.8.6	Isomorphism	56
3.8.6.1	*	56
3.8.6.2	Lax	56
3.8.7	Endomorphism	57
3.8.7.1	Automorphism	57
3.8.7.2	*	57
3.8.8	Catamorphism	57
3.8.8.1	*	57
3.8.8.2	Catamorphism law	57
3.8.8.3	Anamorphism	58
3.8.9	Kernel	58
3.8.9.1	Kernel homomorphism	58
3.9	Object	59
3.9.1	*	59
3.9.2	Terminal object	59
3.9.3	Initial object	59
3.10	Set category	60
3.11	Natural transformation	60
3.11.1	*	61
3.11.2	Natural transformation component	61
3.11.2.1	*	61
3.11.3	Natural transformation in Haskell	61
3.11.4	Cat category	62
3.11.4.1	*	62
3.11.4.2	Bicategory	62
3.12	Category dual	62
3.12.1	Coalgebra	63

3.13	Thin category	63
3.13.1	*	63
3.14	Commuting diagram	63
3.14.1	*	63
3.15	Universal construction	64
3.15.1	*	64
3.16	Product	64
3.16.1	*	64
3.17	Coproduct	64
3.17.1	*	65
3.18	Free object	65
3.19	Internal category	65
3.20	Hom set	65
3.20.1	*	65
3.20.2	Hom-functor	66
3.20.3	Exponential object	66
3.20.3.1	*	66
3.20.3.2	Enriched category	66
4	Data type	68
4.1	*	68
4.2	Actual type	68
4.3	Algebraic data type	68
4.3.1	*	68
4.4	Cardinality	68
4.4.1	*	68
4.5	Data constant	69
4.6	Data constructor	69
4.7	data declaration	69
4.8	Dependent type	69
4.8.1	*	69
4.9	Gen type	69
4.10	Higher-kinded data type	69
4.10.1	*	69
4.11	newtype declaration	70
4.12	Principal type	70
4.13	Product data type	70
4.13.1	*	70
4.13.2	Sequence	70
4.13.2.1	*	71
4.13.2.2	List	71
4.14	Proxy type	71
4.15	Static typing	72
4.16	Structural type	72
4.16.1	*	72
4.17	Structural type system	72
4.17.1	*	72
4.18	Sum data type	72
4.19	Type alias	72
4.20	Type class	72
4.20.1	*	72
4.20.2	Arbitrary type class	73
4.20.2.1	Arbitrary function	73
4.20.3	CoArbitrary type class	73
4.20.3.1	*	73

4.20.4	Typeable type class	73
4.20.4.1	*	73
4.20.5	Type class inheritance	73
4.20.6	Derived instance	74
4.20.6.1	*	74
4.21	Type constant	74
4.22	Type constructor	75
4.23	type declaration	75
4.24	Typed hole	75
4.24.1	*	75
4.25	Type inference	75
4.25.1	*	75
4.26	Type class instance	75
4.27	Type rank	75
4.27.1	*	76
4.28	Type variable	76
4.29	Unlifted type	76
4.29.1	*	76
4.30	Data structure	77
4.30.1	Cons cell	77
4.30.2	Construct	77
4.30.2.1	*	77
4.30.3	Leaf	77
4.30.4	Node	77
4.31	Linear type	77
4.31.1	*	77
4.32	NonEmpty list data type	77
4.33	Session type	78
4.34	Binary tree	78
4.35	Bottom value	78
4.35.1	*	78
4.36	Bound	78
4.36.1	*	78
4.37	Constructor	78
4.37.1	*	78
4.38	Context	79
4.38.1	*	79
4.39	Inhabit	79
4.40	Maybe	79
4.40.0.1	*	79
4.41	Expected type	79
4.42	ADT	79
4.43	Concrete type	79
4.44	Type punning	80
5	Declaration	81
6	Differential operator	82
6.1	*	82
7	Dispatch	83
8	Effect	84
9	Evaluation	85

10 Expression	86
10.1 *	86
10.2 Closed-form expression	86
10.3 RHS	86
10.4 LHS	86
10.5 Redex	87
10.6 Concatenate	87
10.7 Alpha equivalence	87
10.8 Ground expression	87
10.8.1 *	87
10.9 Variable	87
10.9.1 *	87
11 First-class	88
12 Function	89
12.1 *	89
12.2 Arity	90
12.3 Bijection	90
12.3.1 *	90
12.4 Combinator	90
12.5 Function application	91
12.5.1 *	91
12.6 Function body	91
12.7 Function composition	91
12.7.1 *	91
12.8 Function head	91
12.9 Function range	92
12.10 Higher-order function	92
12.10.1 *	92
12.10.2 Fold	92
12.11 Injection	92
12.11.1 *	93
12.12 Partial function	93
12.13 Purity	93
12.13.1 *	93
12.14 Pure function	93
12.15 Sectioning	93
12.16 Surjection	93
12.16.1 *	94
12.17 Unsafe function	94
12.17.1 *	94
12.18 Variadic	94
12.19 Domain	94
12.20 Codomain	94
12.21 Open formula	94
12.22 Recursion	94
12.22.1 *	94
12.22.2 Base case	95
12.22.3 Tail recursion	95
12.22.4 Polymorphic recursion	95
12.22.4.1 *	95
12.23 Free variable	95
12.24 Closure	95
12.24.1 *	95

12.25	Parameter	95
12.25.1	*	96
12.26	Partial application	96
12.26.1	*	96
12.27	Well-formed formula	96
12.27.1	*	96
13	Homotopy	97
13.1	*	97
14	IO	98
15	Kind	99
15.1	*	99
16	Lambda calculus	100
16.1	*	100
16.2	Lambda cube	100
16.2.1	*	101
16.3	Lambda function	101
16.3.1	*	101
16.3.2	Anonymous lambda function	101
16.3.2.1	*	101
16.4	β -reduction	101
16.4.1	*	101
16.4.2	β -normal form	101
16.4.2.1	*	102
16.5	Calculus of constructions	102
16.5.1	*	102
16.6	Curry–Howard correspondence	102
16.6.1	*	102
16.7	Currying	102
16.7.1	*	103
16.8	Hindley–Milner type system	103
16.8.1	*	103
16.9	Reduction	103
16.9.1	*	103
16.10	β - η normal form	103
16.10.1	*	103
16.11	η -abstraction	103
16.11.1	*	104
16.12	Lambda expression	104
17	Lense	105
18	Operation	106
18.1	Constant	106
18.2	Binary operation	106
18.2.1	*	106
18.3	Operator	106
18.3.1	Shift operator	106
18.3.1.1	*	106
18.4	Infix	107
18.5	Fixity	107
18.5.1	*	107
18.6	Zero	107

19	Permutation	108
20	Phrase	109
21	Point-free	110
21.1	*	110
21.2	Blackbird	110
21.2.1	*	110
21.3	Swing	111
21.4	Squish	111
22	Polymorphism	112
22.1	*	112
22.2	Levity polymorphism	112
22.3	Parametric polymorphism	112
22.3.1	Rank-1 polymorphism	112
22.3.1.1	*	112
22.3.2	Let-bound polymorphism	113
22.3.3	Constrained polymorphism	113
22.3.3.1	Ad hoc polymorphism	113
22.3.4	Impredicative polymorphism	113
22.3.4.1	*	113
22.3.5	Higher-rank polymorphism	113
22.3.5.1	*	114
22.4	Subtype polymorphism	114
22.5	Row polymorphism	114
22.6	Kind polymorphism	114
22.7	Linearity polymorphism	115
23	Pragma	116
23.1	LANGUAGE pragma	116
23.1.1	LANGUAGE option	116
23.1.1.1	*	116
23.1.1.2	Useful by default	116
23.1.1.3	AllowAmbiguousTypes	116
23.1.1.4	ApplicativeDo	116
23.1.1.5	ConstrainedClassMethods	117
23.1.1.6	CPP	117
23.1.1.7	DeriveFunctor	117
23.1.1.8	ExplicitForAll	117
23.1.1.9	FlexibleContexts	117
23.1.1.10	FlexibleInstances	118
23.1.1.11	GeneralizedNewtypeDeriving	118
23.1.1.12	ImplicitParams	118
23.1.1.13	LambdaCase	118
23.1.1.14	MultiParamTypeClasses	118
23.1.1.15	MultiWayIf	119
23.1.1.16	OverloadedStrings	119
23.1.1.17	PartialTypeSignatures	119
23.1.1.18	RankNTypes	119
23.1.1.19	ScopedTypeVariables	120
23.1.1.20	TupleSections	120
23.1.1.21	TypeApplications	120
23.1.1.22	TypeSynonymInstances	120
23.1.1.23	UndecidableInstances	121
23.1.1.24	ViewPatterns	121

23.1.1.25 DatatypeContexts	121
23.1.1.26 StandaloneKindSignatures	121
23.1.1.27 PartialTypeSignatures	122
23.1.2 How to make a GHC LANGUAGE extension	122
24 Predicative	124
25 Compositionality	125
25.1 *	125
26 Ψ-combinator	126
26.1 *	126
27 Quantifier	127
27.1 *	127
27.2 Forall quantifier	127
27.2.1 *	127
28 Referential transparency	128
28.1 *	128
29 Relation	129
29.1 *	129
30 REPL	130
31 Semantics	131
31.1 Operational semantics	131
31.2 Denotational semantics	131
31.2.1 Abstraction	131
31.2.1.1 *	132
31.2.1.2 Leaky abstraction	132
31.2.2 Ambigram	132
31.2.3 Binary	132
31.2.4 Arbitrary	132
31.2.5 Refutable	132
31.2.6 Irrefutable	133
31.3 Axiomatic semantics	133
31.3.1 Property	133
31.3.1.1 *	133
31.3.1.2 Associativity	133
31.3.1.3 Left associative	134
31.3.1.4 Right associative	134
31.3.1.5 Non-associative	134
31.3.1.6 Basis	134
31.3.1.7 Commutativity	135
31.3.1.8 Idempotence	135
31.3.1.9 Distributive property	135
31.4 Argument	135
31.4.1 Argument of a function	136
31.4.1.1 *	136
31.5 Content word	136
31.6 Ancient Greek and Latin prefixes	136
31.6.1 *	136
31.7 Idiom	136
31.7.1 *	136

31.8 Impredicative	136
31.9 Context-free grammar	136
31.9.1 *	138
32 Set	139
32.1 *	139
32.2 Closed set	139
32.3 Power set	139
32.4 Singleton	139
32.5 Russell's paradox	139
32.6 Cartesian product	140
32.6.1 Pullback	140
32.6.1.1 *	140
33 Shrinking	141
34 Spine	142
35 Superclass	143
36 Tensor	144
36.1 *	144
37 Testing	145
37.1 Property testing	145
37.1.1 Function property	145
37.1.2 Property testing type	145
37.1.3 Generator	145
37.1.3.1 *	146
37.1.3.2 Custom generator	146
37.1.4 Reusing test code	146
37.1.4.1 Test Commutative property	146
37.1.4.2 Test Symmetry property	146
37.1.4.3 Test Equivalence property	147
37.1.4.4 Test Inverse property	147
37.1.5 QuickCheck	147
37.1.5.1 Manual automation with QuickCheck properties	147
37.2 Write tests algorithm	148
38 Uncurry	149
39 Unit	150
40 Nullary	151
41 Logic	152
41.1 Proposition	152
41.1.1 *	152
41.1.2 Atomic proposition	152
41.1.2.1 *	152
41.1.3 Compound proposition	152
41.1.3.1 *	152
41.1.4 Propositional logic	152
41.1.4.1 *	153
41.1.4.2 First-order logic	153
41.2 Logical connective	153
41.2.1 *	153

41.2.2	Conjunction	153
41.2.3	Disjunction	154
41.3	Predicate	154
41.4	Statement	154
41.4.1	*	154
41.5	Iff	155
42	Haskell structures	156
42.1	Pattern match	156
42.1.1	As-pattern	156
42.1.1.1	*	156
42.1.2	Wild-card	156
42.1.2.1	*	156
42.1.3	Case	157
42.1.4	Guard	157
42.1.4.1	*	157
42.1.5	Pattern guard	157
42.1.5.1	*	158
42.1.6	Lazy pattern	158
42.1.6.1	*	158
42.1.7	Pattern binding	158
42.1.7.1	*	158
42.2	Smart constructor	158
42.3	Level of code	159
42.3.1	*	159
42.3.2	Type level	159
42.3.2.1	Type level declaration	159
42.3.2.2	Type check	159
42.3.3	Term level	160
42.3.4	Compile level	160
42.3.4.1	*	160
42.3.5	Runtime level	160
42.3.6	Kind level	160
42.3.6.1	Kind check	160
42.4	Orphan type instance	161
42.5	Undefined	161
42.6	Hierarchical module name	161
42.6.1	*	166
42.7	import	166
42.8	Let	167
42.8.1	*	167
42.9	Where	167
42.9.1	*	168
42.10	Reserved word	168
42.10.1	*	168
42.11	Haskell Language Report	168
42.11.1	*	168
42.12	Haskell'	168
42.12.1	*	168

43 Computer science	169
43.1 Guerrilla patch	169
43.1.1 Monkey patch	169
43.2 Interface	169
43.3 Module	169
43.4 Scope	169
43.4.1 Dynamic scope	169
43.4.2 Lexical scope	169
43.4.2.1 *	170
43.4.3 Local scope	170
43.4.3.1 *	170
43.5 Shadowing	170
43.6 Syntactic sugar	170
43.7 System F	170
43.7.1 *	170
43.8 Tail call	170
43.9 Thunk	170
43.10 Application memory	171
43.11 Turing machine	171
43.11.1 Turing complete	171
43.11.1.1 *	171
44 Graph theory	172
44.1 Successor	172
44.1.1 Direct successor	172
44.2 Predecessor	172
44.2.1 Direct predecessor	172
44.3 Degree	172
44.3.1 Indegree	172
44.3.2 Outdegree	172
44.4 Adjacency matrix	172
44.4.0.1 InstanceSigs	173
44.5 Strongly connected	173
44.5.1 *	173
44.5.2 Strongly connected component	173
44.5.2.1 *	173
45 Linear	174
45.1 *	174
46 Stream	175
47 Bisimulation	176
47.1 *	176
48 Syntax tree	177
48.1 Abstract syntax tree	177
48.1.1 *	177
48.2 Concrete syntax tree	177
48.2.1 *	177
49 Domain specific language	178
49.1 *	178
49.2 Embedded domain specific language	178
49.2.1 *	178

50 Tagless-final	179
III Give definitions	180
51 Identity type	181
52 Constant type	182
53 Gen	183
54 Tensorial strength	184
55 Strong monad	185
56 Weak head normal form	186
56.1 *	186
57 Function image	187
57.1 *	187
58 Invertible	188
59 Invertibility	189
60 Define LANGUAGE pragma options	190
60.1 ExistentialQuantification	190
60.2 GADTs	190
60.3 *	190
60.4 GeneralizedNewTypeClasses	190
60.5 FuncitonalDependencies	190
61 GHC check keys	191
61.1 -Wno-partial-type-signatures	191
62 Generalised algebraic data types	192
62.1 *	192
63 Order theory	193
63.1 Domain theory	193
63.2 Lattice	193
63.3 Order	193
63.3.1 Preorder	193
63.3.1.1 *	193
63.3.1.2 Total preorder	193
63.3.2 Partial order	194
63.3.2.1 *	194
63.4 Partial order	194
63.5 Total order	194
64 Universal algebra	195
65 Relation	196
65.1 Reflexivity	196
65.1.1 *	196
65.2 Irreflexivity	196
65.2.1 *	196
65.3 Transitivity	196

65.3.1 *	197
65.4 Symmetry	197
65.4.1 *	197
65.5 Equivalence	197
65.5.1 *	197
65.6 Antisymmetry	197
65.6.1 *	197
65.7 Asymmetry	197
65.7.1 *	198
66 Cryptomorphism	199
66.1 *	199
67 Lexically scoped type variables	200
68 Abstract data type	201
68.1 *	201
69 Concrete type	202
70 Functional dependencies	203
71 MonoLocalBinds	204
72 KindSignatures	205
73 ExplicitNamespaces	206
74 Combinator pattern	207
75 Symbolic expression	208
75.1 *	208
76 Polynomial	209
76.1 *	209
77 Data family	210
78 Type synonym family	211
79 Indexed type family	212
79.1 *	212
80 TypeFamilies	213
81 Error	214
81.1 *	214
82 Exception	215
82.1 *	215
83 ConstraintKinds	216
84 Specialisation	217
84.1 *	217
85 Diagram	218

86	Cathegory theoretical presheaf	219
87	Topological presheaf	220
88	Diagonal functor	221
89	Limit functor	222
90	Dual vector space	223
91	Fundamental group	224
92	Algebra of continuous function	225
93	Tangent and cotangent bundle	226
94	Group action / representation	227
95	Lie algebra	228
96	Tensor product	229
97	Forgetful functor	230
98	Free functor	231
99	Homomorphism group	232
100	Representable functor	233
101	Corecursion	234
102	Coinduction	235
103	Initial algebra of an endofunctor	236
104	Terminal coalgebra for an endofunctor	237
IV	Citations	238
V	Good code	240
105	Good: Type aliasing	241
106	Good: Type wideness	242
107	Good: Print	243
108	Good: Fold	244
109	Good: Computation model	245
110	Good: Make bottoms only local	246
111	Good: Newtype wrap is ideally transparent for compiler and does not change performance	247
112	Good: Instances of types/type classes must go with code you write	248

113 Good: Functions can be abstracted as arguments	249
114 Good: Infix operators can be bind to arguments	250
115 Good: Arbitrary	251
116 Good: Principle of Separation of concerns	252
117 Good: Function composition	253
118 Good: Point-free	254
118.1Good: Point-free is great in multi-dimentionns	254
119 Good: Functor application	255
120 Good: Parameter order	256
121 Good: Applicative monoid	257
122 Good: Creative process	258
122.1Pick phylosophy principles one to three the more - the harder the implementation	258
122.2Draw the most blurred representation	258
122.3Deduce abstractions and write remotely what they are	258
122.4Model of computation	258
122.4.1 Model the domain	258
122.4.2 Model the types	258
122.4.3 Think how to write computations	258
122.5Create	258
123 «Good: About operators (<\$) (**>) (<*) (>>) »>	259
124 Good: About functions like {mapM, sequence}_	260
125 Good: Guideliles	261
125.1Wiki.haskell	261
125.1.1 Documentation	261
125.1.1.1 Comments write in application terms, not technical.	261
125.1.1.2 Tell what code needs to do not how it does.	261
125.1.2 Haddock	261
125.1.2.1 Put haddock comments to ever exposed data type and function.	261
125.1.2.2 Haddock header	261
125.1.3 Code	261
125.1.3.1 Try to stay closer to portable (Haskell98) code	261
125.1.3.2 Try make lines no longer 80 chars	261
125.1.3.3 Last char in file should be newline	261
125.1.3.4 Symbolic infix identifiers is only library writer right	261
125.1.3.5 Every function does one thing.	261
126 Good: Use Typed holes to progress the code	262
127 Good: Haskell allows infinite terms but not infinite types	263
128 Good: Use type sysonims to differ the information	264
129 «Good: Control.Monad.Error -> Control.Monad.Except»>	265

130Good: Monad OR Applicative	266
130.0.1 Start writing monad using 'return', 'ap', 'liftM', 'liftM2', '»' instead of 'do', '»='	266
130.0.2 Basic case when Applicative can be used	266
130.0.3 Applicative block vs Monad block	266
131Good: Haskell Package Versioning Policy	267
131.1 *	267
132Good: Linear type	268
133Good: Exception vs Error	269
134Good: Let vs. Where	270
135Good: RankNTypes	271
136Good: Orphan type instance	272
137Good: Smart constructor	273
138Good: Thin category	274
139Good: Recursion	275
140Good: Monoid	276
141Good: Free monad	277
142Good: Use mostly where clauses	278
143Good: Where clause is in a scope with function parameters	279
144Good: Strong preference towards pattern matching over {head, tail, etc.} functions	280
145Good: Patternmatching is possible on monadic bind in do	281
146Good: Applicative vs Monad	282
147Good: StateT, ReaderT, WriterT	283
148Good: Working with MonadTrans and lift	284
149Good: Don't mix Where and Let	285
150Good: Where vs. Let	286
151Good: The proper nature algorithm that models behaviour of many objects is computation heavy	287
152Good: In Haskell parameters bound by lambda declaration instantiate to only one concrete type	288
153Good: Instance is a good structure to draw a type line	289
154Good: MTL vs. Transformers	290

VI	Bad code	291
155	Bad pragma	292
155.1	Bad: Dangerous LANGUAGE pragma option	292
VII	Useful functions to remember	293
156	Prelude	294
156.1	Ord	294
156.2	Calc	294
156.3	List operations	294
157	Data.List	295
158	Data.Char	296
159	QuickCheck	297
VIII	Tools	298
160	ghc-pkg	299
161	Search over the Haskell packages code: Codesearch from Aelve	300
162	Integration of NixOS/Nix with Haskell IDE Engine (HIE) and Emacs (Spacemacs)	301
162.11.	Install the Cachix: https://github.com/cachix/cachix	301
162.22.	Installation of HIE: https://github.com/infinisil/all-hies/#cached-builds	301
162.2.1.2.1.	Provide cached builds	301
162.2.2.2.a.	Installation on NixOS distribution:	301
162.2.3.2.2.b.	Installation with Nix package manager:	302
162.33.	Emacs (Spacemacs) configuration:	302
162.44.	Open the Haskell file from a project	303
162.55.	Be pleased writing code	303
162.66.	(optional) Debugging	303
163	Debugger	305
164	GHCID	306
IX	Libs	307
165	Exceptions	308
165.1	Exceptions - optionally pure extensible exceptions that are compatible with the mtl	308
165.2	Safe-exceptions - safe, simple API equivalent to the underlying implementation in terms of power, encourages best practices minimizing the chances of getting the exception handling wrong.	308
165.3	Enclosed-exceptions - capture exceptions from the enclosed computation, while reacting to asynchronous exceptions aimed at the calling thread.	308
166	Memory management	309
166.1	membrain - type-safe memory units	309
167	Parsers - megaparsec	310

168	CLIs - optparse-applicative	311
169	HTML - Lucid	312
170	Web applications - Servant	313
171	IO libraries	314
171.1	Conduit - practical, monolythic, guarantees termination return	314
171.2	Pipes + Pipes Parse - modular, more primitive, theoretically driven	314
172	JSON - aeson	315
173	Backpack	316
X	Drafts	317
174	Exception handling	318
175	Constraints	321
176	Monad transformers and their type classes	323
177	Layering monad transformers	324
178	Hoogle	325
178.1	Search	325
178.2	Scope	325
178.2.1	Default	325
178.2.2	Hierarchical module name system (from big letter):	325
178.2.3	Packages (lower case):	326
179	ST-Trick monad	327
179.1	*	327
180	Either	328
180.1	*	328
181	Inverse	329
182	Inversion	330
183	Inverse function	331
184	Inverse morphism	332
185	Partial inverse	333
186	PatternSynonyms	334
186.1	*	334
187	GHC debug keys	335
187.1	ddump-ds	335
187.1.1	*	335
188	GHC optimize keys	336
188.1	foptimal-applicative-do	336

189	Computational trinitarianism	337
189.1 *		338
190	Techniques functional programming deals with the state	339
190.1	Minimizing	339
190.2	Concentrating	339
190.3	Deferring	339
191	Monadic Error handling	340
192	Functions	341
193	Void	342
193.1 *		342
194	Constructive proof	343
195	Intuitionistic logic	344
195.1 *		344
196	Principle of explosion	345
196.1 *		345
197	Universal property	346
198	Yoneda lemma	347
199	Monoidal category, functoriality of ADTs, Profunctors	348
200	Const functor	349
201	Arrow in Haskell	350
202	Contravariant functor	351
203	Profunctor	352
XI	Reference	353
204	Functor-Applicative-Monad Proposal	354
204.1 *		354
205	Haskell-98	355
205.1	Old instance termination rules	355
206	Performance results and comparisons of types & solutions	356
XII	Liturgy	357

Contents

Part I

Introduction

“Employ your time in improving yourself by other men’s writings so that you shall come easily by what others have labored hard for.”
(Socrates by Plato)

Important notes on Haskell, [category](#) theory & related fields, terms and recommendations.

Resources:

- Web book: <https://blog.latukha.com/haskell-notes>
- GitHub: <https://github.com/Anton-Latukha/haskell-notes>
- GitLab: <https://gitlab.com/Anton.Latukha/haskell-notes>
- View PDF: <https://github.com/Anton-Latukha/haskell-notes/blob/master/README.pdf>
- Download PDF: <https://github.com/Anton-Latukha/haskell-notes/raw/master/README.pdf>
- L^AT_EX: <https://github.com/Anton-Latukha/haskell-notes/raw/master/README.tex>

This is a complex Org markup file with L^AT_EX formulas.
GitHub & GitLab only partially parse Org into HTML.

To get the full view:

- Outline navigation
- L^AT_EX formulas:
$$\left[-\frac{\hbar^2}{2m}\nabla^2 + V(\vec{r}, t)\right]\Psi(\vec{r}, t) = i\hbar\frac{\partial}{\partial t}\Psi(\vec{r}, t), \quad \sum_{k,j}\left[-\frac{\hbar^2}{\sqrt{a}}\frac{\partial}{\partial q^k}\left(\sqrt{a}a^{kj}\frac{\partial}{\partial q^j}\right) + V\right]\Psi + \frac{\hbar}{i}\frac{\partial\Psi}{\partial t} = 0$$
- [Interlinks](#): Interlinks

, please refer to Org mode capable viewer/editor, or to the web book.

Note about markup: <<<This is a radio target>>> - for dynamic org-mode linking.

To prettify radio targets in Emacs with Elisp snippet to prettify <<<Radio targets>>> to Radio targets:

```
;;; 2019-06-12: NOTE: Prettify '<<<Radio targets>>>' to be shown as '_Radio_targets_' when `org-
;;; This is improvement of the code from: Tobias&glmorous: https://emacs.stackexchange.com/quest
;;; There exists library created from the sample: https://github.com/talwrii/org-hide-targets
(defcustom org-hidden-links-additional-re "\\(<<<\\)[[:print:]]+?\\(>>>\\)"
  "Regular expression that matches strings where the invisible-property of the sub-matches 1 and
:type '(choice (const :tag "Off" nil) regexp)
:group 'org-link)
```

```
(make-variable-buffer-local 'org-hidden-links-additional-re)

(defun org-activate-hidden-links-additional (limit)
  "Put invisible-property org-link on strings matching `org-hide-links-additional-re'."
  (if org-hidden-links-additional-re
      (re-search-forward org-hidden-links-additional-re limit t)
      (goto-char limit)
      nil))

(defun org-hidden-links-hook-function ()
  "Add rule for `org-activate-hidden-links-additional' to `org-font-lock-extra-keywords'.
  You can include this function in `org-font-lock-set-keywords-hook'."
  (add-to-list 'org-font-lock-extra-keywords
    '(org-activate-hidden-links-additional
      (1 '(face org-target invisible org-link))
      (2 '(face org-target invisible org-link)))))

(add-hook 'org-font-lock-set-keywords-hook #'org-hidden-links-hook-function)

SCHT: and metadata in :properties: - of my org-drill practices, please just run org-drill-strip-all-data.
```


Part II

Definitions

Chapter 1

Algebra

al-jabr - assemble parts.

A system of parts based on given axioms ([properties](#)).

—

- a. [Abstract algebra](#) - the study of number systems and operations within them.
- b. [Algebra](#) - vector space over a field with a multiplication.
- c. [Algebra](#) - a [set](#) with its [algebraic structure](#).

1.1 *

Algebras

1.2 Algebraic

Composite from simple parts.

Also: [Algebraic data type](#).

1.3 Algebraic structure

[Algebraic structure](#) on a [set](#) (called carrier [set](#) or underlying [set](#)) is a collection of finitary operations on that [set](#).

The [set](#) with this [structure](#) is also called an [algebra](#).

[Algebraic structures](#) include [groups](#), [rings](#), fields, and lattices. More complex [structures](#) can be defined by introducing multiple operations, different underlying [sets](#), or by altering the defining axioms. Examples of more complex [algebraic structures](#) include vector spaces, modules, and [algebras](#).

Table 1.1: Algebraic structures

	Closure	Associativity	Identity	Invertability	Commutativity
Semigroupoid		✓			
Small Category		✓	✓		
Groupoid		✓	✓	✓	
Magma	✓				
Quasigroup	✓			✓	
Loop	✓		✓	✓	
Semigroup	✓	✓			
Inverse Semigroup	✓	✓		✓	
Monoid	✓	✓	✓		
Group	✓	✓	✓	✓	
Abelian group	✓	✓	✓	✓	✓
Ring	✓	✓	✓	✓	under +

1.3.1 *

Algebraic structures

1.3.2 Fundamental theorem of algebra

Any non-constant single-variable polynomial with complex coefficients has at least one complex root.

From this definition follows property that the field of complex numbers is algebraically closed.

1.4 Modular arithmetic

System for integers where numbers wrap around the certain values (single - modulus, plural - moduli).

Example - 12-hour clock.

1.4.1 *

Clock arithmetic

1.4.2 Modulus

Special numbers where arithmetic wraps around in modular arithmetic.

1.4.2.1 *

Moduli - plural.

Chapter 2

Bind

Establishing equality between two [objects](#).

Most often:

- equating [variable](#) to a value.
- equating [parameter](#) of a [function](#) to an [argument](#) ([variable](#)/value/[function](#)). This term often is equated to [applying argument](#) to a [function](#), which includes [\$\beta\$ -reduction](#).

2.1 *

Binds
Binding
Bindings

Chapter 3

Category theory

Category \mathcal{C} consists of the **basis**:

Primitives:

- a. **Objects** - $a^{\mathcal{C}}$. A **node**. **Object** of some **type**. Often **sets**, than it is **Set category**.
- b. **Arrows** - $(a, b)^{\mathcal{C}}$ (AKA **morphisms** mappings).
- c. **Arrow (morphism) composition** - **binary operation**: $(a, b)^{\mathcal{C}} \circ (b, c)^{\mathcal{C}} \equiv (a, c)^{\mathcal{C}} \mid \forall a, b, c \in \mathcal{C}$.
AKA principle of **compositionality** for **arrows**.

Properties (or axioms):

- a. **Associativity** of **morphisms**: $h \circ (g \circ f) \equiv (h \circ g) \circ f \mid f_{a \rightarrow b}, g_{b \rightarrow c}, h_{c \rightarrow d}$.
- b. Every **object** has (two-sided) **identity morphism** (& in fact - exactly one): $1_x \circ f_{a \rightarrow x} \equiv f_{a \rightarrow x}, g_{x \rightarrow b} \circ 1_x \equiv g_{x \rightarrow b} \mid \forall x \exists 1_x, \forall f_{a \rightarrow x}, \forall g_{x \rightarrow b}$.
- c. Principle of **compositionality**.

From these axioms, can be proven that there is exactly one **identity morphism** for every **object**.

Object and **morphism** are complete **abstractions** for anything.

In majority of cases under **object** is a state and **morphism** is a change.

3.1 *

Category
Categories

3.2 Abelian category

Generalised [category](#) for homological [algebra](#) (having a possibility of basic constructions and techniques for it).

[Category](#) which:

- has a [zero object](#),
- has all [binary](#) biproducts,
- has all [kernel](#)'s and cokernels,
- (it has all [pullbacks](#) and pushouts)
- all [monomorphism](#)'s and [epimorphism](#)'s are normal.

[Abelian category](#) is very stable; for example they are regular and they satisfy the snake lemma. The class of [Abelian categories](#) is [closed](#) under several categorical constructions.

There is notion of [Abelian monoid](#) (AKS [Commutative monoid](#)) and [Abelian group](#) ([Commutative group](#)).

Basic examples of $*$:

- [category](#) of Abelian [groups](#)
- [category](#) of modules over a [ring](#).

$*$ are widely used in [algebra](#), [algebraic](#) geometry, and topology.

$*$ has many constructions like in [categories](#) of modules:

- kernels
- exact [sequences](#)
- [commutative](#) diagrams

$*$ has disadvantage over [category](#) of modules. [Objects](#) do not necessarily have elements that can be manipulated directly, so traditional definitions do not work. Methods must be supplied that allow definition and manipulation of [objects](#) without the use of elements.

3.2.1 $*$

Abelian categories

3.3 Composition

Axiom of [Category](#).

3.3.1 *

Composable
Compositions

3.4 Endofunctor category

From the name, in this [Category](#):

- [objects](#) of *End* are [Endofunctors](#) $E^{C \rightarrow C}$
- [morphisms](#) are [natural transformations](#) between [endofunctors](#)

3.5 Functor

* full translation (map) of one [category](#) into another.

Translating [objects](#) and [morphisms](#) (as input can take [morphism](#) or [object](#)).

* - [forgetful](#) - discards part of the [structure](#).

* - faithful - fully preserves all [morphisms](#) - [injective](#) on Hom-sets.

* - full - translation of [morphisms](#) fully covers all the [morphisms](#) between according objects in the target category.

For [Functor type class](#) or [fmap](#) - see [Power set functor](#).

[Functor properties](#) (axioms):

- $F^{C \rightarrow D}(a) \mid \forall a^C$ - every source [object](#) is mapped to [object](#) in target [category](#)
- $\overline{(F^{C \rightarrow D}(a), F^{C \rightarrow D}(b))}^{\rightarrow D} \mid \forall \overline{(a, b)}^{\rightarrow C}$ - every source [morphism](#) is mapped to target [category morphism](#) between corresponding [objects](#)
- $F^{C \rightarrow D}(\overrightarrow{g}^C \circ \overrightarrow{f}^C) = F^{C \rightarrow D}(\overrightarrow{g}^C) \circ F^{C \rightarrow D}(\overrightarrow{f}^C) \mid \forall y = \overrightarrow{f}^C(x), \forall \overrightarrow{g}^C(y)$ - [composition](#) of [morphisms](#) translates directly (tautologically goes from other two)

These axioms guarantee that [composition](#) of [functors](#) can be fused into one [functor](#) with [composition](#) of [morphisms](#). This process called [fusion](#).

In Haskell this axioms have form:

```
fmap id = id
fmap (f . g) = fmap f . fmap g
```

Since `*` is 1-1 mapping of initial [objects](#) - it is a memoizable dictionary with [cardinality](#) of initial [objects](#). Also in [Hask category](#) [functors](#) are obviously [endofunctors](#) \therefore they are special [kinds](#) of containers for the parametric values (AKA [product type](#)). In Haskell [product type](#) `*` are [endo-functors](#) from [polymorphic type](#) into a [functor](#) wrapper of a [polymorphic type](#).

`*` translates in one direction, and does not provide algorithm of reversing itself or retrieving the parametric value.

3.5.1 `*`

Functors

3.5.2 Power set functor

$\mathcal{P}^{S \rightarrow \mathcal{P}(S)}$

`*` - [functor](#) from [set](#) S to its [power set](#) $\mathcal{P}(S)$.

[Functor type class](#) in Haskell defines a `*` and allows to do [function application](#) inside [type structure](#) layers (denoted f or m). [IO](#) is also such [structure](#).

[Power set](#) is unique to the [set](#), `*` is unique to the [category](#) ([data type](#)).

`*` embodies in itself any [endofunctor](#). It is easily seen from Haskell definition - that the `*` is the [polymorphic](#) generalization over any [endofunctor](#) in a [category](#). [Application](#) of a [function](#) to `*` gives a particular [endofunctor](#) (see [Hask category](#)).

```
class Functor f where
  fmap :: (a -> b) -> f a -> f b
```

[Functor](#) instance must be of [kind](#) `(* -> *)`, so instance for [higher-kinded data type](#) must be [applied](#) until this [kind](#).

[Composed](#) `*` can [lift functions](#) through any layers of [structures](#) that belong to [Functor type class](#).

`*` can be used to filter-out [error](#) cases ([Nothing](#) & Left cases) in [Maybe](#), [Either](#) and related [types](#).

3.5.2.1 `*`

`fmap`
Functor type class

3.5.2.2 Power set functor laws

[Type](#) instance of [functor](#) should abide this laws:

a. `*`

Functor laws

b. Power set functor identity law

```
fmap id == id
```


c. Power set functor composition law

```
fmap (f.g) == fmap f . fmap g
```

In words, it is if several [functions](#) are [composed](#) and then [fmap](#) is [applied](#) on them - it should be the same as if [functions](#) was [fmapped](#) and then [composed](#).

3.5.2.3 Lift

```
fmap :: (a -> b) -> (f a -> f b)
```

[Functor](#) takes [function](#) $a \rightarrow b$ and returns a [function](#) $f\ a \rightarrow f\ b$ this is called [lifting](#) a [function](#). [Lift](#) does a [function application](#) through the [data structure](#).

a. *

Lifting

3.5.2.4 Power set functor is a free monad

Since:

- $\forall e \in S : \exists \{e\} \in \mathcal{P}(S) \models \forall e \in S : \exists (e \rightarrow \{e\}) \equiv unit$
- $\forall \mathcal{P}(S) : \mathcal{P}(S) \in \mathcal{P}(S) \models \forall \mathcal{P}(S) : \exists (\mathcal{P}(\mathcal{P}(S)) \rightarrow \mathcal{P}(S)) \equiv join$

3.5.3 Functorial

Corresponds to [functor laws](#).

3.5.4 Forgetful functor

[Functor](#) that forgets part or all of what defines [structure](#) in [domain category](#).

$F^{Grp \rightarrow Set}$ that translates [groups](#) into their underlying [sets](#).

[Constant functor](#) is another example.

3.5.4.1 *

Forgetful

3.5.5 Identity functor

Maps all [category](#) to itself. All [objects](#) and [morphisms](#) to themselves.

Denotation:

$1^{C \rightarrow C}$

3.5.6 Endofunctor

Is a [functor](#) which source ([domain](#)) and target ([codomain](#)) are the same [category](#).

$$F^{C \rightarrow C}, E^{C \rightarrow C}$$

3.5.6.1 *

Endofunctors

3.5.7 Applicative functor

* - Computer science term. [Category](#) theory name - [lax monoidal functor](#). And in [category](#) *Set*, and so in [category](#) *Hask* all [applicatives](#) and [monads](#) are strong (have [tensorial strength](#)).

* - [sequences functorial](#) computations (plain [functors](#) can't).

```
(<*>) :: f (a -> b) -> f a -> f b
```

Requires [Functor](#) to exist.

Requires [Monoidal structure](#).

Has [monoidal structure](#) rules, separated from [function application](#) inside [structure](#).

[Data type](#) can have several [applicative](#) implementations.

Standard definition:

```
class Functor f => Applicative f
  where
    (<*>) :: f (a -> b) -> f a -> f b
    pure  :: a -> f a
```

`pure` - if a [functor](#), [identity Kleisli arrow](#), [natural transformation](#).

[Composition](#) of `*` always produces `*`, contrary to [monad](#) ([monads](#) are not [closed](#) under [composition](#)).

`Control.Monad` has an old [function](#) `ap` that is old implementation of `<*>`:

```
ap :: Monad m => m (a -> b) -> m a -> m b
```

3.5.7.1 *

[Applicative](#)

[Applicatives](#)

[Applicative functors](#)

3.5.7.2 Applicative law**3.5.7.3 ***

Applicative laws

- a. Applicative identity law

```
pure id <*> v = v
```

- b. Applicative composition law [Function composition](#) works regularly.

```
pure (.) <*> u <*> v <*> w = u <*> (v <*> w)
```

- c. Applicative homomorphism law Internal [function application](#) doesn't change the [structure](#) around values.

```
pure f <*> pure x = pure (f x)
```

- d. Applicative interchange law On condition that internal [order](#) of [evaluation](#) is preserved - [order](#) of operands is not relevant.

```
u <*> pure y = pure ($ y) <*> u
```

3.5.7.4 Applicative function

- a. liftA*

- a. liftA Essentially a [fmap](#).

```
:type liftA
liftA :: Applicative f => (a -> b) -> f a -> f b
Lifts function into applicative function.
```

- b. liftA2 Lifts [binary function](#) across two [Applicative functors](#).

```
liftA2 :: Applicative f => (a -> b -> c) -> f a -> f b -> f c
liftA2 f x y == pure f <*> x <*> y
```

- c. «[liftA2 \(<*>\)](#)» [liftA2 \(<*>\)](#) is pretty useful. It can [lift binary operation](#) through the two layers:
It is two-layer [Applicative](#).

```
liftA2 :: Applicative f => (    a        -> b -> c ) -> f    a        -> f    b    -
<*> :: Applicative f =>    (f  (a -> b) -> f a -> f b)
liftA2 (<*>) :: (Applicative f1, Applicative f2) =>    f1 (f2 (a -> b)) -> f1 (f2 a) -
```

- d. «[liftA2 \(liftA2 \(<*>\)\)](#)» [liftA2 \(<*>\)](#) 3-layer version.

- e. liftA3 [liftA2 3-parameter](#) version.

```
liftA3 f x y z == pure f <*> x <*> y <*> z
```

- b. Conditional [applicative](#) computations

```
when :: Applicative f => Bool -> f () -> f ()
```

Only when True - perform an [applicative](#) computation.

```
unless :: Applicative f => Bool -> f () -> f ()
```

Only when False - perform an [applicative](#) computation.

3.5.7.5 Special applicatives

- a. Identity applicative

```
-- Applicative f =>
-- f ~ Identity
type Id = Identity
instance Applicative Id
  where
    pure :: a -> Id a
    (<*>) :: Id (a -> b) -> Id a -> Id b

mkId = Identity
xs = [1, 2, 3]

const <$> mkId xs <*> mkId xs'
-- [1,2,3]
```

- b. Constant applicative It holds only to one value. The [function](#) does not exist and last [parameter](#) is a phantom.

```
-- Applicative f =>
-- f ~ Constant e
type C = Constant
instance Applicative C
  where
    pure :: a -> C e a
    (<*>) :: C e (a -> b) -> C e a -> C e b
```

- c. Maybe applicative "There also can be no [function](#) at all."

If [function](#) might not exist - embed `f` in [Maybe structure](#), and use [Maybe applicative](#).

```
-- f ~ Maybe
type M = Maybe
pure :: a -> M a
(<*>) :: M (a -> b) -> M a -> M b
```

- d. Either applicative `pure` is `Right`.
 Defaults to `Left`.
 And if there is two `Left`'s - to `Left` of the first `argument`.
- e. Validation applicative The Validation `data type` isomorphic to `Either`, but has accumulative `Applicative` on the `Left` side.
 Validation `data type` is not a `monad`. Validation is an example of, "An `applicative functor` that is not a `monad`."
 While `Either monad` on `Left case` just drops computation and returns this first `Left`.
`Monad` needs to process the result of computation - it requires to be able to process all `Left error statement` cases for Validation, it is or non-terminating `Monad` or one which is impossible to implement in `polymorphic` way with Validation.

3.5.7.6 Monad

monos sole
monáda `unit`

* - `monoid` in `endofunctor category` with η (`unit`) and μ (`join`) `natural transformations`.

`Monad` on \mathcal{C} is $\{E^{\mathcal{C} \rightarrow \mathcal{C}}, \eta, \mu\}$:

- $E^{\mathcal{C} \rightarrow \mathcal{C}}$ - is an `endofunctor`
- two `natural transformations`, $1^{\mathcal{C}} \rightarrow E$ and $E \circ E \rightarrow E$:
 - $\eta^{1^{\mathcal{C}} \rightarrow E} = \text{unit}^{Identity \rightarrow E}(x) = f^{x \rightarrow E(x)}(x)$
 - $\mu^{(E \circ E) \rightarrow E} = \text{join}^{(E \circ E) \rightarrow (Identity \circ E)}(x) = |y = E(x)| = f^{E(y) \rightarrow y}(y)$

where:

- \mathcal{C} is a `category`
- $1^{\mathcal{C}}$ denotes the \mathcal{C} `identity functor`
- $(E \circ E)$ - `endofunctor` $\mathcal{C} \rightarrow \mathcal{C}$

Definition with $\{E^{\mathcal{C} \rightarrow \mathcal{C}}, \eta, \mu\}$ (in `Hask`: $\{e :: f a \rightarrow f b, \text{pure}, \text{join}\}$) - is classic categorical, in Haskell minimal complete definition is $\{fmap, \text{pure}, (>=>)\}$.

If there is a `structure` S , and a way of taking `object` x into S and a way of collapsing $S \circ S$ - there probably a `monad`.

Mostly `monads` used for sequencing actions (computations) (that looks like imperative programming), with ability to depend on previous chains. Note if `monad` is `commutative` - it does not `order` actions.

`Monad` can shorten/terminate [sequence](#) of computations. It is implemented inside `Monad` instance. For example [Maybe monad](#) on [Nothing](#) drops chain of computation and returns [Nothing](#).

* inherits the [Applicative](#) instance methods:

```
import Control.Monad (ap)
return == pure
ap == (<*>) -- + Monad requirement
```

Table 3.1: `Monad` in mathematics and Haskell

Math	Meaning	Cat/Fctr	$X \in C$	Type	Haskell
Id	endofunctor "Id"	$C \rightarrow C$	$X \rightarrow Id(X)$	$a \rightarrow a$	<code>id</code>
E	endofunctor "monad"	$C \rightarrow C$	$X \rightarrow E(X)$	$m\ a \rightarrow m\ b$	<code>fmap</code>
η	natural transformation "unit"	$Id \rightarrow E$	$Id(X) \rightarrow E(X)$	$a \rightarrow m\ a$	<code>pure</code>
μ	natural transformation "multiplication"	$E \circ E \rightarrow E$	$E(E(X)) \rightarrow E(X)$	$m\ (m\ a) \rightarrow m\ a$	<code>join</code>

Internals of `Monad` are Haskell [data types](#), and as such - they can be consumed any number of times.

[Composition](#) of [monadic types](#) does not always results in [monadic type](#).

a. *

Monads
Monadic

b. Monad law `Monad` corresponds to [functor laws](#) & [applicative laws](#) and additionally:

a. * Monad laws

b. Monad left identity law

```
pure x >>= f == f x
```

Explanation:

```
>>= :: Monad f => f a -> (a -> f b) -> f b
      pure x >>=      f          == f x
```

Rule that `>>=` must get first [argument structure](#) internals and [apply](#) to the [function](#) that is the second [argument](#).

c. Monad right identity law

```
f >>= pure == f
```

Explanation:

```
>>= :: Monad f => f a -> (a -> f b) -> f b
      f      >>=      pure      == f
```

AKA it is a [tacit](#) description of a [monad bind](#) as [endofunctor](#).

d. Monad associativity law

```
(m >>= f) >>= g == m >>= (\ x -> f x >>= g)
```

c. Monad type class

```
class Applicative m => Monad m where
  (>>=) :: m a -> (a -> m b) -> m b
  (>>) :: m a -> m b -> m b
  return :: a -> m a
```

a. MonadPlus type class Is a [monoid](#) over [monad](#), with additional rules.

The precise [set](#) of rules ([properties](#)) not agreed upon. Class instances obey [monoid](#) & [left zero](#) rules, some additionally obey [left catch](#) and others [left distribution](#).

Overall there * currently reforms ([MonadPlus](#) reform proposal) in several smaller nad strictly defined [type classes](#).

Subclass of an [Alternative](#).

a. *

Monadplus

d. [Functor](#) -> [Applicative](#) -> [Monad](#) progression

```
<$> :: Functor    f => (a -> b) -> f a -> f b
<*> :: Applicative f => f (a -> b) -> f a -> f b
=<< :: Monad      f => (a -> f b) -> f a -> f b
```

[pure](#) & [join](#) are [Natural transformations](#) for the [fmap](#).

e. Monad function

a. Return function

```
return == pure
```

Nonstrict.

b. Join function

```
join :: Monad m => m (m a) -> m a
```

Generales knowledge of [concat](#).

[Kleisli composition](#) that flattens two layers of [structure](#) into one.

The way to express ordering in [lambda calculus](#) is to nest.

a. *

join

b. [join](#) . [fmap](#) == ([=<<](#))

```

-- b = f b
fmap      :: Monad f => (a -> f b) -> f a -> f (f b)
join      :: Monad f =>                f (f a) -> f a
join . fmap :: Monad f => (a -> f b) -> f a      -> f b
flip      >>= :: Monad f => (a -> f b) -> f a      -> f b

```

c. Bind function

```

>>=      :: Monad f => f a -> (a -> f b) -> f b
join . fmap :: Monad f => (a -> f b) -> f a -> f b
Nonstrict.

```

The most ubiquitous way to `>>=` something is to use [Lambda function](#):

```

getLine >>= \name -> putStrLn "age pls:"

```

Also very neat way is to bundle and handle [Monad](#) - is to bundle it with [bind](#), and leave [applied](#) partially.

And use that partial bundle as a [function](#) - every [evaluation](#) of the [function](#) would trigger [evaluation](#) of internal [Monad structure](#). Thumbs up.

```

printOneOf  Bool -> IO ()
printOneOf False = putStr "1"
printOneOf  True  = putStr "2"

```

```

quant  (Bool -> IO b) -> IO b
quant = (>>=) (randomRIO (False, True))

```

```

recursePrintOneOf  Monad m  (t -> m a) -> t -> m b
recursePrintOneOf f x = (f x) >> (recursePrintOneOf f x)

```

```

main  IO ()
main = recursePrintOneOf (quant) $ printOneOf

```

a. *

- Monad extend
- Monad bind
- Monad bind
- Binder
- Binder function

a. (`>>=`)

b. `>>=`

c. (`=>`)

d. `=>`

d. Sequencing operator (`>>`) `==` (`*>`): Discard any resulting value of the action and [sequence](#) next action.

[Applicative](#) has a similar [operator](#).

```

(>>) :: m a -> m b -> m b
(*>) :: f a -> f b -> f b

```

e. [Monadic](#) versions of [list functions](#)

```

sequence :: (Traversable t, Monad m) => t (m a) -> m (t a)

```


`Sequence` gets the traversable of `monadic` computations and swaps it into `monad` computation of traverse. In the result the collection of `monadic` computations turns into one long `monadic` computation on traverse of data.

If some step of this long computation fails - `monad` fails.

```
mapM :: (Traversable t, Monad m) => (a -> m b) -> t a -> m (t b)
```

`mapM` gets the `AMB function`, then takes traversable data. Then applies `AMB function` to traversable data, and returns converted `monadic` traversable data.

```
foldM :: (Foldable t, Monad m) => (b -> a -> m b) -> b -> t a -> m b
foldl :: Foldable t           => (b -> a -> b) -> b -> t a -> b
```

* is a `monadic foldl`.

`b` is initial cumulative value, `m b` is a cumulative bank.
Right folding achieved by reversing the input `list`.

```
filterM :: Applicative m => (a -> m Bool) -> [a] -> m [a]
filter ::                  (a -> Bool) -> [a] -> [a]
```

Take Boolean `monadic` computation, filter the `list` by it.

```
zipWithM :: Applicative m => (a -> b -> m c) -> [a] -> [b] -> m [c]
zipWith ::                  (a -> b -> c) -> [a] -> [b] -> [c]
```

Take `monadic` combine `function` and combine two lists with it.

```
msum :: (Foldable t, MonadPlus m) => t (m a) -> m a
sum  :: (Foldable t, Num a)       => t a -> a
```

f. `liftM*`

a. `liftM` Essentially a `fmap`.

```
liftM :: Monad m => (a -> b) -> m a -> m b
```

Lifts a `function` into `monadic equivalent`.

b. `liftM2` `Monadic liftA2`.

```
liftM2 :: Monad m => (a -> b -> c) -> m a -> m a -> m c
```

Lifts `binary function` into `monadic equivalent`.

f. Comonad `Category C` `comonad` is a `monad` of `opposite category Cop`.

g. Kleisli arrow `Morphism` that while doing computation also adds `monadic`-able `structure`.

`a -> m b`

- a. *
 - Kleisli arrows
 - Kleisli morphism
 - Kleisli morphisms

- h. Kleisli composition [Composition](#) of [Kleisli arrows](#).

```
(<=<) :: Monad m => (b -> m c) -> (a -> m b) -> a -> m c infixr 1
;; compare
(.)   ::          (b -> c) -> (a -> b) -> a -> c
```

Often used left-to-right version:

```
(>=>) :: Monad m => (a -> m b) -> (b -> m c) -> a -> m c
;; compare
(>>=) :: Monad m =>      m a -> (a -> m b)      -> m b
```

Which allows to replace [monadic bind](#) chain with [Kleisli composition](#).

```
f1 arg >>= f2 >>= f3
==
f1 >=> f2 >=> f3 $ arg
==
f3 <=< f2 <=< f1 $ arg
```

- i. Kleisli category [Category](#) \mathcal{C} , E , $\overrightarrow{\eta}$, $\overrightarrow{\mu}$ [monad](#) over \mathcal{C} .

[Kleisli category](#) \mathcal{C}_T of \mathcal{C} :

$$\text{Obj}(\mathcal{C}_T) = \text{Obj}(\mathcal{C})$$

$$\text{Hom}_{\mathcal{C}_T}(x, y) = \text{Hom}_{\mathcal{C}}(x, E(y))$$

- j. Special monad

- a. Identity monad Wraps data in the [Identity constructor](#).

Useful: Creates [monads](#) from [monad](#) transformers.

[Bind](#): Applies internal value to the [bound function](#).

Code:

```
newtype Identity a = Identity { runIdentity :: a }

-- coerce is a function that directly moves data between type aliases
instance Functor Identity where
    fmap      = coerce

instance Applicative Identity where
```

```

pure      = Identity
(<*>)     = coerce

instance Monad Identity where
  m >=> k  = k (runIdentity m)

```

Example:

```

-- derive the State monad using the StateT monad transformer
type State s a = StateT s Identity a

```

- b. Maybe monad Something that may not be or not return a result. Any lookups into the real world, database queries.

Bind: **Nothing** input gives **Nothing** output, **Just x** input uses **x** as input to the **bound function**.

When some computation results in **Nothing** - drops the chain of computations and returns **Nothing**.

Zero: **Nothing**

Plus: result in first occurrence of **Just** else **Nothing**.

Code:

```

data Maybe a = Nothing | Just a

instance Monad Maybe where
  return      = Just
  fail        = Nothing
  Nothing >=> _ = Nothing
  (Just x) >=> f = f x

```

```

instance MonadPlus Maybe where
  mzero      = Nothing
  Nothing `mplus` x = x
  x `mplus` _    = x

```

Example:

Given 3 dictionaries:

- a. Full names to email addresses,
- b. Nicknames to email addresses,
- c. Email addresses to email preferences.

Create a **function** that finds a person's email preferences based on **either** a full name or a nickname.

```

data MailPref = HTML | Plain
data MailSystem = ...

getMailPrefs :: MailSystem -> String -> Maybe MailPref

```

```
getMailPrefs sys name =
  do let nameDB = fullNameDB sys
      nickDB = nickNameDB sys
      prefDB = prefsDB sys
      addr <- (lookup name nameDB) `mplus` (lookup name nickDB)
      lookup addr prefDB
```

- c. Either monad When computation results in **Left** - drops other computations & returns the received **Left**.
- d. Error monad Something that can fail, throw **exceptions**.

The failure process records the description of a failure. **Bind function** uses successful values as input to the **bound function**, and passes failure information on without executing the **bound function**.

Useful:

Composing **functions** that can fail. Handle **exceptions**, create **error** handling **structure**.

Zero: empty **error**.

Plus: if first **argument** failed then execute second **argument**.

- e. List monad Computations which may return 0 or more possible results.

Bind: The **bound function** is **applied** to all possible values in the input **list** and the resulting lists are concatenated into **list** of all possible results.

Useful: Building computations from **sequences** of non-deterministic operations.

Zero: `[]`

Plus: `(++)`

a. `*`
`[]` monad

- f. Reader monad Creates a read-only shared environment for computations.

The **pure function** ignores the environment, while `»=` passes the inherited environment to both subcomputations.

Today it is defined through **ReaderT** transformer:

```
type Reader r = ReaderT r Identity -- equivalent to ((->) e), (e ->)
```

Old definition was:

```
newtype Reader e a = Reader { runReader :: (e -> a) }
```

For `(e ->)`:

- **Functor** is `(.)`

```
fmap :: (b -> c) -> (a -> b) -> a -> c
fmap = (.)
```

- [Applicative](#):

- `pure` is `const`

```
pure :: a -> b -> a
pure x _ = x
```

- `(<*>)` is:

```
(<*>) :: (a -> b -> c) -> (a -> b) -> a -> c
(<*>) f g = \a -> f a (g a)
```

- [Monad](#):

```
(>>=) :: (a -> b) -> (b -> a -> c) -> a -> c
(>>=) m k = Reader $ \r ->
  runReader (k (runReader m r)) r
```

```
join :: (e -> e -> a) -> e -> a
join f x = f x x
```

```
runReader
  :: Reader r a -- the Reader to run
  -> r -- an initial environment
  -> a -- extracted final value
```

Usage:

```
data Env = ...
```

```
createEnv :: IO Env
createEnv = ...
```

```
f :: Reader Env a
f = do
  a <- g
  pure a
```

```
g :: Reader Env a
g = do
  env <- ask -- "Open the environment namespace into env"
  a <- h env -- give env to h
  pure a
```

```
h :: Env -> a
... -- use env and produce the result
```

```
main :: IO ()
main = do
  env <- createEnv
  a = runReader g env
  ...
```

In Haskell under normal circumstances impure [functions](#) should not directly call impure [functions](#).

`h` is an impure [function](#), and `createEnv` is impure [function](#), so they should have intermediary.

- g.* Writer monad Computations which accumulate [monoid](#) data to a shared Haskell storage.

So `*` is parametrized by [monoidal type](#).

Accumulator is maintained separately from the returned values.

Shared value modified through [Writer monad](#) methods.

`*` frees creator and code from manually keeping the track of accumulation.

Bind: The [bound function](#) is [applied](#) to the input value, [bound function](#) allowed to `<>` to the accumulator.

```
type Writer r = WriterT r Identity
```

Example:

```
f :: Monoid b => a -> (a, b)
f a = if _condition_
      then runWriter $ g a
      else runWriter do
        a1 <- h a
        pure a1
```

```
g :: Monoid b => Writer b a
g a = do
  tell _value1_ -- accumulator <> _value1_
  pure a -- observe that accumulator stored inside monad and only a main value needs to
```

```
h :: Monoid b => Writer b a
h a = do
  tell _value2_ -- accumulator <> _value_
  pure a
```

```
runWriter :: Writer w a -> (a, w) -- Unwrap a writer computation as a (result, accumulator)
-- The inverse of writer.
```

`WriterT`, `Writer` unnecessarily keeps the entire logs in the memory. Use `fast-logger` for logging.

- h.* State monad Computations that pass-over a state.

The [bound function](#) is [applied](#) to the input value to produce a state transition [function](#) which is [applied](#) to the input state.

[Pure](#) functional language cannot update values in place because it violates [referential transparency](#).

```
type State s = StateT s Identity
```

`Binding` copies and transforms the state `parameter` through the `sequence` of the `bound functions` so that the same state storage is never used twice. Overall this gives the illusion of in-place update to the programmer and in the code, while in fact the auto-generated transition `functions` handle the state changes.

Example `type`: `State st a`

`State` describes `functions` that consume a state and produce a `tuple` of result and an updated state.

`Monad` manages the state with the next process:

Where:

- `f` - processor making `function`
- `pA`, `pAB`, `pB` - state processors
- `sN` - states
- `vN` - values

`Bind` with a processor making `function` from state processor (`pA`) creates a new state processor (`pAB`).

The wrapping and unwrapping by `State/runState` is implicit.

- k. Monad transformer $*$ is a practical solution to the current functional programming problem about [composition](#) of [monads](#).

[Monad](#) is not [closed](#) under composition.

[Composition](#) of [monadic types](#) does not always results in [monadic type](#).

Basic [case](#): during implementation of [monadic type composition](#), $\text{type } m \rightarrow T \ m \ a$ arises, which does not allow to [unit](#), [join](#) the m [monadic](#) layers.

$*$ have desirable properties and can add them to [monads](#). $*$ use their implementation to solve the composition [type](#) layering and allow to attach desirable [property](#) to result.

$*$ solve [monad composition](#) and [type](#) layering by cheating, using own [structure](#) and information about itself. It is often that process involves a [catamorphism](#) of a $*$ [type](#) layer.

In [type](#) signatures of transformers $*T \ m \rightarrow m$ is already an extended [monad](#), so $*T$ is just a wrapper to point that out.

Transformers have a light wrapper around the data that tags the modification with this transformer.

Main [monadic structure](#) m is wrapped around the internal data (core is a). The [structure](#) that corresponds to the transformer creation [properties](#) (if it emitted by η of a transformer), goes into m . Open [parameters](#) go external to the m .

```
newtype ExceptT e m a =
  ExceptT { runExceptT :: m (Either e a) }
```

```
newtype MaybeT m a =
  MaybeT { runMaybeT :: m (Maybe a) }
```

```
newtype ReaderT r m a =
  ReaderT { runReaderT :: r -> m a }
```

This has an [effect](#) that on stacking [monad](#) transformers, m becomes [monad stack](#), and every next transformer injects the transformer creation-specific properties η inside the [stack](#), so out-most transformer has inner-most [structure](#). Base [monad](#) is structurally the outermost.

- a. $\text{MaybeT } *$ extends [monads](#) by injecting [Maybe](#) layer underneath [monad](#), and processing that [structure](#):

```
newtype MaybeT m a = MaybeT { runMaybeT :: m (Maybe a) }
```

- b. $\text{EitherT } *$ extends [monads](#) by injecting [Either](#) layer underneath [monad](#), and processing that [structure](#):

```
newtype EitherT e m a = EitherT { runEitherT :: m (Either e a) }
```

[EitherT](#) of [either](#) package gets replaced by [ExceptT](#) of [transformers](#) or [mtl](#) packages.

a. * ExceptT

c. ReaderT Definition:

```
newtype ReaderT r m a = ReaderT { runReaderT :: r -> m a }
```

* **functions**: input **monad** `m a`, out: `m a` wrapped it in a free-variable `r` (**partially applied function**).

That allows to use transformed `m a`, now it requires and can use the `r` passed environment.

To create a **Reader monad**:

```
type Reader r = ReaderT r Identity
```

d. MonadTrans **type class** Allows to **lift monadic** actions into a larger **context** in a neutral way.

pure takes a parametric **type** and embodies it into constructed **structure** (talking of **monad** transformers - **structure** of the stacked **monads**).

lift takes **monad** and extends it with a transformer.

In fact, for **monad** transformers - **lift** is a last stage of the **pure**, it follows from the **lift** law.

Method:

```
lift :: Monad m => m a -> t m a
```

Lift a computation from the **argument monad** to the constructed **monad**.

Neutral means:

```
lift . return = return
```

```
lift (m >>= f) = lift m >>= (lift . f)
```

The general pattern with **MonadTrans** instances is that it is usually lifts the **injection** of the known **structure** of transformer over some **Monad**.

lift embeds one **monadic** action into **monad transformer**.

The difference between **pure**, **lift** and **MaybeT** constructor becomes clearer if you look at the **types**:

Example, for **MaybeT IO a**:

```
pure      ::      a  -> MaybeT IO a
lift      ::      IO a  -> MaybeT IO a
MaybeT   ::      IO (Maybe a) -> MaybeT IO a
```

```
x = (undefined :: IO a)
```

```

:t (pure x)
(pure x) :: Applicative t => t (IO a)  -- t recieves one argument of product type
:t (pure x :: MaybeT IO a)
-- Expected type: MaybeT IO a1
-- Actual type: MaybeT IO (IO a0)

-- While the real type would be
:t (pure x :: MaybeT IO (IO a))
(pure x :: MaybeT IO (IO a)) :: MaybeT IO (IO a) -- This goes into a conflict of what ty

```

```

:t (lift x)
(lift x) :: MonadTrans t => t IO a  -- result is a proper expected product type

-- To belabour
:t (lift x :: MaybeT IO a)
(lift x) :: MonadTrans t => t IO a  -- result is a proper expected product type

```

lift is a [natural transformation](#) η from an [Identity monad](#) ([functor](#)) with other [monad](#) as content into transformer [monad](#) ([functor](#)), with the preservation of the contained [monad](#):

```

-- Abstract monads with content as parameters. Define '~>' as a family of morphisms that
type f ~> g = forall x. f x -> g x
-- follows
lift :: m ~> t m

```

- a. [MonadIO type class](#) ^{*} - allows to [lift IO](#) action until reaching the [IO monad](#) layer at the top of the [Monad stack](#) (which is allways in the Haskell code that does [IO](#)).

```

class (Monad m) => MonadIO m where
  liftIO :: IO a -> m a
liftIO laws:

```

```

liftIO . pure = pure

```

```

liftIO (m >>= f) = liftIO m >>= (liftIO . f)
Which is identical laws to MonadTrans lift.

```

Since [lift](#) is one step, and [liftIO](#) all steps - all steps defined in terms of one step and all other steps, so the most frequent implementation is self-[recursive lift](#) .

```

liftIO:

```

```

liftIO ioa = lift $ liftIO ioa
a. *
  liftIO

```

3.5.7.7 Alternative type class

[Monoid](#) over [applicative](#). Has left catch [property](#).

Allows to run simoltieniously several instances of a computation (or computations) and from them yeld one result by law from $\langle | \rangle :: \text{Type} \rightarrow \text{Type} \rightarrow \text{Type}$.

Minimal complete definition:

```
empty :: f a    -- The identity element of <|>
(<|>) :: f a -> f a -> f a    -- Associative binary operation

a. *
    Alternative
```

3.5.7.8 «<=*>=>»>

Do calculation, but ignore the value from the first [argument](#).

`* > ≡ >>`

3.5.8 Monoidal functor

[Functors](#) between [monoidal categories](#) that preserves [monoidal structure](#).

3.5.9 Fusion

```
fmap f . fmap g = fmap (f . g)
```

`*` - [functor](#) axiom that allows to greatly simplify computations.

3.5.10 «<=\$>=>»>

Get & [set](#) a value inside [Functor](#).

3.5.11 Multifunctor

Generalizes the concept of [functor](#) between [categories](#), canonical [morphisms](#) between multicategories.

Works over N [type](#) arguments instead of one.

To put simply - accepts multiple arguments, from that information constructs source [product category](#) ([Cartesian product](#)) of [categories](#), and is a [functor](#) from [product category](#) to target [category](#).

To put even simpler - [functor](#) that takes as an [argument](#) the [product](#) of [types](#).

In Haskell there is only one [category](#), [Hask](#), so in Haskell `*` is still $(Hask \times Hask) \rightarrow Hask \Rightarrow |(Hask \times Hask) \equiv Hask| \Rightarrow Hask \rightarrow Hask$ [endofunctor](#).

Any [product](#) or sum in a Cartesian [category](#) is a `*`.

Code definition:

```

class Bifunctor f
  where
    bimap :: (a -> a') -> (b -> b') -> f a a' -> f a a'
    bimap f g = first f . second g
    first :: (a -> a') -> f a b -> f a' b
    first f = bimap f id
    second :: (b -> b') -> f a b -> f a b'
    second = bimap id

```

3.5.11.1 *

Bifunctor

3.5.12 *

«<=<\$=>»>

3.6 Hask category

Category of Haskell where **objects** are **types** and **morphisms** are **functions**.

It is a hypothetical **category** at the moment, since **undefined** and **bottom values** break the theory, is not Cartesian **closed**, it does not have sums, **products**, or **initial object**, **()** is not a **terminal object**, **monad** identities fail for almost all instances of the **Monad** class.

That is why Haskell developers think in subset of Haskell where **types** do not have **bottom values**. This only includes **functions** that terminate, and typically only finite values. The corresponding **category** has the expected initial and terminal **objects**, sums and **products**, and instances of **Functor** and **Monad** really are **endofunctors** and **monads**.

Hask contains subcategories, like **Lst** containing only **list types**.

Haskell and **Category** concepts:

- Things that take a **type** and return another **type** are **type constructors**.
- Things that take a **function** and return another **function** are higher-order **functions**.

3.6.1 *

Hask

3.7 Magma

Set with a **binary operation** which form a **closure**.

3.7.1 Mag category

The [category of magmas](#), denoted *Mag*, has as [objects](#) - [sets](#) with a [binary operation](#), and [morphisms](#) given by homomorphisms of operations (in the [universal algebra](#) sense).

3.7.1.1 *

MAG

Magma category

Category of magmas

3.7.2 Semigroup

[Magma](#) with [associative property](#) of [operation](#).

Defined in Haskell as:

```
class Semigroup a where
  (<>) :: a -> a -> a
```

3.7.2.1 *

Semigroups

3.7.2.2 Monoid

[Semigroup](#) with [identity](#) element. [Category](#) with a one [object](#).

Ideally fits as an accumulation class.

```
class Monoid m where
  mempty :: m
  mappend :: m -> m -> m
  mappend = (<>)
  mconcat :: [m] -> m
  mconcat = foldr mappend mempty
```

* can be simplified to [category](#) with a single [object](#), remember that [monoid operation](#) is a [composition](#) of [morphisms operation](#) in [category](#).

For example to represent the whole non-negative integers with the one [object](#) and [morphism](#) "1" is absolutely enough, [composition operation](#) is "+".

```
import Data.Monoid
do
  show (mempty :: Num a => Sum a)
  -- "Sum {getSum = 0}"
  show $ Sum 1
  -- "Sum {getSum = 1}"
  show $ (Sum 1) <> (Sum 1) <> (Sum 1)
  -- "Sum {getSum = 3}"
  -- ...
```

Also backwards - any single-object category is a monoid. Category has an identity requirement and associativity of composition requirement, which makes it a free monoid.

a. *

Monoidal
Monoids

b. Monoid laws

a. Monoid left identity law

`mempty <> x = x`

b. Monoid right identity law

`x <> mempty = x`

c. Monoid associativity law

`x <> mempty = x (y <> z) = (x <> y) <> z`

`mconcat = foldr (mempty <>)`

Everything associative can be `mappend`.

c. Commutative monoid Commutativity property:

$x \circ y = y \circ x$

Opens a big abilities in concurrent and distributed processing.

a. *

Abelian monoid

d. Group Monoid that has inverse for every element.

a. *

Groups

b. Commutative group Group operation obeys the axiom of commutativity.

a. *

Abelian group

b. Ring Commutative group under + & monoid under \times , $+$ \times connected by distributive property.

- and \times are generalized binary operations of addition and multiplication. \times has no requirement for commutativity.

Example: set of same size square matrices of numbers with matrix operations form a ring.

a. *

Rings

3.8 Morphism

morphe form

Arrow between two objects in a category.

General description: Arrow from source to target. Denotes something.

On a level of objects: is probably structure-preserving map from one mathematical structure to another of the same type.

Morphism is a generalization ($f(x * y) \equiv f(x) \diamond f(y)$) of homomorphism ($f(x * y) \equiv f(x) * f(y)$). Under morphism almost always is the meaning of homomorphism-like properties.

Morphism can be anything.

If morphism corresponds to function requirements - then it is a function.

3.8.1 *

Morphisms

Arrow

Arrows

3.8.2 Homomorphism

homos same (was chosen because of initial English mistranslation to "similar")

morphe form

similar form

* map between two algebraic structures of the same type, operation-preserving.

$$f_{x \rightarrow y} = f(a \star b) = f(a) \diamond f(b),$$

where x, y are sets with additional algebraic structure that includes \star, \diamond accordingly; a, b are elements of set x .

* sends identity morphisms to identity morphisms and inverses to inverses.

The concept of * has been generalized under the name of morphism to many structures that either do not have an underlying set, or are not algebraic.

3.8.2.1 *

Homomorphic

3.8.3 Identity morphism

Identity morphism - or simply identity: $x \in C : id_x = 1_x : x \rightarrow x$

Composed with other morphism gives same morphism.

Corresponds to Reflexivity and Automorphism.

3.8.3.1 Identity

Identity only possible with **morphism**. See **Identity morphism**.

There is also distinct **Zero** value.

- a. Two-sided identity of a predicate $P(e, a) = P(a, e) = a \mid \exists e \in S, \forall a \in S$
 $P()$ is **commutative**.

Predicate

- b. Left identity of a predicate $\exists e \in S, \forall a \in S : P(e, a) = a$

Predicate

- c. Right identity of a predicate $P(a, e) = a \mid \exists e \in S, \forall a \in S$

Predicate

3.8.3.2 Identity function

Return itself.

$(\backslash x.x)$

$\text{id} :: a \rightarrow a$

3.8.4 Monomorphism

mono only
morphe form

Maps one to one (uniquely), so invertable (always has **inverse morphism**), so preserves the information/**structure**.

Domain can be equal or less to the **codomain**.

$f^{X \rightarrow Y}, \forall x \in X \exists! y = f(x) \models f(x) \equiv f_{mono}(x)$ - from **homomorphism context**

$f_{mono} \circ g1 = f_{mono} \circ g2 \models g1 \equiv g2$ - from general **morphism context**

Thus $*$ is left cancelable.

If $*$ is a **function** - it is **injective**. Initial **set** of f is fully uniquely mapped onto the **image** of f .

3.8.4.1 *

Monomorphic

Monomorphisms

3.8.5 Epimorphism

epi on, over
morphe form

* is right cancelable [morphism](#).

$f^{X \rightarrow Y}, \forall y \in Y \exists f(x) \models f(x) \equiv f_{epi}(x)$ - from [homomorphism context](#)

$g_1 \circ f_{epi} = g_2 \circ f_{epi} \Rightarrow g_1 \equiv g_2$ - from general [morphism context](#)

In [Set category](#) if * is a [function](#) - it is [surjective](#) ([image](#) of it fully uses [codomain](#))
[Codomain](#) is called a projection of the [domain](#).

* fully maps into the target.

3.8.5.1 *

Epimorphic
Epimorphisms

3.8.6 Isomorphism

isos equal
morphe form

Not equal, but equal for current intents and purposes.

[Morphism](#) that has [inverse](#).

Almost equal, but not quite: ([Integer](#), [Bool](#)) & ([Bool](#), [Integer](#)) - but can be transformed losslessly into one another.

[Bijective homomorphism](#) is also [isomorphism](#).

$$f^{-1, b \rightarrow a} \circ f^{a \rightarrow b} \equiv 1^a, f^{a \rightarrow b} \circ f^{-1, b \rightarrow a} \equiv 1^b$$

2 reasons for non-[isomorphism](#):

- [function](#) at least ones collapses a values of [domain](#) into one value in [codomain](#)
- [image](#) (of a [function](#) in [codomain](#)) does not fill-in [codomain](#). Then [isomorphism](#) can exists for [image](#) but not whole [codomain](#).

[Categories](#) are [isomorphic](#) if there $R \circ L = ID$

3.8.6.1 *

Isomorphic
Isomorphisms

3.8.6.2 Lax

Holds up to [isomorphism](#).

(upon the transformation can be used as the same)

3.8.7 Endomorphism

endo internal
morphe form

Arrow from [object](#) to itself.

[Endomorphism](#) forms a [monoid](#) ([object](#) exists and [category](#) requirements already in place).

3.8.7.1 Automorphism

αυτο *auto* self
form form

[Isomorphic endomorphism](#).

Corresponds to [identity](#), [reflexivity](#), [permutation](#).

a. *

Automorphic
 Automorphisms

3.8.7.2 *

Endomorphic
 Endomorphisms

3.8.8 Catamorphism

kata downward
morphe form

Unique [arrow](#) from an initial [algebra structure](#) into different [algebra structure](#).

* in FP is a generalization folding, deconstruction of a [data structure](#) into more primitive [data structure](#) using a [functor](#) F-[algebra structure](#).

* reduces the [structure](#) to a lower level [structure](#).

* creates a projection of a [structure](#) to a lower level [structure](#).

3.8.8.1 *

Catamorphic
 Catamorphisms

3.8.8.2 Catamorphism law

a. Hylomorphism [catamorphism](#) \circ [anamorphism](#)

Expanding and collapsing the [structure](#).

Table 3.2: [Catamorphism](#) laws in Haskell

Rule name	Haskell
cata-cancel	<code>cata phi . InF = phi . fmap (cata phi)</code>
cata-refl	<code>cata InF = id</code>
cata-fusion	<code>f . phi = phi . fmap f => f . cata phi = cata phi</code>
cata-compose	<code>eps :: f -> g => cata phi . cata (In . eps) = cata (phi . eps)</code>

a. *

Hylomorphic
Hylomorphisms

3.8.8.3 Anamorphism

Generalizes `unfold`.

Dual concept to [catamorphism](#).

Increases the [structure](#).

[Morphism](#) from a [coalgebra](#) to the final [coalgebra](#) for that [endofunctor](#).

Is a [function](#) that generates a [sequence](#) by repeated [application](#) of the [function](#) to its previous result.

a. *

Anamorphic
Anamorphisms

3.8.9 Kernel

[Kernel](#) of a [homomorphism](#) is a number that measures the [degree homomorphism](#) fails to meet [injectivity](#) (AKA be [monomorphic](#)).

It is a number of [domain](#) elements that fail [injectivity](#):

- elements not included into [morphism](#)
- elements that collapse into one element in [codomain](#)

thou [Kernel](#) $[x|x \leftarrow 0||x \geq 2]$.

Denotation:

$$\ker T = \{\mathbf{v} \in V : T(\mathbf{v}) = \mathbf{0}_W\}.$$

3.8.9.1 Kernel homomorphism

[Morphism](#) of elements from the [kernel](#).

Complementary [morphism](#) of elements that make main [morphism](#) not [monomorphic](#).

3.9 Object

Absolute [abstraction](#).

Point.

Can have [properties](#).

Often abstracts mathematical [structure](#).

3.9.1 *

Structure

Structures

Objects

3.9.2 Terminal object

One that receives unique [arrow](#) from every [object](#).

$$\exists! : x \rightarrow 1 \mid \exists 1 \in \mathcal{C}, \forall x \in \mathcal{C}$$

* is an empty [sequence](#) () in Haskell.

Called a [unit](#), so receives *terminal* or [unit arrow](#).

[Dual](#) of [initial object](#).

Denotation:

[Category](#) theory

1

Haskell

()

3.9.3 Initial object

One that emits unique [arrow](#) into every [object](#).

$$\exists! : \emptyset \rightarrow x \mid \exists \emptyset \in \mathcal{C}, \forall x \in \mathcal{C}$$

If [initial object](#) is `Void` (most frequently) - emitted [arrows](#) called absurd, because they can not be called.

[Dual](#) of [terminal object](#).

Denotation:

[Category](#) theory:

\emptyset

Haskell:

Void

3.10 Set category

Category in which objects are sets, morphisms are functions.

Denotation:

Set

3.11 Natural transformation

Roughly $*$ is:

`trans :: F a -> G a`

, while `a` is polymorphic variable.

Naturality condition: $\forall a \exists (F a \rightarrow G a)$, or , analogous to parametric polymorphism in functions. Since $*$ in a category, stating $\forall (F a \rightarrow G a)$

Naturality condition means that all morphisms that take part in homotopy of source functor to target functor must exist, and that is the same, diagrams that take part in transformation, should commute, and different paths bring same result: if α - natural transformation, α_a natural transformation component - $G f \circ \alpha_a = \alpha_b \circ F f$.

Since $*$ are just a type of parametric polymorphic function - they can compose.

$*$ ($\vec{\eta}^{\mathcal{D}}$) is transforming : $\vec{\eta}^{\mathcal{D}} \circ F^{C \rightarrow \mathcal{D}} = G^{C \rightarrow \mathcal{D}}$.

$*$ abstraction creates higher-language of Category theory, allowing to talk about the composition and transformation of complex entities.

It is a process of transforming $F^{C \rightarrow \mathcal{D}}$ into $G^{C \rightarrow \mathcal{D}}$ using existing morphisms in target category \mathcal{D} .

Since it uses morphisms - it is structure-preserving transformation of one functor into another. It is mostly a lossy transformation. Only existing morphisms can make it exist.

Existence of $*$ between two functors can be seen as some relation.

Can be observed to be a "morphism of functors", especially in functor category.

$*$ by $\vec{\eta}_{y^c}^{\mathcal{D}}((x, y)^c) \circ F^{C \rightarrow \mathcal{D}}((x, y)^c) = G^{C \rightarrow \mathcal{D}}((x, y)^c) \circ \vec{\eta}_{x^c}^{\mathcal{D}}((x, y)^c)$, often written short $\vec{\eta}_b \circ F(\vec{f}) = G(\vec{f}) \circ \vec{\eta}_a$.

Notice that the $\vec{\eta}_{x^c}^{\mathcal{D}}((x, y)^c)$ depends on objects&morphisms of \mathcal{C} .


In words: $*$ depends on F and G functors, ability of \mathcal{D} morphisms to do a homotopy of F to G , and $*$:

- for every object in \mathcal{C} picks natural transformation component in \mathcal{D} .
- for every morphism in \mathcal{C} picks the commuting diagram in \mathcal{D} , called naturality square.


Also see: [Natural transformation in Haskell](#)

Knowledge of $*$ forms a [2-category](#).

Can be [composed](#) "vertically":



And horizontally, aka "Godement [product](#)":



[Compositions](#) can be done in any right [order](#), they abide the exchange law.

3.11.1 *

Natural transformations

Naturality condition

Naturality

3.11.2 Natural transformation component

$$\vec{\eta}^{\mathcal{D}}(x) = F^{\mathcal{D}}(x) \rightarrow G^{\mathcal{D}}(x) \mid x \in \mathcal{C}$$

3.11.2.1 *

Component of natural transformation

3.11.3 Natural transformation in Haskell

Family of [parametric polymorphism functions](#) between [endofunctors](#).


In [Hask](#) is $F\ a \rightarrow G\ a$. Can be analogued to repackaging data into another container, never modifies the [object](#) content, it only if - can delete it, because [operation](#) is lossy.

Can be seen as orthogonal to [functors](#).

3.11.4 Cat category

[Category](#) where:

	Part	Is	#
*	object	category	0-cell
\Rightarrow	morphism	functor	1-cell
\Rightarrow	2-morphism	natural transformation , morphisms homotopy	2-cell



Is Cartesian [closed category](#).

3.11.4.1 *

Cat

2-category

3.11.4.2 Bicategory

[2-category](#) that is [enriched](#) and [lax](#).

For handling relaxed [associativity](#) - introduces associator, and for [identity](#) 1-left/right unitor.

Forming from bicategories higher [categories](#) by stacking levels of [abstraction](#) of such [categories](#) - leads to explosion of special cases, differences of every level, and so overall difficulties.

Stacking groupoids ([category](#) in which are [morphisms](#) are invertable) is much more homogenous up to infinity, and forms base of the [homotopy type](#) theory.

3.12 Category dual

[Category duality](#) behaves like a logical [inverse](#).

[Inverse](#) $\mathcal{C} = \mathcal{C}^{op}$ - inverts the direction of [morphisms](#).

[Composition](#) accordingly changes to the [morphisms](#): $(g \circ f)^{op} = f^{op} \circ g^{op}$

Any [statement](#) in the terms of \mathcal{C} in \mathcal{C}^{op} has the [dual](#) - the logical [inverse](#) that is true in \mathcal{C}^{op} terms.

Opposite preserves [properties](#):

- [products](#): $(\mathcal{C} \times \mathcal{D})^{op} \cong \mathcal{C}^{op} \times \mathcal{D}^{op}$

- **functors**: $(F^{\mathcal{C} \rightarrow \mathcal{D}})^{op} \cong F^{\mathcal{C}^{op} \rightarrow \mathcal{D}^{op}}$
- **slices**: $(\mathcal{F} \downarrow \mathcal{G})^{op} \cong (\mathcal{G}^{op} \downarrow \mathcal{F}^{op})$

a. *

Opposite category
 Opposite categories
 Category duality
 Duality
 Dual category
 Dual

3.12.1 Coalgebra

Structures that are **dual** (in the **category**-theoretic sense of reversing **arrows**) to unital **associative algebras**.

Every **coalgebra**, by vector space **duality**, reversing **arrows** - gives rise to an **algebra**. In finite dimensions, this **duality** goes in both directions. In infinite - it should be determined.

3.13 Thin category

\forall **Hom sets** contain **zero** or one **morphism**.

$$f \equiv g \mid \forall x, y \forall f, g : x \rightarrow y$$

A proset (**preordered set**).

3.13.1 *

Proset category
 Posetal category
 Poset category
 Posetal category

3.14 Commuting diagram

Establishes equality in **morphisms** that have same source and target.

Draws the **morphisms** that are:

$$f = g \Rightarrow \{f, y\} : X \rightarrow Y$$

3.14.1 *

Diagram commutes
 Commutes

3.15 Universal construction

Algorithm of constructing definitions in [Category](#) theory.

Specially good to translate [properties](#)/definitions from other theories ([Set theory](#)) to [Categories](#).

Method:

- a. Define a pattern that you defining.
- b. Establish ranking for pattern matches.
- c. The top of ranking, the best match or [set](#) of matches - is the thing you was looking for. Matches are [isomorphic](#) for defined rules.

* uses Yoneda lemma, and as such constructions are defined until [isomorphism](#), and so [isomorphic](#) between each-other.

3.15.1 *

Universal constructions

3.16 Product

[Universal construction](#):

$$\begin{array}{ccccc}
 & & c' & & \\
 & p \swarrow & \downarrow ! & \searrow q & \\
 a & \xleftarrow{\pi_a} & c & \xrightarrow{\pi_b} & b
 \end{array}$$

Pattern: $p : c \rightarrow a, q : c \rightarrow b$

Ranking: $\max \sum^{\forall} (! : c' \rightarrow c \mid p' = p \circ !, q' = q \circ !)$

c' is another candidate.

For [sets](#) - [Cartesian product](#).

* is a pair. Corresponds to [product data type](#) in [Hask](#) (inhabited with all elements of the [Cartesian product](#)).

[Dual](#) is [Coproduct](#).

3.16.1 *

Products

3.17 Coproduct

[Universal constructuon](#):

$$\begin{array}{ccccc}
 & & c' & & \\
 & p \nearrow & \uparrow ! & \nwarrow q & \\
 a & \xrightarrow{\iota_a} & c & \xleftarrow{\iota_b} & b
 \end{array}$$

Pattern: $i : a \rightarrow c, j : b \rightarrow c$

Ranking: $\max \sum_{c'} (! : c \rightarrow c' \mid i' = ! \circ i, j' = ! \circ j)$

c' is another candidate.

For [sets](#) - Disjoint union.

$*$ is a [set](#) assembled from other two [sets](#), in Haskell it is a tagged [set](#) (analogous to disjoint union).

[Dual](#) is [Product](#).

3.17.1 *

Coproducts

3.18 Free object

General particular [structure](#).

In which [structure](#), [properties](#) autofollows from definition, axioms.

Also uses as a term when surcomstances of [structures](#), rules, [properties](#), axioms used coincide with the definition of a particular [object](#) \therefore form [object](#) of this [type](#) with the according [properties](#) and possibilities.

3.19 Internal category

[Category](#) which is included into a bigger [category](#).

3.20 Hom set

All [morphisms](#) from source [object](#) to target [object](#).

Denotation:

$$hom_C(X, Y) = (\forall f : X \rightarrow Y) = hom(X, Y) = C(X, Y)$$

Denotation was not standartized.

[Hom sets](#) belong to [Set category](#).

In [Set category](#): $\exists!(a, b) \iff \exists! Hom, \forall Hom \in Set$. [Set category](#) is special, [Hom sets](#) are also [objects](#) of it.

[Category](#) can include [Set](#), and [hom sets](#), or not.

3.20.1 *

Hom-set

Hom sets

3.20.2 Hom-functor

$hom : \mathcal{C}^{op} \times \mathcal{C} \rightarrow Set$

Functor from the product of \mathcal{C} with its opposite category to the category of sets.

Denotation variants:

$H_A = Hom(-, A)$

$h_A = \mathcal{C}(-, A)$

$Hom(A, -) : \mathcal{C} \rightarrow Set$

Hom-bifunctor:

$Hom(-, -) : \mathcal{C}^{op} \times \mathcal{C} \rightarrow Set$

3.20.3 Exponential object

Generalises the notion of function set to internal object.

As also hom set to internal hom objects.

Cartesian closed (monoidal) category strictly required, as $*$ multiplication holds composition requirement:

$$\circ : hom(y, z) \otimes hom(x, y) \rightarrow hom(x, z)$$

Denotation:

b^a

Universal construction:

$$\begin{array}{ccc} c & c \times a & \\ \vdots & \vdots & \searrow \\ u & u \times 1^a & \\ \downarrow & \downarrow & \\ b^a & b^a \times a \cdot eval & b \end{array}, \text{ where in Category: } b^a - \text{exponential object, } \times - \text{product bifunctor,}$$

a - argument of $*$, b - result, c - candidate, $b^a \equiv (a \Rightarrow b) - *$.

$* b^a$ (also as $(a \Rightarrow b)$) represent exponentiation of cardinality of $\forall b^a$ possibilities.

3.20.3.1 *

Function object

Internal hom

Exponential objects

Hom object

Hom objects

3.20.3.2 Enriched category

Uses Hom objects (exponential objects), which do not belong into Set category.

Category is no longer small, now may be called large.

$$hom(x, y) \in K.$$

Called: $*$ over K (which holds hom objects).

- a.* * Enriched
Large category

Chapter 4

Data type

Set of values.

For **type** to have sense the values must share some sense, **properties**.

4.1 *

Type

Types

Data types

4.2 Actual type

Data type recieved by ->**inferring**->compiling->execution.

4.3 Algebraic data type

Composite **type** formed by combining other **types**.

4.3.1 *

AlgDT

4.4 Cardinality

Number of possible implementations for a given **type** signature.

Disjunction, sum - adds **cardinalities**.

Conjunction, **product** - multiplies **cardinalities**.

4.4.1 *

Cardinalities

4.5 Data constant

* - [constant](#) value; [nullary data constructor](#).

4.6 Data constructor

One instance that [inhabit data type](#).

4.7 data declaration

[Data type declaration](#) is the most general and versatile form to create a new [data type](#).
Form:

```
data [context =>] type typeVars1..n
  = con1  c1t1..i
  | ...
  | conm  cmt1..q
  [deriving]
```

4.8 Dependent type

When [type](#) and values have [relation](#) between them. [Type](#) has restrictions for values, value of a [type variable](#) has a result on the [type](#).

4.8.1 *

Dependent types

4.9 Gen type

[Generator](#). [Gen type](#) is to generate pseudo-random values for parent [type](#). Produces a [list](#) of values that gets infinitely cycled.

4.10 Higher-kinded data type

Any combination of * and ->

[Type](#) that take more [types](#) as arguments.

Humbly really a [function](#)

4.10.1 *

Higher-kinded data types

4.11 newtype declaration

Create a new [type](#) from old [type](#) by attaching a new [constructor](#), allowing [type class instance declaration](#).

```
newtype FirstName = FirstName String
```

Data will have exactly the same representation at runtime, as the [type](#) that is wrapped.

```
newtype Book = Book (Int, Int)
```

```
    (,)
    / \
Integer Integer
```

4.12 Principal type

The most generic [data type](#) that still [typechecks](#).

4.13 Product data type

Is an [algebraic data type](#) representation of a [product](#) construction.
Formed by logical [conjunction](#) (AND, '[*](#)').

Haskell forms:

```
-- 1. As a tuple (the uncurried & most true-form)
(T1, T2)

-- 2. Curried form, data constructor that takes two types
C T1 T2

-- 3. Using record syntax. =r# <inhabitant>= would return the respective =T#=
C { r1 :: T1
    , r2 :: T2
    }
```

4.13.1 *

Product type

4.13.2 Sequence

Enumerated (ordered) [set](#).

Denotation:

```
()
( , )
( , , )
( , , ... )
```

More general mathematical denotation was not established, variants:

$$(n)_{n \in \mathbb{N}}$$

$$\omega \rightarrow X$$

$$\{i : Ord \mid i < \alpha\}$$

In Haskell: [Data type](#) that stores multiple ordered values withing a single value.

Table 4.1: [Sequence constructor](#) naming by [arity](#)

Name	Arity	Denotation
Unit , empty	0	()
Singleton	1	(_)
Tuple, pair, two-tuple	2	(_ , _)
Triple, three- tuple	3	(_ , _ , _)
Sequence	N	(_ , _ , ...)

4.13.2.1 *

Sequences
Tuples
Ordered pair
Ordered triple

4.13.2.2 List

The same [type objects sequence](#).

Denotation:

[]
[,]
[, ,]
[, , ...]

Haskell definition:

```
data [] a = [] | a : [a]
```

Definition is self-referential (self-[recursive](#)), can be seen as [anamorphism](#) (unfold) of the [] (empty [list](#), memory cell which is container of particular [type](#)) and : ([cons operation](#), pointer). As such - can create non-terminating [data type](#) (and computation), in other words - infinite.

4.14 Proxy type

[Proxy type](#) holds no data, but has a phantom [parameter](#) of [arbitrary type](#) (or even [kind](#)). Able to provide [type](#) information, even though has no value of that [type](#) (or it can be may too costly to create one).

```
data Proxy a = ProxyValue
```

```
let proxy1 = (ProxyValue :: Proxy Int) -- a has kind `Type`
let proxy2 = (ProxyValue :: Proxy List) -- a has kind `Type -> Type`
```


4.15 Static typing

Typechecking takes place at compile level.

4.16 Structural type

Mathematical type. They form into structural type system.

4.16.1 *

Structural

4.17 Structural type system

Strict global hierarchy and relationships of types and their properties.

Haskell type system is *.

In most languages typing is name-based, not structural.

4.17.1 *

Structural typing

4.18 Sum data type

Algebraic data type formed by logical disjunction (OR '|').

4.19 Type alias

Create new type constructor, and use all data structure of the base type.

4.20 Type class

Type system construct that adds a support of ad hoc polymorphism.

Type class makes a nice way for defining behaviour, properties over many types/objects at once.

4.20.1 *

Type classes

Typeclass

Typeclasses

4.20.2 Arbitrary type class

Type class of `QuickCheck.Arbitrary` (that is reexported by `QuickCheck`) for creating a generator/distribution of values.

Useful function is `arbitrary` - that autogenerates values.

4.20.2.1 Arbitrary function

Depends on `type` and generates values of that `type`.

4.20.3 CoArbitrary type class

Pseudogenerates a function basing on resulting `type`.

```
coarbitrary :: CoArbitrary a => a -> Gen b -> Gen b
```

4.20.3.1 *

CoArbitrary

4.20.4 Typeable type class

Allows dynamic `type` checking in Haskell for a `type`.

Shift a `typechecking` of `type` from compile time to runtime.

* `type` gets wrapped in the universal `type`, that shifts the `type` checks to runtime.

Also allows:

- Get the `type` of something at runtime (ex. print the `type` of something `typeOf`).
- Compare the `types`.
- Reifying functions from `polymorphic type` to concrete (for functions like `:: Typeable a => a -> String`).

4.20.4.1 *

Typeable

4.20.5 Type class inheritance

Type class has a superclass.

4.20.6 Derived instance

Type class instances sometimes can be automatically [derived](#) from the parent [types](#).

Type classes such as Eq, Enum, Ord, Show can have instances generated based on definition of data type.

P.S.

Language options:

- DeriveAnyClass
- DeriveDataTypeable
- DeriveFoldable
- [DeriveFunctor](#)
- DeriveGeneric
- DeriveLift
- DeriveTraversable
- DerivingStrategies
- DerivingVia
- GeneralisedNewtypeDeriving
- StandaloneDeriving

4.20.6.1 *

Derived
Deriving

4.21 Type constant

[Nullary type constructor](#).

4.22 Type constructor

Name of the [data type](#).

[Constructor](#) that takes [type](#) as an [argument](#) and produces new [type](#).

4.23 type declaration

Synonym for existing [type](#). Uses the same [data constructor](#).

```
type FirstName = String
```

Used to distinct one entities from other entities, while they have the same [type](#).
Also main [type functions](#) can operate on a new [type](#).

4.24 Typed hole

`*` - is a `_` or `_name` in the [expression](#). On [evaluation](#) GHC would show the [derived type](#) information which should be in place of the `*`. That information helps to fill in the gap.

4.24.1 *

Typed holes

4.25 Type inference

Automatic [data type](#) detection for [expression](#).

4.25.1 *

Inferring
Infer
Infers
Inferred

4.26 Type class instance

Block of implementations of [functions](#), based on unique [type class](#)->[type](#) pairing.

4.27 Type rank

Weak ordering of [types](#).

The rank of [polymorphic type](#) shows at what level of nesting `forall` [quantifier](#) appears.
Count-in only [quantifiers](#) that appear to the left of [arrows](#).

```
f1 :: forall a b. a -> b -> a    ==    fi :: a -> b -> c
g1 :: forall a b. (Ord a, Eq b) => a -> b -> a    ==    g1 :: (Ord a, Eq b) => a -> b -> a
```

f1, g1 - [rank-1 types](#). Haskell itself implicitly adds universal [quantification](#).

```
f2 :: (forall a. a->a) -> Int -> Int
g2 :: (forall a. Eq a => [a] -> a -> Bool) -> Int -> Int
```

f2, g2 - [rank-2 types](#). Quantifier is on the left side of a \rightarrow . Quantifier shows that [type](#) on the left can be overloaded.

[Type inference](#) in Rank-2 is possible, but not higher.

```
f3 :: ((forall a. a->a) -> Int) -> Bool -> Bool
```

f3 - [rank3-type](#). Has [rank-2 types](#) on the left of a \rightarrow .

```
f :: Int -> (forall a. a -> a)
g :: Int -> Ord a => a -> a
```

f, g are rank 1. [Quantifier](#) appears to the right of an [arrow](#), not to the left. These [types](#) are not Haskell-98. They are supported in [RankNTypes](#).

4.27.1 *

Type ranks
Rank type
Rank types
Rank-1 type
Rank-1 types
Rank-2 type
Rank-2 types
Rank-3 type
Rank-3 types

4.28 Type variable

Refer to an unspecified [type](#) in Haskell [type](#) signature.

4.29 Unlifted type

[Type](#) that directly exist on the hardware. The [type abstraction](#) can be completely removed. With [unlifted types](#) Haskell [type](#) system directly manages data in the hardware.

4.29.1 *

Unlifted types

4.30 Data structure

4.30.1 Cons cell

Cell that values may [inhabit](#).

4.30.2 Construct

`(:) :: a -> [a] -> [a]`

4.30.2.1 *

Cons

4.30.3 Leaf

-

4.30.4 Node

*
/ \

4.31 Linear type

[Type](#) system and [algebra](#) that also track the multiplicity of data.
There are 3 general [linear type](#) groups:

- 0 - exists only at [type level](#) and is not allowed to be used at value level. Aka `s` in [ST-Trick](#).
- 1 - data that is not duplicated
- 1< - all other data, that can be duplicated multiple times.

4.31.1 *

Linear types

4.32 NonEmpty list data type

`Data.List.NonEmpty`

Has a [Semigroup](#) instance but can't have a [Monoid](#) instance. It never can be an empty [list](#).

```
data NonEmpty a = a :| [a]
  deriving (Eq, Ord, Show)
```

`:|` - an [infix](#) data constructor that takes two ([type](#)) arguments. In other words `:|` returns a [product type](#) of left and right

4.33 Session type

* - allows to check that behaviour conforms to the protocol.

So far very complex, not very productive (or well-established) topic.

4.34 Binary tree

```
data BinaryTree a
  = [[Leaf]]
  | [[Node]] (BinaryTree a) a (BinaryTree a)
```

4.35 Bottom value

A `_` non-value in the [type](#) or [pattern match expression](#). Placeholder for anything.

```
-- _ fits *.
```

4.35.1 *

Bottom
Bottom values

4.36 Bound

Haskell `*` [type class](#) means to have lowest value & highest value, so a [bounded](#) range of values.

4.36.1 *

Bounded

4.37 Constructor

a. [Type constructor](#)

b. [Data constructor](#)

Also see: [Constant](#)

4.37.1 *

Constructors

4.38 Context

Type constraints for polymorphic variables.

Written before the main `type` signature, denoted:

```
TypeClass a => ...
```

4.38.1 *

Contexts

4.39 Inhabit

Values that is a component of `data type set`.

4.40 Maybe

```
data Maybe
  = Nothing
  | Just a
```

Does not represent the information why `Nothing` happened.

For `error` - use `Either`.

Do not propagate `*`.

Handle `*` locally to `where` it is produced. `Nothing` does not hold useful info for debugging & short-circuits the processes. Do not expect code `type` being bug-free, do not return `Maybe` to end user since it would be impossible to debug, return something that preserves `error` information.

4.40.0.1 *

Nodes

4.41 Expected type

`Data type inferred` from the text of the code.

4.42 ADT

a. `Abstract data type`

b. `Algebraic data type`

4.43 Concrete type

Fully defined `type`. Non-polymorphic type.

4.44 Type punning

When [type constructor](#) and [data constructor](#) have the same name.

Theoretically if person knows the rules - * can be solved, because in Haskell [type](#) and [data declaration](#) have different places of use.

Chapter 5

Declaration

[Binding](#) name to [expression](#).

Chapter 6

Differential operator

Denotation.

$\frac{d}{dx}$, D , D_x , ∂_x .

Last one is partial.

$e^{t\frac{d}{dx}}$ - Shift operator.

6.1 *

Differential

Chapter 7

Dispatch

Send, transmission, reference.

Chapter 8

Effect

Observable action.

Chapter 9

Evaluation

For FP see [Bind](#).

Chapter 10

Expression

Finite combination of symbols that is well-formed according to rules that depend on the [context](#).

10.1 *

Expressions

10.2 Closed-form expression

* - mathematical [expression](#) that can be evaluated in a finite number of operations.

May contain:

- constants
- [variables](#)
- operations (e.g., $+$ $-$ \times \div)
- [functions](#) (e.g., nth root, exponent, logarithm, trigonometric [functions](#), and [inverse](#) hyperbolic [functions](#)), but usually no limit.

10.3 RHS

Right-hand side of the [expression](#).

10.4 LHS

Left-hand side of the [expression](#).

10.5 Redex

Reducible expression.

10.6 Concatenate

Link together sequences, expressions.

10.7 Alpha equivalence

Equivalence of a processes in expressions. If expressions have according parameters different, but the internal processes are literally the same process.

10.8 Ground expression

Expression that does not contain any free variables.

10.8.1 *

Ground formula

10.9 Variable

A name for expression.

Haskell has immutable variables.

Except when you hack it with explicit fun tions.

10.9.1 *

Variables

Chapter 11

First-class

Means *it*:

- Can be used as value.
- Passed as an [argument](#).

From 1&2 -> *it* can include itself.

Chapter 12

Function

Full dependency of one quantity from another quantity.

Denotation:

$$y = f(x)$$

$$f : X \rightarrow Y,$$

where X is domain, Y is codomain.

Directionality and property of invariability emerge from one another.

```
-- domain func codomain
*      ->  *
```

$$y(x) = (zx^2 + bx + 3 \mid b = 5)$$

\Var \Constant

\Bound variable

\Free variable

\Parameter

\Name of the function

Lambda abstraction is a function.

Function is a mathematical operation.

Function = Total function = Pure function. Function theoretically can be to memoized.

Also see:

Partial function

Inverse function - often partially exists (partial function).

12.1 *

Functions

Bound variable

12.2 Arity

Number of [parameters](#) of the [function](#).

- [nullary](#) - $f()$
- [unary](#) - $f(x)$
- [binary](#) - $f(x,y)$
- [ternary](#) - $f(x,y,z)$
- [n-ary](#) - $f(x,y,z..)$

12.3 Bijection

[Function](#) is a complete one-to-one pairing of elements of [domain](#) and [codomain](#) ([image](#)).
It means [function](#) both [surjective](#) (so [image](#) == [codomain](#)) and [injective](#) (every [domain](#) element has unique correspondence to the [image](#) element).

For [bijection inverse](#) always exists.

[Bijection operation](#) holds the [equivalence](#) of [domain](#) and [codomain](#).

Denotation:

>->>
 $f : X \rightarrow Y$

L^AT_EX needed to combine symbols:
 $f : X \mapsto Y$

Corresponds to [isomorphism](#).

12.3.1 *

Bijjective
 Bijjective function

12.4 Combinator

[Function](#) without free [variables](#).
[Higher-order function](#) that uses only [function application](#) and other combinators.

```

\ a -> a
\ a b -> a b
\ f g x -> f (g x)
\ f g x y -> f (g x y)

```

Not combinators:

```

\ xs -> sum xs

```

Informal broad meaning: referring to the style of organizing libraries centered around the idea of combining things.

12.5 Function application

* - [bind](#) the [argument](#) to the [parameter](#) of a [function](#), and do a [beta-reduction](#).

12.5.1 *

Apply
Applied
Applying
Application

12.6 Function body

[Expression](#) that haracterizes the process.

12.7 Function composition

```

(.) :: (b -> c) -> (a -> b) -> a -> c

```

```

a -> (a -> b) -> (b -> c) -> c

```

In Haskell inline [composition](#) requires:

```

h.g.f $ i

```

12.7.1 *

Composition
Compose
Composed

12.8 Function head

Is a part with name of the [function](#) and it's paramenterers.
AKA: $f(x)$

12.9 Function range

The range of a [function](#) refers to [either](#) the [codomain](#) or the [image](#) of the [function](#), depending upon usage. Modern usage almost always uses range to mean [image](#).

So, see [Function image](#).

12.10 Higher-order function

[Function arity](#) > 1.

—

Has [function](#) as a [parameter](#).

Evaluates to [function](#).

12.10.1 *

HOF

12.10.2 Fold

[Catamorphism](#) of a [structure](#) to a lower [type](#) of [structure](#). Often to a single value.

[*](#) is a [higher-order function](#) that takes a [function](#) which operates with both main [structure](#) and accumulator [structure](#), [*](#) applies units of [data structure](#) to a [function](#) which works with accumulator. Upon traversing the whole [structure](#) - the accumulator is returned.

12.11 Injection

[Function](#) one-to-one injects from [domain](#) into [codomain](#).

Keeps distinct pairing of elements of [domain](#) and [image](#).

Every element in [image](#) corresponds to one element in [domain](#).

$$\forall a, b \in X, f(a) = f(b) \Rightarrow a = b$$

$$\exists(\text{inverse function}) \mid \forall(\text{injective function})$$

Denotion:

\rightarrow

$f : X \rightarrow Y$

$f : X \rightarrow Y$

Corresponds to [Monomorphism](#).

12.11.1 *

Injective
Injective function
Injectivity

12.12 Partial function

One that does not cover all [domain](#).
[Unsafe](#) and causes trouble.

12.13 Purity

* means properly abstracted.

If the contrary - [abstraction](#) is unpure.

Also see: [pure function](#).

12.13.1 *

Pure

12.14 Pure function

[Function](#) that is [pure](#) \equiv [referentially transparent function](#).

12.15 Sectioning

Writing [function](#) in a parentheses. Allows to pass around [partially applied functions](#).

12.16 Surjection

[Function](#) uses [codomain](#) fully.

$$\forall y \in Y, \exists x \in X$$

Denotation:
 $f : X \rightarrow Y$

Corresponds to [Epimorphism](#).

12.16.1 *

Surjective
Surjective function

12.17 Unsafe function

Function that does not cover at least one edge **case**.

12.17.1 *

Unsafe

12.18 Variadic

* - having **variable arity** (often up to indefinite).

12.19 Domain

Source **set** of a **function**.
 X in $X \rightarrow Y$.

12.20 Codomain

Y in $X \rightarrow Y$.
Codomain - target **set** of a **function**.

12.21 Open formula

Logical **function** that has **arity** and produces **proposition**.

12.22 Recursion

Repeated **function application** when sometimes same **function** gets called.

Allows computation that may require indefinite amount of work.

12.22.1 *

Recursive

12.22.2 Base case

A part of a [recursive function](#) that trivially produces result.

12.22.3 Tail recursion

Tail calls are [recursive](#) invocantions of itself.

12.22.4 Polymorphic recursion

[Type](#) of the [parameter](#) changes in [recursive](#) invocations of [function](#).

Is always a higher-ranked [type](#).

12.22.4.1 *

Milner–Mycroft typability

Milner–Mycroft calculus

12.23 Free variable

[Variable](#) in the fuction that is not [bound](#) by the head.

Until there are * - [function](#) stays [partially applied](#).

12.24 Closure

$f(x) = f^{\mathcal{X} \rightarrow \mathcal{X}} \mid \forall x \in \mathcal{X}, \mathcal{X}$ is [closed](#) under f , it is a trivial [case](#) when [operation](#) is legitimate for all values of the [domain](#).

[Operation](#) on members of the [domain](#) always produces a members of the [domain](#). The [domain](#) is [closed](#) under the [operation](#).

In the [case](#) when there is a [domain](#) values for which [operation](#) is not legitimate/not exists:

$f(x) = f^{\mathcal{V} \rightarrow \mathcal{X}} \mid \mathcal{V} \in \mathcal{X}, \forall x \in \mathcal{V}, \mathcal{X}$ is [closed](#) under f .

12.24.1 *

Closed

12.25 Parameter

para subsidiary

metron measure

Named variable of a [function](#).

[Argument](#) is a supplied value to a [function parameter](#).

[Parameter](#) ([formal parameter](#)) is an [irrefutable](#) pattern, and implemented that way in Haskell.

12.25.1 *

Parameters

Formal parameter

Formal parameters

12.26 Partial application

Part of [function parameters applied](#).

12.26.1 *

Partially applied

12.27 Well-formed formula

[Expression](#), logical [function](#) that is/can produce a [proposition](#).

12.27.1 *

Well formed formula

WFF

wff

WFFS

wffs

Chapter 13

Homotopy

homós same

One can be "continuously deformed" into the other.

For example - [functions](#), [functors](#).

[Natural transformation](#) is a [homotopy](#) of [functors](#).

13.1 *

Homotopies

Homotopic

Chapter 14

IO

Type for values whose evaluations has a possibility to cause side effects or return unpredictable result.

Haskell standard uses **monad** for constructing and transforming **IO** actions.

IO action can be evaluated multiple times.

IO data type has unpure imperative actions inside. Haskell is **pure Lambda calculus**, and un-pure **IO** integrates in the Haskell purely (**type** system abstracts **IO** unpurity inside **IO data type**).

IO sequences effect computation one after another in **order** of needed computation, or occurrence:

```
twoBinds :: IO ()
twoBinds =
  putStrLn "First:" >>
  getLine >>=
  \a ->
  putStrLn "Second:" >>
  getLine >>=
  \b ->
  putStrLn ("\nFirst: "
    ++ a ++ ".\nSecond "
    ++ b ++ ".")
main = twoBinds
```

Sequencing is achieved by compilation of effects performing only while they receive the sugared-in & passed around the **RealWorld** fake **type** value, that value in the every computation gets the new "value" and then passed to the next requested computation. But special thing is about this **parameter**, this **RealWorld type** value passed, but never looked at. GHC realizes, since value is never used, - it means value and **type** can be equated to **()** and moreover reduced from the code, and sequencing stays.

Chapter 15

Kind

`Kind -> Type -> Data`

15.1 *

Kinds

Chapter 16

Lambda calculus

Universal model of computation. Which means `*` can implement any [Turing machine](#).
Based on [function abstraction](#) and [application](#) by substituting [variables](#) and [binding](#) values.

`*` has [lambda terms](#):

- [variable](#) (x)
- [application](#) ($((ts))$)
- [abstraction](#) ([lambda function](#)) ($((\lambda x.t))$)

16.1 `*`

Lambda term
Lambda terms
Lambda variable
Lambda variables

16.2 Lambda cube

[-cube](#) shows the 3 dimensions of generalizations from simply typed [Lambda calculus](#) to [Calculus of constructions](#).

Each dimension of the cube corresponds to a new way of making [objects](#) depend on other [objects](#):

- ([First-class polymorphism](#)) - terms allowed to depend on [types](#), corresponding to [polymorphism](#).
- ([Higher-rank polymorphism](#)) - [types](#) depending on terms, corresponding to [dependent types](#).
- ([Type class](#)) - [types](#) depending on [types](#), corresponding to [type](#) operators.


16.2.1 *

-cube
 λ -cube

16.3 Lambda function

Function of Lambda calculus.

$\lambda xy.x^2 + y^3$
 $\sim \sim \sim$

**16.3.1 ***

Lambda abstraction

16.3.2 Anonymous lambda function

Lambda function that is not binded to any name.

16.3.2.1 *

Anonymous lambda function

16.4 β -reduction

Equation of a parameter to a bound variable, then reducing parameter from the head.

16.4.1 *

β reduction
 Beta-reduction
 Beta reduction

16.4.2 β -normal form

No beta reduction is possible.

16.4.2.1 *

β normal from
 Beta normal form
 Beta-normal form

16.5 Calculus of constructions

Extends the Curry–Howard correspondence to the proofs in the full intuitionistic [predicate](#) calculus (includes proofs of [quantified statements](#)).

[Type](#) theory, typed programming language, and constructivism (philosophy) foundation for mathematics.

Directly relates to Coq programming language.

16.5.1 *

«<CoC>»

16.6 Curry–Howard correspondence

[Equivalence](#) of {[First-order logic](#), computer programming, [Category](#) theory}. They represent each-other, possible in one - possible in the other, so all the definitions and theorems have analogues in other two.

Gives a ground to the [equivalence](#) of computer programs and mathematical proofs.

Lambek added analogue to Cartesian [closed category](#), which can be used to model logic and [type](#) theory.

Table 16.1: Table of basic correspondence

Logic	Type	Category
True	() (any inhabited type)	Terminal
False	Void	Initial
$a \wedge b$	(a, b)	$a \times b$
$a \vee b$	Either a b	a / b
$a \Rightarrow b$	$a \rightarrow b$	b^a

16.6.1 *

Curry–Howard isomorphism
 Curry–Howard–Lambek

16.7 Currying

Translating the [evaluation](#) of a multiple [argument function](#) (or a [tuple](#) of arguments) into evaluating a [sequence](#) of [functions](#), each with a single [argument](#).

16.7.1 *

Curry

16.8 Hindley–Milner type system

Classical [type](#) system for the [Lambda calculus](#) with [Parametric polymorphism](#) and [Type inference](#). [Types](#) marked as [polymorphic variables](#), which enables [type inference](#) over the code.

16.8.1 *

Hindley–Milner

Damas–Milner

Damas–Hindley–Milner

16.9 Reduction

Take out something from a [structure](#), make simpler.

See [Beta reduction](#)

16.9.1 *

Reducible

16.10 β - η normal form

All [\$\beta\$ -reduction](#) and [\$\eta\$ -abstraction](#) are done in the [expression](#).

16.10.1 *

beta-eta normal form

beta eta normal form

16.11 η -abstraction

$$(\lambda x.Mx) \xleftarrow[\eta]{} M$$

```
\ x -> g . f $ x
\ x -> g . f      --eta-abstraction
```


16.11.1 *

η -reduction
 η -conversion
 η abstraction
 η reduction
 η conversion
eta-abstraction
eta-reduction
eta-conversion
eta abstraction
eta reduction
eta conversion

16.12 Lambda expression

See [Lambda calculus](#) ([Lambda terms](#)) and [Expression](#). In majority cases meaning some [Lambda function](#).

Chapter 17

Lense

Library of combinators to provide Haskell (functional language without mutation) with the emulation of **get**-ters and **set**-ters of imperative language.

Chapter 18

Operation

Calculation into output value. Can have [zero](#) & more inputs.

18.1 Constant

[Nullary operation](#).

Also see: [Type constant](#).

18.2 Binary operation

$\forall(a, b) \in S, \exists P(a, b) = f(a, b) : S \times S \rightarrow S$

18.2.1 *

Binary operations

18.3 Operator

Denotation symbol/name for the [operation](#).

18.3.1 Shift operator

[Shift operator](#) defined by Lagrange through [Differential operator](#).

$$T^t = e^{t \frac{d}{dx}}$$

18.3.1.1 *

Shift

18.4 Infix

Form of writing of [operator](#) or [function](#) in-between [variables](#) for [application](#).

For priorities see [Fixity](#).

18.5 Fixity

Declares the presedence of action of a [function/operator](#).

Funciton [application](#) has presedence higher then all [infix](#) operators/[functions](#) (virtually giving it a [priority](#) 10).

Table 18.1: Haskell operators [priority](#) and [fixity](#) association

P	L	Non	R
10			F.A.
9	!!		.
8			^ ~ **
7	*/ div		
6	+-		
5			: , ++
4		<comparison> elem	
3			&&
2			OR
1			
0			\$ \$! seq

18.5.1 *

Infixl

Infixr

Priority

Precedence

18.6 Zero

* is the value with which [operation](#) always yelds [Zero](#) value.

$zero, n \in C : \forall n, zero * n = zero$

* is distinct from [Identity](#) value.

Chapter 19

Permutation

Bijjective function from domain to itself.

Domain & permutation functions & function composition form a group.

Chapter 20

Phrase

Composable expression.

Chapter 21

Point-free

Paradigm [where function](#) only describes the [morphism](#) itself.

Process of converting [function](#) to [point-free](#).

If brackets `()` can be changed to `$` then `$` equal to [composition](#):

```
\ x -> g (f x)
\ x -> g $ f x
\ x -> g . f $ x
\ x -> g . f      --eta-abstraction
```

```
\ x1 x2 -> g (f x1 x2)
\ x1 x2 -> g $ f x1 x2
\ x1 x2 -> g . f x1 $ x2
\ x1      -> g . f x1
```

21.1 *

Pointfree
Tacit
Tacit programming

21.2 Blackbird

`(.) . (.) :: (b -> c) -> (a1 -> a2 -> b) -> a1 -> a2 -> c`

[Composition of compositions](#) `(.) . (.)`. Allows to [compose](#)-in a [binary function](#) `f1(c) (.) . (.) f2(a,b)`.

```
\ f g x y -> f (g x y)
```

21.2.1 *

`.) .`
`(.) . (.)`
Composition of compositions

21.3 Swing

```
swing :: ((a -> b) -> b) -> c -> d) -> c -> a -> d
swing = flip . (. flip id)
swing f = flip (f . runCont . return)
swing f c a = f ($ a) c
```

21.4 Squish

```
f >>= a . b . c =<< g
```


Chapter 22

Polymorphism

polús many

At once several forms.

In Haskell - [abstract](#) over [data types](#).

* [types](#):

22.1 *

Polymorphic

22.2 Levity polymorphism

Extending [polymorphism](#) to work with unlifted and lifted [types](#).

22.3 Parametric polymorphism

[Abstracting](#) over [data types](#) by [parameter](#).

In most languages named as 'Generics' (generic programming).

[Types](#):

22.3.1 Rank-1 polymorphism

[Parametric polymorphism](#) in [rank-1 types](#) by [type variables](#).

22.3.1.1 *

Prenex

Prenex polymorphism

22.3.2 Let-bound polymorphism

It is [property](#) chosen for Haskell [type](#) system.

Haskell is based on [Hindley-Milner type](#) system, it is [let-bound](#).

To have strict [type inference](#) with [*](#) - if [let](#) and [where](#) declarations are [polymorphic](#) - λ declarations - should be not.

See: [Good: In Haskell parameters bound by lambda declaration instantiate to only one concrete type](#).

22.3.3 Constrained polymorphism

Constrained [Parametric polymorphism](#).

22.3.3.1 Ad hoc polymorphism

Artificial [constrained polymorphism](#) dependent on incoming [data type](#).

It is [interface dispatch](#) mechanism of [data types](#).

Achieved by creating a [type class instance functions](#).

Commonly known as overloading.

a. [*](#)

Ad-hoc polymorphism

Ad hoc polymorphic

Ad-hoc polymorphic

Constraint

Constraints

22.3.4 Impredicative polymorphism

[*](#) allows [type](#) entities with [polymorphic types](#) that can contain [type](#) itself.

$T = \forall X. X \rightarrow X : T \in X \models T \in T$

The most powerful form of [parametric polymorphism](#).

See: [Impredicative](#).

This approach has Girard's paradox ([type systems](#) [Russell's paradox](#)).

22.3.4.1 [*](#)

First-class polymorphism

22.3.5 Higher-rank polymorphism

Means that [polymorphic types](#) can appear within other [types](#) ([types of function](#)).

There is a cases [where higher-rank polymorphism](#) than the a Ad hoc - is needed. For example [where ad hoc polymorphism](#) is used in [constraints](#) of several different implementations of [functions](#), and you want to build a [function](#) on top - and use the [abstract interface](#) over these [functions](#).

```
-- ad-hoc polymorphism
f1 :: forall a. MyType Class a => a -> String    ==    f1 :: MyType Class a => a -> String
f1 = -- ...

-- higher-rank polymorphism
f2 :: Int -> (forall a. MyType Class a => a -> String) -> Int
f2 = -- ...
```

By moving forall inside the [function](#) - we can achieve [higher-rank polymorphism](#).

From: <https://news.ycombinator.com/item?id=8130861>

Higher-rank polymorphism is formalized using System F, and there are a few implementations of (in
Useful example aslo a [ST-Trick monad](#).

22.3.5.1 *

Rank-n polymorphism

22.4 Subtype polymorphism

Allows to declare usage of a [Type](#) and all of its Subtypes.

T - [Type](#)

S - Subtype of [Type](#)

<: - subtype of

$S <: T = S \leq T$

Subtyping is:

If it can be done to T, and there is subtype S - then it also can be done to S.

$S <: T : f^{T \rightarrow X} \Rightarrow f^{S \rightarrow X}$

22.5 Row polymorphism

Is a lot like [Subtype polymorphism](#), but aligns itself on allowance (with | r) of subtypes and [types](#) with requested [properties](#).

```
printX :: { x :: Int | r } -> String
printX rec = show rec.x

printY :: { y :: Int | r } -> String
printY rec = show rec.y

-- type is inferred as `{x :: Int, y :: Int | r } -> String`
printBoth rec = printX rec ++ printY rec
```

22.6 Kind polymorphism

Achieved using a phantom [type argument](#) in the [data type declaration](#).

```
;;          * -> *
data Proxy a = ProxyValue
```

Then, by default the [data type](#) can be inhabited and fully work being partially defined.
But multiple instances of [kind polymorphic type](#) can be distinguished by their particular [type](#).

Example is the [Proxy type](#):

```
data Proxy a = ProxyValue

let proxy1 = (ProxyValue :: Proxy Int) -- * :: Proxy Int
let proxy2 = (ProxyValue :: Proxy a)   -- * -> * :: Proxy a
```

22.7 Linearity polymorphism

Leverages [linear types](#).

For example - if [fold](#) over a dynamic array:

- a. In basic Haskell - array would be copied at every step.
- b. Use low-level [unsafe functions](#).
- c. With [Linear type function](#) we guarantee that the array would be used only at one place at a time.

So, if we use a [function](#) `(* -o * -o -o *)` in `foldr` - the [fold](#) will use the initial value only once.

Chapter 23

Pragma

Pragma - instruction to the compiler that specifies how a compiler should process the code. **Pragma** in Haskell have form:

```
{-# PRAGMA options #-}
```

23.1 LANGUAGE pragma

Controls what variations of the language are permitted.

It has a [set](https://downloads.haskell.org/~ghc/latest/docs/html/users_guide/ghc_exts.html) of allowed options: https://downloads.haskell.org/~ghc/latest/docs/html/users_guide/ghc_exts.html, which can be supplied.

23.1.1 LANGUAGE option

23.1.1.1 *

Language options

23.1.1.2 Useful by default

```
import EmptyCase
import FlexibleContexts
import FlexibleInstances
import InstanceSigs
import MultiParamTypeClasses
```

23.1.1.3 AllowAmbiguousTypes

Allow [type](#) signatures which appear that they would result in an unusable [binding](#). However GHC will still check and complain about a [functions](#) that can never be called.

23.1.1.4 ApplicativeDo

Enables an [alternative](#) in-depth [reduction](#) that translates the do-notation to the operators `<$>`, `<*>`, `join` as far as possible.

For GHC to pickup the patterns, the final [statement](#) must match one of these patterns exactly:

```

pure E
pure $ E
return E
return $ E

```

When the [statements](#) of [do expression](#) have dependencies between them, and [ApplicativeDo](#) cannot [infer](#) an [Applicative type](#) - GHC uses a heuristic $O(n^2)$ algorithm to try to use `<*>` as much as possible. This algorithm usually finds the best solution, but in rare complex cases it might miss an opportunity. There is also $O(n^3)$ algorithm that finds the optimal solution: `-foptimal-applicative-do`.

Requires `ap = <*>`, `return = pure`, which is true for the most [monadic types](#).

- Allows use of `do`-notation with [types](#) that are an instance of [Applicative](#) and [Functor](#)
- In some [monads](#), using the [applicative](#) operators is more efficient than [monadic bind](#). For example, it may enable more parallelism.

The only way it shows up at the source level is that you can have a `do expression` with only [Applicative](#) or [Functor](#) constraint.

It is possible to see the actual translation by using `-ddump-ds`.

23.1.1.5 ConstrainedClassMethods

Enable the definition of further [constraints](#) on individual class methods.

23.1.1.6 CPP

Enable [C preprocessor](#).

23.1.1.7 DeriveFunctor

Automatic [deriving](#) of instances for the [Functor type class](#).

For [type power set functor](#) is unique, its derivation implementation can be autochecked.

23.1.1.8 ExplicitForAll

Allow explicit [forall](#) quantifier in places [where](#) it is implicit by Haskell.

23.1.1.9 FlexibleContexts

Ability to use complex [constraints](#) in class [declaration contexts](#).

The only restriction on the [context](#) in a class [declaration](#) is that the class hierarchy must be acyclic.

```

class C a where
  op :: D b => a -> b -> b

class C a => D a where ...

```

$C \Rightarrow D$, so in `C` we can talk about `D`.

Synergizes with [ConstraintKinds](#).

23.1.1.10 FlexibleInstances

Allow [type class](#) instances [types](#) contain nested [types](#).

```
instance C (Maybe Int) where ...
```

Implies [TypeSynonymInstances](#).

23.1.1.11 GeneralizedNewtypeDeriving

Enable GHC's `newtype` cunning generalised [deriving](#) mechanism.

```
newtype Dollars = Dollars Int
  deriving (Eq, Ord, Show, Read, Enum, Num, Real, Bounded, Integral)
```

(In old Haskell-98 only `Eq`, `Ord`, `Enum` could be inherited.)

23.1.1.12 ImplicitParams

Allow definition of [functions](#) expecting implicit [parameters](#). In the Haskell that has static scoping of [variables](#) allows the dynamic scoping, such as in classic Lisp or ELisp. Sure thing this one can be puzzling as hell inside Haskell.

23.1.1.13 LambdaCase

Enables [expressions](#) of the form:

```
\case { p1 -> e1; ...; pN -> eN }
```

-- OR

```
\case
  p1 -> e1
  ...
  pN -> eN
```

23.1.1.14 MultiParamTypeClasses

Implies: [ConstrainedClassMethods](#)

Enable the definitions of [typeclasses](#) with more than one [parameter](#).

```
class Collection c a where
```

23.1.1.15 MultiWayIf

Enable multi-way-if syntax.

```
if | guard1 -> code1
   | ...
   | guardN -> codeN
```

23.1.1.16 OverloadedStrings

Enable overloaded string literals (string literals become desugared via the `IsString` class).

With overload, string literals has [type](#):

```
(IsString a) => a
```

The usual string syntax can be used, e.g. `ByteString`, `Text`, and other variations of string-like [types](#).

Now they can be used in pattern matches as `char->integer` translations. To [pattern match](#) `Eq` must be [derived](#).

To use class `IsString` - [import](#) it from `GHC.Ext`.

23.1.1.17 PartialTypeSignatures

Partial [type](#) signature contains [wildcards](#), placeholders (`_`, `_name`).

Allows programmer to which parts of a [type](#) to annotate and which to [infer](#). Also applies to [constraint](#) part.

As untuped [expression](#), partly typed can not polymorphically recurse.

[-Wno-partial-type-signatures](#) supresses [infer](#) warnings.

23.1.1.18 RankNTypes

Enable [types](#) of [arbitrary](#) rank.

See [Type rank](#).

Implies [ExplicitForAll](#).

Allows `forall` [quantifier](#):

- Left side of \rightarrow
- Right side of \rightarrow
- as [argument](#) of a [constructor](#)
- as [type](#) of a field

- as `type` of an implicit `parameter`
- used in pattern `type` signature of `lexically scoped type variables`

23.1.1.19 ScopedTypeVariables

By default `type variables` do not have a `scope` except inside `type` signatures `where` they are used.

When there are internal `type` signatures provided in the code block (`where`, `let`, etc.) they (main `type` description of a `function` and internal `type` descriptions) restrain one-another and become not truly `polymorphic`, which creates a bounding interdependency of `types` that GHC would complain about.

* option provides the `lexical scope` inside the code block for `type variables` that have `forall quantifier`. Because they are now lexically scoped - those `type variables` are used across internal `type` signatures.

For details see: <https://ocharles.org.uk/guest-posts/2014-12-20-scoped-type-variables.html>

Implies `ExplicitForAll`.

23.1.1.20 TupleSections

Allow `tuple` section syntax:

```
(, True)
(, "I", , , "Love", , 1337)
```

23.1.1.21 TypeApplications

Allow `type application` syntax:

```
read @Int 5

:type pure @[]
pure @[] :: a -> [a]

:type (<*>) @[]
(<*>) @[] :: [a -> b] -> [a] -> [b]

--

instance (CoArbitrary a, Arbitrary b) => Arbitrary (a -> b)

> ($ 0) <$> generate (arbitrary @(Int -> Int))
```

23.1.1.22 TypeSynonymInstances

Now `type` synonym can have its own `type class` instances.

23.1.1.23 UndecidableInstances

Permit instances which may lead to [type-checker](#) non-termination.

GHC has Instance termination rules regardless of [FlexibleInstances](#) [FlexibleContexts](#).

23.1.1.24 ViewPatterns

```
foo (f1 -> Pattern1) = c1
foo (fn -> Pattern2 a b) = g1 a b
```

(*expression* \rightarrow *pattern*): take what is came to match - [apply](#) the *expression*, then do *pattern*-match, and return what originally came to match.

[Semantics](#):

- *expression* & *pattern* share the [scope](#), so also [variables](#).
- if *expression* :: t1 -> t2 && *pattern* :: t2, then (*expression* \rightarrow *pattern*) t1.

* are like [pattern guards](#) that can be nested inside of other patterns.

* are a convenient way to pattern-match [algebraic data type](#).

Additional possible usage:

```
foo a (f2 a -> Pattern3 b c) = g2 b c -- only for function definitions
foo ((f,_), f -> Pattern4) = c2 -- variables can be bount to the left in data constructors and t
```

23.1.1.25 DatatypeContexts

Allow [contexts](#) in [data types](#).

```
data Eq a => Set a = NilSet | ConsSet a (Set a)
```

```
-- NilSet :: Set a
-- ConsSet :: Eq a => a -> Set a -> Set a
```

Considered misfeature. Deprecated. Going to be removed.

23.1.1.26 StandaloneKindSignatures

[Type](#) signatures for [type-level declarations](#).

```
type <name_1> , ... , <name_n> :: <kind>
```

```
type MonoTagged :: Type -> Type -> Type
data MonoTagged t x = MonoTagged x
```

```
type Id :: forall k. k -> k
type family Id x where
  Id x = x
```

```

type C :: (k -> Type) -> k -> Constraint
class C a b where
  f :: a b

type TypeRep :: forall k. k -> Type
data TypeRep a where
  TyInt    :: TypeRep Int
  TyMaybe :: TypeRep Maybe
  TyApp    :: TypeRep a -> TypeRep b -> TypeRep (a b)

```

< GHC 8.10.1 - [type](#) signatures were only for [term level](#) declarations.

Extension makes signatures feature more uniformal.

Allows to [set](#) the [order](#) of [quantification](#), [order](#) of [variables](#) in a [kind](#). For example when using [TypeApplications](#).

Allows to [set](#) full [kind](#) of derivable class, solving situations with [GADT](#) return [kind](#).

```

a. *
   SAKS
   Standalone kind signatures

```

23.1.1.27 PartialTypeSignatures

Very helpful. Helps to solve [type level](#), helps to establish [type](#) signatures and [constraints](#).

Allow to provide `_` in the [type](#) signatures to automatically infer in the [type](#) information there.

Wild cards:

- [Type](#)

```
f :: _ -> _ -> a
```

- [Constraint](#)

```
f :: _ => a -> b -> c
```

- [Named](#)

```
f :: _x -> _x -> a
```

allows to identify the same [wildcard](#).

23.1.2 How to make a GHC LANGUAGE extension

In `libraries/ghc-boot-th/GHC/LanguageExtensions/Type.hs` add new [constructor](#) to the Extension [type](#)

```
data Extension
  = Cpp
  | OverlappingInstances
  ...
  | Foo
```

```
/main/DynFlags.hs extend xFlagsDeps:
```

```
xFlagsDeps = [
  flagSpec "AllowAmbiguousTypes" LangExt.AllowAmbiguousTypes,
  ...
  flagSpec "Foo"                  LangExt.Foo
]
```

It is for basic [case](#). For [testing](#), parser see further: <https://blog.shaynefletcher.org/2019/02/adding-ghc-language-extension.html>

Chapter 24

Predicative

Non-self-referencing definition.

—

Antonym - [Impredicative](#).

Chapter 25

Compositionality

Complex [expression](#) is determined by the constituent [expressions](#) and the rules used to combine them.

If the meaning fully obtainable from the parts and [composition](#) - it is full, [pure compositionality](#).

If there exists [composed idiomatic expression](#) - it is unfull, unpure [compositionality](#), because meaning leaks-in from the sources that are not in the [composition](#).

25.1 *

Principle of compositionality

Composition

Compositional

Chapter 26

Ψ -combinator

Transforms two of the same [type](#), [applying](#) same mediate transformation, and then transforming those into the result.

```
import Data.Function (on)
on :: (b -> b -> c) -> (a -> b) -> a -> a -> c

--\
  * ---
--/
```

26.1 *

Psi-combinator
On-combinator

Chapter 27

Quantifier

Specifies the quantity of specimens.

Two most common [quantifiers](#) \forall ([Forall](#)) and \exists (Exists).
 $\exists!$ - one and only one (exists only unique).

27.1 *

Quantification
Quantifiers
Quantified

27.2 Forall quantifier

Permits to not [infer](#) the [type](#), but to use any that fits. The variant depends on the [LANGUAGE option](#) used:
[ScopedTypeVariables](#)
[RankNTypes](#)
[ExistentialQuantification](#)

27.2.1 *

Forall

Chapter 28

Referential transparency

Given the same input return the same output.

So:

- * **expression** can be replaced with its corresponding resulting value without change for program's behavior.

- * **functions** are **pure**.

28.1 *

Referentially transparent

Chapter 29

Relation

[Relationship](#) between two [objects](#).
Subset of a [Cartesian product](#) between [sets](#) of [objects](#).
Is not directed and not limited.

29.1 *

Relations
Relationship

Chapter 30

REPL

Read-eval-print loop, aka interactive shell.

Chapter 31

Semantics

Philosophical study of meaning.
Meaning of symbols, words.

31.1 Operational semantics

Constructing proofs from logical [assertions](#) and verifying/checking/asserting things about execution and procedures their [properties](#), such as correctness, safety or security.

Good to solve in-point localized tasks.

Process of [abstraction](#).

31.2 Denotational semantics

Construction of [objects](#), that describe/tag the meanings. In Haskell often [abstractions](#) that are ment (denotations), implemented directly in the code, sometimes exist over the code - allowing to reason and implement.

* are [composable](#).

Good to achieve more broad approach/meaning.

Also see [Abstraction](#).

31.2.1 Abstraction

abs away from, off (in absentia)
tractus draw, haul, drag

Purified generalization of process.

Forgetting the details ([axiomatic semantics](#)). Simplified approach. Out of sight - out of mind.

* creates a new semantic level in which one can be absolutely precise ([operational semantics](#)).

It is a great did to name an [abstraction](#) ([denotational semantics](#)).

31.2.1.1 *

Abstractions

Abstracting

Abstract

31.2.1.2 Leaky abstraction

[Abstraction](#) that leaks details that it is supposed to [abstract](#) away.

a. *

Leaky abstractions

31.2.2 Ambigram

ambi both

grámma written character

[Object](#) that from different points of view has the same meaning.

While this word has two contradictory diametrically opposite usages, one was chosen (more frequent).

But it has... Both.

TODO: For merit of differentiating the meaning about different meaning referring to [Tensor](#) as [object](#) with many meanings.

31.2.3 Binary

Two of something.

31.2.4 Arbitrary

arbitrarius uncertain

Random, any one of.

Used as: Any one with *this* [set](#) of [properties](#). ([constraints](#), [type](#), etc.).

When there is a talk about any [arbitrary](#) value - in fact it is a talk about the generalization of computations over the [set](#) of [properties](#).

31.2.5 Refutable

One that has an option to fail.

31.2.6 Irrefutable

One that can not fail.

31.3 Axiomatic semantics

Empirical process of studying something complex by finding and analyzing true [statements](#) about it.

Good for examining interconnections.

31.3.1 Property

Something has a [property](#) in the real world, and in theory its [property](#) corresponds to the law/laws, axioms.

In Haskell under [property](#)/law most often [properties](#) of [algebraic structures](#).

There [property testing](#) wich does what it says.

31.3.1.1 *

Properties

31.3.1.2 Associativity

Joined with common purpose.

$$P(a, P(b, c)) \equiv P(P(a, b), c) \mid \forall (a, b, c) \in S,$$

* - the operations can be grouped arbitrarily.

[Property](#) that determines how operators of the same [precedence](#) are grouped, (in computer science also in the absence of parentheses).

Etymology:

Latin *associatus* past participle of *associare* "[join](#) with", from assimilated form of *ad* "to" + *sociare* "unite with", from *socius* "companion, ally" from PIE **sokw-yo-*, suffixed form of root **sekw-* "to follow".

In Haskell * has influence on parsing when compounds have same [fixity](#).

a. *

Associative

Associative law

Associativity law

31.3.1.3 Left associative

* - the operations are grouped from the left.

Example:

In lambda [expressions](#) same level parts follow grouping from left to right.

$$(\lambda x.x)(\lambda y.y)z \equiv ((\lambda x.x)(\lambda y.y))z$$

a. *

Left associativity

Left-associative

31.3.1.4 Right associative

* - the operations are grouped from the right.

31.3.1.5 Non-associative

Operations can't be chained.

Often is the [case](#) when the output [type](#) is incompatible with the input [type](#).

31.3.1.6 Basis

$\beta\alpha\sigma\iota\varsigma$ - stepping

The initial point, unreducible axioms and terms that spawn a theory.

AKA see [Category](#) theory, or Euclidian geometry [basis](#).

- a. Contravariant The [property](#) of [basis](#), in which if new [basis](#) is a [linear](#) combination of the prior [basis](#), and the change of [basis](#) inverse-proportional for the description of a [Tensors](#) in this basis.

Denotation:

Components for [contravariant basis](#) denoted in the upper indices:

$$V^i = x$$

The [inverse](#) of a [covariant](#) transformation is a [contravariant](#) transformation. Whenever a vector should be invariant under a change of [basis](#), that is to say it should represent the same geometrical or physical [object](#) having the same magnitude and direction as before, its components must transform according to the [contravariant](#) rule.

a. *

Contravariant cofunctor

Contravariant functor - More inline term is [Contravariant cofunctor](#)

- b. Covariant The [property](#) of [basis](#), in which if new [basis](#) is a [linear](#) combination of the prior [basis](#), and the change of [basis](#) proportional for a descriptions of [tensors](#) in basis.

Denotation:

Components for [covariant basis](#) denoted in the upper indices:

$$V_i = x$$

a. *

Covariant functor

Covariant cofunctor

31.3.1.7 Commutativity

$$\forall (a, b) \in S : P(a, b) \equiv P(b, a)$$

a. *

Commutative

Commutative law

31.3.1.8 Idempotence

First [application](#) gives a result. Then same [operation](#) can be [applied](#) multiple times without changing the result.

Example: Start and Stop buttons on machines.

a. *

Idempotent

Idempotency

31.3.1.9 Distributive property

Set S and two [binary](#) operators $+$ \times :

- $x \times (y + z) = (x \times y) + (x \times z)$ - \times is left-[distributive](#) over $+$
- $(y + z) \times x = (y \times x) + (z \times x)$ - \times is right-[distributive](#) over $+$
- left-&right-[distributive](#) - \times is [distributive](#) over $+$

a. *

Distributive rule

Distributive axiom

Distributive law

Distributive

31.4 Argument

arguere to make clear, to shine

* - evidence, proof, [statement](#) that results in system consequences.

31.4.1 Argument of a function

A value binded to the [function parameter](#). Value/topic that the fuction would process/deal with.

Also see [Argument](#).

31.4.1.1 *

Function argument

31.5 Content word

Words that name [objects](#) of reality and their qualities.

31.6 Ancient Greek and Latin prefixes

31.6.1 *

Greek prefix

Latin prefix

31.7 Idiom

* - something having a meaning that can not be [derived](#) from the conjoined meanings. Meaning can be special for language speakers or human with particular knowledge.

* can also mean [applicative functor](#).

31.7.1 *

Idioms

Idiomatic

31.8 Impredicative

Self-referencing definition.

—

Antonym - *[Predicative](#)*.

31.9 Context-free grammar

[Type](#) of formal grammar that is: a [set](#) of production rules that describe all possible string is a given formal language.

Table 31.1: Ancient Greek and Latin prefixes

Meaning	Greek prefix	Latin prefix
above, excess	hyper-	super-, ultra-
across, beyond, through	dia-	trans-
after		post-
again, back		re-
against	anti-	contra-, (in-, ob-)
all	pan	omni-
around	peri-	circum-
away or from	apo-, ap-	ab- (or de-)
bad, difficult, wrong	dys-	mal-
before	pro-	ante-, pre-
between, among		inter-
both	amphi-	ambi-
completely or very		de-, ob-
down		de-, ob-
four	tetra-	quad-
good	eu-	ben-, bene-
half, partially	hemi-	semi-
in, into	en-	il-, im-, in-, ir-
in front of	pro-	pro-
inside	endo-	intra-
large	macro-	(macro-, from Greek)
many	poly-	multi-
not*	a-, an-	de-, dis-, in-, ob-
on	epi-	
one	mono-	uni-
out of	ek-	ex-, e-
outside	ecto-, exo-	extra-, extro-
over	epi-	ob- (sometimes)
self	auto-, aut-, auth-	ego-
small	micro-	
three	tri-	tri-
through	dia-	trans-
to or toward	epi-	ad-, a-, ac-, as-
two	di-	bi-
under, insufficient	hypo-	sub-
with	sym-, syn-	co-, com-, con-
within, inside	endo-	intra-
without	a-, an-	dis- (sometimes)

Term is invented by Noam Chomsky.

31.9.1 *

CFG

Chapter 32

Set

Well-defined collection of distinct [objects](#).

32.1 *

Sets
Set theory

32.2 Closed set

- a. [Set](#) which complements an open [set](#).
- b. Is form of [Closed](#)-form [expression](#). [Set](#) can be [closed](#) in under a [set](#) of operations.

32.3 Power set

For some [set](#) \mathcal{S} , the [power set](#) ($\mathcal{P}(\mathcal{S})$) is a [set](#) of all subsets of \mathcal{S} , including $\{\}$ & \mathcal{S} itself.

Denotation:
 $\mathcal{P}(\mathcal{S})$

32.4 Singleton

[Singleton](#) - [unit set](#) - [set](#) with exactly one element.
Also 1-[sequence](#).

32.5 Russell's paradox

If there exists normal [set](#) of all [sets](#) - it should contain itself, which makes it abnormal.

32.6 Cartesian product

$\mathcal{A} \times \mathcal{B} \equiv \sum^{\vee} (a, b) \mid \forall a \in \mathcal{A}, \forall b \in \mathcal{B}.$

Operation, returns a **set** of all ordered pairs (a, b)

Any **function**, **functor** is a subset of **Cartesian product**.

$$\sum (elem \in (\mathcal{A} \times \mathcal{B})) = cardinality^{\mathcal{A} \times \mathcal{B}}$$

Properties:

- not **associative**
- not **commutative**

32.6.1 Pullback

Subset of the **cartesian product** of two **sets**.

32.6.1.1 *

Pullbacks

Chapter 33

Shrinking


Process of reducing complexity in the test [case](#) - re-run with smaller values and make sure that the test still fails.

Chapter 34

Spine

Is a chain of memory cells, each points to the both value of element and to the next memory cell.

Array:



1:2:3: []

Spine:



Chapter 35

Superclass

Broader parent class.

Chapter 36

Tensor

Object existing out of planes, thus it can translate **objects** from one plane into another. They can be tried to be described with knowledge existing inside planes, but representation would always be partial.

Tensor of rank 1 is a vector.

Translatioin with **tensor** can be seen as **functors**.

36.1 *

Tensors
Tensorial

Chapter 37

Testing

37.1 Property testing

Since [property](#) has a law, then family of that [unit](#) tests can be abstracted into the [lambda function](#).

And tests cases come from [generator](#).

37.1.1 Function property

[Property](#) corresponds to the according law.

In [property testing](#) you need to think additionally about [generator](#) and [shrinking](#).

37.1.2 Property testing type

Table 37.1: [Property testing types](#)

	Exhaustive	Randomized	Unit test
Whole set of values	Exhaustive property test	Randomised property test	One element
Special subset of values	Exhaustive specialised property test	Randomised specialised property test	One element

37.1.3 Generator

```
Seed
|
v
Gen A -> A
^
|
Size
```

Seed allows reproducibility.

There is anyway a need to have some seed.

Size allows setting upper [bound](#) on size of generated value. Think about infinity of [list](#).

After failed test - [shrinking](#) tests value parts of counterexample, finds a part that still fails, and recurses [shrinking](#).

37.1.3.1 *

Generators

37.1.3.2 Custom generator

When certain theorem only works for a specific [set](#) of values - the according [generator](#) needs to be produced.

```
arbitrary :: Arbitrary a => Gen a
suchThat :: Gen a -> (a -> Bool) -> Gen a
elements :: [a] -> Gen a
```

37.1.4 Reusing test code

Often it is convenient to [abstract testing](#) of same [function properties](#):

It can be done with (aka TestSuite [combinator](#)):

```
-- Definition
{-# LANGUAGE ScopedTypeVariables #-}
{-# LANGUAGE AllowAmbiguousTypes #-}
eqSpec :: forall a. Arbitrary a => Spec

-- Usage
{-# LANGUAGE TypeApplications #-}
spec :: Spec
spec = do
  eqSpec @Int

Eq Int
(==) :: Int -> Int -> Bool
  is reflexive
  is symmetric
  is transitive
  is equivalent to (\ a b -> not $ a /= b)
(/=) :: Int -> Int -> Bool
  is antireflexive
  is equivalent to (\ a b -> not $ a == b)
```

37.1.4.1 Test Commutative property

[Commutativity](#)

```
:: Arbitrary a => (a -> a -> a) -> Property
```

37.1.4.2 Test Symmetry property

[Symmetry](#)

```
:: Arbitrary a => (a -> a -> Bool) -> Property
```

37.1.4.3 Test Equivalence property

Equivalence

```
:: (Arbitrary a, Eq b) => (a -> b) -> (a -> b) -> Property
```

37.1.4.4 Test Inverse property

```
:: (Arbitrary a, Eq b) => (a -> b) -> (b -> a) -> Property
```

37.1.5 QuickCheck

Target is a member of the [Arbitrary type class](#).

Target -> Bool is something Testable. This [properties](#) can be complex.

[Generator](#) arbitrary gets the seed, and produces values of Target.

[Function](#) quickCheck runs the loop and tests that generated Target values always comply the [property](#).

37.1.5.1 Manual automation with QuickCheck properties

```
import Test.QuickCheck
import Test.QuickCheck.Function
import Test.QuickCheck.Property.Common
import Test.QuickCheck.Property.Functor
import Test.QuickCheck.Property.Common.Internal

data Four' a b = Four' a a a b
    deriving (Eq, Show)

instance Functor (Four' a) where
    fmap f (Four' a b c d) = Four' a b c (f d)

instance (Arbitrary a, Arbitrary b) => Arbitrary (Four' a b) where
    arbitrary = do
        a1 ← arbitrary
        a2 ← arbitrary
        a3 ← arbitrary
        b ← arbitrary
        return (Four' a1 a2 a3 b)

-- Wrapper around `prop_FunctorId`
prop_AutoFunctorId  Functor f  f a → Equal (f a)
prop_AutoFunctorId = prop_FunctorId T

type Prop_AutoFunctorId f a
    = f a
    → Equal (f a)

-- Wrapper around `prop_AutoFunctorCompose`
prop_AutoFunctorCompose  Functor f  Fun a1 a2 → Fun a2 c → f a1 → Equal (f c)
prop_AutoFunctorCompose f1 f2 = prop_FunctorCompose (applyFun f1) (applyFun f2) T

type Prop_AutoFunctorCompose structureType origType midType resultType
    = Fun origType midType
    → Fun midType resultType
```

```
→ structureType origType
→ Equal (structureType resultType)

main = do
  quickCheck $ eq $ (prop_AutoFunctorId Prop_AutoFunctorId (Four' ()))Integer)
  quickCheck $ eq $ (prop_AutoFunctorId Prop_AutoFunctorId (Four' ())) (Either Bool String))
  quickCheck $ eq $ (prop_AutoFunctorCompose Prop_AutoFunctorCompose (Four' ())) String Integer
  quickCheck $ eq $ (prop_AutoFunctorCompose Prop_AutoFunctorCompose (Four' ())) Integer String
```

37.2 Write tests algorithm

- a. Pick the right language/[stack](#) to implement features.
- b. How expensive breakage can be.
- c. Pick the right tools to test this.

Chapter 38

Uncurry

Replace sequenced lambda [functions](#) into single [function](#) taking [sequence/product](#) of values as [argument](#).

Chapter 39

Unit

Represents existence. Denoted as empty [sequence](#).

()

Type () holds only self-representation [constructor](#) (), & [constructor](#) holds [nothing](#).

Haskell code always should receive something back, hence [nothing](#), emptiness, [void](#) can not be theoretically addressed, practically constructed or received - [unit](#) in Haskell also has a role of a stub in place of emptiness, like in IO ().

Chapter 40

Nullary

Takes no entries; has the [arity](#) of [zero](#).
Has the trivial [domain](#).

Chapter 41

Logic

41.1 Proposition

Purely abstract & theoretical logical [object](#) (idea) that has a Boolean value.

* is expressed by a [statement](#).

41.1.1 *

Propositions

41.1.2 Atomic proposition

Logically undividable [unit](#). Does not contain [logical connectives](#).

41.1.2.1 *

Atomic propositions

41.1.3 Compound proposition

Formed by connecting [propositions](#) by [logical connectives](#).

41.1.3.1 *

Compound propositions

41.1.4 Propositional logic

Studies [propositions](#) and [argument](#) flow.

Refers to logically indivisible units ([atomic propositions](#)) as such, for theory - they are [abstractions](#) with Boolean [properties](#).

Not Turing-complete, impossible to [construct](#) an [arbitrary](#) loop.

41.1.4.1 *

Proposition logic
 Proposition calculus
 Propositional calculus
 Statement logic
 Sentential logic
 Sentential calculus
 Zeroth-order logic

41.1.4.2 First-order logic

Notation systems that use [quantifiers](#), [relations](#), [variables](#) over non-logical [objects](#), allows the use of [expressions](#) that contain [variables](#).

Turing-complete.

Extension of a [propositional logic](#).

a. *

Predicate logic
 First-order predicate logic
 First-order predicate calculus

b. Second-order logic Extension over [first-order logic](#) that quantifies over [relations](#).

a. Higher-order logic Extension over [second-order logic](#) that uses additional [quantifiers](#), stronger [semantics](#).

Is more expressive, but model-theoretic [properties](#) are less well-behaved.

41.2 Logical connective

Logical [operation](#).

41.2.1 *

Logical connectives

41.2.2 Conjunction

Logical AND.

Denotation:

\wedge

Multiplies [cardinalities](#).

Haskell [kind](#):

* *

41.2.3 Disjunction

Logical *OR*

Denotation:

\vee

Summs [cardinalities](#).

41.3 Predicate

[Function](#) with Boolean [codomain](#).

$P : X \rightarrow \{true, false\}$ - * on X .

Notation: $P(x)$

Almost always can include [relations](#), [quantifiers](#).

41.4 Statement

Declarative [expression](#) that is a bearer of a [proposition](#).

When we talk about [expression](#) or [statement](#) being true/false - in fact we refer to the [proposition](#) that they represent.

Difference between [proposition](#), [statement](#), [expression](#):

a. "2 + 3 = 5"

b. "two plus three equals five"

- 1 & 2 are [statements](#). Each of them is a collection of transmission symbols (linguistic [objects](#)) from a symbol systems \equiv [expression](#). Each of them is [expression](#) that bears [proposition](#) (an idea resulting in a Boolean value) \equiv [statement](#).
- 1 & 2 represent the same [proposition](#). [Proposition](#) from 1 \equiv [proposition](#) from 2.
- [Statement](#) 1 \neq [statement](#) 2. They are two different [statements](#), written in different systems. And [statement](#) "2 + 3 = 5" \neq [statement](#) "3 + 2 = 5".

41.4.1 *

Assertion

Assertions

Statements

41.5 Iff

If and only if, exactly when, just.

Denotation:

\iff

Chapter 42

Haskell structures

42.1 Pattern match

Are not [first-class](#). It is a [set](#) of patten match semantic notations.

Must be [linear](#).

* [precedence](#) (especially with more then one [parameter](#), especially with `_` used) often changes the [function](#).

42.1.1 As-pattern

```
f list@(x, xs) = ...
```

```
f (x:xs)    = x:x:xs -- Can be compiled with reconstruction of x:xs
f a@(x:_) = x:a -- Reuses structure without reconstruction
```

42.1.1.1 *

As-patterns

As pattern

As patterns

42.1.2 Wild-card

Matches anything and can not be binded. For matching someting that should pass not checked and is not used.

```
head (x:_)      = x
tail (_:xs)     = xs
```

42.1.2.1 *

Wild-cards

Wildcard

Wildcards

42.1.3 Case

```
case x of
  pattern1 -> ex1
  pattern2 -> ex2
  pattern3 -> ex3
  otherwise -> exDefault
```

Bolting [guards](#) & [expressions](#) with syntactic sugar on [case](#):

```
case () of _
  | expr1      -> ex1
  | expr2      -> ex2
  | expr3      -> ex3
  | otherwise  -> exDefault
```

Pattern matching in [function](#) definitions is realized with [case expressions](#).

42.1.4 Guard

Check values against the [predicate](#) and use the first match definition:

```
f x
  | predicate1 = definition1
  | predicate2 = definition2
  ...
  | x < 0      = definitionN
  ...
  | otherwise  = definitionZ
```

42.1.4.1 *

Guards

42.1.5 Pattern guard

Allows check a [list](#) of pattern matches against [functions](#), and then proceed.

$$(patternMatch1) <- (funcCheck1)$$

```
, (patternMatch2) <- (funcCheck2)
= RHS
```

```
lookup :: Eq a => a -> [(a, b)] -> Maybe b
```

```
addLookup l a1 a2
  | Just b1 <- lookup a1 l
  , Just b2 <- lookup a2 l
  = b1 + b2
{-...other equations...-}
```

Run [functions](#), they must succeed. Then [pattern match](#) results to `b1`, `b2`. Only if successful - execute the equation.

Default in Haskell 2010.

42.1.5.1 *

Pattern guards

42.1.6 Lazy pattern

Defers the [pattern match](#) directly to the last moment of need during execution of the code.

```
f (a, b) = g a b -- It would be checked that the pattern of the pair constructor
-- is present, and that parameters are present in the constructor.
-- Only after that success - work would start on the RHS, aka then construction
-- g would start only then.
```

```
f ~(a, b) = g a b -- Pattern match of (a, b) deferred to the last moment,
-- RHS starts, construction of g starts.
-- For this lazy pattern the equivalent implementation would be:
-- f p = g (fst p) (snd p) -- RHS starts, during construction of g
-- the arguments would be computed and found, or error would be thrown.
```

Due to full laziness deferring everything to the runtime execution - the [lazy pattern](#) is one-size-fits all ([irrefutable](#)), analogous to `_`, and so it does not produce any checks during compilation, and raises [errors](#) during runtime.

`*` is very useful during [recursive](#) construction of [recursive structure](#)/process, especially infinite.

42.1.6.1 *

Lazy-pattern
Lazy patterns

42.1.7 Pattern binding

Entire [LHS](#) is a pattern, is a [lazy pattern](#).

```
fib@(1:tfib) = 1 : 1 : [ a+b | (a,b) <- zip fib tfib ]
```

42.1.7.1 *

Pattern bindings

42.2 Smart constructor

Process/code placing extra rules & [constraints](#) on the construction of values.

42.3 Level of code

There are these levels of Haskell code:

42.3.1 *

Code level

42.3.2 Type level

Level of code that works with data types.

42.3.2.1 Type level declaration

```
type ...
newtype ...
data ...
class ...
instance ...
```

a. *

Type level declarations
Type-level declaration
Type-level declarations

42.3.2.2 Type check

if The type level information is complete (strongly connected graph)

then

Generalize the types and check if type level consistent to term level.

else

Infer the missing type level part from the term level. There are certain situations and structures where ambiguity arises and is unsolvable from the information of the term level (most basic example is polymorphic recursion).

a. *

Typecheck
Typechecking
Typechecks

- b. Complete user-specific kind signature Type level declaration is considered to "have a CUSK" is it has enough syntactic information to warrant completeness (strongly connected graph) and start checking type level correspondence to term level, it is a ad-hock state of type inferring.

In the future GHC would use other algorithm over/instead of CUSK.

- a.* *
 - CUSK
 - CUSKs
 - Complete user-specific kind signatures
 - Complete, user-specific kind signature

42.3.3 Term level

Level of code that does logical execution.

42.3.4 Compile level

Level of code, about compilation processes/results.

42.3.4.1 *

Compilation level

42.3.5 Runtime level

Level of code of main program operation, when machine does computations with compiled binary code.

42.3.6 Kind level

Level of code where kinds & kind declarations are situated, inferred and checked.

42.3.6.1 Kind check

Applying the type check to kind check:

if The kind level information is complete (strongly connected graph)

then

Check if kind level consistent to term level.

else

Infer the missing kind level parts from the type level. There are certain situations and structures where ambiguity arises and is unsolvable from the information of the kind level.

With StandaloneKindSignatures kind completeness happens against found (standalone) kind signature.

With CUSKs extension kind completeness happens against "complete user-specific kind signature"

- a. *
Kindcheck
Kind checks

42.4 Orphan type instance

Hanging [type](#) instance from inconsistent code base.

- a. Supporting [structure](#) not fully present.
- b. Several implementations of instance present.

42.5 Undefined

Placeholder value that helps to do [typechecking](#).

42.6 Hierarchical module name

Hierarchical naming scheme:

```
Algebra                -- Was this ever used?
  DomainConstructor    -- formerly DoCon
  Geometric            -- formerly BasGeomAlg

Codec                  -- Coders/Decoders for various data formats
  Audio
    Wav
    MP3
    ...
  Compression
    Gzip
    Bzip2
    ...
  Encryption
    DES
    RSA
    BlowFish
    ...
  Image
    GIF
    PNG
    JPEG
    TIFF
    ...
  Text
    UTF8
    UTF16
    ISO8859
```

```

    ...
Video
  Mpeg
  QuickTime
  Avi
  ...
Binary          -- these are for encoding binary data into text
  Base64
  Yenc

Control
  Applicative
  Arrow
  Exception      -- (opt, inc. error & undefined)
  Concurrent      -- as hslibs/concurrent
    Chan          -- these could all be moved under Data
    MVar
    Merge
    QSem
    QSemN
    SampleVar
    Semaphore
  Parallel        -- as hslibs/concurrent/Parallel
  Strategies
  Monad           -- Haskell 98 Monad library
    ST            -- ST defaults to Strict variant?
      Strict      -- renaming for ST
      Lazy        -- renaming for LazyST
    State         -- defaults to Lazy
      Strict
      Lazy
    Error
    Identity
    Monoid
    Reader
    Writer
    Cont
    Fix           -- to be renamed to Rec?
    List
    RWS

Data
  Binary          -- Binary I/O
  Bits
  Bool            -- &&, ||, not, otherwise
  Tuple          -- fst, snd
  Char           -- H98
  Complex        -- H98
  Dynamic
  Either
  Int
  Maybe          -- H98
  List           -- H98
  PackedString
  Ratio          -- H98

```

```

Word
IORef
STRef          -- Same as Data.STRef.Strict
  Strict
  Lazy          -- The lazy version (for Control.Monad.ST.Lazy)
Binary         -- Haskell binary I/O
Digest
  MD5
  ...          -- others (CRC ?)
Array          -- Haskell 98 Array library
  Unboxed
  IArray
  MArray
  IO           -- mutable arrays in the IO/ST monads
  ST
Trees
  AVL
  RedBlack
  BTree
Queue
  Bankers
  FIFO
Collection
Graph          -- start with GHC's DiGraph?
FiniteMap
Set
Memo           -- (opt)
Unique

Edison         -- (opt, uses multi-param type classes)
  Prelude      -- large self-contained packages should have
  Collection   -- their own hierarchy? Like a vendor branch.
  Queue        -- Or should the whole Edison tree be placed

Database
  MySQL
  PostgreSQL
  ODBC

Dotnet
  ...          -- Mirrors the MS .NET class hierarchy

Debug          -- see also: Test
  Trace
  Observe      -- choose a default amongst the variants
    Textual    -- Andy Gill's release 1
    ToXmlFile  -- Andy Gill's XML browser variant
    GHood      -- Claus Reinke's animated variant

Foreign
  Ptr
  StablePtr
  ForeignPtr   -- rename to FinalisedPtr? to void confusion with Foreign.Ptr
  Storable
  Marshal

```

```
    Alloc
    Array
    Errors
    Utils
C
    Types
    Errors
    Strings

GHC
    Exts          -- hslibs/lang/GlaExts
    ...

Graphics
    HGL
    Rendering
        Direct3D
        FRAN
        Metapost
        Inventor
        Haven
        OpenGL
            GL
            GLU
    Pan
UI
    FranTk
    Fudgets
    GLUT
    Gtk
    Motif
    ObjectIO
    TkHaskell
X11
    Xt
    Xlib
    Xmu
    Xaw

Hugs
    ...

Language
    Haskell      -- hslibs/hssource
        Syntax
        Lexer
        Parser
        Pretty
    HaskellCore
    Python
    C
    ...

Nhc
    ...
```

```

Numeric          -- exports std. H98 numeric type classes
  Statistics

Network          -- (== hslibs/net/Socket), depends on FFI only
  BER            -- Basic Encoding Rules
  Socket         -- or rename to Posix?
  URI            -- general URI parsing
  CGI            -- one in hslibs is ok?
  Protocol
    HTTP
    FTP
    SMTP

Prelude          -- Haskell98 Prelude (mostly just re-exports
                  other parts of the tree).

Sound            -- Sound, Music, Digital Signal Processing
  ALSA
  JACK
  MIDI
  OpenAL
  SC3            -- SuperCollider

System           -- Interaction with the "system"
  Cmd            -- ( system )
  CPUTime        -- H98
  Directory      -- H98
  Exit           -- ( ExitCode(..), exitWith, exitFailure )
  Environment    -- ( getArgs, getProgName, getEnv ... )
  Info           -- info about the host system
  IO             -- H98 + IOExts - IOArray - IORef
    Select
    Unsafe       -- unsafePerformIO, unsafeInterleaveIO
  Console
    GetOpt
    Readline
  Locale         -- H98
  Posix
    Console
    Directory
    DynamicLinker
      Prim
      Module
    IO
    Process
    Time
  Mem            -- rename from cryptic 'GC'
    Weak         -- (opt)
    StableName   -- (opt)
  Time          -- H98 + extensions
  Win32         -- the full win32 operating system API

Test
  HUnit

```

```

QuickCheck

Text
  Encoding
    QuotedPrintable
    Rot13
  Read
    Lex          -- cut down lexer for "read"
  Show
    Functions    -- optional instance of Show for functions.
  Regex         -- previously RegexString
  Posix         -- Posix regular expression interface
  PrettyPrint   -- default (HughesPJ?)
    HughesPJ
    Wadler
    Chitil
    ...
  HTML          -- HTML combinator lib
  XML
    Combinators
    Parse
    Pretty
    Types
  ParserCombinators -- no default
    ReadP        -- a more efficient "ReadS"
    Parsec
    Hutton_Meijer
    ...

Training          -- Collect study and learning materials
  <name of the tutor>

```

42.6.1 *

Top-level module name
 Top-level module names

42.7 import

`import` [statement](#) by default imports identifiers from the other [module](#), using [hierarchical module name](#), brings into [scope](#) the identifiers to the global [scope](#) both into unqualified and qualifies by the [hierarchical module name](#) forms.

This possibilities can mix and match:

- `<modName> ()` - `import` only instances of [type classes](#).
- `<modName> (x, y)` - `import` only declared indentifiers.
- `qualified <modName>` - discards unqualified names, forse obligatory namespace for the imports.

- `hiding (x, y)` - skip `import` of declared identifies.
- `<modName> as <modName>` - renames `module` namespace.
- `<type/class> (..)` - `import` class & it's methods, or `type`, all its data `constructors` & field names.

42.8 Let

* `expression` is a `set` of cross-recursive lazy pattern bindings.

Declarations permitted:

- `type` signatures
- `function bindings`
- `pattern bindings`

It is an `expression` (macro) and that integrates in external `lexical scope expression` it `applied` in.

Form:

```
let
  b1
  bn
in
  c
```

42.8.1 *

Let expression
Let expressions

42.9 Where

Part of the syntax of the whole `function declaration`, has according `scope`.

As part of whole `declaration` - can extend over definitions of the funtion (pattern matches, `guards`).

Form:

```
f match1 = y
f match2 = y
f x =
  | cond1 x = y
```



```

    | cond2 x = y
    | otherwise = y
where
    y = ... x ...

```

42.9.1 *

Where clause

42.10 Reserved word

Haskell has special meaning for:

case, class, data, deriving, do, else, if, import, in, infix, infixl, infixr, instance, let, of, module, newtype, ...

42.10.1 *

Reserved words

42.11 Haskell Language Report

Document that is a standard of language.

42.11.1 *

Report
Haskell Report
Haskell 98 Language Report
Haskell 98 Report
Haskell 1998 Language Report
Haskell 2010 Language Report
Haskell 2010 Report

42.12 Haskell'

Current language development mod.

<https://prime.haskell.org/>

42.12.1 *

Haskell prime

Chapter 43

Computer science

43.1 Guerrilla patch

* changing code/[applying](#) patch sneakily - and possibility incompatibility with other at runtime. [Monkey patch](#) is derivative term.

43.1.1 Monkey patch

From [Guerrilla patch](#).

* is a way for program to modify supporting system software affecting only the running instance of the program.

43.2 Interface

Point of mutual meeting. Code behind [interface](#) determines how data is consumed.

43.3 Module

Importable organizational [unit](#).

43.4 Scope

Area [where binds](#) are accessible.

43.4.1 Dynamic scope

The name resolution depends upon the program state when the name is encountered, which is determined by the execution [context](#) or calling [context](#).

43.4.2 Lexical scope

[Scope bound](#) by the [structure](#) of source code [where](#) the named entity is defined.

43.4.2.1 *

Static scope

43.4.3 Local scope

Scope applies only in (current) area.

43.4.3.1 *

Local

43.5 Shadowing

When in the local scope bigger scope variable overridden by same name variable from the local scope.

43.6 Syntactic sugar

Artificial way to make language easier to read and write.

43.7 System F

Is parametric polymorphism in programming.

Extends the Lambda calculus by introducing \forall (universal quantifier) over types.

43.7.1 *

Girard–Reynolds polymorphic lambda calculus
Girard-Raynolds

43.8 Tail call

Final evaluation inside the function. Produces the function result.

43.9 Thunk

Not evaluated calculation. Can be dragged around, until be lazily evaluated.

Table 43.1: Application memory structural parts

Storage of	Block name
All not currently processing data	Heap
Function call, local variables	Stack
Static and global variables	Static/Global
Instructions	Binary code

43.10 Application memory

When even Main invoked - it work in [Stack](#), and called [Stack](#) frame. [Stack](#) frame size for [function](#) calculated when it is compiled.

When stacked [Stack](#) frames exceed the [Stack](#) size - [stack](#) overflow happens.

43.11 Turing machine

Mathematical model of computation that defines [abstract Turing machine](#). [Abstract](#) machine which manipulates symbols on a strip of tape, according to a table of rules.

43.11.1 Turing complete

[Set](#) of action rules that can simulate any [Turing machine](#).

43.11.1.1 *

Turing incomplete

Turing incompleteness

Turing completeness

Computationally universal

Chapter 44

Graph theory

44.1 Successor

Object that receives the **arrow**.

44.1.1 Direct successor

Immediate **successor**.

44.2 Predecessor

Object that sends **arrow**.

44.2.1 Direct predecessor

Immediate **predecessor**.

44.3 Degree

Number of **arrows** of **object**.

44.3.1 Indegree

Number of ingoing **arrows**.

44.3.2 Outdegree

Number of outgoing **arrows**.

44.4 Adjacency matrix

Matrix of connection of objects $\{-1, 0, 1\}$.

44.4.0.1 InstanceSigs

Allow adding [type](#) signatures to [type class function](#) instance [declaration](#).

44.5 Strongly connected

If every vertex in a graph is reachable from every other vertex.

It is possible to find all [strongly connected components](#) (and that way also test graph for strong connectivity), in [linear](#) time ($\Theta(V+E)$).

[Binary relation](#) of being [strongly connected](#) is an [equivalence relation](#).

44.5.1 *

Strongly-connected

44.5.2 Strongly connected component

Full [strongly connected](#) subgraph of some graph.

* of a directed graph G is a subgraph that is [strongly connected](#), and has [property](#): no additional edges or vertices from G can be included in the subgraph without breaking its [property](#) of being [strongly connected](#).

44.5.2.1 *

SCC

Strongly connected components

Strongly-connected component

Strongly-connected components

Chapter 45

Linear

Values consumed once or not used.

x^2 consumes x two times.

45.1 *

Linearity

Chapter 46

Stream

* an infinite [sequence](#) that forgets previous [objects](#), and remembers only currently relevant [objects](#).

$E \mid X \rightarrow (X \times A + 1)$, the [set](#) (or [object](#)) of streams on A (final [coalgebra](#) A_* of E).

`cycle` is one of [stream functions](#).

```
a = (cycle [Nothing, Nothing, Just "Fizz"])
b = (cycle [Nothing, Nothing, Nothing, Nothing, Just "Buzz"])
```

Can be:

- indexed, timeless, with current [object](#)
- timed:

```
* [(timescale, event)]
* [(realtime, event)]
```

Has amalgamation with Functional Reactive Programming.

Chapter 47

Bisimulation

When systems have exact external behaviour so for observer they are the same.

[Binary relation](#) between state transition systems that match each other's moves.

47.1 *

Bisimilar

Chapter 48

Syntax tree

Tree of syntactic elements (each [node](#) denotes [construct](#) occurring in the source code) that represent the source code (or human language).

48.1 Abstract syntax tree

"[Abstract](#)" since does not represent every detail of the syntax (ex. parentheses), but rather concentrates on [structure](#) and content.

Widely used in compilers to check the code [structure](#) for accuracy and coherence.

48.1.1 *

AST

48.2 Concrete syntax tree

An ordered, rooted [syntax tree](#) that represents the syntactic [structure](#) of a string according to some [context-free grammar](#).

"Concrete" since (in contrast to "[abstract](#)") - concretely reflects the syntax of the input language.

48.2.1 *

Parse tree
Derivation tree

Chapter 49

Domain specific language

Language design/fitted for particular [domain](#) of [application](#). Mainly should be [Turing incomplete](#), since general-purpose language implies [Turing completeness](#).

49.1 *

Domain-specific language
DSL

49.2 Embedded domain specific language

[DSL](#) used inside outer language.

Two levels of embedding:

- Shallow: [DSL](#) translates into Haskell directly
- Deep: Between [DSL](#) and Haskell there is a [data structure](#) that reflects the [expression tree](#), AKA stores the [syntax tree](#).

49.2.1 *

eDSL

Chapter 50

Tagless-final

Method of embedding **eDSL** in a typed functional host language (Haskell). **Alternative** to the embedding as a (generalized) **algebraic data type**. For parsers of DLS **expressions**: (1/partial) evaluator, compiler, pretty printer, multi-pass optimizer.

* embedding is writing **denotational semantics** for the **DSL** in the host language.

Approach can be used **iff eDSL** is typed. Only well-typed terms become embeddable, and host language can implement also a **eDSL type** system. Approach that **eDSL** code interpretations are **type-preserving**.

One of main pros of * - extensibility: implementation of **DSL** can be used to analyze/evaluate/transform/pretty-print/compile and interpreters can be extended to more passes, optimizations, and new versions of **DSL** while keeping/using/reusing the old versions.

Example fields of **application**: language-integrated queries, non-deterministic & probabilistic programming, delimiter continuation, computability theory, **stream** processing, hardware description languages, generation of specialized numerical kernels, **semantics** of natural language.

Part III

Give definitions

Chapter 51

Identity type

Chapter 52

Constant type

Chapter 53

Gen

Chapter 54

Tensorial strength

Chapter 55

Strong monad

Chapter 56

Weak head normal form

56.1 * WHNF

Chapter 57

Function image

57.1 *

Image

Chapter 58

Invertible

Chapter 59

Invertibility

Chapter 60

Define LANGUAGE pragma options

60.1 ExistentialQuantification

60.2 GADTs

GADT is a generalization over parametric [algebraic data types](#) which allow explicitly denote the [types](#) (type matching) of the [constructors](#) and define [data types](#) using pattern matching on the left side of "data" [statements](#).

60.3 *

GADT
Generalized algebraic data type
First-class phantom data type
Guarded recursive data type
Equality-qualified data type

60.4 GeneralizedNewTypeClasses

60.5 FuncitonalDependencies

Chapter 61

GHC check keys

61.1 -Wno-partial-type-signatures

Supresses [PartialTypeSignatures wildcard infer](#) warning.

Chapter 62

Generalised algebraic data types

LANGUAGE [GADTs](#)

62.1 *

GADT

Chapter 63

Order theory

Investigates in thepht the intuitive notion of [order](#) using [binary relations](#).

63.1 Domain theory

Formalizes approximation and convergense.
Has close [relation](#) to Topology.

63.2 Lattice

[Abstract structure](#) that consists of [partially ordered set](#), [where](#) every two elements have unique supremum and infimum. == * [algebraic structure](#) satisfying certain axiomatic identities.
* [order-theory](#) & [algebraic](#).

63.3 Order

63.3.1 Preorder

$R^X \rightarrow X : \text{Reflexive} \ \& \ \text{Transitive}:$
 aRa
 $aRb, bRc \Rightarrow aRc$

Generalization of [equivalence relations partial orders](#).

* [Antisymmetric](#) \Rightarrow Partial ordering.
* [Symmetric](#) \Rightarrow [Equivalence](#).

63.3.1.1 *

Preordered

63.3.1.2 Total preorder

$\forall a, b : a \leq b \vee b \leq a \Rightarrow \text{Total Preorder}.$

63.3.2 Partial order

A [binary relation](#) must be [reflexive](#), [antisymmetric](#) and [transitive](#).

Partial - not every elements between them need to be comparable.

Good example of $*$ is a genealogical descendancy. Only related people produce [relation](#), not related do not.

63.3.2.1 $*$

Partial orders

Partially ordered set

Partially ordered sets

Poset

Posets

63.4 Partial order

63.5 Total order

Chapter 64

Universal algebra

Studies [algebraic structures](#).

Chapter 65

Relation

65.1 Reflexivity

$$R^{X \rightarrow X}, \forall x \in X : xRx$$

[Order](#) theory: $a \leq a$

* - each element is comparable to itself.

Corresponds to [Identity](#) and [Automorphism](#).

65.1.1 *

Reflexive

Reflexive relation

65.2 Irreflexivity

$$R^{X \rightarrow X}, \forall x \in X : \nexists R(x, x)$$

65.2.1 *

Anti-reflexive

Anti-reflexive relation

Irreflexive

Irreflexive relation

65.3 Transitivity

$$\forall a, b, c \in X, \forall R^{X \rightarrow X} : (aRb \wedge bRc) \Rightarrow aRc$$

* - the start of a chain of [precedence relations](#) must precede the end of the chain.

65.3.1 *

Transitive
Transitive relation

65.4 Symmetry

$$\forall a, b \in X : (aRb \iff bRa)$$

65.4.1 *

Symmetric
Symmetric relation

65.5 Equivalence

Reflexive	Symmetric	Transitive
$\forall x \in X, \exists R : xRx$ $a = a$	$\forall a, b \in X : (aRb \iff bRa)$ $a = b \iff b = a$	$\forall a, b, c \in X, \forall R^{X \rightarrow X} : (aRb \wedge bRc) \Rightarrow aRc$ $a = b, b = c \Rightarrow a = c$

65.5.1 *

Equivalent
Equivalent relation

65.6 Antisymmetry

$\forall a, b \in X : aRb, bRa \Rightarrow a = b \sim aRb, a \neq b \Rightarrow \nexists bRa.$
[Antisymmetry](#) does not say anything about $R(a, a)$.

* - no two different elements precede each other.

65.6.1 *

Antisymmetric
Antisymmetric relation

65.7 Asymmetry

$\forall a, b \in X (aRb \Rightarrow \neg(bRa))$
* \iff [Antisymmetric](#) \wedge [Irreflexive](#).
[Asymmetry](#) \neq "not [symmetric](#)"
[Symmetric](#) \wedge [Asymmetric](#) is only empty relation.

65.7.1 *

Asymmetric

Asymmetric relation

Chapter 66

Cryptomorphism

[Equivalent](#), interconvertable with no loss of information.

66.1 *

Crypomorphic

Chapter 67

Lexically scoped type variables

Enable [lexical scope](#) for [forall](#) quantifier defined [type variables](#)

Implemented in [ScopedTypeVariables](#)

Chapter 68

Abstract data type

Several definitions here, reduce them.

Data type mathematical model, defined by its **semantics** from the user point of view, listing possible values, operations on the data of the **type**, and behaviour of these operations.

* class of **objects** whose logical behaviour is defined by a **set** of values and **set** of operations (analogue to **algebraic structure** in mathematics).

A specification of a **data type** like a **stack** or queue **where** the specification does not contain any implementation details at all, only the operations for that **data type**. This can be thought of as the contract of the **data type**.

68.1 *

AbsDT

Chapter 69

Concrete type

Fully defined [type](#). Non-[polymorphic type](#).

Chapter 70

Functional dependencies

Chapter 71

MonoLocalBinds

Chapter 72

KindSignatures

Chapter 73

ExplicitNamespaces

Chapter 74

Combinator pattern

Chapter 75

Symbolic expression

Nested tree [data structure](#).

Introduced & used in Lisp. Lisp code and data are $*$.

$*$ in Lisp: Atom or [expression](#) of the form $(x \ . \ y)$, x and y are $*$.

Modern abbreviated notation of $*$: $(x \ y)$.

75.1 $*$

S-expression

S-expressions

Sexpression

Sexpressions

Sexp

Sexps

Sexpr

Sexprs

Chapter 76

Polynomial

[Expression](#) consisting of:

- [variables](#)
- coefficients
- addition
- subtraction
- multiplication (including positive integer [variable](#) exponentiation)

[Polynomials](#) form a [ring](#). [Polynomial ring](#).

76.1 *

Polynomials

Chapter 77

Data family

Indexed form of data and newtype definitions.

Chapter 78

Type synonym family

Indexed form of [type](#) synonyms.

Chapter 79

Indexed type family

* additional structure in language that allows ad-hoc overloading of `data types`. AKA are to `types` as `type class` to methods.

Varieties:

- `data family`
- `type` synonym families

Defined by pattern matching the partial `functions` between `types`.

Associates `data types` by `type`-level `function` defined by open-ended collection of valid instances of input `types` and corresponding output `types`.

Normal `type classes` define partial `functions` from `types` to a collection of named values by pattern matching on the input `types`, while `type` families define partial `functions` from `types` to `types` by pattern matching on the input `types`. In fact, in many uses of `type` families there is a single `type class` which logically contains both values and `types` associated with each instance. A `type family` declared inside a `type class` is called an associated `type`.

79.1 *

Type family

Chapter 80

TypeFamilies

Allow use and definition of indexed [type](#) families and data families.

- * are [type](#)-level programming.
- * are overload [data types](#) in the same way that [type classes](#) overload [functions](#).
- * allow handling of [dependent types](#). Before it [Functional dependencies](#) and [GADTs](#) were used to solve that.
- * useful for generic programming, creating highly parametrised interfaces for libraries, and creating interfaces with enhanced static information (much like [dependent types](#)).

Implies: [MonoLocalBinds](#), [KindSignatures](#), [ExplicitNamespaces](#)

Two [types](#) of * are:

Chapter 81

Error

Mistake in the program that can be resolved only by fixing the program.

`error` is a sugar for `undefined`.

Distinct from [Exception](#).

81.1 *

Errors

Chapter 82

Exception

Expected but irregular situation.

Distinct from [Error](#). Also see Exception vs Error

82.1 *

Exceptions

Chapter 83

ConstraintKinds

[Constraints](#) are just handled as [types](#) of a particular [kind](#) ([Constraint](#)). Any [type](#) of the [kind](#) [Constraints](#) can be used as a [constraint](#).

- Anything which is already allowed in code as a [constraint](#) without `*`. Saturated applications to [type classes](#), implicit [parameter](#) and equality [constraints](#).
- [Tuples](#), all of whose component [types](#) have [kind](#) [Constraint](#).

```
type Some a = (Show a, Ord a, Arbitrary a) -- is of kind Constraint.
```

- Anything form of which is not yet known, but the user has declared for it to have [kind](#) [Constraint](#) (for which they need to [import](#) it from `GHC.Exts`):

```
Foo (f :: Type -> Constraint) = forall b. f b => b -> b -- is allowed
-- as well as examples involving type families:
type family Typ a b :: Constraint
type instance Typ Int b = Show b
type instance Typ Bool b = Num b

func :: Typ a b => a -> b -> b
func = ...
```

Chapter 84

Specialisation

Turns [ad hoc polymorphic function](#) into compiled [type](#)-specific implementations.

84.1 *

Specialise
Specialize
Specialization

Chapter 85

Diagram

For [categories](#) C and J , a [diagram](#) of [type](#) J in C is a [covariant functor](#) $D : J \rightarrow C$.

Chapter 86

Category theoretical presheaf

For [categories](#) C and J , a J -[presheaf](#) on C is a [contravariant functor](#) $D : C \rightarrow J$.

Chapter 87

Topological presheaf

If X is a topological space, then the open sets in X form a [partially ordered set](#) $\text{Open}(X)$ under inclusion. Like every [partially ordered set](#), $\text{Open}(X)$ forms a small [category](#) by adding a single [arrow](#) $U \rightarrow V$ if and only if $U \subseteq V$. [Contravariant functors](#) on $\text{Open}(X)$ are called presheaves on X . For instance, by assigning to every open set U the [associative algebra](#) of real-valued continuous functions on U , one obtains a [presheaf](#) of [algebras](#) on X .

Chapter 88

Diagonal functor

The [diagonal functor](#) is defined as the [functor](#) from D to the [functor category](#) D^C which sends each [object](#) in D to the [constant functor](#) at that [object](#).

Chapter 89

Limit functor

For a fixed index [category](#) J , if every [functor](#) $J \rightarrow C$ has a limit (for instance if C is complete), then the [limit functor](#) $C^J \rightarrow C$ assigns to each [functor](#) its limit. The existence of this [functor](#) can be proved by realizing that it is the right-adjoint to the [diagonal functor](#) and invoking the Freyd adjoint [functor](#) theorem. This requires a suitable version of the axiom of choice. Similar remarks [apply](#) to the colimit [functor](#) (which is [covariant](#)).

Chapter 90

Dual vector space

The map which assigns to every vector space its [dual](#) space and to every [linear](#) map its [dual](#) or transpose is a [contravariant functor](#) from the [category](#) of all vector spaces over a fixed field to itself.

Chapter 91

Fundamental group

Consider the [category](#) of pointed topological spaces, i.e. topological spaces with distinguished points. The [objects](#) are pairs (X, x_0) , [where](#) X is a topological space and x_0 is a point in X . A [morphism](#) from (X, x_0) to (Y, y_0) is given by a continuous map $f : X \rightarrow Y$ with $f(x_0) = y_0$.

To every topological space X with distinguished point x_0 , one can define the [fundamental group](#) based at x_0 , denoted $\pi_1(X, x_0)$. This is the [group](#) of [homotopy](#) classes of loops based at x_0 . If $f : X \rightarrow Y$ is a [morphism](#) of pointed spaces, then every loop in X with base point x_0 can be [composed](#) with f to yield a loop in Y with base point y_0 . This [operation](#) is compatible with the [homotopy equivalence relation](#) and the [composition](#) of loops, and we get a [group homomorphism](#) from $\pi_1(X, x_0)$ to $\pi_1(Y, y_0)$. We thus obtain a [functor](#) from the [category](#) of pointed topological spaces to the [category](#) of [groups](#).

In the [category](#) of topological spaces (without distinguished point), one considers [homotopy](#) classes of generic curves, but they cannot be [composed](#) unless they share an endpoint. Thus one has the fundamental groupoid instead of the [fundamental group](#), and this construction is [functorial](#).

Chapter 92

Algebra of continuous function

A [contravariant functor](#) from the [category](#) of topological spaces (with continuous maps as [morphisms](#)) to the [category](#) of real [associative algebras](#) is given by assigning to every topological space X the [algebra](#) $C(X)$ of all real-valued continuous [functions](#) on that space. Every continuous map $f : X \rightarrow Y$ induces an [algebra homomorphism](#) $C(f) : C(Y) \rightarrow C(X)$ by the rule $C(f)(\varphi) = \varphi \circ f$ for every φ in $C(Y)$.

Chapter 93

Tangent and cotangent bundle

The map which sends every differentiable manifold to its tangent bundle and every smooth map to its derivative is a [covariant functor](#) from the [category](#) of differentiable manifolds to the [category](#) of vector bundles.

Doing this constructions pointwise gives the tangent space, a [covariant functor](#) from the [category](#) of pointed differentiable manifolds to the [category](#) of real vector spaces. Likewise, cotangent space is a [contravariant functor](#), essentially the [composition](#) of the tangent space with the [dual](#) space above.

Chapter 94

Group action / representation

Every [group](#) G can be considered as a [category](#) with a single [object](#) whose [morphisms](#) are the elements of G . A [functor](#) from G to [Set](#) is then [nothing](#) but a [group](#) action of G on a particular [set](#), i.e. a G -[set](#). Likewise, a [functor](#) from G to the [category](#) of vector spaces, Vect_K , is a [linear](#) representation of G . In general, a [functor](#) $G \rightarrow C$ can be considered as an "action" of G on an [object](#) in the [category](#) C . If C is a [group](#), then this action is a [group homomorphism](#).

Chapter 95

Lie algebra

Assigning to every real (complex) Lie [group](#) its real (complex) [Lie algebra](#) defines a [functor](#).

Chapter 96

Tensor product

If \mathcal{C} denotes the [category](#) of vector spaces over a fixed field, with [linear](#) maps as [morphisms](#), then the [tensor product](#) $V \otimes W$ defines a [functor](#) $\mathcal{C} \times \mathcal{C} \rightarrow \mathcal{C}$ which is [covariant](#) in both arguments.

Chapter 97

Forgetful functor

The functor $U : \mathbf{Grp} \rightarrow \mathbf{Set}$ which maps a group to its underlying set and a group homomorphism to its underlying function of sets is a functor.[8] Functors like these, which "forget" some structure, are termed forgetful functors. Another example is the functor $\mathbf{Rng} \rightarrow \mathbf{Ab}$ which maps a ring to its underlying additive abelian group. Morphisms in \mathbf{Rng} (ring homomorphisms) become morphisms in \mathbf{Ab} (abelian group homomorphisms).

Chapter 98

Free functor

Going in the opposite direction of [forgetful functors](#) are free [functors](#). The free functor $F : \mathbf{Set} \rightarrow \mathbf{Grp}$ sends every [set](#) X to the free [group](#) generated by X . [Functions](#) get mapped to [group](#) homomorphisms between free [groups](#). Free constructions exist for many [categories](#) based on structured [sets](#). See [free object](#).

Chapter 99

Homomorphism group

To every pair A, B of abelian groups one can assign the abelian group $\text{Hom}(A, B)$ consisting of all group homomorphisms from A to B . This is a functor which is contravariant in the first and covariant in the second argument, i.e. it is a functor $\text{Abop} \times \text{Ab} \rightarrow \text{Ab}$ (where Ab denotes the category of abelian groups with group homomorphisms). If $f : A_1 \rightarrow A_2$ and $g : B_1 \rightarrow B_2$ are morphisms in Ab , then the group homomorphism $\text{Hom}(f, g) : \text{Hom}(A_2, B_1) \rightarrow \text{Hom}(A_1, B_2)$ is given by $g \circ f$. See Hom functor.

Chapter 100

Representable functor

We can generalize the previous example to any [category](#) C . To every pair X, Y of [objects](#) in C one can assign the [set](#) $\text{Hom}(X, Y)$ of [morphisms](#) from X to Y . This defines a [functor](#) to [Set](#) which is [contravariant](#) in the first [argument](#) and [covariant](#) in the second, i.e. it is a [functor](#) $C^{\text{op}} \times C \rightarrow \text{Set}$. If $f : X_1 \rightarrow X_2$ and $g : Y_1 \rightarrow Y_2$ are [morphisms](#) in C , then the [group homomorphism](#) $\text{Hom}(f, g) : \text{Hom}(X_2, Y_1) \rightarrow \text{Hom}(X_1, Y_2)$ is given by $g \circ f$.

[Functors](#) like these are called representable [functors](#). An important goal in many settings is to determine whether a given [functor](#) is representable.

Chapter 101

Corecursion

Chapter 102

Coinduction

proper definition

* [dual](#) to induction.
Generalises to [corecursion](#).

Chapter 103

Initial algebra of an endofunctor

Chapter 104

Terminal coalgebra for an endofunctor

Part IV

Citations

"One of the finer points of the Haskell community has been its propensity for recognizing [abstract](#) patterns in code which have well-defined, lawful representations in mathematics." (Chris Allen, Julie Moronuki - "Haskell Programming from First Principles" (2017))

Part V

Good code

Chapter 105

Good: Type aliasing

Use [data type](#) aliases to deferentiate logic of values.

Chapter 106

Good: Type wideness

Wider the [type](#) the more it is [polymorphic](#), means it has broader [application](#) and fits more [types](#).

The more constrained system has more usefulness.

Unconstrained means most flexible, but also most useless.

Chapter 107

Good: Print

```
print :: Show a => a -> IO ()  
print a = putStrLn (show a)
```

Chapter 108

Good: Fold

`foldr spine recursion` intermediated by the folding. Can terminate at any point.

`foldl spine recursion` is unconditional, then folding starts. Unconditionally recurses across the whole `spine`, if it infinite - infinitely.

Chapter 109

Good: Computation model

Model the [domain](#) and [types](#) before thinking about how to write computations.

Chapter 110

Good: Make bottoms only local

Chapter 111

Good: Newtype wrap is ideally transparent for compiler and does not change performance

Chapter 112

Good: Instances of types/type classes must go with code you write

Chapter 113

**Good: Functions can be
abstracted as arguments**

Chapter 114

**Good: Infix operators can be
bind to arguments**

Chapter 115

Good: Arbitrary

Product types can be tested as a product of random generators.

Sum types require to implement generators with separate constructors, and picking one of them, use oneof or frequency to pick generators.

Chapter 116

Good: Principle of Separation of concerns

Chapter 117

Good: Function composition

In Haskell inline [composition](#) requires:

```
h.g.f $ i
```

[Function application](#) has a higher [priority](#) than [composition](#). That is why parentheses over [argument](#) are needed.

This [precedence](#) allows idiomatically [compose partially applied functions](#).

But it is a way better then:

```
h (g (f i))
```

Chapter 118

Good: Point-free

Use `Tacit` very carefully - it hides `types` and harder to change code `where` it is used.
Use just enough `Tacit` to communicate a bit better. Mostly only partial `point-free` communicates better.

118.1 Good: Point-free is great in multi-dimensions

BigData and OLAP analysis.

Chapter 119

Good: Functor application

[Function application](#) on n levels beneath:

```
(fmap . fmap) function twoLevelStructure
```

How `fmap . fmap` [typechecks](#):

```
(.)      :: (b -> c) -> (a -> b) -> a -> c
fmap     :: Functor f => (m -> n) -> f m -> f n
fmap     :: Functor g => (x -> y) -> g x -> g y

fmap . fmap :: (Functor f, Functor g)
            => ((g x -> g y) -> f . g x -> f . g y)
            -> (( x -> y) -> g x -> g y)
            -> ( x -> y) -> f . g x -> f . g y
fmap . fmap :: (x -> y) -> f . g x -> f . g y
```


Chapter 120

Good: Parameter order

In [functions parameter order](#) is important.

It is best to use first the most reusable [parameters](#).

And as last one the one that can be the most [variable](#), that is important to chain.

Chapter 121

Good: Applicative monoid

There can be more than one valid [Monoid](#) for a [data type](#). &&

There can be more than one valid [Applicative](#) instance for a [data type](#). ->

There can be different [Applicatives](#) with different [Monoid](#) implementations.

Chapter 122

Good: Creative process

- 122.1 Pick philosophy principles one to three the more - the harder the implementation
- 122.2 Draw the most blurred representation
- 122.3 Deduce **abstractions** and write remotely what they are
- 122.4 Model of computation
 - 122.4.1 Model the **domain**
 - 122.4.2 Model the **types**
 - 122.4.3 Think how to write computations
- 122.5 Create

Chapter 123

«<Good: About operators (<\$)
(**>) (<*) (>>) »>

[Where](#) character is not present - discard the according processing of a [parameter](#).
(>>) is an [exception](#), it does the reverse. ignores the first [parameter](#).

Chapter 124

Good: About functions like `{mapM, sequence}_`

Trailing `_` means ignoring the result.

Chapter 125

Good: Guideliles

125.1 Wiki.haskell

125.1.1 Documentation

125.1.1.1 Comments write in [application](#) terms, not technical.

125.1.1.2 Tell what code needs to do not how it does.

125.1.2 Haddock

125.1.2.1 Put haddock comments to ever exposed [data type](#) and [function](#).

125.1.2.2 Haddock header

```
{- |  
Module      : <File name or $Header$ to be replaced automatically>  
Description  : <optional short text displayed on contents page>  
Copyright    : (c) <Authors or Affiliations>  
License      : <license>  
  
Maintainer   : <email>  
Stability    : unstable | experimental | provisional | stable | frozen  
Portability  : portable | non-portable (<reason>  
  
<module description starting at first column>  
-}
```

125.1.3 Code

125.1.3.1 Try to stay closer to portable (Haskell98) code

125.1.3.2 Try make lines no longer 80 chars

125.1.3.3 Last char in file should be newline

125.1.3.4 Symbolic [infix](#) identifiers is only library writer right

125.1.3.5 Every [function](#) does one thing.

Chapter 126

Good: Use Typed holes to progress the code

[Typed holes](#) help build code in complex situations.

Chapter 127

Good: Haskell allows infinite terms but not infinite types

That is why infinite [types](#) throw infinite [type error](#).

Chapter 128

Good: Use type synonyms to differ the information

Even if there is `types` - define `type` synonyms. They are free.

That distinction with synonyms, would allow `TypeSynonymInstances`, which would allow to create a different `type class` instances and behaviour for different information.

Chapter 129

«<Good: Control.**Monad.Error**
-> Control.**Monad.Except**»>

Chapter 130

Good: Monad OR Applicative

130.0.1 Start writing **monad** using 'return', 'ap', '**liftM**', '**liftM2**', '»' instead of 'do', '»='

If you wrote code and really needed only those - move that code to [Applicative](#).

```
return -> pure
ap -> <*>
liftM -> liftA -> <$>
>> -> *>
```

130.0.2 Basic **case** when [Applicative](#) can be used

Can be rewritten in [Applicative](#):

```
func = do
  a <- f
  b <- g
pure (a, b)
```

Can't be rewritten in [Applicative](#):

```
somethingdoSomething' n = do
  a <- f n
  b <- g a
pure (a, b)
```

(f n) creates **monadic structure**, **binds** ot to *a* wich is consumed then by g.

130.0.3 [Applicative](#) block vs **Monad** block

With [Type Applicative](#) every condition fails/succceeds independently. It needs a boilerplate **data constructor**/value pattern matching code to work. And code you can write only for so many cases and **types**, so boilerplate can not be so flexible as **Monad** that allows **polymorphism**.

With [Type Monad](#) computation can return value that dependent from the previous computation result. So abort or dependent processing can happen.

Chapter 131

Good: Haskell Package Versioning Policy

Version policy and dependency management.

[width=.9]Good_{code}/pvp – decision – tree₂019 – 06 – 17₁5 – 49 – 21

131.1 *

PVP

Good: PVP

Chapter 132

Good: Linear type

Linear types are great to control/minimize resource usage.

Chapter 133

Good: Exception vs Error

Many languages and Haskell have it all mixup. Here is table showing what belongs to one or other in standard libraries:

Exception	Prelude.catch, Control. Exception .catch, Control. Exception .try, IOError, Control. Monad . Error
Error	error , assert, Control. Exception .catch, Debug.Trace.trace

Chapter 134

Good: Let vs. Where

`let ... in ...` is a separate [expression](#). In contrast, `where` is [bound](#) to a surrounding syntactic [construct](#) (namespace).

Chapter 135

Good: RankNTypes

Can powerfully synergyze with [ScopedTypeVariables](#).

Chapter 136

Good: Orphan type instance

Practice to address orphan instances:

Does [type class](#) or [type](#) defined by you:

Type class	Type	Recommendation
✓	✓	{ Type , instance} in the same module { Typeclass & instance} in the same module {Define newtype wrap, its instances} in the same module

Chapter 137

Good: Smart constructor

Only proper smart [constructors](#) should be exported. Do not export [data type constructor](#), only a [type](#).

Chapter 138

Good: Thin category

In * all [morphisms](#) are [epimorphisms](#) and [monomorphisms](#).

Chapter 139

Good: Recursion

Writing/thinking about [recursion](#):

- a.* Find the base cases, on input of which the answer can be provided right away. There is mostly one [base case](#), but sometimes there can be several of them. Typical base cases are: [zero](#), the empty [list](#), the empty tree, null, etc.
- b.* Do inductive [case](#). The [recursive](#) invocation. The [argument](#) of a [recursive](#) call needs to be smaller than the current [argument](#). So it would be gradually closer to the [base case](#). The idea is that processes eventually hits the [base case](#).

Simple functional [application](#) is used in the [recursion](#).

Assume that the [functions](#) would return the right result.

Chapter 140

Good: Monoid

<>:

[Sets](#) - union.

Maps - left-biased union.

Number - `Sum`, `Product` form separate [monoid categories](#).

Chapter 141

Good: Free monad

The main [case](#) of usage of Free [monads](#) in Haskell:

Start implementation of the [monad](#) from a Free [monad](#), drafting the base [monadic](#) operations, then add custom operations.

Gradually build on top of Free [monad](#) and try to find homomorphisms from [monad](#) to [objects](#), and if only [objects](#) are needed - get rid of the free [monad](#).

Chapter 142

Good: Use mostly where clauses

Chapter 143

**Good: Where clause is in a scope
with function parameters**

Chapter 144

Good: Strong preference towards pattern matching over {head, tail, etc.} functions

head and tail and alike [functions](#) are often partial ([unsafe](#)) functions.

Chapter 145

Good: Patternmatching is possible on monadic bind in do

Example:

```
instance (Monad m) => Functor (StateT s m) where
  fmap f m = StateT $ \s -> do
    (x, s') <- runStateT m s -- Here is a pattern matching bind
    return (f x, s')
```

Chapter 146

Good: Applicative vs Monad

Giving not Monad but Applicative requirement allows parallel computation, but if there should be a chaining of the intermediate state - it must be [monadic](#).

Chapter 147

Good: StateT, ReaderT, WriterT

Reader trait: `(r ->)`.

Writer trait: `(a, w)`.

State trait is combination of both:

```
newtype StateT s m a =  
  StateT { runStateT :: s -> m (a, s) }
```

```
newtype ReaderT r m a =  
  ReaderT { runReaderT :: r -> m a }
```

```
newtype WriterT w m a =  
  WriterT { runWriterT :: m (a, w) }
```

State trait fully replaces writer.

Chapter 148

Good: Working with MonadTrans and lift

From the `lift . pure = pure` follows that `MonadTrans` [type](#) can have a `pure` defined with `lift`.

Stacking of `MonadTrans` [monads](#) can result in a lot of chained `lift` and `unwraps`. There is many ways to cope with that but the most robust and common is to [abstract](#) representation with `newtype` on the `Monad` [stack](#). This can reduce caining or remove the manual [lifting](#) withing the [Monad](#).

For perfect combination for contributors to be able to extend the code - keep the `Internal` [module](#) that has a raw representation.

Chapter 149

Good: Don't mix Where and Let

`let` and `where` create a [recursive set](#) of definitions with can explode, don't mix them together in code.

Chapter 150

Good: Where vs. Let

Let is self-recursive lazy pattern. It is checked and errors only at execution time. **Binds** only inside **expression** it is binded to.

Where is a part of definition, scoped over definition implemetations and **guards**, not self-recursive.

Chapter 151

Good: The proper nature algorithm that models behaviour of many objects is computation heavy

God does not care about our mathematical difficulties. He integrates empirically.

One who is found of mathematical meaning loves to [apply](#) it. But if we implement the "real" algorithms behind nature processes, we face the need to go through the computations of laws of all particles.

Computation of nature is always a middle way between ideal theory behaviour and computation simplification.

Chapter 152

Good: In Haskell parameters bound by lambda declaration instantiate to only one concrete type

Because of [let-bound polymorphism](#):

This is illegal in Haskell:

```
foo :: (Int, Char)
foo = (\f -> (f 1, f 'a')) id
```

Lambda-bound function (i.e., one passed as [argument](#) to another [function](#)) cannot be instantiated in two different ways, if there is a [let-bound polymorphism](#).

Chapter 153

Good: Instance is a good structure to draw a type line

Instances for [data type](#) can differentiate by [constraints](#) & [types](#) of arguments. So instance can preserve [type](#) boundary, and [data type declaration](#) can stay very [polymorphic](#). If the need to extend the [type](#) boundaries arrive - the instances may extend, or new instances are created, while used [data type](#) still the same and unchanged.

Chapter 154

Good: MTL vs. Transformers

Default of `mtl`.

`Transformers` is Haskell-98, doesn't have functional dependencies, lacks the `monad` classes, has manual `lift` of operations to the composite `monad`.

MTL extends `transformers`, providing more instances, features and possibilities, may include `alternative` packages features as `mtl-tf`.

Part VI

Bad code

Chapter 155

Bad pragma

155.1 Bad: Dangerous **LANGUAGE pragma** option

- **DatatypeContexts**
- **OverlappingInstances**
- **IncoherentInstances**
- **ImpredicativeTypes**
- **AllowAmbiguousTypes**
- **UndecidableInstances** - often

Part VII

Useful **functions** to remember

Chapter 156

Prelude

```
enumFromTo
enumFromThenTo
reverse
show :: Show a => a -> String
flip
sequence - Evaluate each monadic action in the structure from left to right, and collect the results
:sprint - show variables to see what has been evaluated already.
minBound - smaller bound
maxBound - larger bound
cycle :: [a] -> [a] - indefinitely cycle s list
repeat - indefinit lis from value
elemIndex e l - return first index, returns Maybe
fromMaybe (default if Nothing) e :: Maybe a -> a
lookup :: Eq a => a -> [(a, b)] -> Maybe b
```

156.1 Ord

```
compare
```

156.2 Calc

div - always makes rounding down, to infinity
divMod - returns a [tuple](#) containing the result of integral division and modulo

156.3 [List](#) operations

```
concat - [ [a] ] -> [a]
elem x xs - is element a part of a list
zip :: [a] -> [b] -> [(a, b)] - zips two lists together. Zip stops when one list runs out.
zipWith :: (a -> b -> c) -> [a] -> [b] -> [c] - do the action on corresponding elements of list a
```

Chapter 157

Data.List

`intersperse :: a -> [a] -> [a]` - gets the value and incerts it between values in array
`nub` - remove duplicates from the list

Chapter 158

Data.Char

```
ord (Char -> Int)
chr (Int -> Char)
isUpper (Char -> Bool)
toUpper (Char -> Char)
```

Chapter 159

QuickCheck

```
quickCheck :: Testable prop => prop -> IO ()  
quickCheck . verbose - run verbose mode
```

Part VIII

Tools

Chapter 160

ghc-pkg

[List](#) installed packages:

```
ghc-pkg list
```

Chapter 161

Search over the Haskell packages code: Codesearch from Aelve

<https://codesearch.aelve.com/>

Chapter 162

Integration of NixOS/Nix with Haskell IDE Engine (HIE) and Emacs (Spacemacs)

162.1 1. Install the Cachix: <https://github.com/cachix/cachix>

162.2 2. Installation of HIE: <https://github.com/infinisil/all-hies/#cached-builds>

162.2.1 2.1. Provide cached builds

```
cachix use all-hies
```

162.2.2 2.2.a. Installation on NixOS distribution:

```
{ config, pkgs, ... }:
```

```
let
```

```
    all-hies = import (fetchTarball "https://github.com/infinisil/all-hies/tarball/master") {};
```

```
in {
```

```
    environment.systemPackages = with pkgs; [
```

```
        (all-hies.selection { selector = p: { inherit (p) ghc865 ghc864; }; })
```

```
    ];
```

```
}
```

Insert your GHC versions.

Switch to new configuration:

```
sudo -i nixos-rebuild switch
```

162.2.3 2.2.b. Installation with Nix package manager:

```
nix-env -iA selection --arg selector 'p: { inherit (p) ghc865 ghc864; }' -f 'https://github.com/i
```

Insert your GHC versions.

162.3 3. Emacs (Spacemacs) configuration:

```
dotspacemacs-configuration-layers
'(

  auto-completion

  (lsp :variables
    default-nix-wrapper (lambda (args)
      (append
        (append (list "nix-shell" "-I" "." "--command" )
          (list (mapconcat 'identity args " ")))
        )
      (list (nix-current-sandbox))
      )
    )

    lsp-haskell-process-wrapper-function default-nix-wrapper
  )

  (haskell :variables
    haskell-enable-hindent t
    haskell-completion-backend 'lsp
    haskell-process-type 'cabal-new-repl
  )

)

dotspacemacs-additional-packages '(
  direnv
  nix-sandbox
)

(defun dotspacemacs/user-config ()

  (add-hook 'haskell-mode-hook 'direnv-update-environment) ;; If direnv configured

)
```

Where:

auto-completion configures YASnippet.

nix-sandbox (<https://github.com/travisbhartwell/nix-emacs>) has a great helper [functions](#). Using `nix-current-sandbox` function in `default-nix-wrapper` that used to properly configure `lsp-haskell-process-wrapper-function`.

Configuration of the `lsp-haskell-process-wrapper-function` `default-nix-wrapper` is a key for HIE to work in `nix-shell`

Inside `nix-shell` the `haskell-process-type` `'cabal-new-repl` is required.

Configuration was reassembled from: <https://github.com/emacs-lsp/lsp-haskell/blob/8f2dbb6e827b1adce6360c56f795f29ecff1d7f6/lsp-haskell.el#L57> & its authors config: [\[\[https://github.com/sevanspowell/dotfiles/blob/master.spacemacs\]\]](https://github.com/sevanspowell/dotfiles/blob/master/spacemacs)

Refresh Emacs.

162.4 4. Open the Haskell file from a project

Open system monitor, observe the process of environment establishing, packages loading & compiling.

162.5 5. Be pleased writing code

Now, the powers of the Haskell, Nix & Emacs combined. It's fully in your hands now. Be cautious - you can change the world.

162.6 6. (optional) Debugging

a. If receiving sort-of:

```
readCreateProcess : cabal-helper-wrapper failure
```

HIE tries to run `cabal` operations like on the non-Nix system. So it is a problem with detection of `nix-shell` environment, running inside it.

- a.* If HIE keeps getting ready, failing & restarting - check that the projects `ghc --version` is declared in your `all-hie` NixOS configuration.

Chapter 163

Debugger

Provides:

- [set](#) a breakpoints
- observe step-by-step [evaluation](#)
- tracing mode

Breakpoints

```
:break 2
:show breaks
:delete 0
:continue
```

Step-by-step

```
:step main
```

[List](#) information at the breakpoint

```
:list
```

What been evaluated already

```
:sprint name
```

Chapter 164

GHCID

Commands to run the compile/check loop:

cabal > 3.0 command:

```
ghcid --command='cabal v2-repl --repl-options=-fno-code --repl-options=-fno-break-on-exception --g
```

cabal < 3.0 command:

```
ghcid --command='cabal new-repl --ghc-options=-fno-code --ghc-options=-fno-break-on-exception --g
```

nix-shell cabal > 3.0 command:

```
nix-shell --command 'ghcid --command="cabal v2-repl --repl-options=-fno-code --repl-options=-fno-
```

nix-shell cabal < 3.0 command:

```
nix-shell --command 'ghcid --command="cabal new-repl --ghc-options=-fno-code --ghc-options=-fno-b
```

Part IX

Libs

Chapter 165

Exceptions

- 165.1 **Exceptions** - optionally **pure** extensible **exceptions** that are compatible with the mtl
- 165.2 **Safe-exceptions** - safe, simple API **equivalent** to the underlying implementation in terms of power, encourages best practices minimizing the chances of getting the **exception** handling wrong.
- 165.3 **Enclosed-exceptions** - capture **exceptions** from the enclosed computation, while reacting to asynchronous **exceptions** aimed at the calling thread.

Chapter 166

Memory management

166.1 membrain - [type](#)-safe memory units

Chapter 167

Parsers - megaparsec

Chapter 168

CLIs - optparse-[applicative](#)

Chapter 169

HTML - Lucid

Chapter 170

Web applications - Servant

Chapter 171

IO libraries

- 171.1 Conduit - practical, monolythic, guarantees termination return
- 171.2 Pipes + Pipes Parse - modular, more primitive, theoretically driven

Chapter 172

JSON - aeson

Chapter 173

Backpack

On 1-st compilation - `*` analyzes the [abstract](#) signatures without loading side modules, doing the [type check](#) with assumption that modules provide right [type](#) signatures, the process does not emit any [binary](#) code and stores the intermediate code in a special form that allows flexibly connect modules provided. Which allows later to compile project with particular instantiations of the modules. Major work of this process being done by internal Cabal `* support` and `* system` that modifies the intermediate code to fit the [module](#).

Part X

Drafts

Chapter 174

Exception handling

Exception must include all **context** information that may be useful.

Store information in a form for further probable deeper automatic diagnostic.

Sensitive data/dummies for it - can be useful during development.

Sensitive data should be stripped from a program logging & **exceptions**.

Exception system should be extendable, data storage & representation should be easily extendable.

Exception system should allow easy exhaustive checking of **errors**, since the different **errors** can happen.

Exception system should be automatically well-documented and transparent.

Exception system should have controllable breaking changes downstream.

Exception system should allow complex composite (**sets**) **exceptions**.

Exception system should be lightweight on the **type** signatures of other **functions**.

Exception system should automate the collection of **context** for a **exception**.

Exception system should have **properties** and according **functions** for particular **types** of **errors**.

String is simple and convenient to throw **exception**, but really a mistake because it the most cumbersome choice:

- Any **Exception** instance can be converted to a **String** with **either** **show** or **displayException**.
- Does not include key debugging information in the **error** message.
- Does not allow developer to access/manage the **Exception** information.
- **Exception** messages need to be constructed ahead of time, it can not be internationalized, converted to some data/file format.
- **Exception** can have a sensitive information that can be useful for developer during work, but should not be logged/shown to end-user. Stripping it from **Strings** in the changing project is a hard task.
- Impossible to rely on this representation for further/deeper inspection.
- Impossible to have exhaustive checking - no knowledge no check, no warning if some cases are not handled.

Universal [exception type](#):

- Able to inspect every possible [error case](#) with [pattern match](#).
- Self-documenting. Shows the hierarchical system of all [exceptions](#).
- Transparent. Ability to discern in current situation what [exceptions](#) can happen
- New [exception constructor](#) causes breaking change to downstream.
- Wrongly implies completeness. Untreated [Errors](#) can happen, different [exception](#) can arrive from the outside code.

Sum [type](#) must be separate, and [product type structure](#) over it.

Separate [exception type](#) of

Individual [exception types](#):

- Writing & seing & working with exactly what will go wrong because there is only one possible [error](#) for this [type](#) of [exception](#). [Pattern match](#) happens only onconditions, [constructors](#) that should happen.
- Knowledge what exactly goes wrong allows wide usage of [Either](#).
- It is hard to handle complex [exceptions](#) in the unitary system. Real wrorld can return not a particular [case](#), but a [set](#) of cases {[object](#) not found, path is unreachable, access is denied}.
- [Type](#) signatures grow, and even can become complex, since every [case](#) of [exception](#) has its own [type](#).
- Impure [throw](#) that users can/should use for your code must account for all your [exception types](#).

[Abstract exception type](#):

[Exception type](#) entirely opaque and inspectable only by accessor [functions](#).

- Updating the internals without breaking the API
- Semi-automates the [context](#) of [exception](#) with passing it to accessors.
- Predicates can be [applied](#) to more than one [constructor](#). Which are [properties](#) that allows to make complex [exceptions](#) much easier to handle.
- Not self-documenting.

- Possible options by design are hidden from the downstream, documentation must be kept.
- When you change the [exception](#) handling/throwing [errors](#) it does not show to the downstream.

Composit approach:

Provide the [set](#) of [constructors](#) and also a [set](#) of predicates and [set](#) of accessors.

Use [pattern synonyms](#) to provide a documented accessor [set](#) without exposing internal [data type](#).

In GHC 8.8 the change was made:

The fail method of [Monad](#) has been removed in favor of the method of the same name in the MonadFail class.

MonadFail(..) is now exported from the Prelude and Control.[Monad](#) modules.

The MonadFailDesugaring language extension is now deprecated, as its effects are always enabled.

So:

```
import           Control.Monad.Fail
...
class MonadFail m => MonadFile m
...
-- use error instead of fail
Nothing         -> error ("Message " <> show x)
```

Chapter 175

Constraints

Very strong Haskell [type](#) system makes possible to work with code from the top down, an [axiomatic semantics](#) approach, from [constraints](#) into [types](#).

- Helps to form the [type level](#) code (aka [join](#) points of the code).
- Uses the piling up of [constraints](#)/[types](#) information. At some point pick and satisfy [constraints](#), can be done one at a time.
- Provides hints through [type level](#) formulation for [term level](#) calculations, does not formulate the [term level](#).
- Tedious method (a lot of boilerplate and rewriting it) but pretty simple and relaxing.
- [Set](#) of [constraints](#).
- When it is needed or convenient, single [constraint](#) gets a little more realistically concrete/abstracted.

Main [type](#) detail annotation thread can happen in [main](#) or special wrapper [function](#), localization is inside [functions](#).

a. Rest of [constraints set](#) shifts to source [type](#).

3.a. For the class handled or known how to handle - write a [base case](#) instance description.

```
instance (Monad m) => MonadReader r (ReaderT r m)
```

3.b. For others write [recursive](#) instance descriptions:

All other unsolved [constraints](#) move into the source [polymorphic variable](#).

```
instance (MonadError e m) => MonadError e (ReaderT r m)
instance (MonadState s m) => MonadState s (ReaderT r m)
```

- a.* Repeat from 1 until considered done.
- b.* Code condensed into terse form.

`MonadError constraints` is `IOException`, not for the `String`. `IOException` vs `String`.

Reverse pluck `MonadReader constraint` with `runReader` on the `object`.

`MonadState - StateT`

Chapter 176

Monad transformers and their type classes

Chapter 177

Layering **monad** transformers

Different layering of the same **monad** transformers is functionality is the same, but the form is different. Surrounding handling **functions** would need to be different.

Chapter 178

Hoogle

178.1 Search

Text search ([case](#) insensitive):

- `a`
- `map`
- `con map`

[Type](#) search:

- `:: a`
- `:: a -> a`

Text & [type](#):

```
=id a -> a=
```

178.2 [Scope](#)

178.2.1 Default

[Scope](#) is [Haskell Platform](#) (and [Haskell keywords](#)).

All [Hackage](#) packages are available to search with:

178.2.2 [Hierarchical module name](#) system (from big letter):

- `fold +Data.Map` finds results in the `Data.Map` [module](#)

- `file -System` excludes results from modules such as `System.IO`, `System.FilePath.Windows` and `Distribution.System`

178.2.3 Packages (lower **case**):

- `mode +platform`
- `mode +cmdargs` (only)
- `mode +platform +cmdargs`
- `file -base` (Haskell Platform, excluding the "base" package)

Chapter 179

ST-Trick monad

ST is like a [lexical scope](https://wiki.haskell.org/Lexical_scope), where all the [variables](https://wiki.haskell.org/Variables)/state disappear when the [function](https://wiki.haskell.org/Function) returns
[https://wiki.haskell.ohttps://www.schoolofhaskell.com/school/to-infinity-and-beyond/older-but-still-interesting/deamortized-strg/Monad/ST](https://wiki.haskell.org/https://www.schoolofhaskell.com/school/to-infinity-and-beyond/older-but-still-interesting/deamortized-strg/Monad/ST)
<https://dev.to/jvanbruegge/what-the-heck-is-polymorphism-nmh>

179.1 *

ST-Trick

Chapter 180

Either

Allows to separate and preserve information about happened, ex. [error](#) handling.

180.1 *

Either data type

Chapter 181

Inverse

- a.* [Inverse function](#)
- b.* In logic: $P \rightarrow Q \Rightarrow \neg P \rightarrow \neg Q$, & same for [category duality](#).
- c.* For [operation](#): element that allows reversing [operation](#), having an element that with the [dual](#) produces the [identity](#) element.
- d.* See [Inversion](#).

Chapter 182

Inversion

- a.* Is a [permutation where](#) two elements are out of [order](#).
- b.* See [Inverse](#)

Chapter 183

Inverse function

$$f_{x \rightarrow y} \circ (f_{x \rightarrow y})^{-1} = 1_x$$

* \iff function is bijective.

Otherwise - partial inverse

Chapter 184

Inverse morphism

For $f : x \rightarrow y$:

$\exists g : g \circ f = 1^x$ - g is left [inverse](#) of f .

$\exists g : f \circ g = 1^y$ - g is right [inverse](#) of f .

Chapter 185

Partial inverse

* when [function](#) is now [bijective](#). When [bijective](#) see [inverse function](#).

Chapter 186

PatternSynonyms

Enables [pattern synonym declaration](#), which always begins with the `pattern` word.
Allows to [abstract](#)-away the [structures](#) of pattern matching.

186.1 *

Pattern synonym
Pattern synonyms

Chapter 187

GHC debug keys

187.1 -ddump-ds

Dump desugarer output.

187.1.1 *

Desugar
GHC desugar

Chapter 188

GHC optimize keys

188.1 -foptimal-applicative-do

$O(n^3)$

Always finds optimal [reduction](#) into `<*>` for [ApplicativeDo](#) do notation.

Chapter 189

Computational trinitarianism

Taken from: <https://ncatlab.org/nlab/show/computational+trinitarianism>

Under the [statements](#):

- [propositions](#) as [types](#)
- programs as proofs
- [relation](#) between [type](#) theory and [category](#) theory

the following notions are [equivalent](#):

== [proposition](#) proof (Logic)

== generalized element of an [object](#) ([Category](#) theory)

== typed program with output ([Type](#) theory & Computer science)

Table 189.1: [Computational trinitarianism](#)

Logic	Category theory	Type theory
true	terminal object / (-2)-truncated object	h-level 0-type
false	initial object	empty type
proposition	(-1)-truncated object	h-proposition
proof	generalized element	program
cut rule	composition of classifying morphisms / pullback of display maps	substitution
cut elimination for implication	counit for hom-tensor adjunction	beta reduction
introduction rule for implication	unit for hom-tensor adjunction	eta conversion
logical conjunction	product	product type
disjunction	coproduct ((-1)-truncation of)	sum type (b)
implication	internal hom	function type
negation	internal hom into initial object	function type
universal quantification	dependent product	dependent p
existential quantification	dependent sum ((-1)-truncation of)	dependent s
equivalence	path space object	identity type
equivalence class	quotient	quotient typ

Continued from previous page		
Logic	Category theory	Type theory
induction	colimit	inductive type
higher induction	higher colimit	higher inductive type
completely presented set	discrete object/0-truncated object	h-level 2-type
set	internal 0-groupoid	Bishop set/set
universe	object classifier	type of types
modality	closure operator, (idempotent) monad	modal type theory
linear logic	(symmetric, closed) monoidal category	linear type theory
proof net	string diagram	quantum circuit
(absence of) contraction rule	(absence of) diagonal	no-cloning theorem
	synthetic mathematics	domain specification

189.1 *

Trinitarism

Chapter 190

Techniques functional programming deals with the state

190.1 Minimizing

Do not rely on state, try not to change the state. Use it only when it is very necessary.

190.2 Concentrating

Concentrate the state in one place.

190.3 Deferring

Defer state to the last step of the program, or to external system.

Chapter 191

Monadic Error handling

```
(>>=) :: m a -> (a -> m b) -> m b -- A.E   A - computes and drops if error value happens.  
catch :: c a -> (e -> c a) -> c a -- E.E   A - handles "errors" as "normal" values and stops when
```

Chapter 192

Functions

Total [function](#) uses [domain](#) fully, but takes only part of the [codomain](#).

[Function](#) allows to collapse [domain](#) values into [codomain](#) value. Meaning the [function](#) allows to loose the information.

So total [function](#) is a computation that loses the information or into bigger codomains.

That is why the [function](#) has a directionality, and [inverse](#) total process is partially possible.

Directionality and invertability are terms.

Chapter 193

Void

Emptiness.

Can not be grasped, touched.

A logically uninhabited [data type](#).

(Since [basis](#) of logic is tautologically True and [Void](#) value can not be addressed - there is a logical paradox with the [Void](#)).

Is an [object](#) included into the [Hask category](#), since:

```
:t (id :: Void -> Void)
(id :: Void -> Void) :: Void -> Void

id for it exists.
```

[Type](#) system corresponds to [constructive logic](#) and not to the classical logic.

Classical logic answers the question "Is this actually true".

Constructive (Intuitionistic) logic answers the question "Is this provable".

Also has [functions](#):

```
-- Represents logical principle of explosion: from falsehood, anything follows.
absurd :: Void -> a
```

```
-- If Functor holds only Void - it holds no values.
vacuous :: Functor f => f Void -> f a
```

```
-- If Monad holds only Void - it holds no values.
vacuousM :: Monad m => m Void -> m a
```

Design pattern: use [polymorphic data types](#) and [Void](#) to get rid of possibilities when you need to.

193.1 *

Nothing, Haskell [expressions](#) can't return [Void](#).

Also see: [Maybe](#).

Chapter 194

Constructive proof

Method of proof that demonstrates the existence of a mathematical [object](#) by creating or providing a method for creating the [object](#).

Chapter 195

Intuitionistic logic

[Proposition](#) considered **True** due to direct evidence of existence through constructive proof using [Curry-Howard isomorphism](#).

* does not include classic logic fundamental axioms of the excluded middle and double negation elimination. Hence * is weaker than classical logic. Classical logic includes *, all theorems of * are also in classical logic.

195.1 *

Constructive logic

Chapter 196

Principle of explosion

From asserted [statement](#) that contains contradiction - anything can be proven.
Ancient principle of logic. Both in classical & intuitionistic logic.

196.1 *

Ex falso quodlibet

Ex falso sequitur quodlibet

EFG

Ex contradictione quodlibet

Ex contradictione sequitur quodlibet

ECQ

Deductive explosion

Pseudo-Scotus

Chapter 197

Universal **property**

A **property** of some construction which boils down to (is manifestly **equivalent** to) the **property** that an associated **object** is a universal **initial object** of some (auxiliary) **category**.

Chapter 198

Yoneda lemma

Allows the embedding of any [category](#) into a [category](#) of [functors](#) ([contravariant set-valued functors](#)) defined on that [category](#). It also clarifies how the embedded [category](#), of representable [functors](#) and their [natural transformations](#), relates to the other [objects](#) in the larger [functor category](#).

The Yoneda lemma suggests that instead of studying the (locally small) [category](#) $C^{\{\{\{C\}\}\}\mathcal{C}}$, *one should study the [category](#)*

Chapter 199

Monoidal category, functoriality of ADTs, Profunctors

Category equipped with tensor product.

<>

wich is a functor for $*$.

Set category can be monoidal under both product (having terminal object) or coproduct (having initial object) operations, if according operation exist for all objects.

Any one-object category is $*$.

$(a, ()) \sim a$ up to unique isomorphism, which is called Lax monoidal functor.

Product and coproduct are functorial, so, since:
Algebraic data type construction can use:

- Type constructor
- Data constructor
- Const functor
- Identity functor
- Product
- Coproduct

Any algebraic data type is functorial.

Chapter 200

Const functor

Maps all [objects](#) of source [category](#) into one (fixed) [object](#) of target [category](#), and all [morphisms](#) to [identity morphism](#) of that fixed [object](#).

```
instance Functor (Const c)
  where
    fmap :: (a -> b) -> Const c a -> Const c b
    fmap _ (Const c) = Const c
```

In [Category](#) theory denoted:

Δ

Last [type parameter](#) that bears the target [type](#) of lifted [function](#) ([b](#)) and is a [proxy type](#).

Analogy: the container that allways has an [object](#) attached to it, and everything that is put inside - changes the container [type](#) accordingly, and dissapears.

Chapter 201

Arrow in Haskell

```
(->) a b = a -> b
```

[Functorial](#) in the last [argument](#) & called Reader [functor](#).

```
newtype Reader c a = Reader (c -> a)
```

```
  fmap = ( . )
```

Chapter 202

Contravariant functor

```
fmap :: (a -> b) -> Op c a -> Op c b
      (a -> c) -> (b -> c)
```

$$\begin{array}{ccc} a & \longrightarrow & b \\ & \searrow & \vdots \\ & & c \end{array}$$
$$(a \rightarrow b)^C = (a \leftarrow b)^{C^{op}}$$

```
class Contravariant f
  where
    contramap :: (b -> a) -> (f a -> f b)
```

$$\begin{array}{ccc} a & \longrightarrow & b \\ & \searrow & \vdots \text{contravariant} \\ & & c \end{array}$$

If [arrows](#) does not commute Contravariant functor anyway allows to [construct](#) transformation between these such [arrows](#) to other [arrow](#).

Chapter 203

Profunctor

$(\multimap) \ a \ b$

$C^{op} \times C \rightarrow C$

It is called profunctor.

`dimap :: (a' -> a) -> (b -> b') -> p a b -> p a' b'`

So, profunctor in [case](#) of [arrow](#):

$$\begin{array}{ccc} a & \xleftarrow{f} & a' \\ \downarrow h & & \downarrow \text{profunctor} \\ b & \xrightarrow{g} & b' \end{array}$$

```
dimap :: (a' -> a) -> (b -> b') -> p a b -> p a' b'
dimap ::      f           g       -> (a -> b) -> (a' -> b')
dimap ::      f           g       ->      h       -> (a' -> b')
dimap = g . h . f
```

It is [contravariant functor](#) in the first [argument](#), and [covariant functor](#) in the second [argument](#).

```
dimap id <==> fmap
(flip dimap) id <==> contramap
```

Part XI

Reference

Chapter 204

Functor-Applicative-Monad Proposal

Well known event in Haskell history: https://github.com/quchen/articles/blob/master/applicative_monad.md.

Math justice was restored with a RETroactive CONtinuity. Invented in computer science term [Applicative](#) (lax monoidal functor) become a [superclass](#) of [Monad](#).

& that is why:

- `return = pure`
- `ap = <*>`
- `>> = *>`
- `liftM = liftA = fmap`
- `liftM* = liftA*`

Also, a side-kick - [Alternative](#) became a [superclass](#) of [MonadPlus](#). Hence:

- `mzero = empty`
- `mplus = (<|>)`

204.1 *

Applicative-Monad proposal
AMP

Chapter 205

Haskell-98

205.1 Old instance termination rules

- a. \forall class **constraint** ($C\ t_1 \dots t_n$):
 - 1.1. **type variables** have occurrences \leq head
 - 1.2. **constructors+variables+repetitions** $<$ head
 - 1.3. \neg **type functions** (**type func application** can expand to **arbitrary** size)
- b. \forall **functional dependencies**, $tv_{\text{left}} \rightarrow tv_{\text{right}}$, of the class, every **type variable** in $S(tv_{\text{right}})$ must appear in $S(tv_{\text{left}})$, where S is the substitution mapping each **type variable** in the class **declaration** to the corresponding **type** in the instance head.

Chapter 206

Performance results and comparisons of **types** & solutions

Haskell performance

Part XII

Liturgy

- <- *Laos* the people
- <- *ergon* work
- leitourgia* giving back to the community

The life is beautiful.
For all humans that make the life have more uniqueness.

This study would not be possible without mathematicians, Haskellers, scientists, creators, contributors. These people are the most fascinating in my life.

Special accolades for the guys at Serokell. They were the force that got me inspired & gave resources to seriously learn Haskell and create this pocket guide.