targetDP Specification

Alan Gray and Kevin Stratford

Contents

2	1	Intro	duction	2
3		1.1	Abstract	2
4		1.2	Motivation	2
5		1.3	Glossary	3
6	2	Exec	ution model	4
7	3	Mem	ory model	6
8		3.1	Model overview	6
9		3.2	Implementation	7
10	4	Mem	ory Management	8
11		4.1	targetMalloc	9
12		4.2	targetCalloc	10
13		4.3	targetFree	11
14		4.4	copyToTarget	12
15		4.5	copyFromTarget	13
16		4.6	targetConst	14
17		4.7	copyConstToTarget	15
18		4.8	copyConstFromTarget	16
19		4.9	targetConstAddress	17
20		4.10	targetInit3D	18
21		4.11	targetFinalize3D	19
22		4.12	copyToTargetBoundary3D	20
23		4.13	copyFromTargetBoundary3D	21

CONTENTS

1		4.14	copyToTargetPointerMap3D	22
2		4.15	copyFromTargetPointerMap3D	23
3	5	Data	Parallel Execution	24
4		5.1	targetEntry	25
5		5.2	target	26
6		5.3	targetHost	27
7		5.4	targetLaunch	28
8		5.5	targetSynchronize	29
9		5.6	targetTLP	30
10		5.7	targetILP	31
11		5.8	targetCoords3D	32
12		5.9	targetIndex3D	33
13	6	Exar	nple	34

Chapter 1

Introduction

3 1.1 Abstract

- 4 The targetDP API provides an abstraction layer which allows applications to
- 5 target Data Parallel hardware in a platform agnostic manner, by abstracting
- 6 the memory spaces and hierarchy of hardware parallelism. Applications writ-
- ten using targetDP syntax are performance portable: the same source code can
- be compiled for different targets (currently supported are accelerators such as
- GPUs and modern multi-core SIMD CPUs), without performance overheads.
- The targetDP API is aimed at the types of parallelism found in grid-based ap-
- plications, but may be applicable to a wider class of problems. This document
- introduces the targetDP memory and execution models, and specifies the syn-
- tax and functionality of the interface. Implementation details are also provided,
- and a simple example is given to demonstrate usage.

15 1.2 Motivation

- 16 It is becoming increasingly difficult for applications to exploit modern com-
- 17 puters, which continue to increase in complexity and diversity with features
- including multiple multicore CPUs (often distributed across multiple nodes),
- vector floating point units, accelerators such as GPUs and non-uniform dis-
- 20 tributed memory spaces. From a scientist's perspective, it is not only imperative
- 21 to achieve performance, but also to retain maintainability, sustainability and
- portability. The use of a simplistic, well structured and clearly defined abstrac-

- tion layer such as targetDP can allow the programmer to express the scientific
- 2 problems in a way that will automatically achieve good performance across the
- 3 range of leading hardware solutions.

4 1.3 Glossary

- CPU: Central Processing Unit. The main computer chip used in a system, suitable for a wide variety of computational tasks.
- Accelerator: A processing unit which is not used in isolation, but instead in tandem with the CPU, with the aim of improving the performance of key code sections.
- GPU: Graphics Processing Unit. A type of accelerator, originally evolved to render graphics content (particularly to satisfy demands of the gaming industry), but now widely used for general purpose computation.
- Host: Another term for the CPU that "hosts" the application.
- Data Parallel: The type of algorithmic parallelism involved where a single operation is performed to each element of a data set. The extent of parallelism is determined by the size of the data set.
- Target: The device targeted for execution of data parallel operations.

 Depending on the underlying hardware available, the target could simply be the a CPU, or it could be a separate device such as an accelerator.
- CUDA: Compute Unified Device Architecture. The parallel platform and model created by NVIDIA to allow general purpose programming of their GP architectures.
 - TLP: Thread Level Parallelism.

23

• ILP: Instruction Level Parallelism.

Chapter 2

23

Execution model

- 3 The terminology "host" is used to refer to the CPU that is hosting the execution
- 4 of the application, and "target" to refer to the device targeted for execution of
- data parallel operations. The target could be the same CPU as the host, or it
- could be a separate device such as an accelerator (depending on the hardware available).

The targetDP API follows the fork-join model of parallel execution. When the application initiates, a single thread executes sequentially on the host, until it encounters a function to be launched on the target. This function will be executed by a team of threads on the target cooperating in a data-parallel manner (e.g. for a structured grid problem each thread is responsible for a subset of the grid).

To ensure that the target function has completed, a targetSynchronize statement should follow the code location where target function is launched. When the initial thread encounters this statement, it will wait until the target region has completed. It is possible for the initial thread to execute other instructions (which do not depend on the results of the target function), after the function launch but before the synchronisation call. This may result in overlapping of host and target execution, and hence optimisation, in some implementations. Once the target function has completed, the initial thread will continue sequentially until another target function launch is encountered.

Within each target function, each thread is given a unique index which it uses to work in a data-parallel manner. Each thread works independently from all others, but usually operating on a shared data structure where the index is used to determine the portion of data to process.

- COMMENT: Possibly add targetSyncThreads() to allow communication within
- 2 target functions?]
- COMMENT: Some text on reductions needed.

Chapter 3

Memory model

3.1 Model overview

- 4 The targetDP model draws a distinction between the memory spaces accessed
- 5 by the host and target, such that code executed on the host always accesses the
- 6 host memory space, and code executed on the target (i.e. within target func-
- 7 tions) always accesses the target memory space. The host memory space can be
- 8 initialised using regular C/C++ functionality, and the targetDP API provides the
- 9 functionality necessary to manage the target memory space and transfer data
- between the host and target. For each data-parallel data structure, the program-
- mer should create both host and target copies, and should update these from
- each other as and when required.

3.1.1 Host memory model

- The sequential thread executing host code should always access host data struc-
- tures. The memory model is the same as one would expect from a regular
- sequential application.

20

17 3.1.2 Target memory model

- The team of threads performing the execution of target functions should always
- act on target data structures. These can take one of 3 forms:
 - 1. Those created using the targetDP memory allocation API functions. These are shared between all threads in the team, where each thread should use

- its unique index to access the portion of data for which it is responsible.
- 2. Those created using the targetDP constant data management functionality.
- These are read-only and normally used for relatively small amounts of
- constant data.
- 5 3. Those declared within the body of a target function. These are private to
- each thread in the team and should be used for temporary scratch struc-
- 7 tures.
- 8 COMMENT: For 3, at the moment any data declared in the function but
- 9 above the targetTLP keyword will be private for GPU threads but shared for
- CPU (since outside parallel region). So either need to make this clearer above,
- or somehow move OpenMP parallel region to target launch.

2 3.2 Implementation

13 3.2.1 C

- 14 The target memory structures will exist on the same physical memory as the host
- structures. The implementation may either use separate target copies (managed
- using regular C/C++ memory management functionality), or use pointer alias-
- ing for the target versions such that a reference to any part of a target structure
- will correspond to exactly the same physical address as that of the correspond-
- ing host structure.

20 3.2.2 CUDA

- 21 The target memory space will exist on the distinct GPU memory, i.e. in a sepa-
- 22 rate memory space from the host structures.

- Chapter 4
- Memory Management

4.1 targetMalloc

2 4.1.1 Description

The targetMalloc function allocates memory on the target.

4 4.1.2 Syntax

```
void targetMalloc(void** targetPtr, size_t n);
```

- targetptr: A pointer to the allocated memory.
- n: The number of bytes to be allocated.

8 4.1.3 Example

⁹ See Line 1 in Figure 6.3 in Section 6.

10 4.1.4 Implementation

- 11 **C**
- 12 malloc
- 13 CUDA
- 14 cudaMalloc

4.2 targetCalloc

2 4.2.1 Description

- 3 The targetCalloc function allocates, and initialises to zero, memory on the
- 4 target.

5 4.2.2 Syntax

- void targetCalloc(void** targetPtr, size_t n);
- targetptr: A pointer to the allocated memory.
- n: The number of bytes to be allocated.

9 4.2.3 Example

Analogous to Line 1 in Figure 6.3 in Section 6.

4.2.4 Implementation

- 12 **C**
- 13 calloc
- 14 CUDA
- cudaMalloc followed by cudaMemset

4.3 targetFree

2 4.3.1 Description

The targetFree function deallocates memory on the target.

4 4.3.2 Syntax

- void targetFree(void* targetPtr);
- targetPtr: A pointer to the memory to be freed.

7 4.3.3 Example

8 See Line 11 in Figure 6.3 in Section 6.

9 4.3.4 Implementation

- 10 **C**
- 11 free
- 12 CUDA
- 13 cudaFree

4.4 copyToTarget

2 4.4.1 Description

The copyToTarget function copies data from the host to the target.

4 4.4.2 Syntax

- void copyToTarget(void* targetData, const void* data, size_t n);
- targetData: A pointer to the destination array on the target.
- data: A pointer to the source array on the host.
- n: The number of bytes to be copied.

9 4.4.3 Example

See Line 3 in Figure 6.3 in Section 6.

4.4.4 Implementation

- 12 **C**
- 13 тетсру
- 14 CUDA
- 15 cudaMemcpy

4.5 copyFromTarget

₂ 4.5.1 Description

The copyFromTarget function copies data from the target to the host.

4 4.5.2 Syntax

- void copyFromTarget(void* data, const void* targetData, size_t n);
- data: A pointer to the destination array on the host.
- targetData: A pointer to the source array on the target.
- n: The number of bytes to be copied.

9 4.5.3 Example

See Line 9 in Figure 6.3 in Section 6.

4.5.4 Implementation

- 12 **C**
- 13 тетсру
- 14 CUDA
- 15 cudaMemcpy

4.6 targetConst

2 4.6.1 Description

- 3 The __targetConst__ keyword is used in a variable or array declaration to
- 4 specify that the corresponding data can be treated as constant (read-only) on
- 5 the target.

6 4.6.2 Syntax

- 7 __targetConst__ type variableName
- variableName: The name of the variable or array.
- type: The type of variable or array.

10 4.6.3 Example

TO DO.

4.6.4 Implementation

- 13 **C**
- 14 Holds no value
- 15 CUDA
- constant__

4.7 copyConstToTarget

2 4.7.1 Description

- 3 The copyConstToTarget function copies data from the host to the target, where
- 4 the data will remain constant (read-only) during the execution of functions on
- 5 the target.

6 4.7.2 Syntax

```
void copyConstToTarget(void* targetData, const void* data, size_t n);
```

- targetData: A pointer to the destination array on the target. This must have been declared using the __targetConst__ keyword.
- data: A pointer to the source array on the host.
- n: The number of bytes to be copied.

12 4.7.3 Example

See Line 4 in Figure 6.3 in Section 6.

4.7.4 Implementation

- 15 **C**
- 16 memcpy
- 17 CUDA
- cudaMemcpyToSymbol

4.8 copyConstFromTarget

2 4.8.1 Description

- 3 The copyConstFromTarget function copies data from a constant data location
- on the target to the host.

5 4.8.2 Syntax

- void copyConstToTarget(void* targetData, const void* data, size_t n);
- data: A pointer to the destination array on the host.
- \bullet targetData: A pointer to the source array on the target. This must have
- been declared using the __targetConst__ keyword.
- n: The number of bytes to be copied.

4.8.3 Example

Analogous to Line 4 in Figure 6.3 in Section 6.

4.8.4 Implementation

- 14 **C**
- 15 memcpy
- 16 CUDA
- cudaMemcpyFromSymbol

4.9 targetConstAddress

2 4.9.1 Description

- 3 The targetConstAddress function provides the target address for a constant
- 4 object.

5 4.9.2 Syntax

- void targetConstAddress(void** address, objectType object);
- address (output): The pointer to the constant object on the target.
- objectType: The type of the object.
- object (input): The constant object on the target. This should have been declared using the __targetConst__ keyword.

4.9.3 Example

12 **TO DO**.

4.9.4 Implementation

- 14 **C**
- 15 Explicit copying of address.
- 16 CUDA
- cudaGetSymbolAddress

4.10 targetInit3D

2 4.10.1 Description

- 3 The targetInit3D initialises the environment required to perform any of the
- 4 "3D" operations described in the rest of this chapter.

5 4.10.2 Syntax

- 6 void targetInit3D(size_t extent, size_t nFields);
- extent: The total extent of data parallelism (e.g. the number of lattice sites).
- nFields: The extent of data resident within each parallel partition (e.g. the number of fields per lattice site).

4.10.3 Example

12 **TO DO**.

4.10.4 Implementation

14 **C**

15 **TO DO**.

16 CUDA

4.11 targetFinalize3D

- 2 4.11.1 Description
- 3 The targetFinalize3D finalises the targetDP 3D environment.
- 4.11.2 Syntax
- 5 void targetFinalize3D();
- 6 4.11.3 Example
- 7 **TO DO**.
- 8 4.11.4 Implementation
- 9 **C**
- 10 **TO DO**.
- 11 CUDA
- 12 **TO DO**.

4.12 copyToTargetBoundary3D

2 4.12.1 Description

- 3 The copyToTargetBoundary3D function copies the data corresponding to the
- boundaries of a 3D lattice from the host to the target.

5 4.12.2 Syntax

```
void copyToTargetBoundary3D(void* targetData, const void* data,
size_t extent3D[3], size_t nField,
size_t offset, size_t depth);
```

- targetData: A pointer to the destination array on the target.
- data: A pointer to the source array on the host.
- extent3D: An array of 3 integers corresponding to the 3D dimensions of the lattice.
 - nFields: The number of fields per lattice site.
- offset: The number of sites from the lattice edge at which each boundary face should start.
 - depth: The depth of each boundary face.

17 4.12.3 Example

```
18 **TO DO**.
```

13

19 4.12.4 Implementation

```
20 C
21 **TO DO**.
```

4.13 copyFromTargetBoundary3D

2 4.13.1 Description

- The copyFromTargetBoundary3D function copies the data corresponding to the
- boundaries of a 3D lattice from the target to the host.

5 4.13.2 Syntax

```
void copyFromTargetBoundary3D(void* data, const void* targetData,
size_t extent3D[3], size_t nField,
size_t offset, size_t depth);
```

- data: A pointer to the destination array on the host.
- targetData: A pointer to the source array on the target.
- extent3D: An array of 3 integers corresponding to the 3D dimensions of the lattice.
- nFields: The number of fields per lattice site.
- offset: The number of sites from the lattice edge at which each boundary face should start.
 - depth: The depth of each boundary face.

17 4.13.3 Example

```
18 **TO DO**.
```

4.13.4 Implementation

```
20 C
21 **TO DO**.
```

22 CUDA

4.14 copyToTargetPointerMap3D

2 4.14.1 Description

- 3 The copyToTargetPointerMap3D function copies a subset of lattice data from
- 4 the host to the target. The sites to be included are defined using an array of
- 5 pointers passed as input.

6 4.14.2 Syntax

```
void copyToTargetPointerMap3D(void* targetData, const void* data,
size_t extent3D[3], size_t nField,
int includeNeighbours, void** pointerArray);
```

- targetData: A pointer to the destination array on the target.
- data: A pointer to the source array on the host.
- extent3D: An array of 3 integers corresponding to the 3D dimensions of the lattice.
 - nField: The number of fields per lattice site.
 - includeNeighbours: A Boolean switch to specify whether each included site should also have it's neighbours included (in the 19-point 3D stencil).
- pointerArray: An array of nSite pointers, where nSite is the total number of lattice sites. Each lattice site should be included unless the pointer corresponding to that site is NULL.

20 4.14.3 Example

```
21 **TO DO**.
```

22 4.14.4 Implementation

23 **C**

11

14

15

```
24 **TO DO**.
```

25 CUDA

4.15 copyFromTargetPointerMap3D

₂ 4.15.1 Description

- 3 The copyFromTargetPointerMap3D function copies a subset of lattice data from
- 4 the target to the host. The sites to be included are defined using an array of
- 5 pointers passed as input.

6 4.15.2 Syntax

```
void copyFromTargetPointerMap3D(void* data, const void* targetData,
size_t extent3D[3], size_t nField,
int includeNeighbours, void** pointerArray);
```

- data: A pointer to the destination array on the host.
 - targetData: A pointer to the source array on the target.
- extent3D: An array of 3 integers corresponding to the 3D dimensions of the lattice.
 - nField: The number of fields per lattice site.
 - includeNeighbours: A Boolean switch to specify whether each included site should also have it's neighbours included (in the 19-point 3D stencil).
- pointerArray: An array of nSite pointers, where nSite is the total number of lattice sites. Each lattice site should be included unless the pointer corresponding to that site is NULL.

20 4.15.3 Example

```
21 **TO DO**.
```

2 4.15.4 Implementation

```
23 C
```

11

14

15

24 **TO DO**.

25 CUDA

- Chapter 5
- **Data Parallel Execution**

5.1 targetEntry

₂ 5.1.1 Description

- The __targetEntry__ keyword is used in a function declaration or definition
- to specify that the function should be compiled for the target, and that it will be
- 5 called directly from host code.

5.1.2 Syntax

- 7 __targetEntry__ functionReturnType functionName(...
- functionName: The name of the function to be compiled for the target.
- functionReturnType: The return type of the function.
- ... the remainder of the function declaration or definition.

5.1.3 Example

See Line 1 in Figure 6.2 in Section 6.

13 5.1.4 Implementation

- 14 **C**
- 15 Holds no value.
- 16 CUDA
- global__

5.2 target

₂ 5.2.1 Description

- 3 The __target__ keyword is used in a function declaration or definition to spec-
- 4 ify that the function should be compiled for the target, and that it will be called
- 5 from a targetEntry or another target function.

6 5.2.2 Syntax

- __target__ functionReturnType functionName(...
- functionName: The name of the function to be compiled for the target.
- functionReturnType: The return type of the function.
- ... the remainder of the function declaration or definition.

5.2.3 Example

Analogous to Line 1 in Figure 6.2 in Section 6.

5.2.4 Implementation

- 14 **C**
- 15 Holds no value.
- 16 CUDA
- 17 __device__

5.3 targetHost

₂ 5.3.1 Description

- The __targetHost__ keyword is used in a function declaration or definition to
- specify that the function should be compiled for the host.

5.3.2 Syntax

- 6 __targetHost__ functionReturnType functionName(...
- functionName: The name of the function to be compiled for the host.
- functionReturnType: The return type of the function.
- ... the remainder of the function declaration or definition.

5.3.3 Example

Analogous to Line 1 in Figure 6.2 in Section 6.

5.3.4 Implementation

- 13 **C**
- 14 Holds no value.
- 15 CUDA
- extern ''C'' __host__

5.4 targetLaunch

₂ 5.4.1 Description

- 3 The __targetLaunch__ syntax is used to launch a function across a data parallel
- 4 target architecture.


```
functionName __targetLaunch__(size_t extent) \
functionArgument1,functionArgument2,...);
```

- functionName: The name of the function to be launched. This function must be declared as __targetEntry__ .
- functionArguments: The arguments to the function functionName
- extent: The total extent of data parallelism.

12 **5.4.3 Example**

See Line 6 in Figure 6.3 in Section 6.

5.4.4 Implementation

- . C
- 16 Holds no value.
- 17 CUDA
- 18 CUDA <<<...>>> syntax.

5.5 targetSynchronize

2 5.5.1 Description

- 3 The targetSynchronize function is used to block until the preceding __targetLaunch__
- 4 has completed.

5 5.5.2 Syntax

void targetSynchronize();

5.5.3 Example

8 See Line 7 in Figure 6.3 in Section 6.

₉ 5.5.4 Implementation

- 10 **C**
- 11 Dummy function.

12 CUDA

13 cudaThreadSynchronize

5.6 targetTLP

₂ 5.6.1 Description

- 3 The __targetTLP__ syntax is used, within a __targetEntry__ function, to
- specify that the proceeding block of code should be executed in parallel and
- 5 mapped to thread level parallelism (TLP). Note that he behaviour of this op-
- eration depends on the defined virtual vector length (VVL), which controls the
- lower-level Instruction Level Parallelism (ILP) (see following section).

5.6.2 Syntax

```
9 __targetTLP__(int baseIndex, size_t extent)
10 {
11 //code to be executed in parallel
12 }
```

- extent: The total extent of data parallelism, including both TLP and ILP
- baseIndex: the TLP index. This will vary from 0 to extent-VVL with stride VVL. This index should be combined with the ILP index to access shared arrays within the code block (see following section).

₁₇ 5.6.3 Example

See Line 4 in Figure 6.2 in Section 6.

5.6.4 Implementation

20 **C**

13

14

- 21 OpenMP parallel loop.
- 22 CUDA
- 23 CUDA thread lookup.

5.7 targetILP

₂ 5.7.1 Description

- 3 The __targetILP__ syntax is used, within a __targetTLP__ region, to specify
- 4 that the proceeding block of code should be executed in parallel and mapped to
- 5 instruction level parallelism (ILP), where the extent of the ILP is defined by the
- 6 virtual vector length (VVL) in the targetDP implementation. COMMENT: need
- 7 to document VVL in more detail somewhere and link.

5.7.2 Syntax

```
__targetILP__(int vecIndex)
{
//code to be executed in parallel
//code to be executed in parallel
```

 baseIndex: the ILP index. This will vary from 0 to VVL-1. This index should be combined with the TLP index to access shared arrays within the code block (see previous section).

16 **5.7.3** Example

See Line 9 in Figure 6.2 in Section 6.

₁₈ 5.7.4 Implementation

19 **C**

13

- 20 Short vectorizable loop.
- 21 CUDA
- 22 Short vectorizable loop.

5.8 targetCoords3D

₂ 5.8.1 Description

- 3 The targetCoords3D function provides the 3D lattice coordinates correspond-
- 4 ing to a specified linear index.

5.8.2 Syntax 5.8.5 Syntax

- void targetCoords3D(int coords3D[3], int extent3D[3], int index);
- coords3D (output): an array of 3 integers to be populated with the 3D coordinates.
- extent3D (input): An array of 3 integers corresponding to the 3D dimensions of the lattice.
- index (input): the linear index.

12 **5.8.3 Example**

13 **TO DO**

5.8.4 Implementation

15 **C**

16 **TO DO**

17 CUDA

5.9 targetIndex3D

₂ 5.9.1 Description

- The targetIndex3D function returns the linear index corresponding to a speci-
- 4 fied set of 3D lattice coordinates.

5.9.2 Syntax

- 6 int targetIndex3D(int Xcoord,int Ycoord,int Zcoord,int extent3D[3]);
- Xcoord (input): the specified coordinate in the X direction.
- Ycoord (input): the specified coordinate in the Y direction.
- Zcoord (input): the specified coordinate in the Z direction.
- extent3D (input): an array of 3 integers corresponding to the 3D dimensions of the lattice.

12 **5.9.3 Example**

13 **TO DO**

5.9.4 Implementation

15 **C**

16 **TO DO**

7 CUDA

Chapter 6

Example

Consider a simple example: the scaling of a 3-vector field by a constant, as implemented in a sequential programming style in Figure 6.1. On each lattice site exists a 3-vector (a collection of three values corresponding to the 3 spatial dimensions). The outer loop corresponds to lattice sites, and the inner loop to the 3 components within each lattice site. This is a simple example of operations

on "multi-valued" data, a very common situation in scientific simulations.

The lattice-based parallelism corresponding to the outer loop can be mapped to data parallel hardware using targetDP. We introduce targetDP by replacing the sequential code with the function given in Figure 6.2. The t_ syntax is used to identify target data structures. The __targetEntry__ syntax is used to specify that this function is to be executed on the target, and it will be called from host code. We expose the lattice-based parallelism to each of the TLP and ILP levels of hardware parallelism through use of the combination __targetTLP__(baseIndex,N) and __targetILP__(vecIndex) (See Sections 5.6 and 5.7. The former specifies that lattice-based parallelism should be mapped to TLP, where each thread operates on a chunk of lattice sites. The latter specifies that the sites within each chunk should be mapped to ILP. It can be seen that the t_field array is accessed by combining these indexes. The size of the chunk can be set within the targetDP implementation, to give the best performance for a particular architecture.

The scale function is called from host code as shown in Figure 6.3. The memory management facilities are used to allocate and transfer data to and from the target, as described in Chapter 4.

```
for (idx = 0; idx < N; idx++) { //loop over lattice sites
  int iDim;
  for (iDim = 0; iDim < 3; iDim++)
     field[iDim*N+idx] = a*field[iDim*N+idx];
}
</pre>
```

Figure 6.1: A sequential implementation of the scalar multiplication of each element of a lattice data structure.

```
__targetEntry__ void scale(double* t_field) {
                                                              1
                                                              2
 int baseIndex:
                                                              3
  __targetTLP__(baseIndex, N) {
                                                              4
                                                              5
    int iDim, vecIndex;
                                                              6
    for (iDim = 0; iDim < 3; iDim++) {
                                                              7
                                                              8
                                                              9
      __targetILP__ (vecIndex) \
                                                              10
         t_field[iDim*N + baseIndex + vecIndex] =
         t_a*t_field[iDim*N + baseIndex + vecIndex];
                                                              11
                                                              12
  }
                                                              13
 return;
                                                              14
                                                              15
```

Figure 6.2: The targetDP implementation of the scalar multiplication kernel.

```
targetMalloc((void **) &t_field , datasize);
                                                             1
                                                             2
                                                             3
copyToTarget(t_field , field , datasize);
                                                             4
copyConstToTarget(&t_a, &a, sizeof(double));
                                                             5
scale __targetLaunch__(N) (t_field);
                                                             6
                                                             7
targetSynchronize();
                                                             8
copyFromTarget(field , t_field , datasize);
                                                             9
                                                             10
targetFree(t_field);
                                                             11
```

Figure 6.3: The host code used to invoke the targetDP scalar multiplication kernel.