Digital Signal Processing

Lab 3 Introduction

Lab Breakdown


- Integrate the LM61 temperature sensor hardware with the Arduino hardware
 - Take some initial data samples
- Add an interrupt to take samples at known sample times
- Add code to control the start timing and collect a fixed number of samples

Lab Breakdown


- Interface the Arduino with MATLAB to collect and analyze data
- Add code to compute running statistics (mean and variance) from generated data

LM61 Hardware Interface

- It is <u>critical</u> that you wire the temperature sensor correctly!
 - Follow the <u>schematic</u> carefully (not the colors)



Carefully note the pinout!



The pins are shown coming out towards you

Note the wiring

RIT

EEET-425 Digital Signal Processing

Copying Code from the Procedure

In the Lab Procedure, there are text boxes that contain Arduino code

```
AnalogReadSerial: public domain code
   Reads analog input on pin 0, prints to console.
void setup() // runs once when you press reset
  Serial.begin(9600);
void loop() // runs over and over forever
  int sensorValue = analogRead(A0);
  Serial.println(sensorValue);
  delay(1); // delay in between reads for stability
```

Mouse in the box, select all (CTRL-A) and copy. Then paste into the Arduino IDE.

Reading Data using MATLAB

- MATLAB will read data from the Arduino serial port interface
- Copy the following three ".m-files" from myCourses to your working directory (MATLAB Tools\Arduino Interface)
 - ArduinoSerial.m
 - CaptureArduinoData.m
 - ActivePlot.m

Reading Data using MATLAB

- Arduino and MATLAB perform a "handshake" at the beginning of operation
 - Arduino sends "%Arduino Ready"
 - MATLAB returns with "g"
 - Program execution begins

- Use the Command Window (not Live Editor)
- The main routine is "CaptureArduinoData"
- MATLAB can take arguments to set the Com port and the data rate as Name, Value pairs


```
Command Window

fx >> data = CaptureArduinoData('ComPort', 3, 'BaudRate', 9600);
```

Change the ComPort and baud rate accordingly



Data will be echoed in the command window



After data collection is complete, you will be prompted to save the data in a .mat file






 To plot data simultaneously (while reading data) use the active plot options

```
Command Window

fx >> data = CaptureArduinoData('ComPort', 3, 'BaudRate', 9600, 'NumActivePlots', 1);
```

 Use 'NumActivePlots' property. Must have N+1 data values. All data is plotted against the first data value (e.g. sample number).

Each graph will draw in "real time" so that you can actively see your sample data



If you have a Serial Port Conflict

- Arduino and MATLAB share the serial port
 - Arduino uses it for uploading the sketch
 - Both use it to share data
- Sometimes there is a conflict
 - MATLAB hasn't released the port (e.g. program terminated early via CTRL-C)
 - In MATLAB command window use to release serial port


```
Command Window
f_{\xi}^{x} >> fclose( instrfind )
```


Computing Running Statistics

- The last section of the lab asks you to write some code to compute running statistics
 - Numerically robust approach (see the supplemental resources)
 - Data is generated within Arduino C-code
 - Compute and display for both the amplitude burst and the frequency burst data

Computing Running Statistics

```
float simSample(void)
  // Simulate sensor for stats calculation development
 float simSmpl, simAmp = 1.0, simT = 60;
 //simAmp = ((numSamples > 180) && (numSamples < 300)) ? 0.125 : 1.0; // burst amplitude
 //simT = ((numSamples > 180) && (numSamples < 300)) ? 30.0 : 60.0; // burst frequency
 simSmpl = 180.0 + simAmp*sin((numSamples/simT)*TWO PI); // fixed amplitude, frequency
 return simSmpl;
```





By "comment selecting" the simAmp or simT equations, you can select either input



Lab Report

- This lab report is to be submitted using the IEEE format.
 - Use the template on myCourses

Preparation of Papers for IEEE TRANSACTIONS and JOURNALS (May 2007)

First A. Author, Second B. Author, Jr., and Third C. Author, Member, IEEE¶

Abstract—These-instructions give you guidelines for preparing papers for IEEE TRANSACTIONS and JOURNALS. Use this document as a template if you are using Microsoft Word 6.0 or later. Otherwise, use this document as an instruction set. The electronic file of your paper will be formatted further at IEEE. Define all-symbols used in the abstract. Do not otic references in the abstract. Do not delete the blank line immediately above the abstract, it sets the footnote at the bottom of this column?

Index: Terms—About four key words or phrases inalphabetical-order, separated by commas. For a list of suggested keywords, send a blank - mail to keywords/giece.org or visithttp://www.ieee.org/organizations/pubs/ani_prod/keywrd98.txt¶

I.→INTRODUCTION

THIS document is a template for Microsoft Word versions:

6.0 or later. If you are reading a paper or PDF version of
this document, please download the electronic file, **

TRANS-JOUR.DOC, from the IEEE Web site at
http://www.ieec.org/web/publications/uthor/transipil/mock.html; so
you can use it to prepare your manuscript. If you would prefer
to use LATEX, download IEEE s.LATEX style and sample
files from the same. Web page. Use these LATEX files for

which allows you to see the footnotes. Then, type oversections of TRANS-JOUR.DOC or cut and paste from another document and use markup styles. The pull-down style menu is at the left of the Formatting Toolbar at the top of your Word window (for example, the style at this point in the document is "Text"). Highlight a section that you want to designate with a certain style, then select the appropriate name on the style menu. The style will adjust your forat and line spacing. Do not change the font sizes or line spacing to squeeze more text into a limited number of pages. Use stalics for emphasis; do not underline. ¶

To insert images in Word, position the cursor at the insertion point and either use Insert! Picture! From File or copy the image to the Windows clipboard and then Edit! Paste Special! Picture (with "float over text" unchecked).

IEEE will do the final formatting of your paper. If your paper is intended for a conference, please observe the conference page limits.

II.→PROCEDURE FOR PAPER SUBMISSION¶

A. → Review-Stage¶

Please check with your editor on whether to submit your

Follow the guidelines
and fonts as in the
template.
Use descriptive captions



EEET-425 Digital Signal Processing

Tips to Using the Template

- DO NOT change the:
 - Margins, Fonts, Column settings, etc..
- To collaborate with GoogleDocs it is best to write the report in Docs and then copy to the Word Template when completed

Preparation of Papers for IEEE TRANSACTIONS and JOURNALS (May 2007)

First A. Author, Second B. Author, Jr., and Third C. Author, Member, IEEE¶

Abstract—These instructions give you guidelines for preparing papers for IEEE TRANSACTIONS and JOURNALS. Use this document as a template if you are using Microsoft Word 6.0 or later. Otherwise, use this document as an instruction set. The electronic file of your-paper will be formatted further at IEEE. Define all symbols used in the abstract. Do not cite references in Define an symposis used in the abstract. Do not che references in the abstract. Do not delete the blank line immediately above the abstract; it sets the footnote at the bottom of this column.

alphabetical order, separated by commas. For a list of suggested ywords, send a blank e-mail to keywords@jeee.org or p://www.ieee.org/organizations/pubs/ani_prod/keywrd98.txt¶

I.→INTRODUCTION¶

THIS document is a template for Microsoft Word versions 1 6.0 or later. If you are reading a paper or PDF version of this document, please download the electronic file, e TRANS-JOUR.DOC, from the IEEE Web site at http://www.ieee.org/web/publications/authors/transjnl/index.html so • you-can use it-to-prepare your-manuscript. If-you-would-prefer-

sections of TRANS_JOUR DOC-or-cut-and-paste-from another document and use markup styles. The pull-down style menu is at the left of the Formatting Toolbar at the top of your Word window (for example, the style at this point in the document is "Text"). Highlight a section that you want to designate with a certain style, then select the appropriate name on the style menu. The style will adjust your fonts and line spacing. Do not change the font sizes or line spacing to squeeze more text into a limited number of pages. Use italics for emphasis: do not underline. ¶

To insert images in Word, position the cursor at the insertion point and either use Insert | Picture | From File or copy the image to the Windows clipboard and then Edit | Paste Special Picture (with "float over text" unchecked). ¶

IEEE will do the final formatting of your paper. If you paper is intended for a conference, please observe the conference page limits. ¶

II.→PROCEDURE-FOR-PAPER-SUBMISSION¶



you can use fto prepare you manuscript. If you would preserve to use LATEX, download IEEE + LATEX style and sample - A.—Review Stage |

Flease check with your editor on whether to submit your EEET-425 Digital Signal Processing

Lab Report Tips

- Use the lab report rubric to make sure you have included all the key elements
- Export the Word file to PDF. Submit only the PDF (not the word file)
 - I will ask you for a PDF if you do not do this correctly
- DO NOT submit a ZIP file