Browser Extension
Getting Started
Settings
Changelog

Rainmeter Plugin
Getting Started
Usage
Changelog

OBS Script
Getting Started
Changelog

CLI
Getting Started
Changelog

Creating Adapters

On this page

Adapter Library

Usage

- See wnp.h
- See examples in /examples

c

```c
examples/simple.c:
#include "stdio.h"
#include "wnp.h"

int main(void)
{
  // port, adapter version
  if (wnp_start(1234, "1.0.0", NULL) < 0) {
    perror("Failed to start wnp");
    return -1;
  }
```

Browser Extension
Getting Started
Settings
Changelog

Rainmeter Plugin
Getting Started
Usage
Changelog

OBS Script
Getting Started
Changelog

CLI
Getting Started
Changelog

Creating Adapters

```
    wnp_lock(player);
    printf("Title: %s\n", player->title);
    wnp_unlock(player);
    // try to play-pause
    int event_id = wnp_try_play_pause(player);
    // optionally, wait for a result
    char* event_outcomes[] = {"", "succeeded", "failed"};
    printf("event %d %s\n", event_id, event_outcomes[wnp_wait_for_event_result(ev
    sleep_ms(1000);
  }

  wnp_stop();
  return 0;
}
```

Browser Extension

Getting Started

Settings

Changelog

Rainmeter Plugin

Getting Started

Usage

Changelog

OBS Script

Getting Started

Changelog

CLI

Getting Started

Changelog

Creating Adapters