



# Micro Frontends

Communication Patterns

Satyam Pandey | Sravya Chodisetti

---

## Table of contents

1. Speakers
2. Introduction
3. Communication Patterns
4. Best Practices

---

## Speakers



**Satyam Pandey**

Engineering Manager

Global Merchant Lending, PayPal Credit



**Sravya Chodisetti**

Senior Software Engineer

Global Merchant Lending, PayPal Credit

# Global Merchant Lending in PayPal

*Democratize Credit to our 30M+ Merchant partners!*

*Offer Fast, Fair, Flexible Credit solutions!*

*Grow by enabling growth to our Merchant partners!*

## Product

### **PayPal** Working Capital


#### Key Features

- Sales Based Repayments
- No Credit Check

#### Target Audience

- Small, Micro Sellers with seasonal / unpredictable cashflows

#### Countries Served



### **PayPal** Business Loan

- Traditional Term Loans
- Use Credit Check


- Mature merchants with predictable cash flows



### **LOANBUILDER**


- Paycheck Protection Loans
- Use Credit Check

- Support Government Initiatives during COVID19



# Why is communication important in Micro Frontend Architecture?

Overview





# Introduction


Introduction

Communication Patterns


Best Practices

Q/A

Website



Component Structure



# Introduction

1

## Parent to Fragment

- Element Attributes
- Connected Callback
- Attribute Changed Callback

2

## Fragment to Parent

- Custom Events
- Event Listeners

3

## Fragment to Fragment

- DOM Manipulation
- Attributes and Callbacks
- Event Bus
- Broadcast Channel API

4

## Global Communication

- URL Params
- Global Context and State
- State Management Libraries (Redux)




# Communication Patterns

## Parent to Fragment - Scenario

Website



Component Structure



# Communication Patterns

## Parent to Fragment – Attribute Implementation

### 1 Create a custom attribute on the element


- Create a custom attribute called 'itemData' on the item component

### 2 Pass data as attribute-value to the Fragment

- Pass the plant data to the plant component (instock -true/false) to render plant out-of-stock

### 3 Create lifecycle methods on observed attribute


- Create connectedCallback or attributeChangedCallback hooks on 'inStock'
- Create handlers for the callbacks
- Render the plant item as enabled or disabled based on the value of 'inStock' attribute in the Fragment




# Communication Patterns

## Fragment to Parent - Scenario

Website



Component Structure



# Communication Patterns

## Fragment to Parent – Custom Event Implementation

### 1 Create a custom event on the element


- Create a custom event called 'add-plant' on the 'Add' Button

### 2 Emit the event on action

- Emit the 'add-plant' event on clicking the button

### 3 Create event listener and a handler on the parent


- Add an event listener on the 'content' element
- Listen for the 'add-plant' event
- Execute handler for the next steps
  - send a toast notification for successful update




# Communication Patterns

## Fragment to Fragment - Scenario

Website



Component Structure






# Communication Patterns

## Fragment to Fragment – Implementation – 4 ways

### 1 Direct DOM reference

- Using DOM navigation properties
  - Get elements by X
  - Query selectors
- **Easy to implement**
- **Introduces tight-coupling**
  - Needs DOM context to navigate and identify
  - Defies the concept of MFA






# Communication Patterns


## Fragment to Fragment – Implementation – 4 ways

### 1 Direct DOM reference



### 2 Routing via Parents


- Combine the previous communication patterns –
  - Trigger an event from Source Fragment to Parent
  - Pass the attribute from Parent to Destination Fragment
- Easy to implement
- Increased no. of communications between fragments across DOM tree




# Communication Patterns

## Fragment to Fragment – Implementation – 4 ways

### 1 Direct DOM reference




### 2 Routing via Parents



### 3 Event Bus via Custom Events


- Dispatch custom events and let the events bubble
- Dispatch custom events directly to the Window
- **Event bubbling allows modification at parents in the tree**
  - Stop propagation / Prevent default
  - Intercept and modify payload
- **Heavily dependent on the DOM structure**




# Communication Patterns

## Fragment to Fragment – Implementation – 4 ways


### 1 Direct DOM reference



### 2 Routing via Parents




### 3 Event Bus via Custom Events



### 4 Publish / Subscribe


- Publish and Subscribe model via Broadcast APIs
  - Create and connect to a channel
  - Send messages to the channel
  - Receive messages and perform necessary actions
- Communicate across windows/tabs/iframes
- Channels are open to everyone to publish messages – **pro** or **con** depending on the use-case




# Communication Patterns

## Fragment to Fragment – Implementation – 4 ways


### 1 Direct DOM reference




### 2 Routing via Parents



### 3 Event Bus via Custom Events



### 4 Publish / Subscribe




# Communication Patterns

## Global Communication – Scenarios and Solutions

1

### Product Type

- Scenario
  - You sell multiple products on your website (plants, pots, soil, seeds, etc.)
  - How do you pass the product type information to all fragments in the application?
- Solution
  - URL params
    - `www.mfa.com/plants`
    - `www.mfa.com/pots`
    - `www.mfa.com/seeds`
  - Each Fragment reads the product type from the query/path params in the URL
  - Each Fragment maintains a local state and handles the rendering based on the params






# Communication Patterns

## Global Communication – Scenarios and Solutions

1

### Product Type


- Scenario
  - You sell multiple products on your website (plants, pots, soil, seeds, etc.)
  - How do you pass the product type information to all fragments in the application?
- Solution
  - URL params
    - `www.mfa.com/plants`
    - `www.mfa.com/pots`
    - `www.mfa.com/seeds`
  - Each Fragment reads the product type from the query/path params in the URL
  - Each Fragment maintains a local state and handles the rendering based on the params



2

### User Details

- Scenario
  - You have multiple user categories who use your website (Platinum, gold, silver, etc.) and the features and User experience varies for each category.
  - How do you pass the user details (category, country, language, etc.) to all the fragments in the application?
- Solution
  - Global Scope and Context
    - JS global scope and context APIs
  - State Management Libraries
    - Create Global state for shared data and local state for each fragment to avoid **tight-coupling**






# Communication Patterns

## Global Communication – Scenarios and Solutions

1

### Product Type


- Scenario
  - You sell multiple products on your website (plants, pots, soil, seeds, etc.)
  - How do you pass the product type information to all fragments in the application?
- Solution
  - URL params
    - `www.mfa.com/plants`
    - `www.mfa.com/pots`
    - `www.mfa.com/seeds`
  - Each Fragment reads the product type from the query/path params in the URL
  - Each Fragment maintains a local state and handles the rendering based on the params



2

### User Details


- Scenario
  - You have multiple user categories who use your website (Platinum, gold, silver, etc.) and the features and User experience varies for each category.
  - How do you pass the user details (category, country, language, etc.) to all the fragments in the application?
- Solution
  - Global Scope and Context
    - JS global scope and context APIs
  - State Management Libraries
    - Create Global state for shared data and local state for each fragment to avoid **tight-coupling**



3

### Auth

- Scenario
  - You want to pass Auth information/status to the cart and payment fragments securely
- Solution
  - OAuth and JWT
    - Use OAuth standards to pass user login information
    - Pass JWT tokens to the fragments from the login component to process with the next applicable steps
  - Headers and Cookies
    - In case of a SSR architecture, leverage HTTP headers and cookies to pass secure information



# Best Practices



## Payload size in Custom Events

- When creating and dispatching custom events, keep the payload size small and pass only 'need-to-know' information.
- Additional data can be fetched exclusively by the destination fragment via API calls
- This prevents tight-coupling of fragments and creates freedom to build self-contained fragments


## Event Bus via Custom Events

- Custom events do not bubble by default and need to be explicitly enabled
- Enable bubbling if the use-case needs a parent to intercept the event to act on it.
- Disable bubbling if the events needs to be dispatched to the immediate parent
- Avoid re-rendering of components while working with event bubbling using memo hooks in react and attribute callback handlers in JS

## Broadcast Channel API

- Evaluate the need of broadcast channel based on the data published to the channel
- Avoid publishing sensitive information to the channel as it is open to subscribe to any and all fragments
- If multiple fragments need the same data with a high frequency of data updates, Publish/Subscribe is a great approach

# Best Practices



# Questions?

