

TraP with Conda

Conda is a tool which lies somewhere between a Virtual Environment and a Virtual Machine. It has advantages over the Python virtualenv – particularly that you can specify which Python you wish to use. These instructions will help you to set up and use TraP with Conda. Once setup, you just need to run step 4 and then you can skip to step 17.

1. Download miniconda to your area using:

```
$ wget https://repo.anaconda.com/miniconda/Miniconda3-latest-Linux-x86_64.sh
```

2. Install miniconda using:

```
$ bash Miniconda3-latest-Linux-x86_64.sh
```

Say yes to all of the questions during install.

Then log out of the system and then log in again to confirm changes.

3. Create a new conda environment called “TraP_env” in python 3.11 using:

```
$ conda create --name TraP_env python=3.11
```

You can specify whatever version of Python you wish. For TraP releases including r5.0 and lower, you need Python 2.7. For TraP releases r6.0 and higher, you want Python 3 – but not versions above 3.11 as they are incompatible with sqlalchemy version 1.4.

4. Activate your Conda environment using:

```
$ conda activate TraP_env
```

5. Install TraP with

```
$ pip install trap
```

6. TraP resources

Code: <https://git.astron.nl/RD/trap>

Docs: <https://transients-pipeline.readthedocs.io/en/latest/>

Paper (TraP): <https://ui.adsabs.harvard.edu/abs/2015A%26C....11...25S/abstract>

Paper (Sourcefinder):

<https://ui.adsabs.harvard.edu/abs/2018A%26C....23...92C/abstract>