
schedulerlib

Release 0

La Sapienza, Università di Roma, Emiliano Casalicchio, Antonino

Apr 24, 2026

CONTENTS:

Add your content using reStructuredText syntax. See the [reStructuredText](#) documentation for details.

API REFERENCE

Python bindings for the Scheduler GP module

class `scheduler.ExprNode`

Bases: `pybind11_object`

A node in the expression tree used by the GP individual

property `children`

List of child nodes

property `constValue`

Constant value if the node is a CONST

property `nodeType`

Type of the node (e.g., ADD, CONST, TERMINAL)

size(*self*: `scheduler.ExprNode`) → int

Get the size of the subtree rooted at this node

property `terminalIndex`

Index of the terminal if the node is a TERMINAL

class `scheduler.FitnessEvaluator`

Bases: `pybind11_object`

Evaluates a population of GP individuals by simulating a greedy schedule with each individual's expression tree as the priority function.

After evaluation every *Individual* in the population will have its `fitness` field set to a scalar value that reflects how well the tree minimised response time and energy consumption.

1.1 Fitness formula

Three raw objectives are collected for each individual:

- `compRatio` – fraction of available jobs that were successfully scheduled (higher is better).
- `meanResp` – average response time (completion - arrival) in minutes (lower is better).
- `energy` – total energy consumed across all satellites in watt- minutes (lower is better).

Each objective is normalised to $[0, 1]$ across the current population so that differences in scale cannot dominate the result. The final fitness is then:

$$f = w_{\text{textjobs}} \cdot \widehat{\text{tr}} - w_{\text{texttime}} \cdot \widehat{\text{att}} - w_{\text{textenergy}} \cdot \widehat{\text{ate}}$$

where

$\widehat{\text{tr}}$ denotes population-normalised values and the default weights are $(0.60, 0.25, 0.15)$.

Example

```
from scheduler import SchedulerGP, FitnessEvaluator, SimulationSnapshot
from scheduler import buildTerminalRegistry

gp = SchedulerGP(satellites, jobs)
gp.initialize(populationSize=100)

eval = FitnessEvaluator(buildTerminalRegistry())

for generation in range(50):
    snap = SimulationSnapshot(current_minute, satellites, jobs)
    eval.evaluate(gp.getPopulation(), snap) # writes fitness in place
    gp.solveNextGeneration()
```

evaluate(*self*: scheduler.FitnessEvaluator, *population*: list[scheduler.Individual], *snap*: scheduler.SimulationSnapshot) → None

Score every individual in *population* and write the result into each individual's **fitness** field.

This is the only method the main GP loop needs to call each generation.

Parameters

- **population** (list[Individual]) – The current GP population, obtained via *SchedulerGP.getPopulation()*. Each individual's **fitness** field is updated in place.
- **snap** (SimulationSnapshot) – Read-only snapshot of the current simulation state. The evaluator runs a fresh greedy simulation for every individual, so **snap** is never modified.

Notes

Fitness values are population-relative: the same tree may receive a different score in a different generation if the rest of the population has changed.

evaluate_single(*self*: scheduler.FitnessEvaluator, *individual*: scheduler.Individual, *snap*: scheduler.SimulationSnapshot) → tuple

Evaluate a single individual and return its raw (un-normalised) objectives.

Useful for inspecting the best individual after evolution has finished.

Parameters

- **individual** (Individual) – The GP individual to evaluate.
- **snap** (SimulationSnapshot) – Simulation snapshot used for the evaluation.

Returns

(comp_ratio, mean_response_time, total_energy)

- **comp_ratio** – fraction of available jobs scheduled [0, 1].
- **mean_response_time** – average (completion - arrival) in minutes.
- **total_energy** – total energy consumed (watt-minutes).

Return type

tuple[float, float, float]

property weightEnergy

Weight applied to the energy-consumption penalty. Default 0.15. Increase this to make the GP prefer energy-efficient satellite assignments.

property weightJobs

Weight applied to the completion-ratio reward term. Default 0.60. Increase this to make the GP prioritise scheduling as many jobs as possible.

property weightTime

Weight applied to the mean-response-time penalty. Default 0.25. Increase this to make the GP prioritise faster job turnaround.

class scheduler.Individual

Bases: pybind11_object

Represents a single candidate solution in the Genetic Programming population

property fitness

Evaluated fitness score

property id

Unique identifier of the individual

property tree

The individual's expression tree root node

class scheduler.Job

Bases: pybind11_object

Represents a job/task to be scheduled

property arrivalTime

When the job originally arrived

property dueMinute

The minute by which the job is due

property durationMinutes

Required duration to complete in minutes

property id

Unique identifier of the job

property initialDeadline

Initial established deadline

property name

Name of the job

property priority

Priority level of the job

property remainingDeadline

Remaining time before the deadline is missed

property taskSize

Size or complexity of the task

class scheduler.NodeType

Bases: pybind11_object

Enum representing the type of operation or value in an expression tree node

Members:

ADD : Addition operator

SUB : Subtraction operator

MUL : Multiplication operator

DIV : Division operator

MAX_OP : Maximum of two values

MIN_OP : Minimum of two values

NEG : Negation operator

ABS : Absolute value operator

INV : Inverse value operator

TERMINAL : Terminal node (variable)

CONST : Constant value node

ABS = <NodeType.ABS: 7>**ADD = <NodeType.ADD: 0>****CONST = <NodeType.CONST: 10>****DIV = <NodeType.DIV: 3>****INV = <NodeType.INV: 8>****MAX_OP = <NodeType.MAX_OP: 4>****MIN_OP = <NodeType.MIN_OP: 5>****MUL = <NodeType.MUL: 2>****NEG = <NodeType.NEG: 6>****SUB = <NodeType.SUB: 1>**

```

TERMINAL = <NodeType.TERMINAL: 9>

NodeType.name -> str

property value

class scheduler.Satellite
    Bases: pybind11_object
    Represents a computing satellite resource
    property ComputingCapability
        Max computing capability of the satellite
    property ComputingLoad
        Current computing load
    property RemainingEnergy
        Remaining energy available for computation
    property activeTasks
        Number of active tasks running on the satellite
    property id
        Unique identifier of the satellite
    property listeningDome
        The listening dome availability state
    property name
        Name of the satellite

class scheduler.SchedulerGP
    Bases: pybind11_object
    Genetic Programming Scheduler Manager
    getPopulation(self: scheduler.SchedulerGP) → list[scheduler.Individual]
        Get the current population of individuals
    initialize(self: scheduler.SchedulerGP, populationSize: int = 200, crossoverRate: float = 0.8,
        mutationRate: float = 0.08, elitismCount: int = 2) → None
        Initialize the GP population with parameters
    printSchedule(self: scheduler.SchedulerGP) → None
        Print the best schedule found so far
    solveNextGeneration(self: scheduler.SchedulerGP) → None
        Evaluate the current population and evolve to the next generation

class scheduler.SimulationSnapshot
    Bases: pybind11_object
    A self-contained, point-in-time snapshot of the simulation world.

    The external application must construct and populate a snapshot before calling FitnessEvaluator.evaluate() for each GP generation. All satellite and job objects are copied into the snapshot, so subsequent changes to the originals have no effect on the evaluator.

```

Example

```
snap = scheduler.SimulationSnapshot(  
    currentMinute = 0.0,  
    satellites    = my_satellites,  
    jobs         = my_jobs,  
    uniformEnergy = 2.5,    # watts per minute per satellite  
)
```

property currentMinute

Simulation clock at snapshot time (minutes from epoch).

property energyPerMinute

Energy consumed per minute of computation, indexed by satellite position in the `satellites` list. When non-empty this overrides `uniformEnergy`. Must have the same length as `satellites` if provided.

property jobs

Pool of jobs available for scheduling at this instant.

property satellites

Current state of every satellite in the constellation.

PYTHON MODULE INDEX

S

`scheduler, ??`

`schedulerlib, ??`