



S5L3Consegna

Report generated by Tenable Nessus™

Wed, 22 Oct 2025 11:40:59 EDT

TABLE OF CONTENTS

Vulnerabilities by Host

• 192.168.50.3.....	4
---------------------	---

Nessus Essentials

Vulnerabilities by Host

192.168.50.3

31

CRITICAL

66

HIGH

83

MEDIUM

16

LOW

103

INFO

Scan Information

Start time: Wed Oct 22 11:30:13 2025

End time: Wed Oct 22 11:40:58 2025

Host Information

Netbios Name: METASPLOITABLE

IP: 192.168.50.3

MAC Address: 08:00:27:04:3F:E1

OS: Linux Kernel 2.6 on Ubuntu 8.04 (hardy)

Vulnerabilities

57603 - Apache 2.2.x < 2.2.13 APR apr_palloc Heap Overflow

Synopsis

The remote web server is affected by a buffer overflow vulnerability.

Description

According to its self-reported banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.13. As such, it includes a bundled version of the Apache Portable Runtime (APR) library that contains a flaw in 'apr_palloc()' that could cause a heap overflow.

Note that the Apache HTTP server itself does not pass unsanitized, user-provided sizes to this function so it could only be triggered through some other application that uses it in a vulnerable way.

See Also

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache 2.2.13 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0556

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.4 (CVSS2#E:U/RL:OF/RC:C)

References

BID	35949
CVE	CVE-2009-2412
XREF	CWE:189

Plugin Information

Published: 2012/01/19, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.13
```

45004 - Apache 2.2.x < 2.2.15 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.15. It is, therefore, potentially affected by multiple vulnerabilities :

- A TLS renegotiation prefix injection attack is possible. (CVE-2009-3555)
- The 'mod_proxy_ajp' module returns the wrong status code if it encounters an error which causes the back-end server to be put into an error state. (CVE-2010-0408)
- The 'mod_isapi' attempts to unload the 'ISAPI.dll' when it encounters various error states which could leave call-backs in an undefined state. (CVE-2010-0425)
- A flaw in the core sub-request process code can lead to sensitive information from a request being handled by the wrong thread if a multi-threaded environment is used. (CVE-2010-0434)
- Added 'mod_reqtimeout' module to mitigate Slowloris attacks. (CVE-2007-6750)

See Also

http://httpd.apache.org/security/vulnerabilities_22.html

https://bz.apache.org/bugzilla/show_bug.cgi?id=48359

https://archive.apache.org/dist/httpd/CHANGES_2.2.15

Solution

Upgrade to Apache version 2.2.15 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

9.0

EPSS Score

0.8796

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	21865
BID	36935
BID	38491
BID	38494
BID	38580
CVE	CVE-2007-6750
CVE	CVE-2009-3555
CVE	CVE-2010-0408
CVE	CVE-2010-0425
CVE	CVE-2010-0434
XREF	Secunia:38776
XREF	CWE:200
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2010/10/20, Modified: 2018/11/15

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.15
```

100995 - Apache 2.2.x < 2.2.33-dev / 2.4.x < 2.4.26 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache running on the remote host is 2.2.x prior to 2.2.33-dev or 2.4.x prior to 2.4.26. It is, therefore, affected by the following vulnerabilities :

- An authentication bypass vulnerability exists due to third-party modules using the `ap_get_basic_auth_pw()` function outside of the authentication phase. An unauthenticated, remote attacker can exploit this to bypass authentication requirements. (CVE-2017-3167)

- A NULL pointer dereference flaw exists due to third-party module calls to the `mod_ssl` `ap_hook_process_connection()` function during an HTTP request to an HTTPS port. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. (CVE-2017-3169)

- A NULL pointer dereference flaw exists in `mod_http2` that is triggered when handling a specially crafted HTTP/2 request. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. Note that this vulnerability does not affect 2.2.x. (CVE-2017-7659)

- An out-of-bounds read error exists in the `ap_find_token()` function due to improper handling of header sequences. An unauthenticated, remote attacker can exploit this, via a specially crafted header sequence, to cause a denial of service condition. (CVE-2017-7668)

- An out-of-bounds read error exists in `mod_mime` due to improper handling of Content-Type response headers. An unauthenticated, remote attacker can exploit this, via a specially crafted Content-Type response header, to cause a denial of service condition or the disclosure of sensitive information. (CVE-2017-7679)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.32

https://archive.apache.org/dist/httpd/CHANGES_2.4.26

https://httpd.apache.org/security/vulnerabilities_22.html

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.2.33-dev / 2.4.26 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6546

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	99132
BID	99134
BID	99135
BID	99137
BID	99170
CVE	CVE-2017-3167
CVE	CVE-2017-3169
CVE	CVE-2017-7659
CVE	CVE-2017-7668
CVE	CVE-2017-7679

Plugin Information

Published: 2017/06/22, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/
Installed version : 2.2.8
```

Fixed version : 2.2.33

101787 - Apache 2.2.x < 2.2.34 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache running on the remote host is 2.2.x prior to 2.2.34. It is, therefore, affected by the following vulnerabilities :

- An authentication bypass vulnerability exists in httpd due to third-party modules using the `ap_get_basic_auth_pw()` function outside of the authentication phase. An unauthenticated, remote attacker can exploit this to bypass authentication requirements. (CVE-2017-3167)
- A denial of service vulnerability exists in httpd due to a NULL pointer dereference flaw that is triggered when a third-party module calls the `mod_ssl ap_hook_process_connection()` function during an HTTP request to an HTTPS port. An unauthenticated, remote attacker can exploit this to cause a denial of service condition. (CVE-2017-3169)
- A denial of service vulnerability exists in httpd due to an out-of-bounds read error in the `ap_find_token()` function that is triggered when handling a specially crafted request header sequence. An unauthenticated, remote attacker can exploit this to crash the service or force `ap_find_token()` to return an incorrect value. (CVE-2017-7668)
- A denial of service vulnerability exists in httpd due to an out-of-bounds read error in the `mod_mime` that is triggered when handling a specially crafted Content-Type response header. An unauthenticated, remote attacker can exploit this to disclose sensitive information or cause a denial of service condition. (CVE-2017-7679)
- A denial of service vulnerability exists in httpd due to a failure to initialize or reset the value placeholder in [Proxy-]Authorization headers of type 'Digest' before or between successive key=value assignments by `mod_auth_digest`. An unauthenticated, remote attacker can exploit this, by providing an initial key with no '=' assignment, to disclose sensitive information or cause a denial of service condition. (CVE-2017-9788)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.34

https://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.34 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6546

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	99134
BID	99135
BID	99137
BID	99170
BID	99569
CVE	CVE-2017-3167
CVE	CVE-2017-3169
CVE	CVE-2017-7668
CVE	CVE-2017-7679
CVE	CVE-2017-9788

Plugin Information

Published: 2017/07/18, Modified: 2018/09/17

Plugin Output

tcp/80/www

```
Source          : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version : 2.2.8
```

Fixed version : 2.2.34

158900 - Apache 2.4.x < 2.4.53 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.53. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.53 advisory.

- mod_lua Use of uninitialized value of in r:parsebody: A carefully crafted request body can cause a read to a random memory area which could cause the process to crash. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Chamal De Silva (CVE-2022-22719)
- HTTP request smuggling: Apache HTTP Server 2.4.52 and earlier fails to close inbound connection when errors are encountered discarding the request body, exposing the server to HTTP Request Smuggling Acknowledgements: James Kettle <james.kettle portswigger.net> (CVE-2022-22720)
- Possible buffer overflow with very large or unlimited LimitXMLRequestBody in core: If LimitXMLRequestBody is set to allow request bodies larger than 350MB (defaults to 1M) on 32 bit systems an integer overflow happens which later causes out of bounds writes. This issue affects Apache HTTP Server 2.4.52 and earlier. Acknowledgements: Anonymous working with Trend Micro Zero Day Initiative (CVE-2022-22721)
- Read/write beyond bounds in mod_sed: Out-of-bounds Write vulnerability in mod_sed of Apache HTTP Server allows an attacker to overwrite heap memory with possibly attacker provided data. This issue affects Apache HTTP Server 2.4 version 2.4.52 and prior versions. Acknowledgements: Ronald Crane (Zippenhop LLC) (CVE-2022-23943)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<http://www.apache.org/dist/httpd/Announcement2.4.html>
https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.53 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

192.168.50.3

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6591

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-22719
CVE	CVE-2022-22720
CVE	CVE-2022-22721
CVE	CVE-2022-23943
XREF	IAVA:2022-A-0124-S

Plugin Information

Published: 2022/03/14, Modified: 2023/11/06

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/
Installed version : 2.2.8
Fixed version  : 2.4.53
```

193421 - Apache 2.4.x < 2.4.54 Authentication Bypass

Synopsis

The remote web server is affected by an authentication bypass vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an authentication bypass vulnerability as referenced in the 2.4.54 advisory.

- X-Forwarded-For dropped by hop-by-hop mechanism in mod_proxy: Apache HTTP Server 2.4.53 and earlier may not send the X-Forwarded-* headers to the origin server based on client side Connection header hop-by-hop mechanism. This may be used to bypass IP based authentication on the origin server/application.

Acknowledgements: The Apache HTTP Server project would like to thank Gaetan Ferry (Synacktiv) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0004

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2022-31813
XREF IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.54
```

161948 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Read beyond bounds via ap_rwrite(): The ap_rwrite() function in Apache HTTP Server 2.4.53 and earlier may read unintended memory if an attacker can cause the server to reflect very large input using ap_rwrite() or ap_rputs(), such as with mod_lua's r:puts() function. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28614)

- Read beyond bounds in ap_strcmp_match(): Apache HTTP Server 2.4.53 and earlier may crash or disclose information due to a read beyond bounds in ap_strcmp_match() when provided with an extremely large input buffer. While no code distributed with the server can be coerced into such a call, third-party modules or lua scripts that use ap_strcmp_match() may hypothetically be affected. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-28615)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.1 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:H)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.0054

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:P)

CVSS v2.0 Temporal Score

4.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-28614
CVE	CVE-2022-28615
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2022/06/08, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/
Installed version : 2.2.8
Fixed version  : 2.4.54
```

170113 - Apache 2.4.x < 2.4.55 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.55. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.55 advisory.

- A carefully crafted If: request header can cause a memory read, or write of a single zero byte, in a pool (heap) memory location beyond the header value sent. This could cause the process to crash. This issue affects Apache HTTP Server 2.4.54 and earlier. (CVE-2006-20001)

- Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.54 and prior versions. (CVE-2022-36760)

- Prior to Apache HTTP Server 2.4.55, a malicious backend can cause the response headers to be truncated early, resulting in some headers being incorporated into the response body. If the later headers have any security purpose, they will not be interpreted by the client. (CVE-2022-37436)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.55 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.8 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

7.3

EPSS Score

0.2314

CVSS v2.0 Base Score

7.6 (CVSS2#AV:N/AC:H/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2006-20001
CVE	CVE-2022-36760
CVE	CVE-2022-37436
XREF	IAVA:2023-A-0047-S

Plugin Information

Published: 2023/01/18, Modified: 2023/03/10

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.55
```

172186 - Apache 2.4.x < 2.4.56 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.56. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.56 advisory.

- HTTP request splitting with mod_rewrite and mod_proxy: Some mod_proxy configurations on Apache HTTP Server versions 2.4.0 through 2.4.55 allow a HTTP Request Smuggling attack. Configurations are affected when mod_proxy is enabled along with some form of RewriteRule or ProxyPassMatch in which a non-specific pattern matches some portion of the user-supplied request-target (URL) data and is then re-inserted into the proxied request-target using variable substitution. For example, something like: RewriteEngine on RewriteRule ^/here/(.*) http://example.com:8080/elsewhere?\$1 http://example.com:8080/elsewhere ; [P] ProxyPassReverse /here/ http://example.com:8080/ http://example.com:8080/ Request splitting/smuggling could result in bypass of access controls in the proxy server, proxying unintended URLs to existing origin servers, and cache poisoning. Acknowledgements: finder: Lars Krapf of Adobe (CVE-2023-25690)

- Apache HTTP Server: mod_proxy_uwsgi HTTP response splitting: HTTP Response Smuggling vulnerability in Apache HTTP Server via mod_proxy_uwsgi. This issue affects Apache HTTP Server: from 2.4.30 through 2.4.55.

Special characters in the origin response header can truncate/split the response forwarded to the client.

Acknowledgements: finder: Dimas Fariski Setyawan Putra (nyxsorcerer) (CVE-2023-27522)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.56 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.7152

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-25690
CVE	CVE-2023-27522
XREF	IAVA:2023-A-0124-S

Plugin Information

Published: 2023/03/07, Modified: 2023/10/21

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/
Installed version : 2.2.8
Fixed version  : 2.4.56
```

153583 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by a vulnerability as referenced in the 2.4.49 changelog.

- A crafted request uri-path can cause mod_proxy to forward the request to an origin server chosen by the remote user. (CVE-2021-40438)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

9.0 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.3 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

8.1

EPSS Score

0.9443

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-40438
XREF	IAVA:2021-A-0440-S
XREF	CISA-KNOWN-EXPLOITED:2021/12/15

Plugin Information

Published: 2021/09/23, Modified: 2023/04/25

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/
Installed version : 2.2.8
Fixed version   : 2.4.49
```

153584 - Apache < 2.4.49 Multiple Vulnerabilities

Synopsis

The remote web server is affected by a vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.49. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.49 changelog.

- ap_escape_quotes() may write beyond the end of a buffer when given malicious input. No included modules pass untrusted data to these functions, but third-party / external modules may. (CVE-2021-39275)
- Malformed requests may cause the server to dereference a NULL pointer. (CVE-2021-34798)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

https://downloads.apache.org/httpd/CHANGES_2.4

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.49 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

7.4

EPSS Score

0.4279

CVSS v2.0 Base Score

192.168.50.3

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-34798
CVE	CVE-2021-39275
XREF	IAVA:2021-A-0440-S

Plugin Information

Published: 2021/09/23, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.49
```

171356 - Apache HTTP Server SEoL (2.1.x <= x <= 2.2.x)

Synopsis

An unsupported version of Apache HTTP Server is installed on the remote host.

Description

According to its version, Apache HTTP Server is between 2.1.x and 2.2.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<https://archive.apache.org/dist/httpd/Announcement2.2.txt>

Solution

Upgrade to a version of Apache HTTP Server that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2023/02/10, Modified: 2024/04/02

Plugin Output

tcp/80/www

```
URL : http://192.168.50.3/
Installed version : 2.2.8
Security End of Life : July 11, 2017
Time since Security End of Life (Est.) : >= 8 years
```

134862 - Apache Tomcat AJP Connector Request Injection (Ghostcat)

Synopsis

There is a vulnerable AJP connector listening on the remote host.

Description

A file read/inclusion vulnerability was found in AJP connector. A remote, unauthenticated attacker could exploit this vulnerability to read web application files from a vulnerable server. In instances where the vulnerable server allows file uploads, an attacker could upload malicious JavaServer Pages (JSP) code within a variety of file types and gain remote code execution (RCE).

See Also

<http://www.nessus.org/u?8ebe6246>
<http://www.nessus.org/u?4e287adb>
<http://www.nessus.org/u?cbc3d54e>
<https://access.redhat.com/security/cve/CVE-2020-1745>
<https://access.redhat.com/solutions/4851251>
<http://www.nessus.org/u?dd218234>
<http://www.nessus.org/u?dd772531>
<http://www.nessus.org/u?2a01d6bf>
<http://www.nessus.org/u?3b5af27e>
<http://www.nessus.org/u?9dab109f>
<http://www.nessus.org/u?5eafc70>

Solution

Update the AJP configuration to require authorization and/or upgrade the Tomcat server to 7.0.100, 8.5.51, 9.0.31 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

8.9

EPSS Score

0.9447

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

CVE	CVE-2020-1745
CVE	CVE-2020-1938
XREF	CISA-KNOWN-EXPLOITED:2022/03/17
XREF	CEA-ID:CEA-2020-0021

Plugin Information

Published: 2020/03/24, Modified: 2025/10/16

Plugin Output

tcp/8009/ajp13

Nessus was able to exploit the issue using the following request :

```
0x0000: 02 02 00 08 48 54 54 50 2F 31 2E 31 00 00 0F 2F    ....HTTP/1.1.../
0x0010: 61 73 64 66 2F 78 78 78 78 2E 6A 73 70 00 00    asdf/xxxxx.jsp..
0x0020: 09 6C 6F 63 61 6C 68 6F 73 74 00 FF FF 00 09 6C    .localhost.....l
0x0030: 6F 63 61 6C 68 6F 73 74 00 00 50 00 00 09 A0 06    ocalhost..P.....
0x0040: 00 0A 6B 65 65 70 2D 61 6C 69 76 65 00 00 0F 41    ..keep-alive...A
0x0050: 63 63 65 70 74 2D 4C 61 6E 67 75 61 67 65 00 00    ccept-Language..
0x0060: 0E 65 6E 2D 55 53 2C 65 6E 3B 71 3D 30 2E 35 00    .en-US,en;q=0.5.
0x0070: A0 08 00 01 30 00 00 0F 41 63 63 65 70 74 2D 45    ....0...Accept-E
0x0080: 6E 63 6F 64 69 6E 67 00 00 13 67 7A 69 70 2C 20    ncoding...gzip,
0x0090: 64 65 66 6C 61 74 65 2C 20 73 64 63 68 00 00 0D    deflate, sdch...
0x00A0: 43 61 63 68 65 2D 43 6F 6E 74 72 6F 6C 00 00 09    Cache-Control...
0x00B0: 6D 61 78 2D 61 67 65 3D 30 00 A0 0E 00 07 4D 6F    max-age=0.....Mo
0x00C0: 7A 69 6C 6C 61 00 00 19 55 70 67 72 61 64 65 2D    zilla...Upgrade-
0x00D0: 49 6E 73 65 63 75 72 65 2D 52 65 71 75 65 73 74    Insecure-Request
0x00E0: 73 00 00 01 31 00 A0 01 00 09 74 65 78 74 2F 68    s...1.....text/h
0x00F0: 74 6D 6C 00 A0 0B 00 09 6C 6F 63 61 6C 68 6F 73    tml.....localhos
0x0100: 74 00 0A 00 21 6A 61 76 61 78 2E 73 65 72 76 6C    t...!javax.servl
0x0110: 65 74 2E 69 6E 63 6C 75 64 65 2E 72 65 71 75 65    et.include.reque
0x0120: 73 74 5F 75 72 69 00 00 01 31 00 0A 00 1F 6A 61    st_uri...1....ja
0x0130: 76 61 78 2E 73 65 72 76 6C 65 74 2E 69 6E 63 6C    vax.servlet.incl
0x0140: 75 64 65 2E 70 61 74 68 5F 69 6E 66 6F 00 00 0F    ude.path_info...
0x0150: 57 45 42 2D 49 4E 46 2F 77 65 62 2E 78 6D 6C 00    WEB-INF/web.xml.
0x0160: 0A 00 22 6A 61 76 61 78 2E 73 65 72 76 6C 65 74    .."javax.servlet
0x0170: 2E 69 6E 63 6C 75 64 65 2E 73 65 72 76 6C 65 74    .include.servlet
0x0180: 5F 70 61 74 68 00 00 00 00 FF                    _path.....
```

This produced the following truncated output (limite [...])

201352 - Canonical Ubuntu Linux SEoL (8.04.x)

Synopsis

An unsupported version of Canonical Ubuntu Linux is installed on the remote host.

Description

According to its version, Canonical Ubuntu Linux is 8.04.x. It is, therefore, no longer maintained by its vendor or provider.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it may contain security vulnerabilities.

See Also

<http://www.nessus.org/u?3bdb2d2e>

Solution

Upgrade to a version of Canonical Ubuntu Linux that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2024/07/03, Modified: 2025/03/26

Plugin Output

tcp/80/www

```
OS : Ubuntu Linux 8.04
Security End of Life : May 9, 2013
Time since Security End of Life (Est.) : >= 12 years
```


32314 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness

Synopsis

The remote SSH host keys are weak.

Description

The remote SSH host key has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to set up decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

VPR Score

5.1

EPSS Score

0.0165

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/14, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

32321 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

Synopsis

The remote SSL certificate uses a weak key.

Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

VPR Score

5.1

EPSS Score

0.0165

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

tcp/25/smtp

32321 - Debian OpenSSH/OpenSSL Package Random Number Generator Weakness (SSL check)

Synopsis

The remote SSL certificate uses a weak key.

Description

The remote x509 certificate on the remote SSL server has been generated on a Debian or Ubuntu system which contains a bug in the random number generator of its OpenSSL library.

The problem is due to a Debian packager removing nearly all sources of entropy in the remote version of OpenSSL.

An attacker can easily obtain the private part of the remote key and use this to decipher the remote session or set up a man in the middle attack.

See Also

<http://www.nessus.org/u?107f9bdc>

<http://www.nessus.org/u?f14f4224>

Solution

Consider all cryptographic material generated on the remote host to be guessable. In particular, all SSH, SSL and OpenVPN key material should be re-generated.

Risk Factor

Critical

VPR Score

5.1

EPSS Score

0.0165

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	29179
CVE	CVE-2008-0166
XREF	CWE:310

Exploitable With

Core Impact (true)

Plugin Information

Published: 2008/05/15, Modified: 2020/11/16

Plugin Output

tcp/5432/postgresql

86072 - ISC BIND Unsupported Version Detection

Synopsis

The remote host is running an unsupported version of ISC BIND.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is 9.8.x or earlier. It is, therefore, no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

Solution

Upgrade to a version of ISC BIND that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0541

Plugin Information

Published: 2015/09/22, Modified: 2021/02/16

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version      : 9.11, 9.16, 9.17 or higher
End of Support URL: https://www.isc.org/downloads/
```

10544 - Linux Multiple statd Packages Remote Format String

Synopsis

The remote service is vulnerable to a buffer overflow.

Description

The remote statd service could be brought down with a format string attack - it now needs to be restarted manually.

This means that an attacker may execute arbitrary code thanks to a bug in this daemon.

See Also

<https://seclists.org/bugtraq/2000/Jul/206>

Solution

Upgrade to the latest version of rpc.statd.

Risk Factor

Critical

VPR Score

8.9

EPSS Score

0.3457

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.7 (CVSS2#E:H/RL:OF/RC:C)

References

BID	1480
CVE	CVE-2000-0666
CVE	CVE-2000-0800

Plugin Information

192.168.50.3

Plugin Output

udp/53037/rpc-status

The remote statd service may be vulnerable to a format string attack.

This means that an attacker may execute arbitrary code thanks to a bug in this daemon.

Only older versions of statd under Linux are affected by this problem.

*** Nessus reports this vulnerability using only information that was gathered.

*** Use caution when testing without safe checks enabled.

90022 - OpenSSH < 7.2 Untrusted X11 Forwarding Fallback Security Bypass

Synopsis

The SSH server running on the remote host is affected by a security bypass vulnerability.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.2. It is, therefore, affected by a security bypass vulnerability due to a flaw in ssh(1) that is triggered when it falls back from untrusted X11 forwarding to trusted forwarding when the SECURITY extension is disabled by the X server. This can result in untrusted X11 connections that can be exploited by a remote attacker.

See Also

<http://www.openssh.com/txt/release-7.2>

Solution

Upgrade to OpenSSH version 7.2 or later.

Risk Factor

High

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0218

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-1908

Plugin Information

Published: 2016/03/18, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.2
```

178910 - OpenSSH < 9.3p2 Vulnerability

Synopsis

The SSH server running on the remote host is affected by a vulnerability.

Description

The version of OpenSSH installed on the remote host is prior to 9.3p2. It is, therefore, affected by a vulnerability as referenced in the release-9.3p2 advisory.

- Fix CVE-2023-38408 - a condition where specific libraries loaded via ssh-agent(1)'s PKCS#11 support could be abused to achieve remote code execution via a forwarded agent socket if the following (openssh-9.3p2-1)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.openssh.com/txt/release-9.3p2>

Solution

Upgrade to OpenSSH 9.3p2 / 9.4 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.6478

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.8 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE CVE-2023-38408

Plugin Information

Published: 2023/07/26, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 9.3p2 / 9.4
```

58987 - PHP Unsupported Version Detection

Synopsis

The remote host contains an unsupported version of a web application scripting language.

Description

According to its version, the installation of PHP on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

See Also

<http://php.net/eol.php>

<https://wiki.php.net/rfc/releaseprocess>

Solution

Upgrade to a version of PHP that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0581

Plugin Information

Published: 2012/05/04, Modified: 2024/11/22

Plugin Output

tcp/80/www

```
Source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version : 5.2.4-2ubuntu5.10
```

End of support date : 2011/01/06
Announcement : <http://php.net/eol.php>
Supported versions : 8.1.x / 8.2.x / 8.3.x

63347 - PostgreSQL Unsupported Version Detection

Synopsis

The remote host is running an unsupported version of a database server.

Description

According to its self-reported version number, the installation of PostgreSQL on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

See Also

<https://www.postgresql.org/support/versioning/>

Solution

Upgrade to a version of PostgreSQL that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0583

Plugin Information

Published: 2012/12/28, Modified: 2025/07/15

Plugin Output

tcp/5432/postgresql

```
Version source      :  
Installed version   : 8.3.8
```


Supported versions : 13 / 14 / 15 / 16 / 17

20007 - SSL Version 2 and 3 Protocol Detection

Synopsis

The remote service encrypts traffic using a protocol with known weaknesses.

Description

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

See Also

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

Solution

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2005/10/12, Modified: 2022/04/04

Plugin Output

tcp/25/smtp

- SSLv2 is enabled and the server supports at least one cipher.

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-RC2-CBC-MD5		RSA (512)	RSA	RC2-CBC (40)	MD5
export					
EXP-RC4-MD5		RSA (512)	RSA	RC4 (40)	MD5
export					

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
DES-CBC3-MD5		RSA	RSA	3DES-CBC (168)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
RC4-MD5		RSA	RSA	RC4 (128)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

- SSLv3 is enabled and the server supports at least one cipher.

Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-EDH-RSA-DES-CBC-SHA		DH (512)	RSA	DES-CBC (40)	
SHA1 export					
EDH-RSA-DES-CBC-SHA		DH	RSA	DES-CBC (56)	SHA
[...]					

20007 - SSL Version 2 and 3 Protocol Detection

Synopsis

The remote service encrypts traffic using a protocol with known weaknesses.

Description

The remote service accepts connections encrypted using SSL 2.0 and/or SSL 3.0. These versions of SSL are affected by several cryptographic flaws, including:

- An insecure padding scheme with CBC ciphers.
- Insecure session renegotiation and resumption schemes.

An attacker can exploit these flaws to conduct man-in-the-middle attacks or to decrypt communications between the affected service and clients.

Although SSL/TLS has a secure means for choosing the highest supported version of the protocol (so that these versions will be used only if the client or server support nothing better), many web browsers implement this in an unsafe way that allows an attacker to downgrade a connection (such as in POODLE). Therefore, it is recommended that these protocols be disabled entirely.

NIST has determined that SSL 3.0 is no longer acceptable for secure communications. As of the date of enforcement found in PCI DSS v3.1, any version of SSL will not meet the PCI SSC's definition of 'strong cryptography'.

See Also

<https://www.schneier.com/academic/paperfiles/paper-ssl.pdf>

<http://www.nessus.org/u?b06c7e95>

<http://www.nessus.org/u?247c4540>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<http://www.nessus.org/u?5d15ba70>

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://tools.ietf.org/html/rfc7507>

<https://tools.ietf.org/html/rfc7568>

Solution

Consult the application's documentation to disable SSL 2.0 and 3.0.

Use TLS 1.2 (with approved cipher suites) or higher instead.

Risk Factor

Critical

CVSS v3.0 Base Score

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2005/10/12, Modified: 2022/04/04

Plugin Output

tcp/5432/postgresql

- SSLv3 is enabled and the server supports at least one cipher.
Explanation: TLS 1.0 and SSL 3.0 cipher suites may be used with SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA		DH	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA		RSA	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA		DH	RSA	AES-CBC (128)	
SHA1					
DHE-RSA-AES256-SHA		DH	RSA	AES-CBC (256)	
SHA1					
AES128-SHA		RSA	RSA	AES-CBC (128)	
SHA1					
AES256-SHA		RSA	RSA	AES-CBC (256)	
SHA1					
RC4-SHA		RSA	RSA	RC4 (128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

58662 - Samba 3.x < 3.6.4 / 3.5.14 / 3.4.16 RPC Multiple Buffer Overflows

Synopsis

The remote Samba server is affected by multiple buffer overflow vulnerabilities.

Description

According to its banner, the version of Samba 3.x running on the remote host is earlier than 3.6.4 / 3.5.14 / 3.4.16. It is, therefore, affected by multiple heap-based buffer overflow vulnerabilities.

An error in the DCE/RPC IDL (PIDL) compiler causes the RPC handling code it generates to contain multiple heap-based buffer overflow vulnerabilities. This generated code can allow a remote, unauthenticated attacker to use malicious RPC calls to crash the application and possibly execute arbitrary code as the root user.

Note that Nessus has not actually tried to exploit this issue or otherwise determine if one of the associated patches has been applied.

See Also

<https://www.zerodayinitiative.com/advisories/ZDI-12-061/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-062/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-063/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-064/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-068/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-069/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-070/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-071/>
<https://www.zerodayinitiative.com/advisories/ZDI-12-072/>
<https://www.samba.org/samba/security/CVE-2012-1182.html>
<https://www.samba.org/samba/history/samba-3.6.4.html>
<https://www.samba.org/samba/history/samba-3.5.14.html>
<https://www.samba.org/samba/history/samba-3.4.16.html>
<https://www.samba.org/samba/history/security.html>

Solution

Either install the appropriate patch referenced in the project's advisory or upgrade to 3.6.4 / 3.5.14 / 3.4.16 or later.

Risk Factor

Critical

VPR Score

7.4

EPSS Score

0.7817

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID	52973
CVE	CVE-2012-1182
XREF	ZDI:ZDI-12-061
XREF	ZDI:ZDI-12-062
XREF	ZDI:ZDI-12-063
XREF	ZDI:ZDI-12-064
XREF	ZDI:ZDI-12-068
XREF	ZDI:ZDI-12-069
XREF	ZDI:ZDI-12-070
XREF	ZDI:ZDI-12-071
XREF	ZDI:ZDI-12-072

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2012/04/11, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.6.4 / 3.5.14 / 3.4.16
```

25217 - Samba < 3.0.25 Multiple Vulnerabilities

Synopsis

The remote Samba server is affected by multiple vulnerabilities.

Description

According to its banner, the version of the Samba server installed on the remote host is affected by multiple buffer overflow and remote command injection vulnerabilities, which can be exploited remotely, as well as a local privilege escalation bug.

See Also

<http://www.samba.org/samba/security/CVE-2007-2444.html>

<http://www.samba.org/samba/security/CVE-2007-2446.html>

<http://www.samba.org/samba/security/CVE-2007-2447.html>

Solution

Upgrade to Samba version 3.0.25 or later.

Risk Factor

Critical

VPR Score

7.4

EPSS Score

0.8178

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID 23972

BID 23973

BID 23974

BID	24195
BID	24196
BID	24197
BID	24198
CVE	CVE-2007-2444
CVE	CVE-2007-2446
CVE	CVE-2007-2447

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2007/05/15, Modified: 2018/07/27

Plugin Output

tcp/445/cifs

169505 - Samba < 4.15.13 / 4.16.x < 4.16.8 / 4.17.x < 4.17.4 Multiple Vulnerabilities

Synopsis

The remote Samba server is potentially affected by multiple vulnerabilities.

Description

The version of Samba running on the remote host is prior to 4.15.13, 4.16.x prior to 4.16.8, or 4.17.x prior to 4.17.4. It is, therefore, affected by multiple vulnerabilities:

- Windows Kerberos RC4-HMAC Elevation of Privilege Vulnerability. (CVE-2022-37966, CVE-2022-45141)
- Windows Kerberos Elevation of Privilege Vulnerability. (CVE-2022-37967)
- Netlogon RPC Elevation of Privilege Vulnerability. (CVE-2022-38023)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.samba.org/samba/history/security.html>

<https://www.samba.org/samba/security/CVE-2022-38023.html>

<https://www.samba.org/samba/security/CVE-2022-37966.html>

<https://www.samba.org/samba/security/CVE-2022-37967.html>

<https://www.samba.org/samba/security/CVE-2022-45141.html>

Solution

Upgrade to Samba version 4.15.13, 4.16.8, or 4.17.4 or later.

Risk Factor

Critical

CVSS v3.0 Base Score

9.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

9.1 (CVSS:3.0/E:F/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0155

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-37966
CVE	CVE-2022-37967
CVE	CVE-2022-38023
CVE	CVE-2022-45141
XREF	IAVA:2023-A-0004-S

Plugin Information

Published: 2023/01/04, Modified: 2023/09/11

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 4.15.13
```

76314 - Samba Unsupported Version Detection

Synopsis

The remote host contains an unsupported version of Samba.

Description

According to its self-reported version number, the installation of Samba on the remote host is no longer supported.

Lack of support implies that no new security patches for the product will be released by the vendor. As a result, it is likely to contain security vulnerabilities.

See Also

https://wiki.samba.org/index.php/Samba_Release_Planning

Solution

Upgrade to a version of Samba that is currently supported.

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0593

Plugin Information

Published: 2014/06/30, Modified: 2020/09/22

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
EOL date         : 2009/08/05
```

EOL URL : https://wiki.samba.org/index.php/Samba_Release_Planning
Supported version : 4.6.x / 4.7.x / 4.8.x

46882 - UnrealIRCd Backdoor Detection

Synopsis

The remote IRC server contains a backdoor.

Description

The remote IRC server is a version of UnrealIRCd with a backdoor that allows an attacker to execute arbitrary code on the affected host.

See Also

<https://seclists.org/fulldisclosure/2010/Jun/277>

<https://seclists.org/fulldisclosure/2010/Jun/284>

<http://www.unrealircd.com/txt/unrealsecadvisory.20100612.txt>

Solution

Re-download the software, verify it using the published MD5 / SHA1 checksums, and re-install it.

Risk Factor

Critical

VPR Score

7.4

EPSS Score

0.868

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

References

BID 40820

CVE CVE-2010-2075

Exploitable With

192.168.50.3

CANVAS (true) Metasploit (true)

Plugin Information

Published: 2010/06/14, Modified: 2022/04/11

Plugin Output

tcp/6667

```
The remote IRC server is running as :  
uid=0 (root) gid=0 (root)
```

61708 - VNC Server 'password' Password

Synopsis

A VNC server running on the remote host is secured with a weak password.

Description

The VNC server running on the remote host is secured with a weak password. Nessus was able to login using VNC authentication and a password of 'password'. A remote, unauthenticated attacker could exploit this to take control of the system.

Solution

Secure the VNC service with a strong password.

Risk Factor

Critical

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

Plugin Information

Published: 2012/08/29, Modified: 2015/09/24

Plugin Output

tcp/5900/vnc

```
Nessus logged in using a password of "password".
```


40467 - Apache 2.2.x < 2.2.12 Multiple Vulnerabilities

Synopsis

The remote web server may be affected by several issues.

Description

According to its banner, the version of Apache 2.2.x. running on the remote host is prior to 2.2.12. It is, therefore, affected by the following vulnerabilities :

- A heap-based buffer underwrite flaw exists in the function 'apr_strmatch_precompile()' in the bundled copy of the APR-util library, which could be triggered when parsing configuration data to crash the daemon. (CVE-2009-0023)
- A flaw in the mod_proxy_ajp module in version 2.2.11 only may allow a remote attacker to obtain sensitive response data intended for a client that sent an earlier POST request with no request body. (CVE-2009-1191)
- The server does not limit the use of directives in a .htaccess file as expected based on directives such as 'AllowOverride' and 'Options' in the configuration file, which could enable a local user to bypass security restrictions. (CVE-2009-1195)
- Failure to properly handle an amount of streamed data that exceeds the Content-Length value allows a remote attacker to force a proxy process to consume CPU time indefinitely when mod_proxy is used in a reverse proxy configuration. (CVE-2009-1890)
- Failure of mod_deflate to stop compressing a file when the associated network connection is closed may allow a remote attacker to consume large amounts of CPU if there is a large (>10 MB) file available that has mod_deflate enabled. (CVE-2009-1891)
- Using a specially crafted XML document with a large number of nested entities, a remote attacker may be able to consume an excessive amount of memory due to a flaw in the bundled expat XML parser used by the mod_dav and mod_dav_svn modules. (CVE-2009-1955)
- There is an off-by-one overflow in the function 'apr_brigade_vprintf()' in the bundled copy of the APR-util library in the way it handles a variable list of arguments, which could be leveraged on big-endian platforms to perform information disclosure or denial of service attacks. (CVE-2009-1956)

Note that Nessus has relied solely on the version in the Server response header and did not try to check for the issues themselves or even whether the affected modules are in use.

See Also

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.12 or later. Alternatively, ensure that the affected modules / directives are not in use.

Risk Factor

High

CVSS v3.0 Base Score

8.2 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:H)

CVSS v3.0 Temporal Score

7.8 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

6.4

EPSS Score

0.2152

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

6.8 (CVSS2#E:H/RL:OF/RC:C)

References

BID	34663
BID	35115
BID	35221
BID	35251
BID	35253
BID	35565
BID	35623
CVE	CVE-2009-0023
CVE	CVE-2009-1191
CVE	CVE-2009-1195
CVE	CVE-2009-1890
CVE	CVE-2009-1891
CVE	CVE-2009-1955
CVE	CVE-2009-1956
XREF	CWE:16
XREF	CWE:20
XREF	CWE:119
XREF	CWE:189
XREF	CWE:399

Plugin Information

Published: 2009/08/02, Modified: 2020/04/27

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.12
```

42052 - Apache 2.2.x < 2.2.14 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.14. It is, therefore, potentially affected by multiple vulnerabilities :

- Faulty error handling in the Solaris pollset support could lead to a denial of service. (CVE-2009-2699)

- The 'mod_proxy_ftp' module allows remote attackers to bypass intended access restrictions. (CVE-2009-3095)

- The 'ap_proxy_ftp_handler' function in 'modules/proxy/proxy_ftp.c' in the 'mod_proxy_ftp' module allows remote FTP servers to cause a denial of service. (CVE-2009-3094)

Note that the remote web server may not actually be affected by these vulnerabilities as Nessus did not try to determine whether the affected modules are in use or check for the issues themselves.

See Also

<http://www.securityfocus.com/advisories/17947>

<http://www.securityfocus.com/advisories/17959>

<http://www.nessus.org/u?e470f137>

https://bz.apache.org/bugzilla/show_bug.cgi?id=47645

<http://www.nessus.org/u?c34c4eda>

Solution

Upgrade to Apache version 2.2.14 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.4 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0873

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	36254
BID	36260
BID	36596
CVE	CVE-2009-2699
CVE	CVE-2009-3094
CVE	CVE-2009-3095
XREF	Secunia:36549
XREF	CWE:119
XREF	CWE:264

Plugin Information

Published: 2009/10/07, Modified: 2018/11/15

Plugin Output

tcp/80/www

```
Version source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version : 2.2.8
Fixed version    : 2.2.14
```

62101 - Apache 2.2.x < 2.2.23 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.23. It is, therefore, potentially affected by the following vulnerabilities :

- The utility 'apachectl' can receive a zero-length directory name in the LD_LIBRARY_PATH via the 'envvars' file. A local attacker with access to that utility could exploit this to load a malicious Dynamic Shared Object (DSO), leading to arbitrary code execution.

(CVE-2012-0883)

- An input validation error exists related to 'mod_negotiation', 'Multiviews' and untrusted uploads that can allow cross-site scripting attacks.

(CVE-2012-2687)

Note that Nessus has not tested for these flaws but has instead relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.23

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.23 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.0 (CVSS:3.0/AV:L/AC:H/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0732

CVSS v2.0 Base Score

6.9 (CVSS2#AV:L/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.1 (CVSS2#E:U/RL:OF/RC:C)

References

BID	53046
BID	55131
CVE	CVE-2012-0883
CVE	CVE-2012-2687
XREF	CWE:20
XREF	CWE:74
XREF	CWE:79
XREF	CWE:442
XREF	CWE:629
XREF	CWE:711
XREF	CWE:712
XREF	CWE:722
XREF	CWE:725
XREF	CWE:750
XREF	CWE:751
XREF	CWE:800
XREF	CWE:801
XREF	CWE:809
XREF	CWE:811
XREF	CWE:864
XREF	CWE:900
XREF	CWE:928
XREF	CWE:931
XREF	CWE:990

Plugin Information

Published: 2012/09/14, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.23
```


77531 - Apache 2.2.x < 2.2.28 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.28. It is, therefore, affected by the following vulnerabilities :

- A flaw exists within the 'mod_headers' module which allows a remote attacker to inject arbitrary headers. This is done by placing a header in the trailer portion of data being sent using chunked transfer encoding. (CVE-2013-5704)
- A flaw exists within the 'mod_deflate' module when handling highly compressed bodies. Using a specially crafted request, a remote attacker can exploit this to cause a denial of service by exhausting memory and CPU resources. (CVE-2014-0118)
- The 'mod_status' module contains a race condition that can be triggered when handling the scoreboard. A remote attacker can exploit this to cause a denial of service, execute arbitrary code, or obtain sensitive credential information. (CVE-2014-0226)
- The 'mod_cgid' module lacks a time out mechanism. Using a specially crafted request, a remote attacker can use this flaw to cause a denial of service by causing child processes to linger indefinitely, eventually filling up the scoreboard. (CVE-2014-0231)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.zerodayinitiative.com/advisories/ZDI-14-236/>
https://archive.apache.org/dist/httpd/CHANGES_2.2.29
http://httpd.apache.org/security/vulnerabilities_22.html
<http://swende.se/blog/HTTPChunked.html>

Solution

Upgrade to Apache version 2.2.29 or later.

Note that version 2.2.28 was never officially released.

Risk Factor

Medium

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.6 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.7557

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	66550
BID	68678
BID	68742
BID	68745
CVE	CVE-2013-5704
CVE	CVE-2014-0118
CVE	CVE-2014-0226
CVE	CVE-2014-0231
XREF	EDB-ID:34133

Plugin Information

Published: 2014/09/04, Modified: 2020/04/27

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.29
```

96450 - Apache 2.2.x < 2.2.32 Multiple Vulnerabilities (httpoxy)

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache running on the remote host is 2.2.x prior to 2.2.32. It is, therefore, affected by the following vulnerabilities :

- The Apache HTTP Server is affected by a man-in-the-middle vulnerability known as 'httpoxy' due to a failure to properly resolve namespace conflicts in accordance with RFC 3875 section 4.1.18. The HTTP_PROXY environment variable is set based on untrusted user data in the 'Proxy' header of HTTP requests. The HTTP_PROXY environment variable is used by some web client libraries to specify a remote proxy server. An unauthenticated, remote attacker can exploit this, via a crafted 'Proxy' header in an HTTP request, to redirect an application's internal HTTP traffic to an arbitrary proxy server where it may be observed or manipulated.

(CVE-2016-5387)

- A flaw exists due to improper handling of whitespace patterns in user-agent headers. An unauthenticated, remote attacker can exploit this, via a specially crafted user-agent header, to cause the program to incorrectly process sequences of requests, resulting in interpreting responses incorrectly, polluting the cache, or disclosing the content from one request to a second downstream user-agent. (CVE-2016-8743)

- A CRLF injection allowing HTTP response splitting attacks for sites which use mod_userdir (CVE-2016-4975)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://httpd.apache.org/dev/dist/Announcement2.2.html>

http://httpd.apache.org/security/vulnerabilities_22.html

<https://github.com/apache/httpd/blob/2.2.x/CHANGES>

<https://www.apache.org/security/asf-httpoxy-response.txt>

<https://httpoxy.org>

Solution

Upgrade to Apache version 2.2.32 or later.

Note that the 'httpoxy' vulnerability can be mitigated by applying the workarounds or patches as referenced in the vendor advisory asf-httpoxy-response.txt.

Risk Factor

Medium

CVSS v3.0 Base Score

8.1 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.1 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.775

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	91816
BID	95077
BID	105093
CVE	CVE-2016-4975
CVE	CVE-2016-5387
CVE	CVE-2016-8743
XREF	CERT:797896

Plugin Information

Published: 2017/01/12, Modified: 2019/03/27

Plugin Output

tcp/80/www

```
Source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version : 2.2.8
Fixed version  : 2.2.32
```

193422 - Apache 2.4.x < 2.4.54 HTTP Request Smuggling Vulnerability

Synopsis

The remote web server is affected by a HTTP request smuggling vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by a http request smuggling vulnerability as referenced in the 2.4.54 advisory.

- Possible request smuggling in mod_proxy_ajp: Inconsistent Interpretation of HTTP Requests ('HTTP Request Smuggling') vulnerability in mod_proxy_ajp of Apache HTTP Server allows an attacker to smuggle requests to the AJP server it forwards requests to. This issue affects Apache HTTP Server Apache HTTP Server 2.4 version 2.4.53 and prior versions. Acknowledgements: Richter Z @ 360 Noah Lab

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.3347

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-26377
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.54
```

193423 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of Service mod_sed: If Apache HTTP Server 2.4.53 is configured to do transformations with mod_sed in contexts where the input to mod_sed may be very large, mod_sed may make excessively large memory allocations and trigger an abort. Acknowledgements: This issue was found by Brian Moussalli from the JFrog Security Research team

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.1508

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-30522
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.54
```


193424 - Apache 2.4.x < 2.4.54 Multiple Vulnerabilities (mod_lua)

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.54 advisory.

- Denial of service in mod_lua r:parsebody: In Apache HTTP Server 2.4.53 and earlier, a malicious request to a lua script that calls r:parsebody(0) may cause a denial of service due to no default limit on possible input size. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-29404)

- Information Disclosure in mod_lua with websockets: Apache HTTP Server 2.4.53 and earlier may return lengths to applications calling r:wsread() that point past the end of the storage allocated for the buffer.

Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue (CVE-2022-30556)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0139

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-29404
CVE	CVE-2022-30556
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/
Installed version : 2.2.8
Fixed version  : 2.4.54
```

183391 - Apache 2.4.x < 2.4.58 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- Apache HTTP Server: DoS in HTTP/2 with initial windows size 0: An attacker, opening a HTTP/2 connection with an initial window size of 0, was able to block handling of that connection indefinitely in Apache HTTP Server. This could be used to exhaust worker resources in the server, similar to the well known slow loris attack pattern. This has been fixed in version 2.4.58, so that such connection are terminated properly after the configured connection timeout. This issue affects Apache HTTP Server: from 2.4.55 through 2.4.57. Users are recommended to upgrade to version 2.4.58, which fixes the issue.

Acknowledgements: (CVE-2023-43622)

- Apache HTTP Server: HTTP/2 stream memory not reclaimed right away on RST: When a HTTP/2 stream was reset (RST frame) by a client, there was a time window where the request's memory resources were not reclaimed immediately. Instead, de-allocation was deferred to connection close. A client could send new requests and resets, keeping the connection busy and open and causing the memory footprint to keep on growing. On connection close, all resources were reclaimed, but the process might run out of memory before that. This was found by the reporter during testing of CVE-2023-44487 (HTTP/2 Rapid Reset Exploit) with their own test client. During normal HTTP/2 use, the probability to hit this bug is very low. The kept memory would not become noticeable before the connection closes or times out. Users are recommended to upgrade to version 2.4.58, which fixes the issue. Acknowledgements: (CVE-2023-45802)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.569

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2023-43622
CVE CVE-2023-45802
XREF IAVA:2023-A-0572-S

Plugin Information

Published: 2023/10/19, Modified: 2024/04/29

Plugin Output

tcp/80/www

```
URL : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version : 2.4.58
```

193419 - Apache 2.4.x < 2.4.58 Out-of-Bounds Read (CVE-2023-31122)

Synopsis

The remote web server is affected by an out-of-bounds read vulnerability.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.58. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.58 advisory.

- mod_macro buffer over-read: Out-of-bounds Read vulnerability in mod_macro of Apache HTTP Server. This issue affects Apache HTTP Server: through 2.4.57.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.58 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0035

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-31122
XREF	IAVA:2023-A-0572-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/29

Plugin Output

tcp/80/www

```
URL          : http://192.168.50.3/
Installed version : 2.2.8
Fixed version  : 2.4.58
```

192923 - Apache 2.4.x < 2.4.59 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

The version of Apache httpd installed on the remote host is prior to 2.4.59. It is, therefore, affected by multiple vulnerabilities as referenced in the 2.4.59 advisory.

- Apache HTTP Server: HTTP Response Splitting in multiple modules: HTTP Response splitting in multiple modules in Apache HTTP Server allows an attacker that can inject malicious response headers into backend applications to cause an HTTP desynchronization attack. Users are recommended to upgrade to version 2.4.59, which fixes this issue. Acknowledgements: (CVE-2024-24795)

- Apache HTTP Server: HTTP/2 DoS by memory exhaustion on endless continuation frames: HTTP/2 incoming headers exceeding the limit are temporarily buffered in nghttp2 in order to generate an informative HTTP 413 response. If a client does not stop sending headers, this leads to memory exhaustion.

Acknowledgements: finder: Bartek Nowotarski (<https://nowotarski.info/>) (CVE-2024-27316)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

Solution

Upgrade to Apache version 2.4.59 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.8936

CVSS v2.0 Base Score

192.168.50.3

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-38709
CVE	CVE-2024-24795
CVE	CVE-2024-27316
XREF	IAVA:2024-A-0202-S

Plugin Information

Published: 2024/04/04, Modified: 2024/07/12

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/
Installed version : 2.2.8
Fixed version   : 2.4.59
```


35450 - DNS Server Spoofed Request Amplification DDoS

Synopsis

The remote DNS server could be used in a distributed denial of service attack.

Description

The remote DNS server answers to any request. It is possible to query the name servers (NS) of the root zone ('.') and get an answer that is bigger than the original request. By spoofing the source IP address, a remote attacker can leverage this 'amplification' to launch a denial of service attack against a third-party host using the remote DNS server.

See Also

<https://isc.sans.edu/diary/DNS+queries+for+/5713>

Solution

Restrict access to your DNS server from public network or reconfigure it to reject such queries.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

VPR Score

3.6

EPSS Score

0.3479

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2006-0987

Plugin Information

Published: 2009/01/22, Modified: 2023/10/27

Plugin Output

udp/53/dns

```
The DNS query was 17 bytes long, the answer is 508 bytes long.
```

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the instance of ISC BIND 9 running on the remote name server is 9.9.x prior to 9.9.9-P5 or 9.9.9-S7, 9.10.x prior to 9.10.4-P5, or 9.11.x prior to 9.11.0-P2. It is, therefore, affected by multiple denial of service vulnerabilities :

- A denial of service vulnerability exists in named due to a flaw that is triggered during the handling of a specially crafted answer packet in a response to an RTYPE ANY query. An unauthenticated, remote attacker can exploit this to cause an assertion failure and daemon exit. Note that this vulnerability affects versions 9.4.0 to 9.6-ESV-R11-W1, 9.8.5 to 9.8.8, 9.9.3 to 9.9.9-P4, 9.9.9-S1 to 9.9.9-S6, 9.10.0 to 9.10.4-P4, and 9.11.0 to 9.11.0-P1. (CVE-2016-9131)
- A denial of service vulnerability exists in named in DNSSEC-enabled authoritative servers that is triggered during the handling of a query response that contains inconsistent DNSSEC information. An unauthenticated, remote attacker can exploit this to cause an assertion failure and daemon exit. Note that this vulnerability affects versions 9.9.9-P4, 9.9.9-S6, 9.10.4-P4, and 9.11.0-P1. (CVE-2016-9147)
- A denial of service vulnerability exists in named due to a flaw that is triggered during the handling of a specially crafted answer that contains a DS resource record. An unauthenticated, remote attacker can exploit this to cause an assertion failure and daemon exit. Note that this vulnerability affects versions 9.6-ESV-R9 to 9.6-ESV-R11-W1, 9.8.5 to 9.8.8, 9.9.3 to 9.9.9-P4, 9.9.9-S1 to 9.9.9-S6, 9.10.0 to 9.10.4-P4, and 9.11.0 to 9.11.0-P1. (CVE-2016-9444)
- A denial of service vulnerability exists in named in the nxdomain-redirect functionality that is triggered when handling a specially crafted query. An unauthenticated, remote attacker can exploit this to cause a REQUIRE assertion failure and daemon exit. Note that this vulnerability affects versions 9.9.8-S1 to 9.9.8-S3, 9.9.9-S1 to 9.9.9-S6, and 9.11.0-9.11.0 to P1. (CVE-2016-9778)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01439>

<https://kb.isc.org/article/AA-01440>

<https://kb.isc.org/article/AA-01441>

<https://kb.isc.org/docs/aa-01442>

Solution

Upgrade to ISC BIND version 9.9.9-P5 / 9.9.9-S7 / 9.10.4-P5 / 9.11.0-P2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.5806

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	95386
BID	95388
BID	95390
BID	95393
CVE	CVE-2016-9131
CVE	CVE-2016-9147
CVE	CVE-2016-9444
CVE	CVE-2016-9778

Plugin Information

Published: 2017/01/19, Modified: 2018/12/07

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.9-P5 / 9.9.9-S7 / 9.10.4-P5 / 9.11.0-P2
```


62562 - ISC BIND 9 DNS RDATA Handling DoS

Synopsis

The remote name server may be affected by a denial of service vulnerability.

Description

According to its self-reported version number, the remote installation of BIND can become locked up if certain combinations of RDATA are loaded into the server. Note that Nessus has only relied on the version itself and has not attempted to determine whether or not the install is actually affected.

See Also

<https://kb.isc.org/docs/aa-00801>

<http://ftp.isc.org/isc/bind9/9.6-ESV-R7-P4/CHANGES>

<http://ftp.isc.org/isc/bind9/9.7.6-P4/CHANGES>

<http://ftp.isc.org/isc/bind9/9.8.3-P4/CHANGES>

<http://ftp.isc.org/isc/bind9/9.9.1-P4/CHANGES>

Solution

Upgrade to BIND 9.6-ESV-R7-P4 / 9.6-ESV-R8 / 9.7.6-P4 / 9.7.7 / 9.8.3-P4 / 9.8.4 / 9.9.1-P4 / 9.9.2 or later.

Risk Factor

High

VPR Score

3.6

EPSS Score

0.4508

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID 55852

CVE CVE-2012-5166

Plugin Information

Published: 2012/10/16, Modified: 2018/11/15

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.6-ESV-R7-P4
```

60120 - ISC BIND 9 Multiple Denial of Service Vulnerabilities

Synopsis

The remote name server may be affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the remote installation of BIND is affected by multiple denial of service vulnerabilities :

- Under a heavy query load, the application may use uninitialized data structures related to failed query cache access. This error can cause the application to crash. Note this issue only affects the application when DNSSEC validation is enabled. (CVE-2012-3817)

- Under a heavy, incoming TCP query load, the application can be affected by a memory leak that can lead to decreased performance and application termination on systems that kill processes that are out of memory.

(CVE-2012-3868)

Note that Nessus has only relied on the version itself and has not attempted to determine whether or not the install is actually affected.

See Also

<https://kb.isc.org/article/AA-00729>

<https://kb.isc.org/docs/aa-00730>

<http://ftp.isc.org/isc/bind9/9.6-ESV-R7-P2/CHANGES>

<http://ftp.isc.org/isc/bind9/9.7.6-P2/CHANGES>

<http://ftp.isc.org/isc/bind9/9.8.3-P2/CHANGES>

<http://ftp.isc.org/isc/bind9/9.9.1-P2/CHANGES>

Solution

Upgrade to BIND 9.6-ESV-R7-P2 / 9.7.6-P2 / 9.8.3-P2 / 9.9.1-P2 or later.

Risk Factor

High

VPR Score

3.6

EPSS Score

0.1175

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	54658
BID	54659
CVE	CVE-2012-3817
CVE	CVE-2012-3868

Plugin Information

Published: 2012/07/25, Modified: 2018/11/15

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.6-ESV-R7-P2
```

89998 - ISC BIND 9 Multiple DoS

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the instance of ISC BIND running on the remote name server is affected by multiple denial of service vulnerabilities :

- A denial of service vulnerability exists in files sexpr.c and alist.c when handling control channel packets. An unauthenticated, remote attacker can exploit this, via crafted packets sent to the control channel (rndc) interface, to cause an assertion failure and daemon exit. (CVE-2016-1285)
- A denial of service vulnerability exists in resolver.c when DNS cookies are enabled. An unauthenticated, remote attacker can exploit this, via a malformed cookie with more than one cookie option, to cause an INSIST assertion failure and daemon exit. (CVE-2016-2088)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/aa-01352>

<https://kb.isc.org/article/AA-01362/>

Solution

Upgrade to ISC BIND version 9.9.8-P4 / 9.9.8-S6 / 9.10.3-P4 or later.

Note that version 9.9.8-S6 is a preview version of BIND provided exclusively to ISC Support customers. Additionally, the fix for CVE-2016-2088 is only available in version 9.10.3-P4.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

7.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.6784

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-1285

CVE CVE-2016-2088

Plugin Information

Published: 2016/03/17, Modified: 2025/02/18

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.8-P4 / 9.9.8-S6 / 9.10.3-P4
```

89999 - ISC BIND 9 Multiple DoS

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the instance of ISC BIND running on the remote name server is affected by multiple denial of service vulnerabilities :

- A denial of service vulnerability exists in files resolver.c and db.c when handling DNAME resource signatures. An unauthenticated, remote attacker can exploit this, via a crafted query that generates a response containing a signature record, to cause an assertion failure and daemon exit. (CVE-2016-1286)
- A denial of service vulnerability exists in resolver.c when DNS cookies are enabled. An unauthenticated, remote attacker can exploit this, via a malformed cookie with more than one cookie option, to cause an INSIST assertion failure and daemon exit. (CVE-2016-2088)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/aa-01353>

<https://kb.isc.org/article/AA-01362/>

Solution

Upgrade to ISC BIND version 9.9.8-P4 / 9.9.8-S6 / 9.10.3-P4 or later.

Note that version 9.9.8-S6 is a preview version of BIND provided exclusively to ISC Support customers. Additionally, the fix for CVE-2016-2088 is only available in version 9.10.3-P4.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

7.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.7288

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-1286

CVE CVE-2016-2088

Plugin Information

Published: 2016/03/17, Modified: 2019/11/20

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.8-P4 / 9.9.8-S6 / 9.10.3-P4
```

79861 - ISC BIND 9 Multiple DoS Vulnerabilities

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the remote installation of BIND is affected by multiple denial of service vulnerabilities :

- A flaw exists within the Domain Name Service due to an error in the code used to follow delegations. A remote attacker, with a maliciously-constructed zone or query, could potentially cause the service to issue unlimited queries leading to resource exhaustion. (CVE-2014-8500)
- Multiple flaws exist with the GeoIP feature. These flaws could allow a remote attacker to cause a denial of service. Note these issues only affect the 9.10.x branch. (CVE-2014-8680)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/aa-01216>

<https://kb.isc.org/docs/aa-01217>

<http://www.nessus.org/u?92718697>

<http://www.nessus.org/u?9f54d158>

Solution

Upgrade to BIND version 9.9.6-P1 / 9.10.1-P1 or later.

Risk Factor

High

VPR Score

3.6

EPSS Score

0.6298

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	71590
BID	73191
CVE	CVE-2014-8500
CVE	CVE-2014-8680

Plugin Information

Published: 2014/12/12, Modified: 2018/11/15

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.6-P1
```

94577 - ISC BIND 9 Recursive Response DNAME Record Handling DoS

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the instance of ISC BIND 9 running on the remote name server is affected by a denial of service vulnerability due to improper handling of a recursive response containing a DNAME record in the answer section. An unauthenticated, remote attacker can exploit this to cause an assertion failure and daemon exit.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01434/>

Solution

Upgrade to ISC BIND version 9.9.9-P4 / 9.9.9-S6 / 9.10.4-P4 / 9.11.0-P1 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.4301

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	94067
CVE	CVE-2016-8864

Plugin Information

Published: 2016/11/04, Modified: 2018/12/07

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.9-P4 / 9.9.9-S6 / 9.10.4-P4 / 9.11.0-P1
```

Synopsis

The remote name server may be affected by a denial of service / information disclosure vulnerability.

Description

According to its self-reported version number, the remote installation of BIND does not properly handle resource records with a zero-length RDATA section, which may lead to unexpected outcomes, such as crashes of the affected server, disclosure of portions of memory, corrupted zone data, or other problems.

Note that Nessus has only relied on the version itself and has not attempted to determine whether or not the install is actually affected.

See Also

<http://ftp.isc.org/isc/bind9/9.6-ESV-R7-P1/CHANGES>
<http://ftp.isc.org/isc/bind9/9.7.6-P1/CHANGES>
<http://ftp.isc.org/isc/bind9/9.8.3-P1/CHANGES>
<http://ftp.isc.org/isc/bind9/9.9.1-P1/CHANGES>
<https://kb.isc.org/docs/aa-00698>
<https://www.isc.org/software/bind/advisories/cve-2012-1667>

Solution

Upgrade to BIND 9.6-ESV-R7-P1 / 9.7.6-P1 / 9.8.3-P1 / 9.9.1-P1 or later.

Risk Factor

High

VPR Score

3.6

EPSS Score

0.4084

CVSS v2.0 Base Score

8.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:C)

CVSS v2.0 Temporal Score

6.3 (CVSS2#E:U/RL:OF/RC:C)

References

BID	53772
CVE	CVE-2012-1667
XREF	CERT:381699

Plugin Information

Published: 2012/06/11, Modified: 2018/11/15

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.6-ESV-R7-P1
```

190444 - ISC BIND 9.0.0 < 9.16.48 / 9.9.3-S1 < 9.16.48-S1 / 9.18.0 < 9.18.24 / 9.18.11-S1 < 9.18.24-S1 / 9.19.0 < 9.19.21 Vulnerability (cve-2023-50387)

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the cve-2023-50387 advisory.

- Certain DNSSEC aspects of the DNS protocol (in RFC 4033, 4034, 4035, 6840, and related RFCs) allow remote attackers to cause a denial of service (CPU consumption) via one or more DNSSEC responses, aka the KeyTrap issue. One of the concerns is that, when there is a zone with many DNSKEY and RRSIG records, the protocol specification implies that an algorithm must evaluate all combinations of DNSKEY and RRSIG records. (CVE-2023-50387)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/cve-2023-50387>

Solution

Upgrade to ISC BIND version 9.16.48 / 9.16.48-S1 / 9.18.24 / 9.18.24-S1 / 9.19.21 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.1

EPSS Score

0.4551

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE CVE-2023-50387
XREF IAVA:2024-A-0103-S

Plugin Information

Published: 2024/02/13, Modified: 2024/07/26

Plugin Output

udp/53/dns

Installed version : 9.4.2
Fixed version : 9.16.48

190462 - ISC BIND 9.0.0 < 9.16.48 / 9.9.3-S1 < 9.16.48-S1 / 9.18.0 < 9.18.24 / 9.18.11-S1 < 9.18.24-S1 / 9.19.0 < 9.19.21 Vulnerability (cve-2023-50868)

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the cve-2023-50868 advisory.

- The Closest Encloser Proof aspect of the DNS protocol (in RFC 5155 when RFC 9276 guidance is skipped) allows remote attackers to cause a denial of service (CPU consumption for SHA-1 computations) via DNSSEC responses in a random subdomain attack, aka the NSEC3 issue. The RFC 5155 specification implies that an algorithm must perform thousands of iterations of a hash function in certain situations. (CVE-2023-50868)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/cve-2023-50868>

Solution

Upgrade to ISC BIND version 9.16.48 / 9.16.48-S1 / 9.18.24 / 9.18.24-S1 / 9.19.21 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.3868

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-50868
XREF	IAVA:2024-A-0103-S

Plugin Information

Published: 2024/02/13, Modified: 2025/05/14

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.16.48
```

85896 - ISC BIND 9.0.x < 9.9.7-P3 / 9.10.x < 9.10.2-P4 Multiple DoS

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is potentially affected by the following vulnerabilities :

- A denial of service vulnerability exists due to an assertion flaw that is triggered when parsing malformed DNSSEC keys. An unauthenticated, remote attacker can exploit this, via a specially crafted query to a zone containing such a key, to cause a validating resolver to exit. (CVE-2015-5722)
- A denial of service vulnerability exists in the fromwire_openpgpkey() function in openpgpkey_61.c that is triggered when the length of data is less than 1. An unauthenticated, remote attacker can exploit this, via a specially crafted response to a query, to cause an assertion failure that terminates named. (CVE-2015-5986)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01287>

<https://kb.isc.org/article/AA-01291>

Solution

Upgrade to BIND version 9.9.7-P3 / 9.10.2-P4 or later.

Risk Factor

High

VPR Score

3.7

EPSS Score

0.5078

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2015-5722

CVE CVE-2015-5986

Plugin Information

Published: 2015/09/11, Modified: 2018/06/27

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.7-P3
```

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the cve-2023-3341 advisory.

- The code that processes control channel messages sent to named calls certain functions recursively during packet parsing. Recursion depth is only limited by the maximum accepted packet size; depending on the environment, this may cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. Since each incoming control channel message is fully parsed before its contents are authenticated, exploiting this flaw does not require the attacker to hold a valid RNDC key; only network access to the control channel's configured TCP port is necessary. By sending a specially crafted message over the control channel, an attacker can cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. However, the attack only works in environments where the stack size available to each process/thread is small enough; the exact threshold depends on multiple factors and is therefore impossible to specify universally. (CVE-2023-3341)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/cve-2023-3341>

Solution

Upgrade to ISC BIND version 9.16.44 / 9.16.44-S1 / 9.18.19 / 9.18.19-S1 / 9.19.17 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0014

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-3341
XREF	IAVA:2023-A-0500-S

Plugin Information

Published: 2023/09/20, Modified: 2024/02/16

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.16.44
```

Synopsis

The remote name server is affected by multiple denial of service vulnerabilities.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is affected by multiple denial of service vulnerabilities :

- A denial of service vulnerability exists due to improper handling of certain string formatting options. An authenticated, remote attacker can exploit this, via a malformed Address Prefix List (APL) record, to cause an INSIST assertion failure and daemon exit.

(CVE-2015-8704)

- A denial of service vulnerability exists due to a failure to properly convert OPT records and ECS options to formatted text. A remote attacker can exploit this to cause a REQUIRE assertion failure and daemon exit.

Note that this issue only affects BIND 9.10.x.

(CVE-2015-8705)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01335>

<https://kb.isc.org/article/AA-01336>

Solution

Upgrade to BIND version 9.9.8-P3 / 9.9.8-S4 / 9.10.3-P3 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:H)

CVSS v3.0 Temporal Score

7.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.7

EPSS Score

0.3559

CVSS v2.0 Base Score

6.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:C)

CVSS v2.0 Temporal Score

4.9 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2015-8704

CVE CVE-2015-8705

Plugin Information

Published: 2016/01/26, Modified: 2025/02/18

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.8-P3
```

85241 - ISC BIND 9.7.x < 9.9.7-P2 / 9.10.x < 9.10.2-P3 TKEY Query Handling Remote DoS

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the installation of ISC BIND on the remote name server is potentially affected by a denial of service vulnerability due to a REQUIRE assertion flaw that occurs while handling TKEY queries. A remote attacker can exploit this by using a specially crafted TKEY query to crash the daemon.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01272>

<https://kb.isc.org/article/AA-01279>

<https://kb.isc.org/article/AA-01280>

Solution

Upgrade to BIND version 9.9.7-P2 / 9.10.2-P3 or later, or apply the patch referenced in the advisory.

Risk Factor

High

VPR Score

8.1

EPSS Score

0.9283

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

6.4 (CVSS2#E:F/RL:OF/RC:C)

References

CVE CVE-2015-5477
XREF EDB-ID:37721

Exploitable With

Core Impact (true)

Plugin Information

Published: 2015/08/05, Modified: 2018/06/27

Plugin Output

udp/53/dns

```
Installed version : 9.4.2  
Fixed version    : 9.9.7-P2
```

190463 - ISC BIND 9.9.3-S1 < 9.16.48-S1 / 9.0.0 < 9.16.48 / 9.16.8-S1 < 9.16.48-S1 / 9.18.0 < 9.18.24 / 9.18.11-S1 < 9.18.24-S1 / 9.19.0 < 9.19.21 Vulnerability (cve-2023-4408)

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the cve-2023-4408 advisory.

- The DNS message parsing code in `named` includes a section whose computational complexity is overly high.

It does not cause problems for typical DNS traffic, but crafted queries and responses may cause excessive CPU load on the affected `named` instance by exploiting this flaw. This issue affects both authoritative servers and recursive resolvers. This issue affects BIND 9 versions 9.0.0 through 9.16.45, 9.18.0 through 9.18.21, 9.19.0 through 9.19.19, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.45-S1, and 9.18.11-S1 through 9.18.21-S1. (CVE-2023-4408)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/cve-2023-4408>

Solution

Upgrade to ISC BIND version 9.16.48 / 9.16.48-S1 / 9.18.24 / 9.18.24-S1 / 9.19.21 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0079

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-4408
XREF	IAVA:2024-A-0103-S

Plugin Information

Published: 2024/02/13, Modified: 2024/07/26

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.16.48
```

87502 - ISC BIND 9.x < 9.9.8-P2 / 9.10.x < 9.10.3-P2 Response Parsing Class Attribute Handling DoS

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the remote installation of BIND is affected by a denial of service vulnerability due to improper parsing of incorrect class attributes in db.c. An unauthenticated, remote attacker can exploit this, via a malformed class attribute, to trigger a REQUIRE assertion failure, resulting in a denial of service condition.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/aa-01317>

<http://www.nessus.org/u?06404c1c>

Solution

Upgrade to BIND version 9.9.8-P2 / 9.9.8-S3 / 9.10.3-P2 or later.

Note that 9.9.8-S3 is a preview version of BIND provided exclusively to ISC Support customers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.5409

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	79349
CVE	CVE-2015-8000

Plugin Information

Published: 2015/12/18, Modified: 2020/04/27

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.8-P2 / 9.9.8-S3 / 9.10.3-P2
```

94611 - ISC BIND 9.x < 9.9.9-P3 Options Sections DoS

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the instance of ISC BIND running on the remote name server is 9.x prior to 9.9.9-P3. It is, therefore, affected by a denial of service vulnerability when handling malformed options sections. An unauthenticated, remote attacker can exploit this, via a specially crafted OPT resource record, to cause an assertion failure, resulting in a daemon exit.

See Also

<https://kb.isc.org/article/AA-01433>

Solution

Upgrade to ISC BIND version 9.9.9-P3 / 9.10.4-P3 / 9.11.0 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.5128

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID 93814
CVE CVE-2016-2848

Plugin Information

Published: 2016/11/08, Modified: 2018/12/07

Plugin Output

udp/53/dns

```
Installed version : 9.4.2  
Fixed version    : 9.9.9-P3 / 9.10.4-P3 / 9.11.0
```

Synopsis

The remote name server is affected by multiple vulnerabilities.

Description

According to its self-reported version number, the instance of ISC BIND running on the remote name server is 9.x.x prior to 9.9.10-P1, 9.10.x prior to 9.10.5-P1, or 9.11.x prior to 9.11.1-P1. It is, therefore, affected by multiple vulnerabilities :

- A denial of service vulnerability exists when processing Response Policy Zone (RPZ) rule types. An unauthenticated, remote attacker can exploit this, via a specially crafted query, to cause an infinite loop condition that degrades the server's functionality.

(CVE-2017-3140)

- A privilege escalation vulnerability exists in the BIND installer for Windows due to using an unquoted service path. A local attacker can exploit this to gain elevated privileges provided that the host file system permissions allow this. Note that non-Windows builds and installations are not affected. (CVE-2017-3141)

See Also

<https://kb.isc.org/docs/aa-01495>

<https://kb.isc.org/docs/aa-01496>

Solution

Upgrade to ISC BIND version 9.9.10-P1 / 9.9.10-S2 / 9.10.5-P1 / 9.10.5-S2 / 9.11.1-P1 or later. Note that BIND 9 versions 9.9.10-S2 and 9.10.5-S2 are available exclusively for eligible ISC Support customers.

Risk Factor

High

CVSS v3.0 Base Score

7.8 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.0 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.204

CVSS v2.0 Base Score

7.2 (CVSS2#AV:L/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	99088
BID	99089
CVE	CVE-2017-3140
CVE	CVE-2017-3141
XREF	EDB-ID:42121

Plugin Information

Published: 2017/06/22, Modified: 2019/11/13

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.10-P1
```

62119 - ISC BIND Assertion Error Resource Record RDATA Query Parsing Remote DoS

Synopsis

The remote name server may be affected by a denial of service vulnerability.

Description

According to its self-reported version number, the remote installation of BIND will exit with an assertion failure if a resource record with RDATA in excess of 65535 bytes is loaded and then subsequently queried. Note that Nessus has only relied on the version itself and has not attempted to determine whether or not the install is actually affected.

See Also

<https://kb.isc.org/article/AA-00778/74>

<http://ftp.isc.org/isc/bind9/9.6-ESV-R7-P3/CHANGES>

<http://ftp.isc.org/isc/bind9/9.7.6-P3/CHANGES>

<http://ftp.isc.org/isc/bind9/9.8.3-P3/CHANGES>

<http://ftp.isc.org/isc/bind9/9.9.1-P3/CHANGES>

Solution

Upgrade to BIND 9.6-ESV-R7-P3 / 9.6-ESV-R8 / 9.7.6-P3 / 9.7.7 / 9.8.3-P3 / 9.8.4 / 9.9.1-P3 / 9.9.2 or later.

Risk Factor

High

VPR Score

5.9

EPSS Score

0.5667

CVSS v2.0 Base Score

7.8 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID 55522
CVE CVE-2012-4244

Plugin Information

Published: 2012/09/17, Modified: 2018/09/17

Plugin Output

udp/53/dns

```
Installed version : 9.4.2  
Fixed version    : 9.6-ESV-R7-P3
```

149211 - ISC BIND DNAME Recursion DoS (CVE-2021-25215)

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version, the ISC Bind present on the remote host is affected by a denial of service vulnerability:

- DNAME records, described in RFC 6672, provide a way to redirect a subtree of the domain name tree in the DNS. A flaw in the way named processes these records may trigger an attempt to add the same RRset to the ANSWER section more than once. When a vulnerable version of named receives a query for a record triggering the flaw, the named process will terminate due to a failed assertion check.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/CVE-2021-25215>

Solution

Upgrade to the patched release most closely related to your current version of BIND.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0068

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-25215
XREF	IAVA:2021-A-0206-S

Plugin Information

Published: 2021/04/30, Modified: 2021/11/09

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.31
```

136769 - ISC BIND Service Downgrade / Reflected DoS

Synopsis

The remote name server is affected by Service Downgrade / Reflected DoS vulnerabilities.

Description

According to its self-reported version, the instance of ISC BIND 9 running on the remote name server is affected by performance downgrade and Reflected DoS vulnerabilities. This is due to BIND DNS not sufficiently limiting the number fetches which may be performed while processing a referral response.

An unauthenticated, remote attacker can exploit this to cause degrade the service of the recursive server or to use the affected server as a reflector in a reflection attack.

See Also

<https://kb.isc.org/docs/cve-2020-8616>

Solution

Upgrade to the ISC BIND version referenced in the vendor advisory.

Risk Factor

Medium

CVSS v3.0 Base Score

8.6 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

5.2

EPSS Score

0.0334

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8616
XREF	IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2024/03/12

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

42256 - NFS Shares World Readable

Synopsis

The remote NFS server exports world-readable shares.

Description

The remote NFS server is exporting one or more shares without restricting access (based on hostname, IP, or IP range).

See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

Solution

Place the appropriate restrictions on all NFS shares.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2009/10/26, Modified: 2024/02/21

Plugin Output

tcp/2049/rpc-nfs

```
The following shares have no access restrictions :
```

```
/ *
```

44081 - OpenSSH < 5.7 Multiple Vulnerabilities

Synopsis

The remote SSH service may be affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is earlier than 5.7. Versions before 5.7 may be affected by the following vulnerabilities :

- A security bypass vulnerability because OpenSSH does not properly validate the public parameters in the J-PAKE protocol. This could allow an attacker to authenticate without the shared secret. Note that this issue is only exploitable when OpenSSH is built with J-PAKE support, which is currently experimental and disabled by default, and that Nessus has not checked whether J-PAKE support is indeed enabled. (CVE-2010-4478)
- The auth_parse_options function in auth-options.c in sshd provides debug messages containing authorized_keys command options, which allows remote, authenticated users to obtain potentially sensitive information by reading these messages. (CVE-2012-0814)

See Also

<http://seb.dbzteam.org/crypto/jpake-session-key-retrieval.pdf>

<http://cvsweb.openbsd.org/cgi-bin/cvsweb/src/usr.bin/ssh/Attic/jpake.c#rev1.5>

<http://www.nessus.org/u?2ac4f8d9>

Solution

Upgrade to OpenSSH 5.7 or later.

Risk Factor

High

VPR Score

6.3

EPSS Score

0.0085

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	45304
BID	51702
CVE	CVE-2010-4478
CVE	CVE-2012-0814

Plugin Information

Published: 2011/10/04, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 5.7
```


73079 - OpenSSH < 6.6 Multiple Vulnerabilities

Synopsis

The SSH server on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 6.6. It is, therefore, affected by the following vulnerabilities :

- A flaw exists due to a failure to initialize certain data structures when makefile.inc is modified to enable the J-PAKE protocol. An unauthenticated, remote attacker can exploit this to corrupt memory, resulting in a denial of service condition and potentially the execution of arbitrary code. (CVE-2014-1692)

- An error exists related to the 'AcceptEnv' configuration setting in sshd_config due to improper processing of wildcard characters. An unauthenticated, remote attacker can exploit this, via a specially crafted request, to bypass intended environment restrictions.

(CVE-2014-2532)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.openssh.com/txt/release-6.6>

<https://lists.gt.net/openssh/dev/57663#57663>

Solution

Upgrade to OpenSSH version 6.6 or later.

Risk Factor

High

VPR Score

5.3

EPSS Score

0.046

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

192.168.50.3

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	65230
BID	66355
CVE	CVE-2014-1692
CVE	CVE-2014-2532

Plugin Information

Published: 2014/03/18, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 6.6
```

84638 - OpenSSH < 6.9 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 6.9. It is, therefore, affected by the following vulnerabilities :

- A flaw exists within the `x11_open_helper()` function in the 'channels.c' file that allows connections to be permitted after 'ForwardX11Timeout' has expired. A remote attacker can exploit this to bypass timeout checks and XSECURITY restrictions. (CVE-2015-5352)
- Various issues were addressed by fixing the weakness in agent locking by increasing the failure delay, storing the salted hash of the password, and using a timing-safe comparison function.
- An out-of-bounds read error exists when handling incorrect pattern lengths. A remote attacker can exploit this to cause a denial of service or disclose sensitive information in the memory.
- An out-of-bounds read error exists when parsing the 'EscapeChar' configuration option.

See Also

<http://www.openssh.com/txt/release-6.9>

<http://www.nessus.org/u?725c4682>

Solution

Upgrade to OpenSSH 6.9 or later.

Risk Factor

High

VPR Score

1.4

EPSS Score

0.1017

CVSS v2.0 Base Score

8.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:C)

CVSS v2.0 Temporal Score

6.3 (CVSS2#E:U/RL:OF/RC:C)

References

BID	75525
CVE	CVE-2015-5352

Plugin Information

Published: 2015/07/09, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 6.9
```

93194 - OpenSSH < 7.3 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.3. It is, therefore, affected by multiple vulnerabilities :

- A local privilege escalation when the UseLogin feature is enabled and PAM is configured to read .pam_environment files from home directories. (CVE-2015-8325)
- A flaw exists that is due to the program returning shorter response times for authentication requests with overly long passwords for invalid users than for valid users. This may allow a remote attacker to conduct a timing attack and enumerate valid usernames.
(CVE-2016-6210)
- A denial of service vulnerability exists in the auth_password() function in auth-passwd.c due to a failure to limit password lengths for password authentication. An unauthenticated, remote attacker can exploit this, via a long string, to consume excessive CPU resources, resulting in a denial of service condition.
(CVE-2016-6515)
- An unspecified flaw exists in the CBC padding oracle countermeasures that allows an unauthenticated, remote attacker to conduct a timing attack.
- A flaw exists due to improper operation ordering of MAC verification for Encrypt-then-MAC (EtM) mode transport MAC algorithms when verifying the MAC before decrypting any ciphertext. An unauthenticated, remote attacker can exploit this, via a timing attack, to disclose sensitive information.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.openssh.com/txt/release-7.3>

<https://marc.info/?l=openbsd-announce&m=147005433429403>

Solution

Upgrade to OpenSSH version 7.3 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.8 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.0 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.9249

CVSS v2.0 Base Score

7.2 (CVSS2#AV:L/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	86187
BID	92212
CVE	CVE-2015-8325
CVE	CVE-2016-6515
CVE	CVE-2016-6210

Plugin Information

Published: 2016/08/29, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.3
```

96151 - OpenSSH < 7.4 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.4. It is, therefore, affected by multiple vulnerabilities :

- A flaw exists in ssh-agent due to loading PKCS#11 modules from paths that are outside a trusted whitelist.

A local attacker can exploit this, by using a crafted request to load hostile modules via agent forwarding, to execute arbitrary code. To exploit this vulnerability, the attacker would need to control the forwarded agent-socket (on the host running the sshd server) and the ability to write to the file system of the host running ssh-agent. (CVE-2016-10009)

- A flaw exists in sshd due to creating forwarded Unix-domain sockets with 'root' privileges whenever privilege separation is disabled. A local attacker can exploit this to gain elevated privileges.

(CVE-2016-10010)

- An information disclosure vulnerability exists in sshd within the realloc() function due leakage of key material to privilege-separated child processes when reading keys. A local attacker can possibly exploit this to disclose sensitive key material. Note that no such leak has been observed in practice for normal-sized keys, nor does a leak to the child processes directly expose key material to unprivileged users.

(CVE-2016-10011)

- A flaw exists in sshd within the shared memory manager used by pre-authenticating compression support due to a bounds check being elided by some optimizing compilers and due to the memory manager being incorrectly accessible when pre-authenticating compression is disabled. A local attacker can exploit this to gain elevated privileges. (CVE-2016-10012)

- A denial of service vulnerability exists in sshd when handling KEXINIT messages. An unauthenticated, remote attacker can exploit this, by sending multiple KEXINIT messages, to consume up to 128MB per connection.

- A flaw exists in sshd due to improper validation of address ranges by the AllowUser and DenyUsers directives at configuration load time. A local attacker can exploit this, via an invalid CIDR address range, to gain access to restricted areas.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.openssh.com/txt/release-7.4>

Solution

Upgrade to OpenSSH version 7.4 or later.

Risk Factor

High

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.6 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0224

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	94968
BID	94972
BID	94975
BID	94977
CVE	CVE-2016-10009
CVE	CVE-2016-10010
CVE	CVE-2016-10011
CVE	CVE-2016-10012
CVE	CVE-2016-10708
XREF	EDB-ID:40962

Plugin Information

Published: 2016/12/27, Modified: 2024/03/27

Plugin Output

tcp/22/ssh


```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.4
```

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is prior to 5.2.7. It is, therefore, affected by multiple vulnerabilities :

- There is a buffer overflow flaw in the bundled PCRE library that allows a denial of service attack. (CVE-2008-2371)
- Multiple directory traversal vulnerabilities exist in functions such as 'posix_access', 'chdir', and 'ftok' that allow a remote attacker to bypass 'safe_mode' restrictions. (CVE-2008-2665 and CVE-2008-2666).
- A buffer overflow flaw in 'php_imap.c' may be triggered when processing long message headers due to the use of obsolete API calls. This can be exploited to cause a denial of service or to execute arbitrary code. (CVE-2008-2829)
- A buffer overflow in the 'imageloadfont' function in 'ext/gd/gd.c' can be triggered when a specially crafted font is given. This can be exploited to cause a denial of service or to execute arbitrary code. (CVE-2008-3658)
- A buffer overflow flaw exists in PHP's internal function 'memnstr' which can be exploited by an attacker using the delimiter argument to the 'explode' function. This can be used to cause a denial of service or to execute arbitrary code. (CVE-2008-3659)
- When PHP is used as a FastCGI module, an attacker by requesting a file whose file name extension is preceded by multiple dots can cause a denial of service. (CVE-2008-3660)
- A heap-based buffer overflow flaw in the mbstring extension can be triggered via a specially crafted string containing an HTML entity that is not handled during Unicode conversion. This can be exploited to execute arbitrary code.(CVE-2008-5557)
- Improper initialization of global variables 'page_uid' and 'page_gid' when PHP is used as an Apache module allows the bypassing of security restriction due to SAPI 'php_getuid' function overloading. (CVE-2008-5624)
- PHP does not enforce the correct restrictions when 'safe_mode' is enabled through a 'php_admin_flag' setting in 'httpd.conf'. This allows an attacker, by placing a specially crafted 'php_value' entry in '.htaccess', to be able to write to arbitrary files. (CVE-2008-5625)
- The 'ZipArchive::extractTo' function in the ZipArchive extension fails to filter directory traversal sequences from file names. An attacker can exploit this to write to arbitrary files. (CVE-2008-5658)
- Under limited circumstances, an attacker can cause a file truncation to occur when calling the 'dba_replace'

function with an invalid argument. (CVE-2008-7068)

- A buffer overflow error exists in the function 'date_from_ISO8601' function within file 'xmlrpc.c' because user-supplied input is improperly validated.

This can be exploited by a remote attacker to cause a denial of service or to execute arbitrary code. (CVE-2014-8626)

See Also

<http://cxsecurity.com/issue/WLB-2008110041>

<http://cxsecurity.com/issue/WLB-2008110058>

<http://cxsecurity.com/issue/WLB-2008120011>

<https://seclists.org/fulldisclosure/2008/Jun/237>

<https://seclists.org/fulldisclosure/2008/Jun/238>

<https://www.openwall.com/lists/oss-security/2008/08/08/2>

<https://www.openwall.com/lists/oss-security/2008/08/13/8>

<https://seclists.org/fulldisclosure/2008/Nov/674>

<https://seclists.org/fulldisclosure/2008/Dec/90>

<https://bugs.php.net/bug.php?id=42862>

<https://bugs.php.net/bug.php?id=45151>

<https://bugs.php.net/bug.php?id=45722>

http://www.php.net/releases/5_2_7.php

<http://www.php.net/ChangeLog-5.php#5.2.7>

Solution

Upgrade to PHP version 5.2.8 or later.

Note that version 5.2.7 has been removed from distribution because of a regression in that version that results in the 'magic_quotes_gpc'

setting remaining off even if it was set to on.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.209

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	29796
BID	29797
BID	29829
BID	30087
BID	30649
BID	31612
BID	32383
BID	32625
BID	32688
BID	32948
BID	70928
CVE	CVE-2008-2371
CVE	CVE-2008-2665
CVE	CVE-2008-2666
CVE	CVE-2008-2829
CVE	CVE-2008-3658
CVE	CVE-2008-3659
CVE	CVE-2008-3660
CVE	CVE-2008-5557
CVE	CVE-2008-5624
CVE	CVE-2008-5625
CVE	CVE-2008-5658
CVE	CVE-2008-7068
CVE	CVE-2014-8626
XREF	CWE:20
XREF	CWE:22
XREF	CWE:119
XREF	CWE:264

Plugin Information

Published: 2008/12/05, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.7
```

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP 5.2 installed on the remote host is older than 5.2.14. Such versions may be affected by several security issues :

- An error exists when processing invalid XML-RPC requests that can lead to a NULL pointer dereference. (bug #51288) (CVE-2010-0397)

- An error exists in the function 'fnmatch' that can lead to stack exhaustion.

- An error exists in the sqlite extension that could allow arbitrary memory access.

- A memory corruption error exists in the function 'substr_replace'.

- The following functions are not properly protected against function interruptions :

addslashes, chunk_split, html_entity_decode, iconv_mime_decode, iconv_substr, iconv_mime_encode, htmlentities, htmlspecialchars, str_getcsv, http_build_query, strpbrk, strstr, str_pad, str_word_count, wordwrap, strtok, setcookie, strip_tags, trim, ltrim, rtrim, parse_str, pack, unpack, uasort, preg_match, strrchr, strchr, substr, str_repeat (CVE-2010-1860, CVE-2010-1862, CVE-2010-1864, CVE-2010-2097, CVE-2010-2100, CVE-2010-2101, CVE-2010-2190, CVE-2010-2191, CVE-2010-2484)

- The following opcodes are not properly protected against function interruptions :

ZEND_CONCAT, ZEND_ASSIGN_CONCAT, ZEND_FETCH_RW (CVE-2010-2191)

- The default session serializer contains an error that can be exploited when assigning session variables having user defined names. Arbitrary serialized values can be injected into sessions by including the PS_UNDEF_MARKER, '!', character in variable names.

- A use-after-free error exists in the function 'spl_object_storage_attach'. (CVE-2010-2225)

- An information disclosure vulnerability exists in the function 'var_export' when handling certain error conditions. (CVE-2010-2531)

See Also

http://www.php.net/releases/5_2_14.php

<http://www.php.net/ChangeLog-5.php#5.2.14>

Solution

Upgrade to PHP version 5.2.14 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.0868

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	38708
BID	40948
BID	41991
CVE	CVE-2007-1581
CVE	CVE-2010-0397
CVE	CVE-2010-1860
CVE	CVE-2010-1862
CVE	CVE-2010-1864
CVE	CVE-2010-2097
CVE	CVE-2010-2100
CVE	CVE-2010-2101
CVE	CVE-2010-2190
CVE	CVE-2010-2191
CVE	CVE-2010-2225
CVE	CVE-2010-2484
CVE	CVE-2010-2531
CVE	CVE-2010-3065
XREF	SECUNIA:39675
XREF	SECUNIA:40268

Plugin Information

Published: 2010/08/04, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.14
```


41014 - PHP < 5.2.11 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.11. Such versions may be affected by several security issues :

- An unspecified error occurs in certificate validation inside 'php_openssl_apply_verification_policy'.
- An unspecified input validation vulnerability affects the color index in 'imagecolortransparent()'.
- An unspecified input validation vulnerability affects exif processing.
- Calling 'popen()' with an invalid mode can cause a crash under Windows. (Bug #44683)
- An integer overflow in 'xml_utf8_decode()' can make it easier to bypass cross-site scripting and SQL injection protection mechanisms using a specially crafted string with a long UTF-8 encoding. (Bug #49687)
- 'proc_open()' can bypass 'safe_mode_protected_env_vars'.
(Bug #49026)

See Also

<http://www.php.net/ChangeLog-5.php#5.2.11>

http://www.php.net/releases/5_2_11.php

<http://news.php.net/php.internals/45597>

<http://www.php.net/ChangeLog-5.php#5.2.11>

Solution

Upgrade to PHP version 5.2.11 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.1776

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	36449
BID	44889
CVE	CVE-2009-3291
CVE	CVE-2009-3292
CVE	CVE-2009-3293
CVE	CVE-2009-3294
CVE	CVE-2009-4018
CVE	CVE-2009-5016
XREF	SECUNIA:36791
XREF	CWE:20
XREF	CWE:134
XREF	CWE:264

Plugin Information

Published: 2009/09/18, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.11
```

32123 - PHP < 5.2.6 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.6. Such versions may be affected by the following issues :

- A stack-based buffer overflow in FastCGI SAPI.
- An integer overflow in printf().
- An security issue arising from improper calculation of the length of PATH_TRANSLATED in cgi_main.c.
- A safe_mode bypass in cURL.
- Incomplete handling of multibyte chars inside escapeshellcmd().
- Issues in the bundled PCRE fixed by version 7.6.

See Also

<https://seclists.org/bugtraq/2008/Mar/285>

<https://seclists.org/fulldisclosure/2008/May/102>

<https://seclists.org/fulldisclosure/2008/May/106>

http://www.php.net/releases/5_2_6.php

Solution

Upgrade to PHP version 5.2.6 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.5294

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	27413
BID	28392
BID	29009
CVE	CVE-2007-4850
CVE	CVE-2007-6039
CVE	CVE-2008-0599
CVE	CVE-2008-1384
CVE	CVE-2008-2050
CVE	CVE-2008-2051
XREF	SECUNIA:30048
XREF	CWE:20
XREF	CWE:119
XREF	CWE:264

Plugin Information

Published: 2008/05/02, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.6
```

35067 - PHP < 5.2.8 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that may be affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is earlier than 5.2.8. As such, it is potentially affected by the following vulnerabilities :

- PHP fails to properly sanitize error messages of arbitrary HTML or script code, would code allow for cross-site scripting attacks if PHP's 'display_errors' setting is enabled. (CVE-2008-5814)
- Version 5.2.7 introduced a regression with regard to 'magic_quotes' functionality due to an incorrect fix to the filter extension. As a result, the 'magic_quotes_gpc' setting remains off even if it is set to on. (CVE-2008-5844)

See Also

<https://bugs.php.net/bug.php?id=42718>

http://www.php.net/releases/5_2_8.php

Solution

Upgrade to PHP version 5.2.8 or later.

Risk Factor

High

VPR Score

6.3

EPSS Score

0.0114

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32673
CVE	CVE-2008-5814
CVE	CVE-2008-5844
XREF	CWE:16
XREF	CWE:79

Plugin Information

Published: 2008/12/09, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.8
```

58988 - PHP < 5.3.12 / 5.4.2 CGI Query String Code Execution

Synopsis

The remote web server uses a version of PHP that is affected by a remote code execution vulnerability.

Description

According to its banner, the version of PHP installed on the remote host is earlier than 5.3.12 / 5.4.2, and as such is potentially affected by a remote code execution and information disclosure vulnerability.

An error in the file 'sapi/cgi/cgi_main.c' can allow a remote attacker to obtain PHP source code from the web server or to potentially execute arbitrary code. In vulnerable configurations, PHP treats certain query string parameters as command line arguments including switches such as '-s', '-d', and '-c'.

Note that this vulnerability is exploitable only when PHP is used in CGI-based configurations. Apache with 'mod_php' is not an exploitable configuration.

See Also

<http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/>

<https://bugs.php.net/bug.php?id=61910>

<http://www.php.net/archive/2012.php#id2012-05-03-1>

<http://www.php.net/ChangeLog-5.php#5.3.12>

<http://www.php.net/ChangeLog-5.php#5.4.2>

Solution

Upgrade to PHP version 5.3.12 / 5.4.2 or later. A 'mod_rewrite' workaround is available as well.

Risk Factor

High

VPR Score

8.9

EPSS Score

0.9439

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

BID	53388
CVE	CVE-2012-1823
XREF	CERT:520827
XREF	CISA-KNOWN-EXPLOITED:2022/04/15

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2012/05/04, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.3.12 / 5.4.2
```


Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.3.9. As such, it may be affected by the following security issues :

- The 'is_a()' function in PHP 5.3.7 and 5.3.8 triggers a call to '__autoload()'. (CVE-2011-3379)
- It is possible to create a denial of service condition by sending multiple, specially crafted requests containing parameter values that cause hash collisions when computing the hash values for storage in a hash table. (CVE-2011-4885)
- An integer overflow exists in the exif_process_IFD_TAG function in exif.c that can allow a remote attacker to read arbitrary memory locations or cause a denial of service condition. This vulnerability only affects PHP 5.4.0beta2 on 32-bit platforms. (CVE-2011-4566)
- Calls to libxslt are not restricted via xsltSetSecurityPrefs(), which could allow an attacker to create or overwrite files, resulting in arbitrary code execution. (CVE-2012-0057)
- An error exists in the function 'tidy_diagnose' that can allow an attacker to cause the application to dereference a NULL pointer. This causes the application to crash. (CVE-2012-0781)
- The 'PDORow' implementation contains an error that can cause application crashes when interacting with the session feature. (CVE-2012-0788)
- An error exists in the timezone handling such that repeated calls to the function 'strtotime' can allow a denial of service attack via memory consumption. (CVE-2012-0789)

See Also

<https://www.tenable.com/security/research/tra-2012-01>
http://xhe.myxwiki.org/xwiki/bin/view/XSLT/Application_PHP5
<http://www.php.net/archive/2012.php#id2012-01-11-1>
<https://seclists.org/bugtraq/2012/Jan/91>
<https://bugs.php.net/bug.php?id=55475>
<https://bugs.php.net/bug.php?id=55776>
<https://bugs.php.net/bug.php?id=53502>
<http://www.php.net/ChangeLog-5.php#5.3.9>

Solution

Upgrade to PHP version 5.3.9 or later.

Risk Factor

High

VPR Score

6.3

EPSS Score

0.8858

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.5 (CVSS2#E:H/RL:OF/RC:C)

References

BID	49754
BID	50907
BID	51193
BID	51806
BID	51952
BID	51992
BID	52043
CVE	CVE-2011-3379
CVE	CVE-2011-4566
CVE	CVE-2011-4885
CVE	CVE-2012-0057
CVE	CVE-2012-0781
CVE	CVE-2012-0788
CVE	CVE-2012-0789
XREF	TRA:TRA-2012-01

Exploitable With

Core Impact (true)

Plugin Information

Published: 2012/01/13, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version      : 5.3.9
```

142591 - PHP < 7.3.24 Multiple Vulnerabilities

Synopsis

The version of PHP running on the remote web server is affected by multiple vulnerabilities.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.24. It is, therefore affected by multiple vulnerabilities

See Also

<https://www.php.net/ChangeLog-7.php#7.3.24>

Solution

Upgrade to PHP version 7.3.24 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

STIG Severity

I

References

XREF IAVA:2020-A-0510-S

Plugin Information

Published: 2020/11/06, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
URL      : http://192.168.50.3/ (5.2.4-2ubuntu5.10 under X-Powered-By:
PHP/5.2.4-2ubuntu5.10)
Installed version : 5.2.4-2ubuntu5.10
Fixed version    : 7.3.24
```

63349 - PostgreSQL 7.4 < 7.4.29 / 8.0 < 8.0.25 / 8.1 < 8.1.21 / 8.2 < 8.2.17 / 8.3 < 8.3.11 / 8.4 < 8.4.4 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 7.4 prior to 7.4.29, 8.0 prior to 8.0.25, 8.1 prior to 8.1.21, 8.2 prior to 8.2.17, 8.3 prior to 8.3.11 or 8.4 prior to 8.4.4. As such, it is potentially affected by multiple vulnerabilities :

- A vulnerability in Safe.pm and PL/Perl can allow an authenticated user to run arbitrary Perl code on the database server if PL/Perl is installed and enabled.

(CVE-2010-1169)

- Insecure permissions on the pltcl_modules table could allow an authenticated user to run arbitrary Tcl code on the database server if PL/Tcl is installed and enabled. (CVE-2010-1170)

- An unprivileged database user can remove superuser-only settings that were applied to the user's account with ALTER USER by a superuser thus bypassing settings that should be enforced. (CVE-2010-1975)

See Also

<https://www.postgresql.org/about/news/1203/>

<https://www.postgresql.org/docs/7.4/release-7-4-29.html>

<https://www.postgresql.org/docs/8.0/release-8-0-25.html>

<https://www.postgresql.org/docs/8.1/release-8-1-21.html>

<https://www.postgresql.org/docs/8.2/release-8-2-17.html>

<http://www.postgresql.org/docs/8.3/static/release-8-3-11.html>

<http://www.postgresql.org/docs/8.4/static/release-8-4-4.html>

Solution

Upgrade to PostgreSQL 7.4.29 / 8.0.25 / 8.1.21 / 8.2.17 / 8.3.11 / 8.4.4 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.011

CVSS v2.0 Base Score

8.5 (CVSS2#AV:N/AC:M/Au:S/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

6.3 (CVSS2#E:U/RL:OF/RC:C)

References

BID	40215
BID	40304
CVE	CVE-2010-1169
CVE	CVE-2010-1170
CVE	CVE-2010-1975

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 7.4.29 / 8.0.25 / 8.1.21 / 8.2.17 / 8.3.11 / 8.4.4
```

63355 - PostgreSQL 8.3 < 8.3.18 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 8.3.x prior to 8.3.18, and is, therefore, potentially affected by multiple vulnerabilities :

- Permissions on a function called by a trigger are not properly checked. (CVE-2012-0866)
- Line breaks in object names can be exploited to execute arbitrary SQL commands when reloading a pg_dump file.
(CVE-2012-0868)

See Also

<http://www.postgresql.org/about/news/1377/>

<https://www.postgresql.org/docs/8.3/release-8-3-18.html>

Solution

Upgrade to PostgreSQL 8.3.18 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

6.4 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.5

EPSS Score

0.0535

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID	52188
CVE	CVE-2012-0866
CVE	CVE-2012-0868

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 8.3.18
```

63353 - PostgreSQL 8.3 < 8.3.19 / 8.4 < 8.4.12 / 9.0 < 9.0.8 / 9.1 < 9.1.4 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 8.3.x prior to 8.3.19, 8.4.x prior to 8.4.12, 9.0.x prior to 9.0.8, or 9.1.x prior to 9.1.4. As such, it is potentially affected by multiple vulnerabilities :

- Passwords containing the byte 0x80 passed to the crypt() function in pgcrypto are incorrectly truncated if DES encryption was used. (CVE-2012-2143)
- SECURITY_DEFINER and SET attributes on procedural call handlers are not ignored and can be used to crash the server. (CVE-2012-2655)

See Also

<https://www.postgresql.org/about/news/1398/>

<https://www.postgresql.org/docs/8.3/release-8-3-19.html>

<https://www.postgresql.org/docs/8.4/release-8-4-12.html>

<https://www.postgresql.org/docs/9.0/release-9-0-8.html>

<https://www.postgresql.org/docs/9.1/release-9-1-4.html>

Solution

Upgrade to PostgreSQL 8.3.19 / 8.4.12 / 9.0.8 / 9.1.4 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.5

EPSS Score

0.0576

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	53729
BID	53812
CVE	CVE-2012-2143
CVE	CVE-2012-2655

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 8.3.19 / 8.4.12 / 9.0.8 / 9.1.4
```

94437 - SSL 64-bit Block Size Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of 64-bit block ciphers.

Description

The remote host supports the use of a block cipher with 64-bit blocks in one or more cipher suites. It is, therefore, affected by a vulnerability, known as SWEET32, due to the use of weak 64-bit block ciphers. A man-in-the-middle attacker who has sufficient resources can exploit this vulnerability, via a 'birthday' attack, to detect a collision that leaks the XOR between the fixed secret and a known plaintext, allowing the disclosure of the secret text, such as secure HTTPS cookies, and possibly resulting in the hijacking of an authenticated session.

Proof-of-concepts have shown that attackers can recover authentication cookies from an HTTPS session in as little as 30 hours.

Note that the ability to send a large number of requests over the same TLS connection between the client and server is an important requirement for carrying out this attack. If the number of requests allowed for a single connection were limited, this would mitigate the vulnerability. This plugin requires report paranoia as Nessus has not checked for such a mitigation.

See Also

<https://sweet32.info>

<https://www.openssl.org/blog/blog/2016/08/24/sweet32/>

Solution

Reconfigure the affected application, if possible, to avoid use of all 64-bit block ciphers. Alternatively, place limitations on the number of requests that are allowed to be processed over the same TLS connection to mitigate this vulnerability.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.7 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.3833

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID 92630
BID 92631
CVE CVE-2016-2183
CVE CVE-2016-6329
XREF CEA-ID:CEA-2019-0547

Plugin Information

Published: 2016/11/01, Modified: 2022/12/05

Plugin Output

tcp/25/smtp

List of 64-bit block cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA(512)	RSA	RC2-CBC(40)	MD5

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC(168)	
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC(168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}

```
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

94437 - SSL 64-bit Block Size Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of 64-bit block ciphers.

Description

The remote host supports the use of a block cipher with 64-bit blocks in one or more cipher suites. It is, therefore, affected by a vulnerability, known as SWEET32, due to the use of weak 64-bit block ciphers. A man-in-the-middle attacker who has sufficient resources can exploit this vulnerability, via a 'birthday' attack, to detect a collision that leaks the XOR between the fixed secret and a known plaintext, allowing the disclosure of the secret text, such as secure HTTPS cookies, and possibly resulting in the hijacking of an authenticated session.

Proof-of-concepts have shown that attackers can recover authentication cookies from an HTTPS session in as little as 30 hours.

Note that the ability to send a large number of requests over the same TLS connection between the client and server is an important requirement for carrying out this attack. If the number of requests allowed for a single connection were limited, this would mitigate the vulnerability. This plugin requires report paranoia as Nessus has not checked for such a mitigation.

See Also

<https://sweet32.info>

<https://www.openssl.org/blog/blog/2016/08/24/sweet32/>

Solution

Reconfigure the affected application, if possible, to avoid use of all 64-bit block ciphers. Alternatively, place limitations on the number of requests that are allowed to be processed over the same TLS connection to mitigate this vulnerability.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

6.7 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.3833

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	92630
BID	92631
CVE	CVE-2016-2183
CVE	CVE-2016-6329
XREF	CEA-ID:CEA-2019-0547

Plugin Information

Published: 2016/11/01, Modified: 2022/12/05

Plugin Output

tcp/5432/postgresql

List of 64-bit block cipher suites supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```


42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

VPR Score

6.1

EPSS Score

0.3833

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/25/smtp

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC (168)	MD5
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC (168)	
SHA1					
ADH-DES-CBC3-SHA	0x00, 0x1B	DH	None	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

The fields above are :

{Tenable ciphername}

{Cipher ID code}

Kex={key exchange}

Auth={authentication}

Encrypt={symmetric encryption method}

MAC={message authentication code}

{export flag}

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32)

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?df5555f5>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

VPR Score

6.1

EPSS Score

0.3833

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE CVE-2016-2183

Plugin Information

Published: 2009/11/23, Modified: 2025/02/12

Plugin Output

tcp/5432/postgresql

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

The fields above are :

{Tenable ciphertype}

{Cipher ID code}

Kex={key exchange}

Auth={authentication}

Encrypt={symmetric encryption method}

MAC={message authentication code}

{export flag}

47036 - Samba 3.x < 3.3.13 SMB1 Packet Chaining Memory Corruption

Synopsis

The remote service is affected by a memory corruption vulnerability.

Description

According to its banner, the version of Samba running on the remote host is a version of 3.x before 3.3.13. Such versions are affected by a memory corruption vulnerability when handling specially crafted SMB1 packets.

By exploiting this flaw, a remote, unauthenticated attacker could crash the affected service or potentially execute arbitrary code subject to the privileges of the user running the affected application.

See Also

<https://www.samba.org/samba/security/CVE-2010-2063.html>

<https://www.samba.org/samba/history/security.html>

Solution

Upgrade to Samba 3.3.13 or later.

Risk Factor

High

VPR Score

7.4

EPSS Score

0.7818

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

6.2 (CVSS2#E:F/RL:OF/RC:C)

References

BID 40884

CVE CVE-2010-2063

XREF

Secunia:40145

Exploitable With

Metasploit (true)

Plugin Information

Published: 2010/06/17, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
The remote Samba server appears to be :
```

```
Samba 3.0.20-Debian
```

49228 - Samba 3.x < 3.5.5 / 3.4.9 / 3.3.14 sid_parse Buffer Overflow

Synopsis

The remote Samba server is affected by a buffer overflow vulnerability.

Description

According to its banner, the version of Samba 3.x running on the remote host is earlier than 3.5.5. The 'sid_parse()' and related 'dom_sid_parse()' functions in such versions fail to correctly check their input lengths when reading a binary representation of a Windows SID (Security ID).

An attacker who is able to get a connection to a file share, either authenticated or via a guest connection, can leverage this issue to launch a stack-based buffer overflow attack against the affected smbd service and possibly execute arbitrary code.

Note that Nessus has not actually tried to exploit this issue or determine if one of the patches has been applied.

See Also

https://bugzilla.samba.org/show_bug.cgi?id=7669

<https://www.samba.org/samba/security/CVE-2010-3069.html>

<https://www.samba.org/samba/history/samba-3.5.5.html>

<https://www.samba.org/samba/history/samba-3.4.9.html>

<https://www.samba.org/samba/history/samba-3.3.14.html>

Solution

Either apply one of the patches referenced in the project's advisory or upgrade to 3.5.5 / 3.4.9 / 3.3.14 or later.

Risk Factor

High

VPR Score

5.9

EPSS Score

0.1768

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	43212
CVE	CVE-2010-3069
XREF	Secunia:41354

Plugin Information

Published: 2010/09/15, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.5.5 / 3.4.9 / 3.3.14
```


90508 - Samba 3.x < 4.2.10 / 4.2.x < 4.2.10 / 4.3.x < 4.3.7 / 4.4.x < 4.4.1 Multiple Vulnerabilities (Badlock)

Synopsis

The remote Samba server is affected by multiple vulnerabilities.

Description

The version of Samba running on the remote host is 3.x or 4.2.x prior to 4.2.10, 4.3.x prior to 4.3.7, or 4.4.x prior to 4.4.1. It is, therefore, affected by multiple vulnerabilities :

- A flaw exists in the DCE-RPC client when handling specially crafted DCE-RPC packets. A man-in-the-middle (MitM) attacker can exploit this to downgrade the connection security, cause a denial of service through resource exhaustion, or potentially execute arbitrary code. (CVE-2015-5370)
- A flaw exists in the implementation of NTLMSSP authentication. A MitM attacker can exploit this to clear the NTLMSSP_NEGOTIATE_SIGN and NTLMSSP_NEGOTIATE_SEAL settings, take over the connections, cause traffic to be sent unencrypted, or have other unspecified impact. (CVE-2016-2110)
- A flaw exists in NETLOGON due to a failure to properly establish a secure channel connection. A MitM attacker can exploit this to spoof the computer names of a secure channel's endpoints, potentially gaining session information. (CVE-2016-2111)
- A flaw exists in the integrity protection mechanisms that allows a MitM attacker to downgrade a secure LDAP connection to an insecure version. (CVE-2016-2112)
- A flaw exists due to improper validation of TLS certificates for the LDAP and HTTP protocols. A MitM attacker can exploit this, via a crafted certificate, to spoof a server, resulting in the disclosure or manipulation of the transmitted traffic. (CVE-2016-2113)
- A flaw exists due to a failure to enforce the 'server signing = mandatory' option in smb.conf for clients using the SMB1 protocol. A MitM attacker can exploit this to conduct spoofing attacks. (CVE-2016-2114)
- A flaw exists due to a failure to perform integrity checking for SMB client connections. A MitM attacker can exploit this to conduct spoofing attacks since the protection mechanisms for DCERPC communication sessions are inherited from the underlying SMB connection. (CVE-2016-2115)
- A flaw, known as Badlock, exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A MitM attacker who is able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services. (CVE-2016-2118)

See Also

<https://www.samba.org/samba/security/CVE-2015-5370.html>

<https://www.samba.org/samba/security/CVE-2016-2110.html>

<https://www.samba.org/samba/security/CVE-2016-2111.html>
<https://www.samba.org/samba/security/CVE-2016-2112.html>
<https://www.samba.org/samba/security/CVE-2016-2113.html>
<https://www.samba.org/samba/security/CVE-2016-2114.html>
<https://www.samba.org/samba/security/CVE-2016-2115.html>
<https://www.samba.org/samba/security/CVE-2016-2118.html>
<https://www.samba.org/samba/history/samba-4.2.10.html>
<https://www.samba.org/samba/history/samba-4.3.7.html>
<https://www.samba.org/samba/history/samba-4.4.1.html>
<http://badlock.org>

Solution

Upgrade to Samba version 4.2.10 / 4.3.7 / 4.4.1 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.7993

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 86002

CVE	CVE-2015-5370
CVE	CVE-2016-2110
CVE	CVE-2016-2111
CVE	CVE-2016-2112
CVE	CVE-2016-2113
CVE	CVE-2016-2114
CVE	CVE-2016-2115
CVE	CVE-2016-2118
XREF	CERT:813296

Plugin Information

Published: 2016/04/13, Modified: 2019/11/20

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 4.2.10
```

24685 - Samba < 3.0.24 Multiple Flaws

Synopsis

The remote Samba server is affected by several vulnerabilities that could lead to remote code execution

Description

According to its version number, the remote Samba server is affected by several flaws :

- A denial of service issue occurring if an authenticated attacker sends a large number of CIFS session requests which will cause an infinite loop to occur in the smbd daemon, thus utilizing CPU resources and denying access to legitimate users ;
- A remote format string vulnerability that could be exploited by an attacker with write access to a remote share by sending a malformed request to the remote service (this issue only affects installations sharing an AFS file system when the afsacl.so VFS module is loaded)
- A remote buffer overflow vulnerability affecting the NSS lookup capability of the remote winbindd daemon

Solution

Upgrade to Samba 3.0.24 or newer

Risk Factor

High

VPR Score

5.8

EPSS Score

0.0464

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.5 (CVSS2#E:U/RL:OF/RC:C)

References

BID	22395
BID	22403
BID	22410

CVE	CVE-2007-0452
CVE	CVE-2007-0453
CVE	CVE-2007-0454

Plugin Information

Published: 2007/02/22, Modified: 2018/07/27

Plugin Output

tcp/445/cifs

28228 - Samba < 3.0.27 Multiple Vulnerabilities

Synopsis

The remote Samba server may be affected one or more vulnerabilities.

Description

According to its banner, the version of the Samba server on the remote host contains a boundary error in the 'reply_netbios_packet()'

function in 'nmbd/nmbd_packets.c' when sending NetBIOS replies.

Provided the server is configured to run as a WINS server, a remote attacker can exploit this issue by sending multiple specially crafted WINS 'Name Registration' requests followed by a WINS 'Name Query' request, leading to a stack-based buffer overflow. This could also allow for the execution of arbitrary code.

There is also a stack buffer overflow in nmbd's logon request processing code that can be triggered by means of specially crafted GETDC mailslot requests when the affected server is configured as a Primary or Backup Domain Controller. Note that the Samba security team currently does not believe this particular issue can be exploited to execute arbitrary code remotely.

See Also

https://secuniaresearch.flexerasoftware.com/secunia_research/2007-90/advisory/

<https://www.securityfocus.com/archive/1/483744>

<http://us1.samba.org/samba/security/CVE-2007-4572.html>

<http://us1.samba.org/samba/security/CVE-2007-5398.html>

<https://www.securityfocus.com/archive/1/483742>

<https://www.securityfocus.com/archive/1/483743>

Solution

Upgrade to Samba version 3.0.27 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.4072

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

6.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	26454
BID	26455
CVE	CVE-2007-4572
CVE	CVE-2007-5398
XREF	CWE:119

Plugin Information

Published: 2007/11/16, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

29253 - Samba < 3.0.28 send_mailslot Function Remote Buffer Overflow

Synopsis

The remote Samba server may be affected by a buffer overflow vulnerability.

Description

According to its banner, the version of the Samba server on the remote host is reportedly affected by a boundary error in 'nmbd' within the 'send_mailslot' function. Provided the 'domain logons' option is enabled in 'smb.conf', an attacker can leverage this issue to produce a stack-based buffer overflow using a 'SAMLOGON' domain logon packet in which the username string is placed at an odd offset and is followed by a long 'GETDC' string.

Note that Nessus has not actually tried to exploit this issue nor verify whether the 'domain logons' option has been enabled on the remote host.

See Also

https://secuniaresearch.flexerasoftware.com/secunia_research/2007-99/advisory/

<https://www.securityfocus.com/archive/1/484818/30/0/threaded>

<https://www.samba.org/samba/security/CVE-2007-6015.html>

Solution

Upgrade to Samba version 3.0.28 or later.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.4392

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	26791
CVE	CVE-2007-6015
XREF	CWE:119

Plugin Information

Published: 2007/12/10, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

32476 - Samba < 3.0.30 receive_smb_raw Function Remote Buffer Overflow

Synopsis

The remote Samba server may be affected by a buffer overflow vulnerability.

Description

According to its banner, the version of the Samba server on the remote host is reportedly affected by a boundary error in 'nmbd' within the 'receive_smb_raw' function in 'lib/util_sock.c' when parsing SMB packets received in a client context. By sending specially crafted packets to an 'nmbd' server configured as a local or domain master browser, an attacker can leverage this issue to produce a heap-based buffer overflow and execute arbitrary code with system privileges.

Note that Nessus has not actually tried to exploit this issue, verify the remote 'nmbd' server's configuration, or determine if the fix has been applied.

See Also

https://secuniaresearch.flexerasoftware.com/secunia_research/2008-20/advisory/

<https://www.samba.org/samba/security/CVE-2008-1105.html>

<https://seclists.org/bugtraq/2008/May/328>

Solution

Upgrade to Samba version 3.0.30 or later or apply the patch referenced in the project's advisory.

Risk Factor

High

VPR Score

6.0

EPSS Score

0.7193

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	29404
CVE	CVE-2008-1105
XREF	Secunia:30228
XREF	CWE:119

Plugin Information

Published: 2008/05/29, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
The remote Samba server appears to be :
```

```
Samba 3.0.20-Debian
```

122058 - Samba < 3.4.0 Remote Code Execution Vulnerability

Synopsis

The remote Samba server is affected by a remote code execution vulnerability.

Description

The version of Samba running on the remote host is prior to 3.4.0. It is, therefore, affected by a remote code execution vulnerability in process.c due to a heap-based buffer overflow. An unauthenticated, remote attacker can exploit this to bypass authentication and execute arbitrary commands via Batched / AndX request.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.samba.org/samba/security/CVE-2012-0870.html>

Solution

Upgrade to Samba version 3.4.0 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.489

CVSS v2.0 Base Score

7.9 (CVSS2#AV:A/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	52103
CVE	CVE-2012-0870

Plugin Information

Published: 2019/02/08, Modified: 2019/10/31

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.4.0
```

168018 - Samba < 4.15.12, 4.16.x < 4.16.7, and 4.17.x < 4.17.3 32-Bit Systems Buffer Overflow

Synopsis

The remote Samba server is potentially affected by a buffer overflow vulnerability

Description

The version of Samba running on the remote host is prior to 4.15.12, 4.16.x prior to 4.16.7, or 4.17.x prior to 4.17.3.

It is, therefore, potentially affected by a buffer overflow condition in the bundled Kerberos libraries due to a miss calculation of bytes to allocate for a buffer. An authenticated, remote attacker can exploit this, via a specially crafted ticket containing Privilege Attribute Certificates, to cause a denial of service condition or read beyond the memory bounds.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.samba.org/samba/security/CVE-2022-42898.html>

Solution

Upgrade to Samba version 4.15.12, 4.16.7, 4.17.3 or later.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

7.9 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.0686

CVSS v2.0 Base Score

9.0 (CVSS2#AV:N/AC:L/Au:S/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

7.0 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-42898
XREF	IAVA:2022-A-0495-S

Plugin Information

Published: 2022/11/21, Modified: 2023/10/03

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 4.15.12
```

90509 - Samba Badlock Vulnerability

Synopsis

An SMB server running on the remote host is affected by the Badlock vulnerability.

Description

The version of Samba, a CIFS/SMB server for Linux and Unix, running on the remote host is affected by a flaw, known as Badlock, that exists in the Security Account Manager (SAM) and Local Security Authority (Domain Policy) (LSAD) protocols due to improper authentication level negotiation over Remote Procedure Call (RPC) channels. A man-in-the-middle attacker who is able to intercept the traffic between a client and a server hosting a SAM database can exploit this flaw to force a downgrade of the authentication level, which allows the execution of arbitrary Samba network calls in the context of the intercepted user, such as viewing or modifying sensitive security data in the Active Directory (AD) database or disabling critical services.

See Also

<http://badlock.org>

<https://www.samba.org/samba/security/CVE-2016-2118.html>

Solution

Upgrade to Samba version 4.2.11 / 4.3.8 / 4.4.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

7.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

6.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.7993

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID	86002
CVE	CVE-2016-2118
XREF	CERT:813296

Plugin Information

Published: 2016/04/13, Modified: 2019/11/20

Plugin Output

tcp/445/cifs

```
Nessus detected that the Samba Badlock patch has not been applied.
```

10205 - rlogin Service Detection

Synopsis

The rlogin service is running on the remote host.

Description

The rlogin service is running on the remote host. This service is vulnerable since data is passed between the rlogin client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rlogin is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

Solution

Comment out the 'login' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.5006

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0651

Exploitable With

Metasploit (true)

Plugin Information

Published: 1999/08/30, Modified: 2022/04/11

Plugin Output

tcp/513/rlogin

10245 - rsh Service Detection

Synopsis

The rsh service is running on the remote host.

Description

The rsh service is running on the remote host. This service is vulnerable since data is passed between the rsh client and server in cleartext. A man-in-the-middle attacker can exploit this to sniff logins and passwords. Also, it may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

Finally, rsh is an easy way to turn file-write access into full logins through the .rhosts or rhosts.equiv files.

Solution

Comment out the 'rsh' line in /etc/inetd.conf and restart the inetd process. Alternatively, disable this service and use SSH instead.

Risk Factor

High

VPR Score

6.7

EPSS Score

0.5006

CVSS v2.0 Base Score

7.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:P)

References

CVE CVE-1999-0651

Exploitable With

Metasploit (true)

Plugin Information

Published: 1999/08/22, Modified: 2022/04/11

Plugin Output

tcp/514/rsh

48205 - Apache 2.2.x < 2.2.16 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.16. It is, therefore, potentially affected by multiple vulnerabilities :

- A denial of service vulnerability in mod_cache and mod_dav. (CVE-2010-1452)
- An information disclosure vulnerability in mod_proxy_ajp, mod_reqtimeout, and mod_proxy_http relating to timeout conditions. Note that this issue only affects Apache on Windows, Netware, and OS/2. (CVE-2010-2068)

Note that the remote web server may not actually be affected by these vulnerabilities. Nessus did not try to determine whether the affected modules are in use or to check for the issues themselves.

See Also

http://httpd.apache.org/security/vulnerabilities_22.html
https://issues.apache.org/bugzilla/show_bug.cgi?id=49246
https://bz.apache.org/bugzilla/show_bug.cgi?id=49417
<http://www.nessus.org/u?ce8ac446>

Solution

Upgrade to Apache version 2.2.16 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.2372

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	40827
BID	41963
CVE	CVE-2010-1452
CVE	CVE-2010-2068
XREF	Secunia:40206

Plugin Information

Published: 2010/07/30, Modified: 2018/11/15

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.16
```

50070 - Apache 2.2.x < 2.2.17 Multiple Vulnerabilities

Synopsis

The remote web server may be affected by several issues.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.17. It is, therefore, affected by the following vulnerabilities :

- Errors exist in the bundled expat library that may allow an attacker to crash the server when a buffer is over- read when parsing an XML document. (CVE-2009-3720 and CVE-2009-3560)
- An error exists in the 'apr_brigade_split_line' function in the bundled APR-util library. Carefully timed bytes in requests result in gradual memory increases leading to a denial of service. (CVE-2010-1623) Note that the remote web server may not actually be affected by these vulnerabilities. Nessus did not try to determine whether the affected modules are in use or to check for the issues themselves.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.17
http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.17 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.2286

CVSS v2.0 Base Score

192.168.50.3

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	37203
BID	36097
BID	43673
CVE	CVE-2009-3560
CVE	CVE-2009-3720
CVE	CVE-2010-1623
XREF	Secunia:41701
XREF	CWE:119

Plugin Information

Published: 2010/10/20, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.17
```

53896 - Apache 2.2.x < 2.2.18 APR apr_fnmatch DoS

Synopsis

The remote web server may be affected by a denial of service vulnerability.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.18. It is, therefore, affected by a denial of service vulnerability due to an error in the `apr_fnmatch()` function of the bundled APR library.

If `mod_autoindex` is enabled and has indexed a directory containing files whose filenames are long, an attacker can cause high CPU usage with a specially crafted request.

Note that the remote web server may not actually be affected by this vulnerability. Nessus did not try to determine whether the affected module is in use or to check for the issue itself.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.18

http://httpd.apache.org/security/vulnerabilities_22.html#2.2.18

http://securityreason.com/achievement_securityalert/98

Solution

Upgrade to Apache version 2.2.18 or later. Alternatively, ensure that the 'IndexOptions' configuration option is set to 'IgnoreClient'.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

5.1

EPSS Score

0.5621

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	47820
CVE	CVE-2011-0419
XREF	Secunia:44574

Plugin Information

Published: 2011/05/13, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.18
```

56216 - Apache 2.2.x < 2.2.21 mod_proxy_ajp DoS

Synopsis

The remote web server is affected by a denial of service vulnerability.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.21. It is, therefore, potentially affected by a denial of service vulnerability. An error exists in the 'mod_proxy_ajp' module that can allow specially crafted HTTP requests to cause a backend server to temporarily enter an error state. This vulnerability only occurs when 'mod_proxy_ajp' is used along with 'mod_proxy_balancer'.

Note that Nessus did not actually test for the flaws but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.21

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.21 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

2.2

EPSS Score

0.5232

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	49616
CVE	CVE-2011-3348

Plugin Information

Published: 2011/09/16, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.21
```

57791 - Apache 2.2.x < 2.2.22 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x installed on the remote host is prior to 2.2.22. It is, therefore, potentially affected by the following vulnerabilities :

- When configured as a reverse proxy, improper use of the RewriteRule and ProxyPassMatch directives could cause the web server to proxy requests to arbitrary hosts.

This could allow a remote attacker to indirectly send requests to intranet servers.

(CVE-2011-3368, CVE-2011-4317)

- A heap-based buffer overflow exists when mod_setenvif module is enabled and both a maliciously crafted 'SetEnvIf' directive and a maliciously crafted HTTP request header are used. (CVE-2011-3607)

- A format string handling error can allow the server to be crashed via maliciously crafted cookies.

(CVE-2012-0021)

- An error exists in 'scoreboard.c' that can allow local attackers to crash the server during shutdown.

(CVE-2012-0031)

- An error exists in 'protocol.c' that can allow 'HTTPOnly' cookies to be exposed to attackers through the malicious use of either long or malformed HTTP headers. (CVE-2012-0053)

- An error in the mod_proxy_ajp module when used to connect to a backend server that takes an overly long time to respond could lead to a temporary denial of service. (CVE-2012-4557)

Note that Nessus did not actually test for these flaws, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.22

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.22 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.8226

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	49957
BID	50494
BID	50802
BID	51407
BID	51705
BID	51706
BID	56753
CVE	CVE-2011-3368
CVE	CVE-2011-3607
CVE	CVE-2011-4317
CVE	CVE-2012-0021
CVE	CVE-2012-0031
CVE	CVE-2012-0053
CVE	CVE-2012-4557

Plugin Information

Published: 2012/02/02, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
```

Fixed version : 2.2.22

64912 - Apache 2.2.x < 2.2.24 Multiple XSS Vulnerabilities

Synopsis

The remote web server is affected by multiple cross-site scripting vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.24. It is, therefore, potentially affected by the following cross-site scripting vulnerabilities :

- Errors exist related to the modules mod_info, mod_status, mod_imagemap, mod_ldap, and mod_proxy_ftp and unescaped hostnames and URIs that could allow cross-site scripting attacks. (CVE-2012-3499)

- An error exists related to the mod_proxy_balancer module's manager interface that could allow cross-site scripting attacks. (CVE-2012-4558)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.24

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.24 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.0

EPSS Score

0.5743

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	58165
CVE	CVE-2012-3499
CVE	CVE-2012-4558
XREF	CWE:20
XREF	CWE:74
XREF	CWE:79
XREF	CWE:442
XREF	CWE:629
XREF	CWE:711
XREF	CWE:712
XREF	CWE:722
XREF	CWE:725
XREF	CWE:750
XREF	CWE:751
XREF	CWE:800
XREF	CWE:801
XREF	CWE:809
XREF	CWE:811
XREF	CWE:864
XREF	CWE:900
XREF	CWE:928
XREF	CWE:931
XREF	CWE:990

Plugin Information

Published: 2013/02/27, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.24
```


68915 - Apache 2.2.x < 2.2.25 Multiple Vulnerabilities

Synopsis

The remote web server may be affected by multiple cross-site scripting vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.25. It is, therefore, potentially affected by the following vulnerabilities :

- A flaw exists in the 'RewriteLog' function where it fails to sanitize escape sequences from being written to log files, making it potentially vulnerable to arbitrary command execution. (CVE-2013-1862)
- A denial of service vulnerability exists relating to the 'mod_dav' module as it relates to MERGE requests. (CVE-2013-1896)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.25
http://httpd.apache.org/security/vulnerabilities_22.html
<http://www.nessus.org/u?f050c342>

Solution

Upgrade to Apache version 2.2.25 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.6 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

4.9 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.4176

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	59826
BID	61129
CVE	CVE-2013-1862
CVE	CVE-2013-1896

Plugin Information

Published: 2013/07/16, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.25
```

73405 - Apache 2.2.x < 2.2.27 Multiple Vulnerabilities

Synopsis

The remote web server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is a version prior to 2.2.27. It is, therefore, potentially affected by the following vulnerabilities :

- A flaw exists with the 'mod_dav' module that is caused when tracking the length of CDATA that has leading white space. A remote attacker with a specially crafted DAV WRITE request can cause the service to stop responding.

(CVE-2013-6438)

- A flaw exists in 'mod_log_config' module that is caused when logging a cookie that has an unassigned value. A remote attacker with a specially crafted request can cause the service to crash. (CVE-2014-0098)

Note that Nessus did not actually test for these issues, but instead has relied on the version in the server's banner.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2.27

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.27 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.474

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	66303
CVE	CVE-2013-6438
CVE	CVE-2014-0098

Plugin Information

Published: 2014/04/08, Modified: 2018/09/17

Plugin Output

tcp/80/www

```
Version source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version : 2.2.8
Fixed version    : 2.2.27
```

33477 - Apache 2.2.x < 2.2.9 Multiple Vulnerabilities (DoS, XSS)

Synopsis

The remote web server may be affected by several issues.

Description

According to its banner, the version of Apache 2.2.x running on the remote host is prior to 2.2.9. It is, therefore, affected by multiple vulnerabilities :

- Improper handling of excessive forwarded interim responses may cause denial of service conditions in mod_proxy_http. (CVE-2008-2364)
- A cross-site request forgery vulnerability in the balancer-manager interface of mod_proxy_balancer. (CVE-2007-6420)

Note that the remote web server may not actually be affected by these vulnerabilities. Nessus did not try to determine whether the affected modules are in use or to check for the issues themselves.

See Also

https://archive.apache.org/dist/httpd/CHANGES_2.2

http://httpd.apache.org/security/vulnerabilities_22.html

Solution

Upgrade to Apache version 2.2.9 or later. Alternatively, ensure that the affected modules are not in use.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.2

EPSS Score

0.0504

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID	27236
BID	29653
CVE	CVE-2007-6420
CVE	CVE-2008-2364
CVE	CVE-2007-6423
XREF	Secunia:30621
XREF	CWE:352
XREF	CWE:399

Plugin Information

Published: 2008/07/11, Modified: 2018/06/29

Plugin Output

tcp/80/www

```
Version source      : Server: Apache/2.2.8 (Ubuntu) DAV/2
Installed version   : 2.2.8
Fixed version       : 2.2.9
```

193420 - Apache 2.4.x < 2.4.54 Out-Of-Bounds Read (CVE-2022-28330)

Synopsis

The remote web server is affected by an out-of-bound read vulnerability

Description

The version of Apache httpd installed on the remote host is prior to 2.4.54. It is, therefore, affected by an out-of-bounds read vulnerability as referenced in the 2.4.54 advisory.

- Read beyond bounds in mod_isapi: Apache HTTP Server 2.4.53 and earlier on Windows may read beyond bounds when configured to process requests with the mod_isapi module. Acknowledgements: The Apache HTTP Server project would like to thank Ronald Crane (Zippenhop LLC) for reporting this issue

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

https://httpd.apache.org/security/vulnerabilities_24.html

Solution

Upgrade to Apache version 2.4.54 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.0019

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-28330
XREF	IAVA:2022-A-0230-S

Plugin Information

Published: 2024/04/17, Modified: 2024/04/18

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/  
Installed version : 2.2.8  
Fixed version  : 2.4.54
```

57792 - Apache HTTP Server httpOnly Cookie Information Disclosure

Synopsis

The web server running on the remote host is affected by an information disclosure vulnerability.

Description

The version of Apache HTTP Server running on the remote host is affected by an information disclosure vulnerability. Sending a request with HTTP headers long enough to exceed the server limit causes the web server to respond with an HTTP 400. By default, the offending HTTP header and value are displayed on the 400 error page. When used in conjunction with other attacks (e.g., cross-site scripting), this could result in the compromise of httpOnly cookies.

See Also

http://fd.the-wildcat.de/apache_e36a9cf46c.php

<http://www.nessus.org/u?e005199a>

http://httpd.apache.org/security/vulnerabilities_22.html

<http://svn.apache.org/viewvc?view=revision&revision=1235454>

Solution

Upgrade to Apache version 2.0.65 / 2.2.22 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

2.2

EPSS Score

0.705

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	51706
CVE	CVE-2012-0053
XREF	EDB-ID:18442

Plugin Information

Published: 2012/02/02, Modified: 2018/09/20

Plugin Output

tcp/80/www

Nessus verified this by sending a request with a long Cookie header :

```
GET / HTTP/1.1
Host: 192.168.50.3
Accept-Charset: iso-8859-1,utf-8;q=0.9,*;q=0.1
Accept-Language: en
Connection: Keep-Alive
Cookie: z0=AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA...
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
```

Which caused the Cookie header to be displayed in the default error page
(the response shown below has been truncated) :

```
<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>400 Bad Request</title>
</head><body>
<h1>Bad Request</h1>
<p>Your browser sent a request that this server could not understand.<br />
Size of a request header field exceeds server limit.<br />
<pre>
Cookie: z0=AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA...
```

106232 - Apache ServerTokens Information Disclosure

Synopsis

The remote web server discloses information via HTTP headers.

Description

The HTTP headers sent by the remote web server disclose information that can aid an attacker, such as the server version, operating system, and module versions.

See Also

https://www.owasp.org/index.php/SCG_WS_Apache

Solution

Change the Apache ServerTokens configuration value to 'Prod'

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2018/01/22, Modified: 2020/04/22

Plugin Output

tcp/80/www

The Apache server listening on port 80 contains sensitive information in the HTTP Server field.

Server: Apache/2.2.8 (Ubuntu) DAV/2

12217 - DNS Server Cache Snooping Remote Information Disclosure

Synopsis

The remote DNS server is vulnerable to cache snooping attacks.

Description

The remote DNS server responds to queries for third-party domains that do not have the recursion bit set.

This may allow a remote attacker to determine which domains have recently been resolved via this name server, and therefore which hosts have been recently visited.

For instance, if an attacker was interested in whether your company utilizes the online services of a particular financial institution, they would be able to use this attack to build a statistical model regarding company usage of that financial institution. Of course, the attack can also be used to find B2B partners, web-surfing patterns, external mail servers, and more.

Note: If this is an internal DNS server not accessible to outside networks, attacks would be limited to the internal network. This may include employees, consultants and potentially users on a guest network or WiFi connection if supported.

See Also

http://cs.unc.edu/~fabian/course_papers/cache_snooping.pdf

Solution

Contact the vendor of the DNS software for a fix.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2004/04/27, Modified: 2020/04/07

Plugin Output

udp/53/dns

Nessus sent a non-recursive query for example.edu
and received 4 answers :

23.215.0.241
23.220.75.236
23.220.75.241
23.215.0.236

11213 - HTTP TRACE / TRACK Methods Allowed

Synopsis

Debugging functions are enabled on the remote web server.

Description

The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods that are used to debug web server connections.

See Also

<http://www.nessus.org/u?e979b5cb>

<http://www.apacheweek.com/issues/03-01-24>

<https://download.oracle.com/sunalerts/1000718.1.html>

Solution

Disable these HTTP methods. Refer to the plugin output for more information.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.0

EPSS Score

0.6899

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	9506
BID	9561
BID	11604
BID	33374
BID	37995
CVE	CVE-2003-1567
CVE	CVE-2004-2320
CVE	CVE-2010-0386
XREF	CERT:288308
XREF	CERT:867593
XREF	CWE:16
XREF	CWE:200

Plugin Information

Published: 2003/01/23, Modified: 2024/04/09

Plugin Output

tcp/80/www

To disable these methods, add the following lines for each virtual host in your configuration file :

```
RewriteEngine on
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

Alternatively, note that Apache versions 1.3.34, 2.0.55, and 2.2 support disabling the TRACE method natively via the 'TraceEnable' directive.

Nessus sent the following TRACE request : \n\n----- snip
-----\nTRACE /Nessus2076412632.html HTTP/1.1

Connection: Close
Host: 192.168.50.3
Pragma: no-cache
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8

----- snip -----\n\nand received the following response from the remote server : \n\n----- snip
-----\nHTTP/1.1 200 OK

Date: Wed, 22 Oct 2025 14:38:43 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Connection: close
Transfer-Encoding: chunked
Content-Type: message/http

TRACE /Nessus2076412632.html HTTP/1.1
Connection: Close
Host: 192.168.50.3
Pragma: no-cache

```
User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 5.1; Trident/4.0)
Accept: image/gif, image/x-xbitmap, image/jpeg, image/pjpeg, image/png, */*
Accept-Language: en
Accept-Charset: iso-8859-1,*,utf-8
```

```
----- snip -----\n
```

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the CVE-2021-25219 advisory.

- In BIND 9.3.0 -> 9.11.35, 9.12.0 -> 9.16.21, and versions 9.9.3-S1 -> 9.11.35-S1 and 9.16.8-S1 ->

9.16.21-S1 of BIND Supported Preview Edition, as well as release versions 9.17.0 -> 9.17.18 of the BIND 9.17 development branch, exploitation of broken authoritative servers using a flaw in response processing can cause degradation in BIND resolver performance. The way the lame cache is currently designed makes it possible for its internal data structures to grow almost infinitely, which may cause significant delays in client query processing. (CVE-2021-25219)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/CVE-2021-25219>

Solution

Upgrade to ISC BIND version 9.11.36 / 9.11.36-S1 / 9.16.22 / 9.16.22-S1 / 9.17.19 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.005

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2021-25219
XREF	IAVA:2021-A-0525-S

Plugin Information

Published: 2021/10/28, Modified: 2022/09/27

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.36
```

165312 - ISC BIND 9.9.3-S1 < 9.16.33-S1 / 9.0.0 < 9.16.33 / 9.16.8-S1 < 9.16.33-S1 / 9.18.0 < 9.18.7 / 9.19.0 < 9.19.5 Vulnerability (cve-2022-2795)

Synopsis

The remote name server is affected by a vulnerability vulnerability.

Description

The version of ISC BIND installed on the remote host is prior to tested version. It is, therefore, affected by a vulnerability as referenced in the cve-2022-2795 advisory.

- By flooding the target resolver with queries exploiting this flaw an attacker can significantly impair the resolver's performance, effectively denying legitimate clients access to the DNS resolution service.

(CVE-2022-2795)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/v1/docs/cve-2022-2795>

Solution

Upgrade to ISC BIND version 9.16.33 / 9.16.33-S1 / 9.18.7 / 9.19.5 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.004

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2022-2795
XREF	IAVA:2022-A-0387-S
XREF	IAVA:2023-A-0500-S

Plugin Information

Published: 2022/09/22, Modified: 2024/02/16

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.16.33
```

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is version 9.x prior to 9.11.22, 9.12.x prior to 9.16.6 or 9.17.x prior to 9.17.4. It is, therefore, affected by a denial of service (DoS) vulnerability due to an assertion failure when attempting to verify a truncated response to a TSIG-signed request. An authenticated, remote attacker can exploit this issue by sending a truncated response to a TSIG-signed request to trigger an assertion failure, causing the server to exit.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/cve-2020-8622>

Solution

Upgrade to BIND 9.11.22, 9.16.6, 9.17.4 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0045

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8622
XREF	IAVA:2020-A-0385-S

Plugin Information

Published: 2020/08/27, Modified: 2021/06/03

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.22, 9.16.6, 9.17.4 or later
```

Synopsis

The remote name server is affected by a denial of service vulnerability.

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is 9.x prior to 9.9.9-P2, 9.10.x prior to 9.10.4-P2, or 9.11.0a3 prior to 9.11.0b2. It is, therefore, affected by an error in the lightweight resolver (lwres) protocol implementation when resolving a query name that, when combined with a search list entry, exceeds the maximum allowable length. An unauthenticated, remote attacker can exploit this to cause a segmentation fault, resulting in a denial of service condition. This issue occurs when lwresd or the the named 'lwres' option is enabled.

See Also

<https://kb.isc.org/article/AA-01393>

Solution

Upgrade to ISC BIND version 9.9.8-P3 / 9.9.8-S4 / 9.10.3-P3 or later.

Note that BIND 9 version 9.9.9-S3 is available exclusively for eligible ISC Support customers.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.3422

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2016-2775
XREF	IAVA:2017-A-0004

Plugin Information

Published: 2016/07/21, Modified: 2019/11/14

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.9.9-P2
```

119264 - ISC BIND 9.x.x < 9.11.5 / 9.12.x < 9.12.3 Policy-Bypass Record Update Vulnerability

Synopsis

The remote name server is affected by a policy bypass which enables an unauthorized record update vulnerability.

Description

According to its self-reported version number, the instance of ISC 9.x.x prior to 9.11.5, or 9.12.x prior to 9.12.3. It is, therefore, affected by a policy bypass record update vulnerability.

See Also

<https://kb.isc.org/docs/cve-2018-5741>

Solution

Upgrade to ISC BIND version 9.11.5 / 9.12.3 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.0046

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID	105379
CVE	CVE-2018-5741

Plugin Information

Published: 2018/11/28, Modified: 2019/11/01

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.5
```

62355 - ISC BIND Cache Update Policy Deleted Domain Name Resolving Weakness

Synopsis

The remote name server may be affected by a DNS integrity vulnerability.

Description

According to its self-reported version number, the remote installation of BIND will continue to allow revoked domain names to be resolved due to an issue related to the cache update policy. Note that Nessus has only relied on the version itself and has not attempted to determine whether or not the install is actually affected.

See Also

<http://www.nessus.org/u?38f47769>

<https://www.isc.org/software/bind/advisories/cve-2012-1033>

<http://ftp.isc.org/isc/bind9/9.6-ESV-R6/CHANGES>

<http://ftp.isc.org/isc/bind9/9.7.5/CHANGES>

<http://ftp.isc.org/isc/bind9/9.8.2/CHANGES>

<http://ftp.isc.org/isc/bind9/9.9.0/CHANGES>

Solution

Upgrade to BIND 9.6-ESV-R6 / 9.7.5 / 9.8.2 / 9.9.0 or later.

Risk Factor

Medium

VPR Score

5.9

EPSS Score

0.0098

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	51898
CVE	CVE-2012-1033
XREF	CERT:542123

Plugin Information

Published: 2012/09/27, Modified: 2018/06/27

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.6-ESV-R6
```

136808 - ISC BIND Denial of Service

Synopsis

The remote name server is affected by an assertion failure vulnerability.

Description

A denial of service (DoS) vulnerability exists in ISC BIND versions 9.11.18 / 9.11.18-S1 / 9.12.4-P2 / 9.13 / 9.14.11 / 9.15 / 9.16.2 / 9.17 / 9.17.1 and earlier. An unauthenticated, remote attacker can exploit this issue, via a specially-crafted message, to cause the service to stop responding.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/docs/cve-2020-8617>

Solution

Upgrade to the patched release most closely related to your current version of BIND.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.3 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.9263

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-8617
XREF	IAVA:2020-A-0217-S

Plugin Information

Published: 2020/05/22, Modified: 2023/03/23

Plugin Output

udp/53/dns

```
Installed version : 9.4.2
Fixed version    : 9.11.19
```

40422 - ISC BIND Dynamic Update Message Handling Remote DoS

Synopsis

The remote name server may be affected by a denial of service vulnerability.

Description

The version of BIND installed on the remote host suggests that it suffers from a denial of service vulnerability, which may be triggered by sending a malicious dynamic update message to a zone for which the server is the master, even if that server is not configured to allow dynamic updates.

Note that Nessus obtained the version by sending a special DNS request for the text 'version.bind' in the domain 'chaos', the value of which can be and sometimes is tweaked by DNS administrators.

See Also

<http://www.nessus.org/u?8662ded2>

Solution

Upgrade to BIND 9.4.3-P3 / 9.5.1-P3 / 9.6.1-P3 or later.

Risk Factor

Medium

VPR Score

5.1

EPSS Score

0.3647

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

4.1 (CVSS2#E:F/RL:OF/RC:C)

References

BID	35848
CVE	CVE-2009-0696
XREF	CERT:725188

XREF

CWE:16

Exploitable With

Core Impact (true)

Plugin Information

Published: 2009/07/29, Modified: 2018/06/27

Plugin Output

udp/53/dns

106679 - ISC BIND Zone Data Denial of Service

Synopsis

The remote name server is affected by a memory exhaustion vulnerability

Description

According to its self-reported version number, the installation of ISC BIND running on the remote name server is affected by a memory exhaustion vulnerability. A server is potentially vulnerable if it accepts zone data from another source, as no limit is currently placed on zone data size.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://kb.isc.org/article/AA-01390>

Solution

Follow guidance provided by ISC advisory.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:H)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0186

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.0 (CVSS2#E:U/RL:OF/RC:C)

References

CVE CVE-2016-6170

Plugin Information

Published: 2018/02/08, Modified: 2018/06/29

Plugin Output

tcp/53/dns

```
Installed version : 9.4.2
```

56283 - Linux Kernel TCP Sequence Number Generation Security Weakness

Synopsis

It may be possible to predict TCP/IP Initial Sequence Numbers for the remote host.

Description

The Linux kernel is prone to a security weakness related to TCP sequence number generation. Attackers can exploit this issue to inject arbitrary packets into TCP sessions using a brute-force attack.

An attacker may use this vulnerability to create a denial of service condition or a man-in-the-middle attack.

Note that this plugin may fire as a result of a network device (such as a load balancer, VPN, IPS, transparent proxy, etc.) that is vulnerable and that re-writes TCP sequence numbers, rather than the host itself being vulnerable.

See Also

<https://lwn.net/Articles/455135/>

<http://www.nessus.org/u?62a845fa>

Solution

Contact the OS vendor for a Linux kernel update / patch.

Risk Factor

Medium

VPR Score

5.2

EPSS Score

0.0611

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 49289

CVE CVE-2011-3188

Plugin Information

Published: 2011/09/23, Modified: 2019/03/06

Plugin Output

tcp/0

33447 - Multiple Vendor DNS Query ID Field Prediction Cache Poisoning

Synopsis

The remote name resolver (or the server it uses upstream) is affected by a DNS cache poisoning vulnerability.

Description

The remote DNS resolver does not use random ports when making queries to third-party DNS servers. An unauthenticated, remote attacker can exploit this to poison the remote DNS server, allowing the attacker to divert legitimate traffic to arbitrary sites.

See Also

<https://www.cnet.com/news/massive-coordinated-dns-patch-released/>

https://www.theregister.co.uk/2008/07/21/dns_flaw_speculation/

Solution

Contact your DNS server vendor for a patch.

Risk Factor

Medium

CVSS v3.0 Base Score

6.8 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:C/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

6.1 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.0

EPSS Score

0.8589

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

STIG Severity

I

References

BID	30131
CVE	CVE-2008-1447
XREF	CERT:800113
XREF	IAVA:2008-A-0045
XREF	EDB-ID:6122
XREF	EDB-ID:6123
XREF	EDB-ID:6130

Plugin Information

Published: 2008/07/09, Modified: 2024/04/03

Plugin Output

udp/53/dns

The remote DNS server uses non-random ports for its
DNS requests. An attacker may spoof DNS responses.

List of used ports :

```
+ DNS Server: 82.50.115.194
|- Port: 53906
|- Port: 53906
|- Port: 53906
|- Port: 53906
```

44079 - OpenSSH < 4.9 'ForceCommand' Directive Bypass

Synopsis

The remote SSH service is affected by a security bypass vulnerability.

Description

According to its banner, the version of OpenSSH installed on the remote host is earlier than 4.9. It may allow a remote, authenticated user to bypass the 'sshd_config' 'ForceCommand' directive by modifying the '.ssh/rc' session file.

See Also

<https://www.openssh.com/txt/release-4.9>

Solution

Upgrade to OpenSSH version 4.9 or later.

Risk Factor

Medium

VPR Score

6.1

EPSS Score

0.002

CVSS v2.0 Base Score

6.5 (CVSS2#AV:N/AC:L/Au:S/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

4.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	28531
CVE	CVE-2008-1657
XREF	CWE:264

Plugin Information

Published: 2011/10/04, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 4.9
```

44065 - OpenSSH < 5.2 CBC Plaintext Disclosure

Synopsis

The SSH service running on the remote host has an information disclosure vulnerability.

Description

The version of OpenSSH running on the remote host has an information disclosure vulnerability. A design flaw in the SSH specification could allow a man-in-the-middle attacker to recover up to 32 bits of plaintext from an SSH-protected connection in the standard configuration. An attacker could exploit this to gain access to sensitive information.

See Also

<http://www.nessus.org/u?4984aeb9>

<http://www.openssh.com/txt/cbc.adv>

<http://www.openssh.com/txt/release-5.2>

Solution

Upgrade to OpenSSH 5.2 or later.

Risk Factor

Medium

VPR Score

1.4

EPSS Score

0.0307

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:L/Au:S/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 32319

CVE CVE-2008-5161

XREF CERT:958563

XREF

CWE:200

Plugin Information

Published: 2011/09/27, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 5.2
```

85382 - OpenSSH < 7.0 Multiple Vulnerabilities

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.0. It is, therefore, affected by the following vulnerabilities :

- A security bypass vulnerability exists in the `kbdint_next_device()` function in file `auth2-chall.c` that allows the circumvention of `MaxAuthTries` during keyboard-interactive authentication. A remote attacker can exploit this issue to force the same authentication method to be tried thousands of times in a single pass by using a crafted keyboard-interactive 'devices'

string, thus allowing a brute-force attack or causing a denial of service. (CVE-2015-5600)

- A security bypass vulnerability exists in `sshd` due to improper handling of username data in `MONITOR_REQ_PAM_INIT_CTX` requests. A local attacker can exploit this, by sending a `MONITOR_REQ_PWNAM` request, to conduct an impersonation attack. Note that this issue only affects Portable OpenSSH. (CVE-2015-6563)

- A privilege escalation vulnerability exists due to a use-after-free error in `sshd` that is triggered when handling a `MONITOR_REQ_PAM_FREE_CTX` request. A local attacker can exploit this to gain elevated privileges.

Note that this issue only affects Portable OpenSSH.
(CVE-2015-6564)

- A local command execution vulnerability exists in `sshd` due to setting insecure world-writable permissions for TTYS. A local attacker can exploit this, by injecting crafted terminal escape sequences, to execute commands for logged-in users. (CVE-2015-6565)

See Also

<http://www.openssh.com/txt/release-7.0>

Solution

Upgrade to OpenSSH 7.0 or later.

Risk Factor

High

CVSS v3.0 Base Score

6.1 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:U/C:L/I:N/A:H)

CVSS v3.0 Temporal Score

5.5 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.7

EPSS Score

0.3375

CVSS v2.0 Base Score

8.5 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:C)

CVSS v2.0 Temporal Score

6.7 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	75990
BID	76317
BID	76497
CVE	CVE-2015-5600
CVE	CVE-2015-6563
CVE	CVE-2015-6564
CVE	CVE-2015-6565
XREF	EDB-ID:41173

Plugin Information

Published: 2015/08/13, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.0
```

90023 - OpenSSH < 7.2p2 X11Forwarding xauth Command Injection

Synopsis

The SSH server running on the remote host is affected by a security bypass vulnerability.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.2p2. It is, therefore, affected by a security bypass vulnerability due to improper sanitization of X11 authentication credentials. An authenticated, remote attacker can exploit this, via crafted credentials, to inject arbitrary xauth commands, resulting in gaining read and write access to arbitrary files, connecting to local ports, or performing further attacks on xauth itself. Note that exploiting this vulnerability requires X11Forwarding to have been enabled.

See Also

<http://www.openssh.com/txt/release-7.2p2>

<http://www.openssh.com/txt/x11fwd.adv>

Solution

Upgrade to OpenSSH version 7.2p2 / 7.3 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.4 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:C/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.8 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

3.8

EPSS Score

0.4604

CVSS v2.0 Base Score

5.5 (CVSS2#AV:N/AC:L/Au:S/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

4.3 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE	CVE-2016-3115
XREF	EDB-ID:39569

Plugin Information

Published: 2016/03/18, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.2p2 / 7.3
```

Synopsis

The SSH server running on the remote host is affected by an information disclosure vulnerability.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.5. It is, therefore, affected by an information disclosure vulnerability :

- An unspecified timing flaw exists in the CBC padding oracle countermeasures, within the ssh and sshd functions, that allows an unauthenticated, remote attacker to disclose potentially sensitive information.

Note that the OpenSSH client disables CBC ciphers by default. However, sshd offers them as lowest-preference options, which will be removed by default in a future release.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.openssh.com/txt/release-7.5>

Solution

Upgrade to OpenSSH version 7.5 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2017/04/13, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.5
```

103781 - OpenSSH < 7.6

Synopsis

The SSH server running on the remote host is affected by a file creation restriction bypass vulnerability.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.6. It is, therefore, affected by a file creation restriction bypass vulnerability related to the 'process_open'

function in the file 'sftp-server.c' that allows authenticated users to create zero-length files regardless of configuration.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<http://www.nessus.org/u?09ca048b>

<http://www.nessus.org/u?96a8ea52>

<http://www.openssh.com/txt/release-7.6>

Solution

Upgrade to OpenSSH version 7.6 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.0284

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	101552
CVE	CVE-2017-15906

Plugin Information

Published: 2017/10/11, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.6
```

Synopsis

The SSH server running on the remote host is affected by a information disclosure vulnerability.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 7.8. It is, therefore, affected by an information disclosure vulnerability in the auth2-gss.c, auth2-hostbased.c, and auth2-pubkey due to not delaying for an invalid authenticating user. An unauthenticated, remote attacker can exploit this, via a malformed packet, to potentially enumerate users.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.openwall.com/lists/oss-security/2018/08/15/5>

<https://www.openssh.com/txt/release-7.8>

Solution

Upgrade to OpenSSH version 7.8 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

5.1 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

4.9

EPSS Score

0.8988

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.3 (CVSS2#E:H/RL:OF/RC:C)

References

CVE CVE-2018-15473

Exploitable With

CANVAS (true)

Plugin Information

Published: 2022/04/04, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 7.8
```

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

According to its banner, the version of OpenSSH running on the remote host is prior to 8.0. It is, therefore, affected by the following vulnerabilities:

- A permission bypass vulnerability due to improper directory name validation. An unauthenticated, remote attacker can exploit this, with a specially crafted scp server, to change the permission of a directory on the client. (CVE-2018-20685)
- Multiple arbitrary file downloads due to improper validation of object name and stderr output. An unauthenticated remote attacker can exploit this, with a specially crafted scp server, to include additional hidden files in the transfer. (CVE-2019-6109, CVE-2019-6110)
- An arbitrary file write vulnerability due to improper object name validation. An unauthenticated, remote attacker can exploit this, with a specially crafted scp server, to overwrite arbitrary files in the client directory. (CVE-2019-6111)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://sintonen.fi/advisories/scp-client-multiple-vulnerabilities.txt>

<https://www.openssh.com/txt/release-8.0>

Solution

Upgrade to OpenSSH version 8.0 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.8 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:N)

CVSS v3.0 Temporal Score

6.1 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.5789

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:P)

CVSS v2.0 Temporal Score

4.5 (CVSS2#E:POC/RL:OF/RC:C)

References

CVE	CVE-2018-20685
CVE	CVE-2019-6109
CVE	CVE-2019-6110
CVE	CVE-2019-6111

Plugin Information

Published: 2022/04/04, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 8.0
```

Synopsis

The SSH server running on the remote host is affected by multiple vulnerabilities.

Description

The version of OpenSSH installed on the remote host is prior to 9.6. It is, therefore, affected by multiple vulnerabilities as referenced in the release-9.6 advisory.

- ssh(1), sshd(8): implement protocol extensions to thwart the so-called Terrapin attack discovered by Fabian Bumer, Marcus Brinkmann and Jrg Schwenk. This attack allows a MITM to effect a limited break of the integrity of the early encrypted SSH transport protocol by sending extra messages prior to the commencement of encryption, and deleting an equal number of consecutive messages immediately after encryption starts. A peer SSH client/server would not be able to detect that messages were deleted. While cryptographically novel, the security impact of this attack is fortunately very limited as it only allows deletion of consecutive messages, and deleting most messages at this stage of the protocol prevents user authentication from proceeding and results in a stuck connection. The most serious identified impact is that it lets a MITM to delete the SSH2_MSG_EXT_INFO message sent before authentication starts, allowing the attacker to disable a subset of the keystroke timing obfuscation features introduced in OpenSSH 9.5.

There is no other discernable impact to session secrecy or session integrity. OpenSSH 9.6 addresses this protocol weakness through a new strict KEX protocol extension that will be automatically enabled when both the client and server support it. This extension makes two changes to the SSH transport protocol to improve the integrity of the initial key exchange. Firstly, it requires endpoints to terminate the connection if any unnecessary or unexpected message is received during key exchange (including messages that were previously legal but not strictly required like SSH2_MSG_DEBUG). This removes most malleability from the early protocol. Secondly, it resets the Message Authentication Code counter at the conclusion of each key exchange, preventing previously inserted messages from being able to make persistent changes to the sequence number across completion of a key exchange. Either of these changes should be sufficient to thwart the Terrapin Attack. More details of these changes are in the PROTOCOL file in the OpenSSH source distribution. (CVE-2023-48795)

- ssh-agent(1): when adding PKCS#11-hosted private keys while specifying destination constraints, if the PKCS#11 token returned multiple keys then only the first key had the constraints applied. Use of regular private keys, FIDO tokens and unconstrained keys are unaffected. (CVE-2023-51384)

- ssh(1): if an invalid user or hostname that contained shell metacharacters was passed to ssh(1), and a ProxyCommand, LocalCommand directive or match exec predicate referenced the user or hostname via %u, %h or similar expansion token, then an attacker who could supply arbitrary user/hostnames to ssh(1) could potentially perform command injection depending on what quoting was present in the user-supplied ssh_config(5) directive. This situation could arise in the case of git submodules, where a repository could contain a submodule with shell characters in its user/hostname. Git does not ban shell metacharacters in user or host names when checking out repositories from untrusted sources. Although we believe it is the user's responsibility to ensure validity of arguments passed to ssh(1), especially across a security boundary such as the git example above, OpenSSH 9.6 now bans most shell metacharacters from user and hostnames supplied via the command-line. This countermeasure is not guaranteed to be effective in all situations, as it is infeasible for ssh(1) to universally filter shell metacharacters potentially relevant to user-supplied commands. User/hostnames provided via ssh_config(5) are not subject to these restrictions, allowing configurations that use strange names to continue to be used, under the assumption that the user knows what they are doing in their own configuration files. (CVE-2023-51385)

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.openssh.com/txt/release-9.6>

Solution

Upgrade to OpenSSH version 9.6 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.9 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

6.1

EPSS Score

0.5654

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:POC/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-48795
CVE	CVE-2023-51384
CVE	CVE-2023-51385
XREF	IAVA:2023-A-0701-S

Plugin Information

Published: 2023/12/22, Modified: 2025/02/28

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 9.6p1 / 9.6
```

Synopsis

The remote SSH service is susceptible to a remote denial of service attack.

Description

According to its banner, a version of OpenSSH earlier than version 6.2 is listening on this port. The default configuration of OpenSSH installs before 6.2 could allow a remote attacker to bypass the LoginGraceTime and MaxStartups thresholds by periodically making a large number of new TCP connections and thereby prevent legitimate users from gaining access to the service.

Note that this plugin has not tried to exploit the issue or detect whether the remote service uses a vulnerable configuration. Instead, it has simply checked the version of OpenSSH running on the remote host.

See Also

<https://www.openwall.com/lists/oss-security/2013/02/06/5>

<http://openssh.org/txt/release-6.2>

<https://tools.cisco.com/security/center/viewAlert.x?alertId=28883>

Solution

Upgrade to OpenSSH 6.2 and review the associated server configuration settings.

Risk Factor

Medium

VPR Score

3.6

EPSS Score

0.0179

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID 58162
CVE CVE-2010-5107

Plugin Information

Published: 2013/07/03, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 6.2
```

31737 - OpenSSH X11 Forwarding Session Hijacking

Synopsis

The remote SSH service is prone to an X11 session hijacking vulnerability.

Description

According to its banner, the version of SSH installed on the remote host is older than 5.0. Such versions may allow a local user to hijack X11 sessions because it improperly binds TCP ports on the local IPv6 interface if the corresponding ports on the IPv4 interface are in use.

See Also

<https://bugs.debian.org/cgi-bin/bugreport.cgi?bug=463011>

<https://www.openssh.com/txt/release-5.0>

Solution

Upgrade to OpenSSH version 5.0 or later.

Risk Factor

Medium

VPR Score

5.9

EPSS Score

0.0248

CVSS v2.0 Base Score

6.9 (CVSS2#AV:L/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

5.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	28444
CVE	CVE-2008-1483
CVE	CVE-2008-3234
XREF	Secunia:29522

XREF

CWE:264

Plugin Information

Published: 2008/04/03, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 5.0
```


74326 - OpenSSL 'ChangeCipherSpec' MiTM Potential Vulnerability

Synopsis

The remote host is potentially affected by a vulnerability that could allow sensitive data to be decrypted.

Description

The OpenSSL service on the remote host is potentially vulnerable to a man-in-the-middle (MiTM) attack, based on its response to two consecutive 'ChangeCipherSpec' messages during the incorrect phase of an SSL/TLS handshake.

This flaw could allow a MiTM attacker to decrypt or forge SSL messages by telling the service to begin encrypted communications before key material has been exchanged, which causes predictable keys to be used to secure future traffic.

OpenSSL 1.0.1 is known to be exploitable. OpenSSL 0.9.8 and 1.0.0 are not known to be vulnerable; however, the OpenSSL team has advised that users of these older versions upgrade as a precaution. This plugin detects and reports all versions of OpenSSL that are potentially exploitable.

Note that Nessus has only tested for an SSL/TLS MiTM vulnerability (CVE-2014-0224). However, Nessus has inferred that the OpenSSL service on the remote host is also affected by six additional vulnerabilities that were disclosed in OpenSSL's June 5th, 2014 security advisory :

- An error exists in the 'ssl3_read_bytes' function that permits data to be injected into other sessions or allows denial of service attacks. Note that this issue is exploitable only if SSL_MODE_RELEASE_BUFFERS is enabled. (CVE-2010-5298)
- An error exists related to the implementation of the Elliptic Curve Digital Signature Algorithm (ECDSA) that allows nonce disclosure via the 'FLUSH+RELOAD' cache side-channel attack. (CVE-2014-0076)
- A buffer overflow error exists related to invalid DTLS fragment handling that permits the execution of arbitrary code or allows denial of service attacks.

Note that this issue only affects OpenSSL when used as a DTLS client or server. (CVE-2014-0195)

- An error exists in the 'do_ssl3_write' function that permits a NULL pointer to be dereferenced, which could allow denial of service attacks. Note that this issue is exploitable only if SSL_MODE_RELEASE_BUFFERS is enabled. (CVE-2014-0198)

- An error exists related to DTLS handshake handling that could allow denial of service attacks. Note that this issue only affects OpenSSL when used as a DTLS client.

(CVE-2014-0221)

- An error exists in the 'dtls1_get_message_fragment'

function related to anonymous ECDH cipher suites. This could allow denial of service attacks. Note that this issue only affects OpenSSL TLS clients. (CVE-2014-3470)

OpenSSL did not release individual patches for these vulnerabilities, instead they were all patched under a single version release. Note that the service will remain vulnerable after patching until the service or host is restarted.

See Also

<http://www.nessus.org/u?d5709faa>

<https://www.imperialviolet.org/2014/06/05/earlyccs.html>

<https://www.openssl.org/news/secadv/20140605.txt>

Solution

OpenSSL 0.9.8 SSL/TLS users (client and/or server) should upgrade to 0.9.8za. OpenSSL 1.0.0 SSL/TLS users (client and/or server) should upgrade to 1.0.0m. OpenSSL 1.0.1 SSL/TLS users (client and/or server) should upgrade to 1.0.1h.

Risk Factor

Medium

VPR Score

7.7

EPSS Score

0.9269

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:F/RL:OF/RC:C)

References

BID	66363
BID	66801
BID	67193
BID	67898
BID	67899
BID	67900
BID	67901
CVE	CVE-2010-5298
CVE	CVE-2014-0076
CVE	CVE-2014-0195
CVE	CVE-2014-0198
CVE	CVE-2014-0221
CVE	CVE-2014-0224
CVE	CVE-2014-3470
XREF	CERT:978508

Exploitable With

Core Impact (true)

Plugin Information

Published: 2014/06/05, Modified: 2020/06/12

Plugin Output

tcp/25/smtp

The remote service accepted two consecutive ChangeCipherSpec messages at an incorrect point in the handshake, without closing the connection or sending an SSL alert. This behavior indicates that the service is vulnerable; however, this could also be the result of network interference.

74326 - OpenSSL 'ChangeCipherSpec' MiTM Potential Vulnerability

Synopsis

The remote host is potentially affected by a vulnerability that could allow sensitive data to be decrypted.

Description

The OpenSSL service on the remote host is potentially vulnerable to a man-in-the-middle (MiTM) attack, based on its response to two consecutive 'ChangeCipherSpec' messages during the incorrect phase of an SSL/TLS handshake.

This flaw could allow a MiTM attacker to decrypt or forge SSL messages by telling the service to begin encrypted communications before key material has been exchanged, which causes predictable keys to be used to secure future traffic.

OpenSSL 1.0.1 is known to be exploitable. OpenSSL 0.9.8 and 1.0.0 are not known to be vulnerable; however, the OpenSSL team has advised that users of these older versions upgrade as a precaution. This plugin detects and reports all versions of OpenSSL that are potentially exploitable.

Note that Nessus has only tested for an SSL/TLS MiTM vulnerability (CVE-2014-0224). However, Nessus has inferred that the OpenSSL service on the remote host is also affected by six additional vulnerabilities that were disclosed in OpenSSL's June 5th, 2014 security advisory :

- An error exists in the 'ssl3_read_bytes' function that permits data to be injected into other sessions or allows denial of service attacks. Note that this issue is exploitable only if SSL_MODE_RELEASE_BUFFERS is enabled. (CVE-2010-5298)
 - An error exists related to the implementation of the Elliptic Curve Digital Signature Algorithm (ECDSA) that allows nonce disclosure via the 'FLUSH+RELOAD' cache side-channel attack. (CVE-2014-0076)
 - A buffer overflow error exists related to invalid DTLS fragment handling that permits the execution of arbitrary code or allows denial of service attacks.
- Note that this issue only affects OpenSSL when used as a DTLS client or server. (CVE-2014-0195)
- An error exists in the 'do_ssl3_write' function that permits a NULL pointer to be dereferenced, which could allow denial of service attacks. Note that this issue is exploitable only if SSL_MODE_RELEASE_BUFFERS is enabled. (CVE-2014-0198)
 - An error exists related to DTLS handshake handling that could allow denial of service attacks. Note that this issue only affects OpenSSL when used as a DTLS client. (CVE-2014-0221)
 - An error exists in the 'dtls1_get_message_fragment' function related to anonymous ECDH cipher suites. This could allow denial of service attacks. Note that this issue only affects OpenSSL TLS clients. (CVE-2014-3470)

OpenSSL did not release individual patches for these vulnerabilities, instead they were all patched under a single version release. Note that the service will remain vulnerable after patching until the service or host is restarted.

See Also

<http://www.nessus.org/u?d5709faa>

<https://www.imperialviolet.org/2014/06/05/earlyccs.html>

<https://www.openssl.org/news/secadv/20140605.txt>

Solution

OpenSSL 0.9.8 SSL/TLS users (client and/or server) should upgrade to 0.9.8za. OpenSSL 1.0.0 SSL/TLS users (client and/or server) should upgrade to 1.0.0m. OpenSSL 1.0.1 SSL/TLS users (client and/or server) should upgrade to 1.0.1h.

Risk Factor

Medium

VPR Score

7.7

EPSS Score

0.9269

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.6 (CVSS2#E:F/RL:OF/RC:C)

References

BID	66363
BID	66801
BID	67193
BID	67898
BID	67899
BID	67900
BID	67901
CVE	CVE-2010-5298
CVE	CVE-2014-0076
CVE	CVE-2014-0195
CVE	CVE-2014-0198
CVE	CVE-2014-0221
CVE	CVE-2014-0224
CVE	CVE-2014-3470
XREF	CERT:978508

Exploitable With

Core Impact (true)

Plugin Information

Published: 2014/06/05, Modified: 2020/06/12

Plugin Output

tcp/5432/postgresql

```
The remote service accepted an SSL ChangeCipherSpec message at an incorrect point in the handshake
leading to weak keys being used, and then attempted to decrypt an SSL record using those weak keys.
This plugin detects unpatched OpenSSL 1.0.1, 1.0.0, and 0.9.8 services. Only 1.0.1 has been shown
to
be exploitable; however, OpenSSL 1.0.0 and 0.9.8 have received similar patches and users of these
versions have been advised to upgrade as a precaution.
```

51139 - PHP 5.2 < 5.2.15 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP 5.2 installed on the remote host is older than 5.2.15. Such versions may be affected by several security issues :

- A crash in the zip extract method.
- A possible double free exists in the imap extension.
(CVE-2010-4150)
- An unspecified flaw exists in 'open_basedir'. (CVE-2010-3436)
- A possible crash could occur in 'mssql_fetch_batch()'.
(CVE-2010-3709)
- A NULL pointer dereference exists in 'ZipArchive::getArchiveComment'. (CVE-2010-3709)
- A crash exists if anti-aliasing steps are invalid.
(Bug #53492)
- A crash exists in pdo_firebird getAttribute(). (Bug #53323)
- A user-after-free vulnerability in the Zend engine when a '__set()', '__get()', '__isset()' or '__unset()' method is called can allow for a denial of service attack. (Bug #52879 / CVE-2010-4697)
- A stack-based buffer overflow exists in the 'imagepext()' function in the GD extension. (Bug #53492 / CVE-2010-4698)
- The extract function does not prevent use of the EXTR_OVERWRITE parameter to overwrite the GLOBALS superglobal array and the 'this' variable, which allows attackers to bypass intended access restrictions.
(CVE-2011-0752)

See Also

http://www.php.net/releases/5_2_15.php

<http://www.php.net/ChangeLog-5.php#5.2.15>

Solution

Upgrade to PHP version 5.2.15 or later.

Risk Factor

Medium

VPR Score

5.9

EPSS Score

0.1666

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	44718
BID	44723
BID	45335
BID	45952
BID	46448
CVE	CVE-2010-3436
CVE	CVE-2010-3709
CVE	CVE-2010-4150
CVE	CVE-2010-4697
CVE	CVE-2010-4698
CVE	CVE-2011-0752

Plugin Information

Published: 2010/12/13, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version      : 5.2.15
```


51439 - PHP 5.2 < 5.2.17 / 5.3 < 5.3.5 String To Double Conversion DoS

Synopsis

The remote web server uses a version of PHP that is affected by a denial of service vulnerability.

Description

According to its banner, the version of PHP 5.x installed on the remote host is older than 5.2.17 or 5.3.5.

Such versions may experience a crash while performing string to double conversion for certain numeric values. Only x86 32-bit PHP processes are known to be affected by this issue regardless of whether the system running PHP is 32-bit or 64-bit.

See Also

<https://bugs.php.net/bug.php?id=53632>

http://www.php.net/distributions/test_bug53632.txt

http://www.php.net/releases/5_2_17.php

http://www.php.net/releases/5_3_5.php

Solution

Upgrade to PHP 5.2.17/5.3.5 or later.

Risk Factor

Medium

VPR Score

4.4

EPSS Score

0.1674

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID 45668

CVE

CVE-2010-4645

Plugin Information

Published: 2011/01/07, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.17/5.3.5
```

58681 - PHP 5.2.x filter_globals Subsequence Request Parsing Remote Code Execution

Synopsis

The remote web server uses a version of PHP that may be affected by a remote code execution vulnerability.

Description

According to its banner, the version of PHP installed on the remote host is in the 5.2 release branch. As such, it reportedly may be affected by a remote code execution vulnerability.

An error in the file 'ext/filter/filter.c' does not properly clear the 'filter_globals' struct if PHP encounters issues during its start up process. This struct then contains stale values and can allow an attacker to use a specially crafted request to crash PHP, obtain sensitive information or possibly execute arbitrary code.

Note that this issue reportedly only affects PHP when running as an Apache module and not in other configurations such as CGI, nor when used with other web servers such as IIS.

See Also

<http://www.php.net/ChangeLog-5.php#5.3.0>

<https://seclists.org/bugtraq/2012/Feb/93>

<https://bugs.php.net/bug.php?id=47930>

<http://svn.php.net/viewvc?view=revision&revision=279522>

Solution

Upgrade to PHP version 5.3.0 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.6 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:L/A:L)

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID 52065

Plugin Information

Published: 2012/04/11, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.3.0
```

39480 - PHP < 5.2.10 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.10. Such versions are reportedly affected by multiple vulnerabilities :

- Sufficient checks are not performed on fields reserved for offsets in function 'exif_read_data()'. Successful exploitation of this issue could result in a denial of service condition. (bug 48378)
- Provided 'safe_mode_exec_dir' is not set (not set by default), it may be possible to bypass 'safe_mode' restrictions by preceding a backslash in functions such as 'exec()', 'system()', 'shell_exec()', 'passthru()' and 'popen()' on a system running PHP on Windows. (bug 45997)

See Also

<https://bugs.php.net/bug.php?id=45997>
<https://bugs.php.net/bug.php?id=48378>
http://www.php.net/releases/5_2_10.php
<http://www.php.net/ChangeLog-5.php#5.2.10>

Solution

Upgrade to PHP version 5.2.10 or later.

Risk Factor

Medium

VPR Score

4.4

EPSS Score

0.1009

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	35435
BID	35440
CVE	CVE-2009-2687
XREF	SECUNIA:35441
XREF	CWE:20

Plugin Information

Published: 2009/06/22, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.10
```

43351 - PHP < 5.2.12 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.12. Such versions may be affected by several security issues :

- It is possible to bypass the 'safe_mode' configuration setting using 'tempnam()'. (CVE-2009-3557)
- It is possible to bypass the 'open_basedir' configuration setting using 'posix_mkfifo()'. (CVE-2009-3558)
- Provided file uploading is enabled (it is by default), an attacker can upload files using a POST request with 'multipart/form-data' content even if the target script doesn't actually support file uploads per se. By supplying a large number (15,000+) of files, an attacker could cause the web server to stop responding while it processes the file list. (CVE-2009-4017)
- Missing protection for '\$_SESSION' from interrupt corruption and improved 'session.save_path' check. (CVE-2009-4143)
- Insufficient input string validation in the 'htmlspecialchars()' function. (CVE-2009-4142)

See Also

<http://www.nessus.org/u?57f2d08f>

http://www.php.net/releases/5_2_12.php

<http://www.php.net/ChangeLog-5.php#5.2.12>

Solution

Upgrade to PHP version 5.2.12 or later.

Risk Factor

Medium

VPR Score

6.7

EPSS Score

0.0681

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	37389
BID	37390
CVE	CVE-2009-3557
CVE	CVE-2009-3558
CVE	CVE-2009-4017
CVE	CVE-2009-4142
CVE	CVE-2009-4143
XREF	SECUNIA:37821
XREF	CWE:79
XREF	CWE:264

Plugin Information

Published: 2009/12/18, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.12
```


28181 - PHP < 5.2.5 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.5. Such versions may be affected by various issues, including but not limited to several buffer overflows.

See Also

http://www.php.net/releases/5_2_5.php

Solution

Upgrade to PHP version 5.2.5 or later.

Risk Factor

Medium

VPR Score

6.7

EPSS Score

0.1006

CVSS v2.0 Base Score

4.4 (CVSS2#AV:L/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	26403
BID	69246
CVE	CVE-2007-3996
CVE	CVE-2007-4782
CVE	CVE-2007-4783
CVE	CVE-2007-4784

CVE	CVE-2007-4825
CVE	CVE-2007-4840
CVE	CVE-2007-4887
CVE	CVE-2007-4889
CVE	CVE-2007-5447
CVE	CVE-2007-5653
CVE	CVE-2007-5898
CVE	CVE-2007-5899
CVE	CVE-2007-5900
CVE	CVE-2008-2107
CVE	CVE-2008-2108
CVE	CVE-2008-4107
XREF	CWE:20
XREF	CWE:22
XREF	CWE:78
XREF	CWE:94
XREF	CWE:189
XREF	CWE:200
XREF	CWE:264

Plugin Information

Published: 2007/11/12, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version      : 5.2.5
```

35750 - PHP < 5.2.9 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.2.9. Such versions may be affected by several security issues :

- Background color is not correctly validated with a non true color image in function 'imagerotate()'. (CVE-2008-5498)
- A denial of service condition can be triggered by trying to extract zip files that contain files with relative paths in file or directory names.
- Function 'explode()' is affected by an unspecified vulnerability.
- It may be possible to trigger a segfault by passing a specially crafted string to function 'json_decode()'.
- Function 'xml_error_string()' is affected by a flaw which results in messages being off by one.

See Also

<http://news.php.net/php.internals/42762>

http://www.php.net/releases/5_2_9.php

<http://www.php.net/ChangeLog-5.php#5.2.9>

Solution

Upgrade to PHP version 5.2.9 or later.

Risk Factor

Medium

VPR Score

3.6

EPSS Score

0.111

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	33002
BID	33927
CVE	CVE-2008-5498
CVE	CVE-2009-1271
CVE	CVE-2009-1272
XREF	SECUNIA:34081
XREF	CWE:20
XREF	CWE:200

Plugin Information

Published: 2009/02/27, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.2.9
```

58966 - PHP < 5.3.11 Multiple Vulnerabilities

Synopsis

The remote web server uses a version of PHP that is affected by multiple vulnerabilities.

Description

According to its banner, the version of PHP installed on the remote host is earlier than 5.3.11, and as such is potentially affected by multiple vulnerabilities :

- During the import of environment variables, temporary changes to the 'magic_quotes_gpc' directive are not handled properly. This can lower the difficulty for SQL injection attacks. (CVE-2012-0831)
- The '\$_FILES' variable can be corrupted because the names of uploaded files are not properly validated. (CVE-2012-1172)
- The 'open_basedir' directive is not properly handled by the functions 'readline_write_history' and 'readline_read_history'.
- The 'header()' function does not detect multi-line headers with a CR. (Bug #60227 / CVE-2011-1398)

See Also

<http://www.nessus.org/u?e81d4026>
<https://bugs.php.net/bug.php?id=61043>
<https://bugs.php.net/bug.php?id=54374>
<https://bugs.php.net/bug.php?id=60227>
<https://marc.info/?l=oss-security&m=134626481806571&w=2>
<http://www.php.net/archive/2012.php#id2012-04-26-1>
<http://www.php.net/ChangeLog-5.php#5.3.11>

Solution

Upgrade to PHP version 5.3.11 or later.

Risk Factor

Medium

VPR Score

6.7

EPSS Score

0.1605

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	51954
BID	53403
BID	55297
CVE	CVE-2011-1398
CVE	CVE-2012-0831
CVE	CVE-2012-1172

Plugin Information

Published: 2012/05/02, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.3.11
```

Synopsis

The remote web server uses a version of PHP that is affected by multiple flaws.

Description

According to its banner, the version of PHP installed on the remote host is older than 5.3.2 / 5.2.13. Such versions may be affected by several security issues :

- Directory paths not ending with '/' may not be correctly validated inside 'tempnam()' in 'safe_mode' configuration.
- It may be possible to bypass the 'open_basedir'/'safe_mode' configuration restrictions due to an error in session extensions.
- An unspecified vulnerability affects the LCG entropy.

See Also

http://securityreason.com/achievement_securityalert/82

<http://securityreason.com/securityalert/7008>

<https://seclists.org/fulldisclosure/2010/Feb/208>

http://www.php.net/releases/5_3_2.php

<http://www.php.net/ChangeLog-5.php#5.3.2>

http://www.php.net/releases/5_2_13.php

<http://www.php.net/ChangeLog-5.php#5.2.13>

Solution

Upgrade to PHP version 5.3.2 / 5.2.13 or later.

Risk Factor

Medium

VPR Score

5.3

EPSS Score

0.0557

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	38182
BID	38430
BID	38431
CVE	CVE-2010-1128
CVE	CVE-2010-1129
CVE	CVE-2010-1130
XREF	SECUNIA:38708

Plugin Information

Published: 2010/02/26, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.3.2 / 5.2.13
```


152853 - PHP < 7.3.28 Email Header Injection

Synopsis

The version of PHP running on the remote web server is affected by an email header injection vulnerability.

Description

According to its self-reported version number, the version of PHP running on the remote web server is prior to 7.3.28.

It is, therefore affected by an email header injection vulnerability, due to a failure to properly handle CR-LF sequences in header fields. An unauthenticated, remote attacker can exploit this, by inserting line feed characters into email headers, to gain full control of email header content.

See Also

<https://www.php.net/ChangeLog-7.php#7.3.28>

Solution

Upgrade to PHP version 7.3.28 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2021/08/26, Modified: 2025/05/26

Plugin Output

tcp/80/www

```
URL           : http://192.168.50.3/ (5.2.4-2ubuntu5.10 under X-Powered-By:
PHP/5.2.4-2ubuntu5.10)
Installed version : 5.2.4-2ubuntu5.10
Fixed version    : 7.3.28
```

73289 - PHP PHP_RSHUTDOWN_FUNCTION Security Bypass

Synopsis

The remote web server uses a version of PHP that is potentially affected by a security bypass vulnerability.

Description

According to its banner, the version of PHP 5.x installed on the remote host is 5.x prior to 5.3.11 or 5.4.x prior to 5.4.1 and thus, is potentially affected by a security bypass vulnerability.

An error exists related to the function 'PHP_RSHUTDOWN_FUNCTION' in the libxml extension and the 'stream_close' method that could allow a remote attacker to bypass 'open_basedir' protections and obtain sensitive information.

Note that this plugin has not attempted to exploit this issue, but has instead relied only on PHP's self-reported version number.

See Also

<http://www.nessus.org/u?bcc428c2>

<https://bugs.php.net/bug.php?id=61367>

Solution

Upgrade to PHP version 5.3.11 / 5.4.1 or later.

Risk Factor

Medium

VPR Score

3.4

EPSS Score

0.0016

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID 65673
CVE CVE-2012-1171

Plugin Information

Published: 2014/04/01, Modified: 2024/11/22

Plugin Output

tcp/80/www

```
Version source      : X-Powered-By: PHP/5.2.4-2ubuntu5.10
Installed version   : 5.2.4-2ubuntu5.10
Fixed version       : 5.3.11 / 5.4.1
```

63348 - PostgreSQL 7.4 < 7.4.27 / 8.0 < 8.0.23 / 8.1 < 8.1.19 / 8.2 < 8.2.15 / 8.3 < 8.3.9 / 8.4 < 8.4.2 Multiple Vulnerabilities

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 7.4 prior to 7.4.27, 8.0 prior to 8.0.23, 8.1 prior to 8.1.19, 8.2 prior to 8.2.15, 8.3 prior to 8.3.9 or 8.4 prior to 8.4.2. As such, it is potentially affected by multiple vulnerabilities :

- NULL bytes in SSL Certificates can be used to falsify client or server authentication. (CVE-2009-4034)
- Privilege escalation is possible via changing session state in an index function. (CVE-2009-4136)

See Also

<https://www.postgresql.org/about/news/1170/>
<https://www.postgresql.org/docs/7.4/release-7-4-27.html>
<https://www.postgresql.org/docs/8.0/release-8-0-23.html>
<https://www.postgresql.org/docs/8.1/release-8-1-19.html>
<https://www.postgresql.org/docs/8.2/release-8-2-15.html>
<https://www.postgresql.org/docs/8.3/release-8-3-9.html>
<https://www.postgresql.org/docs/8.4/release-8-4-2.html>

Solution

Upgrade to PostgreSQL 7.4.27 / 8.0.23 / 8.1.19 / 8.2.15 / 8.3.9 / 8.4.2 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.3 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

5.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

5.9

EPSS Score

0.0158

CVSS v2.0 Base Score

6.5 (CVSS2#AV:N/AC:L/Au:S/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

4.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	37333
BID	37334
CVE	CVE-2009-4034
CVE	CVE-2009-4136
XREF	CWE:310

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 7.4.27 / 8.0.23 / 8.1.19 / 8.2.15 / 8.3.9 / 8.4.2
```

Synopsis

The remote database server is affected by a privilege escalation vulnerability.

Description

The version of PostgreSQL installed on the remote host is 7.4 prior to 7.4.30, 8.0 prior to 8.0.26, 8.1 prior to 8.1.22, 8.2 prior to 8.2.18, 8.3 prior to 8.3.12, 8.4 prior to 8.4.5, or 9.0 prior to 9.0.1. It therefore is potentially affected by a privilege escalation vulnerability.

A remote, authenticated attacker could elevate privileges via specially crafted code in a SECURITY DEFINER function.

See Also

<https://www.postgresql.org/about/news/1244/>

<https://www.postgresql.org/docs/7.4/release.html#RELEASE-7-4-30>

<https://www.postgresql.org/docs/8.0/release.html#RELEASE-8-0-26>

<https://www.postgresql.org/docs/8.1/release-8-1-22.html>

<https://www.postgresql.org/docs/8.2/release-8-2-18.html>

<https://www.postgresql.org/docs/8.3/release-8-3-12.html>

<http://www.postgresql.org/docs/8.4/static/release-8-4-5.html>

<https://www.postgresql.org/docs/9.0/release.html#RELEASE-9-0-1>

Solution

Upgrade to PostgreSQL 7.4.30 / 8.0.26 / 8.1.22 / 8.2.18 / 8.3.12 / 8.4.5 / 9.0.1 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.3 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

5.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.5

EPSS Score

0.0136

CVSS v2.0 Base Score

6.0 (CVSS2#AV:N/AC:M/Au:S/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

4.4 (CVSS2#E:U/RL:OF/RC:C)

References

BID 43747

CVE CVE-2010-3433

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version      : 7.4.30 / 8.0.26 / 8.1.22 / 8.2.18 / 8.3.12 / 8.4.5 / 9.0.1
```

Synopsis

The remote database server is affected by a buffer overflow vulnerability.

Description

The version of PostgreSQL installed on the remote host is 8.2.x prior to 8.2.20, 8.3.x prior to 8.3.14, 8.4.x prior to 8.4.7, or 9.0.x prior to 9.0.3. It therefore is potentially affected by a buffer overflow vulnerability.

By calling functions from the intarray optional module with certain parameters, a remote, authenticated attacker could execute arbitrary code on the remote host subject to the privileges of the user running the affected application.

See Also

<https://www.postgresql.org/about/news/1289/>

<https://www.postgresql.org/docs/8.2/release-8-2-20.html>

<https://www.postgresql.org/docs/8.3/release-8-3-14.html>

<http://www.postgresql.org/docs/8.4/static/release-8-4-7.html>

<https://www.postgresql.org/docs/9.0/release-9-0-3.html>

Solution

Upgrade to PostgreSQL 8.2.20 / 8.3.14 / 8.4.7 / 9.0.3 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.3 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:L/I:L/A:L)

CVSS v3.0 Temporal Score

5.5 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.5

EPSS Score

0.0396

CVSS v2.0 Base Score

6.5 (CVSS2#AV:N/AC:L/Au:S/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

4.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	46084
CVE	CVE-2010-4015

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 8.2.20 / 8.3.14 / 8.4.7 / 9.0.3
```

Synopsis

The remote database server is affected by multiple vulnerabilities.

Description

The version of PostgreSQL installed on the remote host is 8.3.x prior to 8.3.20, 8.4.x prior to 8.4.13, 9.0.x prior to 9.0.9, or 9.1.x prior to 9.1.5. It therefore is potentially affected by multiple vulnerabilities :

- A flaw in contrib/xml2's xslt_process can be used to read and write arbitrary files. (CVE-2012-3488)
- An xml_parse() DTD validation flaw can be used to read arbitrary files. (CVE-2012-3489)

See Also

<http://www.postgresql.org/about/news/1407/>

<https://www.postgresql.org/docs/8.3/release-8-3-20.html>

<http://www.postgresql.org/docs/8.4/static/release-8-4-13.html>

<https://www.postgresql.org/docs/9.0/release-9-0-9.html>

<http://www.postgresql.org/docs/9.1/static/release-9-1-5.html>

Solution

Upgrade to PostgreSQL 8.3.20 / 8.4.13 / 9.0.9 / 9.1.5 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

6.5

EPSS Score

0.0104

CVSS v2.0 Base Score

4.9 (CVSS2#AV:N/AC:M/Au:S/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

3.6 (CVSS2#E:U/RL:OF/RC:C)

References

BID	55072
BID	55074
CVE	CVE-2012-3488
CVE	CVE-2012-3489

Plugin Information

Published: 2012/12/28, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 8.3.20 / 8.4.13 / 9.0.9 / 9.1.5
```

Synopsis

The remote database server is affected by a denial of service vulnerability.

Description

The version of PostgreSQL installed on the remote host is 8.3.x prior to 8.3.23, 8.4.x prior to 8.4.16, 9.0.x prior to 9.0.12, 9.1.x prior to 9.1.8 or 9.2 prior to 9.2.3. It is, therefore, potentially affected by a denial of service vulnerability due to a flaw in the enum_recv() function of 'backend/utils/adt/enum.c'. By exploiting this flaw, a remote attacker could crash the affected application.

See Also

<https://www.postgresql.org/about/news/1446/>

<https://www.postgresql.org/docs/8.3/release-8-3-23.html>

<https://www.postgresql.org/docs/8.4/release-8-4-16.html>

<https://www.postgresql.org/docs/9.0/release-9-0-12.html>

<http://www.postgresql.org/docs/9.1/static/release-9-1-8.html>

<http://www.postgresql.org/docs/9.2/static/release-9-2-3.html>

Solution

Upgrade to PostgreSQL 8.3.23 / 8.4.16 / 9.0.12 / 9.1.8 / 9.2.3 or later.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:L)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

1.4

EPSS Score

0.0309

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:L/Au:S/C:N/I:N/A:C)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

References

BID 57844
CVE CVE-2013-0255

Plugin Information

Published: 2013/02/18, Modified: 2024/10/23

Plugin Output

tcp/5432/postgresql

```
Version source      : Fauth.c.L1003.Rauth_failed
Installed version   : 8.3.8
Fixed version       : 8.3.23 / 8.4.16 / 9.0.12 / 9.1.8 / 9.2.3
```

57608 - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

tcp/445/cifs

52611 - SMTP Service STARTTLS Plaintext Command Injection

Synopsis

The remote mail service allows plaintext command injection while negotiating an encrypted communications channel.

Description

The remote SMTP service contains a software flaw in its STARTTLS implementation that could allow a remote, unauthenticated attacker to inject commands during the plaintext protocol phase that will be executed during the ciphertext protocol phase.

Successful exploitation could allow an attacker to steal a victim's email or associated SASL (Simple Authentication and Security Layer) credentials.

See Also

<https://tools.ietf.org/html/rfc2487>

<https://www.securityfocus.com/archive/1/516901/30/0/threaded>

Solution

Contact the vendor to see if an update is available.

Risk Factor

Medium

VPR Score

7.3

EPSS Score

0.6945

CVSS v2.0 Base Score

4.0 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:N)

CVSS v2.0 Temporal Score

3.1 (CVSS2#E:POC/RL:OF/RC:C)

References

BID 46767

CVE	CVE-2011-0411
CVE	CVE-2011-1430
CVE	CVE-2011-1431
CVE	CVE-2011-1432
CVE	CVE-2011-1506
CVE	CVE-2011-2165
XREF	CERT:555316

Plugin Information

Published: 2011/03/10, Modified: 2019/03/06

Plugin Output

tcp/25/smtp

```
Nessus sent the following two commands in a single packet :
```

```
STARTTLS\r\nRSET\r\n
```

```
And the server sent the following two responses :
```

```
220 2.0.0 Ready to start TLS
250 2.0.0 Ok
```

90317 - SSH Weak Algorithms Supported

Synopsis

The remote SSH server is configured to allow weak encryption algorithms or no algorithm at all.

Description

Nessus has detected that the remote SSH server is configured to use the Arcfour stream cipher or no cipher at all. RFC 4253 advises against using Arcfour due to an issue with weak keys.

See Also

<https://tools.ietf.org/html/rfc4253#section-6.3>

Solution

Contact the vendor or consult product documentation to remove the weak ciphers.

Risk Factor

Medium

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/04/04, Modified: 2016/12/14

Plugin Output

tcp/22/ssh

```
The following weak server-to-client encryption algorithms are supported :
```

```
arcfour
arcfour128
arcfour256
```

```
The following weak client-to-server encryption algorithms are supported :
```

```
arcfour
arcfour128
arcfour256
```

31705 - SSL Anonymous Cipher Suites Supported

Synopsis

The remote service supports the use of anonymous SSL ciphers.

Description

The remote host supports the use of anonymous SSL ciphers. While this enables an administrator to set up a service that encrypts traffic without having to generate and configure SSL certificates, it offers no way to verify the remote host's identity and renders the service vulnerable to a man-in-the-middle attack.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?3a040ada>

Solution

Reconfigure the affected application if possible to avoid use of weak ciphers.

Risk Factor

Low

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.027

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID 28482
CVE CVE-2007-1858

Plugin Information

Published: 2008/03/28, Modified: 2023/10/27

Plugin Output

tcp/25/smtp

The following is a list of SSL anonymous ciphers supported by the remote TCP server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC(56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
ADH-AES128-SHA SHA1	0x00, 0x34	DH	None	AES-CBC(128)	
ADH-AES256-SHA SHA1	0x00, 0x3A	DH	None	AES-CBC(256)	
ADH-RC4-MD5	0x00, 0x18	DH	None	RC4(128)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/25/smtp

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject    : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After  : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```

51192 - SSL Certificate Cannot Be Trusted

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2010/12/15, Modified: 2025/06/16

Plugin Output

tcp/5432/postgresql

The following certificate was part of the certificate chain sent by the remote host, but it has expired :

```
| -Subject    : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Not After  : Apr 16 14:07:45 2010 GMT
```

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain  
| -Issuer  : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for  
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-  
base.localdomain
```


15901 - SSL Certificate Expiry

Synopsis

The remote server's SSL certificate has already expired.

Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

Solution

Purchase or generate a new SSL certificate to replace the existing one.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2004/12/03, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

The SSL certificate has already expired :

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

15901 - SSL Certificate Expiry

Synopsis

The remote server's SSL certificate has already expired.

Description

This plugin checks expiry dates of certificates associated with SSL- enabled services on the target and reports whether any have already expired.

Solution

Purchase or generate a new SSL certificate to replace the existing one.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2004/12/03, Modified: 2021/02/03

Plugin Output

tcp/5432/postgresql

The SSL certificate has already expired :

```
Subject      : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Issuer       : C=XX, ST=There is no such thing outside US, L=Everywhere, O=OCOSA,
OU=Office for Complication of Otherwise Simple Affairs, CN=ubuntu804-base.localdomain,
emailAddress=root@ubuntu804-base.localdomain
Not valid before : Mar 17 14:07:45 2010 GMT
Not valid after  : Apr 16 14:07:45 2010 GMT
```

45411 - SSL Certificate with Wrong Hostname

Synopsis

The SSL certificate for this service is for a different host.

Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

Plugin Output

tcp/25/smtp

```
The identities known by Nessus are :
```

```
192.168.50.3
192.168.50.3
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

45411 - SSL Certificate with Wrong Hostname

Synopsis

The SSL certificate for this service is for a different host.

Description

The 'commonName' (CN) attribute of the SSL certificate presented for this service is for a different machine.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

Plugin Information

Published: 2010/04/03, Modified: 2020/04/27

Plugin Output

tcp/5432/postgresql

```
The identities known by Nessus are :
```

```
192.168.50.3
192.168.50.3
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

89058 - SSL DROWN Attack Vulnerability (Decrypting RSA with Obsolete and Weakened eNcryption)

Synopsis

The remote host may be affected by a vulnerability that allows a remote attacker to potentially decrypt captured TLS traffic.

Description

The remote host supports SSLv2 and therefore may be affected by a vulnerability that allows a cross-protocol Bleichenbacher padding oracle attack known as DROWN (Decrypting RSA with Obsolete and Weakened eNcryption). This vulnerability exists due to a flaw in the Secure Sockets Layer Version 2 (SSLv2) implementation, and it allows captured TLS traffic to be decrypted. A man-in-the-middle attacker can exploit this to decrypt the TLS connection by utilizing previously captured traffic and weak cryptography along with a series of specially crafted connections to an SSLv2 server that uses the same private key.

See Also

<https://drownattack.com/>

<https://drownattack.com/drown-attack-paper.pdf>

Solution

Disable SSLv2 and export grade cryptography cipher suites. Ensure that private keys are not used anywhere with server software that supports SSLv2 connections.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.6

EPSS Score

0.9003

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID 83733
CVE CVE-2016-0800
XREF CERT:583776

Plugin Information

Published: 2016/03/01, Modified: 2025/04/04

Plugin Output

tcp/25/smtp

The remote host is affected by SSL DROWN and supports the following vulnerable cipher suites :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA (512)	RSA	RC2-CBC (40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA (512)	RSA	RC4 (40)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
RC4-MD5	0x01, 0x00, 0x80	RSA	RSA	RC4 (128)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

65821 - SSL RC4 Cipher Suites Supported (Bar Mitzvah)

Synopsis

The remote service supports the use of the RC4 cipher.

Description

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

See Also

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf

Solution

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

VPR Score

7.3

EPSS Score

0.9032

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID	58796
BID	73684
CVE	CVE-2013-2566
CVE	CVE-2015-2808

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/25/smtp

List of RC4 cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA (512)	RSA	RC4 (40)	MD5
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
RC4-MD5	0x01, 0x00, 0x80	RSA	RSA	RC4 (128)	MD5
ADH-RC4-MD5	0x00, 0x18	DH	None	RC4 (128)	MD5
RC4-MD5	0x00, 0x04	RSA	RSA	RC4 (128)	MD5
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	MD5

SHA1

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```


65821 - SSL RC4 Cipher Suites Supported (Bar Mitzvah)

Synopsis

The remote service supports the use of the RC4 cipher.

Description

The remote host supports the use of RC4 in one or more cipher suites.

The RC4 cipher is flawed in its generation of a pseudo-random stream of bytes so that a wide variety of small biases are introduced into the stream, decreasing its randomness.

If plaintext is repeatedly encrypted (e.g., HTTP cookies), and an attacker is able to obtain many (i.e., tens of millions) ciphertexts, the attacker may be able to derive the plaintext.

See Also

<https://www.rc4nomore.com/>

<http://www.nessus.org/u?ac7327a0>

<http://cr.yp.to/talks/2013.03.12/slides.pdf>

<http://www.isg.rhul.ac.uk/tls/>

https://www.imperva.com/docs/HII_Attacking_SSL_when_using_RC4.pdf

Solution

Reconfigure the affected application, if possible, to avoid use of RC4 ciphers. Consider using TLS 1.2 with AES-GCM suites subject to browser and web server support.

Risk Factor

Medium

CVSS v3.0 Base Score

5.9 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS v3.0 Temporal Score

5.4 (CVSS:3.0/E:U/RL:X/RC:C)

VPR Score

7.3

EPSS Score

0.9032

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

4.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID	58796
BID	73684
CVE	CVE-2013-2566
CVE	CVE-2015-2808

Plugin Information

Published: 2013/04/05, Modified: 2025/05/09

Plugin Output

tcp/5432/postgresql

List of RC4 cipher suites supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
RC4-SHA	0x00, 0x05	RSA	RSA	RC4 (128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/25/smtp

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-
base.localdomain
```

57582 - SSL Self-Signed Certificate

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

6.4 (CVSS2#AV:N/AC:L/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2012/01/17, Modified: 2022/06/14

Plugin Output

tcp/5432/postgresql

```
The following certificate was found at the top of the certificate
chain sent by the remote host, but is self-signed and was not
found in the list of known certificate authorities :
```

```
| -Subject : C=XX/ST=There is no such thing outside US/L=Everywhere/O=OCOSA/OU=Office for
Complication of Otherwise Simple Affairs/CN=ubuntu804-base.localdomain/E=root@ubuntu804-
base.localdomain
```

26928 - SSL Weak Cipher Suites Supported

Synopsis

The remote service supports the use of weak SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer weak encryption.

Note: This is considerably easier to exploit if the attacker is on the same physical network.

See Also

<http://www.nessus.org/u?6527892d>

Solution

Reconfigure the affected application, if possible to avoid the use of weak ciphers.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

References

XREF	CWE:326
XREF	CWE:327
XREF	CWE:720
XREF	CWE:753
XREF	CWE:803
XREF	CWE:928
XREF	CWE:934

Plugin Information

Published: 2007/10/08, Modified: 2021/02/03

Plugin Output

192.168.50.3

Here is the list of weak SSL ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA(512)	RSA	RC4(40)	MD5
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC(56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA(512)	RSA	DES-CBC(40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA(512)	RSA	RC4(40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC(56)	

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

81606 - SSL/TLS EXPORT_RSA <= 512-bit Cipher Suites Supported (FREAK)

Synopsis

The remote host supports a set of weak ciphers.

Description

The remote host supports EXPORT_RSA cipher suites with keys less than or equal to 512 bits. An attacker can factor a 512-bit RSA modulus in a short amount of time.

A man-in-the-middle attacker may be able to downgrade the session to use EXPORT_RSA cipher suites (e.g. CVE-2015-0204). Thus, it is recommended to remove support for weak cipher suites.

See Also

<https://www.smacktls.com/#freak>

<https://www.openssl.org/news/secadv/20150108.txt>

<http://www.nessus.org/u?b78da2c4>

Solution

Reconfigure the service to remove support for EXPORT_RSA cipher suites.

Risk Factor

Medium

VPR Score

1.4

EPSS Score

0.9247

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.2 (CVSS2#E:U/RL:OF/RC:C)

References

BID 71936

CVE CVE-2015-0204

Plugin Information

Published: 2015/03/04, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

```
EXPORT_RSA cipher suites supported by the remote server :
```

```
Low Strength Ciphers (<= 64-bit key)
```

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EXP-DES-CBC-SHA	0x00, 0x08	RSA(512)	RSA	DES-CBC(40)	
SHA1 export					
EXP-RC2-CBC-MD5	0x00, 0x06	RSA(512)	RSA	RC2-CBC(40)	MD5
export					
EXP-RC4-MD5	0x00, 0x03	RSA(512)	RSA	RC4(40)	MD5
export					

```
The fields above are :
```

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```


52503 - Samba 3.x < 3.3.15 / 3.4.12 / 3.5.7 'FD_SET' Memory Corruption

Synopsis

The remote Samba server is affected by a memory corruption vulnerability.

Description

According to its banner, the version of Samba 3.x running on the remote host is earlier than 3.3.15 / 3.4.12 / 3.5.7. An error exists in the range checks on file descriptors in the 'FD_SET' macro that allows stack corruption. This corruption can cause Samba to crash or to continually try selecting on an improper descriptor set.

An attacker who is able to get a connection to a file share, either authenticated or via a guest connection, can leverage this issue to launch a denial of service attack against the affected smbd service.

Note the possibility of arbitrary code execution exists with this type of vulnerability but has not been confirmed.

Also note that Nessus has not actually tried to exploit this issue or otherwise determine if one of the patches has been applied.

See Also

https://bugzilla.samba.org/show_bug.cgi?id=7949

<http://www.samba.org/samba/security/CVE-2011-0719.html>

<https://www.samba.org/samba/history/samba-3.3.15.html>

<https://www.samba.org/samba/history/samba-3.4.12.html>

<https://www.samba.org/samba/history/samba-3.5.7.html>

Solution

Either apply one of the patches referenced in the project's advisory or upgrade to 3.3.15 / 3.4.12 / 3.5.7 or later.

Risk Factor

Medium

VPR Score

3.6

EPSS Score

0.156

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

References

BID	46597
CVE	CVE-2011-0719
XREF	Secunia:43512

Plugin Information

Published: 2011/03/02, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.3.15 / 3.4.12 / 3.5.7
```

55733 - Samba 3.x < 3.3.16 / 3.4.14 / 3.5.10 Multiple Vulnerabilities

Synopsis

The remote Samba server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Samba 3.x running on the remote host is earlier than 3.3.16 / 3.4.14 / 3.5.10. As such, it is potentially affected by several vulnerabilities in the Samba Web Administration Tool (SWAT) :

- A cross-site scripting vulnerability exists because of a failure to sanitize input to the username parameter of the 'passwd' program. (Issue #8289)
- A cross-site request forgery (CSRF) vulnerability can allow SWAT to be manipulated when a user who is logged in as root is tricked into clicking specially crafted URLs sent by an attacker. (Issue #8290)

Note that these issues are only exploitable when SWAT is enabled, and it is not enabled by default.

Also note that Nessus has relied only on the self-reported version number and has not actually determined whether SWAT is enabled, tried to exploit these issues, or determine if the associated patches have been applied.

See Also

https://bugzilla.samba.org/show_bug.cgi?id=8289
https://bugzilla.samba.org/show_bug.cgi?id=8290
<https://www.samba.org/samba/security/CVE-2011-2522>
<https://www.samba.org/samba/security/CVE-2011-2694>
<https://www.samba.org/samba/history/samba-3.3.16.html>
<https://www.samba.org/samba/history/samba-3.4.14.html>
<https://www.samba.org/samba/history/samba-3.5.10.html>

Solution

Either apply one of the patches referenced in the project's advisory or upgrade to 3.3.16 / 3.4.14 / 3.5.10 or later.

Risk Factor

Medium

VPR Score

6.7

EPSS Score

0.1492

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

5.3 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	48899
BID	48901
CVE	CVE-2011-2522
CVE	CVE-2011-2694
XREF	EDB-ID:17577
XREF	Secunia:45393

Plugin Information

Published: 2011/07/29, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.3.16 / 3.4.14 / 3.5.10
```

Synopsis

The remote Samba server is affected by a denial of service vulnerability.

Description

According to its banner, the version of Samba running on the remote host is 3.x prior to 3.5.22, 3.6.x prior to 3.6.17 or 4.0.x prior to 4.0.8. It is, therefore, potentially affected by a denial of service vulnerability.

An integer overflow error exists in the function 'read_nttrans_ea_lis' in the file 'nttrans.c' that could allow denial of service attacks to be carried out via specially crafted network traffic.

Note if 'guest' connections are allowed, this issue can be exploited by a remote, unauthenticated attacker.

Further note that Nessus has relied only on the self-reported version number and has not actually tried to exploit this issue or determine if the associated patch has been applied.

See Also

<https://www.samba.org/samba/security/CVE-2013-4124.html>

<https://www.samba.org/samba/history/samba-3.5.22.html>

<https://www.samba.org/samba/history/samba-3.6.17.html>

<https://www.samba.org/samba/history/samba-4.0.8.html>

<http://www.nessus.org/u?a31cffce>

Solution

Either install the patch referenced in the project's advisory, or upgrade to version 3.5.22 / 3.6.17 / 4.0.8 or later.

Risk Factor

Medium

VPR Score

4.4

EPSS Score

0.8681

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	61597
CVE	CVE-2013-4124
XREF	EDB-ID:27778

Plugin Information

Published: 2013/08/08, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.5.22 / 3.6.17 / 4.0.8
```

Synopsis

The remote Samba server may be affected by multiple vulnerabilities.

Description

According to its banner, the version of Samba server on the remote host is earlier than 3.0.37 / 3.2.15 / 3.3.8 / 3.4.2. Such versions are potentially affected by multiple issues :

- If a user in '/etc/passwd' is misconfigured to have an empty home directory, then connecting to the home share of this user will use the root of the file system as the home directory. (CVE-2009-2813)
- Specially crafted SMB requests on authenticated SMB connections can send smbd into a 100% loop, causing a denial of service. (CVE-2009-2906)
- When 'mount.cifs' is installed as a setuid program, a user can pass it a credential or password path to which he or she does not have access and then use the '--verbose' option to view the first line of that file. (CVE-2009-2948)

See Also

<https://www.samba.org/samba/security/CVE-2009-2906.html>

<https://www.samba.org/samba/security/CVE-2009-2948.html>

<https://www.samba.org/samba/security/CVE-2009-2813.html>

Solution

Upgrade to Samba 3.0.37 / 3.2.15 / 3.3.8 / 3.4.2 or later.

Risk Factor

Medium

VPR Score

6.6

EPSS Score

0.0051

CVSS v2.0 Base Score

6.0 (CVSS2#AV:N/AC:M/Au:S/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

4.4 (CVSS2#E:U/RL:OF/RC:C)

References

BID	36572
BID	36573
CVE	CVE-2009-2813
CVE	CVE-2009-2906
CVE	CVE-2009-2948
XREF	CWE:264

Plugin Information

Published: 2009/10/02, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
The remote Samba server appears to be :  
Samba 3.0.20-Debian
```


Synopsis

The remote Samba server is affected by multiple vulnerabilities.

Description

According to its banner, the version of Samba running on the remote host is 3.5.x prior to 3.5.21, 3.6.x prior to 3.6.12, or 4.x prior to 4.0.1. It is, therefore, affected by the following vulnerabilities :

- An unspecified flaw exists in the Samba Web Administration Tool (SWAT) that allows a remote attacker to conduct clickjacking attacks via a FRAME or IFRAME element. (CVE-2013-0213)
- A cross-site request forgery vulnerability exists due to a failure to require multiple steps or explicit confirmation for sensitive transactions in the Samba Web Administration Tool (SWAT). A remote attacker can exploit this, by convincing a user to follow a crafted URL, to cause the user to perform unintended actions.

(CVE-2013-0213)

Note that these vulnerabilities are only exploitable when SWAT is enabled, and it is not enabled by default. Additionally, note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.samba.org/samba/security/CVE-2013-0213.html>

<https://www.samba.org/samba/security/CVE-2013-0214.html>

<https://www.samba.org/samba/history/samba-4.0.2.html>

Solution

Upgrade to Samba version 3.5.21 / 3.6.12 / 4.0.2 or later.

Alternatively, install the patch referenced in the vendor advisory.

Risk Factor

Medium

VPR Score

5.9

EPSS Score

0.0407

CVSS v2.0 Base Score

5.1 (CVSS2#AV:N/AC:H/Au:N/C:P/I:P/A:P)

CVSS v2.0 Temporal Score

3.8 (CVSS2#E:U/RL:OF/RC:C)

References

BID	57631
CVE	CVE-2013-0213
CVE	CVE-2013-0214

Plugin Information

Published: 2013/02/04, Modified: 2018/11/15

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 3.5.21 / 3.6.12 / 4.0.2
```

Synopsis

The remote Samba server is potentially affected by a vulnerability.

Description

The version of Samba running on the remote host is potentially affected by a vulnerability. The SMB protocol allows opening files where the client requests read-only access, but then implicitly truncating the opened file if the client specifies a separate OVERWRITE create disposition. This operation requires write access to the file, and in the default Samba configuration the operating system kernel will deny access to open a read-only file for read/write (which the truncate operation requires). However, when Samba has been configured to ignore kernel file system permissions, Samba will truncate a file when the underlying operating system kernel would deny the operation.

Note that Nessus has not tested for these issues but has instead relied only on the application's self-reported version number.

See Also

<https://www.samba.org/samba/security/CVE-2023-4091.html>

<https://www.samba.org/samba/history/security.html>

Solution

Upgrade to Samba version 4.17.12, 4.18.8, or 4.19.1.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:H/A:N)

CVSS v3.0 Temporal Score

5.7 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

4.4

EPSS Score

0.0188

CVSS v2.0 Base Score

6.8 (CVSS2#AV:N/AC:L/Au:S/C:N/I:C/A:N)

CVSS v2.0 Temporal Score

5.0 (CVSS2#E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2023-4091
XREF	IAVA:2023-A-0535

Plugin Information

Published: 2023/10/13, Modified: 2023/11/14

Plugin Output

tcp/445/cifs

```
Installed version : 3.0.20-Debian
Fixed version    : 4.17.12
```

12213 - TCP/IP Sequence Prediction Blind Reset Spoofing DoS

Synopsis

It was possible to send spoofed RST packets to the remote system.

Description

The remote host is affected by a sequence number approximation vulnerability that allows an attacker to send spoofed RST packets to the remote host and close established connections. This may cause problems for some dedicated services (BGP, a VPN over TCP, etc).

See Also

<https://downloads.avaya.com/elmodocs2/security/ASA-2006-217.htm>

<http://www.kb.cert.org/vuls/id/JARL-5ZQR4D>

<http://www-01.ibm.com/support/docview.wss?uid=isg1IY55949>

<http://www-01.ibm.com/support/docview.wss?uid=isg1IY55950>

<http://www-01.ibm.com/support/docview.wss?uid=isg1IY62006>

<http://www.juniper.net/support/security/alerts/niscc-236929.txt>

<https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2005/ms05-019>

<https://docs.microsoft.com/en-us/security-updates/SecurityBulletins/2006/ms06-064>

<http://www.kb.cert.org/vuls/id/JARL-5YGQ9G>

<http://www.kb.cert.org/vuls/id/JARL-5ZQR7H>

<http://www.kb.cert.org/vuls/id/JARL-5YGQAJ>

<http://www.nessus.org/u?cf64c2ca>

<https://isc.sans.edu/diary.html?date=2004-04-20>

Solution

Contact the vendor for a patch or mitigation advice.

Risk Factor

Medium

VPR Score

6.1

EPSS Score

0.0478

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS v2.0 Temporal Score

3.9 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	10183
CVE	CVE-2004-0230
XREF	CERT:415294
XREF	EDB-ID:276
XREF	EDB-ID:291

Plugin Information

Published: 2004/04/25, Modified: 2019/03/06

Plugin Output

tcp/0

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2023/04/19

Plugin Output

tcp/25/smtp

TLsv1 is enabled and the server supports at least one cipher.

104743 - TLS Version 1.0 Protocol Detection

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS v2.0 Base Score

6.1 (CVSS2#AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE:327

Plugin Information

Published: 2017/11/22, Modified: 2023/04/19

Plugin Output

tcp/5432/postgresql

TLsv1 is enabled and the server supports at least one cipher.

42263 - Unencrypted Telnet Server

Synopsis

The remote Telnet server transmits traffic in cleartext.

Item	Description
1	...
2	...
3	...
4	...
5	...
6	...
7	...
8	...
9	...
10	...
11	...
12	...
13	...
14	...
15	...
16	...
17	...
18	...
19	...
20	...
21	...
22	...
23	...
24	...
25	...
26	...
27	...
28	...
29	...
30	...
31	...
32	...
33	...
34	...
35	...
36	...
37	...
38	...
39	...
40	...
41	...
42	...
43	...
44	...
45	...
46	...
47	...
48	...
49	...
50	...
51	...
52	...
53	...
54	...
55	...
56	...
57	...
58	...
59	...
60	...
61	...
62	...
63	...
64	...
65	...
66	...
67	...
68	...
69	...
70	...
71	...
72	...
73	...
74	...
75	...
76	...
77	...
78	...
79	...
80	...
81	...
82	...
83	...
84	...
85	...
86	...
87	...
88	...
89	...
90	...
91	...
92	...
93	...
94	...
95	...
96	...
97	...
98	...
99	...
100	...

The remote host is running a Telnet server over an unencrypted channel.

Using Telnet over an unencrypted channel is not recommended as logins, passwords, and commands are transferred in cleartext. This allows a remote, man-in-the-middle attacker to eavesdrop on a Telnet session to obtain credentials or other sensitive information and to modify traffic exchanged between a client and server.

SSH is preferred over Telnet since it protects credentials from eavesdropping and can tunnel additional data streams such as an X11 session.

Solution

Disable the Telnet service and use SSH instead.

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced visibility and networking opportunities	Proactive networking and industry engagement
2. Limited marketing budget	Reduced reach and brand awareness	Strategic marketing and social media presence
3. Limited product differentiation	Increased competition and lower margins	Product innovation and differentiation
4. Limited customer base	Reduced sales volume and revenue	Targeted marketing and customer acquisition
5. Limited financial resources	Reduced operational flexibility and growth potential	Financial planning and resource optimization

Medium

CVSS v3.0 Base Score

6.5 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v2.0 Base Score

5.8 (CVSS2#AV:N/AC:M/Au:N/C:P/I:P/A:N)

Plugin Information

Published: 2009/10/27, Modified: 2024/01/16

Plugin Output

tcp/23/telnet

```
Nessus collected the following banner from the remote Telnet server :

----- snip -----

_ _ _ _ _ | _ _ _ _ _ _ _ | _ _ ( _ _ | _ _ | _ _ | _ _ \
| ' _ ' \ / _ \ / _ \ ' _ ' / _ \ | ' _ \ | / _ \ ' _ ' \ / _ \ ) | | | | | | | | | | | | | | | | | |
| | | | | | _ \ | | ( | \ _ \ | | | | ( | | | ( | | | | _ \ / _ \ |
| _ | | | | \ _ \ | \ _ \ , | _ \ | | \ _ \ | | | \ _ \ , | _ \ | | \ _ \ |
                                     | _ |

Warning: Never expose this VM to an untrusted network!
```

```
Contact: msfdev[at]metasploit.com
Login with msfadmin/msfadmin to get started
metasploitable login:
----- snip -----
```

88490 - Web Server Error Page Information Disclosure

Synopsis

The remote web server discloses information via a default error page.

Description

The default error page sent by the remote web server discloses information that can aid an attacker, such as the server version and languages used by the web server.

Solution

Modify the web server to not disclose detailed information about the underlying web server, or use a custom error page instead.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/01/29, Modified: 2022/04/11

Plugin Output

tcp/80/www

```
Server Type      : Apache
Server Version   : Apache/2.2.8
Source           : http://192.168.50.3/SpWK3IFk
```

88099 - Web Server HTTP Header Information Disclosure

Synopsis

The remote web server discloses information via HTTP headers.

Description

The HTTP headers sent by the remote web server disclose information that can aid an attacker, such as the server version and languages used by the web server.

Solution

Modify the HTTP headers of the web server to not disclose detailed information about the underlying web server.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2016/01/22, Modified: 2019/04/30

Plugin Output

tcp/80/www

```
Server type      : Apache
Server version   : 2.2.8
Source           : 2.2.8
Additional data   : X-Powered-By: PHP/5.2.4-2ubuntu5.10
```

10114 - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

icmp/0

The difference between the local and remote clocks is 3220 seconds.

42983 - ISC BIND 9 DNSSEC Cache Poisoning

Synopsis

The remote name server is affected by a cache poisoning vulnerability.

Description

According to its version number, the remote installation of BIND suffers from a cache poisoning vulnerability. This issue affects all versions prior to 9.4.3-P5, 9.5.2-P2 or 9.6.1-P3.

Note that only nameservers that allow recursive queries and validate DNSSEC records are affected. Nessus has not attempted to verify if this configuration applies to the remote service, though, so this could be a false positive.

See Also

<https://www.isc.org/advisories/CVE2009-4022>

<http://www.vupen.com/english/advisories/2010/1352>

<http://www.vupen.com/english/advisories/2010/0622>

<http://www.vupen.com/english/advisories/2009/3335>

Solution

Upgrade to BIND 9.4.3-P5 / 9.5.2-P2 / 9.6.1-P3 or later.

Risk Factor

Low

VPR Score

5.9

EPSS Score

0.2841

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	37118
CVE	CVE-2009-4022
CVE	CVE-2010-0382
XREF	CERT:418861

Plugin Information

Published: 2009/12/02, Modified: 2018/06/27

Plugin Output

udp/53/dns

234554 - OpenSSH < 10.0 DisableForwarding

Synopsis

The SSH server running on the remote host is affected by a vulnerability.

Description

The version of OpenSSH installed on the remote host is prior to 10.0. It is, therefore, affected by a vulnerability. In sshd in OpenSSH the DisableForwarding directive does not adhere to the documentation stating that it disables X11 and agent forwarding.

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.openssh.com/txt/release-10.0>

Solution

Upgrade to OpenSSH version 10.0 or later.

Risk Factor

Low

CVSS v3.0 Base Score

3.8 (CVSS:3.0/AV:L/AC:L/PR:L/UI:N/S:C/C:N/I:L/A:N)

VPR Score

2.4

EPSS Score

0.0001

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:N/I:P/A:N)

STIG Severity

I

References

CVE CVE-2025-32728
XREF IAVA:2025-A-0258

Plugin Information

Published: 2025/04/17, Modified: 2025/06/10

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 10.0
```

Synopsis

The SSH server running on the remote host is affected by a remote code execution vulnerability.

Description

The version of OpenSSH installed on the remote host is prior to 10.1. It is, therefore, affected by a vulnerability as referenced in the release-10.1p1 advisory.

- ssh in OpenSSH before 10.1 allows control characters in usernames that originate from certain possibly untrusted sources, potentially leading to code execution when a ProxyCommand is used. The untrusted sources are the command line and %-sequence expansion of a configuration file. (A configuration file that provides a complete literal username is not categorized as an untrusted source.) (CVE-2025-61984)

Note that Nessus has not tested for this issue but has instead relied only on the application's self-reported version number.

See Also

<https://www.openssh.com/releasenotes.html#10.1p1>

Solution

Upgrade to OpenSSH version 10.1/10.1p1 or later.

Risk Factor

Low

CVSS v3.0 Base Score

3.6 (CVSS:3.0/AV:L/AC:H/PR:L/UI:N/S:U/C:L/I:L/A:N)

VPR Score

4.0

EPSS Score

0.0001

CVSS v2.0 Base Score

2.4 (CVSS2#AV:L/AC:H/Au:S/C:P/I:P/A:N)

STIG Severity

II

References

CVE CVE-2025-61984
XREF IAVA:2025-A-0729

Plugin Information

Published: 2025/10/10, Modified: 2025/10/10

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 10.1 / 10.1.p1
```

44080 - OpenSSH X11UseLocalhost X11 Forwarding Port Hijacking

Synopsis

The remote SSH service may be affected by an X11 forwarding port hijacking vulnerability.

Description

According to its banner, the version of SSH installed on the remote host is older than 5.1 and may allow a local user to hijack the X11 forwarding port. The application improperly sets the 'SO_REUSEADDR' socket option when the 'X11UseLocalhost' configuration option is disabled.

Note that most operating systems, when attempting to bind to a port that has previously been bound with the 'SO_REUSEADDR' option, will check that either the effective user-id matches the previous bind (common BSD-derived systems) or that the bind addresses do not overlap (Linux and Solaris). This is not the case with other operating systems such as HP-UX.

See Also

<https://www.openssh.com/txt/release-5.1>

Solution

Upgrade to OpenSSH version 5.1 or later.

Risk Factor

Low

VPR Score

3.6

EPSS Score

0.0002

CVSS v2.0 Base Score

1.2 (CVSS2#AV:L/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

0.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	30339
CVE	CVE-2008-3259

XREF

CWE:200

Plugin Information

Published: 2011/10/04, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 5.1
```


53841 - Portable OpenSSH ssh-keysign ssh-rand-helper Utility File Descriptor Leak Local Information Disclosure

Synopsis

Local attackers may be able to access sensitive information.

Description

According to its banner, the version of OpenSSH running on the remote host is earlier than 5.8p2. Such versions may be affected by a local information disclosure vulnerability that could allow the contents of the host's private key to be accessible by locally tracing the execution of the ssh-keysign utility. Having the host's private key may allow the impersonation of the host.

Note that installations are only vulnerable if ssh-rand-helper was enabled during the build process, which is not the case for *BSD, OS X, Cygwin and Linux.

See Also

<http://www.openssh.com/txt/portable-keysign-rand-helper.adv>

<http://www.openssh.com/txt/release-5.8p2>

Solution

Upgrade to Portable OpenSSH 5.8p2 or later.

Risk Factor

Low

VPR Score

3.4

EPSS Score

0.0006

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.6 (CVSS2#E:U/RL:OF/RC:C)

References

BID 47691

CVE CVE-2011-4327
XREF Secunia:44347

Plugin Information

Published: 2011/05/09, Modified: 2024/03/27

Plugin Output

tcp/22/ssh

```
Version source      : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
Installed version   : 4.7p1
Fixed version       : 5.8p2
```

86328 - SSH Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Synopsis

The remote host allows SSH connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

Description

The remote SSH server allows connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party can find the shared secret in a short amount of time (depending on modulus size and attacker resources).

This allows an attacker to recover the plaintext or potentially violate the integrity of connections.

See Also

<https://weakdh.org/>

<https://stribika.github.io/2015/01/04/secure-secure-shell.html>

Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.9

EPSS Score

0.9403

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/10/09, Modified: 2022/12/05

Plugin Output

tcp/22/ssh

The SSH server is vulnerable to the Logjam attack because :

It supports diffie-hellman-group1-sha1 key exchange.

It supports diffie-hellman-group-exchange-sha1 key exchange and allows a moduli smaller than or equal to 1024.

Note that only an attacker with nation-state level resources can effectively make use of the vulnerability, and only against sessions where the vulnerable key exchange algorithms are used.

70658 - SSH Server CBC Mode Ciphers Enabled

Synopsis

The SSH server is configured to use Cipher Block Chaining.

Description

The SSH server is configured to support Cipher Block Chaining (CBC) encryption. This may allow an attacker to recover the plaintext message from the ciphertext.

Note that this plugin only checks for the options of the SSH server and does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable CBC mode cipher encryption, and enable CTR or GCM cipher mode encryption.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

VPR Score

1.4

EPSS Score

0.0307

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	32319
CVE	CVE-2008-5161
XREF	CERT:958563
XREF	CWE:200

Plugin Information

Published: 2013/10/28, Modified: 2023/10/27

Plugin Output

tcp/22/ssh

The following client-to-server Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc  
aes128-cbc  
aes192-cbc  
aes256-cbc  
blowfish-cbc  
cast128-cbc  
rijndael-cbc@lysator.liu.se
```

The following server-to-client Cipher Block Chaining (CBC) algorithms are supported :

```
3des-cbc  
aes128-cbc  
aes192-cbc  
aes256-cbc  
blowfish-cbc  
cast128-cbc  
rijndael-cbc@lysator.liu.se
```

153953 - SSH Weak Key Exchange Algorithms Enabled

Synopsis

The remote SSH server is configured to allow weak key exchange algorithms.

Description

The remote SSH server is configured to allow key exchange algorithms which are considered weak.

This is based on the IETF draft document Key Exchange (KEX) Method Updates and Recommendations for Secure Shell (SSH) RFC9142. Section 4 lists guidance on key exchange algorithms that SHOULD NOT and MUST NOT be enabled. This includes:

diffie-hellman-group-exchange-sha1

diffie-hellman-group1-sha1

gss-gex-sha1-*

gss-group1-sha1-*

gss-group14-sha1-*

rsa1024-sha1

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

See Also

<https://datatracker.ietf.org/doc/html/rfc9142>

Solution

Contact the vendor or consult product documentation to disable the weak algorithms.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:L/I:N/A:N)

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2021/10/13, Modified: 2024/03/22

Plugin Output

tcp/22/ssh

The following weak key exchange algorithms are enabled :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group1-sha1
```


71049 - SSH Weak MAC Algorithms Enabled

Synopsis

The remote SSH server is configured to allow MD5 and 96-bit MAC algorithms.

Description

The remote SSH server is configured to allow either MD5 or 96-bit MAC algorithms, both of which are considered weak.

Note that this plugin only checks for the options of the SSH server, and it does not check for vulnerable software versions.

Solution

Contact the vendor or consult product documentation to disable MD5 and 96-bit MAC algorithms.

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2013/11/22, Modified: 2016/12/14

Plugin Output

tcp/22/ssh

```
The following client-to-server Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-sha1-96
```

```
The following server-to-client Message Authentication Code (MAC) algorithms
are supported :
```

```
  hmac-md5
  hmac-md5-96
  hmac-sha1-96
```

83875 - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Synopsis

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

Description

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.9

EPSS Score

0.9403

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/28, Modified: 2024/09/11

Plugin Output

tcp/25/smtp

Vulnerable connection combinations :

```
SSL/TLS version : SSLv3
Cipher suite    : TLS1_CK_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
Diffie-Hellman MODP size (bits) : 512
Logjam attack difficulty : Easy (could be carried out by individuals)

SSL/TLS version : SSLv3
Cipher suite    : TLS1_CK_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : SSLv3
Cipher suite    : TLS1_CK_DHE_RSA_WITH_DES_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : SSLv3
Cipher suite    : TLS1_CK_DHE_RSA_WITH_3DES_EDE_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : SSLv3
Cipher suite    : TLS1_CK_DHE_RSA_WITH_AES_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : TLSv1.0
Cipher suite    : TLS1_CK_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
Diffie-Hellman MODP size (bits) : 512
Logjam attack difficulty : Easy (could be carried out by individuals)

SSL/TLS version : TLSv1.0
Cipher suite    : TLS1_CK_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : TLSv1.0
Cipher suite    : TLS1_CK_DHE_RSA_WITH_DES_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : TLSv1.0
Cipher suite    : TLS1_CK_DHE_RSA_WITH_3DES_EDE_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

SSL/TLS version : TLSv1.0
```

Cipher suite : TLS1_CK_DHE_RSA_WITH_AES_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)

83875 - SSL/TLS Diffie-Hellman Modulus <= 1024 Bits (Logjam)

Synopsis

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits.

Description

The remote host allows SSL/TLS connections with one or more Diffie-Hellman moduli less than or equal to 1024 bits. Through cryptanalysis, a third party may be able to find the shared secret in a short amount of time (depending on modulus size and attacker resources). This may allow an attacker to recover the plaintext or potentially violate the integrity of connections.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to use a unique Diffie-Hellman moduli of 2048 bits or greater.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.9

EPSS Score

0.9403

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

1.9 (CVSS2#E:U/RL:OF/RC:C)

References

BID	74733
CVE	CVE-2015-4000
XREF	CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/28, Modified: 2024/09/11

Plugin Output

tcp/5432/postgresql

Vulnerable connection combinations :

```
SSL/TLS version  : SSLv3
Cipher suite     : TLS1_CK_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version  : SSLv3
Cipher suite     : TLS1_CK_DHE_RSA_WITH_AES_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version  : SSLv3
Cipher suite     : TLS1_CK_DHE_RSA_WITH_3DES_EDE_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version  : TLSv1.0
Cipher suite     : TLS1_CK_DHE_RSA_WITH_AES_256_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version  : TLSv1.0
Cipher suite     : TLS1_CK_DHE_RSA_WITH_AES_128_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

```
SSL/TLS version  : TLSv1.0
Cipher suite     : TLS1_CK_DHE_RSA_WITH_3DES_EDE_CBC_SHA
Diffie-Hellman MODP size (bits) : 1024
Logjam attack difficulty : Hard (would require nation-state resources)
```

83738 - SSL/TLS EXPORT_DHE <= 512-bit Export Cipher Suites Supported (Logjam)

Synopsis

The remote host supports a set of weak ciphers.

Description

The remote host supports EXPORT_DHE cipher suites with keys less than or equal to 512 bits. Through cryptanalysis, a third party can find the shared secret in a short amount of time.

A man-in-the-middle attacker may be able to downgrade the session to use EXPORT_DHE cipher suites. Thus, it is recommended to remove support for weak cipher suites.

See Also

<https://weakdh.org/>

Solution

Reconfigure the service to remove support for EXPORT_DHE cipher suites.

Risk Factor

Low

CVSS v3.0 Base Score

3.7 (CVSS:3.0/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

3.2 (CVSS:3.0/E:U/RL:O/RC:C)

VPR Score

3.9

EPSS Score

0.9403

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

2.2 (CVSS2#E:U/RL:ND/RC:C)

References

BID 74733
CVE CVE-2015-4000
XREF CEA-ID:CEA-2021-0004

Plugin Information

Published: 2015/05/21, Modified: 2022/12/05

Plugin Output

tcp/25/smtp

EXPORT_DHE cipher suites supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

Synopsis

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

Description

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

See Also

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

Solution

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

Risk Factor

Medium

CVSS v3.0 Base Score

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

5.1

EPSS Score

0.9396

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	70574
CVE	CVE-2014-3566
XREF	CERT:577193

Plugin Information

Published: 2014/10/15, Modified: 2023/06/23

Plugin Output

tcp/25/smtp

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

78479 - SSLv3 Padding Oracle On Downgraded Legacy Encryption Vulnerability (POODLE)

Synopsis

It is possible to obtain sensitive information from the remote host with SSL/TLS-enabled services.

Description

The remote host is affected by a man-in-the-middle (MitM) information disclosure vulnerability known as POODLE. The vulnerability is due to the way SSL 3.0 handles padding bytes when decrypting messages encrypted using block ciphers in cipher block chaining (CBC) mode.

MitM attackers can decrypt a selected byte of a cipher text in as few as 256 tries if they are able to force a victim application to repeatedly send the same data over newly created SSL 3.0 connections.

As long as a client and service both support SSLv3, a connection can be 'rolled back' to SSLv3, even if TLSv1 or newer is supported by the client and service.

The TLS Fallback SCSV mechanism prevents 'version rollback' attacks without impacting legacy clients; however, it can only protect connections when the client and service support the mechanism. Sites that cannot disable SSLv3 immediately should enable this mechanism.

This is a vulnerability in the SSLv3 specification, not in any particular SSL implementation. Disabling SSLv3 is the only way to completely mitigate the vulnerability.

See Also

<https://www.imperialviolet.org/2014/10/14/poodle.html>

<https://www.openssl.org/~bodo/ssl-poodle.pdf>

<https://tools.ietf.org/html/draft-ietf-tls-downgrade-scsv-00>

Solution

Disable SSLv3.

Services that must support SSLv3 should enable the TLS Fallback SCSV mechanism until SSLv3 can be disabled.

Risk Factor

Medium

CVSS v3.0 Base Score

3.4 (CVSS:3.0/AV:N/AC:H/PR:N/UI:R/S:C/C:L/I:N/A:N)

CVSS v3.0 Temporal Score

3.1 (CVSS:3.0/E:P/RL:O/RC:C)

VPR Score

5.1

EPSS Score

0.9396

CVSS v2.0 Base Score

4.3 (CVSS2#AV:N/AC:M/Au:N/C:P/I:N/A:N)

CVSS v2.0 Temporal Score

3.4 (CVSS2#E:POC/RL:OF/RC:C)

References

BID	70574
CVE	CVE-2014-3566
XREF	CERT:577193

Plugin Information

Published: 2014/10/15, Modified: 2023/06/23

Plugin Output

tcp/5432/postgresql

Nessus determined that the remote server supports SSLv3 with at least one CBC cipher suite, indicating that this server is vulnerable.

It appears that TLSv1 or newer is supported on the server. However, the Fallback SCSV mechanism is not supported, allowing connections to be "rolled back" to SSLv3.

10407 - X Server Detection

Synopsis

An X11 server is listening on the remote host

Description

The remote host is running an X11 server. X11 is a client-server protocol that can be used to display graphical applications running on a given host on a remote client.

Since the X11 traffic is not ciphered, it is possible for an attacker to eavesdrop on the connection.

Solution

Restrict access to this port. If the X11 client/server facility is not used, disable TCP support in X11 entirely (-nolisten tcp).

Risk Factor

Low

CVSS v2.0 Base Score

2.6 (CVSS2#AV:N/AC:H/Au:N/C:P/I:N/A:N)

Plugin Information

Published: 2000/05/12, Modified: 2019/03/05

Plugin Output

tcp/6000/x11

```
X11 Version : 11.0
```

21186 - AJP Connector Detection

Synopsis

There is an AJP connector listening on the remote host.

Description

The remote host is running an AJP (Apache JServ Protocol) connector, a service by which a standalone web server such as Apache communicates over TCP with a Java servlet container such as Tomcat.

See Also

<http://tomcat.apache.org/connectors-doc/>

<http://tomcat.apache.org/connectors-doc/ajp/ajpv13a.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/04/05, Modified: 2019/11/22

Plugin Output

tcp/8009/ajp13

The connector listing on this port supports the ajp13 protocol.

18261 - Apache Banner Linux Distribution Disclosure

Synopsis

The name of the Linux distribution running on the remote host was found in the banner of the web server.

Description

Nessus was able to extract the banner of the Apache web server and determine which Linux distribution the remote host is running.

Solution

If you do not wish to display this information, edit 'httpd.conf' and set the directive 'ServerTokens Prod' and restart Apache.

Risk Factor

None

Plugin Information

Published: 2005/05/15, Modified: 2025/03/31

Plugin Output

tcp/0

```
The Linux distribution detected was :  
- Ubuntu 8.04 (gutsy)
```

111465 - Apache HTTP Server Error Page Detection

Synopsis

The remote web server version can be obtained via a default error page.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from an error page.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/07/31, Modified: 2025/10/16

Plugin Output

tcp/80/www

```
Version : 2.2.8
Source  : Apache/2.2.8 (Ubuntu) DAV/2
URL     : http://192.168.50.3/.htaccess
```


48204 - Apache HTTP Server Version

Synopsis

It is possible to obtain the version number of the remote Apache HTTP server.

Description

The remote host is running the Apache HTTP Server, an open source web server. It was possible to read the version number from the banner.

See Also

<https://httpd.apache.org/>

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0530

Plugin Information

Published: 2010/07/30, Modified: 2023/08/17

Plugin Output

tcp/80/www

```
URL      : http://192.168.50.3/
Version  : 2.2.8
Source   : Server: Apache/2.2.8 (Ubuntu) DAV/2
backported : 0
modules  : DAV/2
os       : Ubuntu
```

45590 - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2025/09/29

Plugin Output

tcp/0

Following application CPE's matched on the remote system :

```
cpe:/a:apache:http_server:2.2.8 -> Apache Software Foundation Apache HTTP Server
cpe:/a:isc:bind:9.4. -> ISC BIND
cpe:/a:isc:bind:9.4.2 -> ISC BIND
cpe:/a:mysql:mysql -> MySQL MySQL
cpe:/a:openbsd:openssh:4.7 -> OpenBSD OpenSSH
cpe:/a:openbsd:openssh:4.7p1 -> OpenBSD OpenSSH
cpe:/a:php:php:5.2.4 -> PHP PHP
cpe:/a:php:php:5.2.4-2ubuntu5.10 -> PHP PHP
cpe:/a:postgresql:postgresql -> PostgreSQL
cpe:/a:samba:samba:3.0.20 -> Samba Samba
```

10028 - DNS Server BIND version Directive Remote Version Detection

Synopsis

It is possible to obtain the version number of the remote DNS server.

Description

The remote host is running BIND or another DNS server that reports its version number when it receives a special request for the text 'version.bind' in the domain 'chaos'.

This version is not necessarily accurate and could even be forged, as some DNS servers send the information based on a configuration file.

Solution

It is possible to hide the version number of BIND by using the 'version' directive in the 'options' section in named.conf.

Risk Factor

None

References

XREF IAVT:0001-T-0583

Plugin Information

Published: 1999/10/12, Modified: 2022/10/12

Plugin Output

udp/53/dns

```
Version : 9.4.2
```

11002 - DNS Server Detection

Synopsis

A DNS server is listening on the remote host.

Description

The remote service is a Domain Name System (DNS) server, which provides a mapping between hostnames and IP addresses.

See Also

https://en.wikipedia.org/wiki/Domain_Name_System

Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

Risk Factor

None

Plugin Information

Published: 2003/02/13, Modified: 2017/05/16

Plugin Output

tcp/53/dns

11002 - DNS Server Detection

Synopsis

A DNS server is listening on the remote host.

Description

The remote service is a Domain Name System (DNS) server, which provides a mapping between hostnames and IP addresses.

See Also

https://en.wikipedia.org/wiki/Domain_Name_System

Solution

Disable this service if it is not needed or restrict access to internal hosts only if the service is available externally.

Risk Factor

None

Plugin Information

Published: 2003/02/13, Modified: 2017/05/16

Plugin Output

udp/53/dns

11951 - DNS Server Fingerprinting

Synopsis

It may be possible to fingerprint the remote DNS server.

Description

This script attempts to identify the remote DNS server type and version by sending various invalid requests to the remote DNS server and analyzing the error codes returned.

See Also

<http://cr.yp.to/surveys/dns1.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/16, Modified: 2022/04/11

Plugin Output

udp/53/dns

```
Nessus was not able to reliably identify the remote DNS server type.  
It might be :
```

```
ISC BIND 9.4.2
```

```
The fingerprint differs from these known signatures on 1 points.  
If you know the type and version of the remote DNS server, please send  
the following signature to dns-signatures@nessus.org :
```

```
4q:2:5:1q:1:1q:1q:1q:0X:0AAXD:0X:0X:0Z0X:0X:0X:4q:4q:4q:0X:0X:2:0AAXD:
```

72779 - DNS Server Version Detection

Synopsis

Nessus was able to obtain version information on the remote DNS server.

Description

Nessus was able to obtain version information by sending a special TXT record query to the remote host.

Note that this version is not necessarily accurate and could even be forged, as some DNS servers send the information based on a configuration file.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0937

Plugin Information

Published: 2014/03/03, Modified: 2024/09/24

Plugin Output

tcp/53/dns

```
DNS server answer for "version.bind" (over TCP) :
```

```
9.4.2
```

35371 - DNS Server hostname.bind Map Hostname Disclosure

Synopsis

The DNS server discloses the remote host name.

Description

It is possible to learn the remote host name by querying the remote DNS server for 'hostname.bind' in the CHAOS domain.

Solution

It may be possible to disable this feature. Consult the vendor's documentation for more information.

Risk Factor

None

Plugin Information

Published: 2009/01/15, Modified: 2011/09/14

Plugin Output

udp/53/dns

```
The remote host name is :  
metasploitable
```


54615 - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

tcp/0

```
Remote device type : general-purpose  
Confidence level : 95
```

35716 - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

tcp/0

```
The following card manufacturers were identified :
```

```
08:00:27:04:3F:E1 : PCS Systemtechnik GmbH
```

86420 - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

tcp/0

```
The following is a consolidated list of detected MAC addresses:  
- 08:00:27:04:3F:E1
```

10092 - FTP Server Detection

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0030

XREF IAVT:0001-T-0943

Plugin Information

Published: 1999/10/12, Modified: 2023/08/17

Plugin Output

tcp/21/ftp

```
The remote FTP banner is :
```

```
220 (vsFTPd 2.3.4)
```

10107 - HTTP Server Type and Version

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0931

Plugin Information

Published: 2000/01/04, Modified: 2020/10/30

Plugin Output

tcp/80/www

```
The remote web server type is :  
Apache/2.2.8 (Ubuntu) DAV/2
```

24260 - HyperText Transfer Protocol (HTTP) Information

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive is enabled, etc...

This test is informational only and does not denote any security problem.

Solution

n/a

Risk Factor	Impact	Control
1. Lack of industry connections	Reduced sales and market penetration	Networking and strategic partnerships
2. Limited marketing budget	Low brand awareness and visibility	Targeted digital marketing and social media
3. Intense competition	Price wars and reduced profit margins	Product differentiation and innovation
4. Economic downturn	Reduced consumer spending and demand	Cost-cutting measures and diversification
5. Technological obsolescence	Loss of competitive edge and market share	Continuous R&D and innovation
6. Regulatory changes	Increased compliance costs and operational challenges	Proactive legal and regulatory engagement
7. Supply chain disruptions	Increased costs and delivery delays	Diversified suppliers and inventory management
8. Talent acquisition challenges	Reduced productivity and innovation	Competitive compensation and employee development
9. Customer churn	Reduced revenue and market stability	Excellent customer service and loyalty programs
10. Financial mismanagement	Debt accumulation and potential bankruptcy	Transparent financial reporting and prudent budgeting

None

Plugin Information

Published: 2007/01/30, Modified: 2024/02/26

Plugin Output

tcp/80/www

Response Code : HTTP/1.1 200 OK

```
Protocol version : HTTP/1.1
```

```
HTTP/2 TLS Support: No
```

HTTP/2 Cleartext Support: No

SSL : no

```
Keep-Alive : yes
```

Options allowed : (Not implemented)

Headers :

Date: Wed, 22 Oct 2025 14:38:55 GMT

Server: Apache/2.2.8 (Ubuntu) DAV/2

X-Powered-By: PHP/5.2.4-2ubuntu5.10

```
Keep-Alive: timeout=15, max=98
```

Connection: Keep-Alive

Transfer-Encoding: chunked

Content-Type: text/html

Response Body :

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>
```

[illegible]

|_| |_| |_| _| _| _|, |_| |_| ._| / |_| _| / |_| _| _|, |_| ._| / |_| _| |_| |_|
|_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

11156 - IRC Daemon Version Detection

Synopsis

The remote host is an IRC server.

Description

This plugin determines the version of the IRC daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/11/19, Modified: 2016/01/08

Plugin Output

tcp/6667

```
The IRC server version is : Unreal3.2.8.1. FhiXOoE [*=2309]
```


10397 - Microsoft Windows SMB LanMan Pipe Server Listing Disclosure

Synopsis

It is possible to obtain network information.

Description

It was possible to obtain the browse list of the remote Windows system by sending a request to the LANMAN pipe. The browse list is the list of the nearest Windows systems of the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2022/02/01

Plugin Output

tcp/445/cifs

```
Here is the browse list of the remote host :
```

```
METASPLOITABLE ( os : 0.0 )
```

10394 - Microsoft Windows SMB Log In Possible

Synopsis

It was possible to log into the remote host.

Description

The remote host is running a Microsoft Windows operating system or Samba, a CIFS/SMB server for Unix. It was possible to log into it using one of the following accounts :

- Guest account
- Supplied credentials

See Also

<http://www.nessus.org/u?5c2589f6>

<https://support.microsoft.com/en-us/help/246261>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2000/05/09, Modified: 2025/07/21

Plugin Output

tcp/445/cifs

```
- NULL sessions may be enabled on the remote host.
```

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

tcp/445/cifs

```
The remote Operating System is : Unix
The remote native LAN manager is : Samba 3.0.20-Debian
The remote SMB Domain Name is : METASPLOITABLE
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/139/smb

```
An SMB server is running on this port.
```

11011 - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

tcp/445/cifs

```
A CIFS server is running on this port.
```

100871 - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote host supports the following versions of SMB :
  SMBv1
```

106716 - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

tcp/445/cifs

```
The remote host does NOT support the following SMB dialects :
__version__  __introduced in windows version__
2.0.2        Windows 2008
2.1          Windows 7
2.2.2        Windows 8 Beta
2.2.4        Windows 8 Beta
3.0          Windows 8
3.0.2        Windows 8.1
3.1          Windows 10
3.1.1        Windows 10
```

10719 - MySQL Server Detection

Synopsis

A database server is listening on the remote port.

Description

The remote host is running MySQL, an open source database server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0802

Plugin Information

Published: 2001/08/13, Modified: 2025/09/24

Plugin Output

tcp/3306/mysql

```
Service : mysql  
Version : unknown
```


10437 - NFS Share Export List

Synopsis

The remote NFS server exports a list of shares.

Description

This plugin retrieves the list of NFS exported shares.

See Also

<http://www.tldp.org/HOWTO/NFS-HOWTO/security.html>

Solution

Ensure each share is intended to be exported.

Risk Factor

None

Plugin Information

Published: 2000/06/07, Modified: 2019/10/04

Plugin Output

tcp/2049/rpc-nfs

```
Here is the export list of 192.168.50.3 :
```

```
/ *
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/21/ftp

```
Port 21/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/22/ssh

```
Port 22/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/23/telnet

```
Port 23/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/25/smtp

```
Port 25/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/80/www

```
Port 80/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/139/smb

```
Port 139/tcp was found to be open
```

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

tcp/445/cifs

```
Port 445/tcp was found to be open
```


19506 - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2025/10/01

Plugin Output

tcp/0

Information about this scan :

```
Nessus version : 10.10.0
Nessus build : 20152
Plugin feed version : 202510211937
Scanner edition used : Nessus Home
Scanner OS : LINUX
Scanner distribution : debian10-x86-64
Scan type : Normal
Scan name : S5L3Consegna
```

```
Scan policy used : Basic Network Scan
Scanner IP : 192.168.50.10
Port scanner(s) : nessus_syn_scanner
Port range : 21-23,25,80,110,139,443,445,3389
Ping RTT : 110.727 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : yes
Plugin debugging enabled : no
Paranoia level : 2
Report verbosity : 2
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 5
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2025/10/22 11:30 EDT (UTC -04:00)
Scan duration : 622 sec
Scan for malware : no
```

209654 - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

tcp/0

Following OS Fingerprints were found

Remote operating system : Polycom SIP Device
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (hardy)
Confidence level : 95
Method : SSH
Type : general-purpose
Fingerprint : SSH:SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1

Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
Type : general-purpose
Fingerprint : unknown

Remote operating system : Linux Kernel 2.6
Confidence level : 70
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B10113:F0x12:W5840:00204ffff:M1460:
P2:B10113:F0x12:W5792:00204ffff0402080affffff4445414401030305:M1460:
P3:B00000:F0x00:W0:00:M0

P4:191500_7_p=25

Remote operating system : Unix
Confidence level : 70
Method : smb
Type : general-purpose
Fingerprint : unknown

Remote operating system : Unix
Confidence level : 45
Method : MSRPC
Type : general-purpose
Fingerprint : unknown

Following fingerprints could not be used to determine OS :

SMTP:!:220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple
Affairs
ed093088706603bfd5dc237399b498da2d4d31c6
i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple Affairss/
CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple Affairs
ed093088706603bfd5dc237399b498da2d4d31c6

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

tcp/0

```
Remote operating system : Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)
Confidence level : 95
Method : HTTP
```

Not all fingerprints could give a match. If you think that these signatures would help us improve OS fingerprinting, please submit them by visiting <https://www.tenable.com/research/submitsignatures>.

```
SSH:SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
```

```
SinFP:
```

```
P1:B10113:F0x12:W5840:00204ffff:M1460:
P2:B10113:F0x12:W5792:00204ffff0402080affffff4445414401030305:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191500_7_p=25
```

```
SMTP:!:220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```

```
SSLcert:!:i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple
Affairss/CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple
Affairs
```

```
ed093088706603bfd5dc237399b498da2d4d31c6
```

```
i/CN:ubuntu804-base.localdomaini/O:OCOSAI/OU:Office for Complication of Otherwise Simple Affairs/
CN:ubuntu804-base.localdomains/O:OCOSAs/OU:Office for Complication of Otherwise Simple Affairs
ed093088706603bfd5dc237399b498da2d4d31c6
```

The remote host is running Linux Kernel 2.6 on Ubuntu 8.04 (gutsy)

117886 - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

tcp/0

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SSH service.
```

181418 - OpenSSH Detection

Synopsis

An OpenSSH-based SSH server was detected on the remote host.

Description

An OpenSSH-based SSH server was detected on the remote host.

See Also

<https://www.openssh.com/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2023/09/14, Modified: 2025/10/21

Plugin Output

tcp/22/ssh

```
Service : ssh
Version : 4.7p1
Banner  : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
```

50845 - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

tcp/25/smtp

50845 - OpenSSL Detection

Synopsis

The remote service appears to use OpenSSL to encrypt traffic.

Description

Based on its response to a TLS request with a specially crafted server name extension, it seems that the remote service is using the OpenSSL library to encrypt traffic.

Note that this plugin can only detect OpenSSL implementations that have enabled support for TLS extensions (RFC 4366).

See Also

<https://www.openssl.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/11/30, Modified: 2020/06/12

Plugin Output

tcp/5432/postgresql

48243 - PHP Version Detection

Synopsis

It was possible to obtain the version number of the remote PHP installation.

Description

Nessus was able to determine the version of PHP available on the remote web server.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0936

Plugin Information

Published: 2010/08/04, Modified: 2025/05/26

Plugin Output

tcp/80/www

Nessus was able to identify the following PHP version information :

Version : 5.2.4-2ubuntu5.10
Source : X-Powered-By: PHP/5.2.4-2ubuntu5.10

66334 - Patch Report

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Plugin Information

Published: 2013/07/08, Modified: 2025/10/14

Plugin Output

tcp/0

```
. You need to take the following 10 actions :
```

```
[ Apache 2.4.x < 2.4.59 Multiple Vulnerabilities (192923) ]
```

```
+ Action to take : Upgrade to Apache version 2.4.59 or later.
```

```
+ Impact : Taking this action will resolve the following 77 different vulnerabilities :
```

```
CVE-2024-27316, CVE-2024-24795, CVE-2023-45802, CVE-2023-43622, CVE-2023-38709
CVE-2023-31122, CVE-2023-27522, CVE-2023-25690, CVE-2022-37436, CVE-2022-36760
CVE-2022-31813, CVE-2022-30556, CVE-2022-30522, CVE-2022-29404, CVE-2022-28615
CVE-2022-28614, CVE-2022-28330, CVE-2022-26377, CVE-2022-23943, CVE-2022-22721
CVE-2022-22720, CVE-2022-22719, CVE-2021-40438, CVE-2021-39275, CVE-2021-34798
CVE-2017-9788, CVE-2017-7679, CVE-2017-7668, CVE-2017-7659, CVE-2017-3169
CVE-2017-3167, CVE-2016-8743, CVE-2016-5387, CVE-2016-4975, CVE-2014-0231
CVE-2014-0226, CVE-2014-0118, CVE-2014-0098, CVE-2013-6438, CVE-2013-5704
CVE-2013-1896, CVE-2013-1862, CVE-2012-4558, CVE-2012-4557, CVE-2012-3499
CVE-2012-2687, CVE-2012-0883, CVE-2012-0053, CVE-2012-0031, CVE-2012-0021
CVE-2011-4317, CVE-2011-3607, CVE-2011-3368, CVE-2011-3348, CVE-2011-0419
CVE-2010-2068, CVE-2010-1623, CVE-2010-1452, CVE-2010-0434, CVE-2010-0425
CVE-2010-0408, CVE-2009-3720, CVE-2009-3560, CVE-2009-3555, CVE-2009-3095
CVE-2009-3094, CVE-2009-2699, CVE-2009-2412, CVE-2009-1956, CVE-2009-1955
CVE-2009-1891, CVE-2009-1890, CVE-2009-1195, CVE-2009-1191, CVE-2009-0023
CVE-2007-6750, CVE-2006-20001
```

```
[ ISC BIND 9.0.0 < 9.16.48 / 9.9.3-S1 < 9.16.48-S1 / 9.18.0 < 9.18.24 / 9.18.11-S1 < 9.18.24-S1 /  
9.19.0 < 9.19.21 Vulnerability (cve-2023-50387) (190444) ]
```

+ Action to take : Upgrade to ISC BIND version 9.16.48 / 9.16.48-S1 / 9.18.24 / 9.18.24-S1 / 9.19.21 or later.

+ Impact : Taking this action will resolve the following 36 different vulnerabilities :
CVE-2023-50387, CVE-2023-3341, CVE-2022-2795, CVE-2021-25219, CVE-2021-25215
CVE-2020-8622, CVE-2020-8617, CVE-2020-8616, CVE-2018-5741, CVE-2017-3141
CVE-2017-3140, CVE-2016-9778, CVE-2016-9444, CVE-2016-9147, CVE-2016-9131
CVE-2016-8864, CVE-2016-2848, CVE-201 [...]]

118224 - PostgreSQL STARTTLS Support

Synopsis

The remote service supports encrypting traffic.

Description

The remote PostgreSQL server supports the use of encryption initiated during pre-login to switch from a cleartext to an encrypted communications channel.

See Also

<https://www.postgresql.org/docs/9.2/protocol-flow.html#AEN96066>

<https://www.postgresql.org/docs/9.2/protocol-message-formats.html>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/10/19, Modified: 2022/04/11

Plugin Output

tcp/5432/postgresql

```
Here is the PostgreSQL's SSL certificate that Nessus
was able to collect after sending a pre-login packet :
```

```
----- snip -----
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
```

```
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
             7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
             73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
             D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
             8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
             98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
             00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
           0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
           1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
           68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
           83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
           A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
           15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]
```

26024 - PostgreSQL Server Detection

Synopsis

A database service is listening on the remote host.

Description

The remote service is a PostgreSQL database server, or a derivative such as EnterpriseDB.

See Also

<https://www.postgresql.org/>

Solution

Limit incoming traffic to this port if desired.

Risk Factor

None

Plugin Information

Published: 2007/09/14, Modified: 2025/09/24

Plugin Output

tcp/5432/postgresql

```
Service : postgresql  
Version : unknown
```

110976 - PostgreSQL Unauthenticated Version Detection

Synopsis

It was possible to gather database version information from an error message.

Description

It was possible to guess the remote PostgreSQL database version from a unique error message.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/07/10, Modified: 2025/09/29

Plugin Output

tcp/5432/postgresql

```
Source  : Fauth.c.L1003.Rauth_failed
Version : 8.3.8
```


22227 - RMI Registry Detection

Synopsis

An RMI registry is listening on the remote host.

Description

The remote host is running an RMI registry, which acts as a bootstrap naming service for registering and retrieving remote objects with simple names in the Java Remote Method Invocation (RMI) system.

See Also

<https://docs.oracle.com/javase/1.5.0/docs/guide/rmi/spec/rmiTOC.html>

<http://www.nessus.org/u?b6fd7659>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/08/16, Modified: 2025/03/19

Plugin Output

tcp/1099/rmi_registry
tcp/1099/rmi_registry

```
Valid response received for port 1099:
0x00:  51 AC ED 00 05 77 0F 01 87 3C CF 07 00 00 01 9A    Q....w...<.....
0x10:  0C 5C 41 84 80 00 75 72 00 13 5B 4C 6A 61 76 61    .\A...ur..[Ljava
0x20:  2E 6C 61 6E 67 2E 53 74 72 69 6E 67 3B AD D2 56    .lang.String;..V
0x30:  E7 E9 1D 7B 47 02 00 00 70 78 70 00 00 00 00    ...{G...xp....
```

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/111/rpc-portmapper

```
The following RPC services are available on TCP port 111 :  
- program: 100000 (portmapper), version: 2
```

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/111/rpc-portmapper

```
The following RPC services are available on UDP port 111 :  
- program: 100000 (portmapper), version: 2
```

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/2049/rpc-nfs

```
The following RPC services are available on TCP port 2049 :
```

- program: 100003 (nfs), version: 2
- program: 100003 (nfs), version: 3
- program: 100003 (nfs), version: 4

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/2049/rpc-nfs

```
The following RPC services are available on UDP port 2049 :
```

- program: 100003 (nfs), version: 2
- program: 100003 (nfs), version: 3
- program: 100003 (nfs), version: 4

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/37849/rpc-status

```
The following RPC services are available on TCP port 37849 :  
- program: 100024 (status), version: 1
```

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/38952/rpc-mountd

```
The following RPC services are available on TCP port 38952 :
```

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/43251/rpc-nlockmgr

```
The following RPC services are available on UDP port 43251 :
```

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3
- program: 100021 (nlockmgr), version: 4

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

tcp/43669/rpc-nlockmgr

```
The following RPC services are available on TCP port 43669 :
```

- program: 100021 (nlockmgr), version: 1
- program: 100021 (nlockmgr), version: 3
- program: 100021 (nlockmgr), version: 4

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/45188/rpc-mountd

```
The following RPC services are available on UDP port 45188 :
```

- program: 100005 (mountd), version: 1
- program: 100005 (mountd), version: 2
- program: 100005 (mountd), version: 3

11111 - RPC Services Enumeration

Synopsis

An ONC RPC service is running on the remote host.

Description

By sending a DUMP request to the portmapper, it was possible to enumerate the ONC RPC services running on the remote port. Using this information, it is possible to connect and bind to each service by sending an RPC request to the remote port.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/08/24, Modified: 2011/05/24

Plugin Output

udp/53037/rpc-status

```
The following RPC services are available on UDP port 53037 :  
- program: 100024 (status), version: 1
```

53335 - RPC portmapper (TCP)

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/04/08, Modified: 2011/08/29

Plugin Output

tcp/111/rpc-portmapper

10223 - RPC portmapper Service Detection

Synopsis

An ONC RPC portmapper is running on the remote host.

Description

The RPC portmapper is running on this port.

The portmapper allows someone to get the port number of each RPC service running on the remote host by sending either multiple lookup requests or a DUMP request.

Solution

n/a

Risk Factor

None

CVSS v3.0 Base Score

0.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N)

CVSS v2.0 Base Score

0.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:N/A:N)

References

CVE CVE-1999-0632

Plugin Information

Published: 1999/08/19, Modified: 2019/10/04

Plugin Output

udp/111/rpc-portmapper

10263 - SMTP Server Detection

Synopsis

An SMTP server is listening on the remote port.

Description

The remote host is running a mail (SMTP) server on this port.

Since SMTP servers are the targets of spammers, it is recommended you disable it if you do not use it.

Solution

Disable this service if you do not use it, or filter incoming traffic to this port.

Risk Factor

None

References

XREF IAVT:0001-T-0932

Plugin Information

Published: 1999/10/12, Modified: 2020/09/22

Plugin Output

tcp/25/smtp

```
Remote SMTP server banner :  
220 metasploitable.localdomain ESMTP Postfix (Ubuntu)
```

42088 - SMTP Service STARTTLS Command Support

Synopsis

The remote mail service supports encrypting traffic.

Description

The remote SMTP service supports the use of the 'STARTTLS' command to switch from a cleartext to an encrypted communications channel.

See Also

<https://en.wikipedia.org/wiki/STARTTLS>

<https://tools.ietf.org/html/rfc2487>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/10/09, Modified: 2019/03/20

Plugin Output

tcp/25/smtp

```
Here is the SMTP service's SSL certificate that Nessus was able to
collect after sending a 'STARTTLS' command :
```

```
----- snip -----
```

```
Subject Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain
```

```
Issuer Name:
```

```
Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
```

```
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
             7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
             73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
             D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
             8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
             98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
             00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
           0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
           1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
           68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
           83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
           A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
           15 6E 8D 30 38 F6 CA 2E 75

----- snip ----- [...]
```


70657 - SSH Algorithms and Languages Supported

Synopsis

An SSH server is listening on this port.

Description

This script detects which algorithms and languages are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/28, Modified: 2025/01/20

Plugin Output

tcp/22/ssh

```
Nessus negotiated the following encryption algorithm(s) with the server :
```

```
Client to Server: aes256-ctr
Server to Client: aes256-ctr
```

```
The server supports the following options for compression_algorithms_server_to_client :
```

```
none
zlib@openssh.com
```

```
The server supports the following options for mac_algorithms_client_to_server :
```

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

```
The server supports the following options for server_host_key_algorithms :
```

```
ssh-dss
ssh-rsa
```

```
The server supports the following options for encryption_algorithms_client_to_server :
```

```
3des-cbc
aes128-cbc
```

```
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

The server supports the following options for `mac_algorithms_server_to_client` :

```
hmac-md5
hmac-md5-96
hmac-ripemd160
hmac-ripemd160@openssh.com
hmac-sha1
hmac-sha1-96
umac-64@openssh.com
```

The server supports the following options for `kex_algorithms` :

```
diffie-hellman-group-exchange-sha1
diffie-hellman-group-exchange-sha256
diffie-hellman-group1-sha1
diffie-hellman-group14-sha1
```

The server supports the following options for `compression_algorithms_client_to_server` :

```
none
zlib@openssh.com
```

The server supports the following options for `encryption_algorithms_server_to_client` :

```
3des-cbc
aes128-cbc
aes128-ctr
aes192-cbc
aes192-ctr
aes256-cbc
aes256-ctr
arcfour
arcfour128
arcfour256
blowfish-cbc
cast128-cbc
rijndael-cbc@lysator.liu.se
```

149334 - SSH Password Authentication Accepted

Synopsis

The SSH server on the remote host accepts password authentication.

Description

The SSH server on the remote host accepts password authentication.

See Also

<https://tools.ietf.org/html/rfc4252#section-8>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/05/07, Modified: 2021/05/07

Plugin Output

tcp/22/ssh

10881 - SSH Protocol Versions Supported

Synopsis

A SSH server is running on the remote host.

Description

This plugin determines the versions of the SSH protocol supported by the remote SSH daemon.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/03/06, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
The remote SSH daemon supports the following versions of the
SSH protocol :
```

- 1.99
- 2.0

153588 - SSH SHA-1 HMAC Algorithms Enabled

Synopsis

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Description

The remote SSH server is configured to enable SHA-1 HMAC algorithms.

Although NIST has formally deprecated use of SHA-1 for digital signatures, SHA-1 is still considered secure for HMAC as the security of HMAC does not rely on the underlying hash function being resistant to collisions.

Note that this plugin only checks for the options of the remote SSH server.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2021/09/23, Modified: 2022/04/05

Plugin Output

tcp/22/ssh

```
The following client-to-server SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
hmac-sha1
hmac-sha1-96
```

```
The following server-to-client SHA-1 Hash-based Message Authentication Code (HMAC) algorithms are supported :
```

```
hmac-sha1
hmac-sha1-96
```

10267 - SSH Server Type and Version Information

Synopsis

An SSH server is listening on this port.

Description

It is possible to obtain information about the remote SSH server by sending an empty authentication request.

Solution

n/a

Risk Factor

None

References

XREF IAVT:0001-T-0933

Plugin Information

Published: 1999/10/12, Modified: 2024/07/24

Plugin Output

tcp/22/ssh

```
SSH version : SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1
SSH supported authentication : publickey,password
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/25/smtp

```
This port supports SSLv2/SSLv3/TLSv1.0.
```

56984 - SSL / TLS Versions Supported

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/01, Modified: 2025/06/16

Plugin Output

tcp/5432/postgresql

```
This port supports SSLv3/TLSv1.0.
```


45410 - SSL Certificate 'commonName' Mismatch

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

Plugin Output

tcp/25/smtp

```
The host name known by Nessus is :
```

```
metasploitable
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

45410 - SSL Certificate 'commonName' Mismatch

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Plugin Information

Published: 2010/04/03, Modified: 2021/03/09

Plugin Output

tcp/5432/postgresql

```
The host name known by Nessus is :
```

```
metasploitable
```

```
The Common Name in the certificate is :
```

```
ubuntu804-base.localdomain
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

```
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
```

```
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
            0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
            1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
            68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
            83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
            A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
            15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
                    83 0C 7A F1 E3 2D EE 43 6D E8 13 CC
SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]
```

10863 - SSL Certificate Information

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2008/05/19, Modified: 2021/02/03

Plugin Output

tcp/5432/postgresql

```
Subject Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Issuer Name:

Country: XX
State/Province: There is no such thing outside US
Locality: Everywhere
Organization: OCOSA
Organization Unit: Office for Complication of Otherwise Simple Affairs
Common Name: ubuntu804-base.localdomain
Email Address: root@ubuntu804-base.localdomain

Serial Number: 00 FA F9 3A 4C 7F B6 B9 CC

Version: 1

Signature Algorithm: SHA-1 With RSA Encryption

Not Valid Before: Mar 17 14:07:45 2010 GMT
Not Valid After: Apr 16 14:07:45 2010 GMT

Public Key Info:

Algorithm: RSA Encryption
```

```
Key Length: 1024 bits
Public Key: 00 D6 B4 13 36 33 9A 95 71 7B 1B DE 7C 83 75 DA 71 B1 3C A9
            7F FE AD 64 1B 77 E9 4F AE BE CA D4 F8 CB EF AE BB 43 79 24
            73 FF 3C E5 9E 3B 6D FC C8 B1 AC FA 4C 4D 5E 9B 4C 99 54 0B
            D7 A8 4A 50 BA A9 DE 1D 1F F4 E4 6B 02 A3 F4 6B 45 CD 4C AF
            8D 89 62 33 8F 65 BB 36 61 9F C4 2C 73 C1 4E 2E A0 A8 14 4E
            98 70 46 61 BB D1 B9 31 DF 8C 99 EE 75 6B 79 3C 40 A0 AE 97
            00 90 9D DC 99 0D 33 A4 B5
Exponent: 01 00 01

Signature Length: 128 bytes / 1024 bits
Signature: 00 92 A4 B4 B8 14 55 63 25 51 4A 0B C3 2A 22 CF 3A F8 17 6A
            0C CF 66 AA A7 65 2F 48 6D CD E3 3E 5C 9F 77 6C D4 44 54 1F
            1E 84 4F 8E D4 8D DD AC 2D 88 09 21 A8 DA 56 2C A9 05 3C 49
            68 35 19 75 0C DA 53 23 88 88 19 2D 74 26 C1 22 65 EE 11 68
            83 6A 53 4A 9C 27 CB A0 B4 E9 8D 29 0C B2 3C 18 5C 67 CC 53
            A6 1E 30 D0 AA 26 7B 1E AE 40 B9 29 01 6C 2E BC A2 19 94 7C
            15 6E 8D 30 38 F6 CA 2E 75

Fingerprints :

SHA-256 Fingerprint: E7 A7 FA 0D 63 E4 57 C7 C4 A5 9B 38 B7 08 49 C6 A7 0B DA 6F
                    83 0C 7A F1 E3 2D EE 43 6D E8 13 CC
SHA-1 Fingerprint: ED 09 30 88 70 66 03 BF D5 DC 23 73 99 B4 98 DA 2D [...]
```

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/25/smtp

Here is the list of SSL CBC ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
export					
EXP-EDH-RSA-DES-CBC-SHA	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
SHA1 export					
EDH-RSA-DES-CBC-SHA	0x00, 0x15	DH	RSA	DES-CBC(56)	
SHA1					
EXP-ADH-DES-CBC-SHA	0x00, 0x19	DH(512)	None	DES-CBC(40)	
SHA1 export					
ADH-DES-CBC-SHA	0x00, 0x1A	DH	None	DES-CBC(56)	
SHA1					

EXP-DES-CBC-SHA SHA1	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC (56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name -----	Code -----	KEX ---	Auth ----	Encryption -----	MAC ---
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC (168)	MD5
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name -----	Code -----	KEX	Auth	Encryption	MAC
	[...]				

70544 - SSL Cipher Block Chaining Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/10/22, Modified: 2021/02/03

Plugin Output

tcp/5432/postgresql

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DH	RSA	AES-CBC (128)	
SHA1					

DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC(256)
SHA1				
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)
SHA1				
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)
SHA1				

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

tcp/25/smtp

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv1

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH (512)	RSA	DES-CBC (40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC (56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH (512)	None	DES-CBC (40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH (512)	None	RC4 (40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC (56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA (512)	RSA	DES-CBC (40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA (512)	RSA	RC2-CBC (40)	MD5

EXP-RC4-MD5 export	0x00, 0x03	RSA (512)	RSA	RC4 (40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC (56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC (168)	
ADH-DES-CBC3-SHA SHA1	0x00, 0x1B	DH	None	3DES-CBC (168)	
DES-CBC3-SHA SHA1	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	[...]
------	------	-----	------	-------

21643 - SSL Cipher Suites Supported

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>

<http://www.nessus.org/u?e17ffced>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2006/06/05, Modified: 2024/09/11

Plugin Output

tcp/5432/postgresql

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv1

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC (168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC (168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	---	-----	---
DHE-RSA-AES128-SHA	0x00, 0x33	DH	RSA	AES-CBC (128)	
SHA1					
DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC (256)	
SHA1					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC (128)	
SHA1					

AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)
SHA1				
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)
SHA1				

SSL Version : SSLv3

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	[...]		

62563 - SSL Compression Methods Supported

Synopsis

The remote service supports one or more compression methods for SSL connections.

Description

This script detects which compression methods are supported by the remote service for SSL connections.

See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

Plugin Output

tcp/25/smtp

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```

62563 - SSL Compression Methods Supported

Synopsis

The remote service supports one or more compression methods for SSL connections.

Description

This script detects which compression methods are supported by the remote service for SSL connections.

See Also

<http://www.iana.org/assignments/comp-meth-ids/comp-meth-ids.xml>

<https://tools.ietf.org/html/rfc3749>

<https://tools.ietf.org/html/rfc3943>

<https://tools.ietf.org/html/rfc5246>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2012/10/16, Modified: 2022/04/11

Plugin Output

tcp/5432/postgresql

```
Nessus was able to confirm that the following compression method is
supported by the target :
```

```
DEFLATE (0x01)
```


57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/25/smtp

Here is the list of SSL PFS ciphers supported by the remote server :

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC(168)	

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DHE-RSA-AES128-SHA SHA1	0x00, 0x33	DH	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA SHA1	0x00, 0x39	DH	RSA	AES-CBC(256)	

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/12/07, Modified: 2021/03/09

Plugin Output

tcp/5432/postgresql

Here is the list of SSL PFS ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	

SHA1

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
DHE-RSA-AES128-SHA	0x00, 0x33	DH	RSA	AES-CBC(128)	
DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC(256)	

SHA1

The fields above are :

```
{Tenable ciphername}  
{Cipher ID code}  
Kex={key exchange}  
Auth={authentication}  
Encrypt={symmetric encryption method}  
MAC={message authentication code}  
{export flag}
```

51891 - SSL Session Resume Supported

Synopsis

The remote host allows resuming SSL sessions.

Description

This script detects whether a host allows resuming SSL sessions by performing a full SSL handshake to receive a session ID, and then reconnecting with the previously used session ID. If the server accepts the session ID in the second connection, the server maintains a cache of sessions that can be resumed.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/02/07, Modified: 2021/09/13

Plugin Output

tcp/25/smtp

```
This port supports resuming SSLv3 sessions.
```

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/25/smtp

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Low Strength Ciphers (<= 64-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
EXP-RC2-CBC-MD5 export	0x04, 0x00, 0x80	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x02, 0x00, 0x80	RSA(512)	RSA	RC4(40)	MD5
EXP-EDH-RSA-DES-CBC-SHA SHA1 export	0x00, 0x14	DH(512)	RSA	DES-CBC(40)	
EDH-RSA-DES-CBC-SHA SHA1	0x00, 0x15	DH	RSA	DES-CBC(56)	
EXP-ADH-DES-CBC-SHA SHA1 export	0x00, 0x19	DH(512)	None	DES-CBC(40)	
EXP-ADH-RC4-MD5 export	0x00, 0x17	DH(512)	None	RC4(40)	MD5
ADH-DES-CBC-SHA SHA1	0x00, 0x1A	DH	None	DES-CBC(56)	
EXP-DES-CBC-SHA SHA1 export	0x00, 0x08	RSA(512)	RSA	DES-CBC(40)	
EXP-RC2-CBC-MD5 export	0x00, 0x06	RSA(512)	RSA	RC2-CBC(40)	MD5
EXP-RC4-MD5 export	0x00, 0x03	RSA(512)	RSA	RC4(40)	MD5
DES-CBC-SHA SHA1	0x00, 0x09	RSA	RSA	DES-CBC(56)	

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	---	----	-----	---
DES-CBC3-MD5	0x07, 0x00, 0xC0	RSA	RSA	3DES-CBC(168)	MD5
EDH-RSA-DES-CBC3-SHA SHA1	0x00, 0x16	DH	RSA	3DES-CBC(168)	
ADH-DE [...]					

156899 - SSL/TLS Recommended Cipher Suites

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Plugin Information

Published: 2022/01/20, Modified: 2024/02/12

Plugin Output

tcp/5432/postgresql

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	----	----	-----	----
EDH-RSA-DES-CBC3-SHA	0x00, 0x16	DH	RSA	3DES-CBC(168)	
SHA1					
DES-CBC3-SHA	0x00, 0x0A	RSA	RSA	3DES-CBC(168)	
SHA1					

High Strength Ciphers (>= 112-bit key)

Name	Code	KEX	Auth	Encryption	MAC
-----	-----	----	----	-----	----
DHE-RSA-AES128-SHA	0x00, 0x33	DH	RSA	AES-CBC(128)	
SHA1					
DHE-RSA-AES256-SHA	0x00, 0x39	DH	RSA	AES-CBC(256)	
SHA1					
AES128-SHA	0x00, 0x2F	RSA	RSA	AES-CBC(128)	
SHA1					
AES256-SHA	0x00, 0x35	RSA	RSA	AES-CBC(256)	
SHA1					
RC4-SHA	0x00, 0x05	RSA	RSA	RC4(128)	
SHA1					

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

25240 - Samba Server Detection

Synopsis

An SMB server is running on the remote host.

Description

The remote host is running Samba, a CIFS/SMB server for Linux and Unix.

See Also

<https://www.samba.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2022/10/12

Plugin Output

tcp/445/cifs

104887 - Samba Version

Synopsis

It was possible to obtain the samba version from the remote operating system.

Description

Nessus was able to obtain the samba version from the remote operating by sending an authentication request to port 139 or 445. Note that this plugin requires SMB1 to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/11/30, Modified: 2019/11/22

Plugin Output

tcp/445/cifs

```
The remote Samba Version is : Samba 3.0.20-Debian
```

96982 - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

tcp/445/cifs

```
The remote host supports SMBv1.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/21/ftp

```
An FTP server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/22/ssh

```
An SSH server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/23/telnet

```
A telnet server is running on this port.
```

22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/25/smtp

```
An SMTP server is running on this port.
```


22964 - Service Detection

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/08/19, Modified: 2024/03/26

Plugin Output

tcp/80/www

```
A web server is running on this port.
```

25220 - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

tcp/0

11819 - TFTP Daemon Detection

Synopsis

A TFTP server is listening on the remote port.

Description

The remote host is running a TFTP (Trivial File Transfer Protocol) daemon. TFTP is often used by routers and diskless hosts to retrieve their configuration. It can also be used by worms to propagate.

Solution

Disable this service if you do not use it.

Risk Factor

None

Plugin Information

Published: 2003/08/13, Modified: 2022/12/28

Plugin Output

udp/69/tftp

110723 - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

tcp/0

```
SSH was detected on port 22 but no credentials were provided.  
SSH local checks were not enabled.
```


10287 - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2023/12/04

Plugin Output

udp/0

```
For your information, here is the traceroute from 192.168.50.10 to 192.168.50.3 :  
192.168.50.10  
192.168.50.3
```

```
Hop Count: 1
```

19288 - VNC Server Security Type Detection

Synopsis

A VNC server is running on the remote host.

Description

This script checks the remote VNC server protocol version and the available 'security types'.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/07/22, Modified: 2021/07/13

Plugin Output

tcp/5900/vnc

```
\n\nThe remote VNC server chose security type #2 (VNC authentication)
```


65792 - VNC Server Unencrypted Communication Detection

Synopsis

A VNC server with one or more unencrypted 'security-types' is running on the remote host.

Description

This script checks the remote VNC server protocol version and the available 'security types' to determine if any unencrypted 'security-types' are in use or available.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2013/04/03, Modified: 2014/03/12

Plugin Output

tcp/5900/vnc

```
The remote VNC server supports the following security type
which does not perform full data communication encryption :
```

```
  2 (VNC authentication)
```

11424 - WebDAV Detection

Synopsis

The remote server is running with WebDAV enabled.

Description

WebDAV is an industry standard extension to the HTTP specification.

It adds a capability for authorized users to remotely add and manage the content of a web server.

If you do not use this extension, you should disable it.

Solution

<http://support.microsoft.com/default.aspx?kbid=241520>

Risk Factor

None

Plugin Information

Published: 2003/03/20, Modified: 2011/03/14

Plugin Output

tcp/80/www

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

udp/137/netbios-ns

```
The following 7 NetBIOS names have been gathered :
```

```
METASPLOITABLE = Computer name
METASPLOITABLE = Messenger Service
METASPLOITABLE = File Server Service
__MSBROWSE__    = Master Browser
WORKGROUP       = Workgroup / Domain name
WORKGROUP       = Master Browser
WORKGROUP       = Browser Service Elections
```

```
This SMB server seems to be a Samba server - its MAC address is NULL.
```

52703 - vsftpd Detection

Synopsis

An FTP server is listening on the remote port.

Description

The remote host is running vsftpd, an FTP server for UNIX-like systems written in C.

See Also

<http://vsftpd.beasts.org/>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/03/17, Modified: 2019/11/22

Plugin Output

tcp/21/ftp

```
Source  : 220 (vsFTPd 2.3.4)
Version : 2.3.4
```