

8AL Aluminium Cylinders

Product Offering

Calgaz has two types of 8AL cylinders designed to meet your needs. The 8ALE and 8ALU are both approved for global use and vary only slightly in terms of appearance and weight.

All cylinders have the universal C10 valve as standard and can be filled with both non-reactive and reactive gases.

Characteristic							
	Contents	Pressure	Dimensions	Weight			
8ALE	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	1.2 kg (2.65lb)			
8ALU	58 litres	35 bar (500 psi)	362 mm x 89 mm (14 1/4" x 3 1/2")	0.73 kg (1.6 lb)			



*8ALU Picture

Specifications						
	Approvals	Туре	Cylinder Valve	Recommended Equipment		
8ALE	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.		
8ALU	Global	Non-Refillable	C10			



Contact Details

Americas

Global Headquarters Houston, TX, USA +1 713 624 8000

Customer Service and Manufacturing Facility Cambridge, MD, USA +1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Customer Service and **Manufacturing Facility** Stoke-on-Trent, United Kingdom +44 0808 164 8897

Middle East Sales Dubai, UAE +971 56 131 2346

South East Asia & Australia

Distribution Singapore +65 3129 2321

China

Customer Service and Distribution Shanghai +86 21 6090 3711

info@calgaz.com

www.calgaz.com