

6D/6DM Steel Cylinders

Product offering

The 6D and 6DM are globally approved steel cylinders. These cylinders are ideally suited for non reactive gas use. In addition steel cylinders are often specified for use in Mines and other explosive atmospheres (please check regulations). The 6D cylinder holds 103 litres nominal gas capacity and the 6DM being more compact 58 litres of gas. The small lightweight cylinders are easy to carry around. Both cylinders are fitted with a C10 valve.



6D



6DM

Characteristic				
	Contents	Service Pressure	Dimensions	Weight
6D	103 liters	69 bar (1000 psig)	345mm x 83mm (13 1/2" x 3 1/4")	1.4 kg (3 lb)
6DM	58 liters	69 bar (1000 psig)	83mm x 204mm (3.259" x 8.093")	0.9 kg (1.90 lb)

Specifications				
	Approvals	Type	Cylinder Valve	Recommended Equipment
6D	Global	Non-Refillable	C10	Most commonly used regulators include 700 Series, DFR 2000 Series, or 4200 Trigger regulators.
6DM	Global	Non-Refillable	C10	



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United
Kingdom
+44 0808 164 8897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 3129 2321

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com