

Project File Guide

remitbee-playwright — what every folder and file is for, in the order you see them in VS Code · updated 05 Oct 2026 (Jenkins)

How the pieces fit: you start a run with **run.sh** (or an npm script in **package.json**) → Playwright reads **playwright.flow.config.ts** → runs the test cases in **tests/flows** → each test calls the helpers in **flows/** to click through the CP → using accounts and data from **config/environments.ts** and **.env** → results land in **test-results/**, **playwright-report/** and **reports/**. On Jenkins the same run is started by the **Jenkinsfile** through **ci/jenkins-run.sh**.

Reading the VS Code sidebar

Mark	Meaning
M (yellow)	Modified: the file changed since the last git commit. Commit and push so Jenkins gets the change.
U (green)	Untracked: a new file git has not saved yet.
No letter	Saved in git and unchanged. Everything in the screenshot of 05 Oct is committed and pushed (commit "New Fix with Jenkins").
Green dot on a folder	node_modules: installed libraries (ignored by git).
Grey name	Ignored by git on purpose: generated or private (node_modules, playwright-report, test-results, .env).

"Edit it?" column: **Yes** = normal daily work · **Sometimes** = when settings or data change · **Rarely** = only for setup changes · **Never** = generated automatically, do not edit by hand.

0. ci/ — what Jenkins runs

Added 05 Oct 2026 for the Jenkins pipeline. Can also be run on the Mac to do exactly what Jenkins does.

File / folder	What it is for	Edit it?
ci/jenkins-run.sh	Runs the suite the Jenkins way. Settings come from environment variables: SUITE (smoke, regression, all, module, test), MODULE, TEST_ID, WORKERS and SPLIT_SHARED_ACCOUNTS. With the split on, Send Money (SM-) and Auth (PA-) run with one browser after the rest, because they share test accounts. Each pass writes its own report (playwright-report/main, /shared) and JUnit file. Try: SUITE=smoke DRY_RUN=1 bash ci/jenkins-run.sh (prints the commands only).	Rarely

1. config/ — test settings and test data

One place for every URL, account and value the tests use, so nothing is hard-coded inside tests.

File / folder	What it is for	Edit it?
config/environments.ts	Exports ENV : staging URL (cp.wisecapitals.com), API URL, all test account emails (personal, business, blocked, restricted, deleted, wallet, rates, rewards, transactions, DT One...), the common password, OTP 121212, amounts, promo codes and DT One countries. Every value can be overridden from .env .	Sometimes

2. flows/ — the “how to do it” helpers (Flow objects)

Each CP module has one helper class that knows its screens: element locators and steps such as “open escalation”, “attach file” or “select country”. Tests call these steps. When the CP UI changes, the fix goes here once instead of in every test.

File / folder	What it is for	Edit it?
flows/FlowBase.ts	Parent of every helper. Login with password + OTP (with retries for staging hiccups), dismiss cookie banner and pop-ups, open sidebar menus, check that an API request fired.	Sometimes
account/AccountFlow.ts	Account details page, edit dialogs, business/personal tabs, switching accounts from the user menu.	Yes
auth/LoginFlow.ts	Login screen, 2-step OTP, invalid logins, forgot / reset password.	Yes
currency-converter/CurrencyConverterFlow.ts	Public currency converter page: amounts, currency pickers, “Send money” link.	Yes
dashboard/DashboardFlow.ts	Dashboard widgets, balances, shortcuts.	Yes
dtone/DtoneFlow.ts	DT One services: mobile top-up, eSIM, gift cards, bill payment, payment-type step (stops before paying).	Yes
escalation/EscalationFlow.ts	Resolution centre: create escalation, pick issue/problem, message, attach file, search, close.	Yes
exchange/ExchangeFlow.ts	Currency exchange between wallets.	Yes
help/HelpFlow.ts	Help centre categories, search, articles, contact us.	Yes
rates/RatesFlow.ts	Exchange rates and rate alerts.	Yes
recipients/RecipientsFlow.ts	Add / edit / search recipients and bank details.	Yes
referral/ReferralFlow.ts	Referral page and invite link.	Yes
rewards/RewardsFlow.ts	Rewards page and promo codes.	Yes
schedule/ScheduleFlow.ts	Scheduled transfers wizard and list.	Yes
send-money/SendMoneyFlow.ts	Send money flow: amount, recipient, purpose, payment method, review.	Yes
settings/SettingsFlow.ts	Settings tabs, 2-step activation, notifications, preferred bank.	Yes
signup/SignupFlow.ts	Sign-up form and validation.	Yes
transactions/TransactionsFlow.ts	Transaction list, filters and details.	Yes
verification/VerificationFlow.ts	KYC levels: fresh sign-up, personal info, Persona sandbox upload.	Yes

File / folder	What it is for	Edit it?
wallet/WalletFlow.ts	CAD and multi-currency wallets, add funds, withdraw.	Yes

2a. flows/voice/ — Jev AI voice commands used inside tests

Used only by test file 19-voice. Turns a spoken-style sentence into a browser action. Needs TYPESAFE_API_KEY in .env.

File / folder	What it is for	Edit it?
VoiceHelper.ts	Main entry: takes a command ("open send money"), reads the page, asks Jev, performs the action.	Rarely
voiceFixture.ts	Adds a ready-made voice object to the voice tests.	Rarely
jev-src/constants.mjs	The questions sent to Jev and the confidence thresholds.	Rarely
jev-src/jev.mjs	Makes the call to the Jev (TypeSafe) API.	Rarely
jev-src/snapshot.mjs	Lists the clickable elements on the page for Jev.	Rarely
jev-src/spans.mjs	Pulls the text to type (search words, URLs) out of a command.	Rarely
jev-src/policy.mjs	Decides from Jev's answers: act, wait, ask to confirm, or ignore.	Rarely
jev-src/executor.mjs	Carries out the chosen action in the browser.	Rarely
PageBrowserAdapter.mjs	Left over from the original standalone voice browser; not used by the tests.	Never

2b. junit-results/ — results file for Jenkins

File / folder	What it is for	Edit it?
junit-results/*.xml	Pass/fail of every test in JUnit format. Created only when CI=true (Jenkins, or ci/jenkins-run.sh). Jenkins reads it for the test-result trend graph. Generated, and ignored by git.	Never

3. node_modules/ — installed libraries

File / folder	What it is for	Edit it?
node_modules/	Playwright, TypeScript, dotenv, the Jev SDK and their dependencies. Created by npm install ; ignored by git. If it gets corrupted, delete it and run npm install again.	Never

4. playwright/ — saved login sessions (optional)

File / folder	What it is for	Edit it?
playwright/auth.setup.ts	One-time login with "Remember this device" that saves cookies so OTP can be skipped. Run: npx playwright test --config=playwright.flow.config.ts --project=setup.	Rarely
playwright/.auth/personal.json business.json, restricted.json	The saved login cookies for each account type. Private. Now listed in .gitignore; remove them from git once with git rm -r --cached playwright/.auth. The test runs do not use them.	Never

5. playwright-report/ — HTML report

File / folder	What it is for	Edit it?
playwright-report/	The interactive HTML report of the last run: every test, pass/fail, and for failures the screenshot, video and step trace. Open with ./run.sh report . Replaced on every run.	Never

6. reports/ — shareable PDFs

File / folder	What it is for	Edit it?
Remitbee-CP-Playwright-Flow-Report-2026-10-01.pdf	Full run of 01 Oct (1 browser): 372 tests, 356 passed, 0 failed, 16 skipped.	Never
Remitbee-CP-Regression-Report-2026-10-05-1600.pdf	Regression of 05 Oct, 16:00 (6 browsers): 322 passed, 6 failed, 7 skipped.	Never
Remitbee-CP-Regression-Report-2026-10-05-1642.pdf	Regression of 05 Oct, 16:42 (10 browsers): 317 passed, 8 failed, 10 skipped.	Never
Jenkins-Readiness-Remitbee-Playwright.xlsx	Checklist of what is needed before Jenkins can run the suite, with owner and status.	Sometimes
Other PDFs	Earlier guides (framework guide, management overview, this file guide) are sent in chat; save them here if you want them in the project.	Never

7. test-data/ — files the tests upload

File / folder	What it is for	Edit it?
verification/sample-id-doc.pdf	Dummy ID document — Persona KYC upload (VF tests) and escalation attachment (ES-11).	Rarely
verification/sample-id.png	Dummy ID photo used by the verification flow.	Rarely
verification/sample-address-proof.png	Dummy proof-of-address image for verification uploads.	Rarely

8. test-results/ — evidence of failures

File / folder	What it is for	Edit it?
test-results/<test name>/	One folder per failed test: error-context.md (the error + a snapshot of the page at failure), screenshot, video and trace.zip (open with <code>npx playwright show-trace</code>). This is what we use to diagnose and fix failures. Cleared at the start of every run. With <code>ci/jenkins-run.sh</code> there is one sub-folder per pass (main, shared).	Never

9. tests/flows/ — the test cases (“what to check”)

One file per CP module. Every test has an ID (e.g. AC-07) and tags: **@smoke** (quick core set) and **@regression** (full set). Run one file with `./run.sh <module>`, one test with `./run.sh AC-07`.

File / folder	What it is for	Edit it?
00-signup.flow.spec.ts	Sign-up — 30 tests (SU-)	Yes
01-auth.flow.spec.ts	Login, 2-step, forgot password — 31 tests (PA-)	Yes

File / folder	What it is for	Edit it?
02-dashboard.flow.spec.ts	Dashboard — 13 tests (DB-)	Yes
03-send-money.flow.spec.ts	Send money — 20 tests (SM-)	Yes
04-exchange.flow.spec.ts	Currency exchange — 20 tests (CE-)	Yes
05-wallet.flow.spec.ts	Wallets — 14 tests (CADB-)	Yes
06-recipients.flow.spec.ts	Recipients — 24 tests (RC-)	Yes
07-settings.flow.spec.ts	Settings — 15 tests (ST-)	Yes
08-transactions.flow.spec.ts	Transactions — 18 tests (TX-)	Yes
09-rates.flow.spec.ts	Rates and alerts — 18 tests (RC-)	Yes
10-rewards.flow.spec.ts	Rewards and promo codes — 15 tests (RW-)	Yes
11-schedule.flow.spec.ts	Scheduled transfers — 30 tests (SC-)	Yes
12-verification.flow.spec.ts	KYC verification — 17 tests (VF-)	Yes
13-account.flow.spec.ts	Account details and switching — 20 tests (AC-)	Yes
14-escalation.flow.spec.ts	Resolution centre — 20 tests (ES-)	Yes
15-dtone.flow.spec.ts	DT One top-up / eSIM / gift card / bills — 20 tests (DT-)	Yes
16-referral.flow.spec.ts	Referral — 10 tests (RV-)	Yes
17-help.flow.spec.ts	Help centre: 16 tests (HP-). Switched off (not configured on staging); see playwright.flow.config.ts.	Rarely
18-currency-converter.flow.spec.ts	Public currency converter: 16 tests (CC-). Switched off (not configured on staging).	Rarely
19-voice.flow.spec.ts	Voice-driven tests with Jev — 5 tests (tag @voice)	Rarely

10. utils/ — small shared tools

File / folder	What it is for	Edit it?
utils/api-utils.ts	Calls the backend API directly to trigger a password-reset email (used by the forgot-password tests).	Rarely

11. voice-control/ — run the suite by voice

Start with `./run.sh control` and open `http://localhost:4000` in Chrome.

File / folder	What it is for	Edit it?
server.mjs	Local server: starts/stops run.sh, one run at a time, streams progress, counts pass/fail.	Rarely
commands.mjs	Understands what you said (“run AC 07 headless”) and maps it to an allowed run.sh command. Uses Jev for unclear sentences.	Rarely
index.html	The panel: mic button, what it heard, yes/no confirmation, progress, failures, spoken summary.	Rarely

12. Files in the project root

File / folder	What it is for	Edit it?
.env	Your private settings: passwords, TYPESAFE_API_KEY, any overrides of config/environments.ts. Never committed or shared.	Sometimes
.env.example	Template that lists which keys .env can contain (no real secrets). Copy it to .env on a new machine.	Rarely
.gitignore	Tells git what not to save: node_modules, .env, test-results, playwright-report, junit-results, playwright/.auth, OS files.	Rarely
Jenkinsfile	The Jenkins pipeline (new, 05 Oct). Runs in the Playwright Docker image on the "selenium" agent. Parameters: SUITE, MODULE, TEST_ID, WORKERS, SPLIT_SHARED_ACCOUNTS. Passwords come from Jenkins credentials. Publishes JUnit results, the HTML reports and failure screenshots/videos. Test failures make the build yellow (unstable).	Rarely
package-lock.json	Exact versions of every installed library so all machines get the same setup. Updated by npm.	Never
package.json	Project definition: libraries needed and the npm shortcuts (flow:account, flow:smoke, test:flow:headless, voice:control...).	Rarely
playwright.flow.config.ts	Main Playwright settings: test folder, 90-second timeout, 1 browser at a time, staging URL, headed by default (HEADLESS=true for headless), screenshot/video/trace on failure, list + HTML reports, projects "setup" and "flow-chromium". Also: testIgnore switches off Help and Currency converter (RUN_PARKED=true runs them anyway); on Jenkins (CI=true) it adds 1 retry and the JUnit file.	Rarely
README.md	How to set up and run everything: single test, module, smoke, regression, headed/headless, voice panel, debugging, and Jenkins setup (section 16).	Sometimes
run.sh	The shortcut runner: ./run.sh all smoke regression <module> <test ID> failed report control, plus "headless".	Rarely
tsconfig.json	TypeScript compiler settings.	Never

13. Where to look when...

Situation	Go to
A test fails	test-results/<test>/error-context.md and trace.zip → then fix in flows/<module>/...Flow.ts
A CP screen changed (new id / new step)	flows/<module>/...Flow.ts
Add a new test case	tests/flows/NN-<module>.flow.spec.ts (reuse the Flow helper)
A test account or password changed	.env (or the default in config/environments.ts)
Need a new npm shortcut or library	package.json
Change timeouts, headless, reports	playwright.flow.config.ts
Park a test for now	Change test(to test.fixme(in the spec file
Run in parallel	./run.sh regression headless --workers=6 (or SUITE=regression WORKERS=6 bash ci/jenkins-run.sh to split Send Money and Auth)
Switch a module off / on	testIgnore list in playwright.flow.config.ts
Change what Jenkins runs	Jenkinsfile (parameters) and ci/jenkins-run.sh (commands)
Share results	./run.sh report, or the PDFs in reports/