


## Problem 4 – Robbery

You are robber who just stole a TV. Now you must escape the cops without being caught. You are given a map of the city streets. However, the TV is quite heavy and you have **limited energy E**. There a few rules:

- Going from one point to another costs you some **energy** (displayed as a value on each arrow) and takes one turn.
- Each point is being watched by a **video camera**. A point can be **black** (a camera is **not** watching it) or **white** (a camera is watching it). Every turn points change color to the opposite (from black to white and vice versa). See the example below.
- You can only travel to points where the **camera is currently on** (because when you step on it the camera will be off and you will not be caught).
  - After stepping on a point you can **wait 0 or more turns** before going further (the camera will not catch you). Note that every turn you wait costs **W energy**.

Find the path that requires the **least energy** to go to the final point. Print the required energy.



*At each turn points change color as shown above*

### Input

- On the first line you will receive all points in the format "<node1><color1> <node2><color2> ...<nodeK><colorK>".
- On the second line, you will receive the **starting energy**.
- On the third line, you will receive the cost (in energy) for **waiting one turn**.
- On the fourth line, you will receive the **starting node**.
- On the fifth line, you will receive the **ending node**.
- On the sixth line you will receive a number - **n** specifying the **number of point connections**.
- On the next **n** lines you will receive the connections in the format "<start> <end> <distance>".


### Output

- Print the **amount of energy you have** at the end.
- If you do not have enough energy, print how much energy you still need to reach the end in the format "**Busted - need {x} more energy**".

## Constraints

- The amount of points in the city will be between [2...20000].
- The starting energy **E** will be a valid integer between [0...100000].
- The waiting cost **W** will be a valid integer between [0...10000].
- The distance of a connection will be a valid integer between [0...10000].
- The points will always be numbers starting from 0.
- The color will be either "b" or "w" – **b** means the camera is currently **not** watching, **w** means the camera is currently watching.
- There will always be a valid path from **start** to **end**.
- Time limit: **100 ms**. Allowed memory: **32 MB**.

## Examples

Input	Output	Visual
0b 1b 2w 3b 4b 70 10 0 4 7 0 1 25 0 2 30 1 3 12 1 4 15 2 1 3 2 3 15 3 4 18	12	
		<b>Comments</b> Start from 0. <ul style="list-style-type: none"> <li>• Going to 2 costs 30 energy.</li> <li>• Going to 1 costs 10 (for waiting one turn) + 25 = 35 energy</li> </ul> From 2 we go directly to 1 with energy 3. From 1 we need to wait 1 turn for both 3 and 4 to become white and then go for 4 (10 + 15 = 25 energy).

Input	Output
0b 1w 2w 3w 4w 5b 6b 7w 8b 9w 10b 11b 12w 13w 99 5 1 11 18 1 0 5 1 2 17 1 3 22 3 4 17	Busted - need 75 more energy  <b>Comments</b> (Path is 1 -> 3 -> 5 -> 6 -> 8 -> 9 -> 10 -> 12 -> 13 -> 11)

3 5 4 5 6 3 5 7 12 6 4 7 6 8 31 7 2 5 7 10 117 8 9 44 9 10 2 10 6 9 10 12 29 11 9 1 12 13 16 13 11 8	
---	--