

- Screenshot

```

C:\Users\DELL>ipconfig

Windows IP Configuration

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::3d79:a7b4:7fed:b984%19
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 

Wireless LAN adapter Local Area Connection* 11:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : 

Wireless LAN adapter Local Area Connection* 12:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : 

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::64fc:8f9b:25c1:da77%4
    IPv4 Address. . . . . : 192.168.1.3
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.1.1

Ethernet adapter Bluetooth Network Connection:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . : 

C:\Users\DELL>

```

- IP Address : IPv4 Address. : 192.168.1.3
- Subnet Mask : Subnet Mask : 255.255.255.0
- Network address :
 - IP Address : 11000000.10101000.00000001.00000011
 - Subnet Mask : 11111111.11111111.11111111.00000000
 - (AND) : 11000000.10101010.00000001.00000000
 - Network Address : 192.168.1.0
- Nodes that my network can support :
 - Here, Subnet mask : 255.255.255.0 (i.e. /24)
 - Total nodes : $2^{(32-24)} = 2^8 = 256$
 - 2 nodes are reserved for network address and broadcast address.
 - Usable nodes : $256 - 2 = 254$

