



# Flutter Driver App - API Integration Guide

**Target Audience:** Mobile Engineering Team

**Base URL (Staging):** `https://driversklub-backend.onrender.com`

**Base URL (Development):** `http://localhost:3000` (API Gateway)

**Base URL (Production):** AWS Elastic Beanstalk `driversklub-backend-env`

**Auth Header:** `Authorization: Bearer <ACCESS_TOKEN>`

**Version:** 4.6.0 (MMT Smart ID + Pricing Cleanup)

**Last Updated:** January 27, 2026

**Last Verified:** January 27, 2026

## What's New in v4.6.0

- **MMT Smart ID Formatting** - Driver/Vehicle IDs compressed to 10 chars for MMT compliance
- **Pricing Cleanup** - Consolidated pricing config, removed unused rules file
- **Pricing Formula:** `(billableKm × ₹25) × tripMultiplier × bookingMultiplier × vehicleMultiplier`

## What's New in v4.5.0

- **MMT Integration Complete** - Full tracking sync for all trip events
  - Automatic sync: start, arrived, boarded, alight, not-boarded
  - Location updates every 30 seconds via `POST /trips/:id/location`
  - Proper `booking_id` storage from MMT paid endpoint
- **Referral System** - Drivers get unique referral codes to invite other drivers
- **Enhanced Onboarding** - Full KYC submission via `/drivers/new-driver-onboard`
- **Bank Account Details** - Required for payout processing
- **Vehicle Documents** - Chassis, VIN, insurance dates

**Note:** All requests go through the API Gateway. The gateway routes to 6 microservices (Auth, Driver, Vehicle, Assignment, Trip, Notification).



## Table of Contents

1. [Authentication](#)
2. [Daily Attendance](#)
3. [Trip Management](#)
4. [Driver Profile](#)
  - [4.1 Get My Profile](#)
  - [4.2 Get Profile by ID](#)
  - [4.3 Update Profile](#)
  - [4.4 Get My Plans \(Rental History\)](#)
  - [4.5 Driver Preferences](#)
  - [4.6 Get Upload URL](#)
5. [Error Handling](#)
6. [Finance & Rental Plans](#)
  - [6.1 Balance & Status](#)
  - [6.2 Rental Management](#)
  - [6.3 Security Deposit](#)

- [6.4 Transactions & Summary](#)
  - 7. [Rapido Status Management](#)
  - 8. [Pricing & Utilities](#)
  - 9. [Google Maps Service](#)
  - 10. [Referral System](#)
- 

## 1. Authentication

---

### 1.1 New Driver Registration (Onboarding)

The new onboarding flow allows drivers to self-register via the mobile app. It replaces the old "Admin-only" creation model.

#### Step 1: Check Eligibility & Send OTP

**Endpoint:** POST /users/drivers/verify

Use this to screen the phone number.

- If user exists -> Returns error (User already registered).
- If new -> Sends OTP via SMS.

```
// Request
{ "phone": "9876543210" }

// Response
{ "message": "OTP sent successfully" }
```

#### Step 2: Verify OTP

**Endpoint:** POST /users/drivers/verifyOtp

Verify the OTP entered by the driver.

```
// Request
{
  "phone": "9876543210",
  "otp": "123456"
}

// Response
{ "message": "OTP verified successfully" }
```

#### Step 3: Create Account (Signup)

**Endpoint:** POST /users/drivers/signup

Creates the `User` and empty `Driver` profile. Does NOT require Auth token (Public).

```
// Request
{
  "name": "Amit Kumar",
  "phone": "9876543210"
}

// Response
{
  "id": "u-123",
  "shortId": "USR20260123001",
  "name": "Amit Kumar",
  "role": "DRIVER",
  "token": "..."
```

**Note:** If the signup endpoint does not return a token, you must call normal Login ( `POST /auth/verify-otp` ) immediately after signup to get the session token.

#### Step 4: KYC Profile Completion (New Onboarding Flow)

Once signup is complete, use the dedicated onboarding endpoint to submit full KYC:

**Endpoint:** `POST /drivers/new-driver-onboard` **Auth Required:** No (Public endpoint, uses `userId` from signup)

#### Request Body:

```
{
  "userId": "uuid-from-signup-response",
  "firstName": "Raj",
  "lastName": "Kumar",
  "mobile": "9876543210",
  "email": "raj@example.com",
  "dob": "1990-05-15T00:00:00.000Z",
  "address": "123 Main Street, Sector 29",
  "city": "Gurgaon",
  "pincode": 122001,

  "aadharNumber": 123456789012,
  "panNumber": "ABCDE1234F",
  "drivingLicenceNumber": "DL-0120230012345",
  "gstNumber": "22AAAAA0000A1Z5",

  "aadharFront": "https://s3.aws.com/aadhaar-front.jpg",
  "aadharBack": "https://s3.aws.com/aadhaar-back.jpg",
  "panPhoto": "https://s3.aws.com/pan.jpg",
  "driverAgreement": "https://s3.aws.com/agreement.pdf",
  "policeVerification": "https://s3.aws.com/pcv.jpg",
  "currentAddressProof": "https://s3.aws.com/current-address.jpg",
  "permanentAddressProof": "https://s3.aws.com/permanent-address.jpg",

  "haveVehicle": true,
  "vehicleModel": "Tata Tigor EV",
  "vehicleType": "SEDAN",
```

```
"registrationNumber": "DL01AB1234",
"fuelType": "ELECTRIC",
"ownerName": "Raj Kumar",
"rcFrontImage": "https://s3.aws.com/rc-front.jpg",
"rcBackImage": "https://s3.aws.com/rc-back.jpg",

"referralCode": "REF123ABC"
}
```

#### Response (201):

```
{
  "success": true,
  "data": {
    "id": "driver-uuid",
    "shortId": "DRV20260123001",
    "firstName": "Raj",
    "lastName": "Kumar",
    "kycStatus": "PENDING"
  },
  "message": "Documents Uploaded, KYC pending for verification"
}
```

#### Alternative: Update Existing Profile

Use `PATCH /drivers/:id` to update individual fields after onboarding.

#### Personal Information:

- `firstName` , `lastName` , `mobile`
- `email`
- `dob` (Date of Birth)
- `address` , `city` , `pincode`
- `profilePic`

#### KYC Values (Document Numbers):

- `aadharNumber` - 12-digit Aadhaar number
- `panNumber` - 10-character PAN
- `dlNumber` - Driving License number
- `licenseNumber` - Alternative DL field
- `gstNumber` - GST number (optional)

#### Bank Account Details (for payouts):

- `bankAccountNumber` - Bank account number
- `bankIfscCode` - IFSC code
- `bankAccountName` - Account holder name

#### Document Uploads (via S3 Presigned URLs):

- `licenseFront` , `licenseBack` - Driving License images
- `aadharFront` , `aadharBack` - Aadhaar card images
- `panCardImage` - PAN card image

- `livePhoto` - Live selfie for verification
- `bankIdProof` - Bank passbook/statement image

**Vehicle Documents (if driver has assigned vehicle):**

- `rcFrontImage` , `rcBackImage` - RC images
- `fitnessImage` , `fitnessExpiry` - Fitness certificate
- `insuranceImage` , `insuranceStart` , `insuranceExpiry` - Insurance documents
- `chassisNumber` - Vehicle chassis number
- `vinNumber` - Vehicle Identification Number

## 1.2 Send OTP

**Endpoint:** `POST /auth/send-otp`

**Auth Required:** No

**Request Body:**

```
{
  "phone": "9876543210"
}
```

**Response (200):**

```
{
  "success": true,
  "message": "OTP sent successfully"
}
```

## 1.2 Verify OTP

**Endpoint:** `POST /auth/verify-otp`

**Auth Required:** No

**Request Body:**

```
{
  "phone": "9876543210",
  "otp": "123456"
}
```

**Request Headers (Optional):**

```
x-client-type: app
```

**Note:** Set `x-client-type` header to `app` for mobile apps or `web` for web clients. This determines refresh token expiry duration.

**Response (200):**

```
{
  "success": true,
  "statusCode": 200,
  "data": {
    "accessToken": "eyJhbGciOiJIUzI1NiIs...\"",
    "refreshToken": "8f8e23...",
    "user": {
      "id": "uuid-user-id",
      "shortId": "USR20260123001",
      "phone": "9876543210",
      "role": "DRIVER"
    }
  }
}
```

**Token Expiry:**

- **Access Token:** 15 minutes (all clients)
- **Refresh Token:**
  - **Mobile App** ( `x-client-type: app` ): 30 days
  - **Web Client** ( `x-client-type: web` ): 1 day
  - **Default** (no header): 1 day

**Action:**

1. Check if `user.role === 'DRIVER'` . If not, show "Unauthorized App" error.
2. Store `accessToken` securely (Keychain/Keystore).
3. Store `refreshToken` for silent token renewal.

---

### 1.3 Refresh Token

**Endpoint:** `POST /auth/refresh`

**Auth Required:** No

**Request Body:**

```
{
  "refreshToken": "8f8e23..."
}
```

**Response (200):**

```
{
  "success": true,
  "data": {
```

```
    "accessToken": "eyJ..."
  }
}
```

**Implementation:** Call this automatically when you receive `401 Unauthorized` on any protected endpoint.

---

## 2. Daily Attendance

---

### 2.1 Check In (Start Shift)

**Endpoint:** `POST /attendance/check-in`

**Auth Required:** Yes

**Role:** DRIVER

**Request Body:**

```
{
  "driverId": "uuid-driver-id-from-profile",
  "lat": 28.4595,
  "lng": 77.0266,
  "odometer": 10500,
  "selfieUrl": "https://s3.aws.com/bucket/selfie.jpg"
}
```

**Important:** Upload selfie to S3/Cloudinary first, then send the URL.

**Response (201):**

```
{
  "success": true,
  "data": {
    "id": "uuid",
    "shortId": "ATT20260123001",
    "status": "PENDING_APPROVAL",
    "checkInTime": "2025-12-25T08:00:00Z"
  }
}
```

**Side Effects:**

- **Rapido Status:** Driver is automatically marked **ONLINE** on Rapido (if no other conflicts exist).
- 

### 2.2 Check Out (End Shift)

**Endpoint:** `POST /attendance/check-out`

**Auth Required:** Yes

**Role:** DRIVER

**Request Body:**

```
{
  "driverId": "uuid-driver-id",
  "odometer": 10650,
  "odometerImageUrl": "https://s3.aws.com/bucket/odometer.jpg",
  "cashDeposited": 5000
}
```

**Note:**

- `cashDeposited` is the Amount the driver declares they are submitting (Cash + UPI collection) at day end.
- `odometerImageUrl` is optional. Upload odometer image to S3 first using `/drivers/upload-url` , then send the URL.

**Response (200):**

```
{
  "success": true,
  "message": "Check-out successful",
  "data": {
    "checkOutTime": "2025-12-25T18:00:00Z",
    "totalKm": 150
  }
}
```

**Error Responses (400):**

- **Invalid Odometer:** message: "Odometer reading cannot be less than start reading (10500)"
- **Invalid Cash:** message: "Invalid cash deposit amount"

**Side Effects:**

- **Rapido Status:** Driver is forced **OFFLINE** on Rapido immediately.
- 

### 2.3 Start Break (Start Break in Shift)

**Endpoint:** POST `/attendance/start-break`

**Auth Required:** Yes

**Role:** DRIVER

**Request Body:**

```
{
  "driverId": "uuid-driver-id"
}
```

**Response (200):**



```
{
  "success": true,
  "statusCode": 200,
  "message": "Break started successfully",
  "data": {
    "id": "1d0c84d0-a593-4079-8ed3-2ce274ad378d",
    "shortId": "BRK20260123001",
    "driverId": "b16dd8ec-a030-44a9-9175-ebd77013dbd0",
    "checkInTime": "2025-12-25T10:06:20.674Z",
    "checkOutTime": null,
    "status": "APPROVED",
    "approvedBy": null,
    "adminRemarks": null,
    "checkInLat": 19.076,
    "checkInLng": 72.8777,
    "selfieUrl": "https://cdn.example.com/selfies/driver_98765.jpg",
    "odometerStart": 45230,
    "odometerEnd": null,
    "breakStartTime": "2025-12-25T10:07:31.911Z",
    "breakEndTime": null,
    "createdAt": "2025-12-25T10:06:20.674Z",
    "updatedAt": "2025-12-25T10:07:31.920Z"
  }
}
```

## 2.4 End Break (End Break in shift)

**Endpoint:** POST /attendance/end-break

**Auth Required:** Yes

**Role:** DRIVER

**Request Body:**

```
{
  "driverId": "uuid-driver-id",
}
```

**Response (200):**

```
{
  "success": true,
  "statusCode": 200,
  "message": "Break ended successfully",
  "data": {
    "id": "1d0c84d0-a593-4079-8ed3-2ce274ad378d",
    "shortId": "BRK20260123001",
    "driverId": "b16dd8ec-a030-44a9-9175-ebd77013dbd0",
    "checkInTime": "2025-12-25T10:06:20.674Z",
    "checkOutTime": null,
```

```
    "status": "APPROVED",
    "approvedBy": null,
    "adminRemarks": null,
    "checkInLat": 19.076,
    "checkInLng": 72.8777,
    "selfieUrl": "https://cdn.example.com/selfies/driver_98765.jpg",
    "odometerStart": 45230,
    "odometerEnd": null,
    "breakStartTime": "2025-12-25T10:07:31.911Z",
    "breakEndTime": "2025-12-25T10:08:14.312Z",
    "createdAt": "2025-12-25T10:06:20.674Z",
    "updatedAt": "2025-12-25T10:08:14.316Z"
  }
}
```

## 2.5 Get Attendance History

**Endpoint:** GET /attendance/history?driverId={uuid}

**Auth Required:** Yes

**Response (200):**

```
{
  "success": true,
  "data": [
    {
      "id": "uuid",
      "shortId": "ATT20260123001",
      "checkInTime": "2025-12-25T08:00:00Z",
      "checkOutTime": "2025-12-25T18:00:00Z",
      "status": "APPROVED",
      "odometerStart": 10500,
      "odometerEnd": 10650
    }
  ]
}
```

## 3. Trip Management

### 3.1 Get My Assigned Trips

**Endpoint:** GET /trips?status=DRIVER\_ASSIGNED

**Auth Required:** Yes

**Role:** DRIVER

**Response (200):**

```
{
  "success": true,
  "data": [
    {
      "id": "uuid-trip-id",
      "shortId": "TRP20260123001",
      "tripType": "AIRPORT",
      "originCity": "Delhi",
      "pickupLocation": "T3 Terminal, Gate 4",
      "pickupLat": 28.5562,
      "pickupLng": 77.1000,
      "dropLocation": "Cyber Hub, Gurgaon",
      "pickupTime": "2025-12-25T10:00:00Z",
      "status": "DRIVER_ASSIGNED",
      "price": 1200,
      "distanceKm": 45
    }
  ]
}
```

### 3.2 Get Trip Details

**Endpoint:** GET /trips/:id

**Auth Required:** Yes

**Response (200):**

```
{
  "success": true,
  "data": {
    "id": "uuid",
    "shortId": "TRP20260123001",
    "tripType": "AIRPORT",
    "pickupLocation": "T3 Terminal, Gate 4",
    "pickupLat": 28.5562,
    "pickupLng": 77.1000,
    "dropLocation": "Cyber Hub",
    "pickupTime": "2025-12-25T10:00:00Z",
    "status": "DRIVER_ASSIGNED",
    "price": 1200,
    "customerPhone": "9876543210",
    "customerName": "John Doe",
    "provider": "MMT"
  }
}
```

### 3.3 🚦 Trip Lifecycle State Machine

Perform these actions **strictly in order**. Send GPS coordinates with every status change.

[!IMPORTANT] **Trip Types:**

- **Internal Trips:** Created by admin, standard flow
- **External Trips (MMT):** From MakeMyTrip, includes `provider: "MMT"`, `providerBookingId`, and `providerMeta.otp`

### Step A: Start Trip (En-route to Pickup)

**Endpoint:** `POST /trips/:id/start`

**Auth Required:** Yes

**Request Body:**

```
{
  "lat": 28.5500,
  "lng": 77.0900
}
```

⚠ **STRICT CONSTRAINT:**

- Can ONLY start within **2.5 hours** of `pickupTime`
- Error if too early: `400 "Cannot start trip more than 2.5 hours before pickup"`

### Response (200) - Internal Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Trip started successfully",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "tripType": "AIRPORT",
    "originCity": "Delhi",
    "destinationCity": "Noida",
    "pickupLocation": "Terminal 1, IGI Airport",
    "pickupLat": 28.5550838,
    "pickupLng": 77.0844015,
    "dropLocation": "Noida, Sector 62",
    "pickupTime": "2026-01-24T16:00:00.000Z",
    "distanceKm": 40,
    "price": 950,
    "status": "STARTED",
    "startedAt": "2026-01-24T05:44:45.105Z",
    "provider": null,
    "providerBookingId": null,
    "customerName": "Amit Sharma",
    "customerPhone": "9876543210",
    "paymentMethod": "CASH"
  }
}
```

## Response (200) - MMT Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Trip started successfully",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "tripType": "AIRPORT",
    "originCity": "Delhi",
    "destinationCity": "Noida",
    "pickupLocation": "Terminal 1, IGI Airport",
    "pickupLat": 28.5550838,
    "pickupLng": 77.0844015,
    "dropLocation": "Noida, Sector 62",
    "pickupTime": "2026-01-24T16:00:00.000Z",
    "distanceKm": 40,
    "price": 950,
    "status": "STARTED",
    "startedAt": "2026-01-24T05:44:45.105Z",
    "provider": "MMT",
    "providerBookingId": "BKS88888800933",
    "providerMeta": {
      "otp": "4963"
    }
  }
}
```

## Side Effects:

- Status: DRIVER\_ASSIGNED → STARTED
- **MMT Trip:** Webhook POST /track/{providerBookingId}/start sent to MMT with driver location

## Step B: Arrived (At Pickup Location)

**Endpoint:** POST /trips/:id/arrived

**Auth Required:** Yes

## Request Body:

```
{
  "lat": 28.5562,
  "lng": 77.1000
}
```

## ⚠️ STRICT CONSTRAINTS:

1. **Geofence:** Must be within **500m** of pickupLat / pickupLng
2. **Time:** Must be within **30 minutes** of pickupTime

## Errors:

- 400 "Driver not within 500m geofence" - Too far from pickup
- 400 "Cannot arrive more than 30 minutes before pickup" - Too early

#### Response (200) - Internal Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Driver marked as arrived",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "status": "ARRIVED_EVENT_SENT",
    "arrivedAt": "2026-01-24T05:53:24.389Z",
    "pickupLocation": "Terminal 1, IGI Airport",
    "pickupLat": 28.5550838,
    "pickupLng": 77.0844015
  }
}
```

#### Response (200) - MMT Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Driver marked as arrived",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "status": "ARRIVED_EVENT_SENT",
    "arrivedAt": "2026-01-24T05:53:24.389Z",
    "pickupLocation": "Terminal 1, IGI Airport",
    "pickupLat": 28.5550838,
    "pickupLng": 77.0844015,
    "provider": "MMT",
    "providerBookingId": "BKS88888800933",
    "providerMeta": {
      "otp": "4963"
    }
  }
}
```

#### Side Effects:

- Status: `STARTED` → `ARRIVED_EVENT_SENT`
- SMS sent to customer: "Driver Arrived"
- **MMT Trip:** Webhook `POST /track/{providerBookingId}/arrived` sent to MMT

---

#### Step C: Passenger Onboard (Ride Begins)

**Endpoint:** `POST /trips/:id/onboard`

**Auth Required:** Yes

### Request Body:

```
{
  "otp": "4963",
  "lat": 28.5550838,
  "lng": 77.0844015
}
```

### Field Details:

- `otp` (optional): For MMT trips, this OTP is required for passenger verification. Get from `providerMeta.otp`
- `lat`, `lng` (optional): Current location at boarding

### Response (200) - Internal Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Passenger boarded",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "status": "STARTED",
    "boardedAt": "2026-01-24T05:54:15.234Z"
  }
}
```

### Response (200) - MMT Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Passenger boarded",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "status": "STARTED",
    "boardedAt": "2026-01-24T05:54:15.234Z",
    "provider": "MMT",
    "providerBookingId": "BKS88888800933"
  }
}
```

### Side Effects:

- Status: `ARRIVED_EVENT_SENT` → `STARTED` (boarded state)
- **MMT Trip:** Webhook `POST /track/{providerBookingId}/boarded` sent to MMT with boarding confirmation

---

### Step D: Complete (Dropoff)

**Endpoint:** POST /trips/:id/complete

**Auth Required:** Yes

**Request Body - Internal Trip (Basic):**

```
{
  "lat": 28.5355,
  "lng": 77.3910,
  "fare": 1200
}
```

**Request Body - MMT Trip (With Extra Charges):**

```
{
  "lat": 28.5355,
  "lng": 77.3910,
  "fare": 1200,
  "extraCharges": {
    "toll": 150,
    "parking": 50
  }
}
```

**Field Details:**

- lat , lng : Drop-off location coordinates
- fare (optional): Final fare amount
- extraCharges (optional): Additional charges breakdown
  - toll (number): Toll charges in rupees
  - parking (number): Parking charges in rupees
  - extraKms (number): Extra kilometer charges
  - extraMinutes (number): Extra time charges

**Auto-Calculated Extra Charges:**

Charge Type	Calculation Logic
Waiting Charges	(Boarded Time - Arrived Time - 45 mins free) * ₹100/30min
Night Charges	Auto-detected. If pickup is 11 PM - 5 AM: Max(25% of Base Fare, ₹250)
Airport Fees	Auto-detected. If Trip Type is AIRPORT : Fixed ₹270
Toll / Parking	Manual. Passed from driver app input.
State Tax	Manual. Passed from driver app input.

**Note:** Extra charges (Waiting, Night, Airport) are **auto-calculated** by the backend based on timestamps and location. Manual values in extraCharges for these fields will be overridden.

**Response (200) - Internal Trip:**



```

{
  "success": true,
  "statusCode": 200,
  "message": "Trip completed successfully",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "tripType": "AIRPORT",
    "originCity": "Delhi",
    "destinationCity": "Noida",
    "pickupLocation": "Terminal 1, IGI Airport",
    "dropLocation": "Noida, Uttar Pradesh, India",
    "pickupTime": "2026-01-24T16:00:00.000Z",
    "distanceKm": 40,
    "price": 950,
    "status": "COMPLETED",
    "completedAt": "2026-01-24T05:54:32.102Z",
    "startedAt": "2026-01-24T05:44:45.105Z",
    "dropLat": 28.5355161,
    "dropLng": 77.3910265
  }
}

```

#### Response (200) - MMT Trip (With Extra Charges):

```

{
  "success": true,
  "statusCode": 200,
  "message": "Trip completed successfully",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "tripType": "AIRPORT",
    "originCity": "Delhi",
    "destinationCity": "Noida",
    "pickupLocation": "Terminal 1, IGI Airport",
    "dropLocation": "Noida, Uttar Pradesh, India",
    "pickupTime": "2026-01-24T16:00:00.000Z",
    "distanceKm": 40,
    "price": 950,
    "status": "COMPLETED",
    "completedAt": "2026-01-24T05:54:32.102Z",
    "startedAt": "2026-01-24T05:44:45.105Z",
    "dropLat": 28.5355161,
    "dropLng": 77.3910265,
    "provider": "MMT",
    "providerBookingId": "BKS88888800933",
    "providerMeta": {
      "otp": "4963"
    }
  }
}

```

```
}  
}
```

#### Side Effects:

- Status: `STARTED` → `COMPLETED`
- Driver becomes available for next assignment
- **MMT Trip:** Webhook `POST /track/{providerBookingId}/align` sent to MMT with:
  - Final coordinates
  - Extra charges (if provided): `extra_charge: 200` (toll + parking)
  - Detailed breakdown in `extra_fare_breakup` object

---

#### Alternative: No Show

**Endpoint:** `POST /trips/:id/noshow`

**Auth Required:** Yes

#### Request Body:

```
{  
  "lat": 28.5550838,  
  "lng": 77.0844015,  
  "reason": "Customer not reachable"  
}
```

#### Field Details:

- `lat` , `lng` : Current location when marking no-show
- `reason` (optional): Reason for no-show

#### ⚠️ STRICT CONSTRAINT:

- Can ONLY mark no-show **AFTER** driver has arrived ( `ARRIVED_EVENT_SENT` status)
- Best practice: Wait **15-30 minutes** past `pickupTime` before marking no-show

#### Response (200) - Internal Trip:

```
{  
  "success": true,  
  "statusCode": 200,  
  "message": "Trip marked as No Show",  
  "data": {  
    "id": "uuid-trip-id",  
    "shortId": "TRP20260123001",  
    "status": "NO_SHOW",  
    "pickupLocation": "Terminal 1, IGI Airport"  
  }  
}
```

#### Response (200) - MMT Trip:

```
{
  "success": true,
  "statusCode": 200,
  "message": "Trip marked as No Show",
  "data": {
    "id": "uuid-trip-id",
    "shortId": "TRP20260123001",
    "status": "NO_SHOW",
    "pickupLocation": "Terminal 1, IGI Airport",
    "provider": "MMT",
    "providerBookingId": "BKS88888800929"
  }
}
```

#### Side Effects:

- Status: `ARRIVED_EVENT_SENT` → `NO_SHOW`
- Driver becomes available for next assignment
- **MMT Trip:** Webhook `POST /track/{providerBookingId}/not_boarded` sent to MMT

### 3.4 Update Live Location

**Endpoint:** `POST /trips/:id/location` **Auth Required:** Yes

#### Request Body:

```
{
  "lat": 28.5500,
  "lng": 77.0900
}
```

#### Response (200):

```
{
  "success": true,
  "message": "Location updated successfully"
}
```

#### Implementation Note:

- Call this endpoint every **30-60 seconds** while trip is in progress ( `STARTED` , `ARRIVED_EVENT_SENT` )
- **MMT Trips:** Location updates are automatically synced to MMT via `PUT /track/{providerBookingId}/location` webhook
- Provides real-time tracking for customers and admin

### 3.5 Get Live Tracking

**Endpoint:** GET /trips/:id/tracking

**Auth Required:** Yes

**Response (200):**

```
{
  "success": true,
  "data": {
    "currentLat": 28.5500,
    "currentLng": 77.0900,
    "lastUpdated": "2025-12-25T09:45:00Z"
  }
}
```

### 3.6 Partner Trips (MMT)

**Identification:** Trips assigned from MakeMyTrip can be identified by:

- provider : "MMT" (in Trip Details)
- providerBookingId : "BKS8888800926" (MMT's booking ID)
- tripType : "AIRPORT" or "OUTSTATION"

**Special Handling Rules:**

#### 1. Prepaid/Zero Payment:

- MMT trips are prepaid.
- **Do NOT collect cash** from the customer even if price is shown.
- Show "PREPAID" tag in the UI.

#### 2. Mandatory OTP:

- MMT requires a valid OTP for onboarding.
- Ensure the driver enters the exact 4-digit OTP provided by the customer.
- OTP is stored in providerMeta.otp field.
- Sending "0000" or invalid OTP may cause MMT to reject the 'Onboard' status.

#### 3. Location Updates (CRITICAL):

- MMT strictly tracks vehicle movement.
- **Must call** POST /trips/:id/location **every 30 seconds** from Start to Alight.
- Failure to send location updates may result in penalties from MMT.

#### 4. Cancellation:

- If a driver cancels an MMT trip, it triggers an immediate unassign webhook to MMT.
- **Avoid frequent cancellations** to maintain fleet rating.

**MMT Trip Event Flow:**

1. **Admin assigns driver** → MMT receives /dispatch/{booking\_id}/assign (Driver Details)
2. **Driver taps "Start"** → MMT receives /track/{booking\_id}/start (Journey Begins)
3. **Driver taps "Arrived"** → MMT receives /track/{booking\_id}/arrived (At Pickup)
4. **Driver enters OTP, taps "Onboard"** → MMT receives /track/{booking\_id}/boarded (Ride Begins)
5. **Every 30 seconds during trip** → MMT receives /track/{booking\_id}/location (Live Tracking)

6. **Driver taps "Complete"** → MMT receives `/track/{booking_id}/align` (Ride Ends + Extra Charges)

#### No-Show Flow:

1. Driver arrives, waits 30+ minutes past pickup time.
2. **Driver taps "No Show"** → MMT receives `/track/{booking_id}/not-boarded` (Cancellation)

---

## 4. Driver Profile

### 4.1 Get My Profile

**Endpoint:** `GET /drivers/me`

**Auth Required:** Yes

**Role:** DRIVER

**Response (200):**

```
{
  "success": true,
  "data": {
    "id": "uuid",
    "shortId": "DRV20260123001",
    "firstName": "Raj",
    "lastName": "Kumar",
    "mobile": "9876543210",
    "licenseNumber": "DL-12345-67890",
    "kycStatus": "APPROVED",
    "status": "ACTIVE",
    "fleet": {
      "id": "uuid",
      "name": "Delhi Cabs Pvt Ltd",
      "city": "DELHI"
    },
    "assignments": [
      {
        "id": "assignment-uuid",
        "shortId": "ASN20260123001",
        "status": "ACTIVE",
        "startDate": "2026-01-12T00:00:00Z",
        "vehicle": {
          "id": "vehicle-uuid",
          "shortId": "VEH20260123001",
          "vehicleNumber": "DL10CA1234",
          "vehicleName": "Tata Tigor EV",
          "fuelType": "ELECTRIC",
          "vehicleType": "SEDAN",
          "status": "ACTIVE"
        }
      }
    ]
  }
}
```

```
}  
}
```

**Note:**

- `assignments` array contains the currently assigned vehicle (if any)
- If no vehicle is assigned, `assignments` will be an empty array `[]`
- Use `assignments[0].vehicle` to access the assigned vehicle details

## 4.2 Get Driver Profile by ID

**Endpoint:** `GET /drivers/:id` **Auth Required:** Yes **Role:** `SUPER_ADMIN`, `OPERATIONS`, `MANAGER`

**Response (200):**

```
{  
  "success": true,  
  "data": {  
    "id": "uuid",  
    "shortId": "DRV20260123001",  
    "firstName": "Raj",  
    "lastName": "Kumar",  
    // ... other fields  
  }  
}
```

## 4.3 Update Driver Profile

**Endpoint:** `PATCH /drivers/:id` **Auth Required:** Yes **Role:** `SUPER_ADMIN`, `OPERATIONS`, `MANAGER`, `DRIVER`

**Request Body (all fields optional):**

```
{  
  "firstName": "Rajesh",  
  "lastName": "Kumar",  
  "mobile": "9876543210",  
  "email": "rajesh@example.com",  
  "dob": "1990-05-15T00:00:00.000Z",  
  "address": "123 Main Street",  
  "city": "Delhi",  
  "pincode": "110001",  
  
  "aadharNumber": "123456789012",  
  "panNumber": "ABCDE1234F",  
  "dlNumber": "DL-0120230012345",  
  "gstNumber": "22AAAAA0000A1Z5",  
  
  "bankAccountNumber": "1234567890123456",  
  "bankIfscCode": "HDFC0001234",  
  "bankAccountName": "Rajesh Kumar",  
}
```

```
"licenseFront": "https://s3.aws.com/license-front.jpg",
"licenseBack": "https://s3.aws.com/license-back.jpg",
"aadharFront": "https://s3.aws.com/aadhaar-front.jpg",
"aadharBack": "https://s3.aws.com/aadhaar-back.jpg",
"panCardImage": "https://s3.aws.com/pan.jpg",
"bankIdProof": "https://s3.aws.com/bank-proof.jpg",

"rcFrontImage": "https://s3.aws.com/rc-front.jpg",
"rcBackImage": "https://s3.aws.com/rc-back.jpg",
"fitnessImage": "https://s3.aws.com/fitness.jpg",
"fitnessExpiry": "2026-12-31",
"insuranceImage": "https://s3.aws.com/insurance.jpg",
"insuranceStart": "2024-01-01",
"insuranceExpiry": "2025-12-31",
"chassisNumber": "MA1AB2CD3EF456789",
"vinNumber": "1HGBH41JXMN109186"
}
```

#### Field Categories:

Category	Fields
Basic Info	firstName , lastName , mobile , email , dob , address , city , pincode
KYC Values	aadharNumber , panNumber , dlNumber , gstNumber
Bank Details	bankAccountNumber , bankIfscCode , bankAccountName
KYC Attachments	licenseFront , licenseBack , aadharFront , aadharBack , panCardImage , bankIdProof
Vehicle Docs	rcFrontImage , rcBackImage , fitnessImage , fitnessExpiry , insuranceImage , insuranceStart , insuranceExpiry , chassisNumber , vinNumber

**Note:** Vehicle document fields are only updated if the driver has an assigned vehicle ( `vehicleId` is set).

#### Response (200):

```
{
  "success": true,
  "data": {
    "id": "uuid",
    "shortId": "DRV20260123001",
    "firstName": "Rajesh",
    "lastName": "Kumar",
    "mobile": "9876543210",
    "email": "rajesh@example.com",
    "kycStatus": "APPROVED",
    "status": "ACTIVE"
  },
}
```

```
"message": "Profile updated successfully"
}
```

#### 4.4 Get My Plans (Rental History)

**Endpoint:** GET /payments/rental/history **Auth Required:** Yes **Role:** DRIVER

**Response (200):**

```
{
  "success": true,
  "data": [
    {
      "id": "uuid",
      "shortId": "RNT20260123001",
      "planName": "Weekly Plan",
      "rentalAmount": 3000,
      "depositAmount": 5000,
      "validityDays": 7,
      "startDate": "2026-01-10T00:00:00.000Z",
      "expiryDate": "2026-01-17T00:00:00.000Z",
      "isActive": true,
      "status": "ACTIVE"
    },
    {
      "id": "uuid-2",
      "shortId": "RNT20251201001",
      "planName": "Monthly Plan",
      "rentalAmount": 10000,
      "depositAmount": 5000,
      "validityDays": 30,
      "startDate": "2025-12-01T00:00:00.000Z",
      "expiryDate": "2025-12-31T00:00:00.000Z",
      "isActive": false,
      "status": "EXPIRED"
    }
  ],
  "message": "Plan history retrieved successfully"
}
```

##### Status Values:

- **ACTIVE** - Current active plan (not expired)
- **EXPIRED** - Plan has passed expiry date
- **INACTIVE** - Plan was deactivated before expiry

##### Use Case:

- Show driver's rental history in "My Plans" section
- Display past plans with their validity periods
- Useful for admin to track driver's subscription history



## 4.5 Driver Preferences

### Get My Preferences

**Endpoint:** GET /drivers/me/preference

**Auth Required:** Yes

**Role:** DRIVER

[!NOTE] **Rapido Status Sync:** Driver availability ( `isAvailable` ) is managed automatically by the backend based on Login, Trip Status, and Breaks. Manual toggling may be overridden.

### Response (200):

```
{
  "success": true,
  "statusCode": 200,
  "message": "Driver preferences retrieved successfully",
  "data": [
    {
      "key": "prefer_airport_rides",
      "displayName": "Prefer airport rides",
      "description": "Prioritize airport pickup and drop trips",
      "category": "TRIP",
      "approvalRequired": true,
      "value": true
    }
  ]
}
```

### Request Preference Change

**Endpoint:** POST /drivers/:id/preference/update

**Auth Required:** Yes

**Role:** DRIVER

### Request Body:

```
{
  "prefer_airport_rides": true,
  "accept_rentals": true,
  "auto_assign_rides": true
}
```

### Response (201):

```
{
  "success": true,
  "message": "Preference change request submitted successfully"
}
```

## 4.6 Get Upload URL (S3 Image Upload)

**Endpoint:** GET /drivers/upload-url

**Auth Required:** Yes

**Role:** DRIVER

### Query Parameters:

- `folder` (required): Folder name - `selfies`, `odometer`, `documents`, `profiles`, `vehicles`
- `fileType` (required): File extension - `jpg`, `jpeg`, `png`, `pdf`

### Request Example:

```
GET /drivers/upload-url?folder=odometer&fileType=jpg
Authorization: Bearer <ACCESS_TOKEN>
```

### Response (200):

```
{
  "success": true,
  "data": {
    "uploadUrl": "https://s3.amazonaws.com/driversklub-assets/odometer/uuid.jpg?X-Amz-...",
    "key": "odometer/uuid.jpg",
    "url": "https://driversklub-assets.s3.ap-south-1.amazonaws.com/odometer/uuid.jpg"
  },
  "message": "Upload URL generated successfully"
}
```

### Upload Flow:

- 1. Request Upload URL:** Call this endpoint with desired folder and file type
- 2. Upload File:** Send a `PUT` request to the `uploadUrl` with the image file as binary body
- 3. Use Final URL:** Send the `url` field to other APIs (e.g., `selfieUrl` in check-in, `odometerImageUrl` in check-out)

### Example Upload (Dart/Flutter):

```
// Step 1: Get presigned URL
final response = await http.get(
  Uri.parse('$baseUrl/drivers/upload-url?folder=odometer&fileType=jpg'),
  headers: {'Authorization': 'Bearer $token'},
);
final data = jsonDecode(response.body)['data'];

// Step 2: Upload file to S3
final file = File(imagePath);
await http.put(
  Uri.parse(data['uploadUrl']),
  body: await file.readAsBytes(),
  headers: {'Content-Type': 'image/jpeg'},
);
```

```
// Step 3: Use the final URL
final imageUrl = data['url'];
```

#### Allowed Folders:

- `selfies` - Driver check-in selfies
- `odometer` - Odometer reading photos
- `documents` - License, Aadhaar, etc.
- `profiles` - Profile pictures
- `vehicles` - Vehicle photos

**Note:** Presigned URLs expire in 5 minutes. Upload must be completed within this time.

## 5. Error Handling

### 5.1 HTTP Status Codes

Code	Error	Meaning	Action
400	VALIDATION_ERROR	Invalid request body	Check request format
400	TOO_EARLY_START	Cannot start > 2.5h before pickup	Wait until allowed time
400	TOO_EARLY_ARRIVE	Cannot arrive > 30min before pickup	Wait until allowed time
400	GEOFENCE_VIOLATION	Not within 500m of pickup	Move closer to pickup location
400	TOO_EARLY_NOSHOW	Cannot mark no-show < 30min after pickup	Wait until allowed time
401	UNAUTHORIZED	Token Invalid/Expired	Call <code>/auth/refresh</code> or re-login
403	FORBIDDEN	Insufficient permissions	Contact admin
404	NOT_FOUND	Trip/Resource not found	Refresh trip list
422	UNPROCESSABLE_ENTITY	Business logic violation	Check trip status
500	INTERNAL_SERVER_ERROR	Backend crash	Retry after few seconds

### 5.2 Error Response Format

```
{
  "success": false,
  "statusCode": 400,
  "errorCode": "TOO_EARLY_START",
  "message": "Cannot start trip more than 2.5 hours before pickup",
}
```

```
"timestamp": "2025-12-25T09:00:00Z"
}
```

## Checklist for Production

- ☐ Implement token refresh logic
- ☐ Add offline queue mechanism
- ☐ Implement background location tracking
- ☐ Add geofencing validation before API calls
- ☐ Add time constraint validation before API calls
- ☐ Implement retry logic for failed requests
- ☐ Add comprehensive error handling
- ☐ Implement push notifications (FCM)
- ☐ Add analytics/crash reporting (Firebase)
- ☐ Test all edge cases (offline, poor network, etc.)

## 6. Finance & Rental Plans

### 6.1 Get Balance & Financial Status

**Endpoint:** GET /payments/balance **Auth Required:** Yes **Role:** DRIVER

**Response (200):**

```
{
  "success": true,
  "data": {
    "depositBalance": 5100,
    "paymentModel": "RENTAL",
    "hasActiveRental": true,
    "rental": {
      "id": "uuid",
      "shortId": "RNT20260123001",
      "planName": "Weekly Starter",
      "amount": 2500,
      "startDate": "2026-01-15T00:00:00Z",
      "expiryDate": "2026-01-22T00:00:00Z",
      "daysRemaining": 30,
      "isExpired": false,
      "vehicle": {
        "id": "vehicle-uuid",
        "shortId": "VEH20260123001",
        "number": "BR34 QW 1234",
        "model": "TATA Tigor EV"
      }
    }
  }
}
```

```
}  
}
```

## 6.2 Rental Management

### 6.2.1 Get Available Plans

**Endpoint:** GET /payments/rental/plans **Description:** List all plans available for subscription.

**Response (200):**

```
{  
  "success": true,  
  "data": [  
    {  
      "id": "uuid",  
      "shortId": "PLN20260123001",  
      "name": "Weekly Starter",  
      "rentalAmount": 3000,  
      "depositAmount": 5000,  
      "validityDays": 7,  
      "description": "Best for new drivers"  
    }  
  ]  
}
```

### 6.2.2 Subscribe to Plan

**Endpoint:** POST /payments/rental **Description:** Initiate payment to subscribe to a plan. Requires checking deposit balance first.

**Request Body:**

```
{  
  "rentalPlanId": "uuid-plan-id"  
}
```

**Response (200):**

```
{  
  "success": true,  
  "data": {  
    "transactionId": "uuid",  
    "paymentUrl": "https://testpay.easebuzz.in/pay/{accessKey}",  
    "accessKey": "0c4d0ab671a967784530587dbca8e2c8...",  
    "txnId": "TXN_1768492822722_AU6QJR"  
  }  
}
```

**Usage:** Open `paymentUrl` in a WebView or browser to complete payment.

### 6.2.3 Get Active Plan Details

**Endpoint:** `GET /drivers/:id/active-plan` **Note:** Use Driver ID from `GET /drivers/me`.

**Response (200):**

```
{
  "success": true,
  "data": {
    "id": "uuid-rental-id",
    "shortId": "RNT20260123001",
    "planName": "Weekly Starter",
    "rentalAmount": 2500,
    "depositAmount": 5000,
    "validityDays": 7,
    "startDate": "2026-01-15T00:00:00Z",
    "expiryDate": "2026-01-22T00:00:00Z",
    "isActive": true,
    "daysRemaining": 5,
    "vehicle": {
      "id": "vehicle-uuid",
      "shortId": "VEH20260123001",
      "number": "BR34 QW 1234",
      "model": "TATA Tigor EV"
    }
  }
}
```

## 6.3 Security Deposit

### 6.3.1 Initiate Top-up

**Endpoint:** `POST /payments/deposit` **Description:** Add money to security deposit via PG.

**Request Body:**

```
{
  "amount": 2000
}
```

**Response (200):**

```
{
  "success": true,
  "data": {
    "transactionId": "uuid",
    "paymentUrl": "https://testpay.easebuzz.in/pay/{accessKey}",
    "accessKey": "0c4d0ab671a967784530587dbca8e2c8...",
    "txnId": "TXN_1768492822722_AU6QJR"
  }
}
```

```
}  
}
```

**Usage:** Open `paymentUrl` in a WebView or browser to complete payment.

---

## 6.4 Transactions & Summary

### 6.4.1 Get Transaction History

**Endpoint:** `GET /payments/transactions` **Query Params:** `page`, `limit`, `type` (DEPOSIT, RENTAL, PENALTY, INCENTIVE)

**Response (200):**

```
{  
  "success": true,  
  "data": {  
    "transactions": [  
      {  
        "id": "uuid",  
        "shortId": "TXN20260123001",  
        "type": "DEPOSIT",  
        "amount": 5000,  
        "status": "SUCCESS",  
        "createdAt": "2025-12-01T10:00:00Z"  
      }  
    ]  
  }  
}
```

### 6.4.2 Get Incentives

**Endpoint:** `GET /payments/incentives`

### 6.4.3 Get Penalties

**Endpoint:** `GET /payments/penalties`

### 6.4.4 Get Daily Collections (Payout Model)

**Endpoint:** `GET /payments/collections`

### 6.4.5 Get Weekly Earnings Summary

**Endpoint:** `GET /payments/earnings/weekly`

**Auth Required:** Yes

**Role:** DRIVER

**Query Parameters:**

- `weeks` (optional, default: 5): Number of weeks to fetch (1-12)

**Response (200):**

```
{
  "success": true,
  "data": {
    "currentWeek": {
      "type": "current",
      "weekNumber": 3,
      "startDate": "2026-01-13",
      "endDate": "2026-01-19",
      "tripCount": 15,
      "tripEarnings": 4500,
      "incentives": 500,
      "penalties": 200,
      "netEarnings": 4800
    },
    "previousWeeks": [
      {
        "weekNumber": 2,
        "startDate": "2026-01-06",
        "endDate": "2026-01-12",
        "tripCount": 12,
        "tripEarnings": 3800,
        "incentives": 300,
        "penalties": 100,
        "netEarnings": 4000
      }
    ],
    "totalEarnings": 8800
  }
}
```

#### Use Case:

- **Earnings Dashboard:** Show weekly summary card on driver home screen
- **Historical Trends:** Track performance over multiple weeks

## 7. Rapido Status Management

[!IMPORTANT] **Automatic Availability Control:**

The backend **automatically manages** the driver's Rapido availability based on their internal schedule.

1. **Busy:** When on an internal trip, break, or upcoming assignment (< 45m).
2. **Available:** When idle.

**Do NOT implement** a manual "Go Online/Offline" toggle for Rapido status in the driver app. If a driver manually overrides this in the Rapido app, the backend will **force them back** to the correct state immediately.

## 8. Pricing & Utilities



## 8.1 Check Fare Estimate

**Endpoint:** POST /pricing/preview

**Auth Required:** Yes

**Role:** DRIVER

**Request Body:**

```
{
  "pickup": "Connaught Place, New Delhi",
  "drop": "Cyber City, Gurgaon",
  "tripType": "INTER_CITY",
  "tripDate": "2024-05-20T10:00:00.000Z",
  "bookingDate": "2024-05-19T10:00:00.000Z",

  // Vehicle (use one):
  "vehicleType": "EV",           // Option 1
  "vehicleSku": "TATA_TIGOR_EV", // Option 2

  "distanceKm": 25.5 // Optional fallback
}
```

**Response (200):**

```
{
  "success": true,
  "data": {
    "distanceSource": "GOOGLE_MAPS", // or "CLIENT_PROVIDED"
    "billableDistanceKm": 26,
    "ratePerKm": 25,
    "baseFare": 650,
    "totalFare": 780,
    "breakdown": {
      "distanceFare": 650,
      "tripTypeMultiplier": 1.2,
      "bookingTimeMultiplier": 1.0,
      "vehicleMultiplier": 1.0
    },
    "currency": "INR"
  },
  "message": "Fare calculated successfully"
}
```

**[!NOTE] Distance Calculation:** The mobile app should calculate distance using Google Maps SDK, Mapbox, or similar before calling this endpoint. The backend uses the provided `distanceKm` to calculate fare based on trip type, booking advance, and vehicle type.

**See Also:** [Pricing Engine Documentation](#) for complete fare calculation details.

## 9. Google Maps Service

---

**Base URL:** `/maps`

These endpoints allow the app to proxy Google Maps requests through the backend, securing the API Key.

### 9.1 Autocomplete

**Endpoint:** `GET /maps/autocomplete` **Query Parameters:** `query` (required) **Use Case:** Address search bar.

### 9.2 Geocode

**Endpoint:** `GET /maps/geocode` **Query Parameters:** `address` (required) **Use Case:** Convert address to Lat/Lng.

---

## 10. Referral System

---

Drivers can invite other drivers to join the platform and earn rewards.

### 10.1 How Referrals Work

1. **Every driver gets a unique referral code** automatically after completing signup
2. New drivers can enter a referral code during registration
3. When the referred driver meets activity criteria, the referrer receives an incentive

### 10.2 Using Referral Code During Signup

When calling `POST /users/drivers/signup`, include the referral code:

```
{
  "name": "New Driver",
  "phone": "9876543210",
  "referralCode": "REF123ABC"
}
```

#### Validation Errors:

Error	Meaning
"Invalid referral code"	Code doesn't exist
"Referral code belongs to an inactive account"	Referrer is deactivated
"Referral code has reached the maximum usage limit"	Referrer hit 50 referral limit

### 10.3 Viewing Your Referral Code

Your referral code is available in your profile response ( `GET /drivers/me` ):

```
{
  "success": true,
  "data": {
    "id": "driver-uuid",
    "shortId": "DRV20260123001",
    "firstName": "Raj",
    // ... other fields
    "user": {
      "id": "user-uuid",
      "shortId": "USR20260123001",
      "referralCode": "RAJ123XYZ"
    }
  }
}
```

## 10.4 Referral Eligibility Criteria

The referred driver must meet these criteria for you to receive the reward:

Criteria	Requirement
Active Days	At least 30 days with approved attendance
Average Rides	At least 8 completed trips per active day

## 10.5 Referral Rewards

When eligibility is met:

- An **INCENTIVE** of the configured amount (default: ₹500) is created
- Incentive category: `REFERRAL`
- Visible in your incentives list ( `GET /payments/incentives` )
- Can be paid out via bank transfer

## 10.6 UI Implementation Tips

```
// Share referral code
void shareReferralCode(String code) {
  Share.share(
    'Join DriversKlub using my referral code: $code\n'
    'Download the app and start earning today!'
  );
}

// Display referral section
Widget buildReferralCard(String referralCode) {
  return Card(
    child: Column(
      children: [
        Text('Your Referral Code'),
```

```
Text(referralCode, style: TextStyle(fontSize: 24, fontWeight: FontWeight.bold)),
ElevatedButton(
  onPressed: () => copyToClipboard(referralCode),
  child: Text('Copy Code'),
),
TextButton(
  onPressed: () => shareReferralCode(referralCode),
  child: Text('Share with Friends'),
),
],
),
);
}
```