

Web Technology LAB -10

NAME – ANURAG

ROLL NO – 22CS3013

The image shows a MongoDB Compass interface. At the top, a 'Create Database' dialog box is open, showing the 'Database Name' as 'testdb' and the 'Collection Name' as 'students'. The 'Time-Series' checkbox is unchecked. Below the dialog, the main interface shows the 'students' collection in the 'testdb' database. The collection contains six documents, each with a unique '_id', 'name' (Anurag), 'age' (21 or 20), and 'email' (22cs3013@rgipt.ac.in).

Create Database Dialog:

- Database Name: testdb
- Collection Name: students
- ☐ Time-Series: Time-series collections efficiently store sequences of measurements over a period of time. [Learn More](#)
- [Additional preferences](#) (e.g. Custom collation, Capped, Clustered collections)
- Buttons: Cancel, Create Database

Students Collection Data:

_id	name	age	email
ObjectId('65f6dfe02ae7b0b8af3329')	Anurag	21	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3329')	Anurag	20	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3321')	Anurag	20	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3322')	Anurag	20	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3323')	Anurag	20	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3324')	Anurag	20	22cs3013@rgipt.ac.in
ObjectId('65f6dfe02ae7b0b8af3325')	Anurag	20	22cs3013@rgipt.ac.in

```
_id: ObjectId('65fa6dfedd2ae78bd8af3328')
name: "anurag"
age: 20
email: "22cs2012@rgipt.ac.in"
```

```
_id: ObjectId('65fa6dfedd2ae70bd8af3321')
```



Delete 1 document



testDb.students

Filter ⓘ

{ age: 21 }

↩ Export

Preview (sample of 1 document)

```
_id: ObjectId('65fa6dfedd2ae70bd8af3319')  
name: "anurag"  
age: 21  
email: "22cs2013@rgipt.ac.in"
```

Cancel

Delete 1 document