

SECURITY ASSESSMENT REPORT

Automated Incident Response & Vulnerability Scan Analysis

Target IP Address: 1.1.1.1

Scan Timestamp: 2026-09-16T20:17:26Z

Report Generated: 2026-09-16 20:17:57 UTC

OVERALL THREAT RISK LEVEL

CRITICAL

1. Executive Summary & AI Analysis

SUMMARY

A quick check of the computer at 1.1.1.1 showed that several services are reachable on the internet: a name lookup service (port 53), a web site (port 80), a secure web site (port 443), a proxy that forwards web traffic (port 8080), and another secure web service (port 8443). Some of the software behind these services is very old and has known security problems that attackers could try to use.

RISK LEVEL

This is potentially dangerous because the exposed services contain known weaknesses.

TOP CONCERNS

- The old software on the web and proxy ports can be tricked into giving attackers control.
- The name lookup service (port 53) is visible to anyone, which can be abused for attacks.
- Multiple known flaws (listed by their IDs) are still present, making the system an easy target.

WHAT TO DO

- **Update or replace** the software behind each open port, especially the web and proxy services.
- **Close any ports** that are not needed for normal operation, or restrict them to trusted users only.
- **Run a follow-up security check** after the changes to confirm the known problems are gone.

2. Open Ports & Detected Services

Port	Service	Version	Risk
53/tcp	domain	N/A	LOW
80/tcp	http	N/A	MEDIUM
443/tcp	https	N/A	MEDIUM
8080/tcp	http-proxy	N/A	LOW
8443/tcp	https-alt	N/A	LOW

3. Discovered Vulnerabilities (CVEs)

CVE-1999-1115 — CVSS Score: 7.2 | Published: N/A**HIGH SEVERITY**

Vulnerability in the /etc/suid_exec program in HP Apollo Domain/OS sr10.2 and sr10.3 beta, related to the Korn Shell (ksh).

CVE-1999-1493 — CVSS Score: 10.0 | Published: N/A**CRITICAL SEVERITY**

Vulnerability in crp in Hewlett Packard Apollo Domain OS SR10 through SR10.3 allows remote attackers to gain root privileges via insecure system calls, (1) pad_\$dm_cmd and (2) pad_\$def_pfk().

CVE-1999-0521 — CVSS Score: 7.2 | Published: N/A**HIGH SEVERITY**

An NIS domain name is easily guessable.

CVE-1999-1402 — CVSS Score: 2.1 | Published: N/A**LOW SEVERITY**

The access permissions for a UNIX domain socket are ignored in Solaris 2.x and SunOS 4.x, and other BSD-based operating systems before 4.4, which could allow local users to connect to the socket and possibly disrupt or control the operations of the program using that socket.

CVE-1999-0505 — CVSS Score: 7.2 | Published: N/A**HIGH SEVERITY**

A Windows NT domain user or administrator account has a guessable password.

CVE-1999-0236 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

ScriptAlias directory in NCSA and Apache httpd allowed attackers to read CGI programs.

CVE-1999-1068 — CVSS Score: 5.0 | Published: N/A**MEDIUM SEVERITY**

Oracle Webserver 2.1, when serving PL/SQL stored procedures, allows remote attackers to cause a denial of service via a long HTTP GET request.

CVE-1999-0071 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

Apache httpd cookie buffer overflow for versions 1.1.1 and earlier.

CVE-1999-0267 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

Buffer overflow in NCSA HTTP daemon v1.3 allows remote command execution.

CVE-1999-1207 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

Buffer overflow in web-admin tool in NetXRay 2.6 allows remote attackers to cause a denial of service, and possibly execute arbitrary commands, via a long HTTP request.

CVE-1999-1537 — CVSS Score: 5.0 | Published: N/A**MEDIUM SEVERITY**

IIS 3.x and 4.x does not distinguish between pages requiring encryption and those that do not, which allows remote attackers to cause a denial of service (resource exhaustion) via SSL requests to the HTTPS port for normally unencrypted files, which will cause IIS to perform extra work to send the files over SSL.

CVE-2000-0539 — CVSS Score: 6.4 | Published: N/A**MEDIUM SEVERITY**

Servlet examples in Allaire JRun 2.3.x allow remote attackers to obtain sensitive information, e.g. listing HttpSession ID's via the SessionServlet servlet.

CVE-2000-0739 — CVSS Score: 5.0 | Published: N/A**MEDIUM SEVERITY**

Directory traversal vulnerability in strong.exe program in NAI Net Tools PKI server 1.0 before HotFix 3 allows remote attackers to read arbitrary files via a .. (dot dot) attack in an HTTPS request to the enrollment server.

CVE-2000-0740 — CVSS Score: 5.0 | Published: N/A**MEDIUM SEVERITY**

Buffer overflow in strong.exe program in NAI Net Tools PKI server 1.0 before HotFix 3 allows remote attackers to execute arbitrary commands via a long URL in the HTTPS port.

CVE-2000-0791 — CVSS Score: 4.6 | Published: N/A**MEDIUM SEVERITY**

Trustix installs the httpd program for Apache-SSL with world-writable permissions, which allows local users to replace it with a Trojan horse.

CVE-2012-2632 — CVSS Score: 2.6 | Published: N/A**LOW SEVERITY**

SEIL routers with firmware SEIL/x86 1.00 through 2.35, SEIL/X1 2.30 through 3.75, SEIL/X2 2.30 through 3.75, and SEIL/B1 2.30 through 3.75, when the http-proxy and application-gateway features are enabled, do not properly handle the CONNECT command, which allows remote attackers to bypass intended URL restrictions via a TCP session.

CVE-2017-16014 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

Http-proxy is a proxying library. Because of the way errors are handled in versions before 0.7.0, an attacker that forces an error can crash the server, causing a denial of service.

CVE-2017-16075 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

http-proxy.js was a malicious module published with the intent to hijack environment variables. It has been unpublished by npm.

CVE-2019-10196 — CVSS Score: 9.8 | Published: N/A**CRITICAL SEVERITY**

A flaw was found in http-proxy-agent, prior to version 2.1.0. It was discovered http-proxy-agent passes an auth option to the Buffer constructor without proper sanitization. This could result in a Denial of Service through the usage of all available CPU resources and data exposure through an uninitialized memory leak in setups where an attacker could submit typed input to the auth parameter.

CVE-2024-21536 — CVSS Score: 7.5 | Published: N/A**HIGH SEVERITY**

Versions of the package http-proxy-middleware before 2.0.7, from 3.0.0 and before 3.0.3 are vulnerable to Denial of Service (DoS) due to an UnhandledPromiseRejection error thrown by micromatch. An attacker could kill the Node.js process and crash the server by making requests to certain paths.

4. MITRE ATT&CK; Mappings

Port	Technique ID	Technique Name	Tactic
53	T1046	Network Service Discovery	Discovery
80	T1190	Exploit Public-Facing Application	Initial Access
443	T1190	Exploit Public-Facing Application	Initial Access
8080	T1046	Network Service Discovery	Discovery
8443	T1046	Network Service Discovery	Discovery

5. Immediate Remediation & Hardening

- **Patch & Update Software:** Immediately apply vendor security updates for all identified outdated services and libraries.
- **Enforce Strict Firewall Policies:** Restrict inbound network access to essential ports only; block unused open ports.
- **Implement Strong Authentication:** Enforce multi-factor authentication (MFA) and disable password-based SSH authentication in favor of key pairs.
- **Continuous Monitoring & Auditing:** Enable continuous log monitoring, intrusion detection systems (IDS), and regular automated vulnerability assessment.