

KNN Classification

Theory and Intuition

- K nearest neighbors is one of the simplest machine learning algorithms.
- It simply assigns a label to new data based on the distance between the old data and new data.
- Let's go through the intuition with an example use case...


- Sexing chicks is still a very manual process:
 en.wikipedia.org/wiki/Chick_sexing
 - Let's imagine we gathered a dataset of baby chick heights and weights.
 - How could we train an algorithm to identify the sex of a new baby chick based on historical features?


• Imagine a height and weight data set

HEIGHT

HEIGHT


We historically know the sex of the chicks:





HEIGHT


How would we assign sex to a new point?




MALE FEMALE

HEIGHT


We intuitively "know" this is likely female.





HEIGHT


Intuition comes from distance to points!



MALE FEMALE

HEIGHT


What about a less obvious point?



MALE FEMALE


HEIGHT

How many points to we consider?



MALE FEMALE


• Let's imagine a situation like this:



MALE FEMALE

HEIGHT


• K=1



MALE FEMALE

HEIGHT


• K=1



MALE FEMALE

HEIGHT


• K=2



MALE FEMALE


HEIGHT

• K=3



MALE FEMALE

• K=4 leads to a tie!




MALE FEMALE

- Tie considerations and options:
 - Always choose an odd K.
 - In case of tie,simply reduce K by I until tie is broken.
 - Randomly break tie.
 - Choose nearest class point.

- What does Scikit-Learn do in case of tie?
 - Warning: Regarding the Nearest Neighbors algorithms, if it is found that two neighbors, neighbor k+1 and k, have identical distances but different labels, the results will depend on the ordering of the training data.


- What does Scikit-Learn do in case of tie?
 - In the case of ties, the answer will be the class that happens to appear first in the set of neighbors.
 - Results are ordered by distance, so it chooses the class of the closest point.

• K=4 leads to a tie!




MALE FEMALE

Choose closest K




MALE FEMALE


Choose closest K




MALE FEMALE


K=5 causes a switch from previous K values.






How to choose best K value?






- We want a K value that **minimizes** error:
 - Error = 1 Accuracy
- Two methods:
 - Elbow method.
 - Cross validate a grid search of multiple K values and choose K that results in lowest error or highest accuracy.


• Elbow method:



• Elbow method:



• Elbow method:




- Cross validation only takes into account the K value with the lowest error rate across multiple folds.
- This could result in a more complex model (higher value of K).
- Consider the context of the problem to decide if larger K values are an issue.

- KNN Algorithm
 - Choose K value.
 - Sort feature vectors (N dimensional space) by distance metric.
 - Choose class based on K nearest feature vectors.

- KNN Considerations:
 - Distance Metric
 - Many ways to measure distance:
 - Minkowski
 - Euclidean
 - Manhattan
 - Chebyshev

- KNN Considerations:
 - Scaling for Distance
 - Features could have vastly different value ranges!



- KNN Considerations:
 - Scaling for Distance
 - Features could have vastly different value ranges!



- KNN Considerations:
 - Scaling for Distance
 - Features could have vastly different value ranges!



Feature 1

- KNN Considerations:
 - Scaling is necessary for KNN.



- While the KNN Algorithm is relatively simple, keep in mind the following considerations:
 - Choosing the optimal K value.
 - Scaling features.
 - Let's continue to explore how to perform KNN for classification!

KNN Classification

Coding Part One: Data and Model

Let's test your new skills on a real data set.

 We'll be analyzing sonar frequencies to help distinguish between rocks or sea

mines!

