Linux Commands(Day 9)

```
Anudeep:~# lsblk
NAME MAJ:MIN RM   SIZE RO TYPE MOUNTPOINTS
sda    8:0    0 388.4M  1 disk
sdb    8:16   0   186M  1 disk
sdc    8:32   0     2G  0 disk [SWAP]
sdd    8:48   0 143.5M  0 disk /mnt/host/wslg/distro
                                /
```

```
Anudeep:~# findmnt
TARGET   SOURCE FSTYPE  OPTIONS
/        /dev/sdd
                ext4    rw,relatime,discard,errors=remount-ro,data=ordered
├─/lib/modules/6.6.87.2-microsoft-standard-WSL2
         none   overlay rw,nosuid,nodev,noatime,lowerdir=/modules,upperdir=/
├─/mnt/host/wsl
         none   tmpfs   rw,relatime
├─/usr/lib/wsl/drivers
         drivers
                9p      ro,nosuid,nodev,noatime,aname=drivers;fmask=222;dmas
├─/mnt/host/wslg
│        none   tmpfs   rw,relatime
│ ├─/mnt/host/wslg/distro
│        /dev/sdd
│               ext4    ro,relatime,discard,errors=remount-ro,data=ordered
│ ├─/mnt/host/wslg/versions.txt
│        none[/etc/versions.txt]
│               overlay rw,relatime,lowerdir=/systemvhd,upperdir=/system/rw/
│ └─/mnt/host/wslg/doc
         none[/usr/share/doc]
                overlay rw,relatime,lowerdir=/systemvhd,upperdir=/system/rw/
├─/usr/lib/wsl/lib
         none   overlay rw,nosuid,nodev,noatime,lowerdir=/gpu_lib_packaged:/
├─/init  rootfs[/init]
                rootfs  ro,size=3976388k,nr_inodes=994097
├─/dev   none   devtmpf rw,nosuid,relatime,size=3976388k,nr_inodes=994097,mo
│ ├─/dev/pts
│        devpts devpts  rw,nosuid,noexec,noatime,gid=5,mode=620,ptmxmode=000
│ └─/dev/shm
         none   tmpfs   rw,nosuid,nodev,noatime
├─/sys   sysfs  sysfs   rw,nosuid,nodev,noexec,noatime
│ └─/sys/fs/cgroup
         cgroup2
                cgroup2 rw,nosuid,nodev,noexec,relatime,nsdelegate
├─/proc  proc   proc    rw,nosuid,nodev,noexec,noatime
│ └─/proc/sys/fs/binfmt_misc
         binfmt_misc
                binfmt_ rw,relatime
├─/run   none   tmpfs   rw,nosuid,nodev,mode=755
│ ├─/run/lock
│        none   tmpfs   rw,nosuid,nodev,noexec,noatime
│ ├─/run/shm
│        none   tmpfs   rw,nosuid,nodev,noatime
│ └─/run/user
│        none   tmpfs   rw,nosuid,nodev,noexec,noatime,mode=755
```

```
Anudeep:~# blkid
/dev/sdd: UUID="4d152259-ba25-4c1a-b406-cb4aca0b8bf6" BLOCK_SIZE="1024" TYPE="ext4"
/dev/sdb: BLOCK_SIZE="4096" TYPE="ext4"
/dev/sdc: UUID="de6e5b92-2f01-40e4-9f07-8ea49c8e1e77" TYPE="swap"
/dev/sda: BLOCK_SIZE="4096" TYPE="ext4"
Anudeep:~# lscpu
Architecture:             x86_64
  CPU op-mode(s):         32-bit, 64-bit
  Address sizes:          39 bits physical, 48 bits virtual
  Byte Order:             Little Endian
CPU(s):                   16
  On-line CPU(s) list:    0-15
Vendor ID:                GenuineIntel
  Model name:             12th Gen Intel(R) Core(TM) i5-1240P
    CPU family:           6
    Model:                154
    Thread(s) per core:   2
    Core(s) per socket:   8
    Socket(s):            1
    Stepping:             3
    BogoMIPS:             4224.01
```

```
Anudeep:~# ulimit
unlimited
Anudeep:~# ulimit -a
core file size (blocks)         (-c) 0
data seg size (kb)              (-d) unlimited
scheduling priority             (-e) 0
file size (blocks)              (-f) unlimited
pending signals                 (-i) 31065
max locked memory (kb)          (-l) 65536
max memory size (kb)            (-m) unlimited
open files                      (-n) 10240
POSIX message queues (bytes)    (-q) 819200
real-time priority              (-r) 0
stack size (kb)                 (-s) 8192
cpu time (seconds)              (-t) unlimited
max user processes              (-u) 31065
virtual memory (kb)             (-v) unlimited
file locks                      (-x) unlimited
Anudeep:~# ulimit -n
10240
Anudeep:~# ulimit -u
31065
```

```
Anudeep:~# ldd
musl libc (x86_64)
Version 1.2.5
Dynamic Program Loader
Usage: /lib/ld-musl-x86_64.so.1 [options] [--] pathname
Anudeep:~# readlink
BusyBox v1.36.1 (2024-05-21 13:38:37 UTC) multi-call binary.

Usage: readlink [-fnv] FILE

Display the value of a symlink

        -f      Canonicalize by following all symlinks
        -n      Don't add newline
        -v      Verbose
```

```
Anudeep:~# getconf
Usage: getconf system_var
        getconf -a
        getconf path_var pathname
        getconf -a pathname
```

```
Anudeep:~# lsusb
lsusb: /sys/bus/usb/devices: No such file or directory
```

```
Anudeep:~# nproc
16
```

```
Anudeep:~# lscpu
Architecture:                x86_64
  CPU op-mode(s):            32-bit, 64-bit
  Address sizes:             39 bits physical, 48 bits virtual
  Byte Order:                Little Endian
CPU(s):                      16
  On-line CPU(s) list:       0-15
Vendor ID:                   GenuineIntel
  Model name:                12th Gen Intel(R) Core(TM) i5-1240P
    CPU family:              6
    Model:                   154
    Thread(s) per core:      2
    Core(s) per socket:      8
    Socket(s):               1
    Stepping:                3
    BogoMIPS:                4224.01
    Flags:                   fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ss ht s
                             yscall nx pdpe1gb rdtscp lm constant_tsc rep_good nopl xtopology tsc_reliable nonstop_tsc cpuid tsc_known
                             _freq pni pclmulqdq vmx ssse3 fma cx16 pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsav
                             e avx f16c rdrand hypervisor lahf_lm abm 3dnowprefetch ssbd ibrs ibpb stibp ibrs_enhanced tpr_shadow ept
                             vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid rdseed adx smap clflushopt clwb sha_ni x
                             saveopt xsavec xgetbv1 xsaves avx_vnni vnmi umip waitpkg gfni vaes vpclmulqdq rdpid movdiri movdir64b fsr
                             m md_clear serialize flush_l1d arch_capabilities
Virtualization features:
  Virtualization:            VT-x
  Hypervisor vendor:         Microsoft
  Virtualization type:       full
Caches (sum of all):
  L1d:                       384 KiB (8 instances)
  L1i:                       256 KiB (8 instances)
  L2:                        10 MiB (8 instances)
  L3:                        12 MiB (1 instance)
```