LINUX COMMANDS

df: Check disk space

```
Anudeep:/# df
Filesystem           1K-blocks      Used Available Use% Mounted on
none                   3981404         0   3981404   0% /lib/modules/6.6.87.2-microsoft-standard-WSL2
none                   3981404         4   3981400   0% /mnt/host/wsl
drivers              395724796 208321724 187403072  53% /usr/lib/wsl/drivers
/dev/sdd                132003     66892     54829  55% /
none                   3981404        72   3981332   0% /mnt/host/wslg
/dev/sdd                132003     66892     54829  55% /mnt/host/wslg/distro
none                   3981404         0   3981404   0% /usr/lib/wsl/lib
none                   3976388         0   3976388   0% /dev
none                   3981404         0   3981404   0% /run
none                   3981404         0   3981404   0% /run/lock
none                   3981404         0   3981404   0% /run/shm
none                   3981404         0   3981404   0% /dev/shm
none                   3981404         0   3981404   0% /run/user
none                   3981404        72   3981332   0% /tmp/.X11-unix
none                   3981404        76   3981328   0% /mnt/host/wslg/versions.txt
none                   3981404        76   3981328   0% /mnt/host/wslg/doc
C:\                  395724796 208321724 187403072  53% /mnt/host/c
D:\                  102398972  19325572  83073400  19% /mnt/host/d
```

Free : Check memory usage

```
Anudeep:/# free
               total        used        free      shared  buff/cache   available
Mem:         7962812      316888     7481640        2992      164284     7487924
Swap:        2097152           0     2097152
```

ps : Display running processes

```
Anudeep:/# ps
PID   USER     TIME  COMMAND
    1 root      0:00 {init(docker-des} /init
    5 root      0:00 {init} plan9 --control-socket 6 --log-level 4 --server-fd 7 --pipe-fd 9 --log-truncate
    8 root      0:00 {SessionLeader} /init
    9 root      0:00 {Relay(10)} /init
   10 root      0:00 -sh
   17 root      0:00 ps
```

Chmod: Change file permissions

```
Anudeep:/# chmod
BusyBox v1.36.1 (2024-05-21 13:38:37 UTC) multi-call binary.

Usage: chmod [-Rcvf] MODE[,MODE]... FILE...

MODE is octal number (bit pattern sstrwxrwxrwx) or [ugoa]{+|-|=}[rwxXst]

        -R      Recurse
        -c      List changed files
        -v      Verbose
        -f      Hide errors
```

Whoami :Displays current user name

```
Anudeep:/# whoami
root
```

Uname: Displays System information

```
Anudeep:/# uname
Linux
```

Grep: Search for specific text

```
Anudeep:/# grep
BusyBox v1.36.1 (2024-05-21 13:38:37 UTC) multi-call binary.

Usage: grep [-HhnlLoqvsrRiwFE] [-m N] [-A|B|C N] { PATTERN | -e PATTERN... | -f FILE... } [FILE]...

Search for PATTERN in FILEs (or stdin)

        -H      Add 'filename:' prefix
        -h      Do not add 'filename:' prefix
        -n      Add 'line_no:' prefix
        -l      Show only names of files that match
        -L      Show only names of files that don't match
        -c      Show only count of matching lines
        -o      Show only the matching part of line
        -q      Quiet. Return 0 if PATTERN is found, 1 otherwise
        -v      Select non-matching lines
        -s      Suppress open and read errors
        -r      Recurse
        -R      Recurse and dereference symlinks
        -i      Ignore case
        -w      Match whole words only
        -x      Match whole lines only
        -F      PATTERN is a literal (not regexp)
        -E      PATTERN is an extended regexp
        -m N    Match up to N times per file
        -A N    Print N lines of trailing context
        -B N    Print N lines of leading context
        -C N    Same as '-A N -B N'
        -e PTRN Pattern to match
        -f FILE Read pattern from file
```

Ln: Create link between files

```
Anudeep:/# ln
BusyBox v1.36.1 (2024-05-21 13:38:37 UTC) multi-call binary.

Usage: ln [-sfnbtv] [-S SUF] TARGET... LINK|DIR

Create a link LINK or DIR/TARGET to the specified TARGET(s)

        -s      Make symlinks instead of hardlinks
        -f      Remove existing destinations
        -n      Don't dereference symlinks - treat like normal file
        -b      Make a backup of the target (if exists) before link operation
        -S SUF  Use suffix instead of ~ when making backup files
        -T      Treat LINK as a file, not DIR
        -v      Verbose
```

Top: Monitor running processes in real time

```
Load average: 0.00 0.01 0.00 1/227 29
  PID  PPID USER     STAT   VSZ %VSZ CPU %CPU COMMAND
    9     8 root     S     3088   0%   2   0% {Relay(10)} /init
    8     1 root     S     3088   0%  11   0% {SessionLeader} /init
    5     1 root     S     3072   0%  15   0% {init} plan9 --control-socket 6 --log-level 4 --server-fd 7 --pipe-fd 9 --
    1     0 root     S     3072   0%  12   0% {init(docker-des} /init
   10     9 root     S     1716   0%   0   0% -sh
   29    10 root     R     1624   0%   2   0% top
```

Tar: Archive files and directories

```
Anudeep:/# tar
BusyBox v1.36.1 (2024-05-21 13:38:37 UTC) multi-call binary.

Usage: tar c|x|t [-ZzJjahmvokO] [-f TARFILE] [-C DIR] [-T FILE] [-X FILE] [LONGOPT]... [FILE]...

Create, extract, or list files from a tar file

        c       Create
        x       Extract
        t       List
        -f FILE Name of TARFILE ('-' for stdin/out)
        -C DIR  Change to DIR before operation
        -v      Verbose
        -O      Extract to stdout
        -m      Don't restore mtime
        -o      Don't restore user:group
        -k      Don't replace existing files
        -Z      (De)compress using compress
        -z      (De)compress using gzip
        -J      (De)compress using xz
        -j      (De)compress using bzip2
        --lzma  (De)compress using lzma
        -a      (De)compress based on extension
        -h      Follow symlinks
        -T FILE File with names to include
        -X FILE File with glob patterns to exclude
        --exclude PATTERN       Glob pattern to exclude
        --overwrite             Replace existing files
        --strip-components NUM  NUM of leading components to strip
        --no-recursion          Don't descend in directories
```