Checking the prerequisites

```
Anudeep:~# pwd
/root
Anudeep:~# ls
week1
Anudeep:~# whoami
root
Anudeep:~# ls -l
total 1
drwxr-xr-x    2 root     root          1024 Oct 11 18:08 week1
```

Creating a directory called member1_lab and creating a file named report.txt

```
Anudeep:~# cd week1
Anudeep:~/week1# cd ..
Anudeep:~# mkdir member1_lab
Anudeep:~# cd member1_lab
Anudeep:~/member1_lab# touch report.txt
Anudeep:~/member1_lab# ls -l
total 0
-rw-r--r--    1 root     root             0 Oct 12 10:03 report.txt
```

Managing the permissions of the user on the file

```
Anudeep:~/member1_lab# chmod 600 report.txt
Anudeep:~/member1_lab# ls -l report.txt
-rw-------    1 root     root             0 Oct 12 10:03 report.txt
```

```
Anudeep:~/member1_lab# chmod u+rw,g+r,o-rwx report.txt
Anudeep:~/member1_lab# ls -l report.txt
-rw-r-----    1 root     root             0 Oct 12 10:03 report.txt
```

```
Anudeep:~/member1_lab# chmod 754 report.txt
Anudeep:~/member1_lab# ls -l report.txt
-rwxr-xr--    1 root     root             0 Oct 12 10:03 report.txt
```

```
Anudeep:~/member1_lab# chmod u=rwx,g=rx,o=r report.txt
Anudeep:~/member1_lab# ls-l report.txt
-sh: ls-l: not found
Anudeep:~/member1_lab# ls -l report.txt
-rwxr-xr--    1 root     root             0 Oct 12 10:03 report.txt
```

Checking anything have changed or conclusion

```
Anudeep:~/member1_lab# stat -c '%A %a %U %G %n' report.txt
-rwxr-xr-- 754 root root report.txt
Anudeep:~/member1_lab# pwd
/root/member1_lab
Anudeep:~/member1_lab# ls -l
total 0
-rwxr-xr--    1 root     root             0 Oct 12 10:03 report.txt
Anudeep:~/member1_lab# stat report.txt
  File: report.txt
  Size: 0               Blocks: 0          IO Block: 1024   regular empty file
Device: 830h/2096d      Inode: 842         Links: 1
Access: (0754/-rwxr-xr--)  Uid: (    0/    root)   Gid: (    0/    root)
Access: 2026-10-12 10:03:02.102995373 +0000
Modify: 2026-10-12 10:03:02.102995373 +0000
Change: 2026-10-12 10:05:20.142973325 +0000
```