# Measuring the Carbon Footprint of Programming Languages

**Anuj Khadka**
Computer Science and Business Analytics
Caldwell University
akhadka@caldwell.edu

**Vladislav D. Veksler**
Computer Science and Business Analytics
Caldwell University
akhadka@caldwell.edu

**Darryl Aucoin**
Computer Science and Business Analytics
Caldwell University
akhadka@caldwell.edu

## Abstract

This project investigates how programming language choice affects the carbon footprint produced during a program execution. Although software is often seen as intangible, every program consumes energy, ultimately contributing to carbon emissions. As the digital system continues to grow, understanding the environmental impact of software has become increasingly important. This experiment studies how identical algorithms behave when implemented in different programming languages running on the same hardware. By measuring and estimating the carbon emissions, the project tends to explore whether programming language designs play an important role in software sustainability, or if it is mostly driven by heavy algorithms. This research combines the aspects of computer science and environmental science to better understand the hidden environmental cost of everyday computational tasks and encourage more sustainable and responsible software development practices.
**Keywords:** carbon footprint, software sustainability, energy consumption

## 1 Introduction

As the tech continues to evolve, software becomes an increaingly central part of our lives. From the apps on our phones to the software running our cars, it's everywhere. Everytime a piece of code runs, it triggers energy usage inside the CPU, GPU, and other hardware components [1]. This subsequent usage of software adds up to the carbon emission a device generates [2]. The carbon footprint of software is a growing concern, as it contributes to climate change and has a significant impact on our planet.

The scale of this concern is larger than most people realize. The information and communication technology (ICT) sector accounts for an estimated of 2.1% to 3.9% of the global greenhouse gas emissions [3]. The global data center energy consumption alone is projected to reach around 945TWh by 2030, which is a significant increase from 153TWh in 2005, 205TWh in 2018. [4, 5]. Unlike the visible emissions from vehicles, software carbon is invisible. There is no smoke when a program runs, yet every computation contributes indirectly to the same atmosphere. This invisibility is precisely what makes it dangerous. It does not trigger the same urgency that the physical pollution does, even as the number grows.

One of the most consequential and least-studied of those decisions is the choice of programming language. The carbon cost of a running program is not determined by a hardwar alone. It is also shaped by how efficient the language runtime executes instructions, manages memory, and utilizes the CPU.In a landmark empirical study, Pereira et al. [6] benchmarked 27 programming languages across 10 problems drawn from the Computer Language Benchmarks Game [7], measuring energy consumption via Intel's Running Average Power Limit (RAPL) interface. They found that the choice of programming language can have a significant impact on energy consumption, with some languages consuming up to 2.5 times more energy than others for the same task. For example, they found that C and Rust were among the most energy-efficient languages, while Python and JavaScript were among the least efficient. Python consumed approximately 75.88 times more energy per benchmark than C while JavaScript consumed approximately 4.45 times more energy per benchmark than C [6]. Since carbon emissions are directly proportional to energy consumption, these differences are not just technical concern, but also a carbon concern. A Python program consuming about 75 times more energy than an equivalent C program does not just run slower, it emits 75 times more carbon for every execution. Now, multiply that by the millions of times a piece of software runs, and the carbon cost becomes staggering.

Prior work in this area, including Pereira et al., reports energy consumption in joules or kilowatt-hours but none of it completes the translation into carbon footprint. This is a critical gap. Energy consumption is the underlying driver, but carbon footprint is the ultimate impact. This unit is most directly relevent to the clomate policy and

environmental decision making. Henderson et al. showed that the emissions can be reduced by up to 30 times just by running the experiments in the locations powered by more renewable energy sources [8].

This paper presents a controlled empirical study comparing the energy consumption and the carbon footprint of six programming languages (C, Rust, Go, Java, Javascript, and Python) across six different algorithms and three imput sizes. The energy consumption is measured using Intel's RAPL (accessed through LibreHardwareMonitor [9]), and real-time carbon intensity data was fetched from Electricity Maps API [10] for the New York grid zone. stat analysis of pairwise langugage difference

## 2 Background

In the following sections, we describe the energy consumption model, carbon intensity assumptions, programming languages, and the implementations of the six algorithms used in this study.

### 2.1 Energy Consumption in Software

To quantify the energy consumed by a software program, we adopt the standard defination of energy as the capacity to do work.

$$E_{\text{energy}} = P_{\text{power}} \times t_{\text{time}} \tag{1}$$

where E is energy measured in Joules(J), Power is rate of energy consumption measured in Watts(W), and Time is the duration of execution measured in seconds(s)[11]. In the context of software execution, the T refers to the wall time, the elapsed time from the first instruction of the measured code path to the last, including CPU computation, memory access, and all other processor activity during execution [12].

**The energy consumed by a CPU package during the program execution can therefore be decomposed as the integral of instantaneos power draw over the execution window. Since power draw is not constant across languages or algorithms, a key finding of Pereira et al. [6], energy efficiency cannot be inferred from execution time alone. A faster program is not necessarily a more energy efficient one. This encourages us to direct hardware level energy measurement via RAPL.**

All experiments were conducted on a desktop with the following specifications: Windows 11 Enterprise 25H2 (Build 26200.8246) operating system, with 32.0 GB RAM, and an Intel Core `i7-14700K` CPU @ 3.40 GHz.

### 2.2 Carbon Intensity

To translate the energy measurements into carbon emissions, we apply the SCI framework.

### 2.3 Programming Language

The programming languages chosen for this study are C, Python, Javascript, Java, Go, and Rust. These languages were selected to represent a range of programming paradigms, performance characteristics, and popularity in the software development community. Each language has its own unique features and trade-offs that may influence the energy consumption and carbon footprint of the algorithms implemented in them [13]. The performance characteristics of these languages are summarized in Table 1.

Table 1: Programming languages, their performance characteristics, and popularity.

| Language | Paradigm | Runtime | Version |
|---|---|---|---|
| C | Manual Memory, Compiled | GCC | 14.3.0 |
| Rust | Ownership, Compiled | Rustc | 1.94.0 |
| Python | Interpreted | CPython | 3.12.10 |
| Javascript | Dynamic, V8 | Node.js | 24.14.0 |
| Java | OOP, JVM | OpenJDK | 21.0.10 |
| Go | GC | Go | 1.26.1 |

**C** provides direct hardware access with no runtime overhead and serves as the energy baseline for all normalized comparisons.

**Rust**

**Go**

**Java**

**JavaScript**

**Python**

### 2.4 Algorithms

The algorithms were chosen to span a range of time complexities and computational patterns, including CPU-bound, memory-bound, and branching-heavy workloads. The six algorithms used in this study are summarized in Table 2.

Table 2: Algorithms, their time complexities and computational patterns.

| Algorithm | Time Complexity | Pattern |
|---|---|---|
| Summation | $O(n)$ | Linear |
| Binary Search | $O(\log n)$ | Logarithmic |
| Merge Sort | $O(n \log n)$ | Divide & Conquer |
| Breadth-First Search (BFS) | $O(V + E)$ | Graph Traversal |
| Hash Table | $O(n) - avg$ | xxxxxx |
| Matrix Multiplication | $O(n^3)$ | Dense Arithemetic |

The pseudocode for each algorithm, as implemented indentically across all languages, is provided below. The implementations are designed to be as similar as possible across languages to ensure a fair comparison of their energy consumption and carbon footprint.

**Summation -** This algorithm performs a single sequential sum over an array of integers. It is a simple CPU-bound with no branching and minimal memory access, making it a baseliune workload that reflects the idle runtime cost of the language.

**Binary Search -** This algorithm halves the search interval over a sorted array. Its time complexity is logarithmic, and it involves branching based on comparisons, which means very few operations are performed at any input size. So, the observed energy difference between languages may be more influenced by the runtime efficiency and overhead than the algorithmic complexity.

**Breadth-First Search -** This algorithm traverses a graph level by level from a source node. It is memory-bound. The primary cost is queue operations and random memory access patterns that can lead to cache misses. The energy consumption may be more sensitive to how efficiently the language runtime manages memory and data structures.

**Merge Sort -** This algorithm recursively divides the array into halves and merges them back in sorted order. Now, just to make sure that we don't get any RecursionError in Python, we will increase the recursion limit for merge sort.

**Hash Table -** This algorithm use open addressing with linear probing. Each operation is O(1) on average, but can be O(n) in the worst case if all keys collide. The energy consumption may be influenced by how well the language runtime optimizes for hash table operations and memory management. the "& 0xFFFFFFFFFFFFFFFF" is used to ensure that the hash result is always a 64bit integer, which is important for consistency across different platforms and languages. This way, we can compare the hash results from C and Python without worrying about differences in integer sizes or overflow behavior.

**Matrix Multiplication -** This algorithm uses the naive triple loop method to multiply two square matrices. It is a dense arithmetic workload with cubic time complexity, which means the number of operations grows rapidly with input size. At n=500 (our large input), it performs 125 million multiplications and additions, which is a significant computational load that can highlight differences in how languages handle CPU-bound tasks and memory access patterns.

# 3 Methodology

This section describes the experimental setup, the measurement protocol used to isolate algorithm energy consumption, the implementation constraints across all six languages, the input sizes used for each algorithm, and idk.

## 3.1 Experimental Setup

All the experiments were conducted on a single dedicated machine to eliminate any inter-machine power variability. The Intel's RAPL interface exposes hardware energy counters directly to software, enabling fine-grained CPU package energy measurement without externam instruments [14]. Baseline idle power draw -

## 3.2 somehting...

The main challenge in cross-language energy measurement is to ensure that we are measuring the energy consumed by the algorithm itself, and not the overhead of the language runtime or other background process. To address this, we designed a custom measurement harness that follows a strict protocol to isolate the algorithm execution. The harness uses a stdin/stout handshake design in which the program initializes once and then loops, executing the algorithm on each trigger without restarting the process.

The measurement sequence is shown in the Listing 1.

```
setup - not timed
print "ready" - not timed
harness newline - start timer
run command - measurement
print checksum - stop timer
flush output - not timed
```

Listing 1: Measurement sequence

The flush() call on line 7 is critical. Without it, the newline sits in a kernel pipe buffer and the program never unblocks, causing the measurement to hang indefinitely. On the program side, each language blocks on its respective stdin/stdout primitive until the trigger arrives, executes the algorithm, and writes the checksum. Listing 2 shows the blocking call used in each language.

```
// C
while (fgets(buf, sizeof(buf), stdin))  {
    run()}

// Python
for line in sys.stdin: run()

// JavaScript
rl.on('line', () => run())

// Java
while(br.readLine() != null) {run()}

// Go
for scanner.Scan() {run()}

// Rust
for line in stdin.lock().lines() {run()}
```

Listing 2: Stdin primitives in each language implementation

C uses fgets rather than scanf because it reads exactly one line including the newline, giving unambiguous trigger semantics. Java uses BufferedReader.readLine() rather than Scanner to avoid locale-aware parsing overhead inside the measurement window. JavaScript uses Node.js's readline event listener. Python uses for line in sys.stdin: rather than repeated input() calls to avoid Python-level function call overhead per iteration.

## 3.3 Output Verification

Before energy measurement, all 36 implementations are verified for correctness. The verification script compiles and

runs each implementation at all three input sizes, compares the checksum printed to stdout against the reference checksum produced by the C implementation, and assigns each language-algortihm-size combination a PASS/FAIL status. Table 3 shows the verification results fot the C implemetation. The C times serves as a reference baseline against which all other languages are measured and normalized. They confirm that execition time scales with the expected time complexity of each program.

Table 3: C — RUN & VERIFY

| Algorithm | Size | Output | Time | Status |
|---|---|---|---|---|
| summation | small | 5050 | 0.0437ms | PASS |
| summation | mid | 50005000 | 0.0406ms | PASS |
| summation | large | 500000500000 | 0.4715ms | PASS |
| binary_search | small | 99 | 0.0448ms | PASS |
| binary_search | mid | 9999 | 0.0392ms | PASS |
| binary_search | large | 999999 | 0.0835ms | PASS |
| merge_sort | small | 100 | 0.0428ms | PASS |
| merge_sort | mid | 10000 | 0.2459ms | PASS |
| merge_sort | large | 1000000 | 24.7405ms | PASS |
| bfs | small | 100 | 0.0430ms | PASS |
| bfs | mid | 1000 | 0.3039ms | PASS |
| bfs | large | 5000 | 7.2774ms | PASS |
| hash_table | small | 64850 | 0.0433ms | PASS |
| hash_table | mid | 649985000 | 0.2467ms | PASS |
| hash_table | large | 64999850000 | 2.1579ms | PASS |
| matrix_mul | small | 9175 | 0.0744ms | PASS |
| matrix_mul | mid | 646700 | 2.5604ms | PASS |
| matrix_mul | large | 10291750 | 47.1134ms | PASS |

The execution times in Table 3 confirms the time complexity scaling. Merge sort grows from 0.0428ms to 24.740ms (a 576× increase) as input scales from small to large with consistent $O(n \log n)$ growth.

### 3.4 Input Sizes

Three input sizes are used for each algorithm to capture scaling behavior: small, mid, and large. The specific sizes are chosen to be large enough to produce measurable energy consumption while still completing within a reasonable time frame across all languages. The input sizes for each algorithm are as defined in Table 4.

Table 4: Input Sizes per Algorithm

| Algorithm | Small | Mid | Large |
|---|---|---|---|
| summation | 100 | 10,000 | 1,000,000 |
| binary_search | 100 | 10,000 | 1,000,000 |
| merge_sort | 100 | 10,000 | 1,000,000 |
| bfs | 100 | 1,000 | 5,000 |
| hash_table | 100 | 10,000 | 100,000 |
| matrix_mul | 50 | 200 | 500 |

baseline power draw - 40w 5s sample

#### 3.4.1 Implementation-specific design decisions

Each language's implementation follows the stdin/stdout handshake protocol. The program prints `"ready"` on startup, then blocks waiting for a newline trigger from the measurement harness before executing the algorithm. The specific I/O primitives used, and the rationale for each choice, are described below:

**C -** fgets

**Python -** stdin/stdout

**JavaScript -** readline

**Java -** public static void main
buffered reader/writer

**Go -** bufio

**Rust -** `wrapping_mul` 2654435761

## 4 Results

## 5 Discussion

## 6 Conclusion


## Acknowledgements

This paper uses AI for few code writing processes, such as generating initial code snippets and providing suggestions for code improvements.

**add some more later in this**


## References


[1] Green Compute UK. *Measuring Environmental Footprint of Code.* https://greencompute.uk/Measurement/Code. 2023. (Visited on 01/2026).

[2] ThoughtWorks. *Calculating software carbon intensity.* https://www.thoughtworks.com/insights/blog/ethical-tech/calculating-software-carbon-intensity. 2023. (Visited on 01/2026).

[3] Charlotte Freitag, Mike Berners-Lee, Kelly Widdicks, Bran Knowles, Gordon S. Blair, and Adrian Friday. "The real climate and transformative impact of ICT: A critique of estimates, trends, and regulations". In: *Patterns* 2.9 (2021), p. 100340. ISSN: 2666-3899. DOI: https://doi.org/10.1016/j.patter.2021.100340. URL: https://www.sciencedirect.com/science/article/pii/S2666389921001884.

[4] IEA. *Energy and AI.* https://www.iea.org/reports/energy-and-ai. (Visited on 01/2026).

[5] Eric Masanet, Arman Shehabi, Nuoa Lei, Sarah Smith, and Jonathan Koomey. *Recalibrating global data center energy-use estimates,* https://datacenters.lbl.gov/sites/default/files/Masanet_et_al_Science_2020.full_.pdf. 2020. (Visited on 01/2026).

[6] Rui Pereira, Marco Couto, Francisco Ribeiro, Rui Rua, Jácome Cunha, João Paulo Fernandes, and João Saraiva. "Energy efficiency across programming languages: how do energy, time, and memory relate?" In: *Proceedings of the 10th ACM SIGPLAN International Conference on Software Language Engineering*. SLE 2017. Vancouver, BC, Canada: Association for Computing Machinery, 2017, pp. 256–267. ISBN: 9781450355254. DOI: 10.1145/3136014.3136031. URL: https://doi.org/10.1145/3136014.3136031.

[7] Isaac Gouy. *The Computer Language Benchmarks Game*. http://benchmarksgame.alioth.debian.org/. (Visited on 01/2026).

[8] Peter Henderson, Jieru Hu, Joshua Romoff, Emma Brunskill, Dan Jurafsky, and Joelle Pineau. "Towards the systematic reporting of the energy and carbon footprints of machine learning". In: *J. Mach. Learn. Res.* 21.1 (Jan. 2020). ISSN: 1532-4435.

[9] https://librehardwaremonitor.com/. (Visited on 03/2026).

[10] https://app.electricitymaps.com/. (Visited on 03/2026).

[11] Mohit Kumar, Youhuizi Li, and Weisong Shi. "Energy consumption in Java: An early experience". In: *2017 Eighth International Green and Sustainable Computing Conference (IGSC)*. 2017, pp. 1–8. DOI: 10.1109/IGCC.2017.8323579.

[12] Kristina Carter, Su Mei Gwen Ho, Mathias Marquar Arhipenko Larsen, Martin Sundman, and Maja H. Kirkeby. *Energy and Time Complexity for Sorting Algorithms in Java*. arXiv:2311.07298v2. 2024. URL: https://arxiv.org/abs/2311.07298.

[13] Siamak Farshidi, Slinger Jansen, and Mahdi Deldar. "A decision model for programming language ecosystem selection: Seven industry case studies". In: *Information and Software Technology* 139 (2021), p. 106640. ISSN: 0950-5849. DOI: https://doi.org/10.1016/j.infsof.2021.106640. URL: https://www.sciencedirect.com/science/article/pii/S0950584921001051.

[14] Kashif Nizam Khan, Mikael Hirki, Tapio Niemi, Jukka K. Nurminen, and Zhonghong Ou. "RAPL in Action: Experiences in Using RAPL for Power Measurements". In: *ACM Trans. Model. Perform. Eval. Comput. Syst.* 3.2 (Mar. 2018). ISSN: 2376-3639. DOI: 10.1145/3177754. URL: https://doi.org/10.1145/3177754.